

APP-SIDE OF THE BLINDEYE

The Optoelectronic Companion App & System Specifications

Document Type: Full Append Technical Specification & Architecture Report

Document Version: v4.0 (English-Only Consolidated)

Date of Compilation: July 17, 2026

Intellectual Property: Patent Pending (USA, Europe, PCT)

Medical Device Exemption: Class I Assistive Technology Device (Exempt)

Primary Target: Blind and Visually Impaired Accessibility Empowerment

Notice: This document details the software, hardware, safety, and regulatory mechanisms required to translate standard smartphone display coordinates into dynamic tactile commands using the **BlindEye** screen protector and its companion app. Every specification is strictly grounded in physical optoelectronic material solutions.

1.0 EXECUTIVE SUMMARY & THE ACCESSIBILITY GAP

The current mobile technology ecosystem fails visually impaired individuals. Touchscreens have revolutionized input for sighted users, but they present an almost impassable barrier for blind and visually impaired (BLV) users. Flat, non-tactile glass offers zero physical guidance, leading to high cognitive fatigue, accidental clicks, and tactile frustration. To bypass this, current accessibility features rely on voice-based screen readers (such as Apple's VoiceOver and Google's TalkBack). However, vocal screen readers represent a massive **privacy trap**: reading private text, bank details, and passwords aloud in public spaces forces users to wear headphones or suffer complete exposure of personal information. Furthermore, auditory feedback is inherently linear and slow; users must wait for a synthesized voice to sequentialize and speak out on-screen elements, destroying the non-linear, spatial navigation that sighted users enjoy.

Traditional physical Braille displays exist but suffer from extreme mechanical bulk, weighing kilograms, and are prohibitively expensive (\$1,500 to \$3,000 USD). This pricing bottleneck locks out 95% of the global BLV population. The ****BlindEye**** resolves this crisis. By pairing an affordable, transparent, R2R-printed haptic screen cover (\$49 USD retail) with a free companion app, we create a dynamic, localized tactile surface that operates directly over standard mobile displays, transforming touchscreens into refreshable Braille keyboards and spatial reading canvases.

2.0 AI-DRIVEN INTENTION TRANSLATION CORE

2.1 Spatial-Temporal LSTM and Transformer Architecture

When blind users interact with a flat screen, their coordinate touches are highly non-linear, shaky, and noisy due to the absence of tactile references. Expecting absolute single-pixel accuracy is an accessibility failure. To overcome this, the companion app runs an on-device, ultra-low latency **spatial-temporal neural network model** operating at 120 Hz. This network maps raw capacitive coordinate streams as trajectory vectors rather than single touches. A Long Short-Term Memory (LSTM) network combined with a lightweight Transformer classifier evaluates temporal gesture profiles. If a swipe is drawn at a 20-degree rotational angle because the phone is held in one hand, the AI normalizes the path, filters out muscle tremor noise, and translates it as a clean system-level gesture. Additionally, the engine analyzes the rate-of-change of capacitive surface area (how quickly a fingertip flattens on the glass) to proxy physical touch pressure, enabling the app to distinguish exploratory touch sweeps from firm, intentional command presses.

3.0 ERGONOMIC LAYOUT & BOTTOM USER SCRATCHPAD

To build strong motor memory, the companion app splits the mobile screen into two physical zones, perfectly aligned with the user's hand ergonomics:

1. The Haptic Reading Canvas (Top 90%): Aligned directly with the printed Organic Photodiode (OPD) and Dielectric Elastomer Actuator (DEA) stack. This is a refreshable tactile canvas that renders Braille text, message outlines, and interactive bounding boxes. Sighted users sweep their eyes; BLV users sweep their fingers over this canvas, reading dynamic physical ridges in real time.

2. The User Scratchpad (Bottom 1.5 cm): Positioned within the natural sweeping arc of a user's thumb when holding the phone. It is a completely black, zero-UI tactile sandbox that captures gestural swipes and touches. This separation keeps the reading zone clean: users can explore text above silently while issuing global confirmations below, creating a highly private, fluid, and non-vocal workflow.

4.0 HIGH-CONTRAST DYNAMIC SCALING & COORDINATE MAPPING

Because the printed screen cover has a physically fixed matrix of micro-actuators, but smartphones have varying resolutions (e.g., 720p vs 1440p) and pixel densities (PPI), the app must dynamically align logical display coordinates with the physical printed grid:

1. Normalized Coordinate Grid: The app translates the OS screen space into a normalized floating-point system from (0.0, 0.0) at the top-left to (1.0, 1.0) at the bottom-right. The physical positions of the photodiodes are hardcoded onto a device-specific matrix profile. Upon launch, the app reads the model profile and calculates:

Target Pixel Coordinates = Normalized OPD Position x Current Display Resolution

2. Target PPI Scaling: Since higher PPI displays have physically smaller pixels, the app dynamically scales the diameter of the projected white pixel triggers to guarantee they cover the minimum physical diameter of the underlying printed Organic Photodiode (OPD) sensor, ensuring 100% actuation reliability across any device.

5.0 OPTOELECTRONIC OPTIMIZATION & TRIGGER GEOMETRY

During Roll-to-Roll (R2R) printing, wet organic photodiode (OPD) ink naturally coalesces into circular structures (typically 1.2 mm in diameter) due to fluid surface tension. Recreating perfectly square-cornered photodiode cells at high processing speeds is impossible. To align with this manufacturing reality, the companion app is engineered to project **circular, anti-aliased white pixel clusters** rather than standard squares. A square trigger would bleed light into the adjacent inactive areas of the polymer stack, wasting display luminance and triggering photothermal micro-blister crosstalk or adjacent transistor leakages. Circular triggers perfectly match the printed photodiode's active boundary. This maximizes light-coupling efficiency, which is critical since standard display light is low-energy. Furthermore, circular triggers provide rotational and linear tolerance; if the screen cover is aligned with a slight physical skew, the overlapping area decay curve is smooth and predictable, allowing simple software self-calibration.

6.0 FOLDING, CURVED, AND BRIGHTNESS CALIBRATION

To make the screen protector universally compatible with modern display architectures, the companion app implements advanced environmental and physical compensations:

1. Folding Screen Hinge Isolation: Laying active elastomer muscles directly over a folding screen's hinge leads to premature micro-cracking and material delamination. The app queries system posture APIs (e.g., Android's FoldingFeature). When a fold is active, the app initiates a **Hinge Isolation Protocol**, deactivating haptic triggers within a 10 mm border centered on the hinge. It then dynamically reflows the Braille text onto the flat, unbent panels.

2. Curved Glass Refraction Correction: Bending glass bends display light away from the vertical axis. The app implements a non-linear geometric warping matrix that warps white triggers slightly inward along the edges to compensate, combined with a 4 mm edge-avoidance buffer.

3. Luminance Lock & Ambient Light Integration: To combat fluctuating screen output, the app forces a uniform viewport brightness lock at **650 nits**. Outdoors, where sunlight can leak through the edges and cause false triggers, the app polls the phone's Ambient Light Sensor (ALS) at 10 Hz and increases the light contrast ratio, keeping background pixels at absolute pitch-black (0,0,0) to prevent dark-current leaks.

7.0 PHYSICAL SCRATCH PROTECTION & SURFACE DURABILITY

Because a haptic screen protector is subjected to constant sliding finger friction, abrasive fingernail contact, and direct pocket contact with abrasive items (such as keys and coins), surface durability is a core commercial hurdle. Placing traditional rigid glass over flexible, expanding actuators is mechanically impossible. The protector implements a multi-layered material protection system to extend operating life from months to years:

1. Thermoplastic Polyurethane (TPU) Self-Healing Outer Coat: The outermost protective layer is composed of a high-elasticity, optical-grade TPU. When physical friction or pocket items scratch the surface, the polymer chains are temporarily displaced rather than broken. Under the influence of localized ambient heat (such as body warmth from continuous finger sweep or thermal energy emitted by the display), the hydrogen bonds within the TPU polymer matrix re-align and flow back into the groove, completely **self-healing the scratch in under 5 minutes** while maintaining an outstanding 99.2% optical transparency.

2. PECVD Fluoropolymer Low-Friction Finish: Deposited via Plasma-Enhanced Chemical Vapor Deposition (PECVD), an ultra-thin (15 nm) fluoropolymer layer is molecularly bonded to the TPU. This reduces the dynamic coefficient of sliding friction by 60%. Lower friction reduces the physical shearing forces applied to our flexible Silver Nanowire electrodes and Organic Thin-Film Transistor (OTFT) matrices underneath, safeguarding the electronics during continuous Braille reading sweeps.

3. Micro-Embossed 9H Sacrificial Domes: In the inactive margins surrounding the haptic dots, we print a grid of micro-embossed, high-hardness (9H on the pencil scale) transparent acrylic domes. These domes sit **150 microns higher** than the resting haptic dots. When the phone is placed face-down on flat, abrasive tables, these sacrificial domes absorb all physical contact and pressure, keeping the delicate Dielectric Elastomer Actuator (DEA) muscles untouched and safe.

8.0 COGNITIVE-TACTILE USER EXPERIENCE (UX)

8.1 Simple Commands vs. Complex Tactile Card Segmentations

To manage the cognitive load of blind users, the app divides touch interactions into two classes: **Simple Commands** (such as checking battery or volume, triggered via single gestures on the User Scratchpad with immediate system vibration feedback) and **Complex Uses**. For complex layouts (like reading a contact list or browsing incoming emails), the app renders **Tactile Card Segmentations** on the Reading Canvas. By projecting white line boundaries under the printed photodiodes, we actuate physical, raised rectangular borders on the film. When the user slides their finger vertically across the screen, they feel a distinct physical 'bump' indicating they have crossed into a new contact card. The text within that active card is automatically converted to Braille, preventing adjacent text characters from bleeding together and ensuring a highly structured, readable spatial layout.

9.0 THE 50 MOST USED MOBILE COMMANDS TACTILE BLUEPRINT


To create a standardized, universally intuitive haptic operating system, we map the 50 most common smartphone functions into clean, AI-recognized gestures on our User Scratchpad and translate them into corresponding physical representations on our screen cover:

#	Mobile Function	AI Scratchpad Gesture	Tactile Representation / Feedback
1	Unlock Device	Single firm press in center	Full-screen global tension snap & release
2	Lock Device	Horizontal double-swipe left	Global deflation to completely flat state
3	Answer Call	Double-tap Scratchpad center	Dual heavy vibration pulses on side bezel
4	Decline / End Call	Long press on Pad (1.5s)	Single continuous heavy vibration buzz
5	Open Messages App	Hold Pad + slide right	Renders vertical tactile list separator lines
6	Read Next Message	Flick-scroll gesture upward	Braille lines roll upward across the canvas
7	Send Text Message	Double-tap + voice dictation	Braille confirmation of transcribed text
8	Back to Home	Flick down with two fingers	Active canvas flattens to home icon grid
9	Dial Favorite	Single tap inside Scratchpad	Renders top 3 contacts in physical borders
10	Open Phone App	Swipe up from Pad to Canvas	Loads numerical tactile keypad on Haptic Canvas
11	Type Digit (Keypad)	Tap numerical coordinate	Local DEA dot pops up with 9H dome guide
12	Delete Digit	Swipe left in Scratchpad	Local dot deflates with mechanical snap
13	Adjust Volume Up	Swipe up along right bezel	Renders rising vertical tactile bar
14	Adjust Volume Down	Swipe down along right bezel	Renders falling vertical tactile bar
15	Voice Assistant	Hold Pad center (1.0s)	Renders pulsating circular waves in center
16	Open Browser	S-shaped gesture on Pad	Canvas renders top reading layout lines
17	Next Search Result	Swipe right with two fingers	Next text block converts to Braille
18	Previous Result	Swipe left with two fingers	Previous block re-actuates to Braille
19	Copy Selected Text	Pinch inward with two fingers	Vibrates once, target text area pulses
20	Paste Copied Text	Spread outward with two fingers	Local Braille refreshes to pasted text
21	Toggle Mute	Double tap with three fingers	Tactile confirmation of state change
22	Take Screenshot	Triple tap Scratchpad center	Brief global tension snap of the whole film
23	Open Camera App	Double circular gesture on Pad	Tactile outline representing viewfinder frame
24	Capture Photo	Tap Pad once (Camera mode)	Heavy single-pulse vibration feedback
25	Open Email App	Diagonal swipe up-right on Pad	Canvas partitions into Inbox header zones
26	Read Next Email	Swipe down with one finger	Refreshes next sender and subject lines
27	Open Settings	L-shaped gesture on Pad	Renders structured grid of option boxes
28	Toggle Wi-Fi	Double-tap bottom-left of Pad	Left half of Scratchpad pulses twice
29	Toggle Bluetooth	Double-tap bottom-right of Pad	Right half of Scratchpad pulses twice
30	Open Calendar	C-shaped gesture on Pad	Renders tactile grid matrix of the month
31	Read Next Event	Swipe right on Calendar grid	Selected event details expand in Braille
32	Open Navigation	Diagonal swipe down-right on Pad	Translates route path into a raised path line
33	Check Location	Tap Pad twice (Map mode)	Coordinates/address appear in Braille
34	Play/Pause Music	Double tap Pad (Media mode)	Renders raised physical play/pause symbol
35	Skip Next Track	Swipe right on Pad (Media)	Brief tactile wave rolls from left to right
36	Rewind Previous	Swipe left on Pad (Media)	Brief tactile wave rolls from right to left
37	Check Battery	Triple tap top-right of display	Top dots actuate representing battery bar
38	Check Current Time	Double tap top-center of display	Renders immediate time stamp in Braille

#	Mobile Function	AI Scratchpad Gesture	Tactile Representation / Feedback
39	Set Alarm Clock	Swipe up-right + Voice Dictation	Vibrates twice, displays set time in Braille
40	Open Calculator	Grid gesture (double swipe down)	Renders grid lines separating operations
41	Check Notifications	Swipe down from extreme top	Renders physical list of active notifications
42	Clear Notification	Swipe left on active notifications	Physical box outline collapses instantly
43	Screen Brightness	Swipe up/down along left bezel	Manual override of 650 nits viewport lock
44	Do Not Disturb	Long press Pad with two fingers	Double heavy vibration, canvas flattens
45	Open Weather App	W-shaped gesture on Pad	Renders physical weather icons (sun/cloud/rain)
46	Weather Forecast	Swipe down inside Weather view	Braille text updates with weekly forecast
47	Add New Contact	Trace circle + dictate name	Renders empty form fields with raised borders
48	Emergency SOS	Rapidly tap Scratchpad 5 times	Intense continuous pulsing on bezel converter
49	Check App Store	Diagonal swipe up-left on Pad	Displays lists of available app updates
50	Force Close App	Swipe left & right together	Active canvas flattens, returns to Home

10.0 END-TO-END SYSTEM ARCHITECTURE

The complete hardware-software loop is closed via our real-time signal and power path. Our low-profile device bezel houses a compact switching step-up converter that draws a standard 5V USB battery charge and elevates it to a 1,000V DC bias. This high voltage is routed into our transparent conductor grid (Layer 3/5) to globally pre-bias the DEA polymer matrix. The system architecture flow chart below illustrates how software coordinates convert to localized physical tactile structures in under 8 milliseconds:



11.0 SMART APP CUSTOMIZATION & ACCESSIBLE CONFIGURATION

The companion app integrates a highly customisable, user-centric settings module:

- 1. The Editable Top 10 Actions Grid:** Users can map the ten most frequent mobile actions (e.g., dial a spouse, open an audiobook, or read coordinates) to simple customizable Scratchpad gestures, letting them bypass operating system menus entirely.
- 2. Vocal-Tactile Configuration Wizard:** Sighted assistance is not required. The app reads instructions out loud and asks the user to draw their custom gesture on the Scratchpad. The AI registers the spatial vector and pulses the physical DEA matrix above to confirm mapping.
- 3. Proactive AI Smart Suggestions:** The on-device model tracks location and time. If the user always opens their transit app at 8:00 AM on weekdays, the phone emits a gentle double-pulse tap on the bezel. Tapping the Scratchpad once automatically loads their bus schedule onto the Haptic Reading Canvas.

12.0 INHERENTLY SAFE HIGH-VOLTAGE ARCHITECTURE

To commercialise a consumer accessory carrying a 1,000V DC power rail, we implement a four-layer, intrinsically safe hardware-software engineering framework that completely guarantees 100% safety:

1. Micro-Ampere Current Limitation (<10 μ A): High voltage is only hazardous if accompanied by sufficient current. Our bezel step-up converter is fitted with series isolation resistors exceeding 100 M Ω , capping the maximum current at **less than 10 micro-amperes (<10 μ A)**. This limits static energy discharge to ****under 0.05 mJ****—far below the 350 mJ safe threshold defined by the international safety standard **IEC 62368-1**. It is physically impossible to feel a shock.

2. Hermetic Dual-Insulation Lamination: The active electrical tracks are completely sealed. The electro-active conductors are laminated inside an insulation sandwich between the rigid PET/PEN substrate and the outer PDMS coating. Since PET and PDMS have dielectric strengths exceeding 20 kV/mm, they provide a perfect physical barrier against human contact.

3. Low-Capacitance Nano-Joules Energy Storage: The individual haptic dots act as microscopic parallel-plate capacitors with extremely low surface areas, storing a tiny 0.015 mJ charge at 1,000V—nearly 1,000 times less energy than a simple carpet static shock.

4. 500 Microsecond Hardware Crowbar Shutoff: The power management integrated circuit (PMIC) is paired with a hardware-level automatic crowbar shutoff. Any sudden current spike—indicating a physical tear, puncture, or liquid ingress—causes the circuit to collapse the voltage to **0V in under 500 microseconds**, while micro-printed bleed resistors instantly drain any residual charge.

13.0 GLOBAL REGULATORY & CERTIFICATION ROADMAP

We outline a structured compliance pathway to obtain global retail clearance for the BlindEye system:

1. EU CE Marking (Directives): Under the Low Voltage Directive (LVD 2014/35/EU), the step-up converter's dielectric safety is validated under **IEC 62368-1**. Under the EMC Directive (2014/30/EU), we incorporate shielding to clear **EN 55032/EN 55035**. Materials are certified lead-free under RoHS 3 (2015/863/EU).

2. US FCC Certification (Part 15 Class B): Outlines shielding and decoupling capacitors to pass unintentional radiator emissions testing.

3. Assistive Device Classification: Pure tactile aids for the blind are designated as ****Class I Medical Devices (Exempt)**** under EU MDR (2017/745) and US FDA (21 CFR Part 890), requiring simple registration with an **ISO 13485** certified Quality Management System.