Imam:

Limit to 1000 rows ▾

```sql
1 •   Create database c241130;
2 •   USE c241130;
3
4 •⊖ CREATE table ID_C241130(
5     S_id INT PRIMARY KEY,
6     S_name VARCHAR(30),
7     S_phoneNumber VARCHAR(30),
8     S_address VARCHAR(30)
9     );
```

Result Grid | Filter Rows: | Edit: | Export/Import: | Wrap Cell Content: ‡A

S_id	S_name	S_phoneNumber	S_address
NULL	NULL	NULL	NULL

```sql
11 •   INSERT INTO ID_C241130(S_id, S_name, S_phoneNumber, S_address)
12     VALUES
13     (101, "Hasan", "01813259241", "Dhaka"),
14     (102, "Kamal", "01813259242", "ctg"),
15     (103, "Rony", "01813259243", "Dhaka"),
16     (104, "Rakib", "01813259244", "com")
```

Result Grid | Filter Rows: | Edit: | Export/Import: | Wrap Cell Content: ‡A

S_id	S_name	S_phoneNumber	S_address
101	Hasan	01813259241	Dhaka
102	Kamal	01813259242	ctg
103	Rony	01813259243	Dhaka
104	Rakib	01813259244	com
NULL	NULL	NULL	NULL

```sql
SELECT S_id, S_name, S_phoneNumber, S_address FROM ID_C241130
WHERE
S_id = 102;
```

Result Grid | Filter Rows: | Edit: | Export/Import: | Wrap Cell Content:

S_id	S_name	S_phoneNumber	S_address
102	Kamal	01813259242	ctg
NULL	NULL	NULL	NULL

Query 1 | id_c241130

```sql
ALTER table ID_C241130
ADD S_CGPA VARCHAR(10);

SELECT * FROM  ID_C241130;
```

Result Grid | Filter Rows: | Edit: | Export/Import: | Wrap Cell Content:

S_id	S_name	S_phoneNumber	S_address	S_CGPA
101	Hasan	01813259241	Dhaka	NULL
102	Kamal	01813259242	ctg	NULL
103	Rony	01813259243	Dhaka	NULL
104	Rakib	01813259244	com	NULL
NULL	NULL	NULL	NULL	NULL

```sql
ALTER table ID_C241130
DROP S_CGPA ;

SELECT * FROM  ID_C241130;
```

Result Grid | Filter Rows: | Edit: | Export/Import: | Wrap Cell Content:

S_id	S_name	S_phoneNumber	S_address
101	Hasan	01813259241	Dhaka
102	Kamal	01813259242	ctg
103	Rony	01813259243	Dhaka
104	Rakib	01813259244	com
NULL	NULL	NULL	NULL

MySQL Workbench

IIUC   IIUC (c241130)

File   Edit   View   Query   Database   Server   Tools   Scripting   Help

Navigator

SCHEMAS

Filter objects

▼ c241130
   Tables
   Views
   Stored Procedures
   Functions
► pizzahome
► sys

Query 1   id_c241130

Limit to 1000 rows

```sql
DROP TABLE ID_C241130;
```

Jewel:

Limit to 1000 rows

```sql
1 •   CREATE DATABASE C241131;
2 •   USE C241131;
3
4 • ⊝ CREATE TABLE ID_NO_C241131(
5       S_id INT PRIMARY KEY,
6       S_name VARCHAR(40),
7       S_phoneNumber VARCHAR(40),
8       S_address VARCHAR(20)
9     );
```

Result Grid | Filter Rows: | Edit: | Export/Import: | Wrap Cell Content:

S_id	S_name	S_phoneNumber	S_address
NULL	NULL	NULL	NULL

```sql
11 •   INSERT INTO ID_NO_C241131(S_id, S_name, S_phoneNumber, S_address)
12     VALUES
13     (101, "Hasan", "0181982565", "DHK"),
14     (102, "kamal", "0188982565", "ctg"),
15     (103, "rony", "0199982565", "Dhk"),
16     (104, "rakib", "0166982565", "com")
17
```

Result Grid | Filter Rows: | Edit: | Export/Import: | Wrap

S_id	S_name	S_phoneNumber	S_address
101	Hasan	0181982565	DHK
102	kamal	0188982565	ctg
103	rony	0199982565	Dhk
104	rakib	0166982565	com
NULL	NULL	NULL	NULL

Query 1

```sql
SELECT S_id, S_name, S_phoneNumber, S_address FROM ID_NO_C241131
WHERE S_id = 102;
```

Result Grid | Filter Rows: | Edit: | Export/Import: | Wrap Cell Content:

S_id	S_name	S_phoneNumber	S_address
102	kamal	0188982565	ctg
NULL	NULL	NULL	NULL

```sql
ALTER table  ID_NO_C241131
ADD S_CGPA VARCHAR(10);

SELECT * FROM ID_NO_C241131;
```

Result Grid | Filter Rows: | Edit: | Export/Import: | Wrap Cell

S_id	S_name	S_phoneNumber	S_address	S_CGPA
101	Hasan	0181982565	DHK	NULL
102	kamal	0188982565	ctg	NULL
103	rony	0199982565	Dhk	NULL
104	rakib	0166982565	com	NULL
NULL	NULL	NULL	NULL	NULL

```
Query 1  ×

1 •    ALTER table  ID_NO_C241131
2      DROP S_CGPA ;
3
4 •    SELECT * FROM ID_NO_C241131;
5
6
7
```

S_id	S_name	S_phoneNumber	S_address
101	Hasan	0181982565	DHK
102	kamal	0188982565	ctg
103	rony	0199982565	Dhk
104	rakib	0166982565	com
NULL	NULL	NULL	NULL

```
Query 1  ×

1 •    DROP TABLE ID_NO_C241131;
2
3
```

Noyel:

```
Limit to 1000 rows

 1 •    CREATE DATABASE C233180;

 2 •    USE C233180;

 3 • ⊖  CREATE TABLE ID_NO_C233180(

 4       S_id INT PRIMARY KEY,

 5       S_name VARCHAR(20),

 6       S_phoneNumber VARCHAR(20),

 7       S_address VARCHAR(20)

 8       );

 9       |
```

Result Grid | Filter Rows: | Edit: | Export/Import: | Wrap Cell Content:

S_id	S_name	S_phoneNumber	S_address
NULL	NULL	NULL	NULL

```
10 •    INSERT INTO ID_NO_C233180(S_id, S_name, S_phoneNumber, S_address)

11      VALUES

12      (101, "Hasan", "0171982565", "DHK"),

13      (102, "kamal", "0181982565", "ctg"),

14      (103, "rony", "0191982565", "Dhk"),|

15      (104, "rakib", "0161982565", "com")
```

Result Grid | Filter Rows: | Edit: | Ex

S_id	S_name	S_phoneNumber	S_address
101	Hasan	0171982565	DHK
102	kamal	0181982565	ctg
103	rony	0191982565	Dhk
104	rakib	0161982565	com
NULL	NULL	NULL	NULL

Limit to 1000 rows

```
1 •    CREATE DATABASE C233180;
2 •    USE C233180;
3
4 •    SELECT S_id, S_name, S_phoneNumber, S_address FROM ID_NO_C233180
5      WHERE S_id = 102;
6
7
```

Result Grid | Filter Rows: | Edit: | Export/Import: | Wrap Cell Content:

S_id	S_name	S_phoneNumber	S_address
102	kamal	0181982565	ctg
NULL	NULL	NULL	NULL

Limit to 1000 rows

```
1 •    ALTER table  ID_NO_C233180
2      ADD S_CGPA VARCHAR(10);
3
4 •    SELECT * FROM ID_NO_C233180;
5
```

Result Grid | Filter Rows: | Edit: | Export/Import:

S_id	S_name	S_phoneNumber	S_address	S_CGPA
101	Hasan	0171982565	DHK	NULL
102	kamal	0181982565	ctg	NULL
103	rony	0191982565	Dhk	NULL
104	rakib	0161982565	com	NULL
NULL	NULL	NULL	NULL	NULL

```
4 •    SELECT * FROM ID_NO_C233180;

5

6 •    ALTER table  ID_NO_C233180

7      DROP S_CGPA ;

8
```

S_id	S_name	S_phoneNumber	S_address
101	Hasan	0171982565	DHK
102	kamal	0181982565	ctg
103	rony	0191982565	Dhk
104	rakib	0161982565	com
NULL	NULL	NULL	NULL

```
1 •    DROP TABLE ID_NO_C233180;

2

3
```