

Warehouse Rover R3 - Operator Manual

Revision C, May 2026. Applies to firmware 3.4 and later.

Contents

1. Safety overview
2. Unpacking and site survey
3. Installing the charging dock
4. Commissioning a new rover
5. Mapping the facility
6. Defining zones and routes
7. Missions and task assignment
8. Status lights and sounds
9. Emergency stop
10. Battery care
11. Payload handling
12. Wi-Fi and 5G connectivity
13. Fleet Manager integration
14. Floors, ramps and thresholds
15. Outdoor loading docks
16. Software updates
17. Routine maintenance
18. Troubleshooting
19. Decommissioning
20. Warranty and support

1. Safety overview

1.1 Do not modify the rover chassis; unauthorised modifications void the warranty. The status light ring indicates the current operating mode; refer to the light codes table in the appendix. Log every incident in Fleet Manager, including near misses, within the same shift. Operators must complete the Northwind certified operator course before using the rover in production. Always confirm that the work area is clear of personnel before starting an autonomous mission. Payloads must be centred on the deck and secured with the supplied retention straps. Keep the charging dock free of debris and ensure the floor in front of it is level.

1.2 Always confirm that the work area is clear of personnel before starting an autonomous mission. Do not modify the rover chassis; unauthorised modifications void the warranty. Payloads must be centred on the deck and secured with the supplied retention straps. Operators must complete the Northwind certified operator course before using the rover in production. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. The rover slows to 0.5 m/s when it detects a person within 2 metres. Log every incident in Fleet Manager, including near misses, within the same shift.

1.3 Log every incident in Fleet Manager, including near misses, within the same shift. Operating temperature range is 0 to 45 degrees Celsius. Always confirm that the work area is clear of personnel before starting an autonomous mission. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. Payloads must be centred on the deck and secured with the supplied retention straps. Keep the charging dock free of debris and ensure the floor in front of it is level. The rover slows to 0.5 m/s when it detects a person within 2 metres.

1.4 Operators must complete the Northwind certified operator course before using the rover in production. Payloads must be centred on the deck and secured with the supplied retention straps. Always confirm that the work area is clear of personnel before starting an autonomous mission. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. Operating temperature range is 0 to 45 degrees Celsius. Keep the charging dock free of debris and ensure the floor in front of it is level. Log every incident in Fleet Manager, including near misses, within the same shift.

1.5 Log every incident in Fleet Manager, including near misses, within the same shift. Operators must complete the Northwind certified operator course before using the rover in production. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. The status light ring indicates the current operating mode; refer to the light codes table in the appendix. Firmware updates are staged to a canary group before fleet-wide rollout. Payloads must be centred on the deck and secured with the supplied retention straps.

1.6 The status light ring indicates the current operating mode; refer to the light codes table in the appendix. The rover slows to 0.5 m/s when it detects a person within 2 metres. Always confirm that the work area is clear of personnel before starting an autonomous mission. Keep the charging dock free of debris and ensure the floor in front of it is level. Operating temperature range is 0 to 45 degrees Celsius. Operators must complete the Northwind certified operator course before using the rover in production. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor.

1.7 Payloads must be centred on the deck and secured with the supplied retention straps. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. Do not modify the rover chassis; unauthorised modifications void the warranty. Always confirm that the work area is clear of personnel before starting an autonomous mission. Keep the charging dock free of debris and ensure the floor in front of it is level. The rover slows to 0.5 m/s when it detects a person within 2 metres.

1.8 Always confirm that the work area is clear of personnel before starting an autonomous mission. Payloads must be centred on the deck and secured with the supplied retention straps. Operators must complete the Northwind certified operator course before using the rover in production. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. Firmware updates are staged to a canary group before fleet-wide rollout. Do not modify the rover chassis; unauthorised modifications void the warranty. Keep the charging dock free of debris and ensure the floor in front of it is level.

2. Unpacking and site survey

2.1 Log every incident in Fleet Manager, including near misses, within the same shift. Do not modify the rover chassis; unauthorised modifications void the warranty. Firmware updates are staged to a canary group before fleet-wide rollout. Payloads must be centred on the deck and secured with the supplied retention straps. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. The status light ring indicates the current operating mode; refer to the light codes table in the appendix. Always confirm that the work area is clear of personnel before starting an autonomous mission.

2.2 The status light ring indicates the current operating mode; refer to the light codes table in the appendix. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. Always confirm that the work area is clear of personnel before starting an autonomous mission. Keep the charging dock free of debris and ensure the floor in front of it is level. Firmware updates are staged to a canary group before fleet-wide rollout. Operating temperature range is 0 to 45

degrees Celsius. Do not modify the rover chassis; unauthorised modifications void the warranty.

2.3 Firmware updates are staged to a canary group before fleet-wide rollout. Keep the charging dock free of debris and ensure the floor in front of it is level. Payloads must be centred on the deck and secured with the supplied retention straps. Always confirm that the work area is clear of personnel before starting an autonomous mission. The rover slows to 0.5 m/s when it detects a person within 2 metres. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation.

2.4 The status light ring indicates the current operating mode; refer to the light codes table in the appendix. Do not modify the rover chassis; unauthorised modifications void the warranty. Operating temperature range is 0 to 45 degrees Celsius. Firmware updates are staged to a canary group before fleet-wide rollout. Log every incident in Fleet Manager, including near misses, within the same shift. Operators must complete the Northwind certified operator course before using the rover in production. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor.

2.5 Always confirm that the work area is clear of personnel before starting an autonomous mission. The rover slows to 0.5 m/s when it detects a person within 2 metres. Payloads must be centred on the deck and secured with the supplied retention straps. Do not modify the rover chassis; unauthorised modifications void the warranty. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Firmware updates are staged to a canary group before fleet-wide rollout. The status light ring indicates the current operating mode; refer to the light codes table in the appendix.

2.6 Payloads must be centred on the deck and secured with the supplied retention straps. Firmware updates are staged to a canary group before fleet-wide rollout. Operating temperature range is 0 to 45 degrees Celsius. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Always confirm that the work area is clear of personnel before starting an autonomous mission. Log every incident in Fleet Manager, including near misses, within the same shift. Operators must complete the Northwind certified operator course before using the rover in production.

2.7 Keep the charging dock free of debris and ensure the floor in front of it is level. Firmware updates are staged to a canary group before fleet-wide rollout. Always confirm that the work area is clear of personnel before starting an autonomous mission. Operators must complete the Northwind certified operator course before using the rover in production. Operating temperature range is 0 to 45 degrees Celsius. Do not modify the rover chassis; unauthorised modifications void the warranty. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor.

2.8 If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Firmware updates are staged to a canary group before fleet-wide rollout. Keep the charging dock free of debris and ensure the floor in front of it is level. Log every incident in Fleet Manager, including near misses, within the same shift. Do not modify the rover chassis; unauthorised modifications void the warranty. Operators must complete the Northwind certified operator course before using the rover in production. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation.

3. Installing the charging dock

3.1 Do not modify the rover chassis; unauthorised modifications void the warranty. The status light ring indicates the current operating mode; refer to the light codes table in the appendix. Payloads must be centred on the deck and secured with the supplied retention straps. Always confirm that the work area is clear of personnel before starting an autonomous mission. Firmware updates are staged to a canary group before fleet-wide rollout. Operators must complete the Northwind certified operator course before using the rover in production. The rover slows to 0.5 m/s when it detects a person within 2 metres.

3.2 Keep the charging dock free of debris and ensure the floor in front of it is level. The status light ring indicates the current operating mode; refer to the light codes table in the appendix. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. Log every incident in Fleet Manager, including near misses, within the same shift. The rover slows to 0.5 m/s when it detects a person within 2 metres. Firmware updates are staged to a canary group before fleet-wide rollout. Payloads must be centred on the deck and secured with the supplied retention straps.

3.3 Always confirm that the work area is clear of personnel before starting an autonomous mission. The status light ring indicates the current operating mode; refer to the light codes table in the appendix. Firmware updates are staged to a canary group before fleet-wide rollout. Log every incident in Fleet Manager, including near misses, within the same shift. Keep the charging dock free of debris and ensure the floor in front of it is level. Operating temperature range is 0 to 45 degrees Celsius. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation.

3.4 The rover slows to 0.5 m/s when it detects a person within 2 metres. Keep the charging dock free of debris and ensure the floor in front of it is level. Log every incident in Fleet Manager, including near misses, within the same shift. Do not modify the rover chassis; unauthorised modifications void the warranty. Payloads must be centred on the deck and secured with the supplied retention straps. Always confirm that the work area is clear of personnel before starting an autonomous mission. Firmware updates are staged to a canary group before fleet-wide rollout.

3.5 Always confirm that the work area is clear of personnel before starting an autonomous mission. The status light ring indicates the current operating mode; refer to the light codes table in the appendix. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. The rover slows to 0.5 m/s when it detects a person within 2 metres. Operators must complete the Northwind certified operator course before using the rover in production. Firmware updates are staged to a canary group before fleet-wide rollout.

3.6 Payloads must be centred on the deck and secured with the supplied retention straps. The status light ring indicates the current operating mode; refer to the light codes table in the appendix. Keep the charging dock free of debris and ensure the floor in front of it is level. Operating temperature range is 0 to 45 degrees Celsius. Operators must complete the Northwind certified operator course before using the rover in production. Always confirm that the work area is clear of personnel before starting an autonomous mission. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation.

3.7 The rover slows to 0.5 m/s when it detects a person within 2 metres. Do not modify the rover chassis; unauthorised modifications void the warranty. Payloads must be centred on the deck and secured with the supplied retention straps. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. The status light ring indicates the current operating mode; refer to the light codes table in the appendix. Operating temperature range is 0 to 45 degrees Celsius. Keep the charging dock free of debris and ensure the floor in front of it is level.

3.8 Payloads must be centred on the deck and secured with the supplied retention straps. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Operators must complete the Northwind certified operator course before using the rover in production. Firmware updates are staged to a canary group before fleet-wide rollout. Log every incident in Fleet Manager, including near misses, within the same shift. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. The rover slows to 0.5 m/s when it detects a person within 2 metres.

4. Commissioning a new rover

4.1 Log every incident in Fleet Manager, including near misses, within the same shift. Always confirm that the work area is clear of personnel before starting an autonomous mission. Firmware updates are staged to a canary group before fleet-wide rollout. Operating temperature range is 0 to 45 degrees Celsius. Operators must complete the Northwind certified operator course before using the rover in production. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Payloads must be centred on the deck and secured with the supplied retention straps.

4.2 Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. Firmware updates are staged to a canary group before fleet-wide rollout. The status light ring indicates the current operating mode; refer to the light codes table in the appendix. Always confirm that the work area is clear of personnel before starting an autonomous mission. Do not modify the rover chassis; unauthorised modifications void the warranty. Keep the charging dock free of debris and ensure the floor in front of it is level. Operators must complete the Northwind certified operator course before using the rover in production.

4.3 Always confirm that the work area is clear of personnel before starting an autonomous mission. Operators must complete the Northwind certified operator course before using the rover in production. Payloads must be centred on the deck and secured with the supplied retention straps. The status light ring indicates the current operating mode; refer to the light codes table in the appendix. Operating temperature range is 0 to 45 degrees Celsius. The rover slows to 0.5 m/s when it detects a person within 2 metres. Keep the charging dock free of debris and ensure the floor in front of it is level.

4.4 Operators must complete the Northwind certified operator course before using the rover in production. Always confirm that the work area is clear of personnel before starting an autonomous mission. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. Log every incident in Fleet Manager, including near misses, within the same shift. The status light ring indicates the current operating mode; refer to the light codes table in the appendix. Do not modify the rover chassis; unauthorised modifications void the warranty. Firmware updates are staged to a canary group before fleet-wide rollout.

4.5 Do not modify the rover chassis; unauthorised modifications void the warranty. Payloads must be centred on the deck and secured with the supplied retention straps. Operating temperature range is 0 to 45 degrees Celsius. Firmware updates are staged to a canary group before fleet-wide rollout. Always confirm that the work area is clear of personnel before starting an autonomous mission. Operators must complete the Northwind certified operator course before using the rover in production. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation.

4.6 Firmware updates are staged to a canary group before fleet-wide rollout. Operating temperature range is 0 to 45 degrees Celsius. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Keep the charging dock free of debris and ensure the floor in front of it is level. Always confirm that the work area is clear of personnel before starting an autonomous mission. Payloads must be centred on the deck and secured with the supplied retention straps. Operators must complete the Northwind certified operator course before using the rover in production.

4.7 Operating temperature range is 0 to 45 degrees Celsius. Do not modify the rover chassis; unauthorised modifications void the warranty. Keep the charging dock free of debris and ensure the floor in front of it is level. Firmware updates are staged to a canary group before fleet-wide rollout. The status light ring indicates the current operating mode; refer to the light codes table in the appendix. Payloads must be centred on the deck and secured with the supplied retention straps. Operators must complete the Northwind certified operator course before using the rover in production.

4.8 Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. The rover slows to 0.5 m/s when it detects a person within 2 metres. Do not modify the rover chassis; unauthorised modifications void the warranty. The status light ring indicates the current

operating mode; refer to the light codes table in the appendix. Operators must complete the Northwind certified operator course before using the rover in production. Log every incident in Fleet Manager, including near misses, within the same shift. Keep the charging dock free of debris and ensure the floor in front of it is level.

5. Mapping the facility

5.1 Keep the charging dock free of debris and ensure the floor in front of it is level. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Always confirm that the work area is clear of personnel before starting an autonomous mission. Operating temperature range is 0 to 45 degrees Celsius. Do not modify the rover chassis; unauthorised modifications void the warranty. Payloads must be centred on the deck and secured with the supplied retention straps. The status light ring indicates the current operating mode; refer to the light codes table in the appendix.

5.2 Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. The rover slows to 0.5 m/s when it detects a person within 2 metres. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Payloads must be centred on the deck and secured with the supplied retention straps. Do not modify the rover chassis; unauthorised modifications void the warranty. Firmware updates are staged to a canary group before fleet-wide rollout. Always confirm that the work area is clear of personnel before starting an autonomous mission.

5.3 Payloads must be centred on the deck and secured with the supplied retention straps. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Log every incident in Fleet Manager, including near misses, within the same shift. Operating temperature range is 0 to 45 degrees Celsius. Always confirm that the work area is clear of personnel before starting an autonomous mission. Keep the charging dock free of debris and ensure the floor in front of it is level.

5.4 Firmware updates are staged to a canary group before fleet-wide rollout. Do not modify the rover chassis; unauthorised modifications void the warranty. Operators must complete the Northwind certified operator course before using the rover in production. Payloads must be centred on the deck and secured with the supplied retention straps. Keep the charging dock free of debris and ensure the floor in front of it is level. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. The status light ring indicates the current operating mode; refer to the light codes table in the appendix.

5.5 Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. Payloads must be centred on the deck and secured with the supplied retention straps. Do not modify the rover chassis; unauthorised modifications void the warranty. Firmware updates are staged to a canary group before fleet-wide rollout. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. The status light ring indicates the current operating mode; refer to the light codes table in the appendix. Operators must complete the Northwind certified operator course before using the rover in production.

5.6 Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. Always confirm that the work area is clear of personnel before starting an autonomous mission. Operating temperature range is 0 to 45 degrees Celsius. Firmware updates are staged to a canary group before fleet-wide rollout. Payloads must be centred on the deck and secured with the supplied retention straps. The status light ring indicates the current operating mode; refer to the light codes table in the appendix. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor.

5.7 Firmware updates are staged to a canary group before fleet-wide rollout. Payloads must be centred

on the deck and secured with the supplied retention straps. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Operators must complete the Northwind certified operator course before using the rover in production. Operating temperature range is 0 to 45 degrees Celsius. Do not modify the rover chassis; unauthorised modifications void the warranty. The status light ring indicates the current operating mode; refer to the light codes table in the appendix.

5.8 If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Always confirm that the work area is clear of personnel before starting an autonomous mission. Operating temperature range is 0 to 45 degrees Celsius. Log every incident in Fleet Manager, including near misses, within the same shift. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. Firmware updates are staged to a canary group before fleet-wide rollout. Payloads must be centred on the deck and secured with the supplied retention straps.

6. Defining zones and routes

6.1 Log every incident in Fleet Manager, including near misses, within the same shift. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Do not modify the rover chassis; unauthorised modifications void the warranty. Always confirm that the work area is clear of personnel before starting an autonomous mission. Operating temperature range is 0 to 45 degrees Celsius. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. Firmware updates are staged to a canary group before fleet-wide rollout.

6.2 Operating temperature range is 0 to 45 degrees Celsius. Always confirm that the work area is clear of personnel before starting an autonomous mission. The status light ring indicates the current operating mode; refer to the light codes table in the appendix. Payloads must be centred on the deck and secured with the supplied retention straps. The rover slows to 0.5 m/s when it detects a person within 2 metres. Operators must complete the Northwind certified operator course before using the rover in production. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor.

6.3 Payloads must be centred on the deck and secured with the supplied retention straps. Firmware updates are staged to a canary group before fleet-wide rollout. The status light ring indicates the current operating mode; refer to the light codes table in the appendix. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Do not modify the rover chassis; unauthorised modifications void the warranty. Always confirm that the work area is clear of personnel before starting an autonomous mission. Keep the charging dock free of debris and ensure the floor in front of it is level.

6.4 The rover slows to 0.5 m/s when it detects a person within 2 metres. The status light ring indicates the current operating mode; refer to the light codes table in the appendix. Operators must complete the Northwind certified operator course before using the rover in production. Payloads must be centred on the deck and secured with the supplied retention straps. Always confirm that the work area is clear of personnel before starting an autonomous mission. Keep the charging dock free of debris and ensure the floor in front of it is level. Do not modify the rover chassis; unauthorised modifications void the warranty.

6.5 The status light ring indicates the current operating mode; refer to the light codes table in the appendix. Log every incident in Fleet Manager, including near misses, within the same shift. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. Payloads must be centred on the deck and secured with the supplied retention straps. Operators must complete the Northwind certified operator course before using the rover in production. Operating temperature range is 0 to 45 degrees Celsius. Always confirm that the work area is clear of personnel before starting an autonomous mission.

6.6 Keep the charging dock free of debris and ensure the floor in front of it is level. The rover slows to 0.5 m/s when it detects a person within 2 metres. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. Do not modify the rover chassis; unauthorised

modifications void the warranty. Operating temperature range is 0 to 45 degrees Celsius. Firmware updates are staged to a canary group before fleet-wide rollout. Payloads must be centred on the deck and secured with the supplied retention straps.

6.7 The status light ring indicates the current operating mode; refer to the light codes table in the appendix. Operators must complete the Northwind certified operator course before using the rover in production. Do not modify the rover chassis; unauthorised modifications void the warranty. Firmware updates are staged to a canary group before fleet-wide rollout. Log every incident in Fleet Manager, including near misses, within the same shift. The rover slows to 0.5 m/s when it detects a person within 2 metres. Keep the charging dock free of debris and ensure the floor in front of it is level.

6.8 The status light ring indicates the current operating mode; refer to the light codes table in the appendix. The rover slows to 0.5 m/s when it detects a person within 2 metres. Operating temperature range is 0 to 45 degrees Celsius. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Operators must complete the Northwind certified operator course before using the rover in production. Log every incident in Fleet Manager, including near misses, within the same shift. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation.

7. Missions and task assignment

7.1 The status light ring indicates the current operating mode; refer to the light codes table in the appendix. Payloads must be centred on the deck and secured with the supplied retention straps. Operators must complete the Northwind certified operator course before using the rover in production. Operating temperature range is 0 to 45 degrees Celsius. The rover slows to 0.5 m/s when it detects a person within 2 metres. Always confirm that the work area is clear of personnel before starting an autonomous mission. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation.

7.2 Payloads must be centred on the deck and secured with the supplied retention straps. Always confirm that the work area is clear of personnel before starting an autonomous mission. The rover slows to 0.5 m/s when it detects a person within 2 metres. Operators must complete the Northwind certified operator course before using the rover in production. Do not modify the rover chassis; unauthorised modifications void the warranty. Firmware updates are staged to a canary group before fleet-wide rollout. Keep the charging dock free of debris and ensure the floor in front of it is level.

7.3 The rover slows to 0.5 m/s when it detects a person within 2 metres. Operating temperature range is 0 to 45 degrees Celsius. Firmware updates are staged to a canary group before fleet-wide rollout. Always confirm that the work area is clear of personnel before starting an autonomous mission. Operators must complete the Northwind certified operator course before using the rover in production. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Log every incident in Fleet Manager, including near misses, within the same shift.

7.4 Keep the charging dock free of debris and ensure the floor in front of it is level. Operators must complete the Northwind certified operator course before using the rover in production. Always confirm that the work area is clear of personnel before starting an autonomous mission. The rover slows to 0.5 m/s when it detects a person within 2 metres. Firmware updates are staged to a canary group before fleet-wide rollout. Operating temperature range is 0 to 45 degrees Celsius. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor.

7.5 Always confirm that the work area is clear of personnel before starting an autonomous mission. Firmware updates are staged to a canary group before fleet-wide rollout. Do not modify the rover chassis; unauthorised modifications void the warranty. The rover slows to 0.5 m/s when it detects a person within 2 metres. Configuration changes made on the rover are overwritten by Fleet Manager at

the next synchronisation. Payloads must be centred on the deck and secured with the supplied retention straps. The status light ring indicates the current operating mode; refer to the light codes table in the appendix.

7.6 Firmware updates are staged to a canary group before fleet-wide rollout. The rover slows to 0.5 m/s when it detects a person within 2 metres. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Operating temperature range is 0 to 45 degrees Celsius. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. Do not modify the rover chassis; unauthorised modifications void the warranty. Keep the charging dock free of debris and ensure the floor in front of it is level.

7.7 Keep the charging dock free of debris and ensure the floor in front of it is level. The rover slows to 0.5 m/s when it detects a person within 2 metres. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. Firmware updates are staged to a canary group before fleet-wide rollout. The status light ring indicates the current operating mode; refer to the light codes table in the appendix. Payloads must be centred on the deck and secured with the supplied retention straps. Operators must complete the Northwind certified operator course before using the rover in production.

7.8 Log every incident in Fleet Manager, including near misses, within the same shift. Firmware updates are staged to a canary group before fleet-wide rollout. Do not modify the rover chassis; unauthorised modifications void the warranty. Always confirm that the work area is clear of personnel before starting an autonomous mission. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Operators must complete the Northwind certified operator course before using the rover in production.

8. Status lights and sounds

8.1 Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Keep the charging dock free of debris and ensure the floor in front of it is level. Always confirm that the work area is clear of personnel before starting an autonomous mission. The status light ring indicates the current operating mode; refer to the light codes table in the appendix. Do not modify the rover chassis; unauthorised modifications void the warranty. Log every incident in Fleet Manager, including near misses, within the same shift.

8.2 If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Do not modify the rover chassis; unauthorised modifications void the warranty. The status light ring indicates the current operating mode; refer to the light codes table in the appendix. Keep the charging dock free of debris and ensure the floor in front of it is level. Payloads must be centred on the deck and secured with the supplied retention straps. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. Always confirm that the work area is clear of personnel before starting an autonomous mission.

8.3 Operating temperature range is 0 to 45 degrees Celsius. Always confirm that the work area is clear of personnel before starting an autonomous mission. Log every incident in Fleet Manager, including near misses, within the same shift. Firmware updates are staged to a canary group before fleet-wide rollout. The status light ring indicates the current operating mode; refer to the light codes table in the appendix. Do not modify the rover chassis; unauthorised modifications void the warranty. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor.

8.4 The status light ring indicates the current operating mode; refer to the light codes table in the appendix. Log every incident in Fleet Manager, including near misses, within the same shift. The rover

slows to 0.5 m/s when it detects a person within 2 metres. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Do not modify the rover chassis; unauthorised modifications void the warranty. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. Always confirm that the work area is clear of personnel before starting an autonomous mission.

8.5 Do not modify the rover chassis; unauthorised modifications void the warranty. Operating temperature range is 0 to 45 degrees Celsius. Always confirm that the work area is clear of personnel before starting an autonomous mission. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Operators must complete the Northwind certified operator course before using the rover in production. The status light ring indicates the current operating mode; refer to the light codes table in the appendix. Keep the charging dock free of debris and ensure the floor in front of it is level.

8.6 Firmware updates are staged to a canary group before fleet-wide rollout. Operating temperature range is 0 to 45 degrees Celsius. Operators must complete the Northwind certified operator course before using the rover in production. Log every incident in Fleet Manager, including near misses, within the same shift. Do not modify the rover chassis; unauthorised modifications void the warranty. Keep the charging dock free of debris and ensure the floor in front of it is level. The rover slows to 0.5 m/s when it detects a person within 2 metres.

8.7 Keep the charging dock free of debris and ensure the floor in front of it is level. The rover slows to 0.5 m/s when it detects a person within 2 metres. Always confirm that the work area is clear of personnel before starting an autonomous mission. Payloads must be centred on the deck and secured with the supplied retention straps. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. Operators must complete the Northwind certified operator course before using the rover in production. Log every incident in Fleet Manager, including near misses, within the same shift.

8.8 Keep the charging dock free of debris and ensure the floor in front of it is level. Operating temperature range is 0 to 45 degrees Celsius. Operators must complete the Northwind certified operator course before using the rover in production. The status light ring indicates the current operating mode; refer to the light codes table in the appendix. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Log every incident in Fleet Manager, including near misses, within the same shift. Always confirm that the work area is clear of personnel before starting an autonomous mission.

9. Emergency stop

9.1 Log every incident in Fleet Manager, including near misses, within the same shift. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Keep the charging dock free of debris and ensure the floor in front of it is level. Operating temperature range is 0 to 45 degrees Celsius. The status light ring indicates the current operating mode; refer to the light codes table in the appendix. Payloads must be centred on the deck and secured with the supplied retention straps. The rover slows to 0.5 m/s when it detects a person within 2 metres.

9.2 Resetting the emergency stop. To reset after an emergency stop, twist the red button clockwise to release it, then press and hold the blue RESUME button for 3 seconds. The rover waits 10 seconds, sounds two short tones, and only then resumes its mission.

9.3 Payloads must be centred on the deck and secured with the supplied retention straps. Firmware updates are staged to a canary group before fleet-wide rollout. Do not modify the rover chassis; unauthorised modifications void the warranty. Always confirm that the work area is clear of personnel before starting an autonomous mission. Keep the charging dock free of debris and ensure the floor in

front of it is level. Operators must complete the Northwind certified operator course before using the rover in production. Operating temperature range is 0 to 45 degrees Celsius.

9.4 The status light ring indicates the current operating mode; refer to the light codes table in the appendix. Log every incident in Fleet Manager, including near misses, within the same shift. Always confirm that the work area is clear of personnel before starting an autonomous mission. Keep the charging dock free of debris and ensure the floor in front of it is level. Operators must complete the Northwind certified operator course before using the rover in production. Do not modify the rover chassis; unauthorised modifications void the warranty. Firmware updates are staged to a canary group before fleet-wide rollout.

9.5 Keep the charging dock free of debris and ensure the floor in front of it is level. Always confirm that the work area is clear of personnel before starting an autonomous mission. Payloads must be centred on the deck and secured with the supplied retention straps. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. The status light ring indicates the current operating mode; refer to the light codes table in the appendix. Operators must complete the Northwind certified operator course before using the rover in production.

9.6 Firmware updates are staged to a canary group before fleet-wide rollout. Operators must complete the Northwind certified operator course before using the rover in production. Do not modify the rover chassis; unauthorised modifications void the warranty. The rover slows to 0.5 m/s when it detects a person within 2 metres. Log every incident in Fleet Manager, including near misses, within the same shift. The status light ring indicates the current operating mode; refer to the light codes table in the appendix. Keep the charging dock free of debris and ensure the floor in front of it is level.

9.7 The status light ring indicates the current operating mode; refer to the light codes table in the appendix. Operators must complete the Northwind certified operator course before using the rover in production. The rover slows to 0.5 m/s when it detects a person within 2 metres. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. Always confirm that the work area is clear of personnel before starting an autonomous mission. Firmware updates are staged to a canary group before fleet-wide rollout. Operating temperature range is 0 to 45 degrees Celsius.

9.8 Operators must complete the Northwind certified operator course before using the rover in production. The status light ring indicates the current operating mode; refer to the light codes table in the appendix. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. Keep the charging dock free of debris and ensure the floor in front of it is level. The rover slows to 0.5 m/s when it detects a person within 2 metres. Firmware updates are staged to a canary group before fleet-wide rollout. Always confirm that the work area is clear of personnel before starting an autonomous mission.

10. Battery care

10.1 Keep the charging dock free of debris and ensure the floor in front of it is level. Firmware updates are staged to a canary group before fleet-wide rollout. The rover slows to 0.5 m/s when it detects a person within 2 metres. The status light ring indicates the current operating mode; refer to the light codes table in the appendix. Operating temperature range is 0 to 45 degrees Celsius. Payloads must be centred on the deck and secured with the supplied retention straps. Operators must complete the Northwind certified operator course before using the rover in production.

10.2 Keep the charging dock free of debris and ensure the floor in front of it is level. Operators must complete the Northwind certified operator course before using the rover in production. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Payloads must be centred on the deck and secured with the supplied retention straps. Configuration changes made on the

rover are overwritten by Fleet Manager at the next synchronisation. Operating temperature range is 0 to 45 degrees Celsius. Firmware updates are staged to a canary group before fleet-wide rollout.

10.3 Storage. If a rover is stored for more than 30 days, charge the battery to between 50% and 60% first, and top it up every 3 months.

10.4 Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. Firmware updates are staged to a canary group before fleet-wide rollout. Always confirm that the work area is clear of personnel before starting an autonomous mission. Log every incident in Fleet Manager, including near misses, within the same shift. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Keep the charging dock free of debris and ensure the floor in front of it is level. Operating temperature range is 0 to 45 degrees Celsius.

10.5 The rover slows to 0.5 m/s when it detects a person within 2 metres. Keep the charging dock free of debris and ensure the floor in front of it is level. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. Payloads must be centred on the deck and secured with the supplied retention straps. Do not modify the rover chassis; unauthorised modifications void the warranty. Always confirm that the work area is clear of personnel before starting an autonomous mission. Firmware updates are staged to a canary group before fleet-wide rollout.

10.6 Operating temperature range is 0 to 45 degrees Celsius. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. The status light ring indicates the current operating mode; refer to the light codes table in the appendix. Log every incident in Fleet Manager, including near misses, within the same shift. Do not modify the rover chassis; unauthorised modifications void the warranty. Operators must complete the Northwind certified operator course before using the rover in production. Always confirm that the work area is clear of personnel before starting an autonomous mission.

10.7 Operators must complete the Northwind certified operator course before using the rover in production. Always confirm that the work area is clear of personnel before starting an autonomous mission. Keep the charging dock free of debris and ensure the floor in front of it is level. Log every incident in Fleet Manager, including near misses, within the same shift. The status light ring indicates the current operating mode; refer to the light codes table in the appendix. Operating temperature range is 0 to 45 degrees Celsius. The rover slows to 0.5 m/s when it detects a person within 2 metres.

10.8 If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Log every incident in Fleet Manager, including near misses, within the same shift. The rover slows to 0.5 m/s when it detects a person within 2 metres. Keep the charging dock free of debris and ensure the floor in front of it is level. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. Do not modify the rover chassis; unauthorised modifications void the warranty. The status light ring indicates the current operating mode; refer to the light codes table in the appendix.

11. Payload handling

11.1 Operators must complete the Northwind certified operator course before using the rover in production. Firmware updates are staged to a canary group before fleet-wide rollout. The status light ring indicates the current operating mode; refer to the light codes table in the appendix. Payloads must be centred on the deck and secured with the supplied retention straps. Keep the charging dock free of debris and ensure the floor in front of it is level. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. Operating temperature range is 0 to 45 degrees Celsius.

11.2 Keep the charging dock free of debris and ensure the floor in front of it is level. Do not modify the rover chassis; unauthorised modifications void the warranty. If the rover behaves unexpectedly, press

the emergency stop and contact your site supervisor. The rover slows to 0.5 m/s when it detects a person within 2 metres. Payloads must be centred on the deck and secured with the supplied retention straps. Always confirm that the work area is clear of personnel before starting an autonomous mission. Operators must complete the Northwind certified operator course before using the rover in production.

11.3 Keep the charging dock free of debris and ensure the floor in front of it is level. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. Do not modify the rover chassis; unauthorised modifications void the warranty. The status light ring indicates the current operating mode; refer to the light codes table in the appendix. Operators must complete the Northwind certified operator course before using the rover in production. The rover slows to 0.5 m/s when it detects a person within 2 metres. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor.

11.4 Always confirm that the work area is clear of personnel before starting an autonomous mission. Firmware updates are staged to a canary group before fleet-wide rollout. Keep the charging dock free of debris and ensure the floor in front of it is level. The rover slows to 0.5 m/s when it detects a person within 2 metres. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. Operating temperature range is 0 to 45 degrees Celsius. Payloads must be centred on the deck and secured with the supplied retention straps.

11.5 Operators must complete the Northwind certified operator course before using the rover in production. Always confirm that the work area is clear of personnel before starting an autonomous mission. Keep the charging dock free of debris and ensure the floor in front of it is level. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. The status light ring indicates the current operating mode; refer to the light codes table in the appendix. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. Payloads must be centred on the deck and secured with the supplied retention straps.

11.6 Operators must complete the Northwind certified operator course before using the rover in production. Log every incident in Fleet Manager, including near misses, within the same shift. Operating temperature range is 0 to 45 degrees Celsius. Keep the charging dock free of debris and ensure the floor in front of it is level. The rover slows to 0.5 m/s when it detects a person within 2 metres. Do not modify the rover chassis; unauthorised modifications void the warranty. Always confirm that the work area is clear of personnel before starting an autonomous mission.

11.7 Always confirm that the work area is clear of personnel before starting an autonomous mission. Payloads must be centred on the deck and secured with the supplied retention straps. The rover slows to 0.5 m/s when it detects a person within 2 metres. The status light ring indicates the current operating mode; refer to the light codes table in the appendix. Log every incident in Fleet Manager, including near misses, within the same shift. Firmware updates are staged to a canary group before fleet-wide rollout. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor.

11.8 Operating temperature range is 0 to 45 degrees Celsius. Firmware updates are staged to a canary group before fleet-wide rollout. The status light ring indicates the current operating mode; refer to the light codes table in the appendix. Keep the charging dock free of debris and ensure the floor in front of it is level. Payloads must be centred on the deck and secured with the supplied retention straps. Operators must complete the Northwind certified operator course before using the rover in production. Do not modify the rover chassis; unauthorised modifications void the warranty.

12. Wi-Fi and 5G connectivity

12.1 The rover slows to 0.5 m/s when it detects a person within 2 metres. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Log every incident in Fleet Manager, including near misses, within the same shift. Operating temperature range is 0 to 45 degrees

Celsius. The status light ring indicates the current operating mode; refer to the light codes table in the appendix. Keep the charging dock free of debris and ensure the floor in front of it is level. Payloads must be centred on the deck and secured with the supplied retention straps.

12.2 Payloads must be centred on the deck and secured with the supplied retention straps. Operators must complete the Northwind certified operator course before using the rover in production. Operating temperature range is 0 to 45 degrees Celsius. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. Always confirm that the work area is clear of personnel before starting an autonomous mission. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Log every incident in Fleet Manager, including near misses, within the same shift.

12.3 The status light ring indicates the current operating mode; refer to the light codes table in the appendix. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Do not modify the rover chassis; unauthorised modifications void the warranty. Always confirm that the work area is clear of personnel before starting an autonomous mission. Log every incident in Fleet Manager, including near misses, within the same shift. Firmware updates are staged to a canary group before fleet-wide rollout. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation.

12.4 The rover slows to 0.5 m/s when it detects a person within 2 metres. Operators must complete the Northwind certified operator course before using the rover in production. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Operating temperature range is 0 to 45 degrees Celsius. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. Firmware updates are staged to a canary group before fleet-wide rollout. The status light ring indicates the current operating mode; refer to the light codes table in the appendix.

12.5 Operators must complete the Northwind certified operator course before using the rover in production. Firmware updates are staged to a canary group before fleet-wide rollout. Always confirm that the work area is clear of personnel before starting an autonomous mission. The rover slows to 0.5 m/s when it detects a person within 2 metres. Payloads must be centred on the deck and secured with the supplied retention straps. Do not modify the rover chassis; unauthorised modifications void the warranty. Keep the charging dock free of debris and ensure the floor in front of it is level.

12.6 Always confirm that the work area is clear of personnel before starting an autonomous mission. Firmware updates are staged to a canary group before fleet-wide rollout. Keep the charging dock free of debris and ensure the floor in front of it is level. Operating temperature range is 0 to 45 degrees Celsius. Payloads must be centred on the deck and secured with the supplied retention straps. The rover slows to 0.5 m/s when it detects a person within 2 metres. Do not modify the rover chassis; unauthorised modifications void the warranty.

12.7 Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. Operating temperature range is 0 to 45 degrees Celsius. Firmware updates are staged to a canary group before fleet-wide rollout. Payloads must be centred on the deck and secured with the supplied retention straps. Log every incident in Fleet Manager, including near misses, within the same shift. Operators must complete the Northwind certified operator course before using the rover in production. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor.

12.8 If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Keep the charging dock free of debris and ensure the floor in front of it is level. Operators must complete the Northwind certified operator course before using the rover in production. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. Always confirm that the work area is clear of personnel before starting an autonomous mission. Operating temperature range is

0 to 45 degrees Celsius. Firmware updates are staged to a canary group before fleet-wide rollout.

13. Fleet Manager integration

13.1 Do not modify the rover chassis; unauthorised modifications void the warranty. Keep the charging dock free of debris and ensure the floor in front of it is level. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. The status light ring indicates the current operating mode; refer to the light codes table in the appendix. Operators must complete the Northwind certified operator course before using the rover in production. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. Firmware updates are staged to a canary group before fleet-wide rollout.

13.2 Firmware updates are staged to a canary group before fleet-wide rollout. Keep the charging dock free of debris and ensure the floor in front of it is level. Always confirm that the work area is clear of personnel before starting an autonomous mission. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. Operating temperature range is 0 to 45 degrees Celsius. The status light ring indicates the current operating mode; refer to the light codes table in the appendix. Do not modify the rover chassis; unauthorised modifications void the warranty.

13.3 The rover slows to 0.5 m/s when it detects a person within 2 metres. Keep the charging dock free of debris and ensure the floor in front of it is level. Firmware updates are staged to a canary group before fleet-wide rollout. Payloads must be centred on the deck and secured with the supplied retention straps. Operating temperature range is 0 to 45 degrees Celsius. Log every incident in Fleet Manager, including near misses, within the same shift. Operators must complete the Northwind certified operator course before using the rover in production.

13.4 The rover slows to 0.5 m/s when it detects a person within 2 metres. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. Keep the charging dock free of debris and ensure the floor in front of it is level. Always confirm that the work area is clear of personnel before starting an autonomous mission. Firmware updates are staged to a canary group before fleet-wide rollout. Operators must complete the Northwind certified operator course before using the rover in production. The status light ring indicates the current operating mode; refer to the light codes table in the appendix.

13.5 Firmware updates are staged to a canary group before fleet-wide rollout. Always confirm that the work area is clear of personnel before starting an autonomous mission. The rover slows to 0.5 m/s when it detects a person within 2 metres. Operating temperature range is 0 to 45 degrees Celsius. Keep the charging dock free of debris and ensure the floor in front of it is level. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor.

13.6 Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. Always confirm that the work area is clear of personnel before starting an autonomous mission. Payloads must be centred on the deck and secured with the supplied retention straps. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. The status light ring indicates the current operating mode; refer to the light codes table in the appendix. Do not modify the rover chassis; unauthorised modifications void the warranty. Keep the charging dock free of debris and ensure the floor in front of it is level.

13.7 Keep the charging dock free of debris and ensure the floor in front of it is level. Do not modify the rover chassis; unauthorised modifications void the warranty. The status light ring indicates the current operating mode; refer to the light codes table in the appendix. The rover slows to 0.5 m/s when it detects a person within 2 metres. Operating temperature range is 0 to 45 degrees Celsius. Operators must complete the Northwind certified operator course before using the rover in production. If the rover

behaves unexpectedly, press the emergency stop and contact your site supervisor.

13.8 Do not modify the rover chassis; unauthorised modifications void the warranty. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. Firmware updates are staged to a canary group before fleet-wide rollout. Payloads must be centred on the deck and secured with the supplied retention straps. Log every incident in Fleet Manager, including near misses, within the same shift. Operators must complete the Northwind certified operator course before using the rover in production. Always confirm that the work area is clear of personnel before starting an autonomous mission.

14. Floors, ramps and thresholds

14.1 Operators must complete the Northwind certified operator course before using the rover in production. Firmware updates are staged to a canary group before fleet-wide rollout. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Log every incident in Fleet Manager, including near misses, within the same shift. Keep the charging dock free of debris and ensure the floor in front of it is level. Do not modify the rover chassis; unauthorised modifications void the warranty. Always confirm that the work area is clear of personnel before starting an autonomous mission.

14.2 Log every incident in Fleet Manager, including near misses, within the same shift. Do not modify the rover chassis; unauthorised modifications void the warranty. Operating temperature range is 0 to 45 degrees Celsius. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Always confirm that the work area is clear of personnel before starting an autonomous mission. Payloads must be centred on the deck and secured with the supplied retention straps. The status light ring indicates the current operating mode; refer to the light codes table in the appendix.

14.3 Ramps. The maximum ramp incline is 5 degrees when loaded and 8 degrees when unloaded. Every ramp must have a flat landing of at least 1.2 m at the top and bottom. Ramps steeper than these limits must be excluded from routes in Fleet Manager.

14.4 Thresholds. The R3 can cross thresholds up to 2 cm high and floor gaps up to 4 cm wide at reduced speed.

14.5 Operators must complete the Northwind certified operator course before using the rover in production. Do not modify the rover chassis; unauthorised modifications void the warranty. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Log every incident in Fleet Manager, including near misses, within the same shift. Always confirm that the work area is clear of personnel before starting an autonomous mission. Firmware updates are staged to a canary group before fleet-wide rollout. Payloads must be centred on the deck and secured with the supplied retention straps.

14.6 Operators must complete the Northwind certified operator course before using the rover in production. Keep the charging dock free of debris and ensure the floor in front of it is level. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Do not modify the rover chassis; unauthorised modifications void the warranty. Always confirm that the work area is clear of personnel before starting an autonomous mission. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. Log every incident in Fleet Manager, including near misses, within the same shift.

14.7 Payloads must be centred on the deck and secured with the supplied retention straps. Always confirm that the work area is clear of personnel before starting an autonomous mission. Do not modify the rover chassis; unauthorised modifications void the warranty. Log every incident in Fleet Manager, including near misses, within the same shift. Keep the charging dock free of debris and ensure the floor

in front of it is level. The rover slows to 0.5 m/s when it detects a person within 2 metres. Operators must complete the Northwind certified operator course before using the rover in production.

14.8 Keep the charging dock free of debris and ensure the floor in front of it is level. Always confirm that the work area is clear of personnel before starting an autonomous mission. Operators must complete the Northwind certified operator course before using the rover in production. Operating temperature range is 0 to 45 degrees Celsius. The status light ring indicates the current operating mode; refer to the light codes table in the appendix. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Firmware updates are staged to a canary group before fleet-wide rollout.

15. Outdoor loading docks

15.1 Log every incident in Fleet Manager, including near misses, within the same shift. The rover slows to 0.5 m/s when it detects a person within 2 metres. Do not modify the rover chassis; unauthorised modifications void the warranty. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. Payloads must be centred on the deck and secured with the supplied retention straps. Operating temperature range is 0 to 45 degrees Celsius. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor.

15.2 Weather limits on loading docks. Outdoor dock operation is permitted only under cover, in light rain, and at temperatures between 0 and 40 degrees Celsius. Suspend outdoor missions when standing water is present.

15.3 Operators must complete the Northwind certified operator course before using the rover in production. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Log every incident in Fleet Manager, including near misses, within the same shift. The rover slows to 0.5 m/s when it detects a person within 2 metres. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. Do not modify the rover chassis; unauthorised modifications void the warranty. Operating temperature range is 0 to 45 degrees Celsius.

15.4 Operators must complete the Northwind certified operator course before using the rover in production. Log every incident in Fleet Manager, including near misses, within the same shift. Firmware updates are staged to a canary group before fleet-wide rollout. The status light ring indicates the current operating mode; refer to the light codes table in the appendix. Keep the charging dock free of debris and ensure the floor in front of it is level. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. Operating temperature range is 0 to 45 degrees Celsius.

15.5 The rover slows to 0.5 m/s when it detects a person within 2 metres. The status light ring indicates the current operating mode; refer to the light codes table in the appendix. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Firmware updates are staged to a canary group before fleet-wide rollout. Log every incident in Fleet Manager, including near misses, within the same shift. Payloads must be centred on the deck and secured with the supplied retention straps. Operating temperature range is 0 to 45 degrees Celsius.

15.6 Keep the charging dock free of debris and ensure the floor in front of it is level. Operating temperature range is 0 to 45 degrees Celsius. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Log every incident in Fleet Manager, including near misses, within the same shift. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. The status light ring indicates the current operating mode; refer to the light codes table in the appendix. Firmware updates are staged to a canary group before fleet-wide rollout.

15.7 The rover slows to 0.5 m/s when it detects a person within 2 metres. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Log every incident in Fleet Manager, including near misses, within the same shift. Always confirm that the work area is clear of

personnel before starting an autonomous mission. The status light ring indicates the current operating mode; refer to the light codes table in the appendix. Do not modify the rover chassis; unauthorised modifications void the warranty. Operating temperature range is 0 to 45 degrees Celsius.

15.8 Always confirm that the work area is clear of personnel before starting an autonomous mission. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. The rover slows to 0.5 m/s when it detects a person within 2 metres. Firmware updates are staged to a canary group before fleet-wide rollout. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Payloads must be centred on the deck and secured with the supplied retention straps. The status light ring indicates the current operating mode; refer to the light codes table in the appendix.

16. Software updates

16.1 Firmware updates are staged to a canary group before fleet-wide rollout. Log every incident in Fleet Manager, including near misses, within the same shift. The status light ring indicates the current operating mode; refer to the light codes table in the appendix. The rover slows to 0.5 m/s when it detects a person within 2 metres. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. Always confirm that the work area is clear of personnel before starting an autonomous mission. Operators must complete the Northwind certified operator course before using the rover in production.

16.2 The status light ring indicates the current operating mode; refer to the light codes table in the appendix. Do not modify the rover chassis; unauthorised modifications void the warranty. The rover slows to 0.5 m/s when it detects a person within 2 metres. Always confirm that the work area is clear of personnel before starting an autonomous mission. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Payloads must be centred on the deck and secured with the supplied retention straps. Operating temperature range is 0 to 45 degrees Celsius.

16.3 Keep the charging dock free of debris and ensure the floor in front of it is level. Payloads must be centred on the deck and secured with the supplied retention straps. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. Operators must complete the Northwind certified operator course before using the rover in production. Log every incident in Fleet Manager, including near misses, within the same shift. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Firmware updates are staged to a canary group before fleet-wide rollout.

16.4 Operating temperature range is 0 to 45 degrees Celsius. The rover slows to 0.5 m/s when it detects a person within 2 metres. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. Log every incident in Fleet Manager, including near misses, within the same shift. Keep the charging dock free of debris and ensure the floor in front of it is level. The status light ring indicates the current operating mode; refer to the light codes table in the appendix. Operators must complete the Northwind certified operator course before using the rover in production.

16.5 Firmware updates are staged to a canary group before fleet-wide rollout. Keep the charging dock free of debris and ensure the floor in front of it is level. Payloads must be centred on the deck and secured with the supplied retention straps. Do not modify the rover chassis; unauthorised modifications void the warranty. The status light ring indicates the current operating mode; refer to the light codes table in the appendix. The rover slows to 0.5 m/s when it detects a person within 2 metres. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor.

16.6 The rover slows to 0.5 m/s when it detects a person within 2 metres. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. Always confirm that the work

area is clear of personnel before starting an autonomous mission. Keep the charging dock free of debris and ensure the floor in front of it is level. Operating temperature range is 0 to 45 degrees Celsius. Payloads must be centred on the deck and secured with the supplied retention straps.

16.7 Log every incident in Fleet Manager, including near misses, within the same shift. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Firmware updates are staged to a canary group before fleet-wide rollout. Operating temperature range is 0 to 45 degrees Celsius. Keep the charging dock free of debris and ensure the floor in front of it is level. The rover slows to 0.5 m/s when it detects a person within 2 metres. Operators must complete the Northwind certified operator course before using the rover in production.

16.8 The status light ring indicates the current operating mode; refer to the light codes table in the appendix. Operators must complete the Northwind certified operator course before using the rover in production. Log every incident in Fleet Manager, including near misses, within the same shift. Firmware updates are staged to a canary group before fleet-wide rollout. The rover slows to 0.5 m/s when it detects a person within 2 metres. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Payloads must be centred on the deck and secured with the supplied retention straps.

17. Routine maintenance

17.1 Maintenance intervals. Inspect the drive wheels every 500 operating hours. Clean the LiDAR window weekly with a lint-free cloth. Replace the bumper ring every 2 years.

17.2 Log every incident in Fleet Manager, including near misses, within the same shift. The rover slows to 0.5 m/s when it detects a person within 2 metres. Firmware updates are staged to a canary group before fleet-wide rollout. Payloads must be centred on the deck and secured with the supplied retention straps. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. Operating temperature range is 0 to 45 degrees Celsius. Operators must complete the Northwind certified operator course before using the rover in production.

17.3 Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. The status light ring indicates the current operating mode; refer to the light codes table in the appendix. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. The rover slows to 0.5 m/s when it detects a person within 2 metres. Always confirm that the work area is clear of personnel before starting an autonomous mission. Log every incident in Fleet Manager, including near misses, within the same shift. Do not modify the rover chassis; unauthorised modifications void the warranty.

17.4 Operating temperature range is 0 to 45 degrees Celsius. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Firmware updates are staged to a canary group before fleet-wide rollout. Always confirm that the work area is clear of personnel before starting an autonomous mission. Operators must complete the Northwind certified operator course before using the rover in production. Payloads must be centred on the deck and secured with the supplied retention straps. The rover slows to 0.5 m/s when it detects a person within 2 metres.

17.5 Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. Payloads must be centred on the deck and secured with the supplied retention straps. Operators must complete the Northwind certified operator course before using the rover in production. Keep the charging dock free of debris and ensure the floor in front of it is level. The status light ring indicates the current operating mode; refer to the light codes table in the appendix. Do not modify the rover chassis; unauthorised modifications void the warranty. Firmware updates are staged to a canary group before fleet-wide rollout.

17.6 The rover slows to 0.5 m/s when it detects a person within 2 metres. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Log every incident in Fleet Manager, including near misses, within the same shift. Always confirm that the work area is clear of personnel before starting an autonomous mission. Operating temperature range is 0 to 45 degrees Celsius. Operators must complete the Northwind certified operator course before using the rover in production. The status light ring indicates the current operating mode; refer to the light codes table in the appendix.

17.7 The rover slows to 0.5 m/s when it detects a person within 2 metres. Payloads must be centred on the deck and secured with the supplied retention straps. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. Log every incident in Fleet Manager, including near misses, within the same shift. Keep the charging dock free of debris and ensure the floor in front of it is level. Always confirm that the work area is clear of personnel before starting an autonomous mission. Firmware updates are staged to a canary group before fleet-wide rollout.

17.8 Operators must complete the Northwind certified operator course before using the rover in production. Operating temperature range is 0 to 45 degrees Celsius. The rover slows to 0.5 m/s when it detects a person within 2 metres. Keep the charging dock free of debris and ensure the floor in front of it is level. Firmware updates are staged to a canary group before fleet-wide rollout. The status light ring indicates the current operating mode; refer to the light codes table in the appendix. Log every incident in Fleet Manager, including near misses, within the same shift.

18. Troubleshooting

18.1 If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. Firmware updates are staged to a canary group before fleet-wide rollout. The rover slows to 0.5 m/s when it detects a person within 2 metres. Operating temperature range is 0 to 45 degrees Celsius. Keep the charging dock free of debris and ensure the floor in front of it is level. Always confirm that the work area is clear of personnel before starting an autonomous mission.

18.2 Operators must complete the Northwind certified operator course before using the rover in production. Log every incident in Fleet Manager, including near misses, within the same shift. Keep the charging dock free of debris and ensure the floor in front of it is level. Operating temperature range is 0 to 45 degrees Celsius. The rover slows to 0.5 m/s when it detects a person within 2 metres. Always confirm that the work area is clear of personnel before starting an autonomous mission. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation.

18.3 If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Operating temperature range is 0 to 45 degrees Celsius. Log every incident in Fleet Manager, including near misses, within the same shift. Always confirm that the work area is clear of personnel before starting an autonomous mission. Keep the charging dock free of debris and ensure the floor in front of it is level. The rover slows to 0.5 m/s when it detects a person within 2 metres. Do not modify the rover chassis; unauthorised modifications void the warranty.

18.4 Log every incident in Fleet Manager, including near misses, within the same shift. Do not modify the rover chassis; unauthorised modifications void the warranty. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. Firmware updates are staged to a canary group before fleet-wide rollout. Operators must complete the Northwind certified operator course before using the rover in production. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. The status light ring indicates the current operating mode; refer to the light codes table in the appendix.

18.5 Operating temperature range is 0 to 45 degrees Celsius. Log every incident in Fleet Manager,

including near misses, within the same shift. Do not modify the rover chassis; unauthorised modifications void the warranty. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. Operators must complete the Northwind certified operator course before using the rover in production. The status light ring indicates the current operating mode; refer to the light codes table in the appendix.

18.6 Operating temperature range is 0 to 45 degrees Celsius. The rover slows to 0.5 m/s when it detects a person within 2 metres. Always confirm that the work area is clear of personnel before starting an autonomous mission. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. Firmware updates are staged to a canary group before fleet-wide rollout. Payloads must be centred on the deck and secured with the supplied retention straps. The status light ring indicates the current operating mode; refer to the light codes table in the appendix.

18.7 Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. Operating temperature range is 0 to 45 degrees Celsius. Firmware updates are staged to a canary group before fleet-wide rollout. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Keep the charging dock free of debris and ensure the floor in front of it is level. Log every incident in Fleet Manager, including near misses, within the same shift. The status light ring indicates the current operating mode; refer to the light codes table in the appendix.

18.8 Always confirm that the work area is clear of personnel before starting an autonomous mission. Payloads must be centred on the deck and secured with the supplied retention straps. Firmware updates are staged to a canary group before fleet-wide rollout. The status light ring indicates the current operating mode; refer to the light codes table in the appendix. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Log every incident in Fleet Manager, including near misses, within the same shift.

19. Decommissioning

19.1 If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Operators must complete the Northwind certified operator course before using the rover in production. Payloads must be centred on the deck and secured with the supplied retention straps. The status light ring indicates the current operating mode; refer to the light codes table in the appendix. Log every incident in Fleet Manager, including near misses, within the same shift. Operating temperature range is 0 to 45 degrees Celsius. Always confirm that the work area is clear of personnel before starting an autonomous mission.

19.2 Operators must complete the Northwind certified operator course before using the rover in production. Payloads must be centred on the deck and secured with the supplied retention straps. The status light ring indicates the current operating mode; refer to the light codes table in the appendix. Log every incident in Fleet Manager, including near misses, within the same shift. Operating temperature range is 0 to 45 degrees Celsius. Do not modify the rover chassis; unauthorised modifications void the warranty. Firmware updates are staged to a canary group before fleet-wide rollout.

19.3 The status light ring indicates the current operating mode; refer to the light codes table in the appendix. Log every incident in Fleet Manager, including near misses, within the same shift. Firmware updates are staged to a canary group before fleet-wide rollout. Do not modify the rover chassis; unauthorised modifications void the warranty. Always confirm that the work area is clear of personnel before starting an autonomous mission. Operators must complete the Northwind certified operator course before using the rover in production. Payloads must be centred on the deck and secured with the supplied retention straps.

19.4 Do not modify the rover chassis; unauthorised modifications void the warranty. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. The status light ring indicates the current operating mode; refer to the light codes table in the appendix. The rover slows to 0.5 m/s when it detects a person within 2 metres. Firmware updates are staged to a canary group before fleet-wide rollout. Operators must complete the Northwind certified operator course before using the rover in production. Payloads must be centred on the deck and secured with the supplied retention straps.

19.5 If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Log every incident in Fleet Manager, including near misses, within the same shift. Do not modify the rover chassis; unauthorised modifications void the warranty. Payloads must be centred on the deck and secured with the supplied retention straps. Firmware updates are staged to a canary group before fleet-wide rollout. Always confirm that the work area is clear of personnel before starting an autonomous mission. Operators must complete the Northwind certified operator course before using the rover in production.

19.6 Operators must complete the Northwind certified operator course before using the rover in production. Always confirm that the work area is clear of personnel before starting an autonomous mission. Keep the charging dock free of debris and ensure the floor in front of it is level. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Do not modify the rover chassis; unauthorised modifications void the warranty. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. Operating temperature range is 0 to 45 degrees Celsius.

19.7 The rover slows to 0.5 m/s when it detects a person within 2 metres. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. Log every incident in Fleet Manager, including near misses, within the same shift. Do not modify the rover chassis; unauthorised modifications void the warranty. Keep the charging dock free of debris and ensure the floor in front of it is level. Payloads must be centred on the deck and secured with the supplied retention straps. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor.

19.8 Always confirm that the work area is clear of personnel before starting an autonomous mission. Operators must complete the Northwind certified operator course before using the rover in production. Firmware updates are staged to a canary group before fleet-wide rollout. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. Do not modify the rover chassis; unauthorised modifications void the warranty. Keep the charging dock free of debris and ensure the floor in front of it is level. The rover slows to 0.5 m/s when it detects a person within 2 metres.

20. Warranty and support

20.1 Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. Do not modify the rover chassis; unauthorised modifications void the warranty. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Firmware updates are staged to a canary group before fleet-wide rollout. Operators must complete the Northwind certified operator course before using the rover in production. Payloads must be centred on the deck and secured with the supplied retention straps. Operating temperature range is 0 to 45 degrees Celsius.

20.2 Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Log every incident in Fleet Manager, including near misses, within the same shift. Operators must complete the Northwind certified operator course before using the rover in production. Payloads must be centred on the deck and secured with the supplied retention straps. The rover slows to 0.5 m/s when it detects a person within 2 metres. Operating temperature range is 0 to 45 degrees Celsius.

20.3 Always confirm that the work area is clear of personnel before starting an autonomous mission. Operators must complete the Northwind certified operator course before using the rover in production. Keep the charging dock free of debris and ensure the floor in front of it is level. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. Operating temperature range is 0 to 45 degrees Celsius. Payloads must be centred on the deck and secured with the supplied retention straps. The status light ring indicates the current operating mode; refer to the light codes table in the appendix.

20.4 Do not modify the rover chassis; unauthorised modifications void the warranty. Keep the charging dock free of debris and ensure the floor in front of it is level. Operating temperature range is 0 to 45 degrees Celsius. Operators must complete the Northwind certified operator course before using the rover in production. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Payloads must be centred on the deck and secured with the supplied retention straps. Log every incident in Fleet Manager, including near misses, within the same shift.

20.5 Operating temperature range is 0 to 45 degrees Celsius. Do not modify the rover chassis; unauthorised modifications void the warranty. Keep the charging dock free of debris and ensure the floor in front of it is level. Payloads must be centred on the deck and secured with the supplied retention straps. Operators must complete the Northwind certified operator course before using the rover in production. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. The rover slows to 0.5 m/s when it detects a person within 2 metres.

20.6 If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Always confirm that the work area is clear of personnel before starting an autonomous mission. Operators must complete the Northwind certified operator course before using the rover in production. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. Operating temperature range is 0 to 45 degrees Celsius. The rover slows to 0.5 m/s when it detects a person within 2 metres. Do not modify the rover chassis; unauthorised modifications void the warranty.

20.7 Firmware updates are staged to a canary group before fleet-wide rollout. Log every incident in Fleet Manager, including near misses, within the same shift. Keep the charging dock free of debris and ensure the floor in front of it is level. If the rover behaves unexpectedly, press the emergency stop and contact your site supervisor. Operating temperature range is 0 to 45 degrees Celsius. Always confirm that the work area is clear of personnel before starting an autonomous mission. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation.

20.8 The status light ring indicates the current operating mode; refer to the light codes table in the appendix. Operators must complete the Northwind certified operator course before using the rover in production. Keep the charging dock free of debris and ensure the floor in front of it is level. Operating temperature range is 0 to 45 degrees Celsius. Configuration changes made on the rover are overwritten by Fleet Manager at the next synchronisation. The rover slows to 0.5 m/s when it detects a person within 2 metres. Log every incident in Fleet Manager, including near misses, within the same shift.