

Data Science & Machine Learning



Eman Raslan  



Course Schedule

Week #	Day1	Day2
1	24-Nov-2023	
2	1-Dec-2023	2-Dec-2023
3	8-Dec-2023	9-Dec-2023
4	15-Dec-2023	16-Dec-2023
5	22-Dec-2023	23-Dec-2023
6	29-Dec-2023	30-Dec-2023
7	5-Jan-2023	6-Jan-2023
8	12-Jan-2023	13-Jan-2023
	19-Jan-2023	
Project		

Course Agenda



Python Basics

Agenda

- Data types
- Arithmetic operations
- Assignment operators
- Input Function
- Print formatting
- Flow Control
- Comparison and Logical operators
- Range Function
- Break, continue and pass
- Nested Statements and Scope
- Functions
- classes
- Reading, writing and append to files
- Errors and Exception Handling
- Lambda, Map, and filter functions
- List comprehension
- NumPy module
- Pandas module

Data Types

Name	Type	Description	Example
Integers	Int	Whole numbers	3 300 200 -2
Floats	Float	Numbers with decimal point	2.3 4.0 -5.3
Strings	Str	Ordered sequence of characters	“hello” ‘Eman’ “2000”
Lists	List	Ordered sequence of objects	[10,”omar”,2.33]
Dictionaries	dict	Unordered Key:Value pairs	{"key1":"value1", "key2":"value2"}
Tuples	Tup	Ordered immutable sequence of objects	(“hello”,4.4,200)
Sets	Set	Unordered collection of unique objects	{“a”,3000}
Booleans	bool	Logical value indicating True or False	True False

Arithmetic Operators

- + (Addition)
- (Subtraction)
- * (Multiplication)
- / (Division)
- // (Floor division)
- % (Modulus)
- ** (Exponentiation)

Variable declaration

Rules for variable names


- names can not start with a **number**
- names can not contain **spaces**, use `_` instead
- names can not contain any of these symbols:
`:'"<>/?|\\!@#%^&*~-+`
- avoid using Python built-in **keywords** like `'list'` and `'str'`
- avoid using the single characters `'l'` (lowercase letter el), `'O'` (uppercase letter oh) and `'I'` (uppercase letter eye) as they can be confused with `'1'` and `'0'`.

Assignment operators

Operator	Meaning	Equivalent
= (Assign)	a=5 Assign 5 to variable a	a = 5
+= (Add and assign)	a+=5 Add 5 to a and assign it as a new value to a	a = a+5
-= (Subtract and assign)	a-=5 Subtract 5 from variable a and assign it as a new value to a	a = a-5
= (Multiply and assign)	a=5 Multiply variable a by 5 and assign it as a new value to a	a = a*5
/= (Divide and assign)	a/=5 Divide variable a by 5 and assign a new value to a	a = a/5
%= (Modulus and assign)	a%=5 Performs modulus on two values and assigns it as a new value to a	a = a%5
= (Exponentiation and assign)	a=5 Multiply a five times and assigns the result to a	a = a**5
//= (Floor-divide and assign)	a//=5 Floor-divide a by 5 and assigns the result to a	a = a//5

Input

Python Input() function



Strings

STRING = "AASHINA"

REVERSE INDEX

-7	-6	-5	-4	-3	-2	-1
0	1	2	3	4	5	6
A	A	S	H	I	N	A

FORWARD INDEX

STRING[0] = 'A'

STRING[1] = 'A'

STRING[2] = 'S'

STRING[3] = 'H'

STRING[4] = 'I'

STRING[5] = 'N'

STRING[6] = 'A'

STRING[-7] = 'A'

STRING[-6] = 'A'

STRING[-5] = 'S'

STRING[-4] = 'H'

STRING[-3] = 'I'

STRING[-2] = 'N'

STRING[-1] = 'A'

Lists

```
L = [ 20, 'Jessa', 35.75, [30, 60, 90] ]  
      ↑   ↑   ↑   ↑  
L[0] L[1] L[2] L[3]
```

- ✓ **Ordered:** Maintain the order of the data insertion.
- ✓ **Changeable:** List is mutable and we can modify items.
- ✓ **Heterogeneous:** List can contain data of different types
- ✓ **Contains duplicate:** Allows duplicates data

List Operations

Operation	Description
<code>x in l1</code>	Check if the list <code>l1</code> contains item <code>x</code> .
<code>x not in l2</code>	Check if list <code>l1</code> does not contain item <code>x</code> .
<code>l1 + l2</code>	Concatenate the lists <code>l1</code> and <code>l2</code> . Creates a new list containing the items from <code>l1</code> and <code>l2</code> .
<code>l1 * 5</code>	Repeat the list <code>l1</code> 5 times.
<code>l1[i]</code>	Get the item at index <code>i</code> .
<code>l1[i:j]</code>	List slicing. Get the items from index <code>i</code> up to index <code>j</code> (excluding <code>j</code>) as a List.
<code>l1[i:j:k]</code>	List slicing with step. Returns a List with the items from index <code>i</code> up to index <code>j</code> taking every <code>k</code> -th item.
<code>len(l1)</code>	Returns a count of total items in a list.
<code>l2.count(60)</code>	Returns the number of times a particular item (60) appears in a list..

List Operations

Operation	Description
l1.index(30)	Returns the index number of a particular item (30) in a list.
l1.index(30, 2, 5)	Returns the index number of a particular item (30) in a list. But search Returns the item with maximum value from a list.
min(l1)	Returns the item with a minimum value from a list.
max(l1)	Returns the item with maximum value from a list.
l1.append(100)	Add item at the end of the list
l1.append([2, 5, 7])	Append the nested list at the end
l1[2] = 40	Modify the item present at index 2
l1.remove(40)	Removes the first occurrence of item 40 from the list.
pop(2)	Removes and returns the item at index 2 from the list.
l1.clear()	Make list empty
l3= l1.copy()	Copy l1 into l2

Tuples

$$T = (20, \text{'Jessa'}, 35.75, [30, 60, 90])$$

↑ ↑ ↑ ↑
T[0] T[1] T[2] T[3]

- ✓ **Ordered:** Maintain the order of the data insertion.
- ✓ **Unchangeable:** Tuples are immutable and we can't modify items.
- ✓ **Heterogeneous:** Tuples can contain data of types
- ✓ **Contains duplicate:** Allows duplicates data


Tuples operations

Operation	Description
x in t1	Check if the tuple t1 contains the item x.
x not in t2	Check if the tuple t1 does not contain the item x.
t1 + t2	Concatenate the tuples t1 and t2. Creates a new tuple containing the items from t1 and t2.
t1 * 5	Repeat the tuple t1 5 times.
t1[i]	Get the item at the index i.
t1[i:j]	Tuple slicing. Get the items from index i up to index j (excluding j) as a tuple.
t1[i:j:k]	Tuple slicing with step. Return a tuple with the items from index i up to index j taking every k-th item.
len(t1)	Returns a count of total items in a tuple
t2.count(60)	Returns the number of times a particular item (60) appears in a tuple.
t1.index(30)	Returns the index number of a particular item(30) in a tuple.
t1.index(40, 2, 5)	Returns the index number of a particular item(30) in a tuple. But search only from index number 2 to 5.
min(t1)	Returns the item with a minimum value from a tuple
max(t1)	Returns the item with maximum value from a tuple

Dictionary

Unordered collections of unique values stored in (Key-Value) pairs.

`d = {'a': 10, 'b': 20, 'c': 30}`



- ✓ **Unordered:** The items in dict are stored without any index value
- ✓ **Unique:** Keys in dictionaries should be Unique
- ✓ **Mutable:** We can add/Modify/Remove key-value after the creation

Dictionary Operations

Operations	Description
dict({'a': 10, 'b': 20})	Create a dictionary using a dict() constructor.
d2 = {}	Create an empty dictionary.
d1.get('a')	Retrieve value using the key name a.
d1.keys()	Returns a list of keys present in the dictionary.
d1.values()	Returns a list with all the values in the dictionary.
d1.items()	Returns a list of all the items in the dictionary with each key-value pair inside a tuple.
len(d1)	Returns number of items in a dictionary.
d1['d'] = 40	Update dictionary by adding a new key.
d1.update({'e': 50, 'f': 60})	Add multiple keys to the dictionary.
d1.setdefault('g', 70)	Set the default value if a key doesn't exist.
d1['b'] = 100	Modify the values of the existing key.
d1.pop('b')	Remove the key b from the dictionary.
d1.popitem()	Remove any random item from a dictionary.
d1.clear()	Removes all items from the dictionary.
'key' in d1.keys()	Check if a key exists in a dictionary.
d1.update(d2)	Add all items of dictionary d2 into d1.
d3= **d1, **d2}	Join two dictionaries.
d2 = d1.copy()	Copy dictionary d1 into d2.
max(d1)	Returns the key with the maximum value in the dictionary d1
min(d1)	Returns the key with the minimum value in the dictionary d1

Set

S = { 20, 'Jessa', 35.75}

- ✓ **Unordered**: Set doesn't maintain the order of the data insertion.
- ✓ **Unchangeable**: Set are immutable and we can't modify items.
- ✓ **Heterogeneous**: Set can contains data of all types
- ✓ **Unique**: Set doesn't allows duplicates items


Set Operations

Operation	Equivalent	Result
<code>len(s)</code>		number of elements in set <code>s</code> (cardinality)
<code>x in s</code>		test <code>x</code> for membership in <code>s</code>
<code>x not in s</code>		test <code>x</code> for non-membership in <code>s</code>
<code>s.issubset(t)</code>	<code>s <= t</code>	test whether every element in <code>s</code> is in <code>t</code>
<code>s.issuperset(t)</code>	<code>s >= t</code>	test whether every element in <code>t</code> is in <code>s</code>
<code>s.union(t)</code>	<code>s t</code>	new set with elements from both <code>s</code> and <code>t</code>
<code>s.intersection(t)</code>	<code>s & t</code>	new set with elements common to <code>s</code> and <code>t</code>
<code>s.difference(t)</code>	<code>s - t</code>	new set with elements in <code>s</code> but not in <code>t</code>
<code>s.symmetric_difference(t)</code>	<code>s ^ t</code>	new set with elements in either <code>s</code> or <code>t</code> but not both
<code>s.copy()</code>		new set with a shallow copy of <code>s</code>


Recap

String	List	Tuple	Set	Dictionary
Immutable	Mutable	Immutable	Mutable	Mutable
Ordered/ Indexed	Ordered/ Indexed	Ordered/ Indexed	Unordered	Unordered
Allows Duplicate Members	Allow Duplicate Members	Allow Duplicate Members	Doesn't allow Duplicate Members	Doesn't allow Duplicate keys
Empty string = ""	Empty list = []	Empty tuple = ()	Empty set = <code>set()</code>	Empty dictionary = {}
String with single element = "H"	List with single item = ["Hello"]	Tuple with single item = ("Hello")	Set with single item = {"Hello"}	Dictionary with single item = {"Hello":1}
	It can store any data types str, list, set, tuple, int and dictionary	It can store any data types str, list, set, tuple, int and dictionary.	It can store data types (int, str, tuple) but not (list, set, dictionary)	Inside of dictionary key can be int, str, and tuple only values can be of any data type int, str, list, set and dictionary.

Flow Control



if, elif, and else Statements




Relational (comparison) operators

Operator	Description	Example
> (Greater than)	It returns True if the left operand is greater than the right	$x > y$ result is True
< (Less than)	It returns True if the left operand is less than the right	$x < y$ result is False
== (Equal to)	It returns True if both operands are equal	$x == y$ result is False
!= (Not equal to)	It returns True if both operands are equal	$x != y$ result is True
>= (Greater than or equal to)	It returns True if the left operand is greater than or equal to the right	$x >= y$ result is True
<= (Less than or equal to)	It returns True if the left operand is less than or equal to the right	$x <= y$ result is False


Logical operators

Operator	Description	Example
and (Logical and)	True if both the operands are True	a and b
or (Logical or)	True if either of the operands is True	a or b
not (Logical not)	True if the operand is False	not a


For Loops



While Loops



Range Function



How to use Python `range(start, stop, step)`

`range()` returns the immutable sequence of numbers starting from the given **start integer** to the **stop-step**. Each number is incremented by adding step value to its preceding number

`range(0, 6, 1)` →

0	1	2	3	4	5
---	---	---	---	---	---

Step. (Optional) Specify the increment.
Default is 1

Stop. (Required) specifying at which position to stop. Not part of the result

Start. (Optional) Start number of sequence. Default is 0

```
for i in range(6):  
    print(i)
```

It returns a range object not list
`type(range(6))` -> class 'range'

Reverse range/ Decrementing

- The diagram illustrates two examples of the range function:

 - Example 1: range(5, -1, -1) results in a list [5, 4, 3, 2, 1, 0].
 - Example 2: reversed(range(6)) results in a list [5, 4, 3, 2, 1, 0].

Both examples point to the same visual representation of the list [5, 4, 3, 2, 1, 0].

List from range `x = list(range(6))` → `0 1 2 3 4 5`

range(-1, -11, -1)

Negative range from -1 to -10

`range(start, stop+step, step)`

Generate an inclusive range

range(0, 10)[5]

Access 5th number of a range()

```
range(10)[3:8]
```

Slice a range to from index 3 to 8

`range(5).start`, `range(5).stop`

Access range() attributes

Range Function

```
>>> # One parameter          >>> # Two parameters        >>> # Three parameters      >>> # Going backwards
>>> for i in range(5):       >>> for i in range(3, 6):     >>> for i in range(4, 10, 2): >>> for i in range(0, -10, -2):
...     print(i)              ...     print(i)                 ...     print(i)                  ...
...                               ...
...                               ...
...                               ...
0                                3                                4                                0
1                                4                                6                                -2
2                                5                                8                                -4
3
4
```

Break, Continue, and Pass

Statement	Description
break	Terminate the current loop . Use the break statement to come out of the loop instantly.
continue	Skip the current iteration of a loop and move to the next iteration
pass	Do nothing . Ignore the condition in which it occurred and proceed to run the program as usual

break

```
for i in sequence:  
    statement 1  
    statement 2  
    ...  
    if condition:  
        break  
        statement x  
        statement n
```

#Next statement after loop

Break Statement

Terminate loop
immediately

Remaining
body of loop

Body of a loop

Execute as long as
condition is True

continue

```
for i in sequence:  
    statement 1  
    statement 2  
    ...  
    if condition:  
        continue  
    statement x  
    statement n
```

continue
Move to the
next iteration

Statements
Skipped

Body of a loop

Execute as long as
condition is True

Nested Loop

```
for i in range(1, 11):
    for j in range(1, 11):
        print(i*j, end=" ")
    print()
```

The diagram illustrates the structure of a nested loop. It features three curly braces: a green brace on the left labeled 'Outer Loop' enclosing the outermost 'for' loop; a red brace in the middle labeled 'Inner loop' enclosing the inner 'for' loop; and a purple brace on the right labeled 'Body of Outer loop' enclosing both the inner loop structure and the final 'print('')' statement. A blue arrow points from the text 'Body of inner loop' to the 'print(i*j, end=" ")' line.

Python Program to Find the Factorial of a Number

Python program to print the duplicate elements of an array

Python program to find $\sum_1^n n!$

Python program to print the elements of an array in reverse order

Python program to print the largest element in an array

Python program to sort the elements of an array in ascending order

Python Program to Remove Punctuation from a String

Python program to find the frequency of each element in the array



Reading and Writing to text files in Python

Opening a File

```
File_object = open(r"File_Name","Access_Mode")
```

```
# Open function to open the file "MyFile1.txt"  
# (same directory) in append mode and  
file1 = open("MyFile.txt","a")  
  
# store its reference in the variable file1  
# and "MyFile2.txt" in D:\Text in file2  
file2 = open(r"D:\Text\MyFile2.txt","w+")
```

File Access Modes

1. **Read Only ('r')** : Open text file for **reading**. The handle is positioned at the **beginning** of the file. If the file does **not exists**, raises I/O **error**. This is also the default mode in which file is opened.
2. **Read and Write ('r+')** : Open the file for **reading** and **writing**. The handle is positioned at the **beginning** of the file. Raises I/O **error** if the file does **not exists**.
3. **Write Only ('w')** : Open the file for **writing**. For existing file, the data is truncated and **over-written**. The handle is positioned at the **beginning** of the file. **Creates** the file if the file does not exists.
4. **Write and Read ('w+')** : Open the file for **reading** and **writing**. For existing file, data is truncated and **over-written**. The handle is positioned at the **beginning** of the file.
5. **Append Only ('a')** : Open the file for **writing**. The file is **created** if it does not exist. The handle is positioned at the **end** of the file. The data being written will be **inserted** at the end, after the existing data.
6. **Append and Read ('a+')** : Open the file for **reading** and **writing**. The file is **created** if it does not exist. The handle is positioned at the **end** of the file. The data being written will be **inserted** at the end, after the existing data.

Closing a file

```
# Opening and Closing a file "MyFile.txt"  
# for object name file1.  
file1 = open("MyFile.txt","a")  
file1.close()
```

Reading from a file

There are three ways to read data from a text file.

1.read() : Returns the read bytes in form of a string. Reads n bytes, if no n specified, reads the **entire file**.

File_object.read([n])

2.readline() : Reads a line of the file and returns in form of a string. For specified n, reads at most n bytes.

However, does not reads more than **one line**, even if n exceeds the length of the line.

File_object.readline([n])

3.readlines() : Reads **all the lines** and return them as each line a string element in a **list**.

File_object.readlines()

Writing to a file

There are two ways to write in a file.

1. write() : Inserts the string str1 in a single line in the text file.

File_object.write(str1)

2. writelines() : For a list of string elements, each string is inserted in the text file. Used to insert multiple strings at a single time.

File_object.writelines(L) for L = [str1, str2, str3]

Using write along with the with() function

Example

```
# Python code to illustrate split() function  
with open("file.txt", "r") as file:  
    data = file.readlines()  
    for line in data:  
        word = line.split()  
        print (word)
```

Copy contents of one file to another file

```
# open both files
```

```
with open('first.txt','r') as firstfile, open('second.txt','a') as secondfile:
```

```
    # read content from first file
```

```
    for line in firstfile:
```

```
        # append content to second file
```

```
        secondfile.write(line)
```

Copy all the content of one file to another file in uppercase

```
# To open the first file in read mode  
f1 = open("sample file 1.txt", "r")  
  
# To open the second file in write mode  
f2 = open("sample file 2.txt", "w")  
  
# For loop to traverse through the file  
for line in f1:  
  
    # Writing the content of the first  
    # file to the second file  
  
    # Using upper() function to  
    # capitalize the letters  
    f2.write(line.upper())
```

Copy odd lines of one file to other

```
# open file in read mode
fn = open('bcd.txt', 'r')
# open other file in write mode
fn1 = open('nfile.txt', 'w')
# read the content of the file line by line
cont = fn.readlines()
type(cont)
for i in range(0, len(cont)):
    if(i % 2 != 0):
        fn1.write(cont[i])
    else:
        pass
```

Count number of lines in a text file in Python

```
file = open("gfg.txt","r")
Counter = 0

# Reading from file
Content = file.read()
CoList = Content.split("\n")

for i in CoList:
    if i:
        Counter += 1
print("This is the number of lines in the file")
print(Counter)
```

Exercise

- Get number of characters, words, spaces and lines in a file
- Read lines from this file and split line on last delimiter in Python and save it to another file


```
first_name1:last_name1:mail1@mail.com:address1
first_name2:last_name2:mail2@mail.com:address2
first_name3:last_name3:mail3@mail.com:address3
first_name4:last_name5:mail4@mail.com:address4
first_name5:last_name6:mail5@mail.com:address5
first_name6:last_name7:mail6@mail.com:address6
first_name7:last_name8:mail7@mail.com:address7
```




Errors Types



- 1.Syntax errors
- 2.Logical errors (Exceptions)

Errors and Exception Handling






map




filter




`filter(function, iterable)`

Returns a sequence from those elements of iterable for which the function returns true.

Lambda



List comprehension




Do this

For this collection

In this situation

```
[x**2 for x in range(0, 50) if x % 3 == 0]
```

Unpacking



*args and **Kwargs

Function definition

```
def fun_name(*args)      → Packing arguments  
    statement(s)
```

Function call

```
fun_name(a,b,c,d)      → Actual arguments
```

****kwargs means**
passing an arbitrary
number of arguments
with keywords



Parameter 1

Parameter 2

Parameter 3

.....

***args means passing an arbitrary number of arguments**

Function definition

```
def fun_name(**kwargs) → Packing keyword arguments  
    statement(s)
```

Function call

```
fun_name(a=1,b=2,c=3) → keyword arguments
```

Using map() function and lambda and count() function create a list which consists of the number of occurrence of letter: a.

Using map() function and lambda and count() function create a list consisted of the number of occurrence of both letters: A and a.

Using filter() function filter the list so that only negative numbers are left.

Using map() and filter() functions add 2000 to the values below 8000.

Write a program that reads the sentence and gives the output as the length of each word in a sentence in the form of a list.



Using map() function and lambda and count() function create a list which consists of the number of occurrence of letter: a.

```
lst2 = list(map(lambda x: x.count("a"), lst1))
```

Using map() function and lambda and count() function create a list consisted of the number of occurrence of both letters: A and a.

```
lst2 = list(map(lambda x: x.lower().count("a"), lst1))
```

Using filter() function filter the list so that only negative numbers are left.


```
lst2 = list(filter(lambda x: x<0, lst1))
print(lst2)
```

Using map() and filter() functions add 2000 to the values below 8000.

```
lst2 = list(map(lambda x: x+2000, filter(lambda x: x<8000, lst1)))
```

Write a program that reads the sentence and gives the output as the length of each word in a sentence in the form of a list.

```
sentence = 'I am learning Python programming with CSEstack'
words = sentence.split()
lengths = map(lambda word: len(word), words)
```



Functions

The diagram illustrates the structure of a Python function definition. The code is shown in a light blue box, and various parts are labeled with arrows:


- Function Name:** Points to the word "add".
- Parameters:** Points to the parameters "num1" and "num2".
- Function Body:** A curly brace on the right side groups the indented code block.
- Return Value:** Points to the **return** statement and its expression "addition".

```
def add(num1, num2):
    print("Number 1:", num1)
    print("Number 2:", num1)
    addition = num1 + num2

    return addition → Return Value
```

```
res = add(2, 4) → Function call
print(res)
```

Classes



Classes

The class is declared
with the keyword
`class`

```
class Rational:  
    def __init__(self, numerator, denominator):  
        self.numerator = numerator  
        self.denominator = denominator
```


Functions and variables
declared inside the class
block should have
indentation.

Class instantiation automatically
invokes an `__init__()`
method if it exists.

Classes

```
class Books:  
    def __init__(self, title, cost):  
        self.title = title  
        self.cost = cost  
    def gettitle(self):  
        print("Title of the book is: "+self.title)  
  
python_book = Books("Learn and Practice Python Programming", 136)  
print(python_book.title)  
print(python_book.cost)  
python_book.gettitle()
```

Inheritance



Child
Inherits
qualities
from parent

Inheritance

```
class ParentClass:

    def feature_1(self):
        print('feature_1 from ParentClass is running...')

    def feature_2(self):
        print('feature_2 from ParentClass is running...')


class ChildClass(ParentClass):

    def feature_3(self):
        print('feature_3 from ChildClass is running...')

obj = ChildClass()
obj.feature_1()
obj.feature_2()
obj.feature_3()
```

Define a class called Songs, it will show the lyrics of a song. Its `__init__()` method should have two arguments:`self` and `lyrics`. `lyrics` is a list. Inside your class create a method called `sing_me_a_song` that prints each element of `lyrics` on his own line. Define a variable:

```
happy_bday = Song(["May god bless you, ", "Have a sunshine on you,", "Happy Birthday to you !"])
```

Call the `sing_me_song` method on this variable.

```
>>> class Song(object):
...     def __init__(self, lyrics):
...         self.lyrics=lyrics
...     def sing_me_a_song(self):
...         for line in self.lyrics:
...             print line
```

```
happy_bday = Song(["May god bless you, ", ... "Have a sunshine on you,", ... "Happy Birthday to you !"])
print happy_bday.sing_me_a_song()
```



Python Modules

```
def add(a, b):  
    return a + b  
  
def sub(a, b):  
    return a - b  
  
def mul(a, b):  
    return a * b  
  
def div(a, b):  
    return a / b
```


```
import Calci  
  
print(Calci.add(10, 5))  
print(Calci.sub(10, 5))  
print(Calci.mul(10, 5))  
print(Calci.div(10, 5))
```

NumPy Basics

NumPy Agenda

- NumPy Intro
- Creating Arrays
- NumPy Array Indexing
- NumPy Array Slicing
- NumPy Data Types
- NumPy Copy vs View
- NumPy Array Shape
- NumPy Array Reshape
- NumPy Array Filter

Creating NumPy Arrays




Creating NumPy Array

`np.array([1,2,3])`



1
2
3

`np.arange(1, n+1)`



$n=5$

1	2	3	4	5
---	---	---	---	---

`np.ones(3)`



1
1
1

`np.zeros(3)`



0
0
0

`np.random.random(3)`



0.5967
0.0606
0.2223

`np.ones((3,2))`

1	1
1	1
1	1

3

`np.zeros((3,2))`

0	0
0	0
0	0

`np.random.random((3,2))`




0.37	0.88
0.75	0.79
0.63	0.16

NumPy Arrays Shape


3D array

1D array




shape: (4,)

2D array



shape: (2, 3)



NumPy Array Indexing

arr[,]

rows selector columns selector

 : :

 [1, 2, 3] [1, 2, 3]

 0:3 0:3

 0 0

 -1 -1

NumPy Array Indexing

	data
0	1
1	2
2	3

	data[0]
	1

	data[1]
	2

	data[0:2]
	1
	2

	data[1:]
	2
	3

	data[-2:]
	2
	3

	data	
0	1	-2
1	2	-1
2	3	
3		

NumPy Array Indexing

`np.array([[1,2],[3,4],[5,6]])`



1	2
3	4
5	6


	0	1
0	1	2
1	3	4
2	5	6


	0	1
0	1	2
1	3	4
2	5	6



	0	1
0	1	2
1	3	4
2	5	6




	0	1
0	1	2
1	3	4
2	5	6

Basic array operations

`data = np.array([1,2])` `data`


`ones = np.ones(2)` `ones`


`data + ones` `=` `data` `ones`

`=` 

`data` `ones` `=` `data` `data` `=` `data` `data` `=`




Broadcasting

$$\begin{array}{c|c} 1 \\ \hline 2 \end{array} * \mathbf{1.6} = \begin{array}{c|c} 1 \\ \hline 2 \end{array} * \begin{array}{c|c} 1.6 \\ \hline 1.6 \end{array} = \begin{array}{c|c} 1.6 \\ \hline 3.2 \end{array}$$

Basic array operations

$$\text{data} + \text{ones} = \begin{array}{c} \text{data} \\ \begin{array}{|c|c|} \hline 1 & 2 \\ \hline 3 & 4 \\ \hline \end{array} \end{array} = \begin{array}{c} \text{ones} \\ \begin{array}{|c|c|} \hline 1 & 1 \\ \hline 1 & 1 \\ \hline \end{array} \end{array} = \begin{array}{|c|c|} \hline 2 & 3 \\ \hline 4 & 5 \\ \hline \end{array}$$

$$\text{data} + \text{ones_row} = \begin{array}{c} \text{data} \\ \begin{array}{|c|c|} \hline 1 & 2 \\ \hline 3 & 4 \\ \hline 5 & 6 \\ \hline \end{array} \end{array} + \begin{array}{c} \text{ones_row} \\ \begin{array}{|c|c|} \hline 1 & 1 \\ \hline \end{array} \end{array} = \begin{array}{c} \text{data} \\ \begin{array}{|c|c|} \hline 1 & 2 \\ \hline 3 & 4 \\ \hline 5 & 6 \\ \hline \end{array} \end{array} + \begin{array}{c} \text{ones_row} \\ \begin{array}{|c|c|} \hline 1 & 1 \\ \hline 1 & 1 \\ \hline 1 & 1 \\ \hline \end{array} \end{array} = \begin{array}{|c|c|} \hline 2 & 3 \\ \hline 4 & 5 \\ \hline 6 & 7 \\ \hline \end{array}$$

More useful array operations

data

1
2
3

$$\text{.max()} = 3$$

data

1
2
3

$$\text{.min()} = 1$$

data

1
2
3

$$\text{.sum()} = 6$$

data

1	2
3	4
5	6

$$\text{.max()} = 6$$

data

1	2
3	4
5	6


$$\text{.min()} = 1$$

data

1	2
3	4
5	6

$$\text{.sum()} = 21$$

More useful array operations



NumPy Copy vs View

View

`arr[1:4]`



Merely offset is changed

Copy

`arr[[1,2,3]]`




Elements are copied
and a new object is
created

NumPy Array Reshape


`data`

1
2
3
4
5
6


`data.reshape(2,3)`




`data.reshape(3,2)`




NumPy Filter Array



NumPy Arrays Transpose



flattening multidimensional arrays




Dot product vs. element-wise

Element-wise

$$\begin{array}{|c|c|} \hline A & B \\ \hline C & D \\ \hline \end{array} * \begin{array}{|c|c|} \hline E & F \\ \hline G & H \\ \hline \end{array}$$

2x2 2x2



$$\begin{array}{|c|c|} \hline A^*E & B^*F \\ \hline C^*G & D^*H \\ \hline \end{array}$$

2x2

Dot product

$$\begin{array}{|c|c|c|} \hline A & B & C \\ \hline D & E & F \\ \hline G & H & I \\ \hline \end{array} .\text{dot}(\begin{array}{|c|c|} \hline J & K \\ \hline L & M \\ \hline N & O \\ \hline \end{array})$$

3x3 3x2



$A^*J + B^*L + C^*N$	$A^*K + B^*M + C^*O$
$D^*J + E^*L + F^*N$	$D^*K + E^*M + F^*O$
$G^*J + H^*L + I^*N$	$G^*K + H^*M + I^*O$

3x2

Numpy Functions

- np.sqrt()
- np.max()
- np.log()
- np.sin()
- np.mean()
- np.square()
- np.sum()
- np.sort()
- np.quantile()
- np.percentile
- np.cov
- np.linalg.norm

Working with mathematical formulas

$$MeanSquareError = \frac{1}{n} \sum_{i=1}^n (Y_{prediction_i} - Y_i)^2$$




Working with mathematical formulas

$$MeanSquareError = \frac{1}{n} \sum_{i=1}^n (Y_{prediction_i} - Y_i)^2$$

```
error = (1/n) * np.sum(np.square(predictions - labels))
```

predictions	labels
1	1
1	2
1	3


```
error = (1/3) * np.sum(np.square(
```



Working with mathematical formulas

```
error = (1/3) * np.sum(np.square(
```

0
-1
-2

```
) )
```

```
error = (1/3) * np.sum(
```

0
1
4

```
)
```

```
error = (1/3) * 5
```

Write a NumPy program to find a matrix or vector norm.

```
import numpy as np
v = np.arange(7)
result = np.linalg.norm(v)
print("Vector norm:")
print(result)
m = np.matrix('1, 2; 3, 4')
result1 = np.linalg.norm(m)
print("Matrix norm:") print(result1)
```

Write a NumPy program to compute the multiplication of two given matrixes.

```
import numpy as np
p = [[1, 0], [0, 1]]
q = [[1, 2], [3, 4]]
print("original matrix:")
print(p)
print(q)
result1 = np.dot(p, q)
print("Result of the said matrix
multiplication:")
print(result1)
```



Write a NumPy program to compute the 80th percentile for all elements in a given array

Write a NumPy program to compute IQR for all elements in a given array

Compute the mean, standard deviation, and variance of a given array

Compute the covariance matrix of two given arrays



Data Quality


Data Quality

The future belongs to those who can control their data

Q =
uality



Data Quality



Source: CrowdFlower 2016

Data Quality



Data Quality



Data Quality

System A

Customer	Age	Zip Code	City	Rate
John Smith		95113	San José	1
Bob Clark	41	10007	New York	2
Jane Harris	-10	60602	Chicago	3

Completeness: Missing data

Validity: Is this a valid age?

System B


Customer	Age	Zip Code	City	Rate
John Smitz	15	95113	San José	A
Robert Clark	30	17000	New York	B
Mark Lee	32	60602	Chicago	C

Integrity: same city, different zip codes

The diagram illustrates data quality issues across two systems, A and B. In System A, the 'Age' field for Jane Harris contains the invalid value '-10'. In System B, the 'Zip Code' field for Robert Clark contains the invalid value '17000'. Both the 'City' fields in both systems contain the value 'New York', which is circled in orange, indicating a potential integrity violation where multiple records share the same city name despite having different zip codes.

Dealing with Missing Values

- Take a first look at the data.
- How many missing data points do we have?
- Figure out why the data is missing!?



Strategies To Handle Missing Values

Missing values

PassengerId	Survived	Pclass	Sex	Age	SibSp	Parch	Ticket	Fare	Cabin	Embarked
1	0	3	male	22	1	0	A/5 21171	7.25		S
2	1	1	female	38	1	0	PC 17599	71.2033	C85	C
3	1	3	female	26	0	0	STON/O2. 3101282	7.925		S
4	1	1	female	35	1	0	113803	53.1	C123	S
5	0	3	male	35	0	0	373450	8.05		S
6	0	3	male		0	0	330877	8.4583		Q

Strategies To Handle Missing Values

- Remove observation/records that have missing values.
- Imputation.

Deleting Columns & Rows with Missing Values

- Here, we either delete a particular row if it has a null value for a particular feature and a particular column if it has more than **70-75%** of missing values.
- This method is advised **only** when there are **enough samples** in the data set.
- Removing the data will lead to **loss of information** which will not give the expected results while predicting the output.

Handling Continuous variables

- This strategy can be applied on a feature which has **numeric** data like the age of a person.
- We can calculate the **mean, median or mode** of the feature and replace it with the missing values.
- This is an **approximation** which **can add variance** to the data set.
- But the loss of the data can be negated by this method which yields **better results** compared to removal of rows and columns.

Handling categorical variables

- A **categorical** feature will have a definite number of possibilities, such as gender, for example.
- Since they have a definite number of classes, we can **assign another class** for the missing values.


Predicting The Missing Values

- Using the features which do not have missing values, we can predict the nulls with the help of a machine learning algorithm.
- This method may result in **better accuracy**, unless a missing value is expected to have a very **high variance**.
 - Example: linear regression to replace the nulls in the feature ‘age’, using other available features.

Using Algorithms Which Support Missing Values

- KNN is a machine learning algorithm which works on the principle of distance measure.
- This algorithm can be used when there are nulls present in the dataset.
- While the algorithm is applied, KNN considers the missing values by taking the majority of the K nearest values.
- In this particular dataset, taking into account the person's age, sex, class etc, we will assume that people having same data for the above mentioned features will have the same kind of fare.
- Another algorithm which can be used here is **RandomForest**.
- This model produces a robust result because it works well on **non-linear** and the **categorical** data.



Time Series Imputations





Interpolation is the process of estimating and inserting missing values in time series data.

Outliers

- An **outlier** is an observation that lies an abnormal distance from other values in a random sample from a population.




Impact Of Outliers On Linear Regression



How To Identify Outliers?

- Box Plot
- Histogram
- Scatter Plot
- Interquartile Range (IQR) based method
- Standard Deviation based method



Exercise

Find Q_1 , Q_2 , and Q_3 for the following data set. Identify any outliers, and draw a box-and-whisker plot.

$$\{5, 40, 42, 46, 46, 48, 49, 50, 50, 52, 53, 55, 56, 58, 75, 102\}$$

There are 15 values, arranged in increasing order. So, Q_2 is the 8th data point, 50.

Q_1 is the 4th data point, 46, and Q_3 is the 12th data point, 56.

The interquartile range IQR is $Q_3 - Q_1$ or $56 - 46 = 10$.


Now we need to find whether there are values less than $Q_1 - (1.5 \times \text{IQR})$ or greater than $Q_3 + (1.5 \times \text{IQR})$.

$$Q_1 - (1.5 \times \text{IQR}) = 46 - 15 = 31$$

$$Q_3 + (1.5 \times \text{IQR}) = 56 + 15 = 71$$


Since 5 is less than 31 and 75 and 102 are greater than 71, there are 3 outliers.

The box-and-whisker plot is as shown. Note that 40 and 58 are shown as the ends of the whiskers, with the outliers plotted separately.



How To Handle The Outliers?

- Doing nothing
- Deleting/Trimming
- Winsorizing (replace the extreme values with a certain percentile value)
- Transformation
- Binning
- Use robust estimators
- Imputing



- List of Machine Learning algorithms which are sensitive to outliers:
① Linear Regression ② Logistic Regression ③ Support Vector Machine ④ K- Nearest Neighbors ⑤ K-Means Clustering ⑥ Hierarchical Clustering ⑦ Principal Component Analysis ⑧ AdaBoost
- List of Machine Learning algorithms which are `not` sensitive to outliers: ① Decision Tree ② Random Forest ③ XGBoost ④ Naive Bayes ⑤ DBSCAN ⑥ NN

Pandas

Pandas Agenda



Pandas


- Pandas is an open source library built on top of NumPy
- It allows for fast analysis and data cleaning and preparation
- It excels in performance and productivity.
- It also has built-in visualization features.
- It can work with data from a wide variety of sources.

Pandas Data Structure

One-dimensional data structure

- contains values along **a single** axis (rows)


rows



Series

Two-dimensional data structure

columns




DataFrame

Pandas Data Structure

Single column data


- o corresponds to a **single variable**
- o information of a **single type**



Series

Multi-column data

- o each column represents a **different variable**
- o every column contains data of **its own type**
- o the information can potentially be **heterogeneous**



DataFrame

Pandas Data Structure

	Name	Team	Number
0	Avery Bradley	Boston Celtics	0.0
1	John Holland	Boston Celtics	30.0
2	Jonas Jerebko	Boston Celtics	8.0
3	Jordan Mickey	Boston Celtics	NaN
4	Terry Rozier	Boston Celtics	12.0
5	Jared Sullinger	Boston Celtics	7.0
6	Evan Turner	Boston Celtics	11.0

ser = pd.Series (df ['Name'])

ser = pd.Series (df ['Team'])

ser = pd.Series (df ['Number'])

Creating a Series

pd.Series(data=None, index=None)

```
# simple list
lst = ['G', 'E', 'E', 'K', 'S', 'F', 'O', 'R', 'G', 'E', 'E', 'K', 'S']
```

```
# forming series
s = pd.Series(lst)
```

```
# simple dict
dct = {'G':2, 'E':4, 'K':2, 'S':2, 'F':1, 'O':1, 'R':1}
```

```
# forming series
s = pd.Series(dct)
```

```
# numpy array
arr = np.array(['G', 'E', 'E', 'K', 'S', 'F', 'O', 'R', 'G', 'E', 'E', 'K', 'S'])
```

```
# forming series
s = pd.Series(arr)
```

Indexing & Slicing A Series

Series1

	Series1
A	1
B	2
C	3
D	4

`series1['A']`

`series1[0]`

`series1[0:3]`

`series1[0:5:2]`

`series1['A':'C']`

Arithmetic Operation

A	1
B	2
C	3
D	4

+

A	1
C	2
E	3
F	4

=

A	2
B	NaN
C	5
D	NaN
E	NaN
F	NaN

Pandas Data Structure



Diagram illustrating the structure of a Pandas DataFrame:

The DataFrame has the following structure:

- Column names:** Name, Team, Number, Position, Age, Height, Weight, College, Salary.
- Index label:** The index is labeled by row number (0 to 6).
- Columns axis=1:** The columns represent different data types: Name (string), Team (string), Number (float), Position (string), Age (float), Height (string), Weight (float), College (string), and Salary (float).
- Index axis=0:** The index represents the position of each row.
- Data:** The data consists of 7 rows of information for basketball players.
- Missing value:** Several cells contain NaN or missing values, such as Position for player 3, Age for player 5, and Height for player 6.

	Name	Team	Number	Position	Age	Height	Weight	College	Salary
0	Avery Bradley	Boston Celtics	0.0	PG	25.0	6-2	180.0	Texas	7730337.0
1	John Holland	Boston Celtics	30.0	SG	27.0	6-5	205.0	Boston University	NaN
2	Jonas Jerebko	Boston Celtics	8.0	PF	29.0	6-10	231.0	NaN	5000000.0
3	Jordan Mickey	Boston Celtics	NaN	PF	21.0	6-8	235.0	LSU	1170960.0
4	Terry Rozier	Boston Celtics	12.0	PG	22.0	6-2	190.0	Louisville	1824360.0
5	Jared Sullinger	Boston Celtics	7.0	C	NaN	6-9	260.0	Ohio State	2569260.0
6	Evan Turner	Boston Celtics	11.0	SG	27.0	6-7	220.0	Ohio State	3425510.0

Creating a DataFrame




Creating a DataFrame

```
# Named Index
fruit = {
    'oranges' : [3,2,0,1],
    'apples'  : [0,3,7,2],
    'grapes'  : [5,6,9,0],
    'pear'    : [1,23,45,1]
}
df = pd.DataFrame(fruit ,index = ['June','July','August','September'])
df
```

	oranges	apples	grapes	pear
June	3	0	5	1
July	2	3	6	23
August	0	7	9	45
September	1	2	0	1

Indexing & Slicing Dataframe

Two points
of reference



loc Vs. iloc

`df.loc[START:STOP:STEP , START:STOP:STEP]`

Select Rows by Names/Labels

Select Columns by Names/Labels

Select Rows by Names/Labels

Select Columns by Names/Labels

`df.iloc[START:STOP:STEP , START:STOP:STEP]`


Select Rows by Indexing Position

Select Columns by Indexing Position


loc Vs. iloc

	loc[] - By Label	iloc[] - By Index
Select Single Row	df.loc['r2']	df.iloc[1]
Select Single Column	df.loc[:, "Courses"]	df.iloc[:, 0]
Select Multiple Rows	df.loc[['r2','r3']]	df.iloc[[1,2]]
Select Multiple Columns	df.loc[:, ["Courses","Fee"]]	df.iloc[:, [0,1]]
Select Rows Range	df.loc['r1':'r4']	df.iloc[0:4]
Select Columns Range	df.loc[:, 'Fee':'Discount']	df.iloc[:,1:4]
Select Alternate Rows	df.loc['r1':'r4':1]	df.iloc[0:4:1]
Select Alternate Columns	df.loc[:, 'Fee':'Discount':1]	df.iloc[:,1:4:1]



Indexing and slicing



loc Vs. iloc




loc Vs. iloc



loc Vs. iloc

df.loc ['cobra':'viper', 'max_speed']




df.loc ['cobra' : 'viper',
row label

cobra 2
viper 5

© w3resource.com

df.loc [[False, False, True]]




New DataFrame


	max_speed	shield
sidewinder	8	9

© w3resource.com


loc Vs. iloc



df.loc [df ['shield'] > 6, ['max_speed']]



loc Vs. iloc



Filter

```
# filter Rows Based on condition  
df[df["Courses"] == 'Spark']  
df.loc[df['Courses'] == value]  
df.query("Courses == 'Spark'")  
df.loc[df['Courses'] != 'Spark']  
df.loc[df['Courses'].isin(values)]  
df.loc[~df['Courses'].isin(values)]
```


Filter

```
# filter Multiple Conditions using Multiple Columns  
df.loc[(df['Discount'] >= 1000) & (df['Discount'] <= 2000)]  
df.loc[(df['Discount'] >= 1200) & (df['Fee'] >= 23000 )]
```

DON'T

df **and** df2

df **or** df2





Filter

```
# Other examples
df[df['Courses'].str.contains("Spark")]
df[df['Courses'].str.lower().str.contains("spark")]
df[df['Courses'].str.startswith("P")]
```


Analyzing DataFrames

- head()
- tail()
- info()
- describe()

Drop Function



Drop Function





Cleaning Empty Cells

```
dropna(self, axis=0, how="any", thresh=None, subset=None,  
inplace=False)
```



- **axis**: possible values are {0 or 'index', 1 or 'columns'}, default 0. If 0, drop rows with null values. If 1, drop columns with missing values.
- **how**: possible values are {'any', 'all'}, default 'any'. If 'any', drop the row/column if any of the values is null. If 'all', drop the row/column if all the values are missing.
- **thresh**: an int value to specify the threshold for the drop operation.
- **subset**: specifies the rows/columns to look for null values.
- **inplace**: a boolean value. If True, the source DataFrame is changed and None is returned.

Cleaning Empty Cells





	name
0	Superman
1	Batman
2	Spiderman

Cleaning Empty Cells



Cleaning Empty Cells



Fillna

The name of the
DataFrame you
want to operate on

The new value that
will replace the
missing values

```
myDataFrame.fillna(fill-value)
```

The name of
the method



Removing Duplicates

The name of your
Pandas dataframe

```
your_dataframe.drop_duplicates(subset=, keep=)
```

The method
name

Parameter specifying a
subset of variables on which
to look for duplicates

Parameter specifying
which duplicate
observation to keep


(i.e., 'first', 'last')

Removing Duplicates

```
your_dataframe.drop_duplicates()
```

name	region	sales	expense
William	East	50000	42000
William	East	50000	42000
Emma	North	52000	43000
Emma	West	52000	43000
Anika	East	65000	44000
Anika	East	72000	53000

Set DataFrame Index



Reset DataFrame Index

The diagram illustrates the process of resetting a DataFrame index. On the left, a DataFrame with four rows and columns A, B, and C is shown. The index values are highlighted with a red border: 1, 3, 5, and 7. An arrow points to the right, where the same DataFrame is shown with its index values reset to 0, 1, 2, and 3, also highlighted with a green border.

	A	B	C
1	a1	1	c1
3	a2	2	c2
5	a3	3	c3
7	a4	4	c4

	A	B	C
0	a1	1	c1
1	a2	2	c2
2	a3	3	c3
3	a4	4	c4

The name of the DataFrame you want to operate on



```
myDataFrame.reset_index(level=, drop=, inplace= )
```

The name of the method



Which "level" of the index you want to remove, if the index has multiple levels (default is all levels)




Whether you want to delete the index when it is removed (default is False)

Whether you want to operate on directly on the DataFrame (default is False)



Group by

```
df.groupby('column_to_group')['column_to_agg'].agg_function()
```



Group by

```
df.groupby('column_to_group')['column_to_agg'].agg_function()
```

```
df.groupby('Name')[AvgBill].sum()
```

Index	Name	Type	AvgBill
0	Lihoh Lihoh	Restaurant	\$45.32
1	Chambers	Restaurant	\$65.33
2	The Square	Bar	\$12.45
3	Tosca Cafe	Restaurant	\$180.34
4	Lihoh Lihoh	Restaurant	\$145.42
5	Chambers	Restaurant	\$25.35



Lihoh Lihoh: \$190.74
Chambers: \$90.68
The Square: \$12.45
Tosca Cafe: \$180.34

Aggregation Methods

Aggregation Method	Description
<code>.count()</code>	The number of non-null records
<code>.sum()</code>	The sum of the values
<code>.mean()</code>	The arithmetic mean of the values
<code>.median()</code>	The median of the values
<code>.min()</code>	The minimum value of the group
<code>.max()</code>	The maximum value of the group
<code>.mode()</code>	The most frequent value in the group
<code>.std()</code>	The standard deviation of the group
<code>.var()</code>	The variance of the group

Group by Example

```
daily_spend_count = df.groupby('Day')['Debit'].count()  
daily_spend_sum = df.groupby('Day')['Debit'].sum()
```

1. Split the data by using
values in the "Day" column

```
daily_spend = df.groupby('Day').agg({'Debit': ['sum', 'count']})
```

2. Perform both "sum" and "count"
operations on the "Debit" column of
the grouped data

```
df.groupby(['Category','Month'])['Debit'].sum()
```

Sort

The name of the DataFrame you want to operate on

```
myDataFrame.sort_values(by, ascending =, inplace = )
```



The column or list of columns you want to sort by



Whether you want to operate on directly on the DataFrame (default is False)



The name of the method



Whether you want to sort in ascending order (default is True)



Correlations


	Maths	Physics	History
0	78	81	53
1	85	77	65
2	67	63	95
3	69	74	87
4	53	46	63
5	81	72	58
6	93	88	73
7	74	76	42

df.corr()





	Maths	Physics	History
Maths	1.000000	0.906340	-0.159063
Physics	0.906340	1.000000	-0.158783
History	-0.159063	-0.158783	1.000000

Data Integration



append



Concatenate

	Country	Currency
0	Japan	Yen
1	China	chin
2	India	rupees

	capital	population
0	Jaya'pura	456750
1	Toronto	3456545
2	Aukland	89752

Pandas concat()

Default axis = 0

axis = 1

	Country	Currency	capital	population
0	Japan	Yen	NaN	NaN
1	China	chin	NaN	NaN
2	India	rupees	NaN	NaN
0	NaN	NaN	Jaya'pura	456750.0
1	NaN	NaN	Toronto	3456545.0
2	NaN	NaN	Aukland	89752.0

```
1 pd.concat([data_3, my_df_drop], axis = 1)
```

	Country	Currency	capital	population
0	Japan	Yen	Jaya'pura	456750
1	China	chin	Toronto	3456545
2	India	rupees	Aukland	89752

Concatenate

	orange	apple	grapes
0	3	0	7
1	2	3	14
2	0	7	6
3	1	2	15

Concat with axis = 0
is same as Append

	grapes	mango	banana	pear	pineapple
0	13	10	20	21	30
1	12	13	23	24	33
3	2	2	4	51	30
4	55	9	0	22	36
5	98	76	9	25	31

Concat with axis = 1

	orange	apple	grapes	mango	banana	pear	pineapple
0	3.0	0.0	7	NaN	NaN	NaN	NaN
1	2.0	3.0	14	NaN	NaN	NaN	NaN
2	0.0	7.0	6	NaN	NaN	NaN	NaN
3	1.0	2.0	15	NaN	NaN	NaN	NaN
0	NaN	NaN	13	10.0	20.0	21.0	30.0
1	NaN	NaN	12	13.0	23.0	24.0	33.0
3	NaN	NaN	2	2.0	4.0	51.0	30.0
4	NaN	NaN	55	9.0	0.0	22.0	36.0
5	NaN	NaN	98	76.0	9.0	25.0	31.0

Concat
axis = 0
Concat
axis = 1
Append


	orange	apple	grapes	grapes	mango	banana	pear	pineapple
0	3.0	0.0	7.0	13.0	10.0	20.0	21.0	30.0
1	2.0	3.0	14.0	12.0	13.0	23.0	24.0	33.0
2	0.0	7.0	6.0	NaN	NaN	NaN	NaN	NaN
3	1.0	2.0	15.0	2.0	2.0	4.0	51.0	30.0
4	NaN	NaN	NaN	55.0	9.0	0.0	22.0	36.0
5	NaN	NaN	NaN	98.0	76.0	9.0	25.0	31.0

Merge Function

index	Year	Temperature
0	1956	16.99
1	1957	10.34
2	1958	21.01
3	1959	23.68
4	1960	24.59
5	1961	25.29
6	1962	8.77
7	1963	26.88
8	1964	15.04



index	Year	Rainfall
0	1956	1.01
1	1957	1.66
2	1958	3.5
3	1959	3.31
4	1960	3.61
5	1961	4.71
6	1962	2
7	1963	3.12
8	1964	1.96



A diagram illustrating the 'Merge Function'. It shows two separate data tables on the left and right, each with an icon above it (Excel for the first, CSV for the second). A large green arrow points downwards from both tables towards a third table at the bottom. This bottom table has columns labeled 'Year', 'Temperature', and 'Rainfall', with three rows of data below them, indicated by ellipses.

Year	Temperature	Rainfall
...

Pandas Merge

`df.merge(right=other_df, on='common_column', how='how_to_join')`

df



index	Year	Rainfall
0	1956	1.01
1	1957	1.66
2	1958	3.5
3	1959	3.31
4	1960	3.61
5	1961	4.71

+

Other_df



index	Year	Temperature
0	1956	16.99
1	1957	10.34
2	1958	21.01
3	1959	23.68
4	1960	24.59
5	1961	25.29


=

index	Year	Temperature
0	1956	16.99
1	1957	10.34
2	1958	21.01
3	1959	23.68
4	1960	24.59
5	1961	25.29




Pandas Merge

how='inner'




natural join

how='outer'




full outer join

how='left'



left outer join

how='right'



right outer join

index	Year	Temperature
0	1956	16.99
1	1957	10.34
2	1958	21.01
3	1959	23.68
4	1960	24.59
5	1961	25.29

index	Year	Rainfall
0	1956	1.01
1	1958	3.5
2	1959	3.31
3	1960	3.61
4	1962	2
5	1963	3.12

index	Year	Temperature	Rainfall
0	1956	16.99	1.01
1	1957	10.34	Nan
2	1958	21.01	3.5
3	1959	23.68	3.31
4	1960	24.59	3.61
5	1961	25.29	Nan
6	1962	Nan	2
7	1963	Nan	3.12

Join

`df_left.join(df_right, how='left')`

df_names	
	Name
Symbol	
APPL	Apple
MSFT	Mircosoft
TSLA	Tesla
GOOG	Google
NFLX	Netflix

df_portfolio	
	Shares
Symbol	
TSLA	20
APPL	50
GOOG	50
AMZN	100

`df_names.join(df_portfolio, how='left')`


	Name	Shares
APPL	Apple	50.0
MSFT	Mircosoft	NaN
TSLA	Tesla	20.0
GOOG	Google	50.0
NFLX	Netflix	NaN

Pandas concat Vs append Vs join Vs merge

- **Concat** gives the flexibility to join based on the axis(all **rows** or **all columns**)
- **Append** is the specific case(`axis=0, join='outer'`) of **concat**
- **Merge** is based on any particular **column** each of the two dataframes, this columns are variables on like '`left_on`', '`right_on`', '`on`'.
- **Join** is based on the indexes (set by **set_index**) on how variable =['`left`', '`right`', '`inner`', '`outer`']

Reading files

music.csv



The screenshot shows a Microsoft Excel spreadsheet titled 'Workbook1'. The data is contained in a single sheet named 'Sheet1'. The columns are labeled 'Artist', 'Genre', 'Listeners', and 'Plays'. The data rows are as follows:

	Artist	Genre	Listeners	Plays
1	Billie Holiday	Jazz	1,300,000	27,000,000
2	Jimi Hendrix	Rock	2,700,000	70,000,000
3	Miles Davis	Jazz	1,500,000	48,000,000
4	SIA	Pop	2,000,000	74,000,000

pandas.read_csv('music.csv')



The code `pandas.read_csv('music.csv')` is shown in red, indicating it is a command. To its right is a table representing the data from the CSV file, structured as a DataFrame with columns: Artist, Genre, Listeners, and Plays. The data is indexed from 0 to 3.

	Artist	Genre	Listeners	Plays
0	Billie Holiday	Jazz	1,300,000	27,000,000
1	Jimi Hendrix	Rock	2,700,000	70,000,000
2	Miles Davis	Jazz	1,500,000	48,000,000
3	SIA	Pop	2,000,000	74,000,000

Export DataFrame to CSV File

Export Pandas DataFrame to CSV File

DataFrame

name

```
df.to_csv(r'Path to save CSV file\File Name.csv')
```

Path e.g.

D:\Python\Tutorial\Example1.csv

Use .txt to
save as text file

File name e.g.



Replace

The name of the dataframe
you want to operate on



```
your_dataframe.replace(to_replace= [...], value= new_val)
```



The method name



The a list of old values
(passed to the to_replace parameter)



The new value
(passed to the value parameter)

```
sales_data.replace(to_replace = -1, value = np.NaN)
```

```
sales_data.replace(to_replace = [-1,-999], value = np.NaN)
```

Replace

The name of the dataframe you want to operate on



```
your_dataframe.replace({ 'col_name': { 'old_val': 'new_val' } })
```

The name of the column you want to operate on



The name of the new replacement value



The method name



The old value to replace



dtypes

df.dtypes



DataFrame	float	int	datetime	string
0	2.0	2	2019-02-10	'f1'



columns appears in series

float	float64
int	int64
datetime	datetime64[ns]
string	object

astype

The name of your
Pandas Series

The Python datatype
that you want to use
(e.g., category, int8, float16, etc)

```
your_series.astype(datatype)
```

The name of
the method

astype

```
your_dataframe.astype( { 'column': 'datatype' } )
```

The name of
the dataframe
column




The datatype you want
to use for that column
(e.g., category, int8, float16, etc)

to_datetime()



`pd.to_datetime(format='Your_Datetime_Format')`

"Given a format, convert a string to a datetime object"



```
earthquakes['date_parsed']=pd.to_datetime(earthquakes['Date'],format="%m/%d/%y")
```

isin



where

```
pd.DataFrame.where(cond=df<90, other="A+")
```


“Where a condition is false, replace a value”

Index	Test1	Test2	Test3
Bob	51	92	14
Sally	71	60	20
Frank	82	86	74
Patty	74	87	99

Index	Test1	Test2	Test3
Bob	51	A+	14
Sally	71	60	20
Frank	82	86	74
Patty	74	87	A+


mask

Pandas mask() vs where()



Apply Function

`df.apply(np.sqrt)`



Apply Function

`df.apply (np.sum, axis = 0)`

↓

df	P	Q
0	9	25
1	9	25
2	9	25

`np.sum`
function apply
for each column

↓ `axis = 0`
`axis 0 represents index`

for column P = index 0 + index 1 + index 2 = $9 + 9 + 9 = 27$

for column Q = index 0 + index 1 + index 2 = $25 + 25 + 25 = 75$

↓
P 27

Q 75

©w3resource.com

`df.apply (np.sum, axis = 1)`

↓

df	P	Q
0	9	25
1	9	25
2	9	25

`np.sum`
function apply
for each row or index

↓ `axis = 1`
`axis 1 represents column`

for index 0 = column P + column Q = $9 + 25 = 34$

for index 1 = column P + column Q = $9 + 25 = 34$

for index 2 = column P + column Q = $9 + 25 = 34$

↓
0 34
1 34
2 34

©w3resource.com

unique & nunique

Age	Department
26	Sales
28	Sales
27	Accounting
32	HR

df.unique()



Age	4
Department	3

Distinct Values in Each Column

Height	Weight	Team
167	65	A
175	70	A
170	72	B
186	80	B
190	86	B
188	94	C
158	50	A
169	58	C
183	78	B
180	85	C

df[‘Team’].unique()



A
B
C

Unique Values in a Column

value_counts

region
East
North
East
South
West
West

.value_counts (...)



value	count
East	2
North	1
South	1
West	2

select_dtypes

`df.select_dtypes(include, exclude)`

```
1. # select all numeric columns
2. df.select_dtypes(include='number')
```

Output:

	Age	Salary
0	26	70000.0
1	28	80000.0
2	27	72000.5
3	32	66000.0

interpolate

	Price
2020-12-04	10.0
2020-12-05	20.0
2020-12-06	NaN
2020-12-07	30.0
2020-12-08	50.0
2020-12-09	20.0
2020-12-10	NaN
2020-12-11	100.0
2020-12-12	30.0
2020-12-13	NaN

```
df.interpolate()
```

	Price
2020-12-04	10.0
2020-12-05	20.0
2020-12-06	25.0
2020-12-07	30.0
2020-12-08	50.0
2020-12-09	20.0
2020-12-10	60.0
2020-12-11	100.0
2020-12-12	30.0
2020-12-13	30.0

get_dummies

The name of
the function

The column or columns you want
to convert to dummy variables

(applicable for dataframes)

```
pd.get_dummies(data_object, columns=, drop_first=)
```

The object you
want to operate on
(e.g., a dataframe, a Series, etc)

A True/False indicator
that specifies if you
want to drop the first
level of the categorical
variable



melt

Country	1800	1801	1802	1803	1804	1805	1806	1807	1808	1809	1810	1811	1812	1813	1814
Afghanistan	3.28M														
Angola	1.57M														
Albania	400k	402k	404k	405k	407k	409k	411k	413k	414k	416k	418k	420k	422k	424k	426k

```
df=df.melt(id_vars=['country'],var_name='Year', value_name='total_Population')
```

•**id_vars** : *tuple, list, or ndarray, optional*

Column(s) to use as identifier variables.

•**value_vars** : *tuple, list, or ndarray, optional*

Column(s) to unpivot/melt. If not specified, uses all columns that are not set as id_vars.

•**var_name** : *scalar*

Name to use for the ‘variable’ column. If None it uses frame.columns.name or ‘variable’.

•**value_name** : *scalar, default ‘value’*

Name to use for the ‘value’ column.

```
1 df[df['country']=='Afghanistan']
✓ 0.4s
```

	country	Year	total_Population
0	Afghanistan	1800	3.28M
197	Afghanistan	1801	3.28M
394	Afghanistan	1802	3.28M
591	Afghanistan	1803	3.28M
788	Afghanistan	1804	3.28M
...
58312	Afghanistan	2096	75.8M
58509	Afghanistan	2097	75.6M
58706	Afghanistan	2098	75.4M
58903	Afghanistan	2099	75.2M
59100	Afghanistan	2100	74.9M

Reshaping Data in Pandas

Melt

df3

	first	last	height	weight
0	John	Doe	5.5	130
1	Mary	Bo	6.0	150

df3.melt(id_vars=['first', 'last'])



	first	last	variable	value
0	John	Doe	height	5.5
1	Mary	Bo	height	6.0
2	John	Doe	weight	130
3	Mary	Bo	weight	150


Pandas

- duplicated
- Isna = Isnull
- To_numpy
- Columns
- Index

Plot

- [pandas.DataFrame.plot.area](#)
- [pandas.DataFrame.plot.bar](#)
- [pandas.DataFrame.plot.barch](#)
- [pandas.DataFrame.plot.box](#)
- [pandas.DataFrame.plot.density](#)
- [pandas.DataFrame.plot.hexbin](#)
- [pandas.DataFrame.plot.hist](#)
- [pandas.DataFrame.plot.kde](#)
- [pandas.DataFrame.plot.line](#)
- [pandas.DataFrame.plot.pie](#)
- [pandas.DataFrame.plot.scatter](#)
- [pandas.DataFrame.boxplot](#)

```
df.plot(kind = 'scatter', x = 'Duration', y = 'Calories')  
plt.show()
```



Practical Lab

- Inconsistent Data Entry (EX1)
- Parsing Dates (EX2)
- Character Encodings (EX3)
- Categorical Data (EX4)
- Handle Missing Values (EX5)
- Handle Outliers (EX6)
- Handle Duplicates(EX7)