

Imitation Learning: A Review

Emanuele Ghelfi

February 28, 2023

Imitation Learning

Assumptions:

- ▶ Reward function not easy to formalize
- ▶ Access to expert demonstrations

Goal:

- ▶ Determine a policy that imitates the expert policy


Imitation Learning

Two main variants:

- ▶ Behavior Cloning
- ▶ Inverse Reinforcement Learning

Behavior Cloning

- ▶ **Supervised Learning** approach
- ▶ Demonstrations not uniformly sampled across the state space
- ▶ Compounding error



Inverse Reinforcement Learning

- ▶ What's the reward function "followed" by the expert?
- ▶ Recover a reward function from the expert demonstrations
- ▶ Train a RL agent using the learned reward function
- ▶ Highly inefficient

Dagger [Ross et al., 2011]

- ▶ One of the main BC method
- ▶ Simple idea: use dataset aggregation to improve generalization on unseen scenario

Algorithm 1 Dagger

- 1: Collect an initial set of trajectories using the expert
 - 2: **for** $i = 1$ to N **do**
 - 3: Train policy with BC
 - 4: Collect data with policy and correct it with the expert
 - 5: Aggregate Dataset
 - 6: **end for**
-

Dagger

Cons:

- ▶ Frequent interactions with environment and expert using trained policy
- ▶ Alleviated by Learning by Cheating [Chen et al., 2020]
 - ▶ Train an agent with **privileged** (perfect) information (expert)
 - ▶ The privileged agent acts a **teacher** that trains a standard (non-privileged) agent

GAIL [Ho and Ermon, 2016]

- ▶ GAN and maximum entropy IRL
- ▶ Main idea: use a discriminator that learns to discriminate **real** (expert) trajectories (π_E) from **fake** (agent) trajectories (π)
- ▶ Combines IRL and BC
- ▶ Discriminator \rightarrow Reward
- ▶ Generator learns directly the policy during training
- ▶ Does **NOT** require expert interaction during training
- ▶ Requires **environmental interaction** for closed loop training

Learning objective for the discriminator D:

$$\max_D \mathbb{E}_{\pi_{\text{red}}} [\log(D(s, a))] + \mathbb{E}_{\pi_{\text{blue}}} [\log(1 - D(s, a))]$$

GAIL

Learning objective for the discriminator D:

$$\max_D \mathbb{E}_{\pi} [\log(D(s, a))] + \mathbb{E}_{\pi_E} [\log(1 - D(s, a))]$$

Simple idea:

- ▶ $D(s, a) \rightarrow$ probability that $(s, a) \sim \pi$ (fake trajectory)

GAIL

Learning objective for the discriminator D:

$$\max_D \mathbb{E}_{\pi} [\log(D(s, a))] + \mathbb{E}_{\pi_E} [\log(1 - D(s, a))]$$

Simple idea:

- ▶ $D(s, a) \rightarrow$ probability that $(s, a) \sim \pi$ (fake trajectory)
- ▶ $D(s, a) \rightarrow 1$ when $(s, a) \sim \pi$

GAIL

Learning objective for the discriminator D:

$$\max_D \mathbb{E}_{\pi} [\log(D(s, a))] + \mathbb{E}_{\pi_E} [\log(1 - D(s, a))]$$

Simple idea:

- ▶ $D(s, a) \rightarrow$ probability that $(s, a) \sim \pi$ (fake trajectory)
- ▶ $D(s, a) \rightarrow 1$ when $(s, a) \sim \pi$
- ▶ $D(s, a) \rightarrow 0$ when $(s, a) \sim \pi_E$

GAIL

Learning objective for the agent is to "confuse" the discriminator:

$$\min_{\pi} \max_D \mathbb{E}_{\pi} [\log(D(s, a))] + \mathbb{E}_{\pi_E} [\log(1 - D(s, a))]$$

The agent uses the discriminator as reward (cost) function.

$$D(s, a) \rightarrow 0$$

Algorithm 2 GAIL


- 1: Collect an initial set of trajectories using the expert policy π_E
- 2: **for** $i = 1$ to N **do**
- 3: Sample trajectories with agent policy π_i
- 4: Update discriminator D with the gradient:

$$\nabla_D = \mathbb{E}_{\pi_i} [\nabla \log(D(s, a))] + \mathbb{E}_{\pi_E} [\nabla \log(1 - D(s, a))]$$

- 5: $\pi_i \rightarrow \pi_{i+1}$ using TRPO with cost function $\log(D(s, a))$
 - 6: **end for**
-

InfoGAIL [Li et al., 2017]

GAIL applied to autonomous driving (TORCS) [Video]



(a) Network architecture for the policy/generator π_θ .

(b) Network architecture for the discriminator D_ω .

InfoGAIL

- ▶ End to End
- ▶ Just 3 actions: steering, acceleration, breaking
- ▶ Handles multiple experts [Chen et al., 2016]
- ▶ Better than BC, GAIL and Human

Table 2: Average rollout distances.

| Method | Avg. rollout distance |
|------------------------|-----------------------|
| Behavior Cloning | 701.83 |
| GAIL | 914.45 |
| InfoGAIL \ RB | 1031.13 |
| InfoGAIL \ RA | 1123.89 |
| InfoGAIL \ WGAN | 1177.72 |
| InfoGAIL (Ours) | 1226.68 |
| Human | 1203.51 |

GAIL - Issues

$$\mathbb{E}_{\pi} [\log(D(s, a))] + \mathbb{E}_{\pi_E} [\log(1 - D(s, a))]$$

What's the gradient wrt π ?

GAIL - Issues


$$\mathbb{E}_{\pi} [\log(D(s, a))] + \mathbb{E}_{\pi_E} [\log(1 - D(s, a))]$$

What's the gradient wrt π ?

- ▶ π affects the data distribution but does not appear in the objective
- ▶ A common solution is to use REINFORCE-like methods ([Williams, 1992] [Schulman et al., 2015]) that tends to have high variance
- ▶ Model-Based methods (MGAIL) make the objective differentiable end-to-end


MGAIL [Baram et al., 2016]

Model-free GAIL





MGAIL [Baram et al., 2016]

Model-based GAIL



Symphony [Igl et al., 2022]

- ▶ Making simulation realistic by learning agents behaviour from **logged trajectories**
- ▶ Parallel Beam Search, Model Based GAIL (MGAIL) and Hierarchical Policies
- ▶ Playback Agents and **Interactive Agents**
- ▶ Useful when you need **Interactive Agents** in simulation



Symphony - Beam Search

- ▶ Select a set of trajectories from the training set
- ▶ Propose a goal with a goal generating policy
- ▶ Goal-conditioned policy proposes actions evaluated by the beam search algorithm
- ▶ Each node in the tree is evaluated by the discriminator
- ▶ Nodes with high score (fake) are **pruned** away
- ▶ Nodes with low score are **kept** and the rollout continues

Symphony - Goal Generation

- ▶ Goal: routes \rightarrow sequence of roadgraph lane segments
- ▶ For each agent, explore the road graph and use a network to classify the most probable ordered set of segments
- ▶ During training, train the network to classify the set of segments with minimal displacement from the GT trajectory
- ▶ Goal as input to the control policy

Symphony - Architecture


- ▶ BC: Discrete action space of 7×21 discretized accelerations and steering angles
- ▶ MGAIL: Continuous action space specifying the xy displacement (Delta Action Model)

Symphony - Dataset

- ▶ Each training batch: 16 run segments of 10 s. Actions computed at 5 Hz
- ▶ Proprietary Dataset: 1.1M run segments
- ▶ WOMD: 64.5K run segments

Hierarchical Model-Based Imitation Learning for Planning in Autonomous Driving [Bronstein et al., 2022]

- ▶ Focus on Ego-vehicle
- ▶ Closed loop **evaluation** with simulated agents (Symphony)
- ▶ Delta Action model
- ▶ BC loss with MGAIL losses



Hierarchical Model-Based Imitation Learning for Planning in Autonomous Driving - Method

- ▶ High-Level route generation
- ▶ Given the scene features and the route the policy outputs the parameters of a GMM
- ▶ The GMM gives a distribution over actions (delta-actions)

Hierarchical Model-Based Imitation Learning for Planning in Autonomous Driving - Losses

$$\mathcal{L} = \mathcal{L}_{\mathcal{D}} + \mathcal{L}_{\mathcal{P}} + \mathcal{L}_{\mathcal{BC}}$$

Hierarchical Model-Based Imitation Learning for Planning in Autonomous Driving - Losses

$$\mathcal{L} = \mathcal{L}_{\mathcal{D}} + \mathcal{L}_{\mathcal{P}} + \mathcal{L}_{\mathcal{BC}}$$

$\mathcal{L}_{\mathcal{D}}$: Discriminator Loss (GAIL)

$$\mathcal{L}_{\mathcal{D}} = -\mathbb{E}_{\pi} [\log(D(s))] - \mathbb{E}_{\pi_E} [\log(1 - D(s))]$$

Hierarchical Model-Based Imitation Learning for Planning in Autonomous Driving - Losses

$$\mathcal{L} = \mathcal{L}_{\mathcal{D}} + \mathcal{L}_{\mathcal{P}} + \mathcal{L}_{\mathcal{BC}}$$

$\mathcal{L}_{\mathcal{D}}$: Discriminator Loss (GAIL)

$$\mathcal{L}_{\mathcal{D}} = -\mathbb{E}_{\pi} [\log(D(s))] - \mathbb{E}_{\pi_E} [\log(1 - D(s))]$$

$\mathcal{L}_{\mathcal{P}}$: Policy Loss (GAIL)

$$\mathcal{L}_{\mathcal{P}} = \mathbb{E}_{\pi} [\log(D(s))]$$

Hierarchical Model-Based Imitation Learning for Planning in Autonomous Driving - Losses

$$\mathcal{L} = \mathcal{L}_{\mathcal{D}} + \mathcal{L}_{\mathcal{P}} + \mathcal{L}_{\mathcal{BC}}$$

$\mathcal{L}_{\mathcal{D}}$: Discriminator Loss (GAIL)

$$\mathcal{L}_{\mathcal{D}} = -\mathbb{E}_{\pi} [\log(D(s))] - \mathbb{E}_{\pi_E} [\log(1 - D(s))]$$

$\mathcal{L}_{\mathcal{P}}$: Policy Loss (GAIL)

$$\mathcal{L}_{\mathcal{P}} = \mathbb{E}_{\pi} [\log(D(s))]$$

$\mathcal{L}_{\mathcal{BC}}$: BC Loss

$$\mathcal{L}_{\mathcal{BC}} = -\mathbb{E}_{\pi_E} [\log(\pi(s, a))]$$

Hierarchical Model-Based Imitation Learning for Planning in Autonomous Driving - Interactive agents

- ▶ Using just playback agents is not enough for closed loop **evaluation** (especially if we condition on novel routes)
- ▶ Road Users should be **interactive** and should diverge in response
- ▶ Idea: Use Symphony agents for other Road Users
- ▶ Symphony agents are not used during training because they condition the AV on the true route → the AV should not diverge too much from the GT trajectory


Hierarchical Model-Based Imitation Learning for Planning in Autonomous Driving - Results

TABLE I: Logged Route on the *Unbiased Test Set*.


| Method | Success rate (%) | Route Failure rate (%) | Collision rate (%) | Off-road rate (%) | Route Progress ratio (%) |
|--------------------|----------------------------------|---------------------------------|---------------------------------|---------------------------------|--------------------------|
| Playback | 98.62 \pm 0.08 | 1.07 \pm 0.07 | 0.05 \pm 0.02 | 0.26 \pm 0.03 | 100.00 \pm 0.00 |
| BC | 86.07 \pm 0.24 | 9.63 \pm 0.20 | 4.53 \pm 0.14 | 2.21 \pm 0.10 | 105.59 \pm 0.40 |
| BC + Route | 94.18 \pm 0.16 | 0.69\pm0.06 | 4.60 \pm 0.14 | 0.75 \pm 0.06 | 98.10 \pm 0.33 |
| MGAIL | 88.90 \pm 0.21 | 9.73 \pm 0.20 | 1.28 \pm 0.08 | 1.00 \pm 0.07 | 101.22 \pm 0.32 |
| MGAIL + Route | 97.45 \pm 0.11 | 0.74 \pm 0.06 | 1.20 \pm 0.07 | 0.77 \pm 0.06 | 100.85 \pm 0.29 |
| MGAIL + BC | 89.84 \pm 0.21 | 8.93 \pm 0.19 | 1.25 \pm 0.08 | 0.73 \pm 0.06 | 105.58 \pm 0.36 |
| MGAIL + BC + Route | 98.22\pm0.09 | 0.69\pm0.06 | 0.77\pm0.06 | 0.37\pm0.04 | 105.30 \pm 0.32 |

Imitation Is Not Enough [Lu et al., 2022]

- ▶ Imitation Learning often fails to account for safety and reliability
- ▶ Imitation Learning with RL using simple rewards



Imitation Is Not Enough



Imitation Is Not Enough

Use a mixture of **RL** and **IL** objectives:

$$\max_{\pi} \mathbb{E}_{\pi} \left[\sum_t \gamma^t R(s_t, a_t) \right] + \lambda \mathbb{E}_{s, a \sim \pi_E} [\log(\pi(s, a))]$$

Imitation Is Not Enough

Simple reward function:

$$R = R_{\text{collision}} + R_{\text{off-road}}$$

$$R_{\text{collision}} = \min(d_{\text{collision}} - 1.0, 0.0)$$

$$R_{\text{off-road}} = \text{clip}(-1.0 - d_{\text{to-edge}}, 0.0, 2.0)$$

Imitation Is Not Enough

- ▶ Do not use reactive agents
- ▶ Imitative Loss discourage the learned policy to deviate too far from logs
- ▶ In this case the logged trajectories are enough

Imitation Is Not Enough - Results

| Method | Training | Top1 (%) | Top10 (%) | Top50 (%) | All (%) | Route Progress Ratio, All(%) |
|--------|----------|---------------------------------|---------------------------------|---------------------------------|---------------------------------|----------------------------------|
| BC | All | 9.74 \pm 0.49 | 6.72 \pm 0.47 | 5.14 \pm 0.39 | 4.35 \pm 0.27 | 99.00 \pm 0.39 |
| MGAIL | All | 7.28 \pm 0.98 | 4.22 \pm 0.77 | 3.40 \pm 0.97 | 2.48\pm0.29 | 99.55\pm1.91 |
| SAC | All | 5.29 \pm 0.66 | 4.64 \pm 1.08 | 4.12 \pm 0.74 | 6.66 \pm 0.44 | 77.82 \pm 8.21 |
| BC-SAC | All | 3.72\pm0.62 | 2.88\pm0.23 | 2.64\pm0.21 | 3.35 \pm 0.31 | 95.26 \pm 8.64 |
| BC | Top10 | 5.79 \pm 0.82 | 3.45 \pm 0.72 | 2.71 \pm 0.57 | 3.64 \pm 0.31 | 98.06\pm0.18 |
| MGAIL | Top10 | 4.21 \pm 0.95 | 2.57 \pm 0.52 | 2.20 \pm 0.52 | 2.45\pm0.35 | 96.57 \pm 1.19 |
| SAC | Top10 | 4.33 \pm 0.47 | 4.11 \pm 0.63 | 3.66 \pm 0.47 | 5.60 \pm 0.86 | 71.05 \pm 2.47 |
| BC-SAC | Top10 | 2.59\pm0.31 | 2.01\pm0.29 | 1.76\pm0.20 | 2.81 \pm 0.26 | 87.63 \pm 0.58 |
| BC | Top1 | 7.66 \pm 1.13 | 7.84 \pm 0.92 | 6.63 \pm 0.78 | 6.85 \pm 0.65 | 94.10\pm1.00 |
| MGAIL | Top1 | 4.24 \pm 0.95 | 3.16 \pm 0.43 | 2.74 \pm 0.46 | 3.79 \pm 0.46 | 93.10 \pm 11.72 |
| SAC | Top1 | 4.15 \pm 0.31 | 3.87 \pm 0.12 | 3.46 \pm 0.16 | 5.98 \pm 1.03 | 75.63 \pm 2.19 |
| BC-SAC | Top1 | 3.61\pm0.87 | 2.96\pm1.11 | 2.69\pm0.87 | 3.38\pm0.48 | 75.00 \pm 17.21 |

Table 2: Failure rates (lower is better) and progress ratios (higher is better) of BC-SAC and baselines on different training/evaluation subsets.

Imitation Is Not Enough - Results





Figure 6: Visualizations of win cases against baseline agents. The cyan car is controlled. **Example 1:** MGAIL collides with a pedestrian coming out of a double parked car while BC-SAC was able to leave an appropriately wide-clearance. **Example 2:** MGAIL does not provide sufficient clearance and collides with the incoming vehicle. **Example 3:** SAC slows down in an intersection resulting in a rear collision. In contrast, BC-SAC keeps an appropriate speed profile through the intersection without a collision.

Model-Based Imitation Learning for Urban Driving

[Hu et al., 2022]

- ▶ Related to World Models [Ha and Schmidhuber, 2018]
- ▶ Jointly learns a model of the world and a policy
- ▶ Leverages 3D geometry
- ▶ Trained offline without online interaction with the environment
- ▶ Can predict diverse and plausible states and actions, that can be interpretably decoded to BEV semantic segmentation

Model-Based Imitation Learning for Urban Driving



Model-Based Imitation Learning for Urban Driving




Observing

The observation encoder e_ϕ **lifts** image features **to 3D**, pools them to **bird's-eye view**, and compresses them to a **1D vector**.

1/5

Model-Based Imitation Learning for Urban Driving




The **prior distribution** $\mathcal{N}(\mu_\theta(\mathbf{h}_1), \sigma_\theta(\mathbf{h}_1)\mathbf{I})$, representing what the model imagines will happen, and the **posterior distribution** $\mathcal{N}(\mu_\phi(\mathbf{h}_1, \mathbf{x}_1), \sigma_\phi(\mathbf{h}_1, \mathbf{x}_1)\mathbf{I})$, representing what actually happened, **are matched** (KL divergence).

Observing

2/5

Model-Based Imitation Learning for Urban Driving




Observing

The **image decoder** g_θ and **bird's-eye view decoder** l_θ output the reconstructed observation and bird's-eye segmentation respectively.

The **driving policy** π_θ outputs the vehicle control.

Model-Based Imitation Learning for Urban Driving




Observing

A recurrent network computes the deterministic transition $\mathbf{h}_2 = f_\theta(\mathbf{h}_1, \mathbf{s}_1)$.

The prior $\mathcal{N}(\mu_\theta(\mathbf{h}_2, \hat{\mathbf{a}}_1), \sigma_\theta(\mathbf{h}_2, \hat{\mathbf{a}}_1)I)$ and posterior $\mathcal{N}(\mu_\phi(\mathbf{h}_2, \mathbf{a}_1, \mathbf{x}_2), \sigma_\phi(\mathbf{h}_2, \mathbf{a}_1, \mathbf{x}_2)I)$ are matched again.

Model-Based Imitation Learning for Urban Driving




Model-Based Imitation Learning for Urban Driving

- ▶ Decoding used just for closed loop **evaluation** (not training)
- ▶ Decoding just used as **auxiliary task**
- ▶ "For simplicity, we have set the weight parameter of the image reconstruction to 0." Cit.

MP3 [Casas et al., 2021]

- ▶ Map, Perceive, Predict, Plan
- ▶ Input: 10 LiDAR sweeps (1s)
- ▶ Range: 140 x 80
- ▶ Resolution: 0.2m/voxels



MP3

Map:

- ▶ Drivable area
- ▶ Reachable lanes
- ▶ Intersection

Occupancy:

- ▶ Current Occupancy
- ▶ Forward occupancy flow

Routing:

- ▶ For each pixel: probability that driving to it is aligned with the input plan
- ▶ 3 Networks: turn right, turn left, go straight

More

- ▶ Learning from All the Vehicles (LAV) [Chen and Krähenbühl, 2022]
- ▶ Reinforcement Learning Coach (ROACH) [Zhang et al., 2021]
- ▶ TransFuser: Multi-Modal Fusion Transformer for End-to-End Autonomous Driving [Chitta et al., 2022]

Our case

- ▶ BC training is ready using the recorded sequences
- ▶ Closed loop training requires a simulator
- ▶ Probably our simulator is not yet ready
 - ▶ Sim2real?
 - ▶ Environments?
 - ▶ Experts?
- ▶ Input representation problem:
 - ▶ Point cloud → simulation is difficult
 - ▶ Images → simulation is very difficult
 - ▶ Boxes → simulation is easy
- ▶ MVMap can help in the scenario generation but what about radars?

Bibliography I



Baram, N., Anschel, O., and Mannor, S. (2016).

Model-based adversarial imitation learning.

arXiv preprint arXiv:1612.02179.



Bronstein, E., Palatucci, M., Notz, D., White, B., Kuefler, A., Lu, Y., Paul, S., Nikdel, P., Mougin, P., Chen, H., et al. (2022).

Hierarchical model-based imitation learning for planning in autonomous driving.

In 2022 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS), pages 8652–8659. IEEE.



Casas, S., Sadat, A., and Urtasun, R. (2021).

Mp3: A unified model to map, perceive, predict and plan.

In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pages 14403–14412.

Bibliography II



Chen, D. and Krähenbühl, P. (2022).

Learning from all vehicles.

In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, pages 17222–17231.



Chen, D., Zhou, B., Koltun, V., and Krähenbühl, P. (2020).

Learning by cheating.

In Conference on Robot Learning, pages 66–75. PMLR.



Chen, X., Duan, Y., Houthoofd, R., Schulman, J., Sutskever, I., and Abbeel, P. (2016).

Infogan: Interpretable representation learning by information maximizing generative adversarial nets.

Advances in neural information processing systems, 29.

Bibliography III



Chitta, K., Prakash, A., Jaeger, B., Yu, Z., Renz, K., and Geiger, A. (2022).

Transfuser: Imitation with transformer-based sensor fusion for autonomous driving.

IEEE Transactions on Pattern Analysis and Machine Intelligence.



Ha, D. and Schmidhuber, J. (2018).

World models.

arXiv preprint arXiv:1803.10122.



Ho, J. and Ermon, S. (2016).

Generative adversarial imitation learning.

Advances in neural information processing systems, 29.

Bibliography IV



Hu, A., Corrado, G., Griffiths, N., Murez, Z., Gurau, C., Yeo, H., Kendall, A., Cipolla, R., and Shotton, J. (2022).

Model-based imitation learning for urban driving.

arXiv preprint arXiv:2210.07729.



Igl, M., Kim, D., Kuefler, A., Mougin, P., Shah, P., Shiarlis, K., Anguelov, D., Palatucci, M., White, B., and Whiteson, S. (2022).

Symphony: Learning realistic and diverse agents for autonomous driving simulation.

arXiv.



Li, Y., Song, J., and Ermon, S. (2017).

Infogail: Interpretable imitation learning from visual demonstrations.

Advances in Neural Information Processing Systems, 30.

Bibliography V



Lu, Y., Fu, J., Tucker, G., Pan, X., Bronstein, E., Roelofs, B., Sapp, B., White, B., Faust, A., Whiteson, S., et al. (2022).

Imitation is not enough: Robustifying imitation with reinforcement learning for challenging driving scenarios.

arXiv preprint arXiv:2212.11419.



Ross, S., Gordon, G., and Bagnell, D. (2011).

A reduction of imitation learning and structured prediction to no-regret online learning.

In Proceedings of the fourteenth international conference on artificial intelligence and statistics, pages 627–635. JMLR Workshop and Conference Proceedings.



Schulman, J., Levine, S., Abbeel, P., Jordan, M., and Moritz, P. (2015).

Trust region policy optimization.

In International conference on machine learning, pages 1889–1897. PMLR.

Bibliography VI



Williams, R. J. (1992).

Simple statistical gradient-following algorithms for connectionist reinforcement learning.

Reinforcement learning, pages 5–32.



Zhang, Z., Liniger, A., Dai, D., Yu, F., and Van Gool, L. (2021).

End-to-end urban driving by imitating a reinforcement learning coach.

In Proceedings of the IEEE/CVF international conference on computer vision, pages 15222–15232.