


Using FacetGrid, catplot and Implot

INTERMEDIATE DATA VISUALIZATION WITH SEABORN



Chris Moffitt
Instructor



Tidy data

- Seaborn's grid plots require data in "tidy format"
- One observation per row of data


	INSTNM	OPEID	REGION	SAT_AVG_ALL	PCTPELL	PCTFLOAN	ADM_RATE_ALL	UG	AVGFACSAL	COMPL_RPY_5YR_RT	DEBT_MDN
0	Alabama A & M University	100200	5	850.0	0.7249	0.8159	0.653841	4380.0	7017.0	0.477631579	14600
1	University of Alabama at Birmingham	105200	5	1147.0	0.3505	0.5218	0.604275	10331.0	10221.0	0.673230442	14250
2	Amridge University	2503400	5	NaN	0.7455	0.8781	NaN	98.0	3217.0	0.636363636	11082
3	University of Alabama in Huntsville	105500	5	1221.0	0.3179	0.4589	0.811971	5220.0	9514.0	0.762222222	15000
4	Alabama State University	100500	5	844.0	0.7567	0.7692	0.463858	4348.0	7940.0	0.43006993	15274

FacetGrid

- The `FacetGrid` is foundational for many data aware grids
- It allows the user to control how data is distributed across columns, rows and hue
- Once a `FacetGrid` is created, the plot type must be mapped to the grid

FacetGrid Categorical Example


```
g = sns.FacetGrid(df, col='HIGHDEG')
g.map(sns.boxplot, 'Tuition',
      order=['1', '2', '3', '4'])
```



catplot()

- The `catplot` is a simpler way to use a `FacetGrid` for categorical data
- Combines the facetting and mapping process into 1 function


```
sns.catplot(x="Tuition", data=df,  
            col="HIGHDEG", kind="box")
```



FacetGrid for regression

- `FacetGrid()` can also be used for scatter or regression plots


```
g = sns.FacetGrid(df, col='HIGHDEG')  
g.map(plt.scatter, 'Tuition', 'SAT_AVG_ALL')
```



Implot


- `lmpplot` plots scatter and regression plots on a `FacetGrid`

```
sns.lmpplot(data=df, x="Tuition", y="SAT_AVG_ALL",  
            col="HIGHDEG", fit_reg=False)
```



Implot with regression

```
sns.lmplot(data=df, x="Tuition", y="SAT_AVG_ALL",  
           col="HIGHDEG", row="REGION")
```




Let's practice!

INTERMEDIATE DATA VISUALIZATION WITH SEABORN

Using PairGrid and pairplot


INTERMEDIATE DATA VISUALIZATION WITH SEABORN



Chris Moffitt
Instructor

Pairwise relationships


- `PairGrid` shows pairwise relationships between data elements



Creating a PairGrid


- The `PairGrid` follows similar API to `FacetGrid`

```
g = sns.PairGrid(df, vars=["Fair_Mrkt_Rent", "Median_Income"])  
g = g.map(sns.scatterplot)
```



Customizing the PairGrid diagonals


```
g = sns.PairGrid(df, vars=["Fair_Mrkt_Rent", "Median_Income"])  
g = g.map_diag(sns.histplot)  
g = g.map_offdiag(sns.scatterplot)
```



Pairplot


- `pairplot` is a shortcut for the `PairGrid`

```
sns.pairplot(df, vars=["Fair_Mrkt_Rent", "Median_Income"], kind="reg",  
             diag_kind="hist")
```



Customizing a pairplot

```
sns.pairplot(df.query("BEDRMS < 3"),  
             vars=["Fair_Mrkt_Rent",  
                  "Median_Income", "UTILITY"],  
             hue="BEDRMS", palette="husl",  
             plot_kws={"alpha": 0.5})
```



Let's practice!

INTERMEDIATE DATA VISUALIZATION WITH SEABORN


Using JointGrid and jointplot

INTERMEDIATE DATA VISUALIZATION WITH SEABORN




Chris Moffitt
Instructor

JointGrid() Overview




Basic JointGrid

```
g = sns.JointGrid(data=df, x="Tuition", y="ADM_RATE_ALL")  
g.plot(sns.regplot, sns.histplot)
```




Advanced JointGrid

```
g = sns.JointGrid(data=df, x="Tuition", y="ADM_RATE_ALL")  
g = g.plot_joint(sns.kdeplot)  
g = g.plot_marginals(sns.kdeplot, shade=True)
```



jointplot()


```
sns.jointplot(data=df, x="Tuition", y="ADM_RATE_ALL", kind='hex')
```



Customizing a jointplot

```
g = (sns.jointplot(x="Tuition",  
                  y="ADM_RATE_ALL",  
                  kind="scatter",  
                  xlim=(0, 25000),  
                  data=df.query('UG < 2500 &  
                                Ownership == "Public"'))  
     .plot_joint(sns.kdeplot))
```

Customizing a jointplot



Let's practice!


INTERMEDIATE DATA VISUALIZATION WITH SEABORN

Selecting Seaborn Plots

INTERMEDIATE DATA VISUALIZATION WITH SEABORN



Chris Moffitt
Instructor




pairplot


jointplot

PairGrid


JointGrid



displot




Implot




catplot


FacetGrid




kdeplot




rugplot




residplot




histplot




ecdfplot




regplot




pointplot




barplot




countplot




boxplot




violinplot




boxenplot



swarmplot



stripplot



heatmap




palplot


matplotlib

Univariate Distribution Analysis

- `displot()` is the best place to start for this analysis
- `rugplot()`, `kdeplot()` and `ecdfplot()` can be useful alternatives




`displot`



`kdeplot`

`rugplot`




`histplot`

`ecdfplot`

matplotlib

Regression Analysis

- `lmplot()` performs regression analysis and supports faceting





Categorical Plots

- Explore data with the categorical plots and facet with `catplot`

pairplot() and jointplot()

- Perform regression analysis with `lmplot`
- Analyze distributions with `displot`



Thank You!

INTERMEDIATE DATA VISUALIZATION WITH SEABORN