

2024-2025 Spring

IE 554 Project – Mathematical Models

Emek Irmak & Ömer Turan Şahinaslan

CONTENTS

1	Dominator Partition Model (variable k)	1
2	Dominator Partition Model (fixed k)	2

1 Dominator Partition Model (variable k)

Sets & Parameters

$G = (V, E)$: a graph with vertex set V of size n and edge set E

Decision Variables

x_{vi} : 1 if vertex v is assigned to the i^{th} block

y_i : 1 if the i^{th} block is used (non-empty)

d_{vi} : 1 if vertex v dominates block i

Objective Function & Constraints

$$\begin{aligned} \min \quad & \sum_{i=1}^n y_i && \text{(minimize the number of blocks used)} \\ \text{s.t.} \quad & \sum_{i=1}^n x_{vi} = 1, \quad \forall v \in V && \text{(each vertex is assigned to one block)} \\ & x_{vi} \leq y_i \quad \forall v \in V, i \in V && \text{(vertex assigned only if block used)} \\ & \sum_{v \in V} x_{vi} \geq y_i \quad \forall i \in V && \text{(block used only if it is not empty)} \\ & x_{ui} + d_{vi} \leq 1 \quad \{\forall u, v \in V \mid \{u, v\} \notin E\}, i \in V && \text{(domination condition)} \\ & \sum_{i=1}^n d_{vi} \geq 1 \quad \forall v \in V && \text{(each vertex dominates at least one block)} \\ & d_{vi} \leq y_i \quad \forall v \in V, i \in V && \text{(cannot dominate an empty block)} \\ & \sum_{v \in V} x_{vi} \geq \sum_{v \in V} x_{v,i+1} \quad \forall i \in \{1, \dots, n-1\} && \text{(blocks are used in order)} \\ & x_{vi}, y_i, d_{vi} \quad \forall v \in V, i \in V && \text{(binary variables)} \end{aligned}$$

2 Dominator Partition Model (fixed k)

Sets & Parameters

$G = (V, E)$: a graph with vertex set V and edge set E

π : dominator partition of size k of G

Decision Variables

x_{vi} : 1 if vertex v is assigned to the i^{th} block

d_{vi} : 1 if vertex v dominates block i

Objective Function & Constraints

$$\begin{array}{ll} \min & 0 \quad \text{(no objective)} \\ \text{s.t.} & \sum_{i=1}^k x_{vi} = 1, \quad \forall v \in V \quad \text{(each vertex is assigned to one block)} \\ & \sum_{v \in V} x_{vi} \geq 1 \quad \forall i \in \pi \quad \text{(no empty blocks)} \\ & x_{ui} + d_{vi} \leq 1 \quad \{\forall u, v \in V \mid \{u, v\} \notin E\}, i \in \pi \quad \text{(domination condition)} \\ & \sum_{i=1}^k d_{vi} \geq 1 \quad \forall v \in V \quad \text{(each vertex dominates at least one block)} \\ & \sum_{v \in V} x_{vi} \geq \sum_{v \in V} x_{v,i+1} \quad \forall i \in \{1, 2, \dots, k-1\} \quad \text{(blocks are used in order)} \\ & x_{vi}, d_{vi} \quad \forall v \in V, i \in \pi \quad \text{(binary variables)} \end{array}$$