

American Society of Agronomy Crop Science Society of America Soil Science Society of America

[Home](#) » [Publications](#) » [Vadose Zone Journal](#)

Vadose Zone Journal Abstract - ORIGINAL RESEARCH PAPERS

Fluid Flow, Heat Transfer, and Solute Transport at Nuclear Waste Storage Tanks in the Hanford Vadose Zone

Vadose Zone Journal

[Add to Binder](#) [View My Binders](#)

This article in VZJ

Vol. 1 No. 1, p. 68-88

Received: Dec 3, 2001
Published: Aug, 2002

* Corresponding author(s):
K_Pruess@lbl.gov

View

- »Abstract
- »Full Text
- »Full Text (PDF)
- »Table of Contents

Download

- »Citation

Alerts

- »Sign up for TOC email alerts

Permissions

- [Request Permissions](#)

Share

- »Email this content
- »Recommend to librarian
- [f Share](#)
- [Tweet](#)

doi:10.2136/vzj2002.6800

Karsten Pruess ^a, Steve Yabusaki ^b, Carl Steefel ^c and Peter Lichtner ^d

[+ Author Affiliations](#)

Abstract

At the Hanford Site, highly radioactive and chemically aggressive waste fluids have leaked from underground storage tanks into the vadose zone. This paper addresses hydrogeological issues at the 241-SX tank farm, especially focusing on Tank SX-108, which is one of the highest heat load, supernate density and ionic strength tanks at Hanford and a known leaker. The behavior of contaminants in the unsaturated zone near SX-108 is determined by an interplay of multiphase fluid flow and heat transfer processes with reactive chemical transport in a complex geological setting. Numerical simulation studies were performed to obtain a better understanding of mass and energy transport in the unique hydrogeologic system created by the SX tank farm. Problem parameters are patterned after conditions at Tank SX-108, and measured data were used whenever possible. Borrowing from techniques developed in geothermal and petroleum reservoir engineering, our simulations feature a comprehensive description of multiphase processes, including boiling and condensation phenomena, and precipitation and dissolution of solids. We find that the thermal perturbation from the tank causes large-scale redistribution of moisture and alters water seepage patterns. During periods of high heat load, fluid and heat flow near the tank are dominated by vapor-liquid counterflow (heat pipe), which provides a much more efficient mechanism than heat conduction for dissipating tank heat. The heat pipe mechanism is also very effective in concentrating dissolved solids near the heat source, where salts may precipitate even if they were only present in small concentrations in ambient fluids. Tank leaks that released aqueous fluids of high ionic strength into the vadose zone were also modeled. The heat load causes formation dry-out beneath the tank, which is accompanied by precipitation of solutes. These may become remobilized at a later time when tank temperatures decline and previously dried out regions are rewetted. Simulated temperature and moisture distributions compare well with borehole measurements performed in 2000. The temperature maximum observed beneath Tank SX-108 can be explained from past thermal history of the tank; it is not necessary to invoke heat generation from leaked radioactive contaminants. A novel composite medium model is used to explore effects of moisture tension-dependent anisotropy, which is shown to have important impacts on fluid flow and solute transport in the Hanford sediments.

Please view the pdf by using the Full Text (PDF) link under 'View' to the left.

Copyright © 2002. Soil Science Society. Published in Vadose Zone Journal1:68–88.

Select Language | ▼

Search Publications

Submit

[Advanced Search](#)

Member Login

Email Address

Password

Log In

[forgot password](#)

[Create Account](#)

Publications

Vadose Zone Journal	
Articles Published	2118
Total Downloads	1194375
Average downloads per article	563

Article History	
Downloads (6 weeks)	7
Downloads (1 year)	45
Downloads (cumulative)	497

Cited By

Experimental study of dynamic effects in moisture transfer in building materials
International Journal of Heat and Mass Transfer
2016 98
Experimental determination of barite dissolution and precipitation rates as a function of temperature and aqueous fluid

[composition](#)
[Geochimica et Cosmochimica Acta](#)
[2016 194](#)
[Thermal diffusion of water vapour in porous materials: Fact or fiction?](#)
[International Journal of Heat and Mass Transfer](#)
[2011 54:7-8](#)
[Competitive Incorporation of Perrhenate and Nitrate into Sodalite](#)
[Environmental Science & Technology](#)
[2014 48:21](#)
[Mineral dissolution and secondary precipitation on quartz sand in simulated Hanford tank solutions affecting subsurface porosity](#)
[Journal of Hydrology](#)
[2012 472-473](#)
[Heat as a tracer to quantify processes and properties in the vadose zone: A review](#)
[Earth-Science Reviews](#)
[2016 159](#)

Journal Links

[Author Resources](#)
[Editor/Reviewer Resources](#)
[Editorial Board](#)
[Special Sections](#)
[New Content Alerts](#)
[Browse All Journals](#)
[Permissions](#)
[Journal Usage Statistics](#)
[Manuscript Invoice Payment](#)
[Submissions](#)
[Content Questions](#)
[Subscription Questions](#)



[Subsurface Placement of Fertilizer Limits Nutrient Leaching](#) | [Read More](#)

[Heat Generating Nuclear Waste in Salt](#) | [Read More](#)

[Waste-rock Weathering Restricted by Oxygen Supply](#) | [Read More](#)

[Hydrological Observatories Featured in VZJ Special Section](#) | [Read More](#)

[More Highlights](#)

© Copyright 2019 - [Copyright Information](#), [Privacy Statement](#), and [Terms of Use](#)
5585 Guilford Road | Madison, WI 53711-5801 | 608-273-8080 | Fax 608-273-2021
[Certification](#): 608-273-8085 | Fax 608-273-2081

[Contact Us](#)