
COMMERCIAL PART LIST			
ITEM	QTY	MIL SPEC/VENDOR PART NUMBER	DESCRIPTION
C1	1	3-906 E1267-80	O-RING, .078 WIDE X .468 ID, EPDM (PARKER)
C2	1	51410-2-06-1-V-TF06-C-GY	QUICK-DISCONNECT NIPPLE (PREECE INC.)
C3	1	1/4 GG-SS	STRAIGHT THREAD ADAPTOR 1/4 NPT TO 1/4 NPT (PARKER)
C4	1	1/4-6 FHG5-S	FEMALE STRAIGHT THREAD ADAPTER 1/4 NPT / 9/16-18 SAE-ORB (PARKER)
C5	1	9796T206	MULTIPURPOSE GAUGE 0-200 PSI PLASTIC CASE, 2" DIAL, 1/4 NPT THREAD (McMASTER)
C6	A/R	MIL-PRF-27617	KRYTOX 240AC, TYPE III LUBRICANT (DUPONT)
C7	A/R	7346A11	PIPE THREAD SEALANT TAPE, 1/4 IN (MCMASTER-CARR)

NOTES:

1. MATERIAL CERTIFICATION REQUIRED PER QUALITY LEVEL SPECIFIED IN WORK ORDER/SOW.
2. TIGHTEN FASTENERS SNUG TIGHT PER ESTABLISHED PROCEDURES.
3. APPLY TEFLON TAPE TO MALE THREADS OF PIPE FITTINGS, BEGINNING TWO THREADS FROM END OF FITTING. WRAP TAPE TIGHTLY IN DIRECTION OF THREADS 2-3 FULL WRAPS. INSTALL INTO FEMALE NPT PORTS. AFTER HAND TIGHT ENGAGEMENT, TIGHTEN 2-4 FULL TURNS.
4. TIGHTEN FLUID FITTING PER MANUFACTURER'S SPECIFICATIONS
5. APPLY THIN FILM OF LUBRICANT TO O-RING PRIOR TO INSTALLATION
6. CLEAN ALL SURFACES WITH ISOPROPYL ALCOHOL AND LET AIR DRY. WIPE WITH CLEAN COTTON SWABS AND/OR LINT-FREE CLOTH.
7. HANDLE WITH CLEAN, LINT-FREE GLOVES.
8. BEFORE STORAGE, PROTECT WITH CONTAMINATION BARRIER. USE CLEAN, NEW, TRANSPARENT POLYETHYLENE BAG FOR SMALL ITEMS OR 4 MIL THICK MINIMUM POLYETHYLENE SHEET AND SEAL. MARK PART NUMBER, A DASH, AND A SERIAL/LOT NUMBER AS SPECIFIED IN WORK ORDER/SOW, BY TAGGING PER SAE-AS478-35D.



REV	DESCRIPTION	APPROVED
1	INITIAL REPOSITORY RELEASE	KJB

REVISION HISTORY

END ITEM

NEXT ASSEMBLY

UNLESS OTHERWISE SPECIFIED:
1. ALL DIMENSIONS ARE IN INCHES
2. BREAK EDGES .010-.020
3. INSIDE CORNERS R.02 MAX
4. LINEAR TOLERANCES:
   .X ± .03
   .XX ± .01
   .XXX ± .005
5. ANGULAR TOLERANCE ± .5°

THIRD ANGLE PROJECTION

THIS DRAWING IS UNDER CONFIGURATION CONTROL: DO NOT REVISE WITHOUT AN APPROVED ECO.

APPROVED: _____

PRIOR TO USE, CHECK WITH CONFIGURATION MANAGEMENT FOR ANY OUTSTANDING ECOS.

DESIGNER		QUALITY	
REVIEWER		MATERIALS	
MECHANICAL		PROJ LEAD	
ELECTRICAL			
STRUCTURAL			
SAFETY			

DIMENSIONS AND TOLERANCING PER ASME Y14.5M-1994

CONTRACT NUMBER: NNC14CA02C
PROJECT CODE: S2-BT3-01

ZIN TECHNOLOGIES
6745 ENGLE ROAD
AIRPORT EXECUTIVE PARK
CLEVELAND, OHIO 44130
(440) 625-2200
www.zin-tech.com

NATIONAL AERONAUTICS AND SPACE ADMINISTRATION
JOHN H. GLENN RESEARCH CENTER
LEWIS FIELD
CLEVELAND, OHIO

TITLE

WATER HOSE PRESSURE GAUGE ASSEMBLY

SIZE	CAGE CODE	DWG NO	REV
C	0SG68	S1101MGA6062	1

SCALE	INITIAL REL DATE	SHEET
1/1		1 OF 1

RELEASE LEVEL: WORKING
MODEL: S1101MGA6062

PRO/E VERSION: Creo 2.0

DWG NO S1101MGA6062 SH 1 REV 1

ZIN_C_2012.frm