# Tracey - EEM Report

Toby McConnell

May 2, 2026

# Chapter 1

# Market Analysis and Competition Analysis

## 1.1 Introduction and Executive Summary

The business proposed in the following paper is based around an adapted version of the Formula Student car that has been designed for the sprint event into a high-performance modified testing vehicle developed as a multi-purpose platform for advanced brake testing and autonomous vehicle (AV) validation in a business-to-business context. The following sections introduce our core value proposition and apply a market segmentation framework to justify a strategic focus on the autonomous sector. Finally, this analysis identifies high-priority entry points and target customers through competitive landscape evaluation, personas, and user journey mapping.

## 1.2 Product Overview and Value Proposition

The operational foundation of this service is a modified high-dynamic vehicle that functions as a moving target for AV systems, recreating complex real-world scenarios where rapid braking, turning, or emergency decision-making is required. To transform the base FS design into a regulated testing platform, the architecture will be updated with sophisticated data-logging features and interchangeable body shells for varied test environments.

A central element of this proposal is the inheritance of the vehicle's original design constraints. Having been designed to meet strict Formula Student regulations—including a cockpit sized for a 95th percentile male—the vehicle possesses features that are strictly redundant for an unmanned testing platform. While these constraints present a potential competitive disadvantage, they are a fundamental reality of the base car's origin. Consequently, following supervisor guidance, this business proposal proceeds with the assumption of a base product utilizing the existing high-performance supercapacitor accumulator, powertrain, and wheel design, while aiming to overlook the specific drawbacks of the FS regulatory framework in the long-term business model.

Our service-based model allows clients to access these advanced testing capabilities without the capital expenditure or maintenance burdens of in-house facilities. This value proposition is structured around three primary benefits:

- **High-speed repeatability** – The service enables consistent braking tests due to the supercapacitor power supply and can operate under extreme conditions enabled by tyre and chassis design. This improves validation accuracy and reduces uncertainty in performance evaluation.
- **Adaptable testing architecture** – Modular configuration with different shells allowing clients to simulate different braking conditions and edge cases without the overhead of large-scale facility changes.
- **Real-world scenario simulation** – Physical testing reduces reliance on software-only validation and helps close the simulation-to-reality gap in autonomous systems development. These tests provide a more accurate representation of real-world decision-making, braking, and crash scenarios, which simulations cannot fully replicate. This makes the service particularly valuable for final-stage vehicle validation.

By offering faster turnaround and reduced infrastructure costs, the service acts as a ”pain reliever” for slow testing cycles and a ”gain creator” for safety validation confidence. This strategic positioning forms the basis for the market segmentation and customer targeting discussed in the subsequent sections.

## 1.3 Market Segmentation Strategy Overview

Market segmentation is essential for identifying groups of customers who seek similar benefits and features from a product. Rather than treating the market as homogeneous, segmentation enables organisations to tailor value propositions and targeting strategies to distinct user needs. A strong segmentation should be mutually exclusive, collectively exhaustive and align with the product’s core value proposition.

In this project, demographic segmentation is not appropriate due to the business-to-business nature of the proposed testing platform targeting at organisations rather than individuals, meaning factors such as age or gender provide limited strategic insight. Instead, a hybrid segmentation approach is adopted, combining user-based segmentation with benefits-based segmentation and occasion-based segmentation. This allows identification of both the types of organisations using the product and the specific outcomes they seek.

- **User-based segmentation:** Categorizes customers by their role within the automotive ecosystem. This includes regulatory agencies, Original Equipment Manufacturers (OEMs), EV startups, and autonomous technology firms. For example, regulatory bodies prioritize certification reliability, whereas AI validation teams require rapid iteration and flexibility.
- **Benefits-based segmentation:** This focuses on the value delivered by the platform. Key benefits include high-speed repeatability, real-world testing conditions, adaptability of test scenarios, and cost efficiency relative to large proving grounds. These benefits do not hold equal importance across all user groups, helping identify customers most aligned with the product's capabilities.
- **Occasion-based segmentation:** Testing needs vary depending on context, such as regulatory certification, early-stage research and development, or edge-case AI validation. Each occasion places different emphasis on flexibility, repeatability, and testing speed.

Combining these approaches enables a structured segmentation strategy. This hybrid framework ensures that segments are defined both by who uses the product and by why they value it and forms the basis for the following market analysis and comparisons.

## 1.4 Market Option 1: Government Brake Testing Market

### 1.4.1 Market Overview and Size Estimation

The government brake testing market includes organisations responsible for validating vehicle braking performance against safety standards. This market spans multiple stages, each relying on established methods designed to prioritise repeatability and regulatory acceptance:

- **Manufacturer pre-certification testing:** Automotive manufacturers typically conduct in–house braking validation before certification using track–based testing, dynamometers, and simulation tools such as finite element modelling (FEM) with companies like Ansys and MSC Software.
- **Government-regulated certification testing:** Certification bodies, like the Driver and Vehicle Standards Agency (DVSA) in the UK, use standardised equipment such as roller brake testers and calibrated decelerometers to measure braking performance with equipment suppliers such as MAHA Maschinenbau Haldenwang providing certified systems

- **Periodic roadworthiness inspection (e.g. MOT testing):** These tests typically use compact roller brake testers or portable decelerometers rather than track-based testing. Suppliers such as Tecalemit Garage Equipment and Capelec provide brake testing hardware commonly used in inspection centres.

To estimate the size of this market we use a top-down estimation approach. The global brake tester market is estimated at $\sim$ 1.5 billion USD [1]. As the majority of brake testing equipment is used in manufacturer validation, certification testing, and periodic inspection, this segment is estimated to account for approximatly 40% of the total brake testing market. Therefore:

$$\begin{aligned} \text{Gov. Brake Testing Market} &= 1.5 \times 0.40 \\ &= 0.60 \text{ billion USD} \end{aligned} \tag{1.4.1}$$

This yields an estimated addressable market of approximately $600 million globally.

### 1.4.2 Market Segmentation

User-based segmentation identifies regulatory agencies, certification laboratories, and inspection operators as primary customers operating within strict compliance frameworks. Benefits-based segmentation shows a strong focus on reliability, standardisation, and regulatory acceptance, with limited emphasis on flexibility. Occasion-based segmentation highlights that testing occurs primarily during certification and compliance checks, requiring fixed procedures Together, these segmentation perspectives indicate limited alignment between the market's priorities and the platform's core value proposition.

### 1.4.3 Commercial Challenges

This market also presents significant commercial challenges. Entry barriers are high due to certification requirements and the need to demonstrate equivalence with established methods, while procurement cycles are long and complex. Product—market fit is also limited. Customers prioritise consistency and risk minimisation, whereas the platform's core advantages lie in flexibility and adaptability. Scalability is constrained by a small customer base and varying international regulations, increasing the need for customisation and slowing expansion. Overall, despite functional relevance, high barriers, weak alignment, and limited scalability make this market unattractive for an early-stage product.

## 1.5 Market Option 2: AI and Autonomous Vehicle Testing Market

### 1.5.1 Market Overview and Size Estimation

The AI and autonomous vehicle testing market consists of automotive manufacturers, electric vehicle startups, and technology firms developing automated driving systems that require validation in complex real-world scenarios. As investment in automated driving has increased, organisations have placed greater emphasis on testing environments capable of validating decision-making, perception systems, and emergency braking behaviour.

The autonomous vehicle testing market can be estimated using a top-down approach. The global autonomous vehicle market is valued at ∼$68.09 billion USD [2]. Automotive manufacturers typically allocate approximately 5–10% of revenue to research and development, with higher values observed in innovation-intensive areas such as autonomous driving. A value of 10% is therefore assumed:

$$\begin{aligned} \text{R\&D Budget} &= 68.09 \times 0.10 \\ &= 6.81 \text{ billion USD} \end{aligned} \tag{1.5.1}$$

Testing and validation activities often account for ∼20–30% [3] of development effort in safety-critical automotive systems. Using a midpoint value of 25%, the addressable testing market can be estimated.

$$\begin{aligned} \text{Testing Market} &= 6.81 \times 0.25 \\ &= 1.70 \text{ billion USD} \end{aligned} \tag{1.5.2}$$

Therefore, the autonomous vehicle testing market is estimated at approximately $1.5–2 billion globally and is projected to grow at a compound annual growth rate (CAGR) of 19.9% [2] from 2025 to 2030.

### 1.5.2 Market Segmentation

User-based segmentation identifies autonomous vehicle R&D teams, EV startups, and automotive innovation divisions as primary customers. These organisations are actively developing automated driving systems and require frequent testing during development. Compared with regulatory bodies, they typically have faster decision-making processes and a greater willingness to adopt new testing technologies. Benefits-based segmentation highlights that customers prioritise flexibility, rapid iteration, and real-world validation. Autonomous systems must be tested across a wide range of edge cases, including emergency braking scenarios. These requirements align closely with a platform capable of repeatable high-speed testing and configurable conditions. Occasion-based segmenta-

tion further reinforces this alignment. Testing occurs during algorithm validation, edge-case scenario development, and system integration phases. These occasions require adaptable testing environments that complement simulation-based workflows. A platform that enables repeatable physical testing under configurable conditions directly supports these activities. Overall, segmentation analysis indicates strong alignment between this market's priorities and the platform's core value proposition. Further analysis in the following sections will also evaluate the strategic fit and competitive positioning within this segment.

## 1.6 Competitive Landscape Analysis

### 1.6.1 Macro Analysis: Porter's 5 Forces

The following analysis applies Porter's Five Forces framework to evaluate the macro-level industry pressures influencing the proposed platform.

| Force | Strength | Analysis |
|---|---|---|
| Threat of New Entrants | Low–Moderate | High capital requirements, specialised engineering expertise, and the need for industry credibility and safety validation limit new entrants. However, the nascent nature of the market reduces accumulated experience, creating some opportunity for new players. |
| Bargaining Power of Suppliers | Moderate | Some high-performance components (e.g. sensors, braking systems) are specialised, increasing dependency, though broader automotive supply chains provide alternative sourcing options. |
| Bargaining Power of Buyers | High | OEMs and technology firms possess significant resources and access to alternative testing methods, increasing price sensitivity. Buyer power is further reinforced by regulatory stakeholders and testbed operators, who influence which testing approaches are accepted. |
| Threat of Substitutes | High | Alternative testing methods, including simulation, proving grounds, and dynamometer testing, act as substitutes by offering cost or flexibility advantages, although often with reduced physical realism. |
| Competitive Rivalry | Moderate | Competition is driven by a mix of testing providers, consultancies, and in-house capabilities. While few direct equivalents exist, indirect competition is strong, requiring clear differentiation in service offering. |

**Table 1.1:** Porter's Five Forces analysis of the advanced vehicle testing industry

The analysis indicates that high buyer power and the threat of substitutes—primarily software-based simulation—represent the most significant commercial hurdles. To mitigate these pressures, the platform must transition from a standard equipment vendor to an integrated validation partner. By providing "ground-truth" physical data that digital environments cannot fully replicate, the service reduces the efficacy of substitutes and establishes a specialized competitive niche. Furthermore, as the autonomous vehicle testing market remains nascent, few firms have accumulated significant long-term operational experience. This limits the extent of established best practices, creating a distinct opportunity for new entrants to shape emerging standards.

### 1.6.2 Micro Analysis: Direct Competitors

Having established the broader industry dynamics at a macro level, the analysis now turns to the micro-level competitive landscape, focusing on key direct competitors operating within this space. Direct competitors include traditional brake dynamometers, automotive proving grounds, and dedicated testing facilities.

| Competitor | Solution Type | Competitive Implication |
|---|---|---|
| AB Dynamics [4] | Driving robots and ADAS test platforms | Provides highly repeatable automated vehicle control for braking and ADAS scenarios, but typically operates within controlled speeds and requires supporting infrastructure. |
| 4activeSystems [5] | Soft crash targets and pedestrian dummies | Enables realistic safety and braking validation scenarios but does not provide full vehicle dynamic testing capability. |
| Humanetics | Anthropomorphic test devices and robotics | Industry standard safety validation tools focused on component-level testing rather than full dynamic vehicle performance. |
| UTAC [6] | Full-scale proving ground facilitys | Offers high realism testing but is expensive and difficult to reconfigure quickly, limiting iteration speed. |
| HORIBA [7] | Brake dynamometers | Provides controlled laboratory testing but lacks real-world high-speed vehicle dynamics. |
| AVL List | Vehicle testing and dynamometer systems | Established engineering validation systems with strong credibility but limited flexibility for rapid scenario adaptation. |

**Table 1.2:** Direct Competitors in Physical Vehicle Testing

### 1.6.3 Micro Analysis: Indirect Competitors

Indirect competitors include software-based simulation platforms and in-house OEM testing systems.

| Competitor Type | Example Providers | Competitive Implication |
|---|---|---|
| Software Simulation Platforms | NVIDIA [8], dSPACE | Provide flexible virtual testing environments allowing rapid iteration but lack physical realism for braking dynamics validation. |
| Physics-based Simulation | Ansys [9] | Enables digital twin modelling and early-stage validation but cannot capture full real-world vehicle behaviour. |
| In-house OEM Testing Rigs | Tesla, Toyota | Tailored testing infrastructure with strong integration but requires high capital investment and limited flexibility. |
| Contract Proving Ground Services | Applus IDIADA, UTAC [6] | High realism physical testing but expensive and constrained by scheduling limitations. |

**Table 1.3:** Indirect Competitors in Autonomous Vehicle Validation

These indirect competitors highlight the broader validation ecosystem, where organisations combine multiple tools to achieve comprehensive testing. The proposed platform aims to complement rather than replace these solutions by providing a hybrid physical testing capability.

## 1.7 Strategic Positioning

To visualise the competitive landscape, a market segmentation map can be constructed based on two key dimensions: testing realism and scenario flexibility. This map (Figure 1.1) helps identify

where different solutions are positioned and where gaps exist in the market.




**Figure 1.1:** Market Segmentation Map for Autonomous Vehicle Validation Solutions

This analysis highlights a gap in the upper-right region, where both realism and flexibility are high. Proving ground facilities (e.g. UTAC) occupy the high-realism but low-flexibility quadrant, while simulation platforms (e.g. NVIDIA) provide high flexibility but limited physical fidelity. Laboratory dynamometer systems typically fall within the low-flexibility, moderate-realism region.

The proposed product is positioned within this high-realism, high-flexibility space, addressing a clear gap in the market. While there are close competitors such as AB Dynamics and 4activeSystems, these solutions generally focus on specific testing scenarios or require supporting infrastructure. In contrast, the proposed platform offers a more generalised and adaptable testing environment, enabling a wider range of use cases within a single system.

Crucially, the platform must be positioned not only as a testing solution for manufacturers, but as an integrated validation tool aligned with the requirements of regulatory bodies and testbed operators. Acceptance by these stakeholders is essential for market access, as they effectively act as gatekeepers to industry adoption.

## 1.8 Target Market Selection

Following the strategic positioning analysis, a clear target market must be defined. The segmentation map indicates strongest alignment within the AI and autonomous vehicle validation space,

where organisations prioritise flexible, high-realism testing environments.
Within this market, further distinction is required to identify the most suitable entry points. Three primary customer groups are considered, differing in procurement complexity, risk tolerance, infrastructure ownership, and testing requirements.

### 1.8.1 Large Automotive OEMs

Established automotive manufacturers developing autonomous driving capabilities, such as BMW, Toyota, Volkswagen Group, and Ford, represent a significant potential customer group. These organisations typically operate large R&D divisions and already maintain extensive validation infrastructure. They tend to prioritise reliability, integration with existing workflows, and long-term supplier relationships, particularly where testing data must fit into established validation pipelines.
However, procurement processes within large OEMs are often complex and involve multiple stakeholders. This can lead to long adoption timelines and higher barriers for new technologies. These organisations are also generally risk-averse and prefer proven suppliers.

### 1.8.2 Electric Vehicle Startups

Electric vehicle (EV) startups, like Rivian, Lucid Motors, NIO, and Polestar, operate with smaller teams and shorter development cycles. These organisations often prioritise rapid iteration, flexibility and cost efficiency and are more willing to adopt novel testing solutions that provide competitive advantage. Also, unlike established OEMs they lack extensive in-house testing infrastructure, increasing reliance on external validation platforms. Decision-making processes are also typically faster, allowing pilot projects and early adoption. It is important to note that startups may have more constrained budgets, limiting large-scale deployment but they still offer strong opportunities for early validation, data generation, and demonstration of capability.

### 1.8.3 Independent AI Technology Firms

Companies focused on autonomous driving software development such as Waymo, Cruise, and Mobileye represent another potential segment. Unlike automotive manufacturers, these firms often do not own physical testing infrastructure, increasing reliance on external platforms that bridge simulation and real-world validation.
Similar to EV startups, these organisations are typically innovation-driven and more willing to trial new technologies. Procurement processes are generally simpler than those of large OEMs, enabling faster engagement. However, the proposed platform is specialised for high-speed braking

and physical validation, and may not be suitable for firms requiring broader testing across multiple domains. As a result, potential customers must be carefully selected, focusing on companies with a strong emphasis on real-world safety validation, such as Waymo, where physical testing of edge-case driving scenarios is critical to system verification.

### 1.8.4 Targeting Strategy

Comparing these segments highlights differences in adoption speed, revenue potential, and strategic value. EV startups offer the fastest entry opportunities due to their flexibility and need for external testing solutions, and are well positioned as early adopters, as they are typically more willing to engage with emerging technologies and tolerate early-stage limitations in exchange for potential competitive advantage. Independent AI technology firms should be considered a secondary entry-level customer group; while their priorities align with the platform's strengths, the product does not fully match broader AI testing requirements. Despite slower adoption, OEMs represent high-value long-term customers. If the platform is successfully integrated into early segments and credibility is established, OEMs should then be targeted for long-term contracts.

Based on this analysis, a phased targeting strategy is appropriate. Initial focus should be placed on EV startups and some specific AI technology firms to generate validation data, refine the platform, and establish market credibility. This early adoption can then support engagement with large OEMs as long-term strategic customers. This approach balances rapid entry with scalable growth.

### 1.8.5 Servicable Obtainable Market (SOM) Estimation

Having established a phased targeting strategy, the market opportunity can be refined by estimating the Serviceable Available Market (SAM) and the Serviceable Obtainable Market (SOM). While the total addressable market is global, the initial commercial focus is centered entirely on the UK market, serving as a strategic beachhead for the platform.

Not all testing activities require high-performance physical validation. Assuming that approximately 30% of the global testing demand involves complex, high-speed, or safety-critical scenarios aligned with the proposed platform's capabilities, the global SAM is estimated as:

$$\text{Global SAM} = 1.70 \times 0.30 \quad = 0.51 \text{ billion USD} \tag{1.8.1}$$

As an early-stage entrant, the strategy prioritizes establishing a dominant presence within the UK's automotive and aerospace clusters before international expansion. By targeting a 5

$$\text{Serviceable Obtainable Market (SOM)} = 0.51 \times 0.05 \quad = 0.026 \text{ billion USD} \tag{1.8.2}$$

This represents a realistic initial revenue opportunity, reflecting a focused geographic targeting strategy within the UK and the inherent constraints of entering a nascent, rapidly evolving market.

## 1.9 Personas and User Journey

To help humanize the market segments and guide product development, three personas have been developed. These represent the specific behaviors, motivations, and pain points of key stakeholders, grounding the platform's value proposition in the practical requirements of vehicle validation:

### Persona 1

**Professional Profile**

**Name/Age**: Kelly Brazier (36)
**Role**: Autonomous validation engineer at an EV startup

**Strategic Drivers**

Needs to validate AI performance across diverse "edge cases" to maintain a competitive lead

**Key Pains**

Inaccuracy of software-only simulation and prohibitive costs of traditional proving grounds.

**Business Environment**

Works in agile teams with short development cycles and zero access to in-house testing tracks

**Operational KPIs (Key Performance Indicators)**

System deployment speed and high-fidelity AI performance data

**Validation Requirements**

**Experience:** Requires a flexible "on-demand" testing service that compliments situation workflow

**End Goals:** Accelerate the transition from software-only validation to physical deployment

**Repeatability:** Demands high consistency between test runs to ensure that any variation in results is due to AI software changes, not platform mechanical variance.

### Persona 2

**Professional Profile**

**Name/Age**: Daniel Carter (44)
**Role**: Procurement Manager at an Independent AI Technology Firm

**Strategic Drivers**

Achieving cost-effective validation and reducing organizational Capital Expenditure

**Key Pains**

Difficulty justifying large infrastructure investments and comparing complex testing service quotes

**Business Environment**

Manages external testing contracts for firms that do not own physical infrastructure

**Operational KPIs (Key Performance Indicators)**

Measurable ROI on testing spend and supply-chain risk mitigation.

**Validation Requirements**

**Experience:** Requires a platform that provides clear performance metrics and transparent, unassailable data outputs for internal auditing.

**Technical Priority:** Needs standardized data reporting formats that allow for direct comparison against simulation-based results to verify accuracy.

**End Goals:** Selection of strategic testing partners that minimize the operational burden and costs of in-house facility maintenance

These personas highlight different priorities across stakeholders and support user-centred design decisions. They also reinforce the segmentation analysis by demonstrating how value proposition elements align with specific customer needs.

Integrating the commercial targets identified in Section 1.9 with the broader stakeholder ecosystem analyzed in Section 2 REFERENCE, the following journey mapping highlights how the product navigates both market adoption and regulatory validation. It helps identify pain points, decision stages, and opportunities for value creation. The user journey for the platform adoption process is structured as follows:

**Table 1.4:** User Journey

| Phase | Action | Primary Stakeholder |
|---|---|---|
| **Discovery** | Identifies simulation gaps in emergency braking and edge-case scenarios. | Kelly (Engineer) |
| **Evaluation** | Conducts cost-benefit analysis vs. traditional proving-ground infrastructure. | Daniel (Procurement) |
| **Integration** | Technical synchronization of AI software with the platform's modular hardware. | Kelly & Ops Team |
| **Execution** | High-speed repeatable braking tests conducted within secure, state-backed track environments. | Kelly & Testbed Ops Director |
| **Expansion** | Integration of validation data into official safety and regulatory certifications. | Independent Liability Assessor |

## 1.10 Role of Users in Development

Understanding how target customers influence product development is important in a market where testing workflows, integration requirements, and validation priorities vary across organisations. During early development, a user-based approach is most appropriate. At this stage, users act as informants, providing insights into testing challenges and validation requirements. Interviews with engineers, safety specialists, and validation teams help identify key needs such as repeatability, data integration, and scenario flexibility, ensuring the product evolves to meet customer requirements. As the product develops, a co-design approach can be adopted, with users contributing to testing features and interface requirements. For example, validation engineers may suggest specific braking scenarios or data outputs for AI model verification. This ensures alignment with real-world workflows. In later stages, elements of user-led design may emerge, with organisations developing their own testing scenarios and applications. This increases adoption and supports continued innovation. However, reliance on user input has limitations. Users may prioritise incremental improvements over transformative solutions, potentially constraining innovation. User participation should therefore be balanced with strategic foresight to address both current and emerging validation challenges.

## 1.11 Intellectual Property and Barriers to Entry

Intellectual property plays a role in protecting the commercial value of the proposed testing platform, although broad patent protection may be limited. The core concept combines existing elements, such as a high-performance vehicle, modular testing configuration, and data acquisition systems, reducing the scope for strong standalone patents. While specific mechanical interfaces or testing architectures may be protectable, alternative implementations remain feasible. Competitive advantage is therefore more likely to rely on trade secrets and accumulated testing data. Proprietary scenario configurations, control strategies, and performance datasets can be retained internally. Over time, repeated high-speed testing generates valuable data, improving validation accuracy and creating switching costs. Additional barriers arise from the specialised engineering integration required and the need for early partnerships with automotive manufacturers. As a result, IP should be viewed as supportive rather than primary, with advantage driven by technical know-how, data, and early market adoption.

## 1.12 Risk Analysis and Strategic Trade-offs

A range of risks must be considered when assessing the feasibility and commercialisation of the product.

### 1.12.1 Initial Product Development Risk

When adapting our FS car for integration with the testing platform, modifications will be required to accommodate data acquisition systems, safety redundancies, modular test interfaces, and repeatable control systems. These adaptations could introduce additional engineering complexity and extend development timelines. Furthermore, user-based development may reveal requirements not anticipated during the initial design phase, potentially requiring redesign of key subsystems.

### 1.12.2 Market Risk

The nascent nature of the market introduces a degree of uncertainty in demand, technology evolution, and regulatory direction. Demand for physical autonomous vehicle validation testing is closely linked to investment trends in automated driving technologies. Furthemore, a reduction in R&D spending or a slowdown in autonomous vehicle deployment could reduce demand for specialised

testing platforms. This risk is particularly relevant given the cyclical nature of investment in emerging technologies.
This risk can be mitigated by targeting multiple customer groups. EV startups and AI technology firms may experience different investment cycles, reducing reliance on a single segment. However, a broader downturn in autonomous vehicle investment would still impact overall demand.

### 1.12.3 Technological Risk

Advances in software simulation may reduce the need for physical testing, acting as a potential substitute. If simulation tools achieve sufficient realism, the platform's value proposition may weaken.
In this scenario, the platform could focus on scenarios where physical validation remains essential, such as extreme braking conditions, tyre–road interactions, environmental variability, and real–time decision–making under uncertain conditions. However, a reduction in demand may still occur as the overall market for physical validation decreases.

### 1.12.4 Strategy and Operational Risk

Developing and maintaining a high-performance testing platform requires significant engineering resources, and operational costs may exceed initial estimates. This risk is closely linked to the chosen market entry strategy. Focusing on EV startups enables faster adoption and early validation but may limit short-term revenue due to smaller budgets. Conversely, targeting large OEMs offers higher contract value but involves longer procurement cycles and higher barriers to entry.
The proposed strategy prioritises early adoption among EV startups and selected AI technology firms to generate validation data and establish credibility. This foundation can then support engagement with larger OEMs. However, if the balance is misjudged, risks emerge. Over-reliance on startups may slow revenue growth and place strain on operational resources, while premature focus on OEMs may delay market entry and prolong development without customer validation. Careful sequencing of customer engagement is therefore essential.

### 1.12.5 Regulatory Risk

Autonomous vehicles operate within a rapidly evolving regulatory environment. Changes in safety certification requirements could affect testing methodologies and validation expectations. If regulatory bodies require specific validation procedures, adaptation may be necessary. Early engagement with industry stakeholders can reduce this risk and may provide a competitive advantage if the platform aligns quickly with emerging standards, positioning it as a preferred testing solution.

### 1.12.6 Competitive Risk

Competitors may develop alternative hybrid testing solutions that combine physical testing with configurable scenarios. Established testing equipment providers may leverage existing customer relationships and infrastructure to introduce similar offerings. This could reduce differentiation and increase price competition.

To maintain a competitive advantage, the platform must emphasise flexibility and rapid, repeatable testing iterations. Accumulating validation data and continuously refining testing scenarios through user-influenced development can further strengthen differentiation and create barriers to entry.

## 1.13 Conclusion

The proposed platform fills a critical market gap by combining high realism with scenario flexibility for autonomous vehicle validation. With an estimated initial UK SOM of $26 million, the business is positioned to capture a high-value niche by prioritizing agile EV startups as early adopters. To realize this commercial opportunity, the following section outlines the Strategy and Stakeholder Analysis required to manage industry gatekeepers and execute the long-term project roadmap. CHECK WITH PAUL!

## References


[1] *Brake Tester Market Size, Share and Forecast*. Pro Market Reports. 2024. URL: https://www.promarketreports.com/reports/brake-tester-232522 (visited on 05/01/2026).

[2] *Autonomous Vehicles Market Size Report*. Grand View Research. 2024. URL: https://www.grandviewresearch.com/industry-analysis/autonomous-vehicles-market (visited on 05/01/2026).

[3] *Testing and Validation: From Hardware Focus to Full Virtualization*. Tech. rep. McKinsey & Company, 2019. URL: https://www.mckinsey.com/~/media/McKinsey/Business%20Functions/Operations/Our%20Insights/Testing%20and%20validation%20From%20hardware%20focus%20to%20full%20virtualization/c0b944bf6469c86cd9ba6d87f078424f.pdf (visited on 05/01/2026).

[4] AB Dynamics. *Autonomous Vehicle Testing Solutions*. 2024. URL: https://www.abdynamics.com/solutions/autonomous-vehicle-testing/ (visited on 05/01/2026).

[5] 4activeSystems. *Automotive Testing Solutions*. 2024. URL: https://www.4activesystems.at (visited on 05/01/2026).

[6] UTAC. *Millbrook Proving Ground (Europe)*. 2024. URL: https://www.utac.com/our-sites/europe/millbrook (visited on 05/01/2026).

[7] Horiba. *Mobility Solutions*. 2024. URL: https://www.horiba.com/int/mobility/ (visited on 05/01/2026).

[8] NVIDIA. *NVIDIA DRIVE Sim: Replicating the Real World in a Virtual Environment*. 2024. URL: https://www.nvidia.com/en-us/self-driving-cars/simulation/ (visited on 05/01/2026).

[9] Ansys. *Ansys Autonomy: Safe Autonomous Vehicle Simulation*. 2024. URL: https://www.ansys.com/products/av-simulation (visited on 05/01/2026).