



targets/basic_routing #163

New issue

Closed

peiqiaoWang opened this issue on Oct 6 · 1 comment



peiqiaoWang commented on Oct 6

When the first installation,I follow the README.

```
cd p4factory/targets/basic_routing/ make bm sudo ./behavioral-model
```

It is successful.

But today,I want to do the same thing,use these code

```
sudo ./behavioral-mode
```

error

```
`wpq@wpq-VirtualBox:~/p4factory/targets/basic_routing$ sudo ./behavioral-model
No PD RPC server address specified, using 127.0.0.1:9090
No listener specified, switch will run in standalone mode

P4 Program: basic_routing

Starting RPC server on port 9090
bmi_port_interface_add(port_mgr, veth_name, n_veth, pcap_filename): ERROR -1 at
main.c:434wpq@wpq-VirtualBox:~/p4factory/targets/basic_routing$`
```

thx

Assignees

No one assigned

Labels

None yet

Projects

None yet

Milestone

No milestone

2 participants



antoninbas commented on Oct 7

Member

Every time you restart your machine, you need to create the veth interfaces again using the script under `tools` . Otherwise you get the error you are seeing because the switch cannot connect to any interface.

antoninbas closed this on Oct 7

Sign up for free

 to join this conversation on GitHub. Already have an account? [Sign in to comment](#)

