
Joins, Subqueries and Indices

Data Retrieval and Performance



SoftUni TeamTechnical Trainers







Software University

https://softuni.bg

Questions





Table of Contents



1. JOINS

Gathering Data From Multiple Tables

2. Subqueries

Query Manipulation on Multiple Levels

3. Indices

Clustered and Non-Clustered Indices






Data from Multiple Tables



Sometimes you need data from several tables:



JOINS



Used to collect data from two or more tables

Types:

INNER JOIN

LEFT JOIN

RIGHT JOIN

FULL JOIN

CROSS JOIN

Cartesian Product



This will produce the Cartesian product:

SELECT last_name, name AS department_name
FROM employees, departments;

■ The result:

last_name	department_name	
Gilbert	Engineering	
Brown	Engineering	
•••	•••	
Gilbert	Sales	
Brown	Sales	

Cartesian Product



- Each row in the first table is paired with all the rows in the second table
- Formed when the join condition is omitted
- To avoid this, always include a valid JOIN condition

Tables




id		first_name	department_id	
	1	Guy	7	,
	2	Kevin	4	ŀ
Z	3	Roberto	1	
	4	Rob	2	<u> </u>
	5	Thierry	NULL	-

id	name		
1	Engineering		
2	Tool Design		
4	Marketing		
•••	•••		
7	Production		

INNER JOIN



Produces a set of records that match in both tables






first_name	name
Guy	Production
Kevin	Marketing
Roberto	Engineering
Rob	Tool Design

Join Conditions

LEFT JOIN



Matches every entry in left table regardless of match in the right




SELECT employees.f	First_name,
departme	ents.name
FROM employees	
LEFT JOIN departme	ents Join Conditions
ON employees.depar	rtment_id =
departments.depart	ment_id;

first_name	name
Guy	Production
Kevin	Marketing
Roberto	Engineering
Rob	Tool Design
Thierry	NULL

RIGHT JOIN



Matches every entry in right table regardless of match in the left




first_name	name
Guy	Production
NULL	Purchasing
N	
NULL	Production

FULL OUTER JOIN



Returns all records in both tables regardless of any match



first_name	name
Guy	Production
The same	
inierry	NULL
Thierry NULL	Purchasing

Cross Join



- Produces a set of associated rows of two tables
 - Multiplication of each row in the first table with each in the second one
 - The result is a Cartesian product when there's no condition in the WHERE clause

Cross Join



department_id	name
1	Engineering
2	Tool Design
3	Sales
4	Marketing

	employee_id	first_name	department_id
	1	Guy	7
	2	Kevin	4
	•••		•••
,	5	Thierry	NULL

Result

department_id	name	employee_id	first_name
1	Engineering	1	Guy
1	Engineering	2	Kevin
1	Engineering		•••
1	Engineering	5	Thierry

Join Overview



first_name	department_id	
Guy	7	
Kevin	4	
Roberto	1	
Rob	2	
Thierry	NÚLL	
NULL	5	

department_id	name	
1	Engineering	
2	Tool Design	
3	Sales	
4	Marketing	
5	Purchasing	
•••	•••	



Join Overview: INNER JOIN



first_name	department_id	
Guy	7	
Kevin	4	
Roberto	1	
Rob	2	
Thierry	NULL	
NULL	5	

department_id	name	
1	Engineering	
2	Tool Design	
3	Sales	
4	Marketing	
5	Purchasing	
10	Finance	

first_name	department_id	name
Kevin	4 Marketing	
Roberto	1 Engineering	
Rob	2 Tool Design	
NULL	5 Purchasing	

Problem: Towns Addresses



 Get information about addresses in the "soft_uni" database, which are

- in San Francisco,Sofia, or Carnation
- display town_id,
 town_name, address_text

town_id	town_name	address_text	
9	San Fransisco	1234 Seaside Way	
9	San Fransisco	5725 Glaze Drive	
15	Carnation	1411 Ranch Drive	
32	Sofia	163 Nishava Str, ent A, apt. 1	

Solution: Towns Addresses



```
SELECT t.town_id, t.name AS town_name,
    a.address_text
FROM towns AS t
JOIN addresses AS a
    ON a.town_id = t.town_id
WHERE t.name IN ('San Francisco', 'Sofia',
'Carnation')
ORDER BY town_id, address_id;
```

Join Overview: LEFT JOIN



first_name	department_id	
Guy	7	
Kevin	4	
Roberto	1	
Peter	8	

department_id	name
1	Engineering
2	Tool Design
3	Sales
4	Marketing

first_name	department_id	name
Guy	7	NULL
Kevin	4	Marketing
Roberto	1	Engineering
Peter	8	NULL

Join Overview: RIGHT JOIN



first_name	department_id	
Peng	13	
Brian	3	
Ruth	7	
Rob	2	

department_id	name	
3	Sales	
16	Executive	
10	Finance	
7	Production	

first_name	department_id	name	
Brian	3	Sales	
NULL	16 Executive		
NULL	10	0 Finance	
Ruth	7	Production	

Problem: Managers



Get information about the first 5 managers in the "soft_uni"

database

- employee_id
- full_name
- department_id
- department_name

employee_id	full_name	department_id	department_name
3	Roberto Tamburello	10	Finance
4	Rob Walters	2	Tool Design
6	Bradley	5	Purchasing
12	Terri Duffy	1	Engineering
21	Peter Krebs	8	Production Control

Solution: Managers



```
SELECT e.employee_id, CONCAT(first_name, ' ',
    last_name) AS full_name, d.department_id,
    d.name AS department_name
FROM employees AS e
RIGHT JOIN departments AS d
    ON d.manager_id = e.employee_id
ORDER BY e.employee_id LIMIT 5;
```

Problem: Employees Projects



- Get information about the employees, working on a project with id = 1. Display:
 - employee_id
 - full_name
 - project_id
 - project_name

employee_id	full_name	project_id	project_name
3	Roberto Tamburello	1	Classic Vest
15	Jeffrey Ford	1	Classic Vest
18	John Campbell	1	Classic Vest
•••		•••	
246	Frank Martinez	1	Classic Vest

Solution: Employees Projects



```
SELECT e.employee_id, CONCAT(e.first_name,' ',
    e.last_name) as full_name, p.project_id,
    p.name AS project_name
FROM employees AS e
JOIN employees_projects AS e_p
    ON e.employee_id = e_p.employee_id
JOIN projects AS p
    ON p.project_id = e_p.project_id
WHERE e p.project id = 1;
```



Subqueries

Query Manipulation On Multiple Levels

Subqueries



- Subqueries SQL query inside a larger one
- Can be nested in SELECT, INSERT, UPDATE, DELETE
 - Usually added within a WHERE clause

SELECT employee_id AS
 id, first_name,
 department_id
FROM employees
WHERE department_id = 1;



id	first_name	department_id
3	Roberto	1
9	Gail	1
•••	•••	1

Problem: Higher Salary



- Count the number of employees who receive a salary, higher than the average
 - Use "soft_uni" database, table "employees"

•••	last_name	first_name	employee_id	
•••	Seamans	Mike	216	
•••	Moreland	Barbara	178	
•••		•••	•••	



Solution: Higher Salary



```
SELECT COUNT(e.employee_id) AS "count"
FROM employees AS e
WHERE e.salary >
    SELECT AVG(salary) AS
    "average_salary" FROM employees
```



Indices

Speed Retrieval of Rows

Indices



- Special lookup tables that speed retrieval of rows
 - Usually implemented as B-trees
- Speed up SELECT queries and WHERE clauses
- Slows down data input
- Should be used for big tables only (e.g., 50 000 rows)
- Should NOT be used on columns that contain a high number of NULL values



Indices Syntax



Index Name

CREATE INDEX index_name_idx
ON table_name(first_column, second_column);

Table Name

Columns



Live Demo in Class

Summary



Joins

SELECT * FROM employees AS e
 JOIN departments AS d ON
d.department_id = e.department_id

- Subqueries are used to nest queries
- Indices improve SQL search performance if used properly





Questions?



















SoftUni Diamond Partners

























Trainings @ Software University (SoftUni)



- Software University High-Quality Education,
 Profession and Job for Software Developers
 - softuni.bg, softuni.org
- Software University Foundation
 - softuni.foundation
- Software University @ Facebook
 - facebook.com/SoftwareUniversity







License



- This course (slides, examples, demos, exercises, homework, documents, videos and other assets) is copyrighted content
- Unauthorized copy, reproduction or use is illegal
- © SoftUni https://about.softuni.bg/
- © Software University https://softuni.bg

