

```
#4 [internal] load .dockerignore
#4 transferring context: 2B done
#4 DONE 0.1s

#5 [1/1] FROM docker.io/library/mysql:8.0@sha256:7dcddc01f13bab2f15cde676d44d01f61fc9f99fe7785e86196dfc07d358ae2b
#5 resolve docker.io/library/mysql:8.0@sha256:7dcddc01f13bab2f15cde676d44d01f61fc9f99fe7785e86196dfc07d358ae2b 0.0s done
#5 CACHED

#6 exporting to image
#6 exporting layers 0.0s done
#6 exporting manifest sha256:8764965ebbaa3d43af17d79bcdcf3b1020beba2bf8ac86fb6b8892fc95ff3515 0.0s done
#6 exporting config sha256:855ef618cd7311d76f097cab32631bf506dd7ccb1d65cb6293d44b48a1e2f702 0.0s done
#6 exporting attestation manifest sha256:4b6a0540481091e5338a9cde2bbc635c1c900badecb72931fa5867400be18d7a 0.0s done
#6 exporting manifest list sha256:5ebafa0a9cfd13fbc06771fc2603e02a04b535cc8d263ee3cb4b18e77fc432a 0.0s done
#6 naming to docker.io/library/tarea-4-mysql_db:latest
#6 naming to docker.io/library/tarea-4-mysql_db:latest done
#6 unpacking to docker.io/library/tarea-4-mysql_db:latest 0.0s done
#6 DONE 0.3s

#7 resolving provenance for metadata file
#7 DONE 0.0s
[+] up 4/4
  ✓ Image tarea-4-mysql_db Built
  ✓ Network tarea-4_default Created
  ✓ Volume tarea-4_db_data Created
  ✓ Container mysql_local Started
PS D:\carrera_2\Quinto Semestre\Base de datos\admin-db-Loeza-Marrufo\Unidad-1\Tarea-4>
```

```
  ✓ Volume tarea-4_db_data Created
  ✓ Container mysql_local Started
PS D:\carrera_2\Quinto Semestre\Base de datos\admin-db-Loeza-Marrufo\Unidad-1\Tarea-4> docker ps
CONTAINER ID   IMAGE          COMMAND                  CREATED        STATUS        PORTS
2f0919d86019   tarea-4-mysql_db "docker-entrypoint.s..." About a minute ago Up About a minute   0.0.0.0:3306->3306/tcp, [::]:3306->3306/tcp
mysql_local
PS D:\carrera_2\Quinto Semestre\Base de datos\admin-db-Loeza-Marrufo\Unidad-1\Tarea-4>
```

```
Learn more at https://docs.docker.com/go/debug-cli/
PS D:\carrera_2\Quinto Semestre\Base de datos\admin-db-Loeza-Marrufo\Unidad-1\Tarea-4> Get-Content .\Creatables.sql | docker exec -i mysql_local
mysql -uroot -psecret
mysql: [Warning] Using a password on the command line interface can be insecure.
PS D:\carrera_2\Quinto Semestre\Base de datos\admin-db-Loeza-Marrufo\Unidad-1\Tarea-4>
```

```
mysql: [Warning] Using a password on the command line interface can be insecure.
PS D:\carrera_2\Quinto Semestre\Base de datos\admin-db-Loeza-Marrufo\Unidad-1\Tarea-4> docker exec -it mysql_local mysql -uroot -psecret -e "USE
tienda_ecommerce; SHOW TABLES;"
mysql: [Warning] Using a password on the command line interface can be insecure.
+-----+
| Tables_in_tienda_ecommerce |
+-----+
| Compras                     |
| DetalleCompra              |
| Pagos                       |
| Producto                   |
+-----+
```

What's next:
Try Docker Debug for seamless, persistent debugging tools in any container or image → `docker debug mysql_local`
Learn more at <https://docs.docker.com/go/debug-cli/>

```
PS D:\carrera_2\Quinto Semestre\Base de datos\admin-db-Loeza-Marrufo\Unidad-1\Tarea-4>
```

```
What's next:
Try Docker Debug for seamless, persistent debugging tools in any container or image → docker debug mysql_local
Learn more at https://docs.docker.com/go/debug-cli/
PS D:\carrera_2\Quinto Semestre\Base de datos\admin-db-Loeza-Marrufo\Unidad-1\Tarea-4> docker exec -it mysql_local mysql -uroot -psecret -e "USE
tienda_ecommerce; SELECT * FROM Producto;"
mysql: [Warning] Using a password on the command line interface can be insecure.
+-----+-----+-----+-----+
| id_producto | nombre_producto | precio_producto | stock_producto |
+-----+-----+-----+-----+
| 1 | Laptop | 12000.00 | 10 |
| 2 | Audifonos | 1500.00 | 15 |
| 3 | Mouse | 500.00 | 20 |
| 4 | Teclado | 800.00 | 12 |
+-----+-----+-----+-----+
```

What's next:
Try Docker Debug for seamless, persistent debugging tools in any container or image → `docker debug mysql_local`
Learn more at <https://docs.docker.com/go/debug-cli/>

```
PS D:\carrera_2\Quinto Semestre\Base de datos\admin-db-Loeza-Marrufo\Unidad-1\Tarea-4>
```

```
PS D:\carrera_2\Quinto Semestre\Base de datos\admin-db-Loeza-Marrufo\Unidad-1\Tarea-4> docker exec -it mysql_local mysql -uroot -psecret
mysql: [Warning] Using a password on the command line interface can be insecure.
Welcome to the MySQL monitor.  Commands end with ; or \g.
Your MySQL connection id is 13
Server version: 8.0.46 MySQL Community Server - GPL

Copyright (c) 2000, 2026, Oracle and/or its affiliates.

Oracle is a registered trademark of Oracle Corporation and/or its
affiliates. Other names may be trademarks of their respective
owners.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

mysql> █
```

```
mysql> USE tienda_ecommerce;
Reading table information for completion of table and column names
You can turn off this feature to get a quicker startup with -A

Database changed
mysql>
mysql> START TRANSACTION;
Query OK, 0 rows affected (0.00 sec)

mysql> █
```

```
mysql>
Query OK, 0 rows affected (0.00 sec)

mysql> INSERT INTO Compras
  -> (fecha_compra, total_compra, estado_compra)
  -> VALUES
  -> (CURDATE(), 16000.00, 'completada');
Query OK, 1 row affected (0.00 sec)

mysql> █
```

```
mysql> UPDATE Producto
  -> SET stock_producto = stock_producto - 20
  -> WHERE id_producto = 4;
ERROR 3819 (HY000): Check constraint 'Producto_chk_1' is violated.
mysql> █
```

```
mysql> ROLLBACK;  
Query OK, 0 rows affected (0.00 sec)  
  
mysql> █
```

```
mysql>  
mysql> SELECT * FROM Producto  
-> WHERE id_producto = 4;  
  
+-----+-----+-----+-----+  
| id_producto | nombre_producto | precio_producto | stock_producto |  
+-----+-----+-----+-----+  
|          4 | Teclado          |          800.00 |             12 |  
+-----+-----+-----+-----+  
1 row in set (0.00 sec)  
  
mysql> █
```

```
mysql> INSERT INTO Compras  
-> (fecha_compra, total_compra, estado_compra)  
-> VALUES  
-> (CURDATE(), 1000.00, 'completada');  
Query OK, 1 row affected (0.00 sec)  
  
mysql> █
```

```
mysql> UPDATE Producto  
-> SET stock_producto = stock_producto - 2  
-> WHERE id_producto = 3;  
Query OK, 1 row affected (0.00 sec)  
Rows matched: 1  Changed: 1  Warnings: 0  
  
mysql> █
```

```
mysql> INSERT INTO DetalleCompra  
-> (id_compra, id_producto, cantidad_producto, precio_unitario)  
-> VALUES  
-> (LAST_INSERT_ID(), 3, 2, 500.00);  
Query OK, 1 row affected (0.00 sec)
```

```
mysql> INSERT INTO Pagos
  -> (id_compra, monto_pago, fecha_pago)
  -> VALUES
  -> (LAST_INSERT_ID(), 0.00, CURDATE());
ERROR 3819 (HY000): Check constraint 'Pagos_chk_1' is violated.
mysql> █
```

```
mysql> ROLLBACK;
Query OK, 0 rows affected (0.03 sec)
█
```

```
mysql> SELECT * FROM Producto
-> WHERE id_producto = 3;
```

```
+-----+-----+-----+-----+
| id_producto | nombre_producto | precio_producto | stock_producto |
+-----+-----+-----+-----+
|          3 | Mouse           |          500.00 |             20 |
+-----+-----+-----+-----+
1 row in set (0.00 sec)
```

```
mysql>
mysql> SELECT * FROM Compras
-> WHERE total_compra = 1000.00;
```

```
+-----+-----+-----+-----+
| id_compra | fecha_compra | total_compra | estado_compra |
+-----+-----+-----+-----+
|          2 | 2026-09-18  |          1000.00 | completada    |
+-----+-----+-----+-----+
1 row in set (0.01 sec)
```

```
mysql>
mysql> SELECT * FROM DetalleCompra
-> WHERE precio_unitario = 500.00;
```

```
+-----+-----+-----+-----+-----+
| id_detalle | id_compra | id_producto | cantidad_producto | precio_unitario |
+-----+-----+-----+-----+-----+
|           2 |          2 |           3 |                2 |          500.00 |
+-----+-----+-----+-----+-----+
1 row in set (0.00 sec)
```

```
mysql> 
```

```
mysql> SELECT * FROM Compras
-> WHERE id_compra = 4;
Empty set (0.00 sec)
```

```
mysql>
mysql> SELECT * FROM DetalleCompra
-> WHERE id_detalle = 3;
```

id_detalle	id_compra	id_producto	cantidad_producto	precio_unitario
3	3	1	2	12000.00

```
1 row in set (0.00 sec)
```

```
mysql>
mysql> SELECT * FROM Pagos
-> WHERE id_compra = 4;
Empty set (0.00 sec)
```

```
mysql>
mysql> SELECT * FROM Producto
-> WHERE id_producto = 3;
```

id_producto	nombre_producto	precio_producto	stock_producto
3	Mouse	500.00	20

```
1 row in set (0.00 sec)
```

```
mysql> █
```

```
1 row in set (0.00 sec)
```

```
mysql> SELECT * FROM DetalleCompra
-> WHERE id_compra = 4;
Empty set (0.00 sec)
```

```
mysql> █
```