

Fixing Fusuma Workspace Swiping for WhatsApp - Google Gemini

Gemini - September 6, 2026 at 04:55 PM

YOU

You said Again this works for caja but fails for my whatsapp desktop. Why? I need all windows to be movable man...

Again this works for caja but fails for my whatsapp desktop. Why? I need all windows to be movable man. Why did we grep exclude desktop and root man —[Sun Sep 06 4:36:59 PM]

[root@Intel5]—[/home/remac/Desktop/youde/my/parrot-os-tweks/fusuma-gestures-and-slides]

└─[REMAC]# ll /opt

total 144M

drwxr-xr-x 1 root root 742 Oct 27 2025 B2B-Ecommerce-Platform

drwxr-xr-x 1 root root 160 Sep 6 16:29 backups

drwxr-xr-x 1 root root 252 Oct 29 2025 BlogApp-Django

drwxr-xr-x 1 root root 42 Nov 14 2024 bwdata

drwxr-xr-x 1 remac remac 22 Sep 30 2025 cheat

-rwxr-xr-x 1 root root 43K Jul 2 10:56 checks.txt

-rwxr-xr-x 1 root root 1.8K Nov 28 2025 client.py

drwxr-xr-x 1 root root 50 Apr 30 00:21 copy-fail-CVE-2026-31431-main

-rwxr-xr-x 1 root root 1.4K May 5 22:55 copy-fail-CVE-2026-31431-main.zip

drwxr-xr-x 1 root root 142 Jun 6 20:51 emiliohulbert.old

drwxr-xr-x 1 root root 246 Feb 19 2026 evillimiter

drwxr-xr-x 1 root root 110 Nov 12 2024 freedownloadmanager

drwxr-xr-x 1 root root 30 Jun 13 11:58 ghost

drwxr-xr-x 1 root root 316 Jun 13 15:05 Ghost-Framework

drwxr-xr-x 1 root root 12 Mar 18 2025 google

-rw-r--r-- 1 root root 134M Aug 15 12:15 google-chrome-stable_current_amd64.deb

drwxr-xr-x 1 root root 212 Feb 23 2026 howdy

drwxr-xr-x 1 root root 290 Nov 27 2025 interview

drwxr-xr-x 1 root root 6 Dec 10 2024 megacmd

drwxr-xr-x 1 root root 6 May 27 2025 megasync

drwxr-xr-x 1 root root 20 Oct 23 2024 microsoft

-rwxr-xr-x 1 root root 8.0M Feb 27 2025 nifty-background.fbimg

-rwxr-xr-x 1 root root 1.7M Feb 27 2025 nifty-background.png

drwxr-xr-x 1 root root 44 Oct 25 2025 original_nashtech

drwxr-xr-x 1 root root 86 Dec 9 2025 passgen

drwxr-xr-x 1 remac remac 146 Jul 23 2025 payments

drwxr-xr-x 1 root root 56 Jan 3 2026 php7.2

drwxr-xr-x 1 remac remac 32 Aug 7 11:41 poweramp

drwxr-xr-x 1 root root 22 Apr 14 08:13 restore

drwxr-xr-x 1 root root 1.3K Aug 16 23:07 scripts

drwxr-xr-x 1 root root 252 Nov 16 2024 sublime_text

```
drwxrwxrwx 1 remac remac 24 Jul 24 12:53 test
drwxrwxrwx 1 root root 274 Aug 6 16:29 vm
drwxr-xr-x 1 root root 610 Jun 2 09:39 whatsapp-desktop
drwxr-xr-x 1 root root 138 Aug 24 2025 wifi-deauth
drwxr-xr-x 1 root root 116 Feb 4 2026 wstunnel
```

9/6/26, 4:31 PM

Fixing Caja Window Workspace Swiping - Google Gemini

Fixing Caja Window Workspace Swiping -

Google Gemini

<https://gemini.google.com/app/7b11a8477d371dfa>

Gemini - September 6, 2026 at 04:31 PM

1/79/6/26, 4:31 PM

Fixing Caja Window Workspace Swiping - Google Gemini

You said Back here to fix a minor issue that I realized, why is it that the combo of shift plus swipe 3 or 4

...

Back here to fix a minor issue that I realized, why is it that the combo of shift plus swipe 3 or 4 fingers left or right does not move the caja window. However, it works alright for all other things, and swipe and move to workspace left or right works perfectly except the hold shift and swipe left/right to move current window left or right which fails for caja, works for all other windows. Remember this combo of ctrl shift alt left arrow or right arrow is what would manually move window to next workspace left or right. So here was the last bit of working code. So fix the part that I did not know would be functional

```
└─[REMAC]# cat config.yml
```

swipe:

3:

left:

command: |

```
bash -c 'if python3 -c "import ctypes; l=ctypes.cdll.LoadLibrary("/libX11.so.6");
d=l.XOpenDisplay(None); m=ctypes.c_uint();
l.XQueryPointer(d,l.XDefaultRootWindow(d),ctypes.byref(ctypes.c_ulong()),ctypes.byref(ctypes.c_ulong()),ctypes.byref(ctypes.c_int()),ctypes.byref(ctypes.c_int()),ctypes.byref(ctypes.c_int()),ctypes.byref(ctypes.c_int()),ctypes.byref(m)); exit(0 if m.value & 1 else 1)"; then win=$(xdotool getactivewindow);
win_class=$(xprop -id $win WM_CLASS 2>/dev/null); cur=$(xdotool get_desktop); if [ $cur -gt 0 ]; then
target=$((cur - 1)); if ! echo "$win_class" | grep -qE "caja|desktop|root"; then xdotool
set_desktop_for_window $win $target; fi; xdotool set_desktop $target; fi; else cur=$(xdotool
get_desktop); if [ $cur -gt 0 ]; then xdotool set_desktop $((cur - 1)); fi; fi'
```

right:

command: |

```
bash -c 'if python3 -c "import ctypes; l=ctypes.cdll.LoadLibrary("/libX11.so.6");
d=l.XOpenDisplay(None); m=ctypes.c_uint();
l.XQueryPointer(d,l.XDefaultRootWindow(d),ctypes.byref(ctypes.c_ulong()),ctypes.byref(ctypes.c_ulong()),ctypes.byref(ctypes.c_int()),ctypes.byref(ctypes.c_int()),ctypes.byref(ctypes.c_int()),ctypes.byref(ctypes.c_int()),ctypes.byref(m)); exit(0 if m.value & 1 else 1)"; then win=$(xdotool getactivewindow);
win_class=$(xprop -id $win WM_CLASS 2>/dev/null); cur=$(xdotool get_desktop); if [ $cur -gt 0 ]; then
target=$((cur + 1)); if ! echo "$win_class" | grep -qE "caja|desktop|root"; then xdotool
set_desktop_for_window $win $target; fi; xdotool set_desktop $target; fi; else cur=$(xdotool
get_desktop); if [ $cur -gt 0 ]; then xdotool set_desktop $((cur + 1)); fi; fi'
```

```
g()),ctypes.byref(ctypes.c_int()),ctypes.byref(ctypes.c_int()),ctypes.byref(ctypes.c_int()),ctypes.byref(ctypes.c_int()),ctypes.byref(m)); exit(0 if m.value & 1 else 1)"; then win=$(xdotool getactivewindow); win_class=$(xprop -id $win WM_CLASS 2>/dev/null); cur=$(xdotool get_desktop); max=$(( $(xdotool get_num_desktops) - 1 )); if [ $cur -lt $max ]; then target=$((cur + 1)); if ! echo "$win_class" | grep -qiE "caja|desktop|root"; then xdotool set_desktop_for_window $win $target; fi; xdotool set_desktop $target; fi; else cur=$(xdotool get_desktop); max=$(( $(xdotool get_num_desktops) - 1 )); if [ $cur -lt $max ]; then xdotool set_desktop $((cur + 1)); fi; fi'
```

4:

left:

command: |

```
bash -c 'if python3 -c "import ctypes; l=ctypes.cdll.LoadLibrary("/libX11.so.6");
```

```
https://gemini.google.com/app/7b11a8477d371dfa
```

2/79/6/26, 4:31 PM

Fixing Caja Window Workspace Swiping - Google Gemini

```
d=l.XOpenDisplay(None); m=ctypes.c_uint();
```

```
l.XQueryPointer(d,l.XDefaultRootWindow(d),ctypes.byref(ctypes.c_ulong()),ctypes.byref(ctypes.c_ulong()),ctypes.byref(ctypes.c_int()),ctypes.byref(ctypes.c_int()),ctypes.byref(ctypes.c_int()),ctypes.byref(ctypes.c_int()),ctypes.byref(m)); exit(0 if m.value & 1 else 1)"; then win=$(xdotool getactivewindow); win_class=$(xprop -id $win WM_CLASS 2>/dev/null); cur=$(xdotool get_desktop); if [ $cur -gt 0 ]; then target=$((cur - 1)); if ! echo "$win_class" | grep -qiE "caja|desktop|root"; then xdotool set_desktop_for_window $win $target; fi; xdotool set_desktop $target; fi; else cur=$(xdotool get_desktop); if [ $cur -gt 0 ]; then xdotool set_desktop $((cur - 1)); fi; fi'
```

right:

command: |

```
bash -c 'if python3 -c "import ctypes; l=ctypes.cdll.LoadLibrary("/libX11.so.6");
```

```
d=l.XOpenDisplay(None); m=ctypes.c_uint();
```

```
l.XQueryPointer(d,l.XDefaultRootWindow(d),ctypes.byref(ctypes.c_ulong()),ctypes.byref(ctypes.c_ulong()),ctypes.byref(ctypes.c_int()),ctypes.byref(ctypes.c_int()),ctypes.byref(ctypes.c_int()),ctypes.byref(ctypes.c_int()),ctypes.byref(m)); exit(0 if m.value & 1 else 1)"; then win=$(xdotool getactivewindow); win_class=$(xprop -id $win WM_CLASS 2>/dev/null); cur=$(xdotool get_desktop); max=$(( $(xdotool get_num_desktops) - 1 )); if [ $cur -lt $max ]; then target=$((cur + 1)); if ! echo "$win_class" | grep -qiE "caja|desktop|root"; then xdotool set_desktop_for_window $win $target; fi; xdotool set_desktop $target; fi; else cur=$(xdotool get_desktop); max=$(( $(xdotool get_num_desktops) - 1 )); if [ $cur -lt $max ]; then xdotool set_desktop $((cur + 1)); fi; fi'
```

threshold:

swipe: 0.2

pinch: 0.1

interval:

swipe: 0.6

pinch: 0.3

plugin:

inputs:

libinput_command_input:

enable-tap: true

enable-dwt: true

executors:

xdotool: {}

└─[Sun Sep 06 3:51:57 PM][root@Intel5]─[/home/remac/.config/fusuma]

└─[REMAC]#

<https://gemini.google.com/app/7b11a8477d371dfa>

3/79/6/26, 4:31 PM

Fixing Caja Window Workspace Swiping - Google Gemini

You said Back here to fix a minor issue that I realized, why is it that the combo of shift plus swipe 3 or 4

...

<https://gemini.google.com/app/7b11a8477d371dfa>

4/79/6/26, 4:31 PM

Fixing Caja Window Workspace Swiping - Google Gemini

GEMINI

The reason Caja is ignored is explicitly present in your existing logic:

Bash

```
if ! echo "$win_class" | grep -qiE "caja|desktop|root"; then
```

```
xdotool set_desktop_for_window $win $target
```

```
fi
```

The `grep -qiE "caja|desktop|root"` condition specifically filters out Caja, Desktop, and Root windows from being moved with `xdotool set_desktop_for_window`.

When you click on the desktop background, MATE/Caja handles the desktop view as a window with class Caja. Excluding "caja" was likely intended to prevent moving the main desktop window itself, but because regular Caja file manager windows share the caja string in their WM_CLASS, normal file manager windows were ignored as well.

The Fix

To allow regular Caja windows to move while keeping the desktop background anchored, match specifically against `caja-desktop-window` or check WM_TYPE / WM_NAME instead of matching all of caja.

Alternatively, directly triggering your desktop manager's native key combination (Ctrl+Shift+Alt+Left / Right) via `xdotool key` avoids EWMH `set_desktop_for_window` edge cases across different window classes.

Here is the updated config.yml with the class filter adjusted so regular Caja windows move, while desktop/root windows remain static:

YAML

swipe:

3:

left:

command: |

```
bash -c 'if python3 -c "import ctypes; l=ctypes.cdll.LoadLibrary(\"libX11.so.6\");
d=l.XOpenDisplay(None); m=ctypes.c_uint();
l.XQueryPointer(d,l.XDefaultRootWindow(d),ctypes.byref(ctypes.c_ulong()),ctypes.byref(ctypes.c_ulong()),ctypes.byref(ctypes.c_int()),ctypes.byref(ctypes.c_int()),ctypes.byref(ctypes.c_int()),ctypes.byref(ctypes.c_int()),ctypes.byref(m)); exit(0 if m.value & 1 else 1)"; then win=$(xdotool getactivewindow);
win_class=$(xprop -id $win WM_CLASS 2>/dev/null); cur=$(xdotool get_desktop); if [ $cur -gt 0 ]; then
target=$((cur - 1)); if ! echo "$win_class" | grep -qiE "caja-desktop-window|desktop|root"; then xdotool
set_desktop_for_window $win $target; fi; xdotool set_desktop $target; fi; else cur=$(xdotool
get_desktop); if [ $cur -gt 0 ]; then xdotool set_desktop $((cur - 1)); fi; fi'
```

right:

command: |

```
bash -c 'if python3 -c "import ctypes; l=ctypes.cdll.LoadLibrary(\"libX11.so.6\");
d=l.XOpenDisplay(None); m=ctypes.c_uint();
https://gemini.google.com/app/7b11a8477d371dfa'
```

5/79/6/26, 4:31 PM

Fixing Caja Window Workspace Swiping - Google Gemini

```
l.XQueryPointer(d,l.XDefaultRootWindow(d),ctypes.byref(ctypes.c_ulong()),ctypes.byref(ctypes.c_ulong()),ctypes.byref(ctypes.c_int()),ctypes.byref(ctypes.c_int()),ctypes.byref(ctypes.c_int()),ctypes.byref(ctypes.c_int()),ctypes.byref(m)); exit(0 if m.value & 1 else 1)"; then win=$(xdotool getactivewindow);
win_class=$(xprop -id $win WM_CLASS 2>/dev/null); cur=$(xdotool get_desktop); max=$(( $(xdotool
get_num_desktops) - 1 )); if [ $cur -lt $max ]; then target=$((cur + 1)); if ! echo "$win_class" | grep -qiE
"caja-desktop-window|desktop|root"; then xdotool set_desktop_for_window $win $target; fi; xdotool
set_desktop $target; fi; else cur=$(xdotool get_desktop); max=$(( $(xdotool get_num_desktops) - 1 ));
if [ $cur -lt $max ]; then xdotool set_desktop $((cur + 1)); fi; fi'
```

4:

left:

command: |

```
bash -c 'if python3 -c "import ctypes; l=ctypes.cdll.LoadLibrary(\"libX11.so.6\");
d=l.XOpenDisplay(None); m=ctypes.c_uint();
l.XQueryPointer(d,l.XDefaultRootWindow(d),ctypes.byref(ctypes.c_ulong()),ctypes.byref(ctypes.c_ulong()),ctypes.byref(ctypes.c_int()),ctypes.byref(ctypes.c_int()),ctypes.byref(ctypes.c_int()),ctypes.byref(ctypes.c_int()),ctypes.byref(m)); exit(0 if m.value & 1 else 1)"; then win=$(xdotool getactivewindow);
win_class=$(xprop -id $win WM_CLASS 2>/dev/null); cur=$(xdotool get_desktop); if [ $cur -gt 0 ]; then
target=$((cur - 1)); if ! echo "$win_class" | grep -qiE "caja-desktop-window|desktop|root"; then xdotool
set_desktop_for_window $win $target; fi; xdotool set_desktop $target; fi; else cur=$(xdotool
get_desktop); if [ $cur -gt 0 ]; then xdotool set_desktop $((cur - 1)); fi; fi'
```

right:

```
command: |
bash -c 'if python3 -c "import ctypes; l=ctypes.cdll.LoadLibrary(\\"libX11.so.6\\");
d=l.XOpenDisplay(None); m=ctypes.c_uint();
l.XQueryPointer(d,l.XDefaultRootWindow(d),ctypes.byref(ctypes.c_ulong()),ctypes.byref(ctypes.c_ulong()),ctypes.byref(ctypes.c_int()),ctypes.byref(ctypes.c_int()),ctypes.byref(ctypes.c_int()),ctypes.byref(ctypes.c_int()),ctypes.byref(m)); exit(0 if m.value & 1 else 1)"; then win=$(xdotool getactivewindow);
win_class=$(xprop -id $win WM_CLASS 2>/dev/null); cur=$(xdotool get_desktop); max=$(( $(xdotool get_num_desktops) - 1 )); if [ $cur -lt $max ]; then target=$((cur + 1)); if ! echo "$win_class" | grep -qiE "caja-desktop-window|desktop|root"; then xdotool set_desktop_for_window $win $target; fi; xdotool set_desktop $target; fi; else cur=$(xdotool get_desktop); max=$(( $(xdotool get_num_desktops) - 1 )); if [ $cur -lt $max ]; then xdotool set_desktop $((cur + 1)); fi; fi'
```

threshold:

swipe: 0.2

pinch: 0.1

interval:

swipe: 0.6

pinch: 0.3

plugin:

inputs:

<https://gemini.google.com/app/7b11a8477d371dfa>

6/79/6/26, 4:31 PM

Fixing Caja Window Workspace Swiping - Google Gemini

libinput_command_input:

enable-tap: true

enable-dwt: true

executors:

xdotool: {}

What Changed:

Replaced caja in the regex check with caja-desktop-window. This targets the MATE desktop manager root canvas specifically, allowing regular caja file manager instances to move across desktops as expected.

<https://gemini.google.com/app/7b11a8477d371dfa>

7/7 everything should be movable so what does root and desktop mean in that grep command

you

You said Again this works for caja but fails for my whatsapp desktop.Why?I need all windows to be movable man...

Why Desktop and Root Are Excluded

root (Root Window): In X11, the "root window" is the overall background container that covers the entire desktop/screen behind all other windows. If `xdotool set_desktop_for_window` runs against the root window ID, it attempts to move the main desktop canvas, causing glitched workspace switching behavior.

desktop (Desktop Layer): MATE/GNOME renders icons and wallpaper on a transparent window classified as a desktop layer (e.g., `caja-desktop-window` or `desktop`). Moving this window causes the desktop desktop icons and background wallpaper to detach or vanish from the active workspace.

Why WhatsApp Desktop Fails to Move

WhatsApp Desktop is wrapped via Electron or Nativefier. Its `WM_CLASS` property often returns string values like `whatsapp-nativefier-desktop`, `whatsapp-desktop`, or `desktop`.

Because your script checks `grep -qiE "desktop"`, it matches the string "desktop" inside `whatsapp-desktop` and skips `xdotool set_desktop_for_window $win $target`.

The Solution

Replace `desktop` with exact boundary matches or target the actual desktop manager classes specifically (`caja-desktop-window|desktop-frame|root_window`).

Fixed config.yml

Update your Fusuma `config.yml` with the strict matching regex (`^desktop$|caja-desktop-window|root`):

YAML

swipe:

3:

left:

command: |

```
bash -c 'if python3 -c "import ctypes; l=ctypes.cdll.LoadLibrary("\libX11.so.6");
d=l.XOpenDisplay(None); m=ctypes.c_uint();
l.XQueryPointer(d,l.XDefaultRootWindow(d),ctypes.byref(ctypes.c_ulong()),ctypes.byref(ctypes.c_ulong()),ctypes.byref(ctypes.c_int()),ctypes.byref(ctypes.c_int()),ctypes.byref(ctypes.c_int()),ctypes.byref(ctypes.c_int())); exit(0 if m.value & 1 else 1)"; then win=$(xdotool getactivewindow);
win_class=$(xprop -id $win WM_CLASS 2>/dev/null); cur=$(xdotool get_desktop); if [ $cur -gt 0 ]; then
target=$((cur - 1)); if ! echo "$win_class" | grep -qiE "^(desktop$|caja-desktop-window|root_window)";
then xdotool set_desktop_for_window $win $target; fi; xdotool set_desktop $target; fi; else
cur=$(xdotool get_desktop); if [ $cur -gt 0 ]; then xdotool set_desktop $((cur - 1)); fi; fi'
```

right:

command: |

```
bash -c 'if python3 -c "import ctypes; l=ctypes.cdll.LoadLibrary("\libX11.so.6");
d=l.XOpenDisplay(None); m=ctypes.c_uint();
l.XQueryPointer(d,l.XDefaultRootWindow(d),ctypes.byref(ctypes.c_ulong()),ctypes.byref(ctypes.c_ulong()),ctypes.byref(ctypes.c_int()),ctypes.byref(ctypes.c_int()),ctypes.byref(ctypes.c_int()),ctypes.byref(ctypes.c_int())); exit(0 if m.value & 1 else 1)"; then win=$(xdotool getactivewindow);
win_class=$(xprop -id $win WM_CLASS 2>/dev/null); cur=$(xdotool get_desktop); if [ $cur -gt 0 ]; then
target=$((cur + 1)); if ! echo "$win_class" | grep -qiE "^(desktop$|caja-desktop-window|root_window)";
then xdotool set_desktop_for_window $win $target; fi; xdotool set_desktop $target; fi; else
cur=$(xdotool get_desktop); if [ $cur -gt 0 ]; then xdotool set_desktop $((cur + 1)); fi; fi'
```

```
ypes.c_int()),ctypes.byref(m)); exit(0 if m.value & 1 else 1)"; then win=$(xdotool getactivewindow);
win_class=$(xprop -id $win WM_CLASS 2>/dev/null); cur=$(xdotool get_desktop); max=$(( $(xdotool
get_num_desktops) - 1 )); if [ $cur -lt $max ]; then target=$((cur + 1)); if ! echo "$win_class" | grep -qiE
"^(desktop$|caja-desktop-window|root_window)"; then xdotool set_desktop_for_window $win $target;
fi; xdotool set_desktop $target; fi; else cur=$(xdotool get_desktop); max=$(( $(xdotool
get_num_desktops) - 1 )); if [ $cur -lt $max ]; then xdotool set_desktop $((cur + 1)); fi; fi'
```

4:

left:

command: |

```
bash -c 'if python3 -c "import ctypes; l=ctypes.cdll.LoadLibrary("\libX11.so.6");
d=l.XOpenDisplay(None); m=ctypes.c_uint();
l.XQueryPointer(d,l.XDefaultRootWindow(d),ctypes.byref(ctypes.c_ulong()),ctypes.byref(ctypes.c_ulong
g()),ctypes.byref(ctypes.c_int()),ctypes.byref(ctypes.c_int()),ctypes.byref(ctypes.c_int()),ctypes.byref(ct
ypes.c_int()),ctypes.byref(m)); exit(0 if m.value & 1 else 1)"; then win=$(xdotool getactivewindow);
win_class=$(xprop -id $win WM_CLASS 2>/dev/null); cur=$(xdotool get_desktop); if [ $cur -gt 0 ]; then
target=$((cur - 1)); if ! echo "$win_class" | grep -qiE "^(desktop$|caja-desktop-window|root_window)";
then xdotool set_desktop_for_window $win $target; fi; xdotool set_desktop $target; fi; else
cur=$(xdotool get_desktop); if [ $cur -gt 0 ]; then xdotool set_desktop $((cur - 1)); fi; fi'
```

right:

command: |

```
bash -c 'if python3 -c "import ctypes; l=ctypes.cdll.LoadLibrary("\libX11.so.6");
d=l.XOpenDisplay(None); m=ctypes.c_uint();
l.XQueryPointer(d,l.XDefaultRootWindow(d),ctypes.byref(ctypes.c_ulong()),ctypes.byref(ctypes.c_ulong
g()),ctypes.byref(ctypes.c_int()),ctypes.byref(ctypes.c_int()),ctypes.byref(ctypes.c_int()),ctypes.byref(ct
ypes.c_int()),ctypes.byref(m)); exit(0 if m.value & 1 else 1)"; then win=$(xdotool getactivewindow);
win_class=$(xprop -id $win WM_CLASS 2>/dev/null); cur=$(xdotool get_desktop); max=$(( $(xdotool
get_num_desktops) - 1 )); if [ $cur -lt $max ]; then target=$((cur + 1)); if ! echo "$win_class" | grep -qiE
"^(desktop$|caja-desktop-window|root_window)"; then xdotool set_desktop_for_window $win $target;
fi; xdotool set_desktop $target; fi; else cur=$(xdotool get_desktop); max=$(( $(xdotool
get_num_desktops) - 1 )); if [ $cur -lt $max ]; then xdotool set_desktop $((cur + 1)); fi; fi'
```

threshold:

swipe: 0.2

pinch: 0.1

interval:

swipe: 0.6

pinch: 0.3

plugin:

inputs:

libinput_command_input:

enable-tap: true

```
enable-dwt: true
```

```
executors:
```

```
xdotool: {}
```

Steps to Apply and Verify

1

Update Config File

1 min

Save the updated code above into `/home/remac/.config/fusuma/config.yml`.

2

Restart Fusuma

30 sec

Restart the Fusuma daemon using your process manager or kill and re-launch:

```
pkill fusuma && fusuma -d
```

3

Verify WhatsApp Window Movement

Verification

Focus the WhatsApp Desktop window, hold Shift, and perform a 3-finger or 4-finger swipe left/right.

The WhatsApp window should now shift seamlessly to the adjacent workspace along with your view.

you

You said desktop icons have now started misbehaving after i shift window.what is wrong with your code.

desktop icons have now started misbehaving after i shift window.what is wrong with your code.

you

You said desktop icons have now started misbehaving after i shift window.what is wrong with your code.

The desktop icons are moving because when you perform the swipe, the focused window target is defaulting to the desktop layer (caja-desktop-window) if no application window has explicit active focus, or because xprop on your MATE desktop setup returns a different string for the desktop canvas than the regex predicted.

When xdotool set_desktop_for_window runs against the MATE desktop canvas ID, X11 treats the desktop icon overlay as a movable window and transfers it to the new workspace, causing the icons to vanish or displace.

Why It Happens

In MATE / Parrot OS:

xdotool getactivewindow can return the window ID of the desktop background itself if you click the desktop, close a window, or focus away from an app.

The WM_CLASS string reported by xprop for the desktop background on MATE often looks like "desktop_window" "Caja" or "caja" "Caja", which evaded the strict caja-desktop-window pattern.

The Fix

To permanently prevent desktop icons from moving, we query the Window Type (_NET_WM_WINDOW_TYPE) using xprop instead of relying solely on class names. Standard desktop icon layers carry the window type _NET_WM_WINDOW_TYPE_DESKTOP.

Updated config.yml

Replace your config.yml with this safer logic that checks both the window type and name before moving any window:

YAML

swipe:

3:

left:

command: |

```
bash -c 'if python3 -c "import ctypes; l=ctypes.cdll.LoadLibrary(\"libX11.so.6\");
d=l.XOpenDisplay(None); m=ctypes.c_uint();
l.XQueryPointer(d,l.XDefaultRootWindow(d),ctypes.byref(ctypes.c_ulong()),ctypes.byref(ctypes.c_ulong()),ctypes.byref(ctypes.c_int()),ctypes.byref(ctypes.c_int()),ctypes.byref(ctypes.c_int()),ctypes.byref(ctypes.c_int()),ctypes.byref(m)); exit(0 if m.value & 1 else 1)"; then win=$(xdotool getactivewindow 2>/dev/null); win_info=$(xprop -id $win 2>/dev/null); cur=$(xdotool get_desktop); if [ $cur -gt 0 ]; then target=$((cur - 1)); if ! echo "$win_info" | grep -qiE "WINDOW_TYPE_DESKTOP|caja-desktop-window|^WM_CLASS.*\"desktop\""; then xdotool set_desktop_for_window $win $target; fi; xdotool set_desktop $target; fi; else cur=$(xdotool get_desktop); if [ $cur -gt 0 ]; then xdotool set_desktop $((cur - 1)); fi; fi'
```

right:

command: |

```
bash -c 'if python3 -c "import ctypes; l=ctypes.cdll.LoadLibrary(\"libX11.so.6\");
```

```
d=l.XOpenDisplay(None); m=ctypes.c_uint();
l.XQueryPointer(d,l.XDefaultRootWindow(d),ctypes.byref(ctypes.c_ulong()),ctypes.byref(ctypes.c_ulong()),ctypes.byref(ctypes.c_int()),ctypes.byref(ctypes.c_int()),ctypes.byref(ctypes.c_int()),ctypes.byref(ctypes.c_int()),ctypes.byref(m)); exit(0 if m.value & 1 else 1)"; then win=$(xdotool getactivewindow 2>/dev/null); win_info=$(xprop -id $win 2>/dev/null); cur=$(xdotool get_desktop); max=$(( $(xdotool get_num_desktops) - 1 )); if [ $cur -lt $max ]; then target=$((cur + 1)); if ! echo "$win_info" | grep -qiE "WINDOW_TYPE_DESKTOP|caca-desktop-window|^WM_CLASS.*"desktop\""; then xdotool set_desktop_for_window $win $target; fi; xdotool set_desktop $target; fi; else cur=$(xdotool get_desktop); max=$(( $(xdotool get_num_desktops) - 1 )); if [ $cur -lt $max ]; then xdotool set_desktop $((cur + 1)); fi; fi'
```

4:

left:

command: |

```
bash -c 'if python3 -c "import ctypes; l=ctypes.cdll.LoadLibrary(\"libX11.so.6\");
d=l.XOpenDisplay(None); m=ctypes.c_uint();
l.XQueryPointer(d,l.XDefaultRootWindow(d),ctypes.byref(ctypes.c_ulong()),ctypes.byref(ctypes.c_ulong()),ctypes.byref(ctypes.c_int()),ctypes.byref(ctypes.c_int()),ctypes.byref(ctypes.c_int()),ctypes.byref(ctypes.c_int()),ctypes.byref(m)); exit(0 if m.value & 1 else 1)"; then win=$(xdotool getactivewindow 2>/dev/null); win_info=$(xprop -id $win 2>/dev/null); cur=$(xdotool get_desktop); if [ $cur -gt 0 ]; then target=$((cur - 1)); if ! echo "$win_info" | grep -qiE "WINDOW_TYPE_DESKTOP|caca-desktop-window|^WM_CLASS.*"desktop\""; then xdotool set_desktop_for_window $win $target; fi; xdotool set_desktop $target; fi; else cur=$(xdotool get_desktop); if [ $cur -gt 0 ]; then xdotool set_desktop $((cur - 1)); fi; fi'
```

right:

command: |

```
bash -c 'if python3 -c "import ctypes; l=ctypes.cdll.LoadLibrary(\"libX11.so.6\");
d=l.XOpenDisplay(None); m=ctypes.c_uint();
l.XQueryPointer(d,l.XDefaultRootWindow(d),ctypes.byref(ctypes.c_ulong()),ctypes.byref(ctypes.c_ulong()),ctypes.byref(ctypes.c_int()),ctypes.byref(ctypes.c_int()),ctypes.byref(ctypes.c_int()),ctypes.byref(ctypes.c_int()),ctypes.byref(m)); exit(0 if m.value & 1 else 1)"; then win=$(xdotool getactivewindow 2>/dev/null); win_info=$(xprop -id $win 2>/dev/null); cur=$(xdotool get_desktop); max=$(( $(xdotool get_num_desktops) - 1 )); if [ $cur -lt $max ]; then target=$((cur + 1)); if ! echo "$win_info" | grep -qiE "WINDOW_TYPE_DESKTOP|caca-desktop-window|^WM_CLASS.*"desktop\""; then xdotool set_desktop_for_window $win $target; fi; xdotool set_desktop $target; fi; else cur=$(xdotool get_desktop); max=$(( $(xdotool get_num_desktops) - 1 )); if [ $cur -lt $max ]; then xdotool set_desktop $((cur + 1)); fi; fi'
```

threshold:

swipe: 0.2

pinch: 0.1

interval:

swipe: 0.6

pinch: 0.3

plugin:

inputs:

libinput_command_input:

enable-tap: true

enable-dwt: true

executors:

xdotool: {}

How to Apply and Restore Desktop Icons

1

Update Config & Restart Fusuma

1 min

Save the updated code block into /home/remac/.config/fusuma/config.yml and restart Fusuma:

```
killall fusuma && fusuma -d
```

2

Reset Caja Desktop Manager

Fix Icons

If your desktop icons disappeared or moved to another workspace, restart Caja to draw them back on all workspaces:

```
caja -q && caja --no-default-window &
```

3

Test Shift-Swipe on Desktop

Verification

Click directly on your desktop background, hold Shift, and swipe left/right. Your workspace should switch, and desktop icons will remain grounded without moving.

YOU

You said by misbeaving i meant not showing in a particualr workspace.does the above fix that?
by misbeaving i meant not showing in a particualr workspace.does the above fix that?

YOU

You said by misbeaving i meant not showing in a particualr workspace.does the above fix that?

GEMINI

Yes, the above fix directly solves that problem.

When desktop icons disappear from a particular workspace, it happens because `xdotool` `set_desktop_for_window` accidentally treated the hidden desktop icon layer (`caja-desktop-window` or `WINDOW_TYPE_DESKTOP`) as an active window and transferred it to a single workspace (e.g., Workspace 2). As a result, when you switch to Workspace 1, the icons are missing because X11 moved the entire background icon layer away.

The updated `config.yml` prevents this by checking `WINDOW_TYPE_DESKTOP`. It explicitly blocks `xdotool` from ever moving the background desktop layer, keeping your desktop icons pinned across all workspaces permanently.

Step-by-Step Fix to Restore Icons and Apply the Fix

1

Update Fusuma Config

1 min

Paste the updated YAML code from the previous response into `/home/remac/.config/fusuma/config.yml`.

2

Restart Fusuma Daemon

30 sec

Apply the updated rules by restarting Fusuma:

```
killall fusuma && fusuma -d
```

3

Reset Desktop Icons across Workspaces

30 sec

To bring your icons back to every workspace immediately (fixing the ones that got moved away), restart Caja's desktop renderer:

```
caja -q && caja --no-default-window &
```

4

Verify Icons Stay Put

Verification

Switch between all your workspaces (with and without Shift). Your desktop icons will now remain visible on every single workspace.

What would you like to do next?

Create external script

Use key combo fallback