

---

# PyVOL Documentation

*Release 1.2.34*

**Ryan Smith**

**Nov 07, 2019**

# CONTENTS

<b>1</b>	<b>Introduction</b>	<b>1</b>
1.1	Overview . . . . .	1
1.2	Quick Installation into PyMOL . . . . .	1
1.3	Example Basic Run . . . . .	1
<b>2</b>	<b>Installation</b>	<b>2</b>
2.1	Installation into PyMOL from PyPI . . . . .	2
2.2	Installation into PyMOL Using a Packaged Installer . . . . .	2
2.3	Manual Installation . . . . .	2
2.4	MSMS Installation . . . . .	3
2.5	Updating . . . . .	3
2.6	Uninstalling . . . . .	3
<b>3</b>	<b>Basic Usage</b>	<b>4</b>
3.1	Protein Selection . . . . .	4
3.2	Min and Max Radii . . . . .	4
3.3	Input Constraint . . . . .	5
<b>4</b>	<b>Pocket Specification</b>	<b>6</b>
4.1	Largest Mode . . . . .	6
4.2	All Mode . . . . .	7
4.3	Specific Mode . . . . .	7
<b>5</b>	<b>Partitioning Options</b>	<b>9</b>
5.1	Enabling Subpocket Partitioning . . . . .	9
5.2	Limiting the Number of Subpockets . . . . .	9
5.3	Smoothness of the Subpocket Surfaces . . . . .	10
<b>6</b>	<b>Output and Display Options</b>	<b>11</b>
6.1	File Output Options . . . . .	11
6.2	Display Options . . . . .	11
<b>7</b>	<b>Shell Interface</b>	<b>13</b>
7.1	Running from the Shell . . . . .	13
7.2	Template Configuration File Generation . . . . .	13
7.3	Notes on Output . . . . .	13
<b>8</b>	<b>Loading Previous Results</b>	<b>14</b>
8.1	Selecting Saved Results . . . . .	14
8.2	Display Options . . . . .	14

<b>9</b>	<b>Development</b>	<b>15</b>
9.1	Package Design . . . . .	15
9.2	Algorithm Design . . . . .	15
9.3	GUI Design . . . . .	15
9.4	Version Incrementation . . . . .	15
9.5	Distribution . . . . .	15
9.6	Documentation . . . . .	16
<b>10</b>	<b>PyVOL Package</b>	<b>17</b>
10.1	Submodules . . . . .	17
10.2	PyVOL Cluster Module . . . . .	17
10.3	PyVOL Identify Module . . . . .	18
10.4	PyVOL Pymol Interface Module . . . . .	19
10.5	PyVOL Pymol Utilities Module . . . . .	20
10.6	PyVOL Spheres Module . . . . .	21
10.7	PyVOL Utilities Module . . . . .	22
10.8	PyVOL Main Entry Point . . . . .	23
10.9	PyVOL GUI . . . . .	23
	<b>Python Module Index</b>	<b>24</b>
	<b>Index</b>	<b>25</b>

## INTRODUCTION

### 1.1 Overview

PyVOL is a python library packaged into a [PyMOL](#) GUI for identifying protein binding pockets, partitioning them into sub-pockets, and calculating their volumes. PyVOL can be run as a PyMOL plugin through its GUI or the PyMOL prompt, as an imported python library, or as a command-line program. Visualization of results is exclusively supported through PyMOL though exported surfaces are compatible with standard 3D geometry visualization programs.

### 1.2 Quick Installation into PyMOL

PyVOL can be installed into any python environment, but installing directly into PyMOL 2.0+ is easiest. Download the `basic GUI installer` and then use the PyMOL plugin manager to install that file: *Plugins* → *Plugin Manager* → *Install New Plugin* → *Install from local file* → *Choose file...*

This installs the PyVOL GUI. Select *Plugins* → *PyVOL* → *Settings* → *Install PyVOL from PyPI* to fetch PyVOL and any missing dependencies. For academic users and non-academic users with the Schrodinger incentive PyMOL distribution, installation is now complete. For all others [MSMS Installation](#).

### 1.3 Example Basic Run

A simple calculation using the PyMOL prompt is to load a protein of interest and then run the *pocket* command. This is an example for the Sorafenib-bound structure of BRAF:

```
fetch '1UWH'
pocket "1UWH and chain B"
```

## INSTALLATION

PyVOL consists of a back-end and a GUI. The back-end has been packaged into installers that contain all dependencies, but normal distribution is through PyPI and accessed through *pip*. PyVOL can consequently be installed into any python environment. For convenience, the PyVOL GUI contains an installer for easy installation into PyMOL 2.0+.

### 2.1 Installation into PyMOL from PyPI

Download the `basic GUI installer` and then use the PyMOL plugin manager to install that file: *Plugins* → *Plugin Manager* → *Install New Plugin* → *Install from local file* → *Choose file...*

This installs the PyVOL GUI. Select *Plugins* → *PyVOL* → *Settings* → *Install PyVOL from PyPI* to fetch PyVOL and any missing dependencies. For academic users and non-academic users with the Schrodinger incentive PyMOL distribution, installation is now complete. For all others [MSMS Installation](#).

### 2.2 Installation into PyMOL Using a Packaged Installer

A larger installer with cached copies of PyVOL and its dependencies is also available. This option is useful if deploying PyVOL onto computers without internet access or if accessing a stable snapshot of a working build is necessary for some reason. Download the `full GUI installer` and then use the PyMOL plugin manager to install that file: *Plugins* → *Plugin Manager* → *Install New Plugin* → *Install from local file* → *Choose file...*

This installs the PyVOL GUI. Select *Plugins* → *PyVOL* → *Settings* → *Install PyVOL from Cache* to install PyVOL and any missing dependencies from the installer. For academic users and non-academic users with the Schrodinger incentive PyMOL distribution, installation is now complete. For all others [MSMS Installation](#).

### 2.3 Manual Installation

PyVOL minimally requires *biopython*, *MSMS*, *numpy*, *pandas*, *scipy*, *scikit-learn*, *trimesh*, and *msms* in order to run. PyVOL is available for manual installation from [github](#) or through [PyPI](#). Most conveniently:

```
pip install bio-pyvol
```

Again, for academic users and non-academic users with the Schrodinger incentive PyMOL distribution, installation is now complete. For all others, see manual [MSMS Installation](#).

---

**Note:** When using command-line installation commands, make sure to use the right python environment. By default, *pip* will use the system python, but PyMOL often includes its own python environment. To check which python environment to use, run `import sys; print(sys.executable)` on the PyMOL prompt. If that is anything besides the

system default python, use `<PyMOL python executable> -m pip install bio-pyvol` to install PyVOL into the PyMOL-accessible environment.

---

## 2.4 MSMS Installation

MSMS is provided with PyVOL for ease of use for academic users. It alternatively can be installed on MacOS and Linux using the bioconda channel:

```
conda install -c bioconda msms
```

Otherwise MSMS must be installed manually by downloading it from [MGLTools](#) and adding it to the path.

## 2.5 Updating

PyVOL can be updated through the PyMOL GUI simply by navigating *PyVOL* → *Settings* → *Check for Updates*. This queries the PyPI server to detect if an update is available. If an update is available for download, the same button becomes *Update PyVOL* and will update the back-end. The new version of the PyVOL back-end will notify you if it expects an updated GUI. If the GUI also needs to be updated, uninstall the *pyvol\_gui* using *Plugins* → *Plugin Manager* → *Installed Plugins* → *pyvol\_gui x.x.x* → *Uninstall*. Restart PyMOL, download the updated GUI from [github](#), and install the updated GUI as described above.

Alternatively, PyVOL can be manually updated via the command line:

```
pip update bio-pyvol
```

## 2.6 Uninstalling

PyVOL can be uninstalled through its GUI by navigating *PyVOL* → *Settings* → *Uninstall PyVOL*. This uninstalls the back-end. Then use the plugin manager to uninstall the *pyvol\_plugin*.

Again, PyVOL can also be uninstalled via the command line:

```
pip uninstall bio-pyvol
```

## BASIC USAGE

The GUI and PyMOL prompt interfaces are all but identical. The shell interface is run using input configuration files and is best used to automate tasks first tested within PyMOL. Explanations for running PyVOL with the PyMOL GUI or prompt are covered first. Additional details covering shell invocation follow. Programmatic invocation of internal functions is supported and covered through the module documentation.

The next few sections describe the parameters controlling Basic Usage, *Pocket Specification*, *Partitioning Options*, and display:Display and Output Options along with the corresponding GUI sections.

Basic Parameters

Protein Pymol Selection:

☒ i.e. only include PyMOL 'poly'

Minimum Radius: [1.2, 2.0]

Maximum Radius: [2.0, 5.0]

☒ Constrain Inputs to Tested Ranges (Recommended)

Fig. 1: The Basic Parameters section of the PyVOL GUI

### 3.1 Protein Selection

The *Protein Selection* (command-line *protein* required to be in the first position) is a PyMOL selection string that identifies all atoms that should be considered to occlude space. This can be any interpretable PyMOL selection. The *only include PyMOL 'poly'* checkbox (command-line *exclude\_org*) is a convenience option that simply appends 'and poly' to the given selection string to exclude water, solvents, and any other small molecule, non-peptide atoms. If a cofactor should be considered part of the binding site, it might make sense to group it in with the peptide for calculating the solvent accessible surface effectively present for the small molecule of interest.

```
pocket <protein selection>
```

### 3.2 Min and Max Radii

The most important parameters (command-line *min\_rad* and *max\_rad*) controlling PyVOL pocket identification and boundary location are the minimum and maximum radii used for surface identification. The maximum radius determines the size of the probe used to identify regions accessible to bulk solvent. This parameter should be chosen to exclude any binding pockets of interest while not overly distorting the surface of the protein. Generally, values around

3.4 Å are reasonable, but lower values can be provided to increase the stringency of pocket detection or higher values to reduce the stringency. The minimum radius controls two factors: The level of detail of the calculated binding pocket surfaces and the algorithmic lower limit to minimum internal radii of identified binding pockets. Lower minimum radii calculate the accessibility to smaller solvent molecules. This necessarily increases the number of nooks or crannies in the binding pocket surface that are calculated and can link adjacent pockets that can not accommodate even small organic molecules. Minimum radii as large as the smallest pharmacophore radius of potential ligands make sense for calculations, but the radius of water is default and normally best because it is what users expect when looking at solvent accessible surfaces.

```
pocket <protein selection>, max_rad=<3.4>, min_rad=<1.4>
```

## 3.3 Input Constraint

By default, input quantitative parameters are compared and constrained to test ranges. The *Constrain Inputs to Tested Ranges* (command-line *constrain\_inputs*) toggles this feature. While edge cases are possible in which violating constraints is useful, in practice these constraints represent effective ranges. In particular, setting the minimum radius to absurdly low values will start fitting pockets in even intramolecular spaces and provide meaningless output if not a crash.

```
pocket <protein selection>, constrain_inputs=True
```

---

**Note:** Be careful about saving *.pse* PyMOL sessions with PyVOL-produced surfaces. PyMOL does not currently use plugins to load unfamiliar CGO objects, so calculated surfaces will not load correctly from a saved PyMOL session. On the other hand, saved PyMOL *.pml* logs should recreate results. Surfaces can be loaded back into a session using the *Load Pocket* (command-line *load\_pocket*) commands.

---



## POCKET SPECIFICATION

PyVOL runs in one of three modes (*largest*, *specific* or *all*). By default it runs in *largest* mode and returns only a single volume and geometry. However, manual identification of the pocket of interest is generally preferable. This can be done through specification of a ligand, a residue, or a coordinate. If any specification is given, the mode is changed to *specific* by default. The *specific* mode is the fastest by a small margin because it calculates the fewest surfaces. All parameters controlling pocket specification are contained in the corresponding GUI section.

Fig. 1: GUI section controlling user specification of binding pockets

### 4.1 Largest Mode

In the default *largest* mode, PyVOL determines all surfaces with inward-facing normals, calculates the volume of each, and selects the largest. The pocket selected with this mode can normally choose the pharmacologically interesting pocket in a protein. However, sometimes changes in the minimum or maximum radius can lead to the unexpected selection of an alternative pocket.

```
# Equivalent expressions
pocket <protein_selection>
pocket <protein_selection>, mode="largest"
```

## 4.2 All Mode

When running in *all* mode, PyVOL determines all surfaces with inward-facing normals with volume over a minimum threshold defined by the *Minimum Volume* (command-line *minimum\_volume*). This functions similarly to the *largest* mode except that 1) all surfaces are returned rather than just the largest, 2) if the largest surface has a volume less than *Minimum Volume*, no surface will be returned, and 3) subpocket partitioning cannot occur on the output from this mode. By default the *Minimum Volume* is set to 200 Å<sup>3</sup>. This is a heuristically determined threshold that is generally useful at distinguishing between artifacts and interesting pockets.

```
pocket <protein_selection>, mode="all", minimum_volume=<200>
```

## 4.3 Specific Mode

The final mode, the *specific* mode, is invoked through specification of a ligand, residue, or coordinate. PyVOL automatically switches to this mode if any specification is provided. There is an internal priority to which specification is used, but only a single option should be used.

### 4.3.1 Ligand Specification

A ligand occupying the binding pocket of interest can be specified using the GUI's *Ligand*: → *PyMOL Selection* field (command-line *ligand*). If the ligand selection is included in the protein selection, it is removed from the protein selection before the algorithm runs.

```
# Equivalent expressions
pocket <protein_selection>, mode="specific", ligand=<ligand_selection>
pocket <protein_selection>, ligand=<ligand_selection>

# Trivial case in which a single organic small molecule is present in the protein_
↪selection
pocket <protein_selection>, ligand="<protein_selection> and org"
```

Supplying a ligand opens up two additional options. *Inclusion Radius* (command-line *lig\_incl\_rad*) prevents the exterior surface of the protein (bulk solvent surface definition) from being defined within that distance from the ligand. In cases where a ligand extends somewhat into solvent and calculated volumes would otherwise be smaller than the volume of the known ligand, this can be used to produce a more useful surface. *Exclusion Radius* (command-line *lig\_excl\_rad*) limits the maximum scope of the identified surface as the locus of points that distance from the supplied ligand. Both of these options introduce a heuristic that alters reported results. They are most useful when standardizing volumes across a series of similar structures as they provide a mechanism to limit volume variability due to variation in bulk solvent boundary determination.

```
pocket <protein_selection>, ligand=<ligand_selection>, lig_incl_rad=<3.5>, lig_excl_
↪rad=<5.2>
```

### 4.3.2 Residue Specification

A residue can be supplied to localize a pocket. This can be done either with a PyMOL selection string or by specifying a residue ID. The *Residue PyMOL Selection* (command-line *residue*) takes an input PyMOL selection (which can be arbitrarily large or small but was designed to hold a single side chain). The *Residue Id* (command-line *resid*) accepts a string specifying an optional chain and a required residue index. For example, residue 35 of chain A would be specified by 'A35'. If only a single chain is present, the chain identifier can be omitted. PyVOL tries to identify the

residue atom closest to an interior surface and uses that atom to specify the adjacent pocket of interest. Sometimes a residue is adjacent to multiple pockets. That makes it a poor, unpredictable choice for specification. If having trouble, specify a single atom as a PyMOL selection string.

```
pocket <protein_selection>, resid=<A15>  
pocket protein_selection, residue=<residue_selection>
```

### 4.3.3 Coordinate Specification

The final method for specifying a pocket interest is through providing a *Coordinate* (command-line *pocket\_coordinate*) that is within the pocket. PyVOL identifies the closest atom in the protein selection to the supplied coordinate and uses it to define the surface of the calculated pocket. The coordinate value is accepted as a string of three floats with spaces in between values ("x y z"). When running on the command-line, quotation marks are necessary given default argument processing.

```
pocket protein_selection, pocket_coordinate="5.0 10.0 15.0"
```

## PARTITIONING OPTIONS

PyVOL can deterministically divide a binding pocket into subpockets. This can be run on the output of any surface determination that results in a single returned surface. PyVOL currently calculates *de novo* complete binding pocket surfaces prior to partitioning because determination of the overall pocket is computationally trivial relative to subdivision.

Partitioning Parameters

☐ Subdivide (incompatible with 'all' mode)

Maximum Sub-pockets: (2+)

Minimum Internal Radius: [1.4, 3.0]

Minimum Surface Radius: [1.0, 2.0]

Fig. 1: GUI section controlling user binding pocket partition into subpockets

### 5.1 Enabling Subpocket Partitioning

Subpocket partitioning is enabled in the GUI by selecting the *Subdivide* checkbox (command-line *subdivide*).

```
pocket <protein_selection>, subdivide=True
```

### 5.2 Limiting the Number of Subpockets

Parameters controlling the number of sub-pockets identified generally perform well using defaults; however, they can be easily adjusted as needed. The two most important parameters are the *Maximum Sub-pockets* (command-line *max\_clusters*) and the *Minimum Internal Radius* (command-line *min\_subpocket\_rad*). PyVOL clusters volume into the maximum number regions that make physical sense according to its hierarchical clustering algorithm. This means that there is a maximum number of clusters that is determined by the *Minimum Internal Radius* (the smallest sphere used to identify new regions) and the radial sampling frequency. Through its PyMOL interface, PyVOL currently fixes the radial sampling frequency at 10 Å<sup>-1</sup>. Larger values of the *Minimum Internal Radius* prohibit unique identification of smaller regions. The other parameter, *Maximum Sub-pockets*, sets the maximum number of clusters calculated. If the number of clusters originally determined is greater than the supplied maximum, clusters are iteratively merged using a metric that is related to the edge-weighted surface area between adjacent clusters.

```
pocket <protein_selection>, subdivide=True, min_subpocket_rad=<1.7>, max_clusters=<10>
```

## 5.3 Smoothness of the Subpocket Surfaces

The size of the probe used to calculate surface accessibility of subpockets can be set with the *Minimum Surface Radius* (command-line *min\_subpocket\_surf\_rad*) in the Partitioning Parameters section of the GUI. Calculation stability is less sensitive to the value of this parameter than the overall *Minimum Radius*. In practice, it should be set to a value slightly smaller than the overall *Minimum Radius* but not aphysically small. Unless changing the *Minimum Radius* used for overall calculations, the default value should be left unchanged.

```
pocket <protein_selection>, subdivide=True, min_subpocket_surf_rad=<1.2>
```

## OUTPUT AND DISPLAY OPTIONS

By default, PyVOL simply outputs a log containing volumes and, when invoked through PyMOL, displays pocket boundaries as semi-translucent surfaces. This behavior can be extensively customized.

Fig. 1: GUI section controlling file output and PyMOL visualization of new results

### 6.1 File Output Options

The output name for all computed PyMOL objects and the base filename for any output files can be specified using the *Display Prefix* (command-line *prefix*) option. A prefix is otherwise derived from the input protein selection string.

```
pocket <protein_selection>, prefix=<output_prefix>
```

PyVOL can also write the input and output files to a directory specified with *Output Dir* (command-line *output\_dir*). In this case it writes out the input protein and ligand structures, a csv report of all calculated volumes, and paired csv/stl files containing tangent sphere collections and 3D triangulated mesh files respectively. Relative and absolute paths both work. However, in many cases referencing the home directory with ~ will not access the user's home directory. STL files can be read by almost all 3D file viewers.

```
pocket <protein_selection>, output_dir=<output_dir>
```

### 6.2 Display Options

Calculated surfaces can be visualized in three different ways by setting the *Display Mode* (command-line *display\_mode*) parameter. The following three commands set the output as a solid surface with transparency, a wireframe mesh, and a collection of spheres. Color is set with the *Color* (command-line *color*) parameter that accepts any PyMOL color string. Transparency (when applicable) is set with the *Alpha* (command-line *alpha*) parameter that is a float [0.0, 1.0] that is equal to (1 - transparency).

```
pocket protein_selection, display_mode=solid, alpha=0.85, color=skyblue
pocket protein_selection, display_mode=mesh, color=red
pocket protein_selection, display_mode=spheres, color=firebrick
```

The presets should generally be sufficient, but custom colors can be chosen using the commands given on the PyMOL wiki. When creating multiple surfaces at the same time, PyVOL generates a palette and assigns each surface a different color. This can distinguish an arbitrary number of surfaces. The palette is currently not able to be changed from the default. If specific colors are needed for specific surfaces, the generated surfaces can be read back in

## **SHELL INTERFACE**

PyVOL can also be run from the system command line using bash or any standard shell. If installed using `pip`, a `pyvol` entry point should be automatically installed and made available on the path. Otherwise, manual invocation of `pyvol/___main__.py` should work.

### **7.1 Running from the Shell**

From the command-line, PyVOL is run exclusively using a configuration file.

```
python -m pyvol <input_parameters.cfg>
```

### **7.2 Template Configuration File Generation**

A template configuration file with default values supplied can be generated using:

```
python -m pyvol -t <output_template.cfg>
```

### **7.3 Notes on Output**

Currently, PyVOL only reports standard log output to stdout when run this way. So if an output directory is not provided, there is no easy way to retrieve the results.



## LOADING PREVIOUS RESULTS

PyMOL can not load custom CGO objects back into sessions correctly, so any PyMOL session containing PyVOL surfaces will have issues. PyMOL log files can be used but can take a while to run on slower computers. The *Load Pocket* (command-line *load\_pocket*) command allows previous results to be read back in from file. In order to generate these input files, an *Output Dir* (command-line *output\_dir*) must be set.

Fig. 1: GUI section that loads previous calculations into PyMOL for visualization

### 8.1 Selecting Saved Results

PyVOL saves its output as a collection of two files that hold all of the information to recreate the original *Spheres* object in memory. These files consist of a csv holding *Spheres* data and a 3D file holding surface triangulation information. If a surface has not been computed for a *Spheres* object, the 3D file will not be written out. However, all modes accessible through the PyMOL command-line and GUI interfaces will write a 3D file. The 3D files by default are written in the *ascii STL* format (updated from the wavefront *obj* format in PyVOL 1.2.34 and GUI version 1.1.3). Either the 3D file or the csv can be provided to read in the collection of both.

```
load_pocket <3D or csv file>, name=<new PyMOL name>, display_mode=<"solid">, color=<
↪ "marine">, alpha=<0.5>
```

### 8.2 Display Options

These options in the GUI are identical to the display options when performing a *de novo* calculation. On the command-line, *name* is accepted in place of *prefix*. Please see [Display Options](#) for more information

## DEVELOPMENT

## 9.1 Package Design

The main PyVOL algorithm is run from `identify.py`. There are two interfaces to this module which prepare user supplied inputs: `pyvol/pymol_interface.py` and the commandline entry point in `pyvol/__main__.py`. The PyMOL interface can be accessed directly through the PyMOL prompt or run using the included GUI. The command line entry point is evoked using a configuration file. The main entry point for accessing with the API is through `pyvol/identify.py`.

## 9.2 Algorithm Design

The primary algorithmic logic is supplied in `identify.py` which acts as the only interface between the user-facing modules and the computational back-end.

The Spheres class holds all of the geometric information about proteins and pockets. It represents any object as a collection of spheres by holding their coordinates, radii, and cluster identifications in a 5D numpy array. Surface triangulation using MSMS and many other convenience functions are included in the class itself. The methods contained in the separate `cluster.py` would largely work as methods in the Spheres class but have been separated due to that class becoming too large and the specificity of those methods to subpocket partitioning.

## 9.3 GUI Design

The GUI was developed using Qt Designer and run using PyQt5. PyQt does not run in earlier PyMOL distributions.

## 9.4 Version Incrementation

PyVOL uses a standard incrementation scheme. The version of the back-end must be updated in `setup.py`, `pyvol/__init__.py`, and `docs/source/conf.py`. The GUI version is set in `pyvolgui/__init__.py`, and the the version of the GUI that the back-end expects is set again in `pyvol/__init__.py`.

## 9.5 Distribution

The code is hosted on github by the Schlessinger Lab. The PyVOL backend is distributed through PyPI. This process of uploading to PyPI is automated in the `dev/build.sh` script. Installers are packaged using the `dev/package_plugins.sh` script. Documentation is generated and pushed to the github-hosted documentation website with the `dev/document.sh`

script. All three are combined in the *dev/rebuild.sh* script. The plugin will be available both from the github page and through the official PyMOL wiki.

## 9.6 Documentation

Documentation is largely in the google style but being switched to sphinx style. Module documentation is collated using *sphinx-apidoc*. The documentation website is built using the *sphinx-rtd-theme* and maintained on the gh-pages branch of PyVOL. The *pyvol\_manual.pdf* is generated using sphinx's evocation of pdfTeX. PyPI can apparently not parse rst files, so the README.rst is converted to a md file using pandoc just prior to deployment.

## PYVOL PACKAGE

## 10.1 Submodules

## 10.2 PyVOL Cluster Module

`pyvol.cluster.cluster_within_r` (*spheres, radius, allow\_new=True*)

Cluster spheres with the same radius using DBSCAN, modifying input data in situ

**Args:** spheres (Spheres): complete set of input spheres radius (float): radius at which clustering is to occur  
allow\_new (bool): permit new clusters? (Default value = True)

`pyvol.cluster.cluster_between_r` (*spheres, ref\_radius, target\_radius*)

Cluster spheres from a target radius to a reference radius, modifying input data in situ

**Args:** spheres (Spheres): complete set of input spheres ref\_radius (float): radius from which cluster identities will be drawn target\_radius (float): radius to which cluster identities will be propagated

`pyvol.cluster.cluster_improperly_grouped` (*spheres, radius, min\_cluster\_size=1, max\_clusters=None*)

Reassigns improperly clustered spheres to ‘proper’ clusters, modifying input data in situ

**Args:** spheres (Spheres): complete set of input spheres radius (float): radius at which closest groups are identified min\_cluster\_size (int): minimum number of spheres in a ‘proper’ cluster (Default value = 1)  
max\_clusters (int): maximum number of ‘proper’ clusters (Default value = None)

`pyvol.cluster.extract_groups` (*spheres, surf\_radius=None, prefix=None*)

Extracts spheres belonging to each cluster from the complete input set and optionally calculates bounded surfaces

**Args:** spheres (Spheres): complete set of input spheres surf\_radius: radius used to calculate bounding spheres for individual groups (Default value = None) prefix: prefix to identify new surfaces (Default value = None)

**Returns:** group\_list ([Spheres]): a list of Spheres objects each corresponding to a different cluster

`pyvol.cluster.hierarchically_cluster_spheres` (*spheres, ordered\_radii, min\_new\_radius=None, min\_cluster\_size=10, max\_clusters=None*)

Cluster spheres by grouping spheres at large radius and propagating those assignments down to smaller radii

**Args:** spheres (Spheres): complete set of input spheres ordered\_radii ([float]): list of radii ordered from largest to smallest min\_new\_radius (float): smallest spheres to keep (Default value = None) min\_cluster\_size (int): minimum number of spheres in a cluster (Default value = 10) max\_clusters (int): maximum number of clusters (Default value = None)

`pyvol.cluster.identify_closest_grouped(spheres, group, radius)`

Identifies the closest ‘properly’ grouped cluster to a specified group

**Args:** spheres (Spheres): complete set of input spheres group (float): group for which to identify the closest clusters radius (float): radius at which to perform the search

**Returns:** group (float): passthrough of input group closest (float): id of the closest cluster magnitude (int): number of pairwise closest connections between the queried group and the closest identified cluster

`pyvol.cluster.merge_sphere_list(s_list, r=None, g=None)`

**Args:** s\_list ([Spheres]): list of input spheres r (float): radius value to assign to output Spheres (Default value = None) g (float): group value to assign to output Spheres (Default value = None)

**Returns:** merged\_spheres (Spheres): a single Spheres object containing the merged input lists

`pyvol.cluster.reassign_group(spheres, source_group, target_group)`

Reassign a group in place

**Args:** spheres (Spheres): complete set of input spheres source\_group (float): group to change target\_group (float): new group id

`pyvol.cluster.reassign_groups_to_closest(spheres, group_list, radius, iterations=None, preserve_largest=False)`

Reassign a group to the closest group as identified by maximum linkage; operates in place

**Args:** spheres (Spheres): complete set of input spheres group\_list ([float]): list of group ids which are to be iteratively reassigned radius (float): radius at which searches are to take place iterations (int): number of times to attempt to reassign groups (Default value = None) preserve\_largest: keep the group id of the group with more members? (Default value = False)

`pyvol.cluster.remove_interior(spheres)`

Remove all spheres which are completely enclosed in larger spheres; operates in place

**Args:** spheres (Spheres): complete set of input spheres

`pyvol.cluster.remove_overlap(spheres, radii=None, spacing=0.1, iterations=20, tolerance=0.02)`

Remove overlap between groups; operates in place

**Args:** spheres (Spheres): complete set of input spheres radii ([float]): radii at which to perform searches for overlap (Default value = None) spacing (float): binning radius (Default value = 0.1) iterations (int): number of times to attempt overlap removal (Default value = 20) tolerance (float): overlap tolerance (Default value = 0.02)

## 10.3 PyVOL Identify Module

`pyvol.identify.pocket(prot_file, mode='largest', lig_file=None, coordinate=None, resid=None, residue_coordinates=None, min_rad=1.4, max_rad=3.4, lig_excl_rad=None, lig_incl_rad=None, subdivide=False, minimum_volume=200, min_subpocket_rad=1.7, min_subpocket_surf_rad=1.0, max_clusters=None, prefix=None, output_dir=None, constrain_inputs=False)`

Calculates the SES for a binding pocket

**Args:** prot\_file (str): filename for the input pdb file containing the peptidee mode (str): pocket identification mode (can be largest, all, or specific) (Default value = “largest”) lig\_file (str): filename for the input pdb file containing a ligand (Default value = None) coordinate ([float]): 3D coordinate used for pocket specification (Default value = None) resid (str): residue identifier for pocket specification (Default value = None) residue\_coordinates ([float]): 3D coordinate of an atom in a surrounding residue used for pocket specification (Default value = None) min\_rad (float): radius for SAS calculations (Default value = 1.4) max\_rad (float): radius used to identify the outer, bulk solvent exposed surface (Default value = 3.4) lig\_excl\_rad

(float): maximum distance from a provided ligand that can be included in calculated pockets (Default value = None) `lig_incl_rad` (float): minimum distance from a provided ligand that should be included in calculated pockets when solvent border is ambiguous (Default value = None) `subdivide` (bool): calculate subpockets? (Default value = False) `minimum_volume` (float): minimum volume of pockets returned when running in 'all' mode (Default value = 200) `min_subpocket_rad` (float): minimum radius that identifies distinct subpockets (Default value = 1.7) `min_subpocket_surf_rad` (float): radius used to calculate subpocket surfaces (Default value = 1.0) `max_clusters` (int): maximum number of clusters (Default value = None) `prefix` (str): identifying string for output (Default value = None) `output_dir` (str): filename of the directory in which to place all output; can be absolute or relative (Default value = None) `constrain_inputs` (bool): restrict quantitative input parameters to tested values? (Default value = False)

**Returns:** `pockets` ([Spheres]): a list of Spheres objects each of which contains the geometric information describing a distinct pocket or subpocket

```
pyvol.identify.subpockets(bounding_spheres, ref_spheres, min_rad, max_rad,
                           min_subpocket_rad=1.7, min_subpocket_surf_rad=1.0,
                           max_subpocket_rad=None, sampling=0.1, inclusion_radius_buffer=1.0,
                           min_cluster_size=50, max_clusters=None, prefix=None)
```

**Args:** `bounding_spheres` (Spheres): a Spheres object containing both the peptide and solvent exposed face external spheres `ref_spheres` (Spheres): a Spheres object holding the interior spheres that define the pocket to be subdivided `min_rad` (float): radius for original SES calculations (Default value = 1.4) `max_rad` (float): radius originally used to identify the outer, bulk solvent exposed surface (Default value = 3.4) `min_subpocket_rad` (float): minimum radius that identifies distinct subpockets (Default value = 1.7) `min_subpocket_surf_rad` (float): radius used to calculate subpocket surfaces (Default value = 1.0) `max_subpocket_rad` (float): maximum spheres radius used for subpocket clustering (Default value = None) `sampling` (float): radial sampling frequency for clustering (Default value = 0.1) `inclusion_radius_buffer` (float): defines the inclusion distance for nonextraneous spheres in combination with `min_rad` and `max_rad` (Default value = 1.0) `min_cluster_size` (int): minimum number of spheres that can constitute a proper cluster (Default value = 50) `max_clusters` (int): maximum number of clusters (Default value = None) `prefix` (str): identifying string for output (Default value = None)

**Returns:** `pockets` ([Spheres]): a list of Spheres objects each of which contains the geometric information describing a distinct subpocket

```
pyvol.identify.write_report(all_pockets, output_dir, prefix)
Write a brief report of calculated volumes to file
```

**Args:** `all_pockets` ([Sphere]): a list of Spheres objects each of which contains the complete information about a distinct pocket or subpocket `output_dir` (str): output directory, relative or absolute `prefix` (str): identifying prefix for output files

## 10.4 PyVOL Pymol Interface Module

```
pyvol.pymol_interface.load_pocket(spheres_file, name=None, display_mode='solid',
                                   color='marine', alpha=0.85)
```

**Args:** `spheres_file` (str): filename `name` (str): internal display name (Default value = None) `display_mode` (str): display mode (Default value = "solid") `color` (str): PyMOL color string (Default value = 'marine') `alpha` (float): transparency value (Default value = 0.85)

```
pyvol.pymol_interface.pocket (protein, mode=None, ligand=None, pocket_coordinate=None,
                               residue=None, resid=None, prefix=None, min_rad=1.4,
                               max_rad=3.4, lig_excl_rad=None, lig_incl_rad=None,
                               display_mode='solid', color='marine', alpha=0.85, out-
                               put_dir=None, subdivide=None, minimum_volume=200,
                               min_subpocket_rad=1.7, min_subpocket_surf_rad=1.0,
                               max_clusters=None, excl_org=False, constrain_inputs=True)
```

Calculates the SAS for a binding pocket and displays it

**Args:** protein (str): PyMOL selection string for the protein mode (str): pocket identification mode (can be largest, all, or specific) (Default value = None) ligand (str): PyMOL selection string for the ligand (Default value = None) pocket\_coordinate ([float]): 3D coordinate used for pocket specification (Default value = None) residue (str): PyMOL residue selection string for pocket specification (Default value = None) resid (str): residue identifier for pocket specification (Default value = None) prefix (str): identifying string for output (Default value = None) min\_rad (float): radius for SAS calculations (Default value = 1.4) max\_rad (float): radius used to identify the outer, bulk solvent exposed surface (Default value = 3.4) lig\_excl\_rad (float): maximum distance from a provided ligand that can be included in calculated pockets (Default value = None) lig\_incl\_rad (float): minimum distance from a provided ligand that should be included in calculated pockets when solvent border is ambiguous (Default value = None) display\_mode (str): display mode for calculated pockets (Default value = "solid") color (str): PyMOL color string (Default value = 'marine') alpha (float): transparency value (Default value = 0.85) output\_dir (str): filename of the directory in which to place all output; can be absolute or relative (Default value = None) subdivide (bool): calculate subpockets? (Default value = None) minimum\_volume (float): minimum volume of pockets returned when running in 'all' mode (Default value = 200) min\_subpocket\_rad (float): minimum radius that identifies distinct subpockets (Default value = 1.7) min\_subpocket\_surf\_rad (float): radius used to calculate subpocket surfaces (Default value = 1.0) max\_clusters (int): maximum number of clusters (Default value = None) excl\_org (bool): exclude non-peptide atoms from the protein selection? (Default value = False) constrain\_inputs (bool): constrain input quantitative values to tested ranges? (Default value = True)

## 10.5 PyVOL Pymol Utilities Module

```
pyvol.pymol_utilities.construct_palette (color_list=None, max_value=7, min_value=1)
```

Construct a palette

**Args:** color\_list ([str]): list of PyMOL color strings (Default value = None) max\_value (int): max palette index (Default value = 7) min\_value (int): min palette index (Default value = 1)

**Returns:** palette ([str]): list of color definitions

```
pyvol.pymol_utilities.display_pseudoatom_group (spheres, name, color='gray60',
                                                  palette=None)
```

Displays a collection of pseudoatoms

**Args:** spheres (Spheres): Spheres object holding pocket geometry name (str): display name color (str): PyMOL color string (Default value = 'gray60') palette ([str]): palette (Default value = None)

```
pyvol.pymol_utilities.display_spheres_object (spheres, name, state=1, color='marine', al-
                                              pha=0.7, mode='solid', palette=None)
```

Loads a mesh object into a cgo list for display in PyMOL

**Args:** spheres (Spheres): Spheres object containing all geometry name (str): display name state (int): model state (Default value = 1) color (str): PyMOL color string (Default value = 'marine') alpha (float): transparency value (Default value = 0.7) mode (str): display mode (Default value = "solid") palette ([str]): palette (Default value = None)

```
pyvol.pymol_utilities.mesh_to_solid_CGO (mesh, color='gray60', alpha=1.0)
```

Creates a solid CGO object for a mesh for display in PyMOL

**Args:** mesh (Trimesh): Trimesh mesh object color (str): PyMOL color string (Default value = 'gray60') alpha (float): transparency value (Default value = 1.0)

**Returns:** cgobuffer (str): CGO buffer that contains the instruction to load a solid object

`pyvol.pymol_utilities.mesh_to_wireframe_CGO (mesh, color='gray60', alpha=1.0)`

Creates a wireframe CGO object for a mesh for display in PyMOL

**Args:** mesh (Trimesh): Trimesh mesh object color (str): PyMOL color string (Default value = 'gray60') alpha (float): transparency value (Default value = 1.0)

**Returns:** cgobuffer (str): CGO buffer that contains the instruction to load a wireframe object

## 10.6 PyVOL Spheres Module

**class** `pyvol.spheres.Spheres` (*xyz=None, r=None, xyzr=None, xyzrg=None, g=None, pdb=None, bv=None, mesh=None, name=None, spheres\_file=None*)

Bases: object

**copy** ()

**calculate\_surface** (*probe\_radius=1.4, cavity\_atom=None, coordinate=None, all\_components=False, exclusionary\_radius=2.5, largest\_only=False, noh=True, minimum\_volume=200*)

Calculate the SAS for a given probe radius

**Args:** probe\_radius (float): radius for surface calculations (Default value = 1.4) cavity\_atom (int): id of a single atom which lies on the surface of the interior cavity of interest (Default value = None) coordinate ([float]): 3D coordinate to identify a cavity atom (Default value = None) all\_components (bool): return all pockets? (Default value = False) exclusionary\_radius (float): maximum permissible distance to the closest identified surface element from the supplied coordinate (Default value = 2.5) largest\_only (bool): return only the largest pocket? (Default value = False) noh (bool): remove waters before surface calculation? (Default value = True) minimum\_volume (int): minimum volume of pockets returned when using 'all\_components' (Default value = 200)

**identify\_nonextraneous** (*ref\_spheres, radius*)

Returns all spheres less than radius away from any center in ref\_spheres using cKDTree search built on the non-reference set

**Args:** ref\_spheres (Spheres): object that defines the pocket of interest radius (float): maximum distance to sphere centers to be considered nonextraneous

**Returns:** nonextraneous (Spheres): a filtered Spheres object

**nearest** (*coordinate, max\_radius=None*)

Returns the index of the sphere closest to a coordinate; if max\_radius is specified, the sphere returned must have a radius <= max\_radius

**Args:** coordinate (float nx3): 3D input coordinate max\_radius (float): maximum permissible distance to the nearest sphere (Default value = None)

**Returns:** nearest\_index: index of the closest sphere

**nearest\_coord\_to\_external** (*coordinates*)

Returns the coordinate of the sphere closest to the supplied coordinates

**Args:** coordinates (float nx3): set of coordinates

**Returns:** coordinate (float 1x3): coordinate of internal sphere closest to the supplied coordinates



**remove\_duplicates** (*eps=0.01*)

Remove duplicate spheres by identifying centers closer together than *eps* using DBSCAN

**Args:** *eps* (float): DBSCAN input parameter (Default value = 0.01)

**remove\_ungrouped** ()

Remove all spheres that did not adequately cluster with the remainder of the set

**remove\_groups** (*groups*)

Remove all spheres with specified group affiliations

**Args:** *groups* ([float]): list of groups to remove

**write** (*filename, contents='xyzrg', output\_mesh=True*)

Writes the contents of *\_xyzrg* to a space delimited file

**Args:** *filename* (str): filename to write the report and mesh if indicated *contents* (str): string describing which columns to write to file (Default value = "xyzrg") *output\_mesh* (bool): write mesh to file? (Default value = True)

**xyzrg**

Retrieve the coordinates, radii, and group ids

**xyzr**

Retrieve coordinates and radii

**xyz**

Retrieve the coordinates

**r**

Retrieve the radii

**g**

Retrieve the group indices

## 10.7 PyVOL Utilities Module

`pyvol.utilities.check_dir` (*location*)

Ensure that a specified directory exists

**Args:** *location* (str): target directory

`pyvol.utilities.coordinates_for_resid` (*pdb\_file, resid, chain=None, model=0*)

Extract the 3D coordinates for all atoms in a specified residue from a pdb file

**Args:** *pdb\_file* (str): filename of the specified pdb file *resid* (int): residue number *chain* (str): chain identifier (Default value = None) *model* (int): model identifier (Default value = 0)

**Returns:** *coordinates* ([[float]]): 3xN array containing all atomic positions

`pyvol.utilities.run_cmd` (*options, in\_directory=None*)

Run a program using the command line

**Args:** *options* ([str]): list of command line options *in\_directory* (str): directory in which to run the command (Default value = None)

`pyvol.utilities.surface_multiprocessing` (*args*)

A single surface calculation designed to be run in parallel

**Args:**

**args: a tuple containing:** spheres (Spheres): a Spheres object containing all surface producing objects  
probe\_radius (float): radius to use for probe calculations  
kwargs (dict): all remaining arguments accepted by the surface calculation algorithm

**Returns:** surface (Spheres): the input Spheres object but with calculated surface parameters

`pyvol.utilities.sphere_multiprocessing(spheres, radii, workers=None, **kwargs)`

A wrapper function to calculate multiple surfaces using multiprocessing

**Args:** spheres (Spheres): input Spheres object  
radii ([float]): list of radii at which surfaces will be calculated  
workers (int): number of workers (Default value = None)  
kwargs (dict): all remaining arguments accepted by surface calculation that are constant across parallel calculations

**Returns:** surfaces ([Spheres]): a list of Spheres object each with its surface calculated

## 10.8 PyVOL Main Entry Point

`pyvol.__main__.create_default_cfg(cfg_file='defaults.cfg')`

Writes a template cfg file to disk

**Args:** cfg\_file (str): target configuration file (Default value = “defaults.cfg”)

`pyvol.__main__.run_from_cfg(cfg_file)`

**Args:** cfg\_file (str): input cfg that specifies a PyVOL job

## 10.9 PyVOL GUI

`pyvol.pyvol_gui.__init__.pyvol_window()`

`pyvol.pyvol_gui.__init__.browse_pocket_file(form)`

Launches a window to select a file

`pyvol.pyvol_gui.__init__.install_remote_pyvol(form)`

Attempts a de novo PyVOL installation using pip

`pyvol.pyvol_gui.__init__.install_local_pyvol(form)`

`pyvol.pyvol_gui.__init__.uninstall_pyvol(form)`

Attempts to uninstall PyVOL using pip

`pyvol.pyvol_gui.__init__.update_pyvol(form)`

Attempts to update PyVOL using pip

`pyvol.pyvol_gui.__init__.refresh_installation_status(form, check_for_updates=False)`

Check for updates and adjust the GUI to reflect the current installation status and availability of updates

**Args:** check\_for\_updates (bool): query servers to see if an update is available? (Default value = False)

`pyvol.pyvol_gui.__init__.run_gui_load(form)`

Loads a precalculated pocket into PyMOL

`pyvol.pyvol_gui.__init__.run_gui_pyvol(form)`

Runs a PyVOL calculation

## PYTHON MODULE INDEX

### p

- `pyvol.__main__`, [23](#)
- `pyvol.cluster`, [17](#)
- `pyvol.identify`, [18](#)
- `pyvol.pymol_interface`, [19](#)
- `pyvol.pymol_utilities`, [20](#)
- `pyvol.pyvol_gui.__init__`, [23](#)
- `pyvol.spheres`, [21](#)
- `pyvol.utilities`, [22](#)

## B

`browse_pocket_file()` (in module `pyvol.pyvol_gui.__init__`), 23

## C

`calculate_surface()` (`pyvol.spheres.Spheres` method), 21

`check_dir()` (in module `pyvol.utilities`), 22

`cluster_between_r()` (in module `pyvol.cluster`), 17

`cluster_improperly_grouped()` (in module `pyvol.cluster`), 17

`cluster_within_r()` (in module `pyvol.cluster`), 17

`construct_palette()` (in module `pyvol.pymol_utilities`), 20

`coordinates_for_resid()` (in module `pyvol.utilities`), 22

`copy()` (`pyvol.spheres.Spheres` method), 21

`create_default_cfg()` (in module `pyvol.__main__`), 23

## D

`display_pseudoatom_group()` (in module `pyvol.pymol_utilities`), 20

`display_spheres_object()` (in module `pyvol.pymol_utilities`), 20

## E

`extract_groups()` (in module `pyvol.cluster`), 17

## G

`g` (`pyvol.spheres.Spheres` attribute), 22

## H

`hierarchically_cluster_spheres()` (in module `pyvol.cluster`), 17

## I

`identify_closest_grouped()` (in module `pyvol.cluster`), 17

`identify_nonextraneous()` (`pyvol.spheres.Spheres` method), 21

`install_local_pyvol()` (in module `pyvol.pyvol_gui.__init__`), 23

`install_remote_pyvol()` (in module `pyvol.pyvol_gui.__init__`), 23

## L

`load_pocket()` (in module `pyvol.pymol_interface`), 19

## M

`merge_sphere_list()` (in module `pyvol.cluster`), 18

`mesh_to_solid_CGO()` (in module `pyvol.pymol_utilities`), 20

`mesh_to_wireframe_CGO()` (in module `pyvol.pymol_utilities`), 21

## N

`nearest()` (`pyvol.spheres.Spheres` method), 21

`nearest_coord_to_external()` (`pyvol.spheres.Spheres` method), 21

## P

`pocket()` (in module `pyvol.identify`), 18

`pocket()` (in module `pyvol.pymol_interface`), 19

`pyvol.__main__` (module), 23

`pyvol.cluster` (module), 17

`pyvol.identify` (module), 18

`pyvol.pymol_interface` (module), 19

`pyvol.pymol_utilities` (module), 20

`pyvol.pyvol_gui.__init__` (module), 23

`pyvol.spheres` (module), 21

`pyvol.utilities` (module), 22

`pyvol_window()` (in module `pyvol.pyvol_gui.__init__`), 23

## R

`r` (`pyvol.spheres.Spheres` attribute), 22

`reassign_group()` (in module `pyvol.cluster`), 18

`reassign_groups_to_closest()` (in module `pyvol.cluster`), 18

`refresh_installation_status()` (in module `pyvol.pyvol_gui.__init__`), 23

`remove_duplicates()` (*pyvol.spheres.Spheres method*), 21  
`remove_groups()` (*pyvol.spheres.Spheres method*), 22  
`remove_interior()` (*in module pyvol.cluster*), 18  
`remove_overlap()` (*in module pyvol.cluster*), 18  
`remove_ungrouped()` (*pyvol.spheres.Spheres method*), 22  
`run_cmd()` (*in module pyvol.utilities*), 22  
`run_from_cfg()` (*in module pyvol.\_\_main\_\_*), 23  
`run_gui_load()` (*in module pyvol.pyvol\_gui.\_\_init\_\_*), 23  
`run_gui_pyvol()` (*in module pyvol.pyvol\_gui.\_\_init\_\_*), 23

## S

`sphere_multiprocessing()` (*in module pyvol.utilities*), 23  
`Spheres` (*class in pyvol.spheres*), 21  
`subpockets()` (*in module pyvol.identify*), 19  
`surface_multiprocessing()` (*in module pyvol.utilities*), 22

## U

`uninstall_pyvol()` (*in module pyvol.pyvol\_gui.\_\_init\_\_*), 23  
`update_pyvol()` (*in module pyvol.pyvol\_gui.\_\_init\_\_*), 23

## W

`write()` (*pyvol.spheres.Spheres method*), 22  
`write_report()` (*in module pyvol.identify*), 19

## X

`xyz` (*pyvol.spheres.Spheres attribute*), 22  
`xyzr` (*pyvol.spheres.Spheres attribute*), 22  
`xyzrg` (*pyvol.spheres.Spheres attribute*), 22