

Productivity Index - Output - By Quantity

Emily Markowitz (Emily.Markowitz@noaa.gov) and Sun-Ling Wang

Feb. 27, 2020

Contents

1	Math Theory: General Total Factor Productivity (<i>TFP</i>) Equation	2
2	Output Method: From Quantity to Quantity Measures	3
2.0.1	Variable Summary	3
2.0.2	Data requirements	3
2.0.2.1	Edit Data	3
2.0.2.2	The naming conventions of the column names.	4
2.0.3	Lets get started	4
2.0.4	Remove any V and Q data where V column has less data than the specied <i>pctmiss</i>	6
2.0.5	Calucate Category Sums of <i>V</i> and <i>Q</i>	6
2.0.5.1	1. If there are instances for a species where there are too few pairs of <i>Q</i> are completely missing from the timeseries or where a percent of <i>Q</i> is missing from the timeseries, we will remove the offending price columns entirely, so they don't influence the downstream price change or price index calculations.	7
2.0.5.2	2. If the first value of $Q_{t,i,s}$ is 0/NA in a timeseries, we (impute) let the next available non-zero/non-NA value of <i>Q</i> in the timeseries inform the past.	8
2.0.5.3	3. If there is a value in the middle of $P_{t,i,s}$'s timeseries that is 0/NA, we (impute) let the most recent past available non-zero/non-NA of $P_{t,i,s}$ in the timeseries inform the future.	9
2.0.6	Impute values of $V_{t,i,s}$ where P was able to be calculated	9
2.0.6.1	1. If the first value of $V_{t,i,s}$ is 0/NA in a timeseries, we let the next available non-zero value of $V_{t,i,s}$ in the timeseries inform the past.	10
2.0.6.2	2. If there is a value in the middle of $V_{t,i,s}$'s timeseries that is 0/NA, we let the most recent past available non-zero of $V_{t,i,s}$ in the timeseries inform the future.	10
2.0.7	Value of species $VV_{t,i}$ where Q available	10
2.0.8	Revenue Share for each species ($R_{t,i,s}$; e.g., Salmon and Flounder)	11
2.0.8.1	Analysis Warnings Checks	12
2.0.9	Revenue Share-Weighted Qunatity Changes for each species ($QCW_{t,i,s}$; e.g., Salmon and Flounder)	12
2.0.10	Quantity Changes for the category ($QC_{t,i}$; e.g., Finfish)	13
2.0.11	Quantity Index for the each category ($QI_{t,i}$)	13
2.1	Redo Analysis for Shellfish	14
2.1.1	Value for all fisheries for species where Q was able to be calculated	20
2.1.2	Revenue Share for the each category ($R_{t,i}$)	21
2.1.2.1	Analysis Warnings Checks	22
2.1.3	Revenue Share-Weighted Qunatity Changes for each category ($QCW_{t,i}$; e.g., Finfish and Shellfish)	22
2.1.4	Quantity Changes for the entire fishery (QC_t)	23
2.1.5	Quantity Index for the entier fishery (QI_t)	23

2.1.6	Sum Total Simple Sum Quantity Output Index	24
2.2	Other Analysis Warnings Checks	25
2.2.0.1	When back calculated, growth rate?	25
2.2.1	View Total Outputs	26
2.2.2	Missing Data	26
2.2.3	Graph 1: Price Index	27
2.2.4	Graph 2: Quantity Index Compare	28
2.2.5	Graph 3: Quantity Compare	29
2.3	Do same analysis via a function!	30
2.3.1	Function	30
2.3.2	A. Import and Edit data	45
2.3.3	B. Enter base year	46
2.3.4	C. Run the function	46
2.3.5	D. Obtain the implicit quantity estimates	46
2.3.6	E. Graph	46
2.3.6.1	Graph 1: Price Index	46
2.3.6.2	Graph 2: Quantity Index Compare	46
2.3.6.3	Graph 3: Quantity Compare	47

1 Math Theory: General Total Factor Productivity (*TFP*) Equation

The general form of the *TFP* can be measured as aggregate output (*Y*) divided by real total inputs (*X*). Rates of TFP growth are constructed using the Törnqvist index approach. The TFP growth over two time periods is defined as:

$$\ln(TFP_t/TFP_{t-1}) = \sum_{i=1}^n \left(\left(\frac{R_{it} + R_{it-1}}{2} \right) * \ln\left(\frac{Y_{it}}{Y_{it-1}}\right) \right) - \sum_{j=1}^m \left(\left(\frac{W_{jt} + W_{jt-1}}{2} \right) * \ln\left(\frac{X_{jt}}{X_{jt-1}}\right) \right)$$

Such that:

- Output = $\sum_{i=1}^n \left(\left(\frac{R_{it} + R_{it-1}}{2} \right) * \ln\left(\frac{Y_{it}}{Y_{it-1}}\right) \right)$
- Input = $\sum_{j=1}^m \left(\left(\frac{W_{jt} + W_{jt-1}}{2} \right) * \ln\left(\frac{X_{jt}}{X_{jt-1}}\right) \right)$

where:

- Y_i are individual outputs. This will later be referred to as Q_i in the following equations.
- X_j are individual inputs
- R_i are output revenue shares
- W_j are input cost shares
- t and $t - 1$ are time subscripts, where 1 is the minimum year in the dataset
- i is category, e.g., Finfish (=1), Shellfish (=2)
- s is species, e.g., Salmon, Alewife, Surf Clams

2 Output Method: From Quantity to Quantity Measures

2.0.1 Variable Summary

Variables

- Q are individual quantity outputs in pounds (lbs).
- V are individual value outputs in dollars (\$)
- R are output revenue shares
- $baseyr$ is the year to base all indicies from

Indicies

- t and $t - 1$ are time subscripts, where 1 is the minimum year in the dataset
- i is category, e.g., Finfish (=1), Shellfish (=2)
- s is species, e.g., Salmon, Alewife, Surf Clams

2.0.2 Data requirements

We need time series data for the value of all species (V_i ; e.g., Total), value of all species in a category (i) ($V_{i=1}$; e.g., Finfish), value of each species in a category (i) ($V_{i=1,s=n}$; e.g., Salmon and Summer Flounder), quantity of all species in a category (i) (in lbs, $Q_{i=1}$; e.g., Finfish and others), and the quantity of each species in a category (i) ($Q_{i=1,s=n}$; e.g., Salmon and Flounder):

2.0.2.1 Edit Data

Here we summate the category and total V because there may be instances where these values may not be the sum of their parts (though they are here). The caluculation Price Index aims to deal with this potential issue.

```
temp<-read.csv(file = paste0(dir.data, "Tornqvist Index-Calculations_OutputEx.csv"))
rownames(temp)<-temp$year
temp$year<-NULL

temp.q<-temp[,grepl(pattern = "Q", x = names(temp))]
temp.q$QE0_0Total<-rowSums(temp.q, na.rm = T)
temp.q$QE1_0Finfish<-rowSums(temp.q[,grepl(x = names(temp.q), pattern = "Q1") ], na.rm = T)
temp.q$QE2_0Shellfish<-rowSums(temp.q[,grepl(x = names(temp.q), pattern = "Q2") ], na.rm = T)

temp.v<-temp[,grepl(pattern = "V", x = names(temp))]
temp.v$VE0_0Total<-rowSums(temp.v, na.rm = T)
temp.v$VE1_0Finfish<-rowSums(temp.v[,grepl(x = names(temp.v), pattern = "V1") ], na.rm = T)
temp.v$VE2_0Shellfish<-rowSums(temp.v[,grepl(x = names(temp.v), pattern = "V2") ], na.rm = T)

temp<-orgional.data<-cbind.data.frame(temp.q, temp.v)

# temp<-orgional.data
# temp$Q1_6Flounder<-rnorm(n = nrow(temp), mean = 300, sd = 100)
# temp$Q0_0Total<-temp$QE0_0Total
```

	Q1_1Salmon	Q1_2Cod	Q2_1Shrimp	Q2_2Clam	Q1_3Flounder	Q1_4SeaBass	QE0_0Total	QE1_0F
2007	NA	2000	100	150	NA	1000	3250	
2008	NA	1900	120	160	NA	1200	3380	

	Q1_1Salmon	Q1_2Cod	Q2_1Shrimp	Q2_2Clam	Q1_3Flounder	Q1_4SeaBass	QE0_0Total	QE1_0F
2009	NA	2000	110	140	NA	900	3150	
2010	20	2500	90	NA	NA	NA	2610	
2011	10	2400	80	NA	NA	NA	2490	
2012	12	2300	100	NA	NA	NA	2412	
2013	11	2000	100	140	NA	1000	3251	
2014	11	2300	110	110	NA	900	3431	
2015	10	2400	90	130	NA	1000	3630	
2016	15	2200	100	160	NA	1100	3575	

2.0.2.2 The nameing conventions of the column names.

For example, in “V1_0Finfish”:

- “V”... refers to the variable represented in the column (here V = “Value”)
- ... “1”... refers to the category index (here, = Finfish)
- ... “_”... is simply a seperator in the title
- Since this is the total, ... “0”.. refers to the index of the species, which is not relevant since this is the sum of the category, hense = 0
- ... “Finfish” is purely descriptive (here the name of the category), so you can follow along with what is happening!

Similarly for “Q2_2Clam”:

- “Q”... refers to the variable represented in the column (here Q = “Quantity”)
- ... “2”... refers to the category index (here, = Shellfish)
- ... “_”... is simply a seperator in the title
- ... “2”.. refers to the index of the species, such that this organism happens to be the second species of this category.
- ... “Clams” is purely descriptive (here the name of the species), so you can follow along with what is happening!

2.0.3 Lets get started

```
ii<-1 #The category index value
category<- c(1,2)
baseyr<-2010
pctmiss<-0.50 #If data are missing by the below percentage, remove data
```

In most of the following examples, we will just focus on the finfish ($i=1$) side of the equation. Here *baseyr* is set to 2010 and the *pctmiss* (The percent of data in a column that we will allow to be missing for analysis; more on that later) is set to 0.5%.

Here I am just going to do some housekeeping:

```
place <- "Test"

warnings.list<-list()
figures.list<-list()
```

```
#####Housekeeping
# Here I am just going to collect some housekeeping items
temp<-data.frame(temp)

NumberOfSpecies<-numbers0(x = c(0, strsplit(x =
                                strsplit(x = names(temp)[2],
                                split = "_")[[1]][2],
                                split = "[a-zA-Z]")[[1]][1]))[1]

category<-unique(as.character(lapply(X = strsplit(x = as.character(names(temp)),
                                split = paste0("_")),
                                function(x) x[1])))
category<-unique(substr(x = category, start = 2, stop = nchar(category)))
category<-category[!grepl(pattern = "[a-zA-Z]", x = category)]
category<-category[!(category %in% numbers0(c(0, (category)[1]))[1])]

temp0<-data.frame(rep_len(x = NA, length.out = nrow(temp)))
tempPC<-data.frame(rep_len(x = NA, length.out = nrow(temp0)))
tempQC<-data.frame(rep_len(x = NA, length.out = nrow(temp0)))

maxyr<-max(rownames(temp))
minyr<-min(rownames(temp))

NameBaseTotal<-paste0(paste(rep_len(x = 0, length.out = nchar(category[1])), collapse = ""),
                      "_", NumberOfSpecies, "Total")

#####Category Specific#####

QColumns0<-QColumns<-grep(pattern = paste0("Q", category[ii],"_"),
                           x = substr(x = names(temp),
                           start = 1,
                           stop = (2+nchar(category[ii]))))

VColumns0<-VColumns<-grep(pattern = paste0("V", category[ii],"_"),
                           x = substr(x = names(temp),
                           start = 1,
                           stop = (2+nchar(category[ii]))))

NameBasecategory<-names(temp)[grepl(pattern = paste0("VE", category[ii],"_"),
                                     x = substr(x = names(temp),
                                     start = 1,
                                     stop = (3+nchar(category[ii]))))]

NameBasecategory<-substr(x = NameBasecategory, start = 3, stop = nchar(NameBasecategory))
```

2.0.4 Remove any V and Q data where V column has less data than the specified *pctmiss*

```

for (i in 1:length(VColumns)) {

  #if the percent missing is less in V or Q columns for a species than the percentmissingtrheshold, w
  if (sum(is.na(temp[VColumns[i]]))/nrow(temp) > pctmiss | #V
      sum(is.na(temp[QColumns[i]]))/nrow(temp) > pctmiss ) {#Q

    names(temp)[VColumns[i]]<-paste0("REMOVED_", names(temp)[VColumns[i]])
    VColumns0<-VColumns0[!(VColumns0 %in% VColumns[i])]
    names(temp)[QColumns[i]]<-paste0("REMOVED_", names(temp)[QColumns[i]])
    QColumns0<-QColumns0[!(QColumns0 %in% QColumns[i])]
  }
}

if (length(VColumns0) == 0 ) {

  warnings.list[length(warnings.list)+1]<-paste0("FYI: ", NameBasecategory, " is no longer being calcul

} else {

VColumns<-names(temp)[VColumns0]
QColumns<-names(temp)[QColumns0]

a<-"No warning."
}

```

No warning.

	Q1_1Salmon	Q1_2Cod	Q2_1Shrimp	Q2_2Clam	REMOVED_Q1_3Flounder	Q1_4SeaBass
2007	NA	2000	100	150	NA	1000
2008	NA	1900	120	160	NA	1200
2009	NA	2000	110	140	NA	900
2010	20	2500	90	NA	NA	NA
2011	10	2400	80	NA	NA	NA
2012	12	2300	100	NA	NA	NA
2013	11	2000	100	140	NA	1000
2014	11	2300	110	110	NA	900
2015	10	2400	90	130	NA	1000
2016	15	2200	100	160	NA	1100

2.0.5 Caluclate Category Sums of V and Q

Because we removed some columns for not meeting a perecent missing threshold of 0.5% and those columns will not be used at all in any part of the further analysis, we need to re-calculate the totals of V and Q for the catagories and the fishery as a whole.

```

# Q
temp.q<-data.frame(temp[,QColumns])
if (ncol(temp.q)>1) {
  temp.q<-rowSums(temp.q, na.rm = T)
}

```

```

temp[ncol(temp)+1]<-temp.q
names(temp)[ncol(temp)]<-paste0("Q",NameBasecategory)

# V
temp.v<-data.frame(temp[,VColumns])
if (ncol(temp.v)>1) {
  temp.v<-rowSums(temp.v, na.rm = T)
}
temp[ncol(temp)+1]<-temp.v
names(temp)[ncol(temp)]<-paste0("V",NameBasecategory)

```

	QE1_0Finfish	VE1_0Finfish	Q1_0Finfish	V1_0Finfish
2007	3000	3800	3000	2800
2008	3100	4020	3100	2820
2009	2900	3910	2900	3010
2010	2520	3190	2520	3190
2011	2410	3280	2410	3280
2012	2312	3150	2312	3150
2013	3011	4080	3011	3080
2014	3211	4270	3211	3370
2015	3410	4700	3410	3700
2016	3315	4480	3315	3380

There may be instances where there are no or too few Q data for that species in a year or ever. The next goal will be to calculate the quantity change, so we need to have a value in there that won't show change. If we left a 0 in the spot, then the price change from 0 to the next year would be huge and misrepresented on the index. To avoid this, we have to deal with four scenarios:

2.0.5.1 1. If there are instances for a species where there are too few pairs of Q are completely missing from the timeseries or where a percent of Q is missing from the timeseries, we will remove the offending price columns entirely, so they don't influence the downstream price change or price index calculations.

Let's say here that if 50% of the data is missing in a given $Q_{t,i,s}$, don't use that to calculate that species $Q_{t,i}$

```

#Find which columns in this table are quantity Columns
cc<-c() #Empty
for (c in 1:length(QColumns)) {
  #If price could never be calculated at any point in the timeseries (is 0/NaN/NA) for a column (c)
  #Remove the column from the analysis.
  #We will not be removing the column from the data, but simply remove it from the variable "QColumns"
  if (sum(temp[,QColumns[c]] %in% c(0, NA, NaN))/nrow(temp) > pctmiss) {
    cc<-c(cc, c)#Collect offending columns
  }
}
if (length(cc)>0){
  QColumns<-QColumns[-cc]
}

```

	Q1_1Salmon	Q1_2Cod	Q1_4SeaBass
2007	NA	2000	1000
2008	NA	1900	1200

	Q1_1Salmon	Q1_2Cod	Q1_4SeaBass
2009	NA	2000	900
2010	20	2500	NA
2011	10	2400	NA
2012	12	2300	NA
2013	11	2000	1000
2014	11	2300	900
2015	10	2400	1000
2016	15	2200	1100

```

if (length(QColumns) < 2) {

  warnings.list[length(warnings.list)+1]<-paste0("FYI: ", NameBasecategory, " is no longer being calcul
} else {
  a<-"No warning."
}

```

No warning.

2.0.5.2 2. If the first value of $Q_{t,i,s}$ is 0/NA in a timeseries, we (impute) let the next available non-zero/non-NA value of Q in the timeseries inform the past.

$$where \begin{cases} if : Q_{t,i=1} = 0, then : Q_{t,i=1} = Q_{t,i=1+1...} \\ if : Q_{t,i \neq 1} = 0, then : Q_{t,i} = Q_{t-1,i} \end{cases}$$

We use this *ReplaceFirst* function:

```

print(ReplaceFirst)

## function(colnames, temp) {
##   for (c0 in 1:length(colnames)) {
##     ##
##     #If the first value of the timeseries of this column (c) is 0/NaN/NA
##     #Change the first value (and subsequent 0/NaN/NA values) to the first available non-0/NaN/NA value
##     if (temp[1,colnames[c0]] %in% c(0, NA, NaN, NULL)) {
##       findfirstvalue<-temp[which(!(temp[,colnames[c0]] %in% c(0, NA, NaN, NULL))),
##       colnames[c0]][1]
##       temp[1,colnames[c0]]<-findfirstvalue
##     }
##   }
##   return(temp)
## }
## <bytecode: 0x000000001963bd38>

temp<-ReplaceFirst(colnames = QColumns, temp)

```

	Q1_1Salmon	Q1_2Cod	Q1_4SeaBass
2007	20	2000	1000
2008	NA	1900	1200
2009	NA	2000	900
2010	20	2500	NA
2011	10	2400	NA

	Q1_1Salmon	Q1_2Cod	Q1_4SeaBass
2012	12	2300	NA
2013	11	2000	1000
2014	11	2300	900
2015	10	2400	1000
2016	15	2200	1100

2.0.5.3 3. If there is a value in the middle of $P_{t,i,s}$'s timeseries that is 0/NA, we (impute) let the most recent past available non-zero/non-NA of $P_{t,i,s}$ in the timeseries inform the future.

We use this *ReplaceMid* function:

```
print(ReplaceMid)

## function(colnames, temp) {
##   for (c0 in 1:length(colnames)) {
##     #If a middle value of the timeseries of this column (c) is 0/NaN/NA
##     #Change the currently 0/NaN/NA value to the previous available non-0/NaN/NA value
##     if (sum(temp[,colnames[c0]] %in% c(0, NA, NaN, NULL))>0) {
##       troublenumber<-which(temp[,colnames[c0]] %in% c(0, NA, NaN, NULL))
##       for (r in 1:length(troublenumber)){
##         findlastvalue<-temp[troublenumber[r]-1, colnames[c0]][1]
##         temp[troublenumber[r],colnames[c0]]<-findlastvalue
##       }
##     }
##   }
##   return(temp)
## }
## <bytecode: 0x00000000172b9a68>
temp<-ReplaceMid(colnames = QColumns, temp)
```

	Q1_1Salmon	Q1_2Cod	Q1_4SeaBass
2007	20	2000	1000
2008	20	1900	1200
2009	20	2000	900
2010	20	2500	900
2011	10	2400	900
2012	12	2300	900
2013	11	2000	1000
2014	11	2300	900
2015	10	2400	1000
2016	15	2200	1100

2.0.6 Impute values of $V_{t,i,s}$ where P was able to be calculated

To ensure that the price index does not rise or fall too quickly with changes (that are really because of NA values) we fill in the missing instances of $V_{t,i,s}$.

$$where \begin{cases} if : V_{t,i=1} = 0, then : V_{t,i=1} = V_{t,i=1+1...} \\ if : V_{t,i \neq 1} = 0, then : V_{t,i} = V_{t-1,i} \end{cases}$$

2.0.6.1 1. If the first value of $V_{t,i,s}$ is 0/NA in a timeseries, we let the next available non-zero value of $V_{t,i,s}$ in the timeseries inform the past.

```
QColumns<-QColumns[!(grepl(pattern = "REMOVED", x = QColumns))]  
VVCOLUMNS<-paste0("V", substr(x = QColumns, start = 2, stop = nchar(QColumns)))  
temp<-ReplaceFirst(colnames = VVCOLUMNS, temp)
```

	V1_1Salmon	V1_2Cod	V1_4SeaBass
2007	100	2800	120
2008	NA	2700	120
2009	NA	2900	110
2010	100	3000	90
2011	100	3100	80
2012	150	2900	100
2013	180	2800	100
2014	170	3200	NA
2015	200	3500	NA
2016	180	3200	NA

2.0.6.2 2. If there is a value in the middle of $V_{t,i,s}$'s timeseries that is 0/NA, we let the most recent past available non-zero of $V_{t,i,s}$ in the timeseries inform the future.

```
temp<-ReplaceMid(colnames = VVCOLUMNS, temp)
```

	V1_1Salmon	V1_2Cod	V1_4SeaBass
2007	100	2800	120
2008	100	2700	120
2009	100	2900	110
2010	100	3000	90
2011	100	3100	80
2012	150	2900	100
2013	180	2800	100
2014	170	3200	100
2015	200	3500	100
2016	180	3200	100

2.0.7 Value of species $VV_{t,i}$ where Q available

$R_{t,i}$, as defined and discussed in the subsequent step, will need to sum to 1 across all species in a category. Therefore, you will need to sum a new total of $V_{t,i}$ available (called $VV_{t,i}$) for the category using only values for species that were used to calculate $Q_{t,i}$ (called $V_{t,i,s,available}$).

$$VV_{t,i} = \sum_{s=1}^n (V_{t,i,s,available})$$

where:

- $VV_{t,i}$ is the new total of $V_{t,i}$ (called $VV_{t,i}$) for the category using only values for species that were used to calculate $Q_{t,i}$
- $V_{t,i,s,available}$ are the $V_{t,i,s}$ where $Q_{t,i,s}$ were able to be calculated

```
temp0<-data.frame(temp[,names(temp) %in% VVColumns],
  rowSums(temp[,names(temp) %in% VVColumns], na.rm = T))#)
names(temp0)[ncol(temp0)]<-paste0("VV",NameBasecategory)
temp0<-data.frame(temp0)
temp[ncol(temp)+1]<-temp0[ncol(temp0)]
```

	V1_1Salmon	V1_2Cod	V1_4SeaBass	VV1_0Finfish
2007	100	2800	120	3020
2008	100	2700	120	2920
2009	100	2900	110	3110
2010	100	3000	90	3190
2011	100	3100	80	3280
2012	150	2900	100	3150
2013	180	2800	100	3080
2014	170	3200	100	3470
2015	200	3500	100	3800
2016	180	3200	100	3480

2.0.8 Revenue Share for each species ($R_{t,i,s}$; e.g., Salmon and Flounder)

$$R_{t,i,s} = V_{t,i,s}/VV_{t,i}$$

where:

- $R_{t,i,s}$ is the revenue share per individual species (s), category (i), for each year (t)
- $V_{t,i,s}$ is the value (\$) per individual species (s), category (i), for each year (t)

Here we divide $V_{t,i,s}$ by $VV_{t,i}$ because $VV_{t,i}$ only includes species used to calculate $V_{t,i,s}$ as per the above price calculations.

```
tempR<-data.frame(data = rep_len(x = NA, length.out = nrow(temp)))
for (c in 1:length(QColumns)) {
  #for renaming the columns
  NameBase<-substr(start = 2,
    stop = nchar(QColumns[c]),
    x = QColumns[c])

  VV<-(temp[,names(temp) %in% paste0("VV", NameBasecategory)]) # sum of V where P was calculated
  V0<-temp[,names(temp) %in% paste0("V", NameBase)] #V of species; to make sure its the same column
  tempR[,c]<-V0/VV
  names(tempR)[c]<-paste0("R", NameBase ) #name the column
}

tempR<-data.frame(tempR)
temp<-cbind.data.frame(temp, tempR)
```

	R1_1Salmon	R1_2Cod	R1_4SeaBass
1	0.0331126	0.9271523	0.0397351
2	0.0342466	0.9246575	0.0410959
3	0.0321543	0.9324759	0.0353698
4	0.0313480	0.9404389	0.0282132

	R1_1Salmon	R1_2Cod	R1_4SeaBass
5	0.0304878	0.9451220	0.0243902
6	0.0476190	0.9206349	0.0317460
7	0.0584416	0.9090909	0.0324675
8	0.0489914	0.9221902	0.0288184
9	0.0526316	0.9210526	0.0263158
10	0.0517241	0.9195402	0.0287356

2.0.8.1 Analysis Warnings Checks

As an additional check, let's make sure that each row sums to 1.

	x
1	1
2	1
3	1
4	1
5	1
6	1
7	1
8	1
9	1
10	1

Is there a warning?

No warning.

2.0.9 Revenue Share-Weighted Qunatity Changes for each species ($QCW_{t,i,s}$; e.g., Salmon and Flounder)

$$QCW_{t,i,s} = \frac{R_{t,i,s} + R_{s,t-1,i}}{2} * \ln\left(\frac{Q_{t,i,s}}{Q_{s,t-1,i}}\right) = \frac{R_{t,i,s} + R_{s,t-1,i}}{2} * [\ln(Q_{t,i,s}) - \ln(Q_{s,t-1,i})]$$

Where:

- $QCW_{t,i,s}$ = Revenue share-weighted quantity change for a species (s)

Such that:

- category's (i) Quantity Change for each species (s) = $\frac{R_{t,i,s} + R_{s,t-1,i}}{2}$
- category's (i) Revenue Share for each species (s) = $\ln\left(\frac{Q_{t,i,s}}{Q_{s,t-1,i}}\right) = [\ln(Q_{t,i,s}) - \ln(Q_{s,t-1,i})]$

We use this *PriceChange* function. For all intensive purposes, replace P with Q :

```
print(PriceChange)

## function(R0, P0) {
##   PCW<-rep_len(x = 0, length.out = length(P0))
##   for (t in 2:length(P0)) {
##     AverageR<-((R0[t]+R0[t-1])/2) #Average Revenue Share
##     PC<-ln(P0[t]/P0[t-1]) #Price Change
##     PCW[t]<-AverageR*PC #Revenue Share-Weighted Price Chage
```

```
##   }
##   return(PCW)
## }
## <bytecode: 0x0000000019e0db98>

#Find which columns in this table are price and revenue share columns
tempQCW<-data.frame(data = rep_len(x = NA, length.out = nrow(temp)))
for (c in 1:length(QColumns)){
#For naming columns
NameBase<-substr(start = 2,
                  stop = nchar(QColumns[c]),
                  x = QColumns[c])

# Calculate
Q0<-temp[, names(temp) %in% paste0("Q", NameBase)]
R0<-temp[, names(temp) %in% paste0("R", NameBase)] #to make sure its the same column
tempQCW[,c]<-PriceChange(R0, Q0)
names(tempQCW)[c]<-paste0("QCW", NameBase ) #name the column
}

temp<-cbind.data.frame(temp, tempQCW)
```

2.0.10 Quantity Changes for the category ($QC_{t,i}$; e.g., Finfish)

$$QC_{t,i} = \ln\left(\frac{Q_{t,i}}{Q_{t-1,i}}\right) = \sum_{s=1}^n (QCW_{t,i,s})$$

Where:

- $QC_{t,i}$ = Quantity change for a category (i)

```
temp[ncol(temp)+1]<-rowSums(tempQCW, na.rm = T)
names(temp)[ncol(temp)]<-paste0("QC", NameBasecategory)
```

	QCW1_1Salmon	QCW1_2Cod	QCW1_4SeaBass	QC1_0Finfish
1	0.0000000	0.0000000	0.0000000	0
2	0.0000000	-0.0474927	0.0073686	0
3	0.0000000	0.0476292	-0.0109989	0
4	0.0000000	0.2089644	0.0000000	0
5	-0.0214306	-0.0384862	0.0000000	0
6	0.0071203	-0.0397029	0.0000000	0
7	-0.0046142	-0.1278630	0.0033828	0
8	0.0000000	0.1279717	-0.0032286	0
9	-0.0048429	0.0392239	0.0029045	0
10	0.0211563	-0.0800763	0.0026235	0

2.0.11 Quantity Index for the each category ($QI_{t,i}$)

We calculate the quantity index first by comparing by multiplying the previous years QI_{t-1} by that year's quantity change QC_t , where the QI of the first year $QI_{t=firstyear,i} = 1$

$$QI_{t,i} = QI_{t-1,i} * \exp(\ln(\frac{Q_{t,i,s}}{Q_{t-1,i,s}})) = QI_{t-1,i} * \exp(QC_{t,i})$$

Where

$$QI_{i,t_{firstyear}} = 1$$

Note that the first row of this column is = 1

Then, to change the price index into base year dollars, we use the following equation:

$$QI_t = QI_t / QI_{t=baseyear}$$

```
tempQI<-PriceIndex(temp, BaseColName = NameBasecategory, baseyr, var = "QC")
temp[ncol(temp)+1]<-(tempQI)
names(temp)[ncol(temp)]<-paste0("QI", NameBasecategory)
```

	QI1_0Finfish
2007	0.8142640
2008	0.7822391
2009	0.8114241
2010	1.0000000
2011	0.9418429
2012	0.9116497
2013	0.8012406
2014	0.9076914
2015	0.9421740
2016	0.8905983

2.1 Redo Analysis for Shellfish

Now lets redo that whole analysis up to this point (via function) for the two species of the shellfish group, as we will need them for the next steps of this analysis.

We use this *ImplicitQuantityOutput* function to calculate the Implicit Quantity Output at Species and category Level:

```
print(ImplicitQuantityOutput.speciescat.q)

## function(temp, ii, baseyr, maxyr, minyr, pctmiss, warnings.list) {
##
##   #####Housekeeping
##   # Here I am just going to collect some housekeeping items
##   temp<-data.frame(temp)
##
##   NumberOfSpecies<-numbers0(x = c(0, strsplit(x =
##                                     strsplit(x = names(temp)[1],
##                                               split = "_")[[1]][2],
##                                               split = "[a-zA-Z]")[[1]][1]))[1]
##
##
##   NameBaseTotal<-substr(x = sort(names(temp)[grep(x = names(temp),
```

```

##                                     pattern = paste0(NumberOfSpecies, "Total"))], decreasing = T)[1]))
##                                     start = 3, stop = nchar(sort(names(temp)[grep(x = names(temp),
##                                     pattern = paste0(NumberOfSpecies, "Total"))], decreasing = T)[1]))
##
## QColumns0<-QColumns<-grep(pattern = paste0("Q", ii, "_"),
##                             x = substr(x = names(temp),
##                                         start = 1,
##                                         stop = (2+nchar(ii))))
##
## VColumns0<-VColumns<-grep(pattern = paste0("V", ii, "_"),
##                             x = substr(x = names(temp),
##                                         start = 1,
##                                         stop = (2+nchar(ii))))
##
## NameBasecategory<-names(temp)[grepl(pattern = paste0("VE", ii, "_"),
##                                       x = substr(x = names(temp),
##                                                   start = 1,
##                                                   stop = (3+nchar(ii))))]
##
## NameBasecategory<-substr(x = NameBasecategory, start = 3, stop = nchar(NameBasecategory))
##
##
##
##
## ###Remove any V and Q data where V column has less data than the specified $pctmiss$
##
## # intersectcol<-base::intersect(x = substr(x = names(temp[,VColumns]), start = 2, stop = nchar(names(temp[,VColumns]))),
## #                               y = substr(x = names(temp[,QColumns]), start = 2, stop = nchar(names(temp[,QColumns]))))
## # unioncol<-base::union(x = substr(x = names(temp[,VColumns]), start = 2, stop = nchar(names(temp[,VColumns]))),
## #                       y = substr(x = names(temp[,QColumns]), start = 2, stop = nchar(names(temp[,QColumns]))))
## #
## # differentcol<-base::setdiff(unioncol, intersectcol)
## #
## # if (length(differentcol) != 0) {
## #   for (i in 1:length(differentcol)) {
## #     names(temp)[grep(pattern = differentcol[i], x = names(temp))]<-
## #       paste0("REMOVED_", names(temp)[grep(pattern = differentcol[i], x = names(temp))])
## #   }
## # }
##
##
## for (i in 1:length(VColumns)) {
##
##   #if the percent missing is less in V or Q columns for a species than the percentmissingtrheshold
##   if (sum(is.na(temp[VColumns[i]]))/nrow(temp) > pctmiss | #V
##       sum(is.na(temp[QColumns[i]]))/nrow(temp) > pctmiss ) {#Q
##
##     names(temp)[VColumns[i]]<-paste0("REMOVED_", names(temp)[VColumns[i]])
##     VColumns0<-VColumns0[!(VColumns0 %in% VColumns[i])]
##     names(temp)[QColumns[i]]<-paste0("REMOVED_", names(temp)[QColumns[i]])
##     QColumns0<-QColumns0[!(QColumns0 %in% QColumns[i])]
##   }
## }

```

```

## }
##
## if (length(VColumns0) == 0 && length(QColumns0) == 0
##   ) {
##
##   warnings.list[length(warnings.list)+1]<-paste0("FYI: ", NameBasecategory, " is no longer being c
##
## } else {
##
##   VColumns<-names(temp)[VColumns0]
##   QColumns<-names(temp)[QColumns0]
##
##   ###Caluclate Category Sums of $V$ and $Q$
##
##   # Because we removed some columns for not meeting a perecent missing threshold of `r pctmiss`% and
##
##   # Q
##   temp.q<-data.frame(temp[,QColumns])
##   if (ncol(temp.q)>1) {
##     temp.q<-rowSums(temp.q, na.rm = T)
##   }
##   temp[ncol(temp)+1]<-temp.q
##   names(temp)[ncol(temp)]<-paste0("Q",NameBasecategory)
##
##   # V
##   temp.v<-data.frame(temp[,VColumns])
##   if (ncol(temp.v)>1) {
##     temp.v<-rowSums(temp.v, na.rm = T)
##   }
##   temp[ncol(temp)+1]<-temp.v
##   names(temp)[ncol(temp)]<-paste0("V",NameBasecategory)
##
##
##   # There may be instances where there are no or too few Q data for that species in a year or ever.
##   ##### 1. If there are instances for a species where there are too few pairs of $Q$ are completely miss
##   # Let's say here that if `r pctmiss*100`% of the data is missing in a given $Q_{t,i,s}$, don't use
##   #Find which columns in this table are price Columns
##
##   cc<-c() #Empty
##   for (c in 1:length(QColumns)) {
##     #If price could never be caluclated at any point in the timeseries (is 0/NaN/NA) for a column (c
##     #Remove the column from the analysis.
##     #We will not be removing the column from the data, but simply remove it from the varaible "QColumn
##     if (sum(temp[,QColumns[c]] %in% c(0, NA, NaN))/nrow(temp) > pctmiss) {
##       cc<-c(cc, c)#Collect offending columns
##     }
##   }
##   if (length(cc)>0){
##     QColumns<-QColumns[-cc]
##   }
##
##
##   #CHECK IF ANALYSIS FAILED:
##

```



```

##   if (length(QColumns) < 2) {
##
##       warnings.list[length(warnings.list)+1]<-paste0("FYI: ", NameBasecategory, " is no longer being c
##
##   } else {
##
##
##       ##### 2. If the first value of  $Q_{\{t,i,s\}}$  is 0/NA in a timeseries, we (impute) let the next avail
##       #  $Q_{\{t,i=1\}} = 0$ , then:  $Q_{\{t,i=1\}} = Q_{\{t,i=1+1\dots\}}$  \\ if:  $Q_{\{t,i \neq 1\}} =$ 
##       temp<-ReplaceFirst(colnames = QColumns, temp)
##
##       ##### 3. If there is a value in the middle of  $P_{\{t,i,s\}}$ 's timeseries that is 0/NA, we (impute)
##       temp<-ReplaceMid(colnames = QColumns, temp)
##
##
##       ###Impute values of  $V_{\{t,i,s\}}$  where P was able to be calculated
##
##       # To ensure that the price index does not rise or fall to quickly with changes (that are really l
##       #  $V_{\{t,i=1\}} = 0$ , then:  $V_{\{t,i=1\}} = V_{\{t,i=1+1\dots\}}$  \\ if:  $V_{\{t,i \neq 1\}} =$ 
##
##       ##### 1. If the first value of  $V_{\{t,i,s\}}$  is 0/NA in a timeseries, we let the next available n
##
##       QColumns<-QColumns[!(grepl(pattern = "REMOVED", x = QColumns))]
##       VVColumns<-paste0("V", substr(x = QColumns, start = 2, stop = nchar(QColumns)))
##       temp<-ReplaceFirst(colnames = VVColumns, temp)
##
##       ##### 2. If there is a value in the middle of  $V_{\{t,i,s\}}$ 's timeseries that is 0/NA, we let the m
##       temp<-ReplaceMid(colnames = VVColumns, temp)
##
##       ###Value of species  $VV_{\{t,i\}}$  where Q available
##       #  $R_{\{t,i\}}$ , as defined and discussed in the subsequent step, will need to sum to 1 across all sp
##       #  $VV_{\{t,i\}} = \sum_{s=1}^n (V_{\{t,i,s, \text{available}\}})$ 
##       #   where:
##       #   -  $VV_{\{t,i\}}$  is the new total of  $V_{\{t,i\}}$  (called  $VV_{\{t,i\}}$ ) for the category using only v
##       #   -  $V_{\{t,i,s, \text{available}\}}$  are the  $V_{\{t,i,s\}}$  where  $Q_{\{t,i,s\}}$  were able to be calculated
##
##       temp0<-data.frame(temp[,names(temp) %in% VVColumns],
##                           # ifelse(length(VVColumns) == 1,
##                           # temp[,names(temp) %in% VVColumns],
##                           rowSums(temp[,names(temp) %in% VVColumns], na.rm = T))#)
##       names(temp0)[ncol(temp0)]<-paste0("VV",NameBasecategory)
##       temp0<-data.frame(temp0)
##       temp[ncol(temp)+1]<-temp0[ncol(temp0)]
##
##
##       ###Revenue Share for each species ( $R_{\{t,i,s\}}$ ; e.g., Salmon and Flounder)
##
##       #  $R_{\{t,i,s\}} = V_{\{t,i,s\}}/VV_{\{t,i\}}$ 
##       #   where:
##       #   -  $R_{\{t,i,s\}}$  is the revenue share per individual species (s), category (i), for each year (
##       #   -  $V_{\{t,i,s\}}$  is the value ($) per individual species (s), category (i), for each year (t)
##       # Here we divide  $V_{\{t,i,s\}}$  by  $VV_{\{t,i\}}$  because  $VV_{\{t,i\}}$  only includes species used to calcul
##
##       tempR<-data.frame(data = rep_len(x = NA, length.out = nrow(temp)))

```



```
##      names(tempQCW)[c]<-paste0("QCW", NameBase ) #name the column
##    }
##
##    temp<-cbind.data.frame(temp, tempQCW)
##
##
##
##
##
##
##
##
###Quantity Changes for the category ($QC_{t,i}$; e.g., Finfish)
##
##   # $$QC_{t,i} = \ln(\frac{Q_{t,i}}{Q_{t-1,i}}) = \sum_{s=1}^n(QCW_{t,i,s})$$
##   # Where:
##   # - $QC_{t,i}$ = Quantity change for a category (i)
##
##   temp[ncol(temp)+1]<-rowSums(tempQCW, na.rm = T)
##   names(temp)[ncol(temp)]<-paste0("QC", NameBasecategory)
##
##
##
##
##
##
##
##
##remove duplicates
##temp<-temp[, !(grepl(pattern = "\\.[0-9]+", x = names(temp)))]
##temp <- temp[, !duplicated(colnames(temp))]
##temp<-temp[, !(grepl(pattern = "\\.[0-9]+", x = names(temp)))]
##temp <- temp[, !duplicated(colnames(temp))]
##
##
##
##
##
##
###Quantity Index for the each category ($QI_{t,i}$)
##
##   # We calculate the quantity index first by comparing by multiplying the previous years $QI_{t-1,i}$
##   # $$QI_{t,i} = QI_{t-1,i}*\exp(\ln(\frac{Q_{t,i,s}}{Q_{t-1,i,s}})) = QI_{t-1,i}*\exp(QC_{t,i})$$
##   # Where
##   # $$QI_{i,t_{first year}} = 1$$
##
##   #Note that the first row of this column is = 1
##
##   # Then, to change the price index into base year dollars, we use the following equation:
##   # $$QI_t = QI_t/QI_t = baseyear$$
##
##   tempQI<-PriceIndex(temp, BaseColName = NameBasecategory, baseyr, var = "QC")
##   temp[ncol(temp)+1]<-(tempQI)
##   names(temp)[ncol(temp)]<-paste0("QI", NameBasecategory)
##
##
##
##
```

```

##      #remove duplicates
##      temp<-temp[, !(grepl(pattern = "\\.[0-9]+", x = names(temp)))]
##      temp <- temp[, !duplicated(colnames(temp))]
##      temp<-temp[, !(grepl(pattern = "\\.[0-9]+", x = names(temp)))]
##      temp <- temp[, !duplicated(colnames(temp))]
##
##
##      #####WARNINGS
##
##      }
##      }
##
##      return(list(temp, warnings.list))
##  }
## <bytecode: 0x000000001e40fb30>
ii<-2 #The category index value

tempS<-ImplicitQuantityOutput.speciescat.q(temp, ii, baseyr, maxyr, minyr,
      pctmiss = pctmiss,
      warnings.list = warnings.list)
temp<-cbind.data.frame(temp, tempS[[1]])
warnings.list<-tempS[[2]]
###Remove duplicate columns
temp<-temp[, !(grepl(pattern = "\\.[0-9]+", x = names(temp)))]
temp<-temp[, !(grepl(pattern = "\\.[0-9]+", x = names(temp)))]
      temp<-temp[, !(grepl(pattern = "\\.[0-9]+", x = names(temp)))]
      temp <- temp[, !duplicated(colnames(temp))]

```

What does the Shellfish data look like?

	R2_1Shrimp	R2_2Clam	QCW2_1Shrimp	QCW2_2Clam	QC2_0Shellfish	QI2_0Shellfish
2007	0.4444444	0.5555556	0.0000000	0.0000000	0.0000000	1.0918916
2008	0.4545455	0.5454545	0.0819526	0.0355288	0.1174814	1.2280076
2009	0.5000000	0.5000000	-0.0415282	-0.0698005	-0.1113287	1.0986305
2010	0.4375000	0.5625000	-0.0940644	0.0000000	-0.0940644	1.0000000
2011	0.5000000	0.5000000	-0.0552108	0.0000000	-0.0552108	0.9462857
2012	0.5263158	0.4736842	0.1145079	0.0000000	0.1145079	1.0610904
2013	0.5454545	0.4545455	0.0000000	0.0000000	0.0000000	1.0610904
2014	0.5500000	0.4500000	0.0522040	-0.1090710	-0.0568670	1.0024330
2015	0.5000000	0.5000000	-0.1053521	0.0793507	-0.0260014	0.9767043
2016	0.5217391	0.4782609	0.0538255	0.1015627	0.1553882	1.1408993

2.1.1 Value for all fisheries for species where Q was able to be calculated

$R_{t,i}$, defined and discussed in the subsequent step, will need to sum to 1 across all species in a category. Therefore, you will need to sum a new total of $V_{t,i}$ (called VV_t) for the category using only values for species that were used to calculate $QI_{t,i}$.

$$VV_t = \sum_{s=1}^n (VV_{t,i})$$

where:

- VV_t is the new total of $V_{t,i}$ for the entire fishery using only values for species that were used to calculate $P_{t,i}$

VV1	_0Finfish	VV2	_0Shellfish	VV0	_0Total
2007	3020		1800		4820
2008	2920		2200		5120
2009	3110		1800		4910
2010	3190		1600		4790
2011	3280		1800		5080
2012	3150		1900		5050
2013	3080		2200		5280
2014	3470		2000		5470
2015	3800		2000		5800
2016	3480		2300		5780

V1__	0Finfish	V2__	0Shellfish
2007	2800		1800
2008	2820		2200
2009	3010		1800
2010	3190		700
2011	3280		900
2012	3150		1000
2013	3080		2200
2014	3370		2000
2015	3700		2000
2016	3380		2300

2.1.2 Revenue Share for the each category ($R_{t,i}$)

$$R_{t,i} = V_{t,i}/V_t$$

where:

- $R_{t,i}$ is the revenue share per individual species (s), category (i), for each year (t)
- $V_{t,i}$ is the value (\$) per individual species (s), category (i), for each year (t)

Here, we don't use VV_t because we want to expand the proportion to include all of the species caught, regardless if they were used in the quantity calculations.

```
tempR<-data.frame(data = rep_len(x = NA, length.out = nrow(temp)))

for (i in 1:length(category)) {

  CatCol<-names(temp)[grep(pattern = paste0("V", category[i],"_", NumberOfSpecies),
                           x = substr(x = names(temp),
                                       start = 1,
                                       stop = nchar(paste0("V", category[i],"_", NumberOfSpecies))))]
  NameBasecategory<-substr(x = CatCol, start = 2, stop = nchar(CatCol))

  tempR[,i]<-temp[,paste0("V", NameBasecategory)]/temp[,paste0("V", NameBaseTotal)]
}
```

```

names(tempR)[i]<-paste0("R", NameBasecategory)
}
temp<-cbind.data.frame(temp, tempR)

```

	R1_0Finfish	R2_0Shellfish	V1_0Finfish	V2_0Shellfish	V0_0Total
2007	0.6086957	0.3913043	2800	1800	4600
2008	0.5617530	0.4382470	2820	2200	5020
2009	0.6257796	0.3742204	3010	1800	4810
2010	0.8200514	0.1799486	3190	700	3890
2011	0.7846890	0.2153110	3280	900	4180
2012	0.7590361	0.2409639	3150	1000	4150
2013	0.5833333	0.4166667	3080	2200	5280
2014	0.6275605	0.3724395	3370	2000	5370
2015	0.6491228	0.3508772	3700	2000	5700
2016	0.5950704	0.4049296	3380	2300	5680

2.1.2.1 Analysis Warnings Checks

As an additional check, let's make sure that each row sums to 1.

	x
2007	1
2008	1
2009	1
2010	1
2011	1
2012	1
2013	1
2014	1
2015	1
2016	1

Is there a warning?

No warning.

2.1.3 Revenue Share-Weighted Qunatity Changes for each category ($QCW_{t,i}$; e.g., Finfish and Shellfish)

$$QCW_{t,i} = \frac{R_{t,i,s} + R_{s,t-1,i}}{2} * \ln\left(\frac{QI_{t,i,s}}{QI_{s,t-1,i}}\right) = \frac{R_{t,i,s} + R_{s,t-1,i}}{2} * [\ln(QI_{t,i,s}) - \ln(QI_{s,t-1,i})]$$

Where:

- $QCW_{t,i}$ = Revenue share-weighted quantity change for each category (i)

Such that:

- category's (i) Quantity Change for each category (i) = $\frac{R_{t,i} + R_{t-1,i}}{2}$
- category's (i) Revenue Share for each category (i) = $\ln\left(\frac{QI_{t,i}}{QI_{t-1,i}}\right) = [\ln(QI_{t,i}) - \ln(QI_{t-1,i})]$

```

#Find which columns in this table are price and revenue share columns
tempQCW<-data.frame(data = rep_len(x = NA, length.out = nrow(temp)))
for (i in 1:length(category)) {

  CatCol<-names(temp)[grep(pattern = paste0("VE", category[i], "_", NumberOfSpecies),
                           x = substr(x = names(temp),
                                       start = 1,
                                       stop = nchar(paste0("VE", category[i], "_", NumberOfSpecies)))))]
  NameBasecategory<-substr(x = CatCol, start = 3, stop = nchar(CatCol))

  # Calculate
  Q0<-temp[, names(temp) %in% paste0("QI", NameBasecategory)]
  R0<-temp[, names(temp) %in% paste0("R", NameBasecategory)] #to make sure its the same column
  tempQCW[,i]<-PriceChange(R0, Q0)
  names(tempQCW)[i]<-paste0("QCW", NameBasecategory ) #name the column
}

temp<-cbind.data.frame(temp, tempQCW)

```

2.1.4 Quantity Changes for the entire fishery (QC_t)

$$QC_t = \ln\left(\frac{QI_{t,i}}{QI_{t-1,i}}\right) = \sum_{s=1}^n (QCW_{t,i})$$

Where:

- QC_t = Quantity change for the entire fishery

```

temp[ncol(temp)+1]<-rowSums(tempQCW, na.rm = T)
names(temp)[ncol(temp)]<-paste0("QC", NameBaseTotal)

```

	QCW1_0Finfish	QCW2_0Shellfish	QC0_0Total
1	0.0000000	0.0000000	0
2	-0.0234816	0.0487284	0
3	0.0217499	-0.0452255	0
4	0.1510636	-0.0260638	0
5	-0.0480755	-0.0109113	0
6	-0.0251493	0.0261235	0
7	-0.0866462	0.0000000	0
8	0.0755254	-0.0224371	0
9	0.0238009	-0.0094036	0
10	-0.0350218	0.0587217	0

2.1.5 Quantity Index for the entire fishery (QI_t)

We calculate the quantity index first by comparing by multiplying the previous years QI_{t-1} by that year's quantity change QC_t , where the QI of the first year $QI_{t=firstyear,i} = 1$

$$QI_t = QI_{t-1} * \exp\left(\ln\left(\frac{QI_{t,i}}{QI_{t-1,i}}\right)\right) = QI_{t-1} * \exp(QC_t)$$

Where

$$QI_{t_{firstyear}} = 1$$

Note that the first row of this column is = 1

Then, to change the price index into base year dollars, we use the following equation:

$$QI_t = QI_t / QI_{t=baseyear}$$

```
tempQI<-PriceIndex(temp, BaseColName = NameBaseTotal, baseyr, var = "QC")
temp[ncol(temp)+1]<-(tempQI)
names(temp)[ncol(temp)]<-paste0("QI", NameBaseTotal)
```

	QI0_0Total
2007	0.8809353
2008	0.9034593
2009	0.8824970
2010	1.0000000
2011	0.9427192
2012	0.9436381
2013	0.8653175
2014	0.9124970
2015	0.9257294
2016	0.9479312

2.1.6 Sum Total Simple Sum Quantity Output Index

$$QEI_t = QE_t / QE_{t=baseyr}$$

Where:

- QE_t is the sum of Q before these calculations; the simple sum
- QEI_t is the index of the sum of Q before these equations

```
#remove duplicates
temp<-temp[, !(grepl(pattern = "\\.[0-9]+", x = names(temp)))]
temp <- temp[, !duplicated(colnames(temp))]
temp<-temp[, !(grepl(pattern = "\\.[0-9]+", x = names(temp)))]
temp <- temp[, !duplicated(colnames(temp))]

QE<-names(temp)[names(temp) %in% paste0("QE", NameBaseTotal)]
temp[,ncol(temp)+1]<-temp[,QE]/temp[,QE][rownames(temp) %in% baseyr]
names(temp)[ncol(temp)]<-paste0("QEI", NameBaseTotal)
```

	QE0_0Total	QEI0_0Total
1	3250	1.2452107
2	3380	1.2950192
3	3150	1.2068966
4	2610	1.0000000
5	2490	0.9540230

	QE0_0Total	QEI0_0Total
6	2412	0.9241379
7	3251	1.2455939
8	3431	1.3145594
9	3630	1.3908046
10	3575	1.3697318

2.2 Other Analysis Warnings Checks

To make sure our analyses worked as intended, let's see if we can back calculate our numbers.

We want the calculated V to equal this check:

2.2.0.1 When back calculated, growth rate?

$$\ln(Q_t/Q_{t-1}) = \sum \left(\left(\frac{R_{i,t} + R_{i,t-1}}{2} \right) * \ln\left(\frac{Q_{t,i}}{Q_{t-1,i}}\right) \right)$$

```
#Part 1
names0<-c(paste0("QI",NameBaseTotal))
for (i in 1:length(category)) {
  names0<-c(names0,
            names(temp)[grep(pattern = paste0("QI", category[i], "_", NumberOfSpecies), names(temp))])
  names(temp)[grep(pattern = paste0("R", category[i], "_", NumberOfSpecies), names(temp))])
}

temp0<-temp[,names0]

temp0[, (ncol(temp0)+1)]<-c(NA, ln(temp0[-nrow(temp0),paste0("QI",NameBaseTotal)]/
                                temp0[-1,paste0("QI",NameBaseTotal)]))
names(temp0)[ncol(temp0)]<-"part1"

#Part 2
temp00<-data.frame()
for (i in 1:length(category)) {
  R0<-temp0[,grep(pattern = paste0("R", category[i]), x = names(temp0))]
  Q0<-temp0[,grep(pattern = paste0("QI", category[i]), x = names(temp0))]

  for (r in 2:(nrow(temp0))){
    temp00[r,i]<-(((R0[r] + R0[r-1])/2) * ln(Q0[r] / Q0[r-1]))
  }
  names(temp00)[i]<-paste0("ln", category[i])
}

temp0[, (ncol(temp0)+1)]<-rowSums(temp00)
names(temp0)[ncol(temp0)]<-"part2"
```

	part1	part2
2007	NA	NA
2008	-0.0252468	0.0252468
2009	0.0234756	-0.0234756

	part1	part2
2010	-0.1249998	0.1249998
2011	0.0589868	-0.0589868
2012	-0.0009742	0.0009742
2013	0.0866462	-0.0866462
2014	-0.0530883	0.0530883
2015	-0.0143972	0.0143972
2016	-0.0236999	0.0236999

Is there a warning?

```
if (length(setdiff(as.character(temp0$part1),
                    as.character(temp0$part2))) != 0) {
  warnings.list[length(warnings.list)+1]<-"Warning: When back calculated, ln(Q_t/Q_{t-1}) = did not equal sum( (R_{i, t} - R_{i, t-1})/2)
  a<-warnings.list[length(warnings.list)][[1]]
} else {
  a<-"No warning."
}
```

Warning: When back calculated, $\ln(Q_t/Q_{t-1}) = \text{did not equal } \text{sum}((R_{i, t} - R_{i, t-1})/2)$
 $\ln((Q_{t,i})(Q_{t-1,i}))^*$

2.2.1 View Total Outputs

	QE0_0Total	VE0_0Total	VV0_0Total	V0_0Total	QC0_0Total	QI0_0Total	QEI0_0Total
2007	3250	5600	4820	4600	0.0000000	0.8809353	1.2452107
2008	3380	6220	5120	5020	0.0252468	0.9034593	1.2950192
2009	3150	5710	4910	4810	-0.0234756	0.8824970	1.2068966
2010	2610	3890	4790	3890	0.1249998	1.0000000	1.0000000
2011	2490	4180	5080	4180	-0.0589868	0.9427192	0.9540230
2012	2412	4150	5050	4150	0.0009742	0.9436381	0.9241379
2013	3251	6280	5280	5280	-0.0866462	0.8653175	1.2455939
2014	3431	6270	5470	5370	0.0530883	0.9124970	1.3145594
2015	3630	6700	5800	5700	0.0143972	0.9257294	1.3908046
2016	3575	6780	5780	5680	0.0236999	0.9479312	1.3697318

2.2.2 Missing Data

```
#value
a<-temp
a<-a[,grep(pattern = "V[1-9]+_[1-9]+", x = names(a))]
if(length(grep(pattern = "REMOVED_", x = names(a)) &
          grep(pattern = "Total", x = names(a), ignore.case = T)) != 0 ){
  a<-a[,-c(grep(pattern = "REMOVED_", x = names(a)), grep(pattern = "Total", x = names(a), ignore.case = T))]
}
ncol0<-ncol(a)
aa<-0
a<-data.frame(a)
if(ncol(a) != 0){
  for (iii in 1:ncol(a)) {
```

```

    aa<-c(aa, ifelse(sum(a[,iii] %in% c(NA, NaN, 0)) == nrow(a), iii, NA))
  }
  vv<-(aa[!(is.na(aa))])
} else {
  pp<-0
}
#quantity
a<-temp
a<-a[,grep(pattern = "Q[1-9]+_[1-9]+", x = names(a))]
if(length(grep(pattern = "REMOVED_", x = names(a)) &
      grep(pattern = "Total", x = names(a), ignore.case = T)) != 0 ){
  a<-a[,-c(grep(pattern = "REMOVED_", x = names(a)), grep(pattern = "Total", x = names(a), ignore.case = T))
}
ncol0<-ncol(a)
aa<-0
a<-data.frame(a)
if(ncol(a) != 0){
  for (iii in 1:ncol(a)) {
    aa<-c(aa, ifelse(sum(a[,iii] %in% c(NA, NaN, 0)) == nrow(a), iii, NA))
  }
  qq<-(aa[!(is.na(aa))])
} else {
  pp<-0
}

```

FYI: 0 of species V columns are completely empty, 1 of species Q columns are completely empty.

2.2.3 Graph 1: Price Index

In theory, *PI* should be negative slope after the baseyear and positive after the base year, but because this data was fabricated without thinking of this, we don't see that here. The index value for the base year is = 1, however.

```

title00<- "_QI-Line"

a0<-data.frame(temp[,grepl(
  pattern = paste0("QI[0-9]+_", NumberOfSpecies),
  x = names(temp))])

a0$Year<-rownames(a0)


a <- gather(a0, Category, val, names(a0)[grepl(pattern = NumberOfSpecies, x = names(a0))], factor_key=TRUE)

a$cat<-as.character(lapply(X = strsplit(x = as.character(a$Category), split = paste0("_", NumberOfSpecies), fixed=TRUE),
  FUN = function(x) x[2]))

temp0<-a

plotnlines(dat = temp0, title00, place)

```



2.2.4 Graph 2: Quantity Index Compare

```

title00<- "_QIvQEI-Line"

temp0<-temp
temp0$Year<-rownames(temp0)


temp0<-data.frame(temp0[,names(temp0) %in% c("Year",
                                             paste0("QI", NameBaseTotal),
                                             paste0("QEI", NameBaseTotal))])

temp0$Year<-rownames(temp)

temp0<-gather(temp0, cat, val,
              names(temp0)[1]:names(temp0)[length(names(temp0))-1],
              factor_key = T)

plotnlines(dat = temp0, title00, place)

```



2.2.5 Graph 3: Quantity Compare

```

title00<- "_QvQE-Line"

temp0<-temp
temp0$Year<-rownames(temp0)


temp0<-data.frame(temp0[,names(temp0) %in% c("Year",
                                             paste0("Q", NameBaseTotal),
                                             paste0("QE", NameBaseTotal))])

temp0$Year<-rownames(temp)

temp0<-gather(temp0, cat, val,
              names(temp0)[1]:names(temp0)[length(names(temp0))-1],
              factor_key = T)

plotnlines(dat = temp0, title00, place)

```



2.3 Do same analysis via a function!

Now that we know the method, we can simplify most of it into a function and do this whole analysis in 4 easy steps:

- A. Import and Edit data
- B. Enter base year
- C. Run the function
- D. Obtain the implicit quantity estimates

2.3.1 Function

We use this *ImplicitQuantityOutput* function to calculate the Implicit Quantity Output at Fishery Level:

```
print(ImplicitQuantityOutput.q)
```

```
## function(temp, baseyr, pctmiss = 1.00,
##                                     title0 = "", place = ""){
##
##   temp.orig<-temp
##
##   warnings.list<-list()
##   figures.list<-list()
## }
```

```

## #####Housekeeping
## # Here I am just going to collect some housekeeping items
## temp<-data.frame(temp)
##
## NumberOfSpecies<-numbers0(x = c(0, strsplit(x =
##                                     strsplit(x = names(temp)[2],
##                                     split = "_")[[1]][2],
##                                     split = "[a-zA-Z]")[[1]][1]))[1]
##
##
##
##
## category<-unique(as.character(lapply(X = strsplit(x = as.character(names(temp)),
##                                     split = paste0("_")),
##                                     function(x) x[1])))
## category<-unique(substr(x = category, start = 2, stop = nchar(category)))
## category<-category[!grepl(pattern = "[a-zA-Z]", x = category)]
## category<-category[!(category %in% numbers0(c(0, (category)[1]))[1])]
##
## temp0<-data.frame(rep_len(x = NA, length.out = nrow(temp)))
## tempPC<-data.frame(rep_len(x = NA, length.out = nrow(temp0)))
## tempQC<-data.frame(rep_len(x = NA, length.out = nrow(temp0)))
##
## maxyr<-max(rownames(temp))
## minyr<-min(rownames(temp))
##
## category<-category00<-sort((category))
## category.rm<-c()
##
##
## NameBaseTotal<-paste0(paste(rep_len(x = 0, length.out = nchar(category[1])), collapse = ""),
##                        "_", NumberOfSpecies, "Total")
##
## for (ii in 1:length(category)) {
##
##   QColumns0<-QColumns<-grep(pattern = paste0("Q", category[ii], "_"),
##                             x = substr(x = names(temp),
##                             start = 1,
##                             stop = (2+nchar(category[ii]))))
##
##   VColumns0<-VColumns<-grep(pattern = paste0("V", category[ii], "_"),
##                             x = substr(x = names(temp),
##                             start = 1,
##                             stop = (2+nchar(category[ii]))))
##
##   NameBasecategory<-names(temp)[grepl(pattern = paste0("VE", category[ii], "_"),
##                                       x = substr(x = names(temp),
##                                       start = 1,
##                                       stop = (3+nchar(category[ii]))))]
##
##   NameBasecategory<-substr(x = NameBasecategory, start = 3, stop = nchar(NameBasecategory))
##
##   if (length(VColumns0) < 2) {

```

```

##
##     warnings.list[length(warnings.list)+1]<-paste0("FYI: ", NameBasecategory, " is no longer being
##     category.rm<-c(category.rm, ii)
##
##   } else {
##
##     #if there are still columns to assess that haven't been "removed"
##     # if (length(VColumns) != 0) {
##     ###Append species and category level calculations
##     temp00<-ImplicitQuantityOutput.speciescat.q(temp, ii=category[ii],
##                                               baseyr, maxyr, minyr,
##                                               pctmiss, warnings.list)
##
##
##     #If data for a category is no longer available after precentmissingthreshold etc, remove it from
##     if (sum(names(temp00[1][[1]]) %in% paste0("QI", NameBasecategory)) == 0) {
##       category.rm<-c(category.rm, ii)
##     } else {
##       temp1<-temp00[[1]]
##       #remove duplicates
##       temp1<-temp1[, !(grepl(pattern = "\\.[0-9]+", x = names(temp1)))]
##       temp1 <- temp1[, !duplicated(colnames(temp1))]
##       temp0<-cbind.data.frame(temp0, temp1)
##     }
##
##     ###Remove duplicate columns
##     temp0<-temp0[, !(grepl(pattern = "\\.[0-9]+", x = names(temp0)))]
##
##     warnings.list<-ImplicitQuantityOutput.speciescat.q(temp, ii=category[ii],
##                                                         baseyr, maxyr, minyr,
##                                                         pctmiss, warnings.list)[[2]]
##   }
##
## }
##
## if(!(is.null(category.rm))) {
##   category<-category[-category.rm]
## }
##
## temp<-temp0#[,2:ncol(temp0)]
##
##
##
## #remove duplicates
## temp<-temp[, !(grepl(pattern = "\\.[0-9]+", x = names(temp)))]
## temp <- temp[, !duplicated(colnames(temp))]
## temp<-temp[, !(grepl(pattern = "\\.[0-9]+", x = names(temp)))]
## temp <- temp[, !duplicated(colnames(temp))]
##
##
## ###Value for all fisheries for species where Q was able to be calculated
## # $R_{t,i}$, defined and discussed in the subsequent step, will need to sum to 1 across all species
## # $$VV_{t} = \sum_{s=1}^n (VV_{t,i})$$

```



```

## # where:
## # - $VV_{t,i}$ is the new total of $V_{t,i}$ for the entire fishery using only values for species
##
## #Total VV
## temp0<-data.frame(temp[,grep(pattern = paste0("VV", "[0-9]+_", NumberOfSpecies),
##                               x = names(temp))],
##                  rowSums(temp[,grep(pattern = "VV", x = names(temp))], na.rm = T))
## names(temp0)[ncol(temp0)]<-paste0("VV",NameBaseTotal)
## temp0<-data.frame(temp0)
## temp[ncol(temp)+1]<-temp0[ncol(temp0)]
##
##
## #Total V
## # names(temp)[names(temp) %in% paste0("V", NameBaseTotal)]<-paste0("REMOVED_V", NameBaseTotal)
##
## temp0<-temp[grep(x = names(temp),
##                  pattern = paste0("V[0-9]+_", NumberOfSpecies))]
## temp0<-temp0[!(grepl(x = names(temp0), pattern = c("VV")))]
## temp0<-temp0[!(grepl(x = names(temp0), pattern = c("REMOVED_")))]
##
## temp[ncol(temp)+1]<-rowSums(temp0, na.rm = T)
## names(temp)[ncol(temp)]<-paste0("V", NameBaseTotal)
##
##
##
## ###Revenue Share for the each category ($R_{t,i}$)
## # $$R_{t,i} = V_{t,i}/V_t$$
## # where:
## # - $R_{t,i}$ is the revenue share per individual species (s), category (i), for each year (t)
## # - $V_{t,i}$ is the value ($) per individual species (s), category (i), for each year (t)
## # Here, we don't use $VV_{t,i}$ because we want to expand the proportion to include all of the species
## tempR<-data.frame(data = rep_len(x = NA, length.out = nrow(temp)))
##
## for (i in 1:length(category)) {
##
##   CatCol<-names(temp)[grep(pattern = paste0("V", category[i], "_", NumberOfSpecies),
##                             x = substr(x = names(temp),
##                                           start = 1,
##                                           stop = nchar(paste0("V", category[i], "_", NumberOfSpecies)))
##                             )]
##   NameBasecategory<-substr(x = CatCol, start = 2, stop = nchar(CatCol))
##
##   tempR[,i]<-temp[,paste0("V", NameBasecategory)]/temp[,paste0("V", NameBaseTotal)]
##   names(tempR)[i]<-paste0("R", NameBasecategory)
## }
## temp<-cbind.data.frame(temp, tempR)
##
## # Is there a warning?
## if (sum(rowSums(tempR, na.rm = T)) != nrow(temp)) {
##   warnings.list[length(warnings.list)+1]<-paste0("Warning: Rows of R_{t,i} for ",NameBaseTotal," d
##   a<-warnings.list[length(warnings.list)][[1]]
## } else {
##   a<- "No warning."
## }

```

```

##
##
##
##
## #remove duplicates
## temp<-temp[, !(grepl(pattern = "\\.[0-9]+", x = names(temp)))]
## temp <- temp[, !duplicated(colnames(temp))]
## temp<-temp[, !(grepl(pattern = "\\.[0-9]+", x = names(temp)))]
## temp <- temp[, !duplicated(colnames(temp))]
##
##
##
##
## ###Revenue Share-Weighted Qunatity Changes for each category ($QCW_{t,i}$; e.g., Finfish and Shell.
## # $$QCW_{t,i} = \frac{R_{t,i,s} + R_{s,t-1,i}}{2} * \ln(\frac{QI_{t,i,s}}{QI_{s,t-1,i}}) = \frac{R_{t,i,s} + R_{s,t-1,i}}{2} * \ln(QI_{t,i,s}) - \frac{R_{s,t-1,i}}{2} * \ln(QI_{s,t-1,i})
## # Where:
## # - $QCW_{t,i}$ = Revenue share-weighted quantity change for each category (i)
## # Such that:
## # - category's (i) Quantity Change for each category (i) = $\frac{R_{t,i,s} + R_{s,t-1,i}}{2}$
## # - category's (i) Revenue Share for each category (i) = $\ln(\frac{QI_{t,i,s}}{QI_{s,t-1,i}}) = [\ln(QI_{t,i,s}) - \ln(QI_{s,t-1,i})]$
##
## #Find which columns in this table are price and revenue share columns
## tempQCW<-data.frame(data = rep_len(x = NA, length.out = nrow(temp)))
## for (i in 1:length(category)) {
##
##     CatCol<-names(temp)[grep(pattern = paste0("VE", category[i], "_", NumberOfSpecies),
##                               x = substr(x = names(temp),
##                                           start = 1,
##                                           stop = nchar(paste0("VE", category[i], "_", NumberOfSpecies)))]
##     NameBasecategory<-substr(x = CatCol, start = 3, stop = nchar(CatCol))
##
##     # Calculate
##     Q0<-temp[, names(temp) %in% paste0("QI", NameBasecategory)]
##     R0<-temp[, names(temp) %in% paste0("R", NameBasecategory)] #to make sure its the same column
##     tempQCW[,i]<-PriceChange(R0, Q0)
##     names(tempQCW)[i]<-paste0("QCW", NameBasecategory ) #name the column
## }
##
## temp<-cbind.data.frame(temp, tempQCW)
##
##
##
##
## ###Quantity Changes for the entire fishery ($QC_{t}$)
## # $$QC_{t} = \ln(\frac{QI_{t,i}}{QI_{t-1,i}}) = \sum_{s=1}^n(QC_{t,i}) $$
## # Where:
## # - $QC_{t}$ = Quantity change for the entire fishery
##
## temp[ncol(temp)+1]<-rowSums(tempQCW, na.rm = T)
## names(temp)[ncol(temp)]<-paste0("QC", NameBaseTotal)

```

```

##
##
## #remove duplicates
## temp<-temp[, !(grepl(pattern = "\\.[0-9]+", x = names(temp)))]
## temp <- temp[, !duplicated(colnames(temp))]
## temp<-temp[, !(grepl(pattern = "\\.[0-9]+", x = names(temp)))]
## temp <- temp[, !duplicated(colnames(temp))]
##
##
## ###Quantity Index for the entier fishery ($QI_{t}$)
## # We calculate the quantity index first by comparing by multiplying the previous years $QI_{t-1}$
## # $$QI_{t} = QI_{t-1} * \exp(\ln(\frac{Q_{t,i}}{Q_{t-1,i}})) = QI_{t-1} * \exp(QC_{t})$$
## # Where
## # $$QI_{t_{first year}} = 1$$
## # Note that the first row of this column is = 1
## # Then, to change the price index into base year dollars, we use the following equation:
## # $$QI_{t} = QI_{t} / QI_{t = baseyear}$$
##
## tempQI<-PriceIndex(temp, BaseColName = NameBaseTotal, baseyr, var = "QC")
## temp[ncol(temp)+1]<-(tempQI)
## names(temp)[ncol(temp)]<-paste0("QI", NameBaseTotal)
##
##
##
##
## #remove duplicates
## temp<-temp[, !(grepl(pattern = "\\.[0-9]+", x = names(temp)))]
## temp <- temp[, !duplicated(colnames(temp))]
## temp<-temp[, !(grepl(pattern = "\\.[0-9]+", x = names(temp)))]
## temp <- temp[, !duplicated(colnames(temp))]
##
##
##
##
## ### Sum Total Simple Sum Quantity Output Index
## # $$QE_{t} = QE_{t} / QE_{t=baseyr}$$
## # Where:
## # - $QE_{t}$ is the sum of Q before these calculations; the simple sum
## # - $QE_{t}$ is the index of the sum of Q before these equations
##
## QE<-names(temp)[names(temp) %in% paste0("QE", NameBaseTotal)]
## # QE<-QE[substr(x = QE, start = 1, stop = 2) %in% "QE"]
## temp[,ncol(temp)+1]<-temp[,QE]/temp[,QE][rownames(temp) %in% baseyr]
## names(temp)[ncol(temp)]<-paste0("QEI", NameBaseTotal)
##
##
##
##
## ## Other Analysis Warnings Checks
## # To make sure our analyses worked as inteded, let's see if we can back calculate our numbers.
## # We want the calcuated V to equal this check:
##
## #####When back calculated, growth rate?
## # $$\ln(Q_t/Q_{t-1}) = \sum( ( \frac{R_{i, t} + R_{i, t-1}}{2} ) * \ln(\frac{Q_{t,i}}{Q_{t-1,i}}))$$

```

```

##
## #Part 1
## names0<-c(paste0("QI",NameBaseTotal))
## for (i in 1:length(category)) {
##   names0<-c(names0,
##   names(temp)[grep(pattern = paste0("QI", category[i], "_", NumberOfSpecies), names(temp))],
##   names(temp)[grep(pattern = paste0("R", category[i], "_", NumberOfSpecies), names(temp))])
## }
##
## temp0<-temp[,names0]
##
## temp0[, (ncol(temp0)+1)]<-c(NA, ln(temp0[-nrow(temp0),paste0("QI",NameBaseTotal)]/
##                               temp0[-1,paste0("QI",NameBaseTotal)]))
## names(temp0)[ncol(temp0)]<-"part1"
##
## #Part 2
## temp00<-data.frame()
## for (i in 1:length(category)) {
##   R0<-temp0[,grep1(pattern = paste0("R", category[i]), x = names(temp0))]
##   Q0<-temp0[,grep1(pattern = paste0("QI", category[i]), x = names(temp0))]
##
##   for (r in 2:(nrow(temp0))) {
##     temp00[r,i]<-(((R0[r] + R0[r-1])/2) * ln(Q0[r] / Q0[r-1]))
##   }
##   names(temp00)[i]<-paste0("ln", category[i])
## }
##
## temp0[, (ncol(temp0)+1)]<-rowSums(temp00)
## names(temp0)[ncol(temp0)]<-"part2"
##
##
## if (length(setdiff(as.character(temp0$part1),
##                     as.character(temp0$part2))) != 0) {
##   warnings.list[length(warnings.list)+1]<-"Warning: When back calculated, ln(Q_t/Q_{t-1}) = did not"
## }
##
##
##
## ####4. Missing Data
##
## #value
## a<-temp
## a<-a[,grep(pattern = "V[1-9]_[1-9]_", x = names(a))]
## if(length(grep(pattern = "REMOVED_", x = names(a)) &
##         grep(pattern = "Total", x = names(a), ignore.case = T)) != 0 ){
##   a<-a[,-c(grep(pattern = "REMOVED_", x = names(a)), grep(pattern = "Total", x = names(a), ignore.
## )
## ncol0<-ncol(a)
## aa<-0
## a<-data.frame(a)
## if(ncol(a) != 0){
##   for (iii in 1:ncol(a)) {
##     aa<-c(aa, ifelse(sum(a[,iii] %in% c(NA, NaN, 0)) == nrow(a), iii, NA))
##   }
## }

```

```

##     vv<-(aa[!(is.na(aa))])
##   } else {
##     pp<-0
##   }
##   #quantity
##   a<-temp
##   a<-a[,grep(pattern = "Q[1-9]+_[1-9]+", x = names(a))]
##   if(length(grep(pattern = "REMOVED_", x = names(a)) &
##             grep(pattern = "Total", x = names(a), ignore.case = T)) != 0 ){
##     a<-a[,-c(grep(pattern = "REMOVED_", x = names(a)), grep(pattern = "Total", x = names(a), ignore.
##   ]
##   ncol0<-ncol(a)
##   aa<-0
##   a<-data.frame(a)
##   if(ncol(a) != 0){
##     for (iii in 1:ncol(a)) {
##       aa<-c(aa, ifelse(sum(a[,iii] %in% c(NA, NaN, 0)) == nrow(a), iii, NA))
##     }
##     qq<-(aa[!(is.na(aa))])
##   } else {
##     pp<-0
##   }
##
##
##
##   warnings.list[length(warnings.list)+1]<-paste0("FYI: ", ifelse(length(vv)==1, 0, length(vv)-1) ,
##                                                    " of species V columns are completely empty, ",
##                                                    ifelse(length(qq)==1, 0, length(qq)-1) ,
##                                                    " of species Q columns are completely empty.")
##
##
##   #####GRAPHS
##   #remove duplicates
##   temp<-temp[, !(grepl(pattern = "\\.[0-9]+", x = names(temp)))]
##   temp <- temp[, !duplicated(colnames(temp))]
##   temp<-temp[, !(grepl(pattern = "\\.[0-9]+", x = names(temp)))]
##   temp <- temp[, !duplicated(colnames(temp))]
##
##
##   #####Calculated Q by Species
##   title00<- "_QI-Species"
##
##   a0<-data.frame(temp[,grepl(
##     pattern = paste0("QI[0-9]+_", NumberOfSpecies),
##     x = names(temp))])
##
##   a0$Year<-rownames(a0)
##
##   a <- gather(a0, Category, val, names(a0)[grepl(pattern = NumberOfSpecies, x = names(a0))], factor_
##
##   a$cat<-as.character(lapply(X = strsplit(x = as.character(a$Category), split = paste0("_", NumberOf
##
##   temp0<-a

```

```

##
## g<-plotnlines(dat = temp0, title00, place)
##
## figures.list[[length(figures.list)+1]]<-g
## names(figures.list)[length(figures.list)]<-paste0(title0, title00)
##
##
## #####Summed Q By Species
## title00<- "_QE-Species"
##
## a0<-data.frame(temp[,grepl(
##   pattern = paste0("QE[0-9]+"_ , NumberOfSpecies),
##   x = names(temp))])
##
## a0$Year<-rownames(a0)
##
## a <- gather(a0, Category, val, names(a0)[grepl(pattern = NumberOfSpecies, x = names(a0))], factor_
##
## a$cat<-as.character(lapply(X = strsplit(x = as.character(a$Category), split = paste0("_", NumberOf
##
## temp0<-a
##
## g<-plotnlines(dat = temp0, title00, place)
##
## figures.list[[length(figures.list)+1]]<-g
## names(figures.list)[length(figures.list)]<-paste0(title0, title00)
##
## #####Qunantity Index
## title00<- "_QI-Line"
##
## a0<-data.frame(temp[,grepl(
##   pattern = paste0("QI[0-9]+"_ , NumberOfSpecies),
##   x = names(temp))])
##
## a0$Year<-rownames(a0)
##
## a <- gather(a0, Category, val, names(a0)[grepl(pattern = NumberOfSpecies, x = names(a0))], factor_
##
## a$cat<-as.character(lapply(X = strsplit(x = as.character(a$Category), split = paste0("_", NumberOf
##
## temp0<-a
##
## g<-plotnlines(dat = temp0, title00, place)
##
## # figures.list[[length(figures.list)+1]]<-g
## # names(figures.list)[length(figures.list)]<-paste0(title0, title00)
##
##
## #####VV
## title00<- "_VV-Line"
##
## a0<-data.frame(temp[,grepl(
##   pattern = paste0("VV[0-9]+"_ , NumberOfSpecies),
##   x = names(temp))])

```

```

##
## a0$Year<-rownames(a0)
##
## a <- gather(a0, Category, val, names(a0)[grepl(pattern = NumberOfSpecies, x = names(a0))], factor_
##
## a$cat<-as.character(lapply(X = strsplit(x = as.character(a$Category),
##                               split = paste0("_", NumberOfSpecies)), function(x) x[2]))
##
## temp0<-a
##
## g<-plotnlines(dat = temp0, title00, place)
##
## figures.list[[length(figures.list)+1]]<-g
## names(figures.list)[length(figures.list)]<-paste0(title0, title00)
##
##
## #####V
## title00<- "_V-Line"
##
## a0<-data.frame(temp[,grepl(
##   pattern = paste0("V[0-9]+_", NumberOfSpecies),
##   x = names(temp))])
## a0<-a0[!grepl(pattern = "REMOVED_", x = names(a0))]
## a0<-a0[!grepl(pattern = "VV[0-9]+_", x = names(a0))]
##
## a0$Year<-rownames(a0)
##
## a <- gather(a0, Category, val, names(a0)[grepl(pattern = NumberOfSpecies, x = names(a0))], factor_
##
## a$cat<-as.character(lapply(X = strsplit(x = as.character(a$Category),
##                               split = paste0("_", NumberOfSpecies)),
##                             function(x) x[2]))
##
## temp0<-a
##
## g<-plotnlines(dat = temp0, title00, place)
##
## figures.list[[length(figures.list)+1]]<-g
## names(figures.list)[length(figures.list)]<-paste0(title0, title00)
##
##
##
## #####V and VV
## title00<- "_VvVV-Line"
##
## a0<-data.frame(temp[,grepl(
##   pattern = paste0("V[0-9]+_", NumberOfSpecies),
##   x = names(temp))])
## a0<-a0[!grepl(pattern = "REMOVED_", x = names(a0))]
##
## a0$Year<-rownames(a0)
##
## a <- gather(a0, Category, val, names(a0)[grepl(pattern = NumberOfSpecies, x = names(a0))], factor_
##

```

```

## a$cat<-paste0(as.character(lapply(X = strsplit(x = as.character(a$Category), split = paste0("_", N
##
##         "_",
##         as.character(lapply(X = strsplit(x = as.character(a$Category), split = paste0("_", N
##
## temp0<-a
##
## g<-plotnlines(dat = temp0, title00, place)
##
## # figures.list[[length(figures.list)+1]]<-g
## # names(figures.list)[length(figures.list)]<-paste0(title0, title00)
##
##
## #####VE
## title00<- "_VE-Line"
##
## a0<-data.frame(temp[,grepl(
##   pattern = paste0("VE[0-9]+_", NumberOfSpecies),
##   x = names(temp))])
##
## a0$Year<-rownames(a0)
##
## temp0<-a0
##
## temp0<-gather(temp0, cat, val,
##               names(temp0)[1]:names(temp0)[length(names(temp0))-1],
##               factor_key = T)
##
## temp0$cat<-paste0(as.character(lapply(X = strsplit(x = as.character(temp0$cat),
##               split = paste0("_", NumberOfSpecies))), function
##               "_",
##               as.character(lapply(X = strsplit(x = as.character(temp0$cat),
##               split = paste0("_", NumberOfSpecies))), function
##
##
## g<-plotnlines(dat = temp0, title00, place)
##
## figures.list[[length(figures.list)+1]]<-g
## names(figures.list)[length(figures.list)]<-paste0(title0, title00)
##
## ##### Quantity Index Compare
## # For comparison, let's recreate those graphs to make sure we are getting the same output:
## title00<- "_QIvQEI-Line"
##
## temp0<-temp
## temp0$Year<-rownames(temp0)
##
## temp0<-data.frame(temp0[,names(temp0) %in% c("Year",
##               paste0("QI", NameBaseTotal),
##               paste0("QEI", NameBaseTotal))])
## temp0$Year<-rownames(temp0)
##
## temp0<-gather(temp0, cat, val,
##               names(temp0)[1]:names(temp0)[length(names(temp0))-1],
##               factor_key = T)

```



```

##
## temp0$cat<-paste0(as.character(lapply(X = strsplit(x = as.character(temp0$cat),
##                                     split = paste0("_", NumberOfSpecies))), function
##                                     "_",
##                                     as.character(lapply(X = strsplit(x = as.character(temp0$cat),
##                                     split = paste0("_", NumberOfSpecies))), function
##
## g<-plotnlines(dat = temp0, title00, place)
##
## figures.list[[length(figures.list)+1]]<-g
## names(figures.list)[length(figures.list)]<-paste0(title0, title00)
##
##
## ##### Revenue Share
## title00<-"_R-Line"
## temp0<-temp
##
## temp0<-temp0[grepl(pattern = paste0("R[0-9]+_", NumberOfSpecies), x = names(temp0))]
## temp0$Year<-rownames(temp0)
##
## temp0<-gather(temp0, cat, val,
##               names(temp0)[1]:names(temp0)[length(names(temp0))-1],
##               factor_key = T)
##
## plotnlines(dat = temp0, title00, place)
##
## figures.list[[length(figures.list)+1]]<-g
## names(figures.list)[length(figures.list)]<-paste0(title0, title00)
##
## ##### Quantity Change
## title00<-"_QC-Line"
## temp0<-temp
##
## temp0<-temp0[grepl(pattern = paste0("QC[0-9]+_", NumberOfSpecies), x = names(temp0))]
## temp0$Year<-rownames(temp0)
##
## temp0<-gather(temp0, cat, val,
##               names(temp0)[1]:names(temp0)[length(names(temp0))-1],
##               factor_key = T)
##
## temp0$cat<-paste0(as.character(lapply(X = strsplit(x = as.character(temp0$cat),
##                                     split = paste0("_", NumberOfSpecies))), function
##                                     "_",
##                                     as.character(lapply(X = strsplit(x = as.character(temp0$cat),
##                                     split = paste0("_", NumberOfSpecies))), function
##
## g<-plotnlines(dat = temp0, title00, place)
##
## figures.list[[length(figures.list)+1]]<-g
## names(figures.list)[length(figures.list)]<-paste0(title0, title00)
##
##
##

```

```

## #####Number Missing V Per Year
## title00<- "_VNumberMissing-Line"
##
## a0<-data.frame(temp.orig[,grepl(
##   pattern = paste0("V[0-9]+_"),
##   x = names(temp.orig)) &
##   !(grepl(
##     pattern = paste0("V[0-9]+_ ", NumberOfSpecies),
##     x = names(temp.orig)))]))
##
## total.no.v<-ncol(a0)*nrow(a0)
##
## cat0<-data.frame(names0 = (names(temp.orig)[grepl(pattern = paste0("VE[0-9]+_ ", NumberOfSpecies),
##   x = names(temp.orig)))]))
##
## cat0$no<-as.character(lapply(X = strsplit(x = as.character(cat0$names0), split = "_"),
##   function(x) x[1]))
##
## cat0$numberofspp<-NA
## for (i in 1:nrow(cat0)) {
##   cat0$numberofspp[i]<-length(grep(pattern = cat0$no[i],
##     x = substr(x = names(a0),
##       start = 1,
##       stop = max(nchar(cat0$no))) ))
## }
##
## cat0$no<-as.character(gsub(pattern = "[a-zA-Z]", replacement = "", x = cat0$no))
##
## cat0$catname<-as.character(lapply(X = strsplit(x = as.character(cat0$names0), split = NumberOfSpecies),
##   function(x) x[2]))
## cat0$label<-paste0(cat0$catname, " (n=", cat0$numberofspp,")")
##
## a<-temp.orig
## a$Year<-rownames(a)
## a<-a[,!grepl(pattern = NumberOfSpecies, x = names(a))]
## a00<-gather(data = a, spp, val, names(a)[1]:names(a)[length(names(a))-1], factor_key = T)
## a00<-a00[grepl(pattern = "V", x = substr(x = a00$spp, start = 1, stop = 1)),]
## a00$na<-0
## a00$na[(is.na(a00$val)) | a00$val %in% 0]<-1
## a00$no<-gsub(pattern = "[a-zA-Z]", replacement = "", x = as.character(lapply(X = strsplit(x = as.character(a00$no),
##   function(x) x[1])) ))
##
## a00$x<-1
##
## aa<-a00
##
## a00<-merge(x = aa, y = cat0, by = "no")
##
## #SUM
## a<-aggregate(x = a00[,c("na", "x")],
##   by = list("Year" = a00$Year, "Category" = a00$catname),
##   FUN = sum, na.rm = T)
##
## a<-rbind.data.frame(a,
##   data.frame(Year = aggregate(x = a00$na, by = list("Year" = a00$Year), FUN = sum)

```

```

##                                     Category = "Total",
##                                     na = aggregate(x = a00$na, by = list("Year" = a00$Year), FUN = sum,
##                                     x = nrow(temp.orig)*ncol(temp.orig)))
##
## a$x.perc<-a$na/a$x*100
## a$bins<-round_any(a$x.perc, 10)
##
## xnames<-as.numeric(paste0(a$Year))
## xnames[!(xnames %in% seq(from = min((as.numeric(xnames))),
##                             to = max(as.numeric(xnames)),
##                             by = 10)))]<-" "
##
## g<-ggplot(data = a, aes(x = factor(Year), y = na, color = Category)) +
##   geom_line(aes(group = Category)) +
##   geom_point() +
##   theme(
##     panel.grid.major.y = element_line( color=NOAALightBlue, size = .1 ),
##     panel.grid.minor.y = element_blank(),
##     panel.grid.major.x = element_blank(),
##     panel.grid.minor.x = element_blank(),
##     axis.line = element_line( color=NOAALightBlue, size = .1 ),
##     axis.ticks = element_blank(), # remove ticks
##     panel.background = element_blank()
##   ) +
##   scale_x_discrete(labels= xnames) +
##   guides(fill=FALSE) +
##   ggtitle(paste0(place, " ", title00))
##
## figures.list[[length(figures.list)+1]]<-g
## names(figures.list)[length(figures.list)]<-paste0(title0, title00)
##
## #####Percent Missing V
## # title00<- "_PctMissingV_Line"
## #
## # g<-ggplot(data = a, aes(x = factor(Year), y = x.perc, color = Category)) +
## #   geom_line(aes(group = Category)) +
## #   geom_point() +
## #   theme(
## #     panel.grid.major.y = element_line( color=NOAALightBlue, size = .1 ),
## #     panel.grid.minor.y = element_blank(),
## #     panel.grid.major.x = element_blank(),
## #     panel.grid.minor.x = element_blank(),
## #     axis.line = element_line( color=NOAALightBlue, size = .1 ),
## #     axis.ticks = element_blank(), # remove ticks
## #     panel.background = element_blank()
## #   ) +
## #   scale_x_discrete(labels= xnames) +
## #   guides(fill=FALSE) +
## #   ggtitle(paste0(place, " ", title00))
## #
## # figures.list[[length(figures.list)+1]]<-g
## # names(figures.list)[length(figures.list)]<-paste0(title0, title00)
##
##

```

```

## # How many V columns have X percentage data missing
## title00<- "_VPctMissing-Bar"
##
## a00<-data.frame(table(a[,names(a) %in% c("bins", "Category")]))
##
## cat00<-merge(y = cat0[,c("catname", "numberofspp")],
##             x = a,
##             by.y = "catname", by.x = "Category")
##
## cat00$label<-paste0(cat00$Category, " (n=", cat00$numberofspp,")")
##
## cat000<-data.frame(table(cat00[,names(cat00) %in% c("label", "bins")]))
##
## xnames<-paste0(sort(as.numeric(paste(unique(a$bins)))), "%")
##
## g<-ggplot(data = cat000, aes(x = factor(bins), y = Freq, fill = label)) +
##   geom_bar(stat="identity", position=position_dodge()) +
##   theme(
##     panel.grid.major.y = element_line( color=NOAALightBlue, size = .1 ),
##     panel.grid.minor.y = element_blank(),
##     panel.grid.major.x = element_blank(),
##     panel.grid.minor.x = element_blank(),
##     axis.line = element_line( color=NOAALightBlue, size = .1 ),
##     axis.ticks = element_blank(), # remove ticks
##     panel.background = element_blank()
##   ) +
##   scale_x_discrete(labels = xnames) +
##   ggtitle(paste0(place, " ", title00))
##
## figures.list[[length(figures.list)+1]]<-g
## names(figures.list)[length(figures.list)]<-paste0(title0, title00)
##
##
## ###OVERVIEW
##
##
##
## #Species
## spp.output<-list()
## spptable0<-data.frame(Analysis = title0,
##                       Place = place,
##                       Catagory = rep_len(x = NA, length.out = length(category)),
##                       TotCount = rep_len(x = NA, length.out = length(category)),
##                       RmCount = rep_len(x = NA, length.out = length(category)),
##                       UsedCount = rep_len(x = NA, length.out = length(category)))
## cat1<-(as.character(lapply(X = strsplit(x = as.character(names(temp)),
##                                         split = paste0("_")),
##                           function(x) x[1])))
## cat2<-(as.character(lapply(X = strsplit(x = as.character(names(temp)),
##                                         split = paste0("_")),
##                           function(x) x[2])))
##
## for (i in 1:length(category)) {

```

```

##      #Orgionally
##      spp.pre<-unique(cat2[grepl(pattern = paste0("V", category[i]), x = cat1)], cat2[grepl(pattern = pa
##      cat.pre<-spp.pre[grepl(pattern = NumberOfSpecies, x = spp.pre)]
##      cat.pre<-unique(gsub(pattern = "[0-9]", replacement = "", x = cat.pre))
##      spp.pre<-spp.pre[!grepl(pattern = NumberOfSpecies, x = spp.pre)]
##      spp.pre<-gsub(pattern = "[0-9]", replacement = "", x = spp.pre)
##      spp.pre<-sort(x = as.character(spp.pre), decreasing = F)
##
##      #In Analysis
##      spp.pst<-cat2[grepl(pattern = paste0("R", category[i]), x = cat1)]
##      cat.pst<-spp.pst[grepl(pattern = NumberOfSpecies, x = spp.pst)]
##      cat.pst<-gsub(pattern = "[0-9]", replacement = "", x = cat.pst)
##      spp.pst<-spp.pst[!grepl(pattern = NumberOfSpecies, x = spp.pst)]
##      spp.pst<-gsub(pattern = "[0-9]", replacement = "", x = spp.pst)
##      spp.pst<-sort(x = as.character(spp.pst), decreasing = F)
##
##      spp.output[[i]]<-list("pre" = spp.pre,
##                           "pst" = spp.pst)
##      names(spp.output)[[i]]<-cat.pst
##      spptable0$Catagory[i]<- cat.pst
##      spptable0$TotCount[i]<-length(spp.pre)
##      spptable0$UsedCount[i]<-ifelse(is.na(length(spp.pst)), 0, length(spp.pst))
##      spptable0$RmCount[i]<-spptable0$TotCount[i] - spptable0$UsedCount[i]
##    }
##
##
##
##
##
##      return(list(temp, warnings.list, figures.list, spptable0, spp.output))
##  }
## <bytecode: 0x0000000018a63668>

```

2.3.2 A. Import and Edit data

```

temp<-read.csv(file = paste0(dir.data, "Tornqvist Index-Calculations_OutputEx.csv"))
rownames(temp)<-temp$year
temp$year<-NULL

temp.q<-temp[,grepl(pattern = "Q", x = names(temp))]
temp.q$QE0_Total<-rowSums(temp.q, na.rm = T)
temp.q$QE1_0Finfish<-rowSums(temp.q[,grepl(x = names(temp.q), pattern = "Q1") ], na.rm = T)
temp.q$QE2_0Shellfish<-rowSums(temp.q[,grepl(x = names(temp.q), pattern = "Q2") ], na.rm = T)

temp.v<-temp[,grepl(pattern = "V", x = names(temp))]
temp.v$VE0_Total<-rowSums(temp.v, na.rm = T)
temp.v$VE1_0Finfish<-rowSums(temp.v[,grepl(x = names(temp.v), pattern = "V1") ], na.rm = T)
temp.v$VE2_0Shellfish<-rowSums(temp.v[,grepl(x = names(temp.v), pattern = "V2") ], na.rm = T)

temp<-orgional.data<-cbind.data.frame(temp.q, temp.v)

```

2.3.3 B. Enter base year

```
baseyr<-baseyr
```

2.3.4 C. Run the function

```
temp00<-ImplicitQuantityOutput.q(temp = orgional.data, baseyr, pctmiss)
temp<-temp00[[1]]
warnings.list0<-temp00[[2]]
figures.list0<-temp00[[3]]
```

2.3.5 D. Obtain the implicit quantity estimates

	QE0_0Total	VE0_0Total	VV0_0Total	V0_0Total	QC0_0Total	QI0_0Total	QEI0_0Total
2007	3250	5600	4820	4600	0.0000000	0.8809353	1.2452107
2008	3380	6220	5120	5020	0.0252468	0.9034593	1.2950192
2009	3150	5710	4910	4810	-0.0234756	0.8824970	1.2068966
2010	2610	3890	4790	3890	0.1249998	1.0000000	1.0000000
2011	2490	4180	5080	4180	-0.0589868	0.9427192	0.9540230
2012	2412	4150	5050	4150	0.0009742	0.9436381	0.9241379
2013	3251	6280	5280	5280	-0.0866462	0.8653175	1.2455939
2014	3431	6270	5470	5370	0.0530883	0.9124970	1.3145594
2015	3630	6700	5800	5700	0.0143972	0.9257294	1.3908046
2016	3575	6780	5780	5680	0.0236999	0.9479312	1.3697318

Did all of the analyses work as intended?

Warning: When back calculated, $\ln(Q_t/Q_{t-1}) = \text{did not equal } \sum((R_{\{i, t\}} - R_{\{i, t-1\}}) / 2) \times \ln((Q_{\{i, t\}}) / (Q_{\{i, t-1\}}))$, FYI: 0 of species V columns are completely empty, 2 of species Q columns are completely empty.

2.3.6 E. Graph

2.3.6.1 Graph 1: Price Index

For comparison, let's recreate those graphs to make sure we are getting the same output:


```
figures.list0$`_QI-Line`
```

```
## NULL
```

2.3.6.2 Graph 2: Quantity Index Compare

For comparison, let's recreate those graphs to make sure we are getting the same output:

```
figures.list0$`_QIvQEI-Line`
```



2.3.6.3 Graph 3: Quantity Compare

```
figures.list0$`_VvVV-Line`
```

```
## NULL
```