

Manually Enter These User-Stories as Issues

US-2.1 — Monsters come from data, not from code · 3 pts

*As a ****game designer****, I want monsters defined in a data file, so that I can add or rebalance a creature without a programmer or a recompile.*

- Given the source tree, when I search for new `Monster()`, then there is exactly one match and it is inside the factory.
- Given a new entry in `monsters.json`, when I run the game, then that creature can appear, with **no** Java file modified.
- Given a known blueprint id, when the factory creates it at depth 1 and depth 5, then the depth-5 monster is stronger.
- Given an **unknown** id, when the factory is asked for it, then a usable fallback monster is returned and the game does not crash.

US-2.2 — Each level is a place with a consistent character · 4 pts

*As a ****player****, I want each dungeon level to feel like a distinct place, so that descending is an experience rather than an increment.*

- Given a generated world, when I inspect each level, then level 1 is Crypt, level 2 is Forge, level 3 is Frost, and each level reports its theme.
- Given any level, when I list every monster and every piece of loot on it, then all of them belong to that level's theme.
- Given a room on a forge level, when I read its flavour text, then it describes heat, not a tomb.
- Given a fourth theme kit and one registry line, when I set `dungeonDepth` to 4 and run, then level 4 uses the new theme **and** `GameWorld` **was not modified**.

US-2.3 — Different kinds of room hold different things · 3 pts

*As a ****player****, I want treasure rooms and boss rooms to feel different from corridors, so that exploring is rewarded.*

- Given a standard room, when it is populated, then it has zero to N monsters, no chest, and non-empty flavour text.

- Given a treasure room, when it is populated, then it has exactly one guard and a chest holding at least two theme-appropriate items.
- Given the final room of the deepest level, when it is populated, then it contains that theme's boss.
- Given RoomPopulator, when I inspect populate(), then it is final, and createEncounter() is abstract.