



From PCP to ZK-STARK

Eli Ben-Sasson | Chief Scientist (East) | February 2019

Overview



Proofs of Computational Integrity (CI)

INTEGRITY

The quality of being honest
(Dictionary)

Proofs of Computational Integrity (CI)

INTEGRITY

The quality of being honest
(Dictionary)

COMPUTATIONAL INTEGRITY

The quality of a computation
being executed honestly

Proofs of Computational Integrity (CI)

INTEGRITY

The quality of being honest
(Dictionary)

COMPUTATIONAL INTEGRITY

The quality of a computation
being executed honestly

CI Statement: total=\$138.16

➤ **Prover:** Party producing proof
(here: Grocer)

➤ **Verifier:** Party checking proof
(here: Customer)

GUESTCHECK™

Date	Table	Guests	Server	
9/10	42	5	K	367137

APPT-SOUP/SAL-ENTREE-VEG/POT-DESSERT-BEV

Item	Qty	Price
Kebab Sampler	10	00
Spinach salad	8	50
cucumber salad	8	50
chicken kebab	13	50
Lamb + veg couscous	19	00
Lamb Tagine	19	00
side rice	4	00
1 coke @ \$2.50	2	50
11 Beer @ \$7.00	14	00
Dessert Briwatts@ \$6	12	00
↳ white + dark	111	00
15% SERVICE CHARGE:	18	00
Tax	9	16
Total	138	16

Thank You — Please Come Again

104 GUESTCHECK™ www.nationalchecking.com MADE IN THE USA

Generic CI statement: Computation C , with public input x and auxiliary private input w , reached output y in T steps

Proofs of Computational Integrity (CI)

INTEGRITY

The quality of being honest
(Dictionary)

COMPUTATIONAL INTEGRITY

The quality of a computation
being executed honestly

Grocery receipts are proofs of computational integrity

- Verification via naive re-execution of computation
- Proof is (i) deterministic, (ii) error free, (iii) one-shot (non-interactive)

GUESTCHECK™			
Date	Table	Guests	Server
9/10	42	5	K
367137			
APPT-SOUP/SAL-ENTREE-VEG/POT-DESSERT-BEV			
Kebab Sampler	10	00	
Spinach salad	8	50	
cucumber salad	8	50	
chicken kebab	13	50	
Lamb + veg couscous	19	00	
Lamb Tagine	19	00	
side rice	4	00	
1 coke @ \$2.50	2	50	
11 Beer @ \$7.00	14	00	
Dessert Briwatts @ \$6	12	00	
↳ white + dark	11	00	
15% SERVICE CHARGE:	18	00	
Tax	9	16	
Total	138	16	
Thank You — Please Come Again			
104 GUESTCHECK™ www.nationalchecking.com MADE IN THE USA			

Generic CI statement: Computation C , with public input x and auxiliary private input w , reached output y in T steps

Proofs of Computational Integrity (CI)

INTEGRITY

The quality of being honest
(Dictionary)

COMPUTATIONAL INTEGRITY

The quality of a computation
being executed honestly

Grocery receipts are proofs of computational integrity

- Verification via naive re-execution of computation
- Proof is (i) deterministic, (ii) error free, (iii) one-shot (non-interactive)
- Modern CI proofs have (i) randomness, (ii) small error, (iii) interaction; in return, offer many benefits...

GUESTCHECK™			
Date	Table	Guests	Server
9/10	42	5	K
367137			
APPT-SOUP/SAL-ENTREE-VEG/POT-DESSERT-BEV			
Kebab Sampler	10	00	
Spinach salad	8	50	
cucumber salad	8	50	
chicken kebab	13	50	
Lamb + veg couscous	19	00	
Lamb Tagine	19	00	
side rice	4	00	
1 coke @ \$2.50	2	50	
11 Beer @ \$7.00	14	00	
Dessert Briwatts@ \$6	12	00	
↳ white + dark	11	00	
15% SERVICE CHARGE:	18	00	
Tax			9 16
Total			138 16
Thank You — Please Come Again			
104 GUESTCHECK™ www.nationalchecking.com MADE IN THE USA			

Generic CI statement: Computation C , with public input x and auxiliary private input w , reached output y in T steps

Modern Computational Integrity proofs [GMR85]

IP, ZK, CS, PCP, MIP, IPCP, LPCP, PCIP, IOP, ...

GUESTCHECK™

Date	Table	Guests	Server	
9/10	42	5	K	367137

APPT-SOUP/SAL-ENTREE-VEG/POT-DESSERT-BEV

Kebab Sampler	10	00
Spinach salad	8	50
cucumber salad	8	50
chicken kebab	13	50
Lamb + veg couscous	19	00
Lamb Tagine	19	00
side rice	4	00
1 coke @ \$2.50	2	50
11 Beer @ \$7.00	14	00
Dessert Briwatts@ \$6	12	00
↳ white + dark	11	00
15% SERVICE CHARGE:	18	00
	Tax	9 16
	Total	138 16
Thank You — Please Come Again		

104 GUESTCHECK™ www.nationalchecking.com MADE IN THE USA

Generic CI statement: Computation C , with public input x and auxiliary private input w , reached output y in T steps

Modern Computational Integrity proofs [GMR85]

IP, ZK, CS, PCP, MIP, IPCP, LPCP, PCIP, IOP, ...

➤ **Privacy (Zero Knowledge, ZK):** Prover's **private inputs** are shielded


GUESTCHECK™				
Date	Table	Guests	Server	Check #
9/10	42	5	K	367137
APPT-SOUP/SAL-ENTREE-VEG/POT-DESSERT-BEV				
				10 00
				8 50
				8 50
				19 00
				4 00
				14 00
				12 00
				11 00
				18 00
				9 16
				138 16
Thank You — Please Come Again				
104 GUESTCHECK™ www.nationalchecking.com MADE IN THE USA				

➤ Generic CI statement: Computation C , with public input x and auxiliary **private input** w , reached output y in T steps

Modern Computational Integrity proofs [GMR85]

IP, ZK, CS, PCP, MIP, IPCP, LPCP, PCIP, IOP, ...

- **Privacy (Zero Knowledge, ZK):** Prover's private inputs are shielded
- **Scalability:** for computation lasting T cycles, proofs
 - generated in $\sim T$ cycles (quasi-linear in T), and
 - verified exponentially faster than T ($\sim \log T$ cycles)




Generic CI statement: Computation C , with public input x and auxiliary private input w , reached output y in T steps

Modern Computational Integrity proofs [GMR85]

IP, ZK, CS, PCP, MIP, IPCP, LPCP, PCIP, IOP, ...

- **Privacy (Zero Knowledge, ZK):** Prover's private inputs are shielded
- **Scalability:** for computation lasting T cycles, proofs
 - generated in $\sim T$ cycles (quasi-linear in T), and
 - verified exponentially faster than T ($\sim \log T$ cycles)
- **Universality (Turing Completeness):** apply to **any computation C**



CartoonStock.com


Generic CI statement: **Computation C** , with public input x and auxiliary private input w , reached output y in T steps



Modern Computational Integrity proofs [GMR85]

IP, ZK, CS, PCP, MIP, IPCP, LPCP, PCIP, IOP, ...

- **Privacy (Zero Knowledge, ZK):** Prover's private inputs are shielded
- **Scalability:** for computation lasting T cycles, proofs
 - generated in $\sim T$ cycles (quasi-linear in T), and
 - verified exponentially faster than T ($\sim \log T$ cycles)
- **Universality (Turing Completeness):** apply to **any computation C**
- **Transparency:** All verifier messages are public random coins



Generic CI statement: **Computation C** , with public input x and auxiliary private input w , reached output y in T steps


Modern Computational Integrity proofs [GMR85]

IP, ZK, CS, PCP, MIP, IPCP, LPCP, PCIP, IOP, ...

- **Privacy (Zero Knowledge, ZK):** Prover's private inputs are shielded
- **Scalability:** for computation lasting T cycles, proofs
 - generated in $\sim T$ cycles (quasi-linear in T), and
 - verified exponentially faster than T ($\sim \log T$ cycles)
- **Universality (Turing Completeness):** apply to any computation
- **Transparency:** All verifier messages are public random coins

Privacy examples

- Zcash shielded transaction: shield payer, payee and payment amount
- Paid taxes on all my 2018 transactions, without revealing them
- My crypto exchange is in the black, without showing my positions
- ...



CartoonStock.com


Modern Computational Integrity proofs [GMR85]

IP, ZK, CS, PCP, MIP, IPCP, LPCP, PCIP, IOP, ...

- **Privacy (Zero Knowledge, ZK):** Prover's private inputs are shielded
- **Scalability:** for computation lasting T cycles, proofs
 - generated in $\sim T$ cycles (quasi-linear in T), and
 - verified exponentially faster than T ($\sim \log T$ cycles)
- **Universality (Turing Completeness):** apply to any computation
- **Transparency:** All verifier messages are public random coins

Scalability examples

Naïve computation time	Verifier time	Prover time
Mega (2^{20})	400	400·Mega
Giga (2^{30})	900	900·Giga
Tera (2^{40})	1600	1600·Tera
Peta (2^{50})	2500	2500·Peta



Modern Computational Integrity proofs [GMR85]


IP, ZK, CS, PCP, MIP, IPCP, LPCP, PCIP, IOP, ...

- **Privacy (Zero Knowledge, ZK):** Prover's private inputs are shielded
- **Scalability:** for computation lasting T cycles, proofs
 - generated in $\sim T$ cycles (quasi-linear in T), and
 - verified exponentially faster than T ($\sim \log T$ cycles)
- **Universality (Turing Completeness):** apply to any computation
- **Transparency:** All verifier messages are public random coins

Scalability examples

Proof scalability can solve blockchain scalability problems

- Suppose computing latest Bitcoin state takes 1Peta (2^{50}) steps
- A single prover spends $2500 \cdot 2^{50}$ steps, posts proof
- All other nodes verify exponentially faster, in 2500 steps




Modern Computational Integrity proofs [GMR85]

IP, ZK, CS, PCP, MIP, IPCP, LPCP, PCIP, IOP, ...

- **Privacy (Zero Knowledge, ZK):** Prover's private inputs are shielded
- **Scalability:** for computation lasting T cycles, proofs
 - generated in $\sim T$ cycles (quasi-linear in T), and
 - verified exponentially faster than T ($\sim \log T$ cycles)
- **Universality (Turing Completeness):** apply to any computation
- **Transparency:** All verifier messages are public random coins

tl;dr my research: PCP-based proofs, concrete efficiency

- 1995: ZK w/ scalable verifier was “galactic algorithm”
- 2018: scalable ZK realized in code for meaningful computation
- using *scalable PCPs* and *Interactive Oracle Proofs (IOPs)*




Modern Computational Integrity proofs [GMR85]

IP, ZK, CS, PCP, MIP, IPCP, LPCP, PCIP, IOP, ...


- **Privacy (Zero Knowledge, ZK):** Prover's private inputs are shielded
- **Scalability:** for computation lasting T cycles, proofs
 - generated in $\sim T$ cycles (quasi-linear in T), and
 - verified exponentially faster than T ($\sim \log T$ cycles)
- **Universality (Turing Completeness):** apply to any computation
- **Transparency:** All verifier messages are public random coins

tl;dr my research : PCP-based proofs, concrete efficiency

Co-authors [2001-2019]: Iddo Bentov, Alessandro Chiesa, Michael Forbes, Ariel Gabizon, Daniel Genkin, Oded Goldreich, Lior Goldberg, Tom Gur, Matan Hamilis, Prahladh Harsha, Yinon Horesh, Yohay Kaplan, Swastik Kopparty, Or Meir, Evgenya Pergament, Michael Riabzev, Shubhangi Saraf, Mark Silberstein, Hennig Stichtenoth, Nicholas Spooner, Madhu Sudan, Eran Tromer, Salil Vadhan, Madars Virza, Avi Wigderson.



Many flavors of proof systems



Variety of
theoretical
constructions
(past 30 yrs)

PCP based, linear PCPs, elliptic
curve+pairing based succinct
NIZKs, proofs for muggles,
quadratic span/arithmetic
programs (QAP/QSP), interactive
oracle proofs (IOP), ...

Many flavors of proof systems

Variety of
theoretical
constructions
(past 30 yrs)

PCP based, linear PCPs, elliptic curve+pairing based succinct NIZKs, proofs for muggles, quadratic span/arithmetic programs (QAP/QSP), interactive oracle proofs (IOP), ...

...and
implementations
(past 5 yrs)

Pinocchio, libsnark, Zcash, Pepper, Buffet, ZKboo, Ligero, Bulletproofs, Hyrax, libstark, Aurora, ...

See zkp.science

Overview

1

Cryptoproofs

2

PCP, IOP
STIK, STARK
FRI

3

Concrete
Questions

zk-STARK definition [BBHR18]

An argument system is a zk-STARK if it satisfies:

zk

zero knowledge: private inputs are shielded

S

Scalable: proofs for CI of computation lasting T cycles are

- generated in roughly T cycles (quasi-linear in T), and
- verified exponentially faster than T (roughly $\log T$ cycles)

T

Transparent: verifier messages are random coins; no trusted setup

AR

ARgument of Knowledge: proof can be generated only by party knowing private input (formally: an efficient procedure can extract the secrets from a prover)

K

Welcome to [REDACTED]

[REDACTED] 3.29

[REDACTED] 2.19

[REDACTED]

3 bananas 800 gm [REDACTED] [REDACTED]

Loaf of bread [REDACTED]

1 chicken [REDACTED] [REDACTED]

SUBTOTAL [REDACTED]

HST [REDACTED]

TOTAL \$21.81

TRANSACTION RECORD #: [REDACTED]

DATE 09/22/2014 TIME 4.25 LANE 4

THANK YOU FOR SHOPPING AT LEE'S

zk-STARK definition [BBHR18]

An argument system is a zk-STARK if it satisfies:

zk

zero knowledge: private inputs are shielded

S

Scalable: proofs for CI of computation lasting T cycles are

- generated in roughly T cycles (quasi-linear in T), and
- verified exponentially faster than T (roughly $\log T$ cycles)

T

Transparent: verifier messages are random coins; no trusted setup

AR

ARgument of Knowledge: proof can be generated only by party knowing private input (formally: an efficient procedure can extract the secrets from a prover)

K

- STARKs may be interactive (use blockchain as source of transparent randomness), gives shorter & safer proofs
- 1st STARK implementation: [SCI-POC](#) [BCG+16]; 1st zk-STARK: [libstark](#) [BBHR18]

Welcome to [REDACTED]

[REDACTED] 3.29

[REDACTED] 2.19

[REDACTED]

3 bananas 800 gm [REDACTED] [REDACTED]

Loaf of bread [REDACTED]

1 chicken [REDACTED] [REDACTED]

SUBTOTAL [REDACTED]

HST [REDACTED]

TOTAL \$21.81

TRANSACTION RECORD #: [REDACTED]

DATE 09/22/2014 TIME 4.25 LANE 4


THANK YOU FOR SHOPPING AT LEE'S

PCPs and polylogarithmic verification

“In this setup, a single reliable PC can monitor the operation of a herd of supercomputers working with possibly extremely powerful but unreliable software and untested hardware” [Babai, Fortnow, Levin, 1991]


Setup: to prove $x \in L$ for some $L \in NTIME(T(n))$

- Verifier has oracle access to PCP π ,
- Verifier runs in time $\text{poly}(n + \log(T(n)))$
- If $x \in L$ then exists π accepted w.p. 1
- If $x \in L$ then all π rejected w.p. $> \frac{1}{2}$



PCP and scalability [BFL, BFLS, AS, AL, K, M 1991-4]

1995



Naive:



Verification = proving

PCP:




Poly-logarithmic verification

PCP and scalability [BFL, BFLS, AS, ALMSS, K, M 1991-4]

1995

Proof
activity
time



Naive:




Verification = proving

PCP:




Poly-logarithmic verification

PCP and scalability [BFL, BFLS, AS, ALMSS, K, M 1991-4]



PCP and scalability [BS, BGHSV, D, M, 2003-8]

2006



Naive:



Verification = proving

PCP:



Quasi-linear proving




Poly-logarithmic verification

PCPs and polylogarithmic verification

“In this setup, a single reliable PC can monitor the operation of a herd of supercomputers working with possibly extremely powerful but unreliable software and untested hardware. ” [Babai, Fortnow, Levin, 1991]

Setup: to prove $x \in L$ for some $L \in NTIME(T(n))$


- Verifier has oracle access to PCP π ,
- Verifier runs in time $\text{poly}(n + \log(T(n)))$
- If $x \in L$ then exists π accepted w.p. 1
- If $x \in L$ then all π rejected w.p. $> \frac{1}{2}$



Interactive Oracle Proofs (IOP) [RRR16, BCS16]

IOP setup: to prove $x \in L$ for some $L \in NTIME(T(n))$


- Verifier has oracle access to 1st oracle π_0 ,
- Verifier sends public randomness r_0



Interactive Oracle Proofs (IOP) [RRR16, BCS16]

IOP setup: to prove $x \in L$ for some $L \in NTIME(T(n))$


- Verifier has oracle access to 1st oracle π_0 ,
- Verifier sends public randomness r_0
- Verifier has oracle access to 2nd oracle π_0
- ...



Interactive Oracle Proofs (IOP) [RRR16, BCS16]

IOP setup: to prove $x \in L$ for some $L \in NTIME(T(n))$

- Verifier has oracle access to 1st oracle π_0 ,
- Verifier sends public randomness r_0
- Verifier has oracle access to 2nd oracle π_0
- ...
- Verifier runs in time $\text{poly}(n + \log(T(n)))$
- If $x \in L$ then $\exists \pi_0, \pi_1, \dots, \pi_t$ accepted w.p. 1
- If $x \in L$ then all $\forall \vec{\pi}$ rejected w.p. $> \frac{1}{2}$



Scalable Transparent **AR**gument of **K**nowledge (**STARK**)

An argument system is a zk-STARK if it satisfies:

zk

zero knowledge: private inputs are shielded

S

Scalable: proofs for CI of computation lasting T cycles are

- generated in roughly T cycles (quasi-linear in T), and
- verified exponentially faster than T (roughly $\log T$ cycles)


T

Transparent: verifier messages are random coins; no trusted setup

AR

K

ARgument of Knowledge: proof can be generated only by party knowing private input (formally: an efficient procedure can extract the secrets from a prover)





IOP tl;dr

With IOPs, can prove results that are yet unknown in PCP model



- 2-round IOP with perfect ZK, non-adaptive verifier for NP [BCGV16]
- Doubly-efficient, constant round, Interactive Proofs [RRR16]
- $O(1)$ -round IOP with linear bit-length proofs and constant query comp [BCGRS17]
- Proximity protocols for Reed-Solomon with linear arithmetic complexity and logarithmic query complexity [BBHR18]
- ...
- Concretely efficient ZK-STARKs [BBC+16, BBHR18, ...]

PCP and scalability [BS, BGHSV, D, M, 2003-8]

2006





IOP and Scalability [BBC+16, BBHR18]



IOP and Scalability

T480 laptop
i7-8550U CPU
@ 1.80GHz
Quad-core
32 GB DDR4 RAM

12/2018



$$= 0 \iff \deg(f(x) \bmod Z_H(x)) < |H| - 1$$


$$x_i = z \iff w : (x - \beta^{2^i} z = a(w^2 + w)) \wedge (z^2 = z) \sum f(h) = 0 \iff \deg(f(x)) < |H| - 1$$

Scalable Transparent IOP of Knowledge (STIK) [BBHR18]

Definition:

An IOP for $L \in NTIME(T(n))$ is said to be:

- **Scalable** if both of following hold:
 - Proving time $T_p = \tilde{O}(T(n)) + poly(n) = T(n) \cdot \log^{O(1)} T(n) + poly(n)$
 - Verifying time $T_v = poly \log T(n)$
- **Transparent** if all verifier messages are public random coins (Arthur-Merlin protocols)
- **IOP of Knowledge** if exists Extractor E that extracts in time $poly T(n)$ a witness w for membership of $x \in L$, from "good" prover P_x



Strict STIK (arithmetic complexity)

Definition:


An STIK for $L \in NTIME(T(n))$ is

- **Strictly Scalable** if both of following hold:
 - Proving time $T_P = O(T(n) \log T(n))$
 - Verifying time $T_V = O(\log T(n)) + \tilde{O}(n)$

Thm [B, Chiesa, Goldberg, Gur, Riabzev, Spooner, 2019]:

Every $L \in NTIME(T(n))$ has a **strict** (ZK)-STIK, where T_P, T_V are measured using arithmetic complexity over field of size $O(T(n))$

Question: Strict STIK, Boolean complexity?




Interactive Oracle Proofs of Proximity (IOPP)

[RRR16, BCS16]

IOPP: to prove oracle f close to code $\mathcal{C} \subset F^n$

- Verifier sends public randomness r_0
- Verifier has oracle access to 1st oracle π_1
- ...
- Verifier runs in time $\text{poly}(n + \log(T(n)))$
- If $f \in \mathcal{C}$ then $\exists \pi_0, \pi_1, \dots, \pi_t$ accepted w.p. 1
- Otherwise, $\forall \vec{\pi}$ rejected w.p. $> s(\Delta(f, \mathcal{C}))$
- s is soundness function, want to maximize it



Fast Reed-Solomon IOPP (FRI) [B, Bentov, Horesh, Riabzev 2018]

Definition: Reed-Solomon code (low deg polys)
 $RS[F, S, \rho] = \{f: S \rightarrow F \mid \deg(f) < \rho|S|\}$

Thm [BBHR 2018]:


$\forall S \subseteq F, S$ is a group of size $N = 2^n$, the code $RS[F, S, \rho]$ has a (fast) IOPP with

- $T_P \leq 6 \cdot N$
- $T_V \leq 21 \cdot \log N$
- $s(\delta) \geq \min\{\delta_0, \delta\}$ for $\delta_0 \approx \frac{1-\rho}{4}$ New: $\delta_0 \approx 1 - \rho^{\frac{1}{3}}$ [BGKS19]


$$\delta_0 \approx 1 - \rho^{\frac{1}{4}} \text{ [BKS18]}$$

$$\text{New: } \delta_0 \approx 1 - \rho^{\frac{1}{3}} \text{ [BGKS19]}$$

Question: Is $s(\delta) \geq \delta - \left(\frac{|S|}{|F|}\right)^{O(1)}$ for δ as large as $1 - \rho$?



Overview



Theory questions with practical impact

1. Strict STIK, Boolean complexity

- $T_P = O(T(n) \log T(n))$ and $T_P = O(\log T(n))$
- Approach: use AG codes over constant alphabets
- Requires quasi-linear encoding time for AG codes

2. Better soundness analysis for FRI

- Is $s(\delta) \geq \delta - \left(\frac{|S|}{|F|}\right)^{O(1)}$ for δ greater than $1 - \rho^{\frac{1}{3}}$?
- Reaching Johnson bound $(1 - \sqrt{\rho})$? Beyond it?

3. Sliding scale conjecture for IOP and STIK?

- Currently soundness error greater than rate (ρ)
- Want soundness error closer to $\text{poly}(\frac{1}{|F|})$
- Perhaps simpler to solve for IOPs than for PCPs?

Crypto-Security Questions

1. STARK-friendly crypto primitives

- SHA2/3 STARK “cost” $\approx 10^4$
- Pedersen STARK “cost” $\approx 10^3$
- MiMC/Jarvis/Friday “cost” $\approx 10^2$ [AGRRT16, AD18]
- How low can you get? Algebraic security analysis?

2. STARK/STIK security analysis

- Best efficient attack on FRI? on other PCPs/PCPPs? [BBGR16]

3. STARK-friendly commitments and accumulators

- Replace Merkle trees with more efficient data structures? [LM18, BBF18]
- With Merkle trees in RO model, do you need λ or 2λ bits RO to reach $2^{-\lambda}$ soundness error?

4. How to formally verify a STIK/STARK constraint system?



Questions?

we're hiring: jobs@starkware.co

learn more: workshop@starkware.co