

Valeurs de référence des accélérations

Rappel : L'accélération est positive vers le bas

	roll	pitch	ax	ay	az
	0	0	0	0	9.81
30 port	0	0	0	-4.905	8.496
30 stbd	0	0	0	4.905	8.496
0	30 down	4.905	0	0	8.496
0	30 up	-4.905	0	0	8.496

Valeurs de référence des quaternions d'orientation

Objectif : tester les orientation et valeurs des quaternions.

cap	roll	pitch	qw	qx	qy	qz
north	0	0	1	+0	0	0
east	0	0	0.707	+0	0	0.707
south	0	0	0	+0	0	1
west	0	0	0.707	+0	0	-0.707
north	30 port	0	0.966	-0.259	0	0
east	30 port	0	0.683	-0.183	0.183	0.683
south	30 port	0	0	+0	0.259	0.966
west	30 port	0	0.683	-0.183	-0.183	-0.683
north	30 stbd	0	0.966	+0.259	0	0
east	30 stbd	0	0.683	+0.183	-0.183	0.683
south	30 stbd	0	0	+0	-0.259	0.966
west	30 stbd	0	0.683	+0.183	0.183	-0.683
north	0	30 down	0.966	+0	0.259	0
east	0	30 down	0.683	+0.183	0.183	0.683
south	0	30 down	0	+0.259	0	0.966
west	0	30 down	0.683	-0.183	0.183	-0.683
north	0	30 up	0.966	+0	-0.259	0
east	0	30 up	0.683	-0.183	-0.183	0.683
south	0	30 up	0	-0.259	-0	0.966
west	0	30 up	0.683	+0.183	-0.183	-0.683