


TEST REPORT EN IEC 62115 Electric toys – Safety	
Report Number.....:	KEYS241104083001LD-01
Date of issue.....:	November 11, 2024
Total number of pages.....	23 pages
Tested by (name + signature).....:	Echo Zhong 
Approved by (name + signature)....:	Jason Zhan 
Testing Laboratory Name.....:	Guangdong KEYS Testing Technology Co., Ltd.
Address.....:	Building 1, No.18, Shihuan Road, Dongcheng Subdistrict, Dongguan, Guangdong, China
Applicant's name.....:	SHINE RING TOYS CO.,LTD.
Address.....:	RM 1406 BUILDING 1 ZHIDI PLAZA NO 399 JIASHAN AVENUE JIAXING CHINA
Manufacturer's name.....:	SHINE RING TOYS CO.,LTD.
Address.....:	RM 1406 BUILDING 1 ZHIDI PLAZA NO 399 JIASHAN AVENUE JIAXING CHINA
Test specification:	
Standard.....:	☒ EN IEC 62115:2020+A11:2020
Test procedure.....:	CE
Non-standard test method.....:	N/A
Test item description.....:	CHILDREN MOTORCYCLE
Trade Mark.....:	N/A
Model/Type reference.....:	909,168,A608,BLF-918,BLF-1260S,BLF-1260L, HS5188,HS6188,959,MD011,R15,1800,H9002,M511,M1250, M888,BD008,JM3188,N011,N888,N999,N518,N5188,A008
Ratings.....:	12V  7Ah(Via battery supply) Input: 110-240V~ 50/60Hz Output:12Vdc 1A(Adapter charge)



General disclaimer:

This report is only for applicant use. Any copying this report to/for any other person or entity, and use our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

List of Attachments:

Attachment 1: 13 pages of photos.

Summary of testing:

N/A

Testing location:

Guangdong KEYS Testing Technology Co., Ltd.

Building 1, No.18, Shihuan Road, Dongcheng Subdistrict, Dongguan, Guangdong, China

Summary of compliance with National Differences:

☒ The product fulfils the requirements of EN IEC 62115:2020+A11:2020

Copy of marking plate for example:

The artwork below may be only a draft.

CHILDREN MOTORCYCLE

Model: 909

Input: 12V  7Ah(Via battery supply)



SHINE RING TOYS CO.,LTD.

Importer name: XXX

Importer address: YYY

Made in China

Note:

xxx means importer company name; YYY means importer company address.

All models rating label are in the same design except for model name and rating. Above label was shown for representing the others models.

Test item particulars : See test report				
Classification of installation and use: class III				
Supply Connection: Not connected to AC Mains directly				
Possible test case verdicts: - test case does not apply to the test object.....: N/A - test object does meet the requirement.....: P (Pass) - test object does not meet the requirement.....: F (Fail)				
Testing :				
Date of receipt of test item: November 4, 2024				
Date (s) of performance of tests: November 4, 2024 to November 11, 2024				
General remarks: "(See Enclosure #)" refers to additional information appended to the report. "(See appended table)" refers to a table appended to the report. Throughout this report a ☐ comma / ☒ point is used as the decimal separator.				
Name and address of factory (ies): SHINE RING TOYS CO.,LTD. RM 1406 BUILDING 1 ZHIDI PLAZA NO 399 JIASHAN AVENUE JIAXING CHINA				
General product information: 1.The appliance/equipment is "CHILDREN MOTORCYCLE" with models"909" as class III appliance . 2.This report is a toy electrical safety standard and only tests the electrical safety of the samples received. 3. The ambient temperature is 25°C. 4. This product is a CHILDREN MOTORCYCLE that suitable for children of over 3 ages and under 14 years old. 5.The equipment is for indoor use only . 6. Models Difference				
Models	Models	Battery specification	Models	Battery specification
909	1800	12V ,7Ah	168	6V ,4.5Ah
BLF-918	H9002		A608	
BLF-1260S	M511		A008	
BLF-1260L	M1250			
HS5188	N888			
HS6188	N999			
959	N518			
MDO11R15	N5188			

Clause	Testing Items	Assessment
1.	Scope	--
2.	Normative references	--
3.	Terms and definitions	--
4.	General requirement	P
5.	General conditions for tests	P
5.2	Preconditioning	P
5.7.2	Electric toys that are used with batteries	P
6.	Criteria for reduced testing	P
6.1	General	P
6.2	Short-circuit resistance	P
6.3	Low power electric toys	P
6.4	Battery circuits	P
7.	Marking and instructions	P
7.1	General	P
7.2	Markings on electric toys	P
7.2.1	Identification	P
7.2.2	Electric toys with replaceable batteries	P
7.2.3	Transformer toys and power supply toys	N/A
7.2.4	Electric toys with more than one power supply	N/A
7.2.5	Electric toys with detachable lamps	N/A
7.2.6	Symbols	P
7.2.7	Durability	P
7.3	Instructions and markings on packaging	P
7.3.1	General	P
7.3.2	Transformer toys and power supply toys	N/A
7.3.3	Electric toys that are used with replaceable batteries	P
7.3.3.1	General	P
7.3.3.2	Coin batteries	N/A
7.3.3.3	Button batteries	N/A
7.4	Instructions for electric toys that can be connected to class I equipment	N/A
7.5	Instructions for ride-on electric toys	N/A
7.6	Temperature warnings	N/A
8.	Power input	P
9.	Heating and abnormal operation	P
9.1	General	P
9.2	Testing condition	--
9.3	Normal operation	P

9.4	Normal operation with insulation short-circuited	N/A
9.5	Abnormal operation with temperature controls made inoperable	N/A
9.6	Electric toys with accessible moving parts locked	N/A
9.7	Additional transformers and power supplies	N/A
9.8	Abnormal supply to electric toys via a USB connection	N/A
9.9	Fault condition in electronic circuits	P
9.10	Compliance criteria	P
10.	Electric strength	P
10.1	Electric strength at operating temperature	P
10.2	Electric strength under humid conditions	N/A
11.	Electric toys used in water, electric toys used with liquid and electric toys cleaned with liquid	N/A
12.	Mechanical strength	P
12.1	Enclosures	P
12.2	Attachment strength	P
13.	Construction	P
13.1	Nominal supply voltage	P
13.2	Transformers, power supplies and battery chargers	N/A
13.3	Thermal cut-outs	N/A
13.4	Batteries	P
13.4.1	Small batteries	N/A
13.4.2	Other batteries	P
13.4.3	Electrolyte leakage	N/A
13.4.4	Electric toys placed above a child	N/A
13.4.5	Parallel connection of batteries	N/A
13.4.6	Battery compartment fasteners	N/A
13.5	Plug and sockets	N/A
13.6	Charging batteries	N/A
13.7	Series motors	N/A
13.8	Working voltage	P
13.9	Electric toys connecting to other equipment	N/A
13.10	Speed limitation of ride-on electric toys	N/A
14.	Protection of cords and wires	P
14.1	Edges and moving parts	P
14.2	Fixed parts	N/A
15.	Components	P
15.1.1	General	P
15.1.2	Switches and automatic controls	P
15.1.3	Other components	P

15.2	Prohibited components	N/A
15.3	Transformers and power supplies	N/A
15.4	Battery chargers	N/A
15.5	Batteries	P
16.	Screws and connections	P
16.1	Fixings	N/A
16.2	Connections	N/A
17.	Clearances and creepage distances	N/A
18.	Resistance to heat and fire	P
18.1	Resistance to heat	N/A
18.2	Resistance to fire	P
18.2.1	General	P
18.2.2	Non-metallic parts	P
18.2.3	Insulating material	N/A
19.	Radiation and similar hazards	--
19.1	General	P
19.2	Optical radiation	P
19.3	Other electromagnetic radiation	N/A
Annex A	Experimental sets	N/A
Annex B	Needle-flame test	N/A
Annex C	Automatic controls and switches	N/A
Annex D	Electric toys with protective electronic circuits	N/A
Annex E	Safety of Electric Toys incorporating Optical Radiation Sources	N/A
Annex I	Safety of remote-controls for electric ride-on toys	N/A
Annex J	Safety of remote controls for electric ride-on toys	N/A

Tables

Clause 8 Power input

Sample description	Rated power input	Measured power input	Assessment
Normal condition	12	2.883	Use with adapters 110V
Normal condition	12	3.552	Use with adapters 240V
Normal condition	12	12.11	DC input

Test requirement:

The power input of transformer toys shall not exceed the rated power input by more than 20%

Clause 9 Heating and abnormal operation

9.2 The unit was freely suspended during normal operation.

9.2 The unit was placed on the floor of the test corner during normal operation.

9.3 The unit was operated by electricity (at 25.8V) until steady conditions were established.

The maximum temperature rises were recorded as follows:

Ambient temperature (°C):		
Location	Temperature Rise (K)	Limited (K)
Battery compartment	5.4	45
PCB	14.6	105
Motor	8.9	70
Enclosure	3.9	50

9.4 The test of 9.3 is repeated, the insulation between accessible parts of different polarity being short circuited in turn.

The maximum temperature rises were recorded as follows:

Ambient temperature (°C):		
Location	Temperature Rise (K)	Limited (K)
--	--	--
--	--	--
--	--	--

9.8.2 This clause was not applicable since its electronic circuit was a low power circuit. Also the protection against fire hazard or dangerous malfunction in other parts of the toy did not rely on the correct function of the electronic circuit.

Clause 13 Mechanical strength (0.5J)

Sample description	Impact point	Test result	Assessment
Enclosure	the obverse side	No breakdown	PASS
Battery compartment	the obverse side	No breakdown	PASS

Clause 15: Critical components information					P
Object / part No.	Manufacturer/ trademark	Type / model	Technical data	Standard	Mark(s) of conformity ¹⁾
Battery	Interchangeable	Interchangeable	12V 7Ah	EN 62133	CE
Adapter	Interchangeable	Interchangeable	Input: 110-240V~50/60Hz Output: 12Vdc 1A	EN 60335-2-29	CE
Motor	Interchangeable	Interchangeable	12V	--	--
Plastic Enclosure	Interchangeable	Interchangeable	PC,UL94V-0,80°C	UL94	UL
PCB	Interchangeable	Interchangeable	V-0	UL94	UL
Internal wire	Interchangeable	Interchangeable	24AWG	--	--
Supplementary information: ¹⁾ Provided evidence ensures the agreed level of compliance. See OD-CB2039.					

Clause 16 Screws and connections

Sample description	Screw size(mm)	Torque(N·m)	Test result	Assessment
Screw for Battery compartment	1.0mm	0.4	No damage	PASS

16.1	TABLE: Threaded Part Torque Test			N/A
Threaded part identification		Diameter of thread (mm)	Column number (I or II)	Applied torque (Nm)
Supplementary information:				

17	TABLE: Clearance And Creepage Distance Measurements					N/A
clearance cl and creepage distance dcr at/of:	Up (V)	U r.m.s. (V)	Required cl (mm)	cl (mm)	required dcr (mm)	dcr (mm)
--	--	--	--	--	--	--
--	--	--	--	--	--	--

Clause 18.2 Resistance to heat and fire

Glow-wire test (550 ±C)		
Location / Part	Test temperature (°C)	Result Observation
Plastic enclosure	550	No flame, no molten drop

18.1	TABLE: Ball Pressure Test of Thermoplastics			N/A
Allowed impression diameter (mm)		--		--
Object/ Part No./ Material	Manufacturer / trademark	Test temperature (C)	Impression diameter (mm)	
--	--	--	--	
--	--	--	--	
Supplementary information: Working voltage not exceeding 12 V and a current not exceeding 3 A.				

18.2.2	TABLE: Glow Wire Test (GWT)					P
Test Conditions.....:		GWT according to IEC 60695-2-11				--
Test temperature (°C).....:		550 °C				--
Object/ Part No./ Material		Manufacturer/ trademark	te,	ti	Specified Layer under Test Specimen ignited, Yes/No	Other remarks
Plastic enclosure		Interchangeable	0	0	No	--
Battery compartment		Interchangeable	0	0	No	--
Supplementary information:						
18.2.3	TABLE: Glow Wire Test (GWT) / Glow Wire Ignition Temperature (GWIT)					N/A
Test Conditions.....:		GWT according to IEC 60695-2-11				--
Test temperature (°C).....:		650 °C				--
Object/ Part No./ Material		Manufacturer/ trademark	te,	ti	Specified Layer under Test Specimen ignited, Yes/No	Other remarks
--		--	--	--	--	--
--		--	--	--	--	--
Object/ Part No./ Material		Manufacturer/ trademark	GWIT		--	Other remarks
--		--	--		--	--
--		--	--		--	--
Supplementary information: Working voltage not exceeding 12 V and a current not exceeding 3 A.						













909



168



A608



A008



BLF-918



BLF-1260S



BLF-1260L



HS5188



HS6188



959



MD011



R15



1800



H9002



M511



M1250



BD008



BD008



JM3188



N011



N888



N999



N518



N5188

--End of Report--