

TEST REPORT

APPLICANT : Yongkang Turui Import & Export Co.,Ltd

ADDRESS : 2nd Floor, No.47, Laoyayan Village, Jiangnanjiedao,
Yongkang City, Zhejiang Province, China

SAMPLE DESCRIPTION : Roller skates

ITEM NO. : QS8007(QS8001 QS8002 QS8003 QS8004 QS8005
QS8006 QS8007 QS8008 QS8009 QS8010)

COUNTRY OF ORIGIN : China

SAMPLE RECEIVED DATE : 16 - Oct - 2024

TURN AROUND TIME : 16 - Oct - 2024 to 25 - Oct - 2024

The following test item(s) was/were performed on submitted sample(s) and/or component(s) confirmed by applicant

TEST REQUESTED	TEST METHOD/REGULATION	RESULT
Roller sport equipment-Roller skates-Safety requirements and test methods	EN 13899:2003	Pass (except clause 6 and 7)

Samples are obtained by express delivery, Results obtained refer only to samples, products or material received in Laboratory, as described in point related to sample description, and tested in conditions shown in present report. Eurofins Product Testing Service (Hangzhou) Co., Ltd ensures that this job has been performed according to our Quality System and complying contract and legal conditions. Unless otherwise stated from the customer, regulation or the standard specification, Eurofins will consider the measurement uncertainty as calculated by our laboratory and apply according to ILAC G8:09/2019-(binary acceptance base on guard band). If you happen to have any comments, please do it by sending email to info.hz@cpt.eurofinscn.com and referring to this report number. Reproduction of this document is only valid if it is done completely and under the written permission of Eurofins Product Testing Service (Hangzhou) Co., Ltd. If you happen to have any complaints, please do it by sending email to chinacomplaint.hz@cpt.eurofinscn.com and referring to this report number.

Eurofins (Hangzhou) contact information**Customer service:** Zoey.Huang@cpt.eurofinscn.com/ +86 571 87203730**Sales specialist:** John.Zhang@cpt.eurofinscn.com/ +86 15381027188

***** FOR FURTHER DETAILS, PLEASE REFER TO THE FOLLOWING PAGE(S) *****

Signed for and on behalf of
Eurofins Product Testing Service (Hangzhou) Co., Ltd



Sara Liu
Quality Manager



SAMPLE PHOTO(S)



A

EFHZ24102182-CG-01

TO BE CONTINUED

REFERENCE SAMPLE PHOTO



The reference samples have not been tested in current report, but according to customer's request, the pictures has also been included. For sample tested in current report, please refer to "sample photo".

TO BE CONTINUED

TEST RESULT

EN 13899:2003 Roller sport equipment-Roller skates-Safety requirements and test methods

1. Number of Tested Sample: 2 pairs
2. Classification: Class B
3. Test Result:

Clause	Test Method/ Requirement	Result
4.3	safety requirement	
4.3.1	Protruding parts and edges During test, protruding parts shall not touch the outside of the test cylinder and are not shielded in all directions by an adjacent surface of equal height. Whose distance is not more than 25mm from the end of the protruding part All edges on the roller skate which can come into contact with parts of the body during normal use shall be rendered safe, or shaped so that injuries cannot occur	PASS
4.3.2	Binding elements Bindings elements shall prevent unintentional detachment of the roller skate from the shoe even under load compliance with this requirements is accepted when no breakage, disconnection, loosening or detachment occurs in roller skates with permanent binding to the shoe during the test, and in roller skates with detachable binding to the shoe during the test in 5.3.7.1,the roller skate bindings and any bracing shall not break during the bending test in 5.4.1	PASS
4.3.3	displacement safety the safety locking or fastening element shall not become detached or loose compliance with this requirement is accepted when the locking or fastening element do not become detached or loose , and do not break after a frontal collision as in 5.3.8 and after endurance testing as 5.3.10	PASS
4.3.4	Connecting fillet The connecting fillet on the heel of the roller skates shall withstand load encountered Compliance with this requirement is accepted when, after the tests in 5.3.8and 5.3.10 the connecting fillet is neither broken nor is there any apparent permanent deformation 5.4.3 the reduction in ground clearance in the centre is not more than 5%between the axles	PASS
4.3.5	Starting and/or breaking device The starting or braking deice shall be designed so that it is strong and secured against unscrewing after test in 5.3.9, the starting device is neither loosened, deformed ,detached nor showing other signs of functional damage No unscrewing of the starting device is found during the test in 5.3.5 The clearance between the bottom edge of the starting or braking device and the ground shall not be less than 10mm	PASS
4.3.6	Rolling gear During operation the rolling gear shall withstand shock loading continuous loading and static loading, it shall be securely fastened to the shoe plate and secured against unintentional detachment	PASS

TO BE CONTINUED

TEST RESULT

Clause	Test Method/ Requirement	Result
4.3.7	axles the axles shall be designed and fitted so that in operation no axles can become loose displaced or deformed and after test in 5.3.8,5.3.10 and 5.4.2 no axle becomes loose, displaced or so deformed as to impair serviceability and the rollers secured to the axles have not become detached the rolling gear axles including associated components may only protrude by no more than 3mm beyond the outer edges of the wheels, when their ends are rounded with a radius of at least 5mm	PASS
4.3.8	Wheels The coefficients of friction μ^0 are obtained during the test in accordance with 5.3.5 Class A:min0.30 Class B min 0.20 after test in 5.3.10 the wheel shall not have loosened on the bearings to the extent that there is a danger of it sliding off the bearings or shown other signs of functional damage/	PASS
4.3.9	bearing the bearing shall be constructed so that no jamming of the wheels can occur during operation, they shall be designed so that maintenance in accordance with the instruction can be carried out without reducing operation safety, dust protection covers shall not come loose during operation the bearing shall be designed so that they are still serviceable after the endurance test in 5.3.10	PASS
4.3.10	Self-locking nuts and other fixings In the case of self-locking nuts, the entire thread length of the nut and its locking part shall be fully engaged with the bolt, self-locking nuts and other fixings loosened on the numerous occasions for maintenance re-assembly or adjustment procedures shall be suitable for this application the information supplied by the manufacturer shall draw attention to the possible loss of the self –locking action of the nuts and other fixings	PASS
4.3.11	Steering facility when the roller skate has a steering facility, this shall be designed so that with the smallest curve radius and the thereby associated maximum load, no contact can occur between wheels and parts of the roller skate, if the steering is adjustable, the wheels shall touch no parts of the roller skate even at the lowest tension during use, compliance with this requirement is accepted if no contact has been established between wheels and any parts of the roller skate during the test in 5.3.4, Following the endurance test in 5.3.10, no parts of the steering mechanism shall be broken nor have become detached The steering mountings or fastening parts shall be secured against detachment with locking elements	N/A

TO BE CONTINUED

TEST RESULT

Clause	Test Method/ Requirement	Result
6	Marking Each roller skate shall be legibly and durably marked with the following information: a) the number of this European Standard; b) the name, trademark or other means of identification of the manufacturer or retailer; c) means of identification of the model; d) maximum weight limit or indication of the class (A or B). If the weight is not marked this shall be given in the package.	N/C
7	Information supplied by the manufacture 7.1 General Easily understood information supplied by the manufacturer shall be supplied with each pair of roller skaters. This shall ensure that even a novice user will be able to use, handle and maintain the roller skates. Text describing difficult or complicated operations are to be complemented with illustrations. The information shall be supplied together with the recommendation that this information shall be retained by the user for future reference. 7.2 Contents The information supplied by the manufacturer shall contain, in text or picture form, at least the information in accordance with 7.2.1 and 7.2.2: 7.2.1 Information about the construction of the roller skate This information shall contain at least: a) a note to the effect that no modifications shall be made that can impair safety. b) a note indicating, if applicable, that the roller skates do not contain a starting and/or braking device. c) a note indicating when self-locking nuts and other self-locking fixings may lose their effectiveness. 7.2.2 Instructions for use The instructions for use shall contain at least: a) Note concerning limitations of use according to the Road Traffic Act and recommendations regarding or descriptions of suitable surfaces (flat, clean, dry and where possible away from other road users). b) Warning that the user should always wear protective equipment (hand/wrist protection, knee protection, head protection and elbow protection) and reflective devices. c) Instruction to check that the roller skaters steering mechanism, if present, is correctly adjusted and that the connective components are firmly secured. d) Description of the correct techniques for use and for braking. 7.2.3 Servicing and maintenance instructions Clear note stating that regular maintenance enhances the safety of the equipment. This includes: a) note regarding the different properties of the various bearing constructions and their maintenance; b) replacement of wheels and buffers (where possible or present); c) lubrication of the bearings; d) steering adjustment; e) note to remove any sharp edges created through use; f) running checks. 7.2.4 Roller skate's class The class including the explanation in 4.2 is to be stated.	N/C

TO BE CONTINUED

TEST RESULT

Notes:

- (1) N/A=Not applicable;
- (2) N/C=Not conducted due to without information provided.

The test item is testing in Eurofins Internal laboratory.

END OF THE REPORT