



Neo4j

Practice Works

ESILV

nicolas.travers (at) devinci.fr

1	Import your dataset in Neo4j	3
1.1	Dataset	3
1.2	Import CSV and build the graph	3
1.2.1	Create Airport nodes	3
1.2.2	Create Airline nodes	4
1.2.3	Create indexes	4
1.2.4	Create Route nodes	4
2	Cypher: Pattern queries on graphs	5
2.1	Simple queries	5
2.2	Complex queries	7
2.2.1	Hard queries	8
2.3	Execution plan	9
3	Bonus/Hard queries/New features	11
3.1	Add an external library	11
3.1.1	Import library	11
3.1.2	Call the library	11
3.2	Change graph renderer	11

1.1 Dataset


In this practice work we will use the *Airport* dataset (available on DVO/Neo4j/Exercices¹). It an archive composed of 3 CSV files which contains:

- Airport information, even with aerodromes and closed ones,
- Airline (companies) that delivers the routes between airports,
- Routes that connects airports and the airlines.

△ In order to import your dataset, you must put the CSV files in the **\$Neo4j_folder/import** folder (you can also put http URL or full path to the file). Each file will be identified by *"file:/airports.csv"*

1.2 Import CSV and build the graph

First, you must connect to the neo4j browser (usually <http://localhost:7474>) where each query must be put in the query field (top of the UI).



To import a CSV file, you must specify for each column in the header the correspondance in your graph

1.2.1 Create Airport nodes

```
LOAD CSV WITH HEADERS FROM "file:/airports.csv" as l
CREATE (airport:Airport{id:toInteger(l.AirportID), name:l.Name, city:l.City,
country:l.Country, IATA:l.IATA, latitude:toFloat(l.Latitude),
longitude: toFloat(l.Longitude), altitude: toFloat(l.Altitude), TimeZone:l.TZ});
```

The LOAD CSV command put each line in main memory, the mapping is set in the CREATE clause:

¹<https://devinci-online.brightspace.com/d2l/le/content/15379/viewContent/20124/View>

```
CREATE (<var>:<Type>{ <cle>:<colonne du CSV>, ...  })
```

The typed values must be mapped properly with `toInteger` and `toFloat` functions.

1.2.2 Create Airline nodes

Idem for Airline nodes:

```
LOAD CSV WITH HEADERS FROM "file:/airlines.csv" as l
CREATE (airline:Airline{id:toInteger(l.AirlineID), name:l.Name, alias:l.Alias, IATA:l.IATA,
    country:l.Country, active:l.Active});
```

1.2.3 Create indexes

Those two CSV files are pretty small. Thus, we didn't need to put indexes previously. However in the following it is necessary to set them on properties in order to be more efficient while creating routes and relationships.

⚠ Only one instruction (index creation) can be run at a time :

```
CREATE INDEX ON :Airport(id);
CREATE INDEX ON :Airline(id);
CREATE INDEX ON :Route(id);
CREATE INDEX ON :Airport(country);
CREATE INDEX ON :Airport(city);
CREATE INDEX ON :Airport(IATA);
CREATE INDEX ON :Route(name);
```

1.2.4 Create Route nodes

Now we can create `Route`² and *relationships* between `Airports` and `Airlines`. Since we are in a transactional environment (ACID properties) we need to add commits while processing in order to empty the cache and so being more efficient:

```
USING PERIODIC COMMIT 200
LOAD CSV WITH HEADERS FROM "file:/routes.csv" as l
MERGE (airline:Airline{id:toInteger(l.AirlineID)} )
MERGE (source:Airport{id:toInteger(l.SourceAirportID)} )
MERGE (dest:Airport{id:toInteger(l.DestAirportID)} )
CREATE (route:Route{equipment:l.Equipment})
CREATE (route) -[:from]-> (source)
CREATE (route) -[:to]-> (dest)
CREATE (route) -[:by]-> (airline)
```

The `MERGE` clause helps to not create nodes a second time but only extract already build ones.


²In english, a route is given road between two destinations.

Chapter 2

Cypher: Pattern queries on graphs

Cypher is a query language for graphs and helps to define patterns which express nodes and relationships between nodes. To query your database, you can use the web interface embedded in Neo4j: <http://localhost:7474>

Our dataset contains **Aiport**, **Airline** and **Route** nodes. The **Route** connects **Aiport** and **Airline** with directed relationships (*from Route to other nodes*). Every pattern queries must respect this orientations on relationships in order to produce a result. Here a sample of the graph we have in the database:



The queryable properties are:

- Node / **Aiport** : id, name, IATA, country, TimeZone, city, latitude, longitude, altitude
- Node / **Airline** : id, name, country, IATA, alias, active
- Node / **Route** : equipment
- Relationship / Route -[:from]-> Airport
- Relationship / Route -[:to]-> Airport
- Relationship / Route -[:by]-> Airline

2.1 Simple queries

2.1.1 Give French Airports' name and IATA code,

Correction :

```
MATCH (a:Airport{country:"France"})
RETURN a.name, a.IATA
```

2.1.2 Give names and IATA codes of French Airline companies only when the IATA code exists and when it is an active Airline,

Correction :

```
MATCH (a:Airline{country:"France"})
WHERE EXISTS(a.IATA) AND a.active = "Y"
RETURN a.name, a.IATA
```

2.1.3 Names of French Airlines with at least one existing route,

Correction :

```
MATCH (a:Airline{country:"France"}) <-- (r:Route)
RETURN DISTINCT a.name
```

2.1.4 Graph¹ of routes which departure is Charles de Gaulle (CDG),

Correction :

```
MATCH (cdg:Airport{IATA:"CDG"}) <-[f:from]- (r:Route)
RETURN cdg, f, r
```

2.1.5 Graph of routes from CDG delivered by a A380 (equipment),

Correction :

```
MATCH (cdg:Airport{IATA:"CDG"}) <-[f:from]- (r:Route)
WHERE r.equipment CONTAINS "380"
RETURN cdg, f, r
```

2.1.6 Cities and Countries which are the destinations of routes from CDG delivered by an A380,

Correction :

```
MATCH (cdg:Airport{IATA:"CDG"}) <-[:from]- (r:Route) -[:to]-> (dest:Airport)
WHERE r.equipment CONTAINS "380"
RETURN dest.country, dest.city
```

2.1.7 From the previous result, give the corresponding airlines name,

Correction :

```
MATCH (cdg:Airport{IATA:"CDG"}) <-[:from]- (r:Route) -[:to]-> (dest:Airport),
      (r) -[:by]-> (comp)
WHERE r.equipment CONTAINS "380"
RETURN dest.country, dest.city, comp.name
```

2.1.8 Graph of routes from CDG to any French airport,

Correction : We can refer the total path by a variable

```
MATCH p=(:Airport{IATA:"CDG"}) <-- (:Route) --> (:Airport{country:"France"})
RETURN p
```

2.1.9 Graph of all routes delivered by an A380,

Correction :

```
MATCH p=(:Airport) <-- (r:Route) --> (:Airport)
WHERE r.equipment CONTAINS "380"
RETURN p
```

¹give the corresponding nodes and the relationships

Chapter 2. Cypher: Pattern queries on graphs

2.2. Complex queries

2.1.10 Graph of all routes coming from a French airport to British airport (United Kingdom),

Correction :

```
MATCH p=(FR:Airport{country:"France"}) <-[:from]- (r:Route) -[:to]->
      (UK:Airport{country:"United Kingdom"})
RETURN p
```

2.1.11 From previous result, give the distinct list of airline names,

Correction :

```
MATCH (FR:Airport{country:"France"}) <-[:from]- (r:Route) -[:to]->
      (UK:Airport{country:"United Kingdom"}),
      (r) -[:by]-> (comp)
RETURN DISTINCT comp.name
```

2.1.12 Idem, but only for which they are delivered by an A320.

Correction :

```
MATCH (FR:Airport{country:"France"}) <-[:from]- (r:Route) -[:to]->
      (UK:Airport{country:"United Kingdom"}),
      (r) -[:by]-> (comp)
WHERE r.equipment CONTAINS "320"
RETURN DISTINCT comp.name
```

2.2 Complex queries

2.2.1 To make more complex queries, we need first to create homogeneous relationships between airports in order to make "jumps". We will create new relationships which labels are airlines name. For this, use the following queries:

```
MATCH (FROM:Airport) <-[:from]- (r:Route) -[:to]-> (TO:Airport),
      (r) -[:by]-> (comp)
WHERE FROM <> TO
MERGE (FROM)-[:path{airline:comp.name}]-> (TO)
```

```
CREATE INDEX ON :path(airline);
```

2.2.2 Give the graph of paths delivered by "Air France" between all French airports,

Correction :

```
MATCH (from:Airport{country:"France"}) -[p:path{airline:"Air France"}]->
      (to:Airport{country:"France"})
RETURN from, to, p
```

2.2.3 Give per destination country the number of paths delivered by "Air France". Sort the result decreasingly,

Correction :

```
MATCH (from:Airport) -[:path{airline:"Air France"}]-> (to:Airport)
RETURN to.country, count(*) AS NB
ORDER BY NB DESC
```

Chapter 2. Cypher: Pattern queries on graphs

2.2. Complex queries

2.2.4 Idem, but when the path does not come from a French airport,

Correction :

```
MATCH (from:Airport) -[:path{airline:"Air France"}]-> (to)
WHERE from.country <> "France"
RETURN to.country,count(*) AS NB
ORDER BY NB DESC
```

2.2.5 Give paths of lengths 2 or 3 (number of relationships) from *Nantes* to *Salt Lake City*,

Correction :

```
MATCH p=(:Airport{city:"Nantes"}) -[:path*2..3]-> (:Airport{city:"Salt Lake City"})
RETURN p
```

2.2.6 Give the shortest path from *Nantes* to *Salt Lake City*,

Correction :

```
MATCH p=shortestpath( (FROM:Airport{city:"Nantes"}) -[:path*]->
    (TO:Airport{city:"Salt Lake City"}) )
RETURN p;
```

2.2.1 Hard queries

2.2.1 Give paths of lengths 2 or 3 from *Nantes* to *Salt Lake City*, delivered only by "Air France",

Correction :

```
MATCH p=(:Airport{city:"Nantes"}) -[:path*2..3]-> (:Airport{city:"Salt Lake City"})
WHERE ALL(path in relationships(p) WHERE path.airline="Air France")
RETURN p
```

2.2.2 All paths of length 2 from Paris only delivered by "Air France" (without direct flights),

Correction :

```
MATCH p=(paris:Airport{city:"Paris"}) -[:path*2]-> (to:Airport)
WHERE ALL(path in relationships(p) WHERE path.airline="Air France")
AND NOT (paris) -[:path]-> (to)
RETURN p
```

2.2.3 For those destinations, give per country the number of paths sorted decreasingly,

Correction :

```
MATCH p=(paris:Airport{city:"Paris"}) -[:path*2]-> (dest:Airport)
WHERE ALL(path in relationships(p) WHERE path.airline="Air France")
AND NOT EXISTS((paris) -[:path]-> (dest))
RETURN dest.country, COUNT(*) AS NB
ORDER BY NB DESC
```

2.2.4 From question 2.2.2, give only those which stops at least once in the United states,

Correction :


```
MATCH p=(paris:Airport{city:"Paris"}) -[:path*2]-> (dest:Airport)
WHERE ALL(path in relationships(p) WHERE path.airline="Air France")
AND NOT EXISTS((paris) --> (dest))
AND ANY(n in nodes(p) WHERE n.country="United States")
RETURN p
```

2.3 Execution plan

We wish to extract execution plans from each query in order to see if indexes were properly used. To achieve this, prefix your query with "EXPLAIN".


2.3.1 From query 2.2.2 show the corresponding execution plan,

Correction :

```
EXPLAIN
MATCH p=(paris:Airport{city:"Paris"}) -[:path*2]-> (to:Airport)
WHERE ALL(path in relationships(p) WHERE path.airline="Air France")
AND NOT (paris) -[:path]-> (to)
RETURN p
```

In the following plan, we can see:

- On top of the plan a "NodeIndexSeek" which scans the index for Airport nodes with a city label whose value is "Paris".
- Then, all paths with a filter on the airline (\$ means the input value "Air France") with a given path length (here 2)
- The right hand-side of the plan gives the "NOT" filter on direct paths from Paris. This branch ends with the "AntiSemiApply" which corresponds to the "NOT".
- Then, project the output and produces the results.




Chapter 2. Cypher: Pattern queries on graphs

2.3. Execution plan

2.3.2 In the following query, a filter is put either on nodes FR and UK which both refer to the index on countries. From which nodes the execution plan begins? When the other side of the path is dealt?

```
EXPLAIN
MATCH (FR:Airport{country:"France"}) <-[:from]-(r:Route) -[:to]->
      (UK:Airport{country:"United Kingdom"}),
      (r) -[:by]-> (comp)
WHERE r.equipment CONTAINS "320"
RETURN DISTINCT comp.name
```

Correction : We can see that **1)** we begin with the UK node, **2)** expand to the routes node, **3)** filter with "320", **4)** expand to from nodes, **5)** filter them by country name (France), **6)** get companies' name from corresponding patterns, **7)** produce distinct values of companies.



Chapter 3

Bonus/Hard queries/New features

3.1 Add an external library

It is possible to add a Java library in Neo4j which can be called in Cypher.

3.1.1 Import library

To import a package/library in Neo4j, it must be put in the "\$NEO4J_FOLDER/plugins/" folder.¹

Then, you need to configure your Neo4j server in order to integrate the Java Class to be called. The config file is available here: \$NEO4J_FOLDER/conf/neo4j.conf.

Add the following line in "neo4j.conf":

```
dbms.unmanaged_extension_classes=XXXX.extension=/YYYY
```

For which XXXX is the plugin's name and YYYY the running class' name in manifest of the plugin.

3.1.2 Call the library

You can call the library thanks to this command line: CALL XXXX.<function>(<params>).

Here is an example of the RDF reading package.



You can also find:

- Graph algorithms: <https://github.com/neo4j-contrib/neo4j-graph-algorithms/releases>
- NeoSemantics: <https://github.com/jbarrasa/neosemantics>

3.2 Change graph renderer

You can render your graph with your own colors and labels. To achieve this, you need to define a CSS stylesheet, extended with 'grass' information. Use the command line ":style" to apply it. Here is an example:

```
:style node {diameter: 50px;color: #A5ABB6;border-color: #9AA1AC;border-width:
↳ 2px;text-color-internal: #FFFFFF;font-size: 10px;} relationship {color:
↳ #A5ABB6;shaft-width: 1px;font-size: 8px;padding: 3px;text-color-external:
↳ #000000;text-color-internal: #FFFFFF;caption: '<type>';} node.Airport {color:
↳ #FF756E;border-color: #E06760;text-color-internal: #FFFFFF;caption: '{country}
↳ {IATA}';} node.Airline {color: #DE9BF9;border-color: #BF85D6;text-color-internal:
↳ #FFFFFF;caption: '{name}';} node.Route {color: #FB95AF;border-color:
↳ #E0849B;text-color-internal: #FFFFFF;caption: '{equipment}';}
```

△The order between node styles are important since each of them overloads previous styles.

You can edit:

- diameter: nodes size,

¹linux: /var/lib/neo4j, windows: C:
Program Files
Neo4j

Chapter 3. Bonus/Hard queries/New features

3.2. Change graph renderer

- `color/border-color/text-color-internal`: colors,
- `caption`: Nodes/relationships name. Take properties with "`<type>`" or "`{ATTRIBUTE}`".