


Application of CNN - Image segmentation

Numerical Methods for Deep Learning

Image Segmentation

The problem: Given an image $y : R^2 \rightarrow R$ compute probability maps for n_c classes, i.e., for $j = 1, \dots, n_c$

$$P_j : R^2 \rightarrow [0, 1], \quad \sum_{j=1}^{n_c} P_j = 1$$



$P_j(x)$ is the probability of a point x to belong to class j .

Setup of Image Segmentation Problem

- ▶ Use a neural network: original image $\rightarrow n_c$ “images”
- ▶ Output image represents class probabilities for each pixel
- ▶ Loss: average cross entropy for **each pixel**
- ▶ Optimize over network parameters

Simple example: a single layer and linear classification

Image Segmentation with Single-Layer NN

Let $\mathbf{Y}_0 \in \mathbb{R}^{n \times n_f}$ with $n_f = n_1 \cdot n_2 \cdot 3$ ($n_1 \times n_2$ RGB data)

$$\mathbf{Y}_1 = \sigma(\mathbf{K}(\boldsymbol{\theta})\mathbf{Y}_0 + \mathbf{B}\mathbf{b}).$$

Use 2D convolutions for $\mathbf{K}(\boldsymbol{\theta})$ and assume k output channels, i.e.,

$$\mathbf{K} = \begin{pmatrix} \mathbf{K}_{2D}(\boldsymbol{\theta}_{11}) & \mathbf{K}_{2D}(\boldsymbol{\theta}_{12}) & \mathbf{K}_{2D}(\boldsymbol{\theta}_{13}) \\ \mathbf{K}_{2D}(\boldsymbol{\theta}_{21}) & \mathbf{K}_{2D}(\boldsymbol{\theta}_{22}) & \mathbf{K}_{2D}(\boldsymbol{\theta}_{23}) \\ \vdots & \vdots & \vdots \\ \mathbf{K}_{2D}(\boldsymbol{\theta}_{k1}) & \mathbf{K}_{2D}(\boldsymbol{\theta}_{k2}) & \mathbf{K}_{2D}(\boldsymbol{\theta}_{k3}) \end{pmatrix}.$$

Then we have to classify each pixel in \mathbf{Y}_1 using $\mathbf{W} \in \mathbb{R}^{k \times n_c}$. This gives the problem

$$\min_{\mathbf{W}, \mathbf{K}, \mathbf{b}} E(\mathbf{W}\text{reshape}(\mathbf{Y}_1), \mathbf{P}), \quad \mathbf{Y}_1 = \sigma(\mathbf{K}(\boldsymbol{\theta})\mathbf{Y}_0 + \mathbf{B}\mathbf{b})$$

Here $\text{reshape}(\mathbf{Y}_1) \in \mathbb{R}^{(n \cdot n_1 \cdot n_2) \times k}$ and E is our cross entropy

References