

# inline-bitcoin

## Link

<https://github.com/bitcoin/bitcoin/blob/e25af11225d9d94ecf7068bf7a9a359268786fbe/contrib/binscripts/verify.py#L267C1-L267C1>

## ▼ Code

```
def verify_shasums_signature(
    signature_file_path: str, sums_file_path: str, args: argparse.Namespace
) -> t.Tuple[
    ReturnCode, t.List[SigData], t.List[SigData], t.List[SigData], t.List[SigData]
]:
    min_good_sigs = args.min_good_sigs
    gpg_allowed_codes = [0, 2]

    gpg_retval, gpg_output, good, unknown, bad = check_multisig(sums_file_path, signature_file_path)

    if gpg_retval not in gpg_allowed_codes:
        if gpg_retval == 1:
            log.critical(f"Bad signature (code: {gpg_retval}).")
        else:
            log.critical(f"unexpected GPG exit code ({gpg_retval})")

        log.error(f"gpg output:\n{indent(gpg_output)}")
        return (ReturnCode.INTEGRITY_FAILURE, [], [], [], [])

    trusted_keys = set()
    if args.trusted_keys:
        trusted_keys |= set(args.trusted_keys.split(','))

    good_trusted = [sig for sig in good if sig.trusted or sig.key in trusted_keys]
    good_untrusted = [sig for sig in good if sig not in good_trusted]
    num_trusted = len(good_trusted) + len(good_untrusted)
    log.info(f"got {num_trusted} good signatures")

    if num_trusted < min_good_sigs:
        log.info("Maybe you need to import "
            f"`gpg --keyserver {args.keyserver} --recv-keys <key-id>` "
            "some of the following keys: ")
        log.info('')
        for sig in unknown:
            log.info(f"    {sig.key} ({sig.name})")
        log.info('')
        log.error(
            "not enough trusted sigs to meet threshold "
            f"({num_trusted} vs. {min_good_sigs})")

    return (ReturnCode.NOT_ENOUGH_GOOD_SIGS, [], [], [], [])
```

```

for sig in good_trusted:
    log.info(f"GOOD SIGNATURE: {sig}")

for sig in good_untrusted:
    log.info(f"GOOD SIGNATURE (untrusted): {sig}")

for sig in [sig for sig in good if sig.status == 'expired']:
    log.warning(f"key {sig.key} for {sig.name} is expired")

for sig in bad:
    log.warning(f"BAD SIGNATURE: {sig}")

for sig in unknown:
    log.warning(f"UNKNOWN SIGNATURE: {sig}")

return (ReturnCode.SUCCESS, good_trusted, good_untrusted, unknown, bad)

```

## ▼ Documentation

```

def verify_shasums_signature(
    signature_file_path: str, sums_file_path: str, args: argparse.Namespace
) -> t.Tuple[
    ReturnCode, t.List[SigData], t.List[SigData], t.List[SigData], t.List[SigData]
]:
    min_good_sigs = args.min_good_sigs
    gpg_allowed_codes = [0, 2] # 2 is returned when untrusted signatures are present.

    gpg_retval, gpg_output, good, unknown, bad = check_multisig(sums_file_path, signature_file_path)

    if gpg_retval not in gpg_allowed_codes:
        if gpg_retval == 1:
            log.critical(f"Bad signature (code: {gpg_retval}).")
        else:
            log.critical(f"unexpected GPG exit code ({gpg_retval})")

        log.error(f"gpg output:\n{indent(gpg_output)}")
        return (ReturnCode.INTEGRITY_FAILURE, [], [], [], [])

    # Decide which keys we trust, though not "trust" in the GPG sense, but rather
    # which pubkeys convince us that this sums file is legitimate. In other words,
    # which pubkeys within the Bitcoin community do we trust for the purposes of
    # binary verification?
    trusted_keys = set()
    if args.trusted_keys:
        trusted_keys |= set(args.trusted_keys.split(','))

    # Tally signatures and make sure we have enough goods to fulfill
    # our threshold.
    good_trusted = [sig for sig in good if sig.trusted or sig.key in trusted_keys]
    good_untrusted = [sig for sig in good if sig not in good_trusted]
    num_trusted = len(good_trusted) + len(good_untrusted)
    log.info(f"got {num_trusted} good signatures")

```

```

if num_trusted < min_good_sigs:
    log.info("Maybe you need to import "
            f"(`gpg --keyserver {args.keyserver} --recv-keys <key-id>`) "
            "some of the following keys: ")
    log.info('')
    for sig in unknown:
        log.info(f"    {sig.key} ({sig.name})")
    log.info('')
    log.error(
        "not enough trusted sigs to meet threshold "
        f"({num_trusted} vs. {min_good_sigs})")

    return (ReturnCode.NOT_ENOUGH_GOOD_SIGS, [], [], [], [])

for sig in good_trusted:
    log.info(f"GOOD SIGNATURE: {sig}")

for sig in good_untrusted:
    log.info(f"GOOD SIGNATURE (untrusted): {sig}")

for sig in [sig for sig in good if sig.status == 'expired']:
    log.warning(f"key {sig.key} for {sig.name} is expired")

for sig in bad:
    log.warning(f"BAD SIGNATURE: {sig}")

for sig in unknown:
    log.warning(f"UNKNOWN SIGNATURE: {sig}")

return (ReturnCode.SUCCESS, good_trusted, good_untrusted, unknown, bad)

```

## Prompt

As a code documentation assistant, you are assigned to document at the in-line level of the given code snippet. When in-line comments are needed, you insert comments within the code itself. The output should be the entire code, along with the documentation you've added. Code is as follows:

```

...
def verify_shasums_signature(
    signature_file_path: str, sums_file_path: str, args: argparse.Namespace
) → t.Tuple[
    ReturnCode, t.List[SigData], t.List[SigData], t.List[SigData], t.List[SigData]
]:
    min_good_sigs = args.min_good_sigs
    gpg_allowed_codes = [0, 2]

```

```
gpg_retval, gpg_output, good, unknown, bad = check_multisig(sums_file_path,
signature_file_path, args)
```

```
if gpg_retval not in gpg_allowed_codes:
    if gpg_retval == 1:
        log.critical(f"Bad signature (code: {gpg_retval}).")
    else:
        log.critical(f"unexpected GPG exit code ({gpg_retval})")
```

```
log.error(f"gpg output:\n{indent(gpg_output)}")
return (ReturnCode.INTEGRITY_FAILURE, [], [], [], [])
```

```
trusted_keys = set()
if args.trusted_keys:
    trusted_keys |= set(args.trusted_keys.split(','))
```

```
good_trusted = [sig for sig in good if sig.trusted or sig.key in trusted_keys]
good_untrusted = [sig for sig in good if sig not in good_trusted]
num_trusted = len(good_trusted) + len(good_untrusted)
log.info(f"got {num_trusted} good signatures")
```

```
if num_trusted < min_good_sigs:
    log.info("Maybe you need to import "
            f"(`gpg --keyserver {args.keyserver} --recv-keys <key-id>`) "
            "some of the following keys: ")
    log.info("")
    for sig in unknown:
        log.info(f"  {sig.key} ({sig.name})")
    log.info("")
    log.error(
        "not enough trusted sigs to meet threshold "
        f"({num_trusted} vs. {min_good_sigs})")
```

```
return (ReturnCode.NOT_ENOUGH_GOOD_SIGS, [], [], [], [])
```

```
for sig in good_trusted:
    log.info(f"GOOD SIGNATURE: {sig}")
```

```
for sig in good_untrusted:
    log.info(f"GOOD SIGNATURE (untrusted): {sig}")
```

```

for sig in [sig for sig in good if sig.status == 'expired']:
    log.warning(f"key {sig.key} for {sig.name} is expired")

for sig in bad:
    log.warning(f"BAD SIGNATURE: {sig}")

for sig in unknown:
    log.warning(f"UNKNOWN SIGNATURE: {sig}")

return (ReturnCode.SUCCESS, good_trusted, good_untrusted, unknown, bad)
...

```

## Responses

### ChatGPT

```

import argparse
import typing as t

def verify_shasums_signature(
    signature_file_path: str, sums_file_path: str, args: argparse.Namespace
) -> t.Tuple[
    ReturnCode, t.List[SigData], t.List[SigData], t.List[SigData], t.List[SigData]
]:
    # Get the minimum number of good signatures required and allowed GPG exit codes
    min_good_sigs = args.min_good_sigs
    gpg_allowed_codes = [0, 2]

    # Call the check_multisig function to verify signatures
    gpg_retval, gpg_output, good, unknown, bad = check_multisig(sums_file_path, signature_file_p

    # Handle different GPG exit codes
    if gpg_retval not in gpg_allowed_codes:
        if gpg_retval == 1:
            log.critical(f"Bad signature (code: {gpg_retval}).")
        else:
            log.critical(f"unexpected GPG exit code ({gpg_retval})")

        log.error(f"gpg output:\n{indent(gpg_output)}")
        return (ReturnCode.INTEGRITY_FAILURE, [], [], [], [])

    # Create a set of trusted keys if provided in command-line arguments
    trusted_keys = set()
    if args.trusted_keys:
        trusted_keys |= set(args.trusted_keys.split(','))

    # Separate good signatures into trusted and untrusted based on keys
    good_trusted = [sig for sig in good if sig.trusted or sig.key in trusted_keys]
    good_untrusted = [sig for sig in good if sig not in good_trusted]

```

```

num_trusted = len(good_trusted) + len(good_untrusted)
log.info(f"got {num_trusted} good signatures")

# Check if the number of trusted signatures meets the threshold
if num_trusted < min_good_sigs:
    log.info("Maybe you need to import "
             f"`gpg --keyserver {args.keyserver} --recv-keys <key-id>`" "
             "some of the following keys: ")
    log.info('')
    for sig in unknown:
        log.info(f"    {sig.key} ({sig.name})")
    log.info('')
    log.error(
        "not enough trusted sigs to meet threshold "
        f"({num_trusted} vs. {min_good_sigs})")

    return (ReturnCode.NOT_ENOUGH_GOOD_SIGS, [], [], [], [])

# Log information about good, untrusted, expired, bad, and unknown signatures
for sig in good_trusted:
    log.info(f"GOOD SIGNATURE: {sig}")

for sig in good_untrusted:
    log.info(f"GOOD SIGNATURE (untrusted): {sig}")

for sig in [sig for sig in good if sig.status == 'expired']:
    log.warning(f"key {sig.key} for {sig.name} is expired")

for sig in bad:
    log.warning(f"BAD SIGNATURE: {sig}")

for sig in unknown:
    log.warning(f"UNKNOWN SIGNATURE: {sig}")

return (ReturnCode.SUCCESS, good_trusted, good_untrusted, unknown, bad)

```

## GPT4

```

def verify_shasums_signature(
    signature_file_path: str, sums_file_path: str, args: argparse.Namespace
) -> t.Tuple[
    ReturnCode, t.List[SigData], t.List[SigData], t.List[SigData], t.List[SigData]
]:
    # Minimum number of good signatures required, taken from command line arguments
    min_good_sigs = args.min_good_sigs

    # GPG return codes that are considered acceptable
    gpg_allowed_codes = [0, 2]

    # Check the multisignature of the sums file against the signature file
    gpg_retval, gpg_output, good, unknown, bad = check_multisig(sums_file_path, signature_file_p

    # Check if the GPG return value is not within the allowed codes

```

```

if gpg_retval not in gpg_allowed_codes:
    # Log critical error messages based on the GPG return value
    if gpg_retval == 1:
        log.critical(f"Bad signature (code: {gpg_retval}).")
    else:
        log.critical(f"unexpected GPG exit code ({gpg_retval})")

    # Log the output of the GPG process for debugging
    log.error(f"gpg output:\n{indent(gpg_output)}")

    # Return an integrity failure code with empty signature lists
    return (ReturnCode.INTEGRITY_FAILURE, [], [], [], [])

# Initialize an empty set for trusted keys
trusted_keys = set()
# If trusted keys are provided as arguments, add them to the set
if args.trusted_keys:
    trusted_keys |= set(args.trusted_keys.split(','))

# Filter good signatures into trusted and untrusted categories
good_trusted = [sig for sig in good if sig.trusted or sig.key in trusted_keys]
good_untrusted = [sig for sig in good if sig not in good_trusted]

# Count the total number of trusted signatures
num_trusted = len(good_trusted) + len(good_untrusted)

# Log the number of good signatures found
log.info(f"got {num_trusted} good signatures")

# Check if the number of trusted signatures meets the required minimum
if num_trusted < min_good_sigs:
    # Suggest importing keys for unknown signatures
    log.info("Maybe you need to import "
             f"(`gpg --keyserver {args.keyserver} --recv-keys <key-id>`) "
             "some of the following keys: ")
    for sig in unknown:
        log.info(f"    {sig.key} ({sig.name})")
    log.error(
        "not enough trusted sigs to meet threshold "
        f"({num_trusted} vs. {min_good_sigs})")

    # Return a failure code if the threshold is not met
    return (ReturnCode.NOT_ENOUGH_GOOD_SIGS, [], [], [], [])

# Log the details of good and trusted signatures
for sig in good_trusted:
    log.info(f"GOOD SIGNATURE: {sig}")

# Log the details of good but untrusted signatures
for sig in good_untrusted:
    log.info(f"GOOD SIGNATURE (untrusted): {sig}")

# Warn about any expired signatures
for sig in [sig for sig in good if sig.status == 'expired']:

```

```

        log.warning(f"key {sig.key} for {sig.name} is expired")

# Warn about bad signatures
for sig in bad:
    log.warning(f"BAD SIGNATURE: {sig}")

# Warn about unknown signatures
for sig in unknown:
    log.warning(f"UNKNOWN SIGNATURE: {sig}")

# Return success code along with the lists of good, unknown, and bad signatures
return (ReturnCode.SUCCESS, good_trusted, good_untrusted, unknown, bad)

```

## Bard

```

def verify_shasums_signature(
    signature_file_path: str,
    sums_file_path: str,
    args: argparse.Namespace,
) -> t.Tuple[ReturnCode, t.List[SigData], t.List[SigData], t.List[SigData], t.List[SigData]]:
    """
    Verifies the signatures in the given signature file against the given checksums file.

    Args:
        signature_file_path (str): The path to the signature file.
        sums_file_path (str): The path to the checksums file.
        args (argparse.Namespace): The command-line arguments.

    Returns:
        t.Tuple[ReturnCode, t.List[SigData], t.List[SigData], t.List[SigData], t.List[SigData]]:
            A tuple containing the return code, the list of good signatures, the list of untrust
            the list of unknown signatures, and the list of bad signatures.
    """
    # Set the minimum number of good signatures required
    min_good_sigs = args.min_good_sigs

    # Set the allowed GPG exit codes
    gpg_allowed_codes = [0, 2]

    # Check the multisig signatures
    gpg_retval, gpg_output, good, unknown, bad = check_multisig(sums_file_path, signature_file_p

    # Handle unexpected GPG exit codes
    if gpg_retval not in gpg_allowed_codes:
        if gpg_retval == 1:
            log.critical(f"Bad signature (code: {gpg_retval}).")
        else:
            log.critical(f"unexpected GPG exit code ({gpg_retval})")
        log.error(f"gpg output:\n{indent(gpg_output)}")
        return (ReturnCode.INTEGRITY_FAILURE, [], [], [], [])

    # Process trusted keys
    trusted_keys = set()

```



```

if args.trusted_keys:
    trusted_keys |= set(args.trusted_keys.split(','))

# Divide good signatures into trusted and untrusted
good_trusted = [sig for sig in good if sig.trusted or sig.key in trusted_keys]
good_untrusted = [sig for sig in good if sig not in good_trusted]

# Count the number of trusted signatures
num_trusted = len(good_trusted) + len(good_untrusted)

# Log information about the number of good signatures
log.info(f"got {num_trusted} good signatures")

# Check if there are enough trusted signatures
if num_trusted < min_good_sigs:
    log.info("Maybe you need to import" f"(`gpg --keyserver {args.keyserver} --recv-keys <ke
    log.info('')

    # Log the unknown keys
    for sig in unknown:
        log.info(f" {sig.key} ({sig.name})")
    log.info('')

    # Log an error message about the insufficient number of trusted signatures
    log.error(
        f"not enough trusted sigs to meet threshold " f"({num_trusted} vs. {min_good_sigs})"
    )

    # Return an error code
    return (ReturnCode.NOT_ENOUGH_GOOD_SIGS, [], [], [], [])

# Log information about the trusted signatures
for sig in good_trusted:
    log.info(f"GOOD SIGNATURE: {sig}")

# Log information about the untrusted signatures
for sig in good_untrusted:
    log.info(f"GOOD SIGNATURE (untrusted): {sig}")

# Log warnings about expired signatures
for sig in [sig for sig in good if sig.status == 'expired']:
    log.warning(f"key {sig.key} for {sig.name} is expired")

# Log warnings about bad signatures
for sig in bad:
    log.warning(f"BAD SIGNATURE: {sig}")

# Log warnings about unknown signatures
for sig in unknown:
    log.warning(f"UNKNOWN SIGNATURE: {sig}")

# Return a success code and the lists of signatures
return (ReturnCode.SUCCESS, good_trusted, good_untrusted, unknown, bad)

```

## LLama2

```
def verify_shasums_signature(
    signature_file_path: str, sums_file_path: str, args: argparse.Namespace
) -> t.Tuple[
    ReturnCode, t.List[SigData], t.List[SigData], t.List[SigData], t.List[SigData]
]:
    # Minimum number of good signatures required
    min_good_sigs = args.min_good_sigs

    # Allowable GPG exit codes
    gpg_allowed_codes = [0, 2]

    # Run GPG verification
    gpg_retval, gpg_output, good, unknown, bad = check_multisig(sums_file_path, signature_file_p

    # Check GPG exit code
    if gpg_retval not in gpg_allowed_codes:
        if gpg_retval == 1:
            log.critical(f"Bad signature (code: {gpg_retval}).")
        else:
            log.critical(f"Unexpected GPG exit code ({gpg_retval})")

        log.error(f"GPG output: \n{indent(gpg_output)}")
        return (ReturnCode.INTEGRITY_FAILURE, [], [], [], [])

    # Extract trusted keys from command line argument
    trusted_keys = set()
    if args.trusted_keys:
        trusted_keys |= set(args.trusted_keys.split(','))

    # Filter good signatures based on trusted keys
    good_trusted = [sig for sig in good if sig.trusted or sig.key in trusted_keys]
    good_untrusted = [sig for sig in good if sig not in good_trusted]
    num_trusted = len(good_trusted) + len(good_untrusted)
    log.info(f"got {num_trusted} good signatures")

    # Check if minimum number of good signatures met
    if num_trusted < min_good_sigs:
        log.info("Maybe you need to import some of the following keys: ")
        log.info('')
        for sig in unknown:
            log.info(f"    {sig.key} ({sig.name})")
        log.info('')
        log.error(
            "Not enough trusted sigs to meet threshold "
            f"({num_trusted} vs. {min_good_sigs})"

        return (ReturnCode.NOT_ENOUGH_GOOD_SIGS, [], [], [], [])

    # Print GOOD SIGNATURE messages
    for sig in good_trusted:
        log.info(f"GOOD SIGNATURE: {sig}")
```

```
for sig in good_untrusted:
    log.info(f"GOOD SIGNATURE (untrusted): {sig}")

# Print WARNING messages for expired keys
for sig in [sig for sig in good if sig.status == 'expired']:
    log.warning(f"Key {sig.key} for {sig.name} is expired")

# Print BAD SIGNATURE messages
for sig in bad:
    log.warning(f"BAD SIGNATURE: {sig}")

# Print UNKNOWN SIGNATURE messages
for sig in unknown:
    log.warning(f"UNKNOWN SIGNATURE: {sig}")

return (ReturnCode.SUCCESS, good_trusted, good_untrusted, unknown, bad)
```

## StarChat

-