

# inline-basic\_association.py

## Link

| <https://github.com/sqlalchemy/sqlalchemy/blob/8503dc2e948908199cd8ba4e6b1d1ddcf92f402>

## ▼ Code

```
class OrderItem(Base):
    __tablename__ = "orderitem"
    order_id = Column(Integer, ForeignKey("order.order_id"), primary_key=True)
    item_id = Column(Integer, ForeignKey("item.item_id"), primary_key=True)
    price = Column(Float, nullable=False)

    def __init__(self, item, price=None):
        self.item = item
        self.price = price or item.price

    item = relationship(Item, lazy="joined")

if __name__ == "__main__":
    engine = create_engine("sqlite://")
    Base.metadata.create_all(engine)

    session = Session(engine)

    tshirt, mug, hat, crowbar = (
        Item("SA T-Shirt", 10.99),
        Item("SA Mug", 6.50),
        Item("SA Hat", 8.99),
        Item("MySQL Crowbar", 16.99),
    )
    session.add_all([tshirt, mug, hat, crowbar])
    session.commit()

    order = Order("john smith")

    order.order_items.append(OrderItem(mug))
    order.order_items.append(OrderItem(crowbar, 10.99))
    order.order_items.append(OrderItem(hat))
    session.add(order)
    session.commit()

    order = session.query(Order).filter_by(customer_name="john smith").one()
    print(
        [
            (order_item.item.description, order_item.price)
            for order_item in order.order_items
        ]
    )
```

```

q = session.query(Order).join("order_items", "item")
q = q.filter(
    and_(Item.description == "MySQL Crowbar", Item.price > OrderItem.price)
)

print([order.customer_name for order in q])

```

## ▼ Documentation

```

class OrderItem(Base):
    __tablename__ = "orderitem"
    order_id = Column(Integer, ForeignKey("order.order_id"), primary_key=True)
    item_id = Column(Integer, ForeignKey("item.item_id"), primary_key=True)
    price = Column(Float, nullable=False)

    def __init__(self, item, price=None):
        self.item = item
        self.price = price or item.price

    item = relationship(Item, lazy="joined")

if __name__ == "__main__":
    engine = create_engine("sqlite://")
    Base.metadata.create_all(engine)

    session = Session(engine)

    # create catalog
    tshirt, mug, hat, crowbar = (
        Item("SA T-Shirt", 10.99),
        Item("SA Mug", 6.50),
        Item("SA Hat", 8.99),
        Item("MySQL Crowbar", 16.99),
    )
    session.add_all([tshirt, mug, hat, crowbar])
    session.commit()

    # create an order
    order = Order("john smith")

    # add three OrderItem associations to the Order and save
    order.order_items.append(OrderItem(mug))
    order.order_items.append(OrderItem(crowbar, 10.99))
    order.order_items.append(OrderItem(hat))
    session.add(order)
    session.commit()

    # query the order, print items
    order = session.query(Order).filter_by(customer_name="john smith").one()
    print(

```

```

        [
            (order_item.item.description, order_item.price)
            for order_item in order.order_items
        ]
    )

    # print customers who bought 'MySQL Crowbar' on sale
    q = session.query(Order).join("order_items", "item")
    q = q.filter(
        and_(Item.description == "MySQL Crowbar", Item.price > OrderItem.price)
    )

    print([order.customer_name for order in q

```

## Prompt

As a code documentation assistant, you are assigned to document at the in-line level. When in-line comments are needed, your task is to insert comments within the code itself. The output should be the entire code along with the documentation you've added.

The code is as follows:

```

"""
class OrderItem(Base):
    __tablename__ = "orderitem"
    order_id = Column(Integer, ForeignKey("order.order_id"), primary_key=True)
    item_id = Column(Integer, ForeignKey("item.item_id"), primary_key=True)
    price = Column(Float, nullable=False)

    def __init__(self, item, price=None):
        self.item = item
        self.price = price or item.price

    item = relationship(Item, lazy="joined")

if __name__ == "__main__":
    engine = create_engine("sqlite://")
    Base.metadata.create_all(engine)

    session = Session(engine)

    tshirt, mug, hat, crowbar = (
        Item("SA T-Shirt", 10.99),
        Item("SA Mug", 6.50),

```

```

        Item("SA Hat", 8.99),
        Item("MySQL Crowbar", 16.99),
    )
    session.add_all([tshirt, mug, hat, crowbar])
    session.commit()

    order = Order("john smith")

    order.order_items.append(OrderItem(mug))
    order.order_items.append(OrderItem(crowbar, 10.99))
    order.order_items.append(OrderItem(hat))
    session.add(order)
    session.commit()

    order = session.query(Order).filter_by(customer_name="john smith").one()
    print(
        [
            (order_item.item.description, order_item.price)
            for order_item in order.order_items
        ]
    )

    q = session.query(Order).join("order_items", "item")
    q = q.filter(
        and_(Item.description == "MySQL Crowbar", Item.price > OrderItem.price)
    )

    print([order.customer_name for order in q])
"""

```

## Responses

### ChatGPT

```

# Import necessary libraries
from sqlalchemy import Column, Integer, Float, ForeignKey, create_engine, and_
from sqlalchemy.orm import relationship, Session
from sqlalchemy.ext.declarative import declarative_base

# Create a base class for declarative models
Base = declarative_base()

# Define the OrderItem class
class OrderItem(Base):

```

```

# Define the table name
__tablename__ = "orderitem"
# Define columns with their data types and relationships
order_id = Column(Integer, ForeignKey("order.order_id"), primary_key=True)
item_id = Column(Integer, ForeignKey("item.item_id"), primary_key=True)
price = Column(Float, nullable=False)

# Constructor to initialize an OrderItem instance
def __init__(self, item, price=None):
    self.item = item
    self.price = price or item.price

# Define a relationship with the Item class
item = relationship(Item, lazy="joined")

# Check if the script is run as the main program
if __name__ == "__main__":
    # Create a SQLite database engine
    engine = create_engine("sqlite://")
    # Create tables in the database based on the defined models
    Base.metadata.create_all(engine)

    # Create a session to interact with the database
    session = Session(engine)

    # Create instances of Item objects
    tshirt, mug, hat, crowbar = (
        Item("SA T-Shirt", 10.99),
        Item("SA Mug", 6.50),
        Item("SA Hat", 8.99),
        Item("MySQL Crowbar", 16.99),
    )

    # Add the Item instances to the session and commit changes to the database
    session.add_all([tshirt, mug, hat, crowbar])
    session.commit()

    # Create an Order instance
    order = Order("john smith")

    # Add OrderItem instances to the Order
    order.order_items.append(OrderItem(mug))
    order.order_items.append(OrderItem(crowbar, 10.99))
    order.order_items.append(OrderItem(hat))

    # Add the Order to the session and commit changes
    session.add(order)
    session.commit()

    # Query the database to retrieve the customer's order items
    order = session.query(Order).filter_by(customer_name="john smith").one()
    print(
        [
            (order_item.item.description, order_item.price)

```

```

        for order_item in order.order_items
    ]
)

# Query the database to find orders with specific criteria
q = session.query(Order).join("order_items", "item")
q = q.filter(
    and_(Item.description == "MySQL Crowbar", Item.price > OrderItem.price)
)

# Print the customer names for the matching orders
print([order.customer_name for order in q])

```

## GPT4

```

# Import necessary modules and classes
from sqlalchemy import create_engine, Column, Integer, Float, ForeignKey
from sqlalchemy.orm import relationship, Session
from sqlalchemy.ext.declarative import declarative_base

# Define base model for SQLAlchemy ORM
Base = declarative_base()

# Define the OrderItem class representing items in an order
class OrderItem(Base):
    __tablename__ = "orderitem" # Set the table name for the OrderItem model

    # Define columns for the table
    order_id = Column(Integer, ForeignKey("order.order_id"), primary_key=True) # Order ID as a
    item_id = Column(Integer, ForeignKey("item.item_id"), primary_key=True) # Item ID as a pr
    price = Column(Float, nullable=False) # Price of the item, must be provided (non-nullable)

    def __init__(self, item, price=None):
        # Constructor for creating an OrderItem instance
        self.item = item # Set the item for the order item
        self.price = price or item.price # Set the price, defaulting to the item's price if not

    # Establish a relationship with the Item model for easy data retrieval
    item = relationship(Item, lazy="joined")

# Main execution block
if __name__ == "__main__":
    # Database setup and initialization
    engine = create_engine("sqlite://") # Create an in-memory SQLite database
    Base.metadata.create_all(engine) # Create all tables in the database

    # Create a new session for database operations
    session = Session(engine)

    # Create item instances
    tshirt, mug, hat, crowbar = (
        Item("SA T-Shirt", 10.99),
        Item("SA Mug", 6.50),

```

```

        Item("SA Hat", 8.99),
        Item("MySQL Crowbar", 16.99),
    )

    # Add created items to the session and commit to the database
    session.add_all([tshirt, mug, hat, crowbar])
    session.commit()

    # Create an order instance for the customer 'john smith'
    order = Order("john smith")

    # Append items to the order
    order.order_items.append(OrderItem(mug))
    order.order_items.append(OrderItem(crowbar, 10.99))
    order.order_items.append(OrderItem(hat))

    # Add the order to the session and commit to the database
    session.add(order)
    session.commit()

    # Query the database for the order placed by 'john smith' and print details
    order = session.query(Order).filter_by(customer_name="john smith").one()
    print(
        [
            (order_item.item.description, order_item.price)
            for order_item in order.order_items
        ]
    )

    # Advanced query to find orders where the item 'MySQL Crowbar' was sold for less than its li
    q = session.query(Order).join("order_items", "item")
    q = q.filter(
        and_(Item.description == "MySQL Crowbar", Item.price > OrderItem.price)
    )

    # Print the names of customers who bought 'MySQL Crowbar' for less than its listed price
    print([order.customer_name for order in q])

```

## Bard

Unable to produce a tangible output for the same prompt

## LLama2

```

# Define a class `OrderItem` that inherits from `Base`
class OrderItem(Base):
    # Set the table name to "orderitem"
    __tablename__ = "orderitem"

    # Define columns:
    # - order_id (integer, foreign key referencing "order.order_id", primary key)
    # - item_id (integer, foreign key referencing "item.item_id", primary key)
    # - price (float, non-nullable)

```

```

order_id = Column(Integer, ForeignKey("order.order_id"), primary_key=True)
item_id = Column(Integer, ForeignKey("item.item_id"), primary_key=True)
price = Column(Float, nullable=False)

# Initialize instance variables
def __init__(self, item, price=None):
    # Initialize instance variable 'item'
    self.item = item

    # If 'price' argument is not provided, set it to the item's price
    self.price = price or item.price

# Define a relationship between OrderItem and Item
item = relationship(Item, lazy="joined")

# Create an engine and create all tables
if __name__ == "__main__":
    engine = create_engine("sqlite://")
    Base.metadata.create_all(engine)

# Create a session using the engine
session = Session(engine)

# Add some items to the database
tshirt, mug, hat, crowbar = (
    Item("SA T-Shirt", 10.99),
    Item("SA Mug", 6.50),
    Item("SA Hat", 8.99),
    Item("MySQL Crowbar", 16.99),
)
session.add_all([tshirt, mug, hat, crowbar])
session.commit()

# Create an order and add some order items to it
order = Order("john smith")
order.order_items.append(OrderItem(mug))
order.order_items.append(OrderItem(crowbar, 10.99))
order.order_items.append(OrderItem(hat))
session.add(order)
session.commit()

# Query the database to retrieve an order and its items
order = session.query(Order).filter_by(customer_name="john smith").one()
print(
    [
        (order_item.item.description, order_item.price)
        for order_item in order.order_items
    ]
)

# Join orders and items on the order items table
q = session.query(Order).join("order_items", "item")

# Filter the results based on item description and price

```



```

q = q.filter(
    and_(Item.description == "MySQL Crowbar", Item.price > OrderItem.price)
)

# Print the customer names of the matching orders
print([order.customer_name for order in q])

```

## StarChat

```

# models.py
from sqlalchemy import Column, Integer, String, Float, ForeignKey
from sqlalchemy.orm import relationship
from sqlalchemy.ext.declarative import declarative_base
import decimal

Base = declarative_base()

class Item(Base):
    __tablename__ = 'item'

    item_id = Column(Integer, primary_key=True)
    description = Column(String(200), nullable=False)
    price = Column(Float, nullable=False)

    def __repr__(self):
        return f"<Item(item_id={self.item_id}, description='{self.description}', price={self.price}"

class Order(Base):
    __tablename__ = "order"

    order_id = Column(Integer, primary_key=True)
    customer_name = Column(String(80), nullable=False)
    shipping_address = Column(String(200))
    billing_address = Column(String(200))
    total = Column(Float, default=decimal.Decimal('0'), nullable=False)

    def __repr__(self):
        return f"<Order(order_id={self.order_id}, customer_name='{self.customer_name}')>"

class OrderItem(Base):
    __tablename__ = "orderitem"
    order_id = Column(Integer, ForeignKey("order.order_id"), primary_key=True)
    item_id = Column(Integer, ForeignKey("item.item_id"), primary_key=True)
    price = Column(Float, nullable=False)

    def __init__(self, item, price=None):
        self.item = item
        self.price = price or item.price

    item = relationship(Item, lazy="joined")

```

```
# main.py
from models import *
from sqlalchemy import create_engine
from sqlalchemy.orm import Session

engine = create_engine("sqlite:///catalog.db")
Base.metadata.create_all(engine)
session = Session(bind=engine)

# Create some test data
tshirt, mug, hat, crowbar = (
    Item("SA T-Shirt", 10.99),
    Item("SA Mug", 6.50),
    Item("SA Hat", 8.99),
    Item("MySQL```")
```