

# file:dict\_of\_sets\_with\_default.py

## Link

[sqlalchemy/examples/association/dict\\_of\\_sets\\_with\\_default.py](#)  
[at 8503dc2e948908199cd8ba4e6b1d1ddcf92f4020 ·](#)  
[sqlalchemy/sqlalchemy · GitHub](#)

## ▼ Code

```
import operator

from sqlalchemy import Column
from sqlalchemy import create_engine
from sqlalchemy import ForeignKey
from sqlalchemy import Integer
from sqlalchemy import String
from sqlalchemy.ext.associationproxy import association_proxy
from sqlalchemy.ext.declarative import declarative_base
from sqlalchemy.orm import relationship
from sqlalchemy.orm import Session
from sqlalchemy.orm.collections import KeyFuncDict

class Base:
    id = Column(Integer, primary_key=True)

Base = declarative_base(cls=Base)

class GenDefaultCollection(KeyFuncDict):
```

```

def __missing__(self, key):
    self[key] = b = B(key)
    return b

class A(Base):
    __tablename__ = "a"
    associations = relationship(
        "B",
        collection_class=lambda: GenDefaultCollection(
            operator.attrgetter("key")
        ),
    )

    collections = association_proxy("associations", "values")
    """Bridge the association from 'associations' over to the
    association proxy of B.
    """

class B(Base):
    __tablename__ = "b"
    a_id = Column(Integer, ForeignKey("a.id"), nullable=False)
    elements = relationship("C", collection_class=set)
    key = Column(String)

    values = association_proxy("elements", "value")
    """Bridge the association from 'elements' over to the
    'value' element of C."""

    def __init__(self, key, values=None):
        self.key = key
        if values:
            self.values = values

```

```

class C(Base):
    __tablename__ = "c"
    b_id = Column(Integer, ForeignKey("b.id"), nullable=False)
    value = Column(Integer)

    def __init__(self, value):
        self.value = value

if __name__ == "__main__":
    engine = create_engine("sqlite://", echo=True)
    Base.metadata.create_all(engine)
    session = Session(engine)

    # only "A" is referenced explicitly. Using "collections"
    # we deal with a dict of key/sets of integers directly.

    session.add_all([A(collections={"1": {1, 2, 3}})])
    session.commit()

    a1 = session.query(A).first()
    print(a1.collections["1"])
    a1.collections["1"].add(4)
    session.commit()

    a1.collections["2"].update([7, 8, 9])
    session.commit()

    print(a1.collections["2"])

```

## ▼ Documentation

```

"""An advanced association proxy example which
illustrates nesting of association proxies to produce multi-1
collections, in this case a dictionary with string keys and s

```

```
as values, which conceal the underlying mapped classes.
```

```
This is a three table model which represents a parent table r  
dictionary of string keys and sets as values, where each set  
collection of integers. The association proxy extension is us  
details of this persistence. The dictionary also generates ne  
upon access of a non-existent key, in the same manner as Pyth  
"collections.defaultdict" object.
```

```
"""
```

---

## Prompt

As a code documentation assistant, you are responsible for documenting at the file/script level. When provided a file level code, your approach involves generating a header comment to be added at the top of the file. This comment should be the documentation for the code and include all relevant information needed to understand or use the script. The code is provided below.

---

## Responses

### ChatGPT

```
"""
```

```
File-level Documentation
```

```
This script defines three SQLAlchemy models: A, B, and C, and de
```

#### Classes:

- Base: The base class for all models, with a primary key 'id'.
- A: Represents a model 'a' with a relationship to model 'B'.
- B: Represents a model 'b' with a relationship to model 'C'.
- C: Represents a model 'c' with an 'Integer' value.

#### Dependencies:

- SQLAlchemy: The script depends on SQLAlchemy for defining and

#### Usage:

1. The script creates an SQLite database using 'create\_engine'.
2. It defines three models 'A', 'B', and 'C', and establishes relationships.
3. The script demonstrates how to add, query, and modify data in the database.

Note: This script serves as an example and may need modification for specific use cases.

Author: [Your Name]

Date: [Date]

"""

## GPT4

"""

File: sqlalchemy\_association\_proxy\_example.py

This script demonstrates the use of SQLAlchemy for ORM (Object-Relational Mapping). It showcases the creation and manipulation of database tables using declarative classes, association proxy, and relationship handling.

#### Key Features:

- Declarative Base: Defines the base class for declarative classes.
- Association Proxy: Utilizes the `association\_proxy` feature for
- Custom Collection Class: Implements `GenDefaultCollection` to
- Relationship Mapping: Establishes relationships between different

- Session Handling: Demonstrates the creation of a session and

#### Models:

- A: Represents a table 'a' with a relationship to 'B' and uses
- B: Represents a table 'b' with a foreign key relationship to
- C: Represents a table 'c' with a foreign key relationship to

#### Usage:

The script is executed as a standalone program. It creates an in adding and retrieving data using SQLAlchemy's session management with SQLAlchemy and should be adapted for practical applications:

#### Dependencies:

- SQLAlchemy: A Python SQL toolkit and Object-Relational Mapping
- ```
"""
```

## Bard

```
"""
```

This code demonstrates how to use association proxies to create

#### ## Setting up the Database

The code starts by importing the necessary modules from SQLAlchemy

The ``create_engine()`` function is then used to create a new SQLA

The ``Base.metadata.create_all(engine)`` method is called to creat

#### ## Defining the Classes

The code defines three classes: ``A``, ``B``, and ``C``. These classe

The ``A`` class has a many-to-many relationship with the ``B`` clas

The `B` class has a many-to-many relationship with the `C` class.

The `key` column in the `B` table is used to create a unique key.

### ## Working with the Classes

The code creates a new instance of the `A` class and adds it to the session.

The code then queries the session for the `A` instance and prints its value.

Finally, the code updates the set for the key `2` with the value `1`.

### ## Association Proxies

Association proxies are a way to create a virtual relationship between two classes.

### ## Conclusion

This code demonstrates how to use association proxies to create a virtual relationship between two classes.

## LLama2

```
# File: sqla_example.py
# Description: Example usage of SQLAlchemy ORM and declarative model
# Author: Your Name
```

```
# Import necessary libraries
```

```
from sqlalchemy import (
```

```
    Column,
```

```
    create_engine,
```

```
    ForeignKey,
```

```
    Integer,
```

```
    String,
```

```
    association_proxy,
```

```

        declarative_base,
        relationship,
        Session,
        KeyFuncDict,
    )

# Define base class with integer ID column and primary key
class Base:
    id = Column(Integer, primary_key=True)

# Create declarative base using Base class
Base = declarative_base(cls=Base)

# Define dictionary-like collection class with missing item handling
class GenDefaultCollection(KeyFuncDict):
    def __missing__(self, key):
        self[key] = b = B(key)
        return b

# Define class A with tablename "a" and relationships to classes B and C
class A(Base):
    __tablename__ = "a"
    associations = relationship(
        "B",
        collection_class=lambda: GenDefaultCollection(
            operator.attrgetter("key")
        ),
    )
    collections = association_proxy("associations", "values")
    """Bridge the association from 'associations' over to the 'values'
    association proxy of B."""

# Define class B with tablename "b" and relationships to class A and C
class B(Base):
    __tablename__ = "b"
    a_id = Column(Integer, ForeignKey("a.id"), nullable=False)

```



```

elements = relationship("C", collection_class=set)
key = Column(String)
values = association_proxy("elements", "value")
"""Bridge the association from 'elements' over to the
'value' element of C."""

def __init__(self, key, values=None):
    self.key = key
    if values:
        self.values = values

# Define class C with tablename "c" and relationship to class B
class C(Base):
    __tablename__ = "c"
    b_id = Column(Integer, ForeignKey("b.id"), nullable=False)
    value = Column(Integer)

    def __init__(self, value):
        self.value = value

# If this file is run as main, create database connection and a
if __name__ == "__main__":
    engine = create_engine("sqlite://", echo=True)
    Base.metadata.create_all(engine)
    session = Session(engine)

    # Add data to table A using collections attribute
    session.add_all([A(collections={"1": {1, 2, 3}})])
    session.commit()

    # Retrieve data from table A and print associated collection
    a1 = session.query(A).first()
    print(a1.collections["1"])

    # Modify associated collection for a1
    a1.collections["1"].add(4)

```

```
session.commit()

# Update associated collection for a1
a1.collections["2"].update([7, 8, 9])
session.commit()

# Print updated associated collection for a1
print(a1.collections["2"])
```

## StarChat

```
"""
```

This module demonstrates how to implement custom collections in  
It also shows off some other features like Association Proxies v  
The specific implementation details may not apply to most projec