

```

package rooms;

import java.util.ArrayList;
import java.util.Random;

public class RoomTester {

    private static Random rand = new Random();

    public static Room randomRoom(boolean validRoom) {
        Room r = null;
        if (validRoom) {
            int rnum = rand.nextInt(1000 - 100) + 100;
            //try a random number until we get a good one.
            //isValidRoomNo is a static method. We can call from outside
            // as long as it is not private
            while(Room.isValidRoomNo(rnum) == false){
                rnum = rand.nextInt(1000 - 100) + 100;
            }
            r = new Room(rnum, "single", false);
        }
        return r;
    }

    public static void printAll(ArrayList<Room> arr) {
        for (int i = 0; i < arr.size(); i++) {
            if(arr.get(i)!=null){
                System.out.println(arr.get(i));
            }else{
                System.out.println("null");
            }
        }
    }

    public static void printHotel(ArrayList<Room> arr) {
        for (int i = 0; i < arr.size(); i++) {
            if(arr.get(i)!=null){
                arr.get(i).showRoom();
            }
        }
        System.out.println();
    }

    public static void main(String[] args) {

        ArrayList<Room> hotel = new ArrayList<Room>();

        for (int i = 0; i < 4; i++) {
            hotel.add(randomRoom(true));
        }

        printAll(hotel);

        boolean randbool = false;
        if (rand.nextInt(6) > 3) {
            randbool = true;
        }

        hotel.add(randomRoom(randbool));
    }
}

```

```
        System.out.println(Room.getCount() + " rooms are created");

        boolean done = false;
        for (int i = hotel.size() - 1; i >= 0 && !done; i--) {
            if (hotel.get(i) != null) {
                hotel.get(i).setRoomType("single");
                done = true;
            }
        }

        printHotel(hotel);
    } // end of main
} // end of class
```