

v1.0.0 OAS 3.0.0

Cal ID API

 API Support  MIT

Download OpenAPI Document

API documentation for external developers integrating with Cal ID. This documentation is auto-generated from our OpenAPI specification and includes details on all available endpoints, request/response schemas, and authentication methods.

Authentication is required for all endpoints and can be done using API key generated from the Cal ID dashboard under the `settings/developer/api-keys` page. Use the Authorization header with the Bearer scheme to authenticate your requests.

Example:

- API Key: `Authorization: Bearer calid_XXXXX`

Note: To manage Team's resources use the Team's owner/admin API key

Server

https://api.cal.id

Production server

Authentication

Auth Type ▾

No authentication selected

Client Libraries

 Shell

 Ruby

 Node.js

 PHP

 Python

 More

Shell Curl

Health

Health check endpoints

Operations

GET /health

/health

Health check endpoint

Responses

> 200 Successful response

GET /health

Shell Curl ▾

1 curl https://api.cal.id/health

▶ Test Request

200

Show Schema ☐

```
{
  "success": true,
  "message": "string",
  "data": {
    "status": "string",
    "timestamp": "2026-05-26T06:30:08.430Z",
    "uptime": 1,
    "environment": "string",
    "version": "string"
  }
}
```

Successful response

Users

User management endpoints

Operations

GET

 /users/me

PUT

 /users/edit-profile

POST

 /users/edit-profile/avatar

GET

 /users/{userslug}

/users/me

Get current user profile

Responses

- > **200** Current user profile
- > **401** Unauthorized

GET /users/me

Shell Curl ▾

1 curl https://api.cal.id/users/me \

2 --header 'Authorization: Bearer YOUR_SECRET_TOKEN'

▶ Test Request

200 401

Show Schema ☐

{

"success": true,

"data": {

▲

```
    "id": 1,
    "email": "hello@example.com",
    "name": "string",
    "username": "string",
    "role": "string",
    "createdAt": "2026-05-26T06:30:08.430Z",
    "emailVerified": "2026-05-26T06:30:08.430Z"
  },
  "message": "string",
  "meta": {
    "pagination": {
      "page": 1,
      "limit": 1,
      "total": 1,
      "totalPages": 1
    }
  }
}
```



Current user profile

/users/edit-profile

Edit user profile

Body

application/json

allowDynamicBooking boolean Example
Allow dynamic booking behavior based on availability.

allowSEOIndexing boolean Example
Allow search engines to index the public booking page.

appTheme string | null Example
Application theme preference for supported clients.

avatarUrl string | null

bio string Example
Short public profile biography.

brandColor string Example
Primary brand color used on booking pages.

completedOnboarding boolean Example
Marks onboarding as completed for the user.

darkBrandColor string [Example](#)

Brand color used for dark theme contexts.

disableImpersonation boolean [Example](#)

Prevent admin impersonation for this user when enabled.

hideBranding boolean [Example](#)

Hide platform branding on booking pages and emails.

locale string [Example](#)

Locale code used for formatting and localized content.

metadata object [Example](#)

Flexible metadata object for advanced profile settings.

Empty object

+ Show Child Attributes

+ Show additional properties

Responses

- > **200** Profile updated successfully
- > **401** Unauthorized

PUT /users/edit-profile

Shell Curl ▾

```
1 curl https://cal-id.id/users/edit-profile \
```

```
1 curl https://api.cal.id/users/edit-profile \
2   --request PUT \
3   --header 'Content-Type: application/json' \
4   --header 'Authorization: Bearer YOUR_SECRET_TOKEN' \
5   --data '{
6     "username": "john-doe",
7     "name": "John Doe",
8     "bio": "Founder at Example Inc.",
9     "avatarUrl": null,
10    "timeZone": "Asia/Kolkata",
11    "weekStart": "Monday",
12    "hideBranding": false,
13    "allowDynamicBooking": true,
14    "allowSEOIndexing": true,
15    "receiveMonthlyDigestEmail": true,
16    "brandColor": "#2563EB",
17    "darkBrandColor": "#1E40AF",
18    "theme": "light",
19    "appTheme": "light",
20    "completedOnboarding": true,
```

200 401

Show Schema 

```
{
  "success": true,
  "data": {
    "id": 1,
    "username": null,
    "email": "string",
    "name": null,
    "avatarUrl": null
  },
  "message": "string",
  "pagination": {
    "page": 1,
    "limit": 1,
    "total": 1,
    "totalPages": 1
  }
}
```

► Test Request

/users/edit-profile/avatar

Upload avatar via multipart/form-data

Body

avatar string required Example

Avatar Image file selected from the client file picker.

```
}
}
```

Responses

- > **200** Avatar updated successfully
- > **400** Bad Request
- > **401** Unauthorized

POST /users/edit-profile/avatarShell Curl 

```
1 curl https://api.cal.id/users/edit-profile/avatar \  
2 --request POST \  
3 --header 'Content-Type: multipart/form-data' \  
4 --header 'Authorization: Bearer YOUR_SECRET_TOKEN' \  
5 --form 'avatar=profile-avatar.png'
```

 Test Request

200 400 401

Show Schema 

```
{  
  "success": true,  
  "data": {  
    "avatarUrl": "string"  
  },  
  "message": "string",  
  "meta": {  
    "pagination": {  
      "page": 1,  
      "limit": 1,  
      "total": 1,  
      "totalPages": 1  
    }  
  }  
}
```

Avatar updated successfully

/users/{userslug}

Get user public events

Path Parameters

userslug string · min length: 1 **required** [Example](#)

Public user slug used in profile and booking URLs.

Responses

- > **200** User public events
- > **401** Unauthorized
- > **404** Default Response

GET /users/{userslug} Shell Curl ▾

```
1 curl https://api.cal.id/users/john-doe \  
2 --header 'Authorization: Bearer YOUR_SECRET_TOKEN'
```

▶ Test Request

200 401 404 Show Schema ☐

```
{  
  "success": true,  
  "data": [  
    {  
      "username": "string",  
      "name": "string",  
      "email": "hello@example.com",  
      "bio": "string",  
      "avatarUrl": null,  
      "allowSEOIndexing": true,  
      "brandColor": "string",  
      "darkBrandColor": "string",  
      "theme": null  
    }  
  ],  
  "message": "string",  
  "meta": {  
    "pagination": {  
      "page": 1,  
      "limit": 1,  
      "total": 1,  
      "totalPages": 1  
    }  
  }  
}
```

Event Types

Event type management endpoints

Operations

```
GET /event-types/  
POST /event-types/  
GET /event-types/{id}  
PATCH /event-types/{id}  
DELETE /event-types/{id}
```

/event-types/

Get all event types for the authenticated user (paginated)

Query Parameters

page integer · min: 1 Default Example

Page number for paginated event type results.

limit integer · min: 1 · max: 100 Default Example

Maximum number of event types returned per page.

orderBy string · enum Example

Field used to sort event type results.

values

id

title

slug

length

position

orderDir string · enum Default Example

Sorting direction for event type results.

values

asc

desc

title string Example

Case-insensitive title filter.

slug string Example

Case-insensitive slug filter.

hidden boolean Example

Filter by hidden/public status.

Responses

- > **200** Paginated list of event types
- > **400** Invalid query parameters
- > **401** Unauthorized
- > **422** Validation failed

GET /event-types/Shell Curl ▾

```
1 curl 'https://api.cal.id/event-types/?page=1&limit=10&orderBy=id&orderDir=desc&'
2 --header 'Authorization: Bearer YOUR_SECRET_TOKEN'
```

► Test Request

200 400 401 422

Show Schema

/event-types/

success: true	
"data": [	
Create a new event type for the authenticated user	
"id": 1,	
Body "title": "string",	required application/json
"slug": "string",	
"description": null,	
slug string: min length: 4, max length: 100 required Example	
"interfaceLanguage": null,	
Unique URL slug for the event type under the owner account.	
"position": 1,	
"locations": null,	
title string: min length: 4, max length: 255 required Example	
bookingFields: null,	
Human-readable title for the event type shown in booking pages and calendars.	
"offsetStart": 1,	
afterEventBuffer: true, Default Example	
Buffer time in minutes blocked after each booking.	
"userId": null,	
"teamId": null,	
"profileId": null,	
allowReschedulingPastBookings boolean Default Example	
Whether past bookings are eligible for rescheduling.	
"timeZone": null,	
periodType: "string",	
"periodStartDate": "2026-05-26T06:30:08.430Z",	
assignAllTeamMembers boolean Default Example	
Whether all team members should be assigned for this event type.	
"periodEndDate": "2026-05-26T06:30:08.430Z",	
periodCountDays: null,	
"periodCountCalendarDays": null,	
assignRoundRoomMembersToSegmentOnBookingPage Example	
Whether round-room members should be selected using a segment query.	
"lockedTimeZone": null,	
"requiresConfirmation": true,	
"requiresConfirmationWillBlockSlot": true,	
beforeEventBuffer integer Default Example	
Buffer time in minutes blocked before each booking.	
"requiresConfirmationForFreeEmail": true,	
"requiresBookerEmailVerification": true,	
"recurringEvent": null,	
bookingFields array Example	
Full replacement of existing booking fields. Omit to preserve existing fields. Null is not	
accepted. Internal system-managed properties such as editable and sources are not accepted.	
"hideCalendarEventDetails": true,	
"minimumBookingNotice": 1,	
bookingLimits Example	
"beforeEventBuffer": 1,	
"afterEventBuffer": 1,	
Booking limits configuration payload.	
"seatsPerTimeSlot": null,	
"onlyShowFirstAvailableSlot": true,	
currency string Default Example	
ISO currency code. Reschedule price is	
"disableRescheduling": null,	
"disableHostCancelling": null,	
customReplyToEmail string null Example	
Custom reply to email used in booking communications.	
"seatsShowAttendees": null,	
"seatsShowAvailabilityCount": null,	

description string | null. Example
 "scheduledId": null,
 Optional event type description shown to bookers.

+ Show additional properties
 "currency": "string",
 "slotInterval": null,
 "metadata": null,

Responses
 "successRedirectUrl": null,
 "forwardParamsSuccessRedirect": null,

```
> 201 Event type created successfully
  "bookingLimits": null,
  "durationLimits": null,
  "isInstantEvent": true,
  "instantMeetingExpiryTimeOffsetInSeconds": 1,
> 400 Invalid event type data
  "assignAllTeamMembers": true,
  "assignRRMembersUsingSegment": true,
> 401 Unauthorized
  "rrSegmentQueryValue": null,
  "useEventTypeDestinationCalendarEmail": true,
> 409 Event type slug already exists
  "isRRWeightsEnabled": true,
  "maxLeadThreshold": null,
  "includeNoShowInRRCalculation": true,
  "allowReschedulingPastBookings": true,
  "hideOrganizerEmail": true,
  "maxActiveBookingsPerBooker": null,
  "maxActiveBookingPerBookerOfferReschedule": true,
  "customReplyToEmail": null,
  "eventTypeColor": null,
  "rescheduleWithSameRoundRobinHost": true,
  "secondaryEmailId": null,
  "useBookerTimezone": true,
  "restrictionScheduleId": null,
  "createdDate": "2026-05-26T06:30:08.430Z",
  "updatedAt": "2026-05-26T06:30:08.430Z"
}
],
"message": "string",
"meta": {
  "pagination": {
    "page": 1,
    "limit": 1,
    "total": 1,
    "totalPages": 1
  }
}
}
```

Paginated list of event types

POST /event-types/Shell Curl ▾

```
1 curl https://api.cal.id/event-types/ \  
2 --request POST \  
3 --header 'Content-Type: application/json' \  
4 --header 'Authorization: Bearer YOUR_SECRET_TOKEN' \  
5 --data '{  
6   "title": "30 Minute Discovery Call",  
7   "slug": "discovery-call-30"  
}'
```

/event-types/{id}

Get event type by ID for the authenticated user

▶ Test Request

Path Parameters 200 400 401 404 422Show Schema

id integer · greater than: 0 **required** Example
Numeric event type identifier.

Responses

- 200 Event type details retrieved.
{"success": true, "data": {"id": 1, "title": "string", "slug": "string", "description": null, "interfaceLanguage": null, "position": 1, "locations": null, "bookingFields": null, "length": 1, "offsetStart": 1, "hidden": true, "userId": null, "teamId": null, "profileId": null, "timeZone": null, "lockedTimeZone": null}}
- 400 Invalid event type ID.
- 401 Unauthorized.
- 404 Event type not found.
- 422 Validation failed.

GET /event-types/{id}Shell Curl ▾

```
1 curl https://api.cal.id/event-types/42 \  
2 --header 'Authorization: Bearer YOUR_SECRET_TOKEN'
```

▶ Test Request

200 400 401 404 422Show Schema

```
{  
  "success": true,  
  "data": {  
    "id": 1,  
    "title": "string",  
    "slug": "string",  
    "description": null,  
    "interfaceLanguage": null,  
    "position": 1,  
    "locations": null,  
    "bookingFields": null,  
    "length": 1,  
    "offsetStart": 1,  
    "hidden": true,  
    "userId": null,  
    "teamId": null,  
    "profileId": null,  
    "timeZone": null,  
    "lockedTimeZone": null  
  }  
}
```

```
"description": null,
"interfaceLanguage": null,
"position": 1,
"locations": null,
"bookingFields": null,
"length": 1,
"offsetStart": 1,
"hidden": true,
"userId": null,
"teamId": null,
"profileId": null,
"timeZone": null,
"periodType": "string",
"periodStartDate": "2026-05-26T06:30:08.430Z",
"periodEndDate": "2026-05-26T06:30:08.430Z",
"periodDays": null,
"periodCountCalendarDays": null,
"lockTimeZoneToggleOnBookingPage": true,
"lockedTimeZone": null,
"requiresConfirmation": true,
```

/event-types/{id}

Update event type details for the authenticated user

Path Parameters

id integer Example
Numeric event type identifier.

Body

```
"seatsPerTimeSlot": null,
"onlyShowFirstAvailableSlot": true,
"disableCancelling": null,
"disableRescheduling": null,
"disableHostCancelling": null,
```

application/json

allowReschedulingPastBookings boolean Default Example
Whether past bookings are eligible for rescheduling.

assignAllTeamMembers boolean Default Example
Whether all team members should be assigned for this event type.

assignRoundRobinMembersUsingSegment boolean Default Example
Whether round-robin members should be selected using a segment query.

beforeEventBuffer integer Default Example
Buffer time in minutes blocked before each booking.

bookingFieldsExpiryOffsetInSeconds 1,

Full replacement list of user-managed booking fields.

```
"assignAllTeamMembers": true,
"assignRRMembersUsingSegment": true,
+ Show additional properties
"showAttendeeValue": null,
"useEventTypeDestinationCalendarEmail": true,
"bookingLimitsExample": {
  "isRRWeightsEnabled": true,
  "maxLeadThreshold": null,
  "includeNoShowInRRCalculation": true,
  "allowReschedulingPastBookings": true,
  "currency": "string",
  "hideOrganizerEmail": true,
  "maxActiveBookingsPerBooker": null,
  "maxActiveBookingPerBookerOfferReschedule": true,
  "customReplyToEmail": "null",
  "eventTypeName": "string",
  "eventTypeId": "string",
  "eventColor": "string",
  "rescheduleWithSameRoundRobinHost": true,
  "description": "string",
  "secondaryEmailId": "string",
  "useBookerTimezone": true,
  "restrictionScheduleId": "string",
  "createdDate": "2026-05-26T06:30:08.430Z",
  "disableCancelling": true,
  "updatedDate": "2026-05-26T06:30:08.430Z"
}
Whether guests are prevented from cancelling bookings.
"message": "string",
"disableGuests": true,
"pagination": {
  "page": 1,
  "limit": 1,
  "total": 1,
  "totalPages": 1
}
```

Responses

}

- > 200 Event type updated successfully
- > 400 Event type details retrieved
- > 401 Unauthorized
- > 404 Event type not found
- > 409 Event type slug already exists
- > 422 Validation failed

/event-types/{id}

Delete event type for the authenticated user

Shell Curl ▾

```
1 curl https://api.cal.id/event-types/42 \  
2 --request PATCH \  
3 --header 'Content-Type: application/json' \  
4 --header 'Authorization: Bearer YOUR_SECRET_TOKEN' \  
5 --data '{  
6   "title": "Updated Discovery Call"  
7 }'
```

Path Parameters

id integer · greater than: 0 **required** Example

Numeric event type identifier.

Responses

▶ Test Request

> 200 Event type deleted successfully

> 200 400 401 404 409 422
400 Invalid event type ID

Show Schema ☐

```
{  
  "success": true,  
}
```

> 401 Unauthorized

> 404 Event type not found

> 422 Validation failed

```
"data": {
  "id": 1,
  "title": "string",
  "slug": "string",
  "description": null,
  "interfaceLanguage": null,
  "position": 1,
  "locations": null,
  "timezone": null,
```

DELETE /event-types/{id}

Shell Curl ▾

```
1 curl https://api.cal.id/event-types/42 \
2   --request DELETE \
3   --header 'Authorization: Bearer YOUR_SECRET_TOKEN'
```

▶ Test Request

200 400 401 404 422

Show Schema ☐

```
{
  "success": true,
  "data": null,
  "message": "string",
  "meta": {
    "pagination": {
      "page": 1,
      "limit": 1,
      "total": 1,
      "totalPages": 1
    }
  }
}
```

Event type deleted successfully

```
"createdAt": "2025-05-26T13:02:00.000Z",
"seatsPerTimeSlot": null,
"onlyShowFirstAvailableSlot": true,
```

Teams

Team management endpoints

Operations

```
GET /teams/
POST /teams/
GET /teams/{teamId}
```

```
PATCH /teams/{teamId}
DELETE /teams/{teamId}
```

[Show More ▾](#)

Team Event Types

Event type management endpoints for teams

Operations

```
GET /teams/{teamId}/event-types
POST /teams/{teamId}/event-types
GET /teams/{teamId}/event-types/{eventTypeId}
PATCH /teams/{teamId}/event-types/{eventTypeId}
DELETE /teams/{teamId}/event-types/{eventTypeId}
```

[Show More ▾](#)

Team Memberships

Membership management endpoints for teams

Operations

```
GET /teams/{teamId}/memberships
POST /teams/{teamId}/memberships
GET /teams/{teamId}/memberships/{membershipId}
PATCH /teams/{teamId}/memberships/{membershipId}
DELETE /teams/{teamId}/memberships/{membershipId}
```

[Show More ▾](#)

Team Schedules

Schedule management endpoints for teams

Operations

GET /teams/{teamId}/schedules

Show More ▾

Availability

User availability management endpoints

Operations

GET /availability/
POST /availability/
DELETE /availability/{availabilityId}
PATCH /availability/{availabilityId}

/availability/

Get current user availability

Query Parameters

dateFrom string · min length: 1 **required** Example
Availability window start timestamp (ISO-8601).

dateTo string · min length: 1 **required** Example
Availability window end timestamp (ISO-8601).

eventId integer · greater than: 0 · min: 1 Example
Optional event type identifier to scope returned availability.

Responses

- > **200** Current user availability
- > **400** Invalid availability query parameters
- > **401** Unauthorized
- > **500** Failed to retrieve availability

GET /availability/ Shell Curl ▾

```
1 curl 'https://api.cal.id/availability/?dateFrom=2026-05-01T00%3A00%3A00.000Z&dateTo=2026-05-01T00%3A00%3A00.000Z'
2 --header 'Authorization: Bearer YOUR_SECRET_TOKEN'
```

▶ Test Request

200 400 401 500 Show Schema ☐

```
{
  "success": true,
  "data": {
    "busy": [
      {
        "start": "string",
        "end": "string",
        "title": "string",
        "source": null
      }
    ],
    "timeZone": "string",
    "dateRanges": [
      {
        "start": "string",
        "end": "string"
      }
    ],
    "oooExcludedDateRanges": [],
    "workingHours": [
      {
        "days": [
          1
        ],
        "startTime": 1,
        "endTime": 1,
        "userId": 1
      }
    ]
  }
}
```


Create availability for the current user and given schedule

Body {
 "dateOverrides": [],
 "currentSeats": [],
 "datesOutOfOffice": {}
}

required application/json

days array integer[] · 1... required Example

Weekday numbers for recurring availability (0 = Sunday, 6 = Saturday).

meta {

endTime string · min length: 1 required Example

Availability end timestamp stored as time-of-day in UTC-compatible format.

scheduleId integer · greater than: 0 · min: 1 required Example

Schedule identifier that owns this availability block.

startTime string · min length: 1 required Example

Availability start timestamp stored as time-of-day in UTC-compatible format.

Current user availability

Responses

- > **200** Created availability
- > **400** Invalid availability payload
- > **401** Unauthorized
- > **500** Failed to create availability

POST /availability/ Shell Curl ▾

```
1 curl https://api.cal.id/availability/ \  
2   --request POST \  
3   --header 'Content-Type: application/json' \  
4   --header 'Authorization: Bearer YOUR_SECRET_TOKEN' \  
5   --data '{  
6     "scheduleId": 42,  
7     "days": [  
8       1,  
9       2,  
10      3,  
11      4,  
12      5  
13    ],  
14    "startTime": "1970-01-01T09:00:00.000Z",  
15    "endTime": "1970-01-01T17:00:00.000Z"  
16  }'
```

► Test Request

200 400 401 500

Show Schema 

```
{
  "success": true,
  "data": {
    "id": 1,
    "userId": 1,
    "eventType": 1,
    "days": [
      1
    ],
    "startTime": "2026-05-26T06:30:08.430Z",
    "endTime": "2026-05-26T06:30:08.430Z",
    "date": "2026-05-26T06:30:08.430Z",
    "scheduleId": 1,
    "targetTimeZones": [
      "string"
    ],
    "Schedule": {
      "userId": 1
    }
  },
  "message": "string",
  "meta": {
    "pagination": {
      "page": 1,
      "limit": 1,
      "totalItems": 1,
      "totalPages": 1
    }
  }
}
```

/availability/{availabilityId}

Delete an availability

}

Path Parameters

availabilityId string · `^[1-9]\d*$` required Example
Numeric availability identifier.

Responses

- > **200** Availability deleted
- > **400** Invalid availability id
- > **401** Unauthorized

- > **403** Forbidden
- > **500** Failed to delete availability

DELETE /availability/{availabilityId}

Shell Curl ▾

```
1 curl https://api.cal.id/availability/101 \  
2   --request DELETE \  
3   --header 'Authorization: Bearer YOUR_SECRET_TOKEN'
```

▶ Test Request

200 400 401 403 500

Show Schema ☐

```
{  
  "success": true,  
  "message": "string"  
}
```

Availability deleted

/availability/{availabilityId}

Update an availability

Path Parameters

availabilityId string · `^[1-9]\d*$` **required** Example

Numeric availability identifier.

Body

required

application/json

days array integer[] · 1... **required** Example

Weekday numbers for recurring availability (0 = Sunday, 6 = Saturday).

endTime string · min length: 1 **required** Example

Availability end timestamp stored as time-of-day in UTC-compatible format.

scheduleId integer · greater than: 0 · min: 1 **required** Example

Schedule identifier that owns this availability block.

startTime string · min length: 1 **required** [Example](#)

Availability start timestamp stored as time-of-day in UTC-compatible format.

Responses

- > **200** Updated availability
- > **400** Invalid availability update payload
- > **401** Unauthorized
- > **403** Forbidden
- > **500** Failed to update availability

PATCH /availability/{availabilityId}

Shell Curl ▾

```
1 curl https://api.cal.id/availability/101 \  
2   --request PATCH \  
3   --header 'Content-Type: application/json' \  
4   --header 'Authorization: Bearer YOUR_SECRET_TOKEN' \  
5   --data '{  
6     "scheduleId": 42,  
7     "days": [  
8       1,  
9       2,  
10      3,  
11      4,  
12      5  
13    ],  
14    "startTime": "1970-01-01T09:00:00.000Z",  
15    "endTime": "1970-01-01T17:00:00.000Z"  
16  }'
```

▶ Test Request

200 400 401 403 500

Show Schema ☐

```
{  
  "success": true,  
  "data": {  
    "id": 1,  
    "userId": 1,  
    "eventType": 1,  
    "availabilityId": 1,  
    "scheduleId": 42,  
    "days": [1, 2, 3, 4, 5],  
    "startTime": "1970-01-01T09:00:00.000Z",  
    "endTime": "1970-01-01T17:00:00.000Z"  
  }  
}
```

```
    "days": [
      1
    ],
    "startTime": "2026-05-26T06:30:08.430Z",
    "endTime": "2026-05-26T06:30:08.430Z",
    "date": "2026-05-26T06:30:08.430Z",
    "scheduleId": 1,
    "targetTimeZones": [
      "string"
    ],
    "Schedule": {
      "userId": 1
    }
  },
  "message": "string",
  "meta": {
    "pagination": {
      "page": 1,
      "limit": 1,
      "total": 1,
      "totalPages": 1
    }
  }
}
```

Schedule

User schedule management endpoints

Operations

```
GET /schedule/
POST /schedule/
DELETE /schedule/{scheduleId}
PATCH /schedule/{scheduleId}
```

/schedule/

Get current user schedules

Responses

- > 200 Current user schedules
- > 401 Unauthorized

```
GET /schedule/
```

Shell Curl ▾

```
1 curl https://api.cal.id/schedule/ \  
2 --header 'Authorization: Bearer YOUR_SECRET_TOKEN'
```

▶ Test Request

200 401

Show Schema ☐

```
{  
  "success": true,  
  "data": [  
    {  
      "id": 1,  
      "userId": 1,  
      "name": "string",  
      "availability": [  
        {  
          "id": 1,  
          "userId": 1,  
          "eventId": 1,  
          "days": [  
            1  
          ],  
          "startTime": "2026-05-26T06:30:08.430Z",  
          "endTime": "2026-05-26T06:30:08.430Z",  
          "date": "2026-05-26T06:30:08.430Z",  
          "scheduleId": 1,  
          "targetTimeZones": [  
            "string"  
          ]  
        }  
      ],  
      "timeZone": null  
    }  
  ],  
  "message": "string",  
  "meta": {  
    "pagination": {  
      "page": 1,  
      "limit": 1,  
      "total": 1  
    }  
  }  
}
```

/schedule/

Create a Schedule

Body

name string required Example
Human-readable schedule name.

timeZone string Example
IANA timezone identifier used for this schedule.

required

application/json

Responses

- > **200** Schedule created
- > **400** Validation failed
- > **401** Unauthorized

POST /schedule/

Shell Curl ▾

```
1 curl https://api.cal.id/schedule/ \  
2   --request POST \  
3   --header 'Content-Type: application/json' \  
4   --header 'Authorization: Bearer YOUR_SECRET_TOKEN' \  
5   --data '{  
6     "name": "Weekday Working Hours",  
7     "timeZone": "Asia/Kolkata"  
8   }'
```

▶ Test Request

200 400 401

Show Schema ☐

```
{  
  "success": true,  
  "data": {  
    "id": 1,  
    "userId": 1,  
    "name": "string",  
    "availability": [  
      {  
        "id": 1,  
        "userId": 1,  
        "eventId": 1,  
        "days": [  
          1  
        ],  
        "startTime": "2026-05-26T06:30:08.430Z",  
        "endTime": "2026-05-26T06:30:08.430Z",  
        "date": "2026-05-26T06:30:08.430Z",  
        "scheduleId": 1,  
        "targetTimeZones": [  
          "string"  
        ]  
      }  
    ],  
    "timeZone": null  
  },  
  "message": "string"  
}
```

/schedule/{scheduleId}

```
"page": 1,
Path Parameters 1,
"total": 1,
```

```

scheduleId string ^[1-9]\d*$ required Example
    }
    Numeric schedule identifier.
  }
}

```

Schedule created
Responses

- > **200** Schedule deleted
- > **401** Unauthorized
- > **403** Forbidden

Shell Curl

```
1 curl https://api.cal.id/schedule/42 \  
2     --request DELETE \  
3     --header 'Authorization: Bearer YOUR_SECRET_TOKEN'
```

► Test Request

200 401 403

Show Schema

```
{
  "success": true,
  "message": "string"
}
```

Schedule deleted

/schedule/{scheduleId}

Update a schedule for the current user

Path Parameters

scheduleId string · `^[1-9]\d*$` required Example

Numeric schedule identifier.

Body

application/json

name string Example
Human-readable schedule name.

timeZone string Example
IANA timezone identifier used for this schedule.

Responses

- > **200** Schedule updated
- > **400** Validation failed
- > **401** Unauthorized
- > **403** Forbidden

PATCH /schedule/{scheduleId} Shell Curl ▾

```
1 curl https://api.cal.id/schedule/42 \  
2   --request PATCH \  
3   --header 'Content-Type: application/json' \  
4   --header 'Authorization: Bearer YOUR_SECRET_TOKEN' \  
5   --data '{  
6     "name": "Updated Weekday Working Hours"  
7   }'
```

▶ Test Request

200 400 401 403 Show Schema ☐

```
{  
  "success": true,  
  "data": {  
    "id": 1,  
    "userId": 1,  
    "name": "string",  
    "availability": [  
      {  
        "id": 1,  
        "userId": 1,  
        "eventTypeId": 1,  

```

```
    "days": [  
      1  
    ],  
    "startTime": "2026-05-26T06:30:08.430Z",  
    "endTime": "2026-05-26T06:30:08.430Z",  
    "date": "2026-05-26T06:30:08.430Z",  
    "scheduleId": 1,  
    "targetTimeZones": [  
      "string"  
    ]  
  }  
}
```

Slots

Available slots retrieval endpoints

Operations

GET

 /slots/

POST

 /slots/reserve

GET

 /slots/{uid}

DELETE

 /slots/{uid}

PATCH

 /slots/{uid}

Show More ▾

Booking

Event booking endpoints

Operations

GET

 /booking/

POST

 /booking/

GET

 /booking/{id}

POST

 /booking/{id}/cancel

PATCH

 /booking/{id}/change_confirmation

PATCH

 /booking/{id}/reassignBookingAutomatically

PATCH

 /booking/{id}/reassignBookingToUser

```
PATCH /booking/{id}/reschedule
```

/booking/

Get current user bookings

Query Parameters

status string · enum Default Example

Booking status bucket filter.

values

upcoming

recurring

past

cancelled

unconfirmed

teamId integer · greater than: 0 · min: 1 Example

Filter by a single team ID. Admin/owner receives all team bookings; members receive only host/attendee bookings.

eventTypeIds array integer[] Example

Filter by event type IDs.

attendeeEmail string · email Example

Filter by attendee email.

attendeeName string Example

Filter by attendee name.

bookingUid string Example

Filter by booking UID.

afterStartDate string · date-time Example

Include bookings starting after this ISO timestamp.

beforeEndDate string · date-time Example

Include bookings ending before this ISO timestamp.

afterUpdatedDate string · date-time [Example](#)

Include bookings updated after this ISO timestamp.

beforeUpdatedDate string · date-time [Example](#)

Include bookings updated before this ISO timestamp.

afterCreatedDate string · date-time [Example](#)

Include bookings created after this ISO timestamp.

beforeCreatedDate string · date-time [Example](#)

Include bookings created before this ISO timestamp.

sortStart string · enum [Example](#)

Sort direction for booking start time.

values

asc

desc

sortEnd string · enum [Example](#)

Sort direction for booking end time.

values

asc

desc

sortCreated string · enum [Example](#)

Sort direction for booking creation time.

values

asc

desc

sortUpdated string · enum [Example](#)

Sort direction for booking update time.

values

asc

desc

page integer · greater than: 0 · min: 1 [Default](#) [Example](#)

Page number (1-based).

limit integer · greater than: 0 · min: 1 · max: 500 [Default](#) [Example](#)

Maximum number of bookings returned per page.

Responses

- > **200** User bookings retrieved

- > **400** Bad Request

- > **401** Unauthorized

- > **403** Forbidden

/booking/

Create a new booking

Body

required

application/json

end string · date-time **required** Example

Booking end time (ISO 8601, e.g., '2025-10-09T15:00:00+05:30')

responses object **required** Example

Booking form responses containing attendee details

+ Show Child Attributes

start string · date-time **required** Example

Booking start time (ISO 8601, e.g., '2025-10-09T14:30:00+05:30')

eventId integer · greater than: 0 · min: 1 Example

Unique identifier for the event type

eventTypeSlug string · min length: 1 Example

Event type slug selector. Accepted formats: `<slug>` for your own event type, `<username>/<slug>` (owner-prefixed user format), or `team/<teamSlug>/<slug>` for team event types.

language string Default Example

Language code for email communications (e.g., 'en', 'es', 'fr')

metadata object Default Example

Additional metadata for the booking

Empty object

+ Show Child Attributes

timeZone string Default Example

IANA timezone identifier (e.g., 'Asia/Calcutta', 'America/New_York')

Responses

> **200** Booking created

> **400** Bad Request

> **401** Unauthorized

> **500** Internal Server Error

GET /booking/

Shell Curl ▾

```
1 curl 'https://api.cal.id/booking/?status=upcoming&teamId=42&eventIds=12&att
2 --header 'Authorization: Bearer YOUR_SECRET_TOKEN'
```

[▶ Test Request](#)

200 400 401 403

[Show Schema](#)

```
{
  "success": true,
  "data": [
    {
      "id": 1,
      "title": null,
```

POST /booking/

[Shell Curl](#) ▼

```
1 curl https://api.cal.id/booking/ \
2   --request POST \
3   --header 'Content-Type: application/json' \
4   --header 'Authorization: Bearer YOUR_SECRET_TOKEN' \
5   --data '{
6     "eventType": 12,
7     "start": "2026-05-02T10:00:00.000Z",
8     "end": "2026-05-02T10:30:00.000Z",
9     "responses": {
10      "name": "Jane Doe",
11      "email": "jane@example.com",
12      "location": {
13        "value": "integrations:google:meet",
14        "optionValue": ""
15      }
16    }
17  }'
```

cURL [▶ Test Request](#)

```
"slug": "string".
```

200 400 401 500

[Show Schema](#)

```
{
  "success": true,
  "data": {
    "id": 1,
    "uid": "string",
    "userId": 1,
    "status": "PENDING",
    "startTime": "string",
    "endTime": "string",
    "paymentRequired": true,
    "paymentUid": "string",
    "paymentId": 1,
    "isDryRun": true
  },
```

```
  "message": "string",
  "meta": {
    "pagination": {
      "page": 1,
      "limit": 1,
      "totalPages": 1
    }
  }
}
```

Get booking by id

Path Parameters

id integer · greater than: 0 · min: 1 **required** Example
Numeric booking identifier.

```
  "disableRescheduling": true,
  "eventTypeColor": null
},
{
  "references": [],
  "payment": [],
  "user": {
    "id": 1,
    "name": null,
    "email": "hello@example.com"
  },
  "attendees": [],
  "seatsReferences": [],
  "assignmentReason": []
}
```

Responses

> 200 Booking

> 400 Bad Request

> 401 Unauthorized

> 404 Booking not found or invalid credentials

GET /booking/{id}

Shell Curl ▾

```
1 curl https://api.cal.id/booking/101 \
2 --header 'Authorization: Bearer YOUR_SECRET_TOKEN'
```

► Test Request

200 400 401 404

Show Schema ☐

```
{
  "success": true,
  "data": {
    "id": 1,
    "title": null,
    "description": null,
    "customInputs": {},
    "startTime": null,
    "endTime": null,
    "createdAt": "string",
    "updatedAt": "string",
    "metadata": {},
    "uid": null,
    "recurringEventId": null,
    "location": null,
    "status": null,
    "paid": true,
  }
}
```



```

"fromReschedule": null,
"rescheduled": null,
"isRecorded": true,
"eventType": {
  "id": 1,
  "title": "string",
  "slug": "string",
  "eventName": "string",
  "price": 1,
  "currency": "string",
  "recurringEvent": null,
  "metadata": {},
  "seatsByType": {
    "ROUND_ROBIN": {
      "showAttendees": true,
      "hosts": [
        {
          "user": {
            "id": 1,
            "name": null,
            "email": "hello@example.com"
          }
        }
      ]
    }
  },
  "calIdTeam": {
    "id": 1,
    "name": "string",
    "slug": "string"
  }
}

```

/booking/{id}/cancel

Cancel booking by id

Optional request body field controls for cancellation scope, seated-event seat cancellation, and payment refund handling.

Path Parameters

id integer · greater than 0 min: 1 required Example
Numeric booking identifier.

Body

Optional controls for cancellation scope, seated-event seat cancellation, and payment refund handling.

Optional controls for cancellation scope, seated-event seat cancellation, and payment refund handling.

allRemainingBookings boolean Example

When true, cancels all remaining future bookings in the recurring series from now onward.

allowReschedulingPastBookings boolean Default Example

When true, allows past bookings to be rescheduled.

autoRefund boolean Default Example
When true, attempts payment cancellation/refund for paid bookings and marks booking payment metadata as refunded.

disableCancellation boolean Default Example

When true, disables cancellation for the booking.

disableRescheduling boolean Default Example

When true, prevents past bookings from being rescheduled.

eventTypeId integer · greater than 0 min: 1 required Example

Optional event type ID for cancelling a specific event type.

cancelledBy string · email Example

Optional actor email recorded as the canceller (cancelledBy) on the booking.

attendees array

seatReferenceUid string Example

Optional seat reference UID for cancelling a specific attendee seat in seated event types.

hosts array

Responses

> **200** Booking cancelled

```
> 400 Bad Request
  "paymentOption": null,
  "amount": 1,
  "currency": "string",
  "success": true
}
> 401 Unauthorized
  "message": "string"
}
> 404 Booking not found or invalid credentials
  "message": "string"
```

POST /booking/{id}/cancel

Shell Curl ▾

```
1 curl https://api.cal.id/booking/101/cancel \
2   --request POST \
3   --header 'Content-Type: application/json' \
4   --header 'Authorization: Bearer YOUR_SECRET_TOKEN' \
5   --data '{
6     "cancellationReason": "Rescheduling required"
7   }'
```

► Test Request

200 400 401 404

Show Schema ☐

```
{
  "success": true,
  "data": {
    "success": true,
    "message": "string",
    "onlyRemovedAttendee": true,
    "bookingId": 1,
    "bookingUid": "string"
  },
  "message": "string",
  "meta": {
    "pagination": {
      "page": 1,
      "limit": 1,
      "total": 1,
      "totalPages": 1
    }
  }
}
```

/booking/{id}/change_confirmation

Change booking confirmation status (accept or decline)

Path Parameters

id integer · greater than: 0 · min: 1 **required** [Example](#)
Numeric booking identifier.

Body

required

application/json

confirmed boolean **required** [Example](#)
Whether the booking is accepted (`true`) or declined (`false`).

reason string [Example](#)
Optional reason for declining or accepting.

recurringEventId string | null [Default](#) [Example](#)
Optional recurring event instance identifier.

Responses

- > **200** Booking status changed
- > **400** Bad Request
- > **401** Unauthorized
- > **404** Booking not found or invalid credentials

PATCH /booking/{id}/change_confirmation Shell Curl ▾

```
1 curl https://api.cal.id/booking/101/change_confirmation \  
2   --request PATCH \  
3   --header 'Content-Type: application/json' \  
4   --header 'Authorization: Bearer YOUR_SECRET_TOKEN' \  
5   --data '{  
6     "confirmed": true  
7   }'
```

▶ Test Request

200 400 401 404 Show Schema ☐

```
{  
  "success": true,  
  "message": "Booking confirmed successfully."  
}
```

```
"data": {
  "message": "string",
  "status": "string",
  "bookingId": 1
},
"message": "string",
"meta": {
  "pagination": {
    "page": 1,
    "limit": 1,
    "total": 1,
    "totalPages": 1
  }
}
```

Booking status changed

/booking/{id}/reassignBookingAutomatically

Reassign booking to automatically via round robin

Path Parameters

id integer · greater than: 0 · min: 1 **required** Example

Numeric booking identifier.

Responses

- > **200** Booking reassigned
- > **400** Bad Request
- > **401** Unauthorized
- > **404** Booking not found or invalid credentials

PATCH /booking/{id}/reassignBookingAutomatically

Shell Curl ▾

```
1 curl https://api.cal.id/booking/101/reassignBookingAutomatically \
2 --request PATCH \
```

```
3 --header 'Authorization: Bearer YOUR_SECRET_TOKEN'
```

[▶ Test Request](#)

200 400 401 404

[Show Schema](#) ☐

```
{
  "success": true,
  "data": {
    "bookingId": 1
  },
  "message": "string",
  "meta": {
    "pagination": {
      "page": 1,
      "limit": 1,
      "total": 1,
      "totalPages": 1
    }
  }
}
```

Booking reassigned

/booking/{id}/reassignBookingToUser

Reassign round robin booking to a certain user

Path Parameters

id integer · greater than: 0 · min: 1 **required** [Example](#)

Numeric booking identifier.

Body

required

application/json

userId integer · greater than: 0 · min: 1 **required** [Example](#)

User ID to whom the booking should be reassigned.

reason string [Example](#)

Optional reassignment reason.

Responses

- > **200** Booking reassigned
- > **400** Bad Request
- > **401** Unauthorized
- > **404** Booking not found or invalid credentials

PATCH /booking/{id}/reassignBookingToUser

Shell Curl ▾

```
1 curl https://api.cal.id/booking/101/reassignBookingToUser \  
2   --request PATCH \  
3   --header 'Content-Type: application/json' \  
4   --header 'Authorization: Bearer YOUR_SECRET_TOKEN' \  
5   --data '{  
6     "userId": 321  
7   }'
```

▶ Test Request

200 400 401 404

Show Schema ☐

```
{  
  "success": true,  
  "data": {  
    "newUserId": 1,  
    "bookingId": 1  
  },  
  "message": "string",  
  "meta": {  
    "pagination": {  
      "page": 1,  
      "limit": 1,  
      "total": 1,  
      "totalPages": 1  
    }  
  }  
}
```

Booking reassigned

/booking/{id}/reschedule

Reschedule booking by id

Path Parameters

id integer · greater than: 0 · min: 1 **required** [Example](#)

Numeric booking identifier.

Body

required

application/json

start string · min length: 1 **required** [Example](#)

New booking start time as an ISO timestamp string.

rescheduledBy string · email [Example](#)

Optional email of the actor initiating the reschedule.

reschedulingReason string [Example](#)

Optional reason for rescheduling.

seatUid string [Example](#)

Seat reference UID for seat-based reschedule flows.

Responses

- > **200** Booking rescheduled
- > **400** Bad Request
- > **401** Unauthorized
- > **404** Booking not found or invalid credentials

PATCH /booking/{id}/reschedule

Shell Curl ▾

```
1 curl https://api.cal.id/booking/101/reschedule \  
2   --request PATCH \  
3   --header 'Content-Type: application/json' \  
4   --header 'Authorization: Bearer YOUR_SECRET_TOKEN' \  
5   --data '{  
6     "start": "2026-05-03T11:00:00.000Z"  
7   }'
```

▶ Test Request

200 400 401 404

Show Schema 

```
{
  "success": true,
  "data": {
    "bookingId": 1,
    "bookingUid": "string"
  },
  "message": "string",
  "meta": {
    "pagination": {
      "page": 1,
      "limit": 1,
      "total": 1,
      "totalPages": 1
    }
  }
}
```

Booking rescheduled

Contacts

Operations

[GET](#) /contacts/
[POST](#) /contacts/
[GET](#) /contacts/{id}
[PATCH](#) /contacts/{id}
[DELETE](#) /contacts/{id}
[GET](#) /contacts/{id}/meetings

Show More 

Webhook

Operations

`GET /webhook/`
`POST /webhook/`
`GET /webhook/{id}`
`PATCH /webhook/{id}`
`DELETE /webhook/{id}`

/webhook/

Get user webhooks

Query Parameters

page integer · greater than: 0 · min: 1 [Default](#) [Example](#)
1-based page number.

limit integer · greater than: 0 · min: 1 · max: 500 [Default](#) [Example](#)
Maximum number of records to return per page.

Responses

- > **200** User webhook retrieved
- > **401** Unauthorized

`GET /webhook/`

Shell Curl ▾

```
1 curl 'https://api.cal.id/webhook/?page=1&limit=100' \  
2 --header 'Authorization: Bearer YOUR_SECRET_TOKEN'
```

▶ Test Request

200 401

Show Schema ☐

```
{  
  "success": true,  
  "data": [  
    {
```

```
"payloadTemplate": null,
"platformOAuthClientId": null,
"id": "string",
"eventTriggers": [
  "BOOKING_CREATED"
],
"subscriberUrl": "string",
"active": true,
"secret": null
}
],
"message": "string",
"meta": {
  "pagination": {
    "page": 1,
    "limit": 1,
    "total": 1,
    "totalPages": 1
  }
}
```

/webhook/

User webhook retrieved

Created webhook by id

Body

required

application/json

eventTriggers array · enum **required** [Example](#)

Webhook events that should trigger delivery.

values

BOOKING_CREATED

BOOKING_PAYMENT_INITIATED

BOOKING_PAID

BOOKING_RESCHEDULED

BOOKING_REQUESTED

+ Show all values

subscriberUrl string **required** [Example](#)

Destination URL that receives webhook requests.

active boolean [Example](#)

Whether this webhook is currently enabled.

payloadTemplate string | null [Example](#)

Optional custom payload template delivered to the subscriber.

secret string | null Example

Optional shared secret used to sign webhook payloads.

Responses

> **200** Webhook created

> **401** Unauthorized

POST /webhook/

Shell Curl ▾

```
1 curl https://api.cal.id/webhook/ \  
2   --request POST \  
3   --header 'Content-Type: application/json' \  
4   --header 'Authorization: Bearer YOUR_SECRET_TOKEN' \  
5   --data '{  
6     "subscriberUrl": "https://example.com/webhooks/calid",  
7     "eventTriggers": [  
8       "BOOKING_CREATED"  
9     ],  
10    "active": true  
11  }'
```

▶ Test Request

200 401

Show Schema ☐

```
{  
  "success": true,  
  "data": {  
    "payloadTemplate": null,  
    "platformOAuthClientId": null,  
    "id": "string",  
    "eventTriggers": [  
      "BOOKING_CREATED"  
    ],  
    "subscriberUrl": "string",  
    "active": true,  
    "secret": null  
  },  
  "message": "string",  
  "meta": {  
    "pagination": {  
      "page": 1,  
      "total": 1  
    }  
  }  
}
```

```
"limit": 1,  
"total": 1,  
"totalPages": 1
```

```
}
```

```
}
```

```
}
```

Webhook created



