

# A Formal Development of a Polychronous Polytimed Coordination Language

Hai Nguyen Van	Frédéric Boulanger	Burkhart Wolff
<a href="mailto:hai.nguyenvan.phie@gmail.com">hai.nguyenvan.phie@gmail.com</a>	<a href="mailto:frederic.boulanger@centralesupelec.fr">frederic.boulanger@centralesupelec.fr</a>	<a href="mailto:burkhart.wolff@lri.fr">burkhart.wolff@lri.fr</a>

April 22, 2020



# Contents

<b>1</b>	<b>A Gentle Introduction to TESL</b>	<b>5</b>
1.1	Context . . . . .	5
1.2	The TESL Language . . . . .	6
1.2.1	Instantaneous Causal Operators . . . . .	7
1.2.2	Temporal Operators . . . . .	7
1.2.3	Asynchronous Operators . . . . .	8
<b>2</b>	<b>Core TESL: Syntax and Basics</b>	<b>9</b>
2.1	Syntactic Representation . . . . .	9
2.1.1	Basic elements of a specification . . . . .	9
2.1.2	Operators for the TESL language . . . . .	10
2.1.3	Field Structure of the Metric Time Space . . . . .	10
2.2	Defining Runs . . . . .	14
<b>3</b>	<b>Denotational Semantics</b>	<b>17</b>
3.1	Denotational interpretation for atomic TESL formulae . . . . .	17
3.2	Denotational interpretation for TESL formulae . . . . .	18
3.2.1	Image interpretation lemma . . . . .	18
3.2.2	Expansion law . . . . .	19
3.3	Equational laws for the denotation of TESL formulae . . . . .	19
3.4	Decreasing interpretation of TESL formulae . . . . .	19
3.5	Some special cases . . . . .	21
<b>4</b>	<b>Symbolic Primitives for Building Runs</b>	<b>23</b>
4.0.1	Symbolic Primitives for Runs . . . . .	23
4.1	Semantics of Primitive Constraints . . . . .	24
4.1.1	Defining a method for witness construction . . . . .	25
4.2	Rules and properties of consistence . . . . .	25
4.3	Major Theorems . . . . .	26
4.3.1	Interpretation of a context . . . . .	26
4.3.2	Expansion law . . . . .	26
4.4	Equations for the interpretation of symbolic primitives . . . . .	26
4.4.1	General laws . . . . .	26
4.4.2	Decreasing interpretation of symbolic primitives . . . . .	27
<b>5</b>	<b>Operational Semantics</b>	<b>29</b>
5.1	Operational steps . . . . .	29
5.2	Basic Lemmas . . . . .	32

<b>6</b>	<b>Semantics Equivalence</b>	<b>35</b>
6.1	Stepwise denotational interpretation of TESL atoms . . . . .	35
6.2	Coinduction Unfolding Properties . . . . .	39
6.3	Interpretation of configurations . . . . .	44
<b>7</b>	<b>Main Theorems</b>	<b>51</b>
7.1	Initial configuration . . . . .	51
7.2	Soundness . . . . .	51
7.3	Completeness . . . . .	55
7.4	Progress . . . . .	57
7.5	Local termination . . . . .	68
<b>8</b>	<b>Properties of TESL</b>	<b>71</b>
8.1	Stuttering Invariance . . . . .	71
8.1.1	Definition of stuttering . . . . .	71
8.1.2	Alternate definitions for counting ticks. . . . .	73
8.1.3	Stuttering Lemmas . . . . .	73
8.1.4	Lemmas used to prove the invariance by stuttering . . . . .	74
8.1.5	Main Theorems . . . . .	94

# Chapter 1

## A Gentle Introduction to TESL

### 1.1 Context

The design of complex systems involves different formalisms for modeling their different parts or aspects. The global model of a system may therefore consist of a coordination of concurrent sub-models that use different paradigms such as differential equations, state machines, synchronous data-flow networks, discrete event models and so on, as illustrated in [Figure 1.1](#). This raises the interest in architectural composition languages that allow for “bolting the respective sub-models together”, along their various interfaces, and specifying the various ways of collaboration and coordination [2].

We are interested in languages that allow for specifying the timed coordination of subsystems by addressing the following conceptual issues:

- events may occur in different sub-systems at unrelated times, leading to *polychronous* systems, which do not necessarily have a common base clock,
- the behavior of the sub-systems is observed only at a series of discrete instants, and time coordination has to take this *discretization* into account,
- the instants at which a system is observed may be arbitrary and should not change its behavior (*stuttering invariance*),
- coordination between subsystems involves causality, so the occurrence of an event may enforce the occurrence of other events, possibly after a certain duration has elapsed or an event has occurred a given number of times,
- the domain of time (discrete, rational, continuous. . . ) may be different in the subsystems, leading to *polytimed* systems,
- the time frames of different sub-systems may be related (for instance, time in a GPS satellite and in a GPS receiver on Earth are related although they are not the same).

In order to tackle the heterogeneous nature of the subsystems, we abstract their behavior as clocks. Each clock models an event, i.e., something that can occur or not at a given time. This time is measured in a time frame associated with each clock, and the nature of time (integer, rational, real, or any type with a linear order) is specific to each clock. When the event associated



Figure 1.1: A Heterogeneous Timed System Model

with a clock occurs, the clock ticks. In order to support any kind of behavior for the subsystems, we are only interested in specifying what we can observe at a series of discrete instants. There are two constraints on observations: a clock may tick only at an observation instant, and the time on any clock cannot decrease from an instant to the next one. However, it is always possible to add arbitrary observation instants, which allows for stuttering and modular composition of systems. As a consequence, the key concept of our setting is the notion of a clock-indexed Kripke model:  $\Sigma^\infty = \mathbb{N} \rightarrow \mathcal{K} \rightarrow (\mathbb{B} \times \mathcal{T})$ , where  $\mathcal{K}$  is an enumerable set of clocks,  $\mathbb{B}$  is the set of booleans – used to indicate that a clock ticks at a given instant – and  $\mathcal{T}$  is a universal metric time space for which we only assume that it is large enough to contain all individual time spaces of clocks and that it is ordered by some linear ordering ( $\leq_{\mathcal{T}}$ ).

The elements of  $\Sigma^\infty$  are called runs. A specification language is a set of operators that constrains the set of possible monotonic runs. Specifications are composed by intersecting the denoted run sets of constraint operators. Consequently, such specification languages do not limit the number of clocks used to model a system (as long as it is finite) and it is always possible to add clocks to a specification. Moreover, they are *compositional* by construction since the composition of specifications consists of the conjunction of their constraints.

This work provides the following contributions:

- defining the non-trivial language **TESL\*** in terms of clock-indexed Kripke models,
- proving that this denotational semantics is stuttering invariant,
- defining an adapted form of symbolic primitives and presenting the set of operational semantic rules,
- presenting formal proofs for soundness, completeness, and progress of the latter.

## 1.2 The TESL Language

The TESL language [1] was initially designed to coordinate the execution of heterogeneous components during the simulation of a system. We define here a minimal kernel of operators that

will form the basis of a family of specification languages, including the original TESL language, which is described at <http://wdi.supelec.fr/software/TESL/>.

### 1.2.1 Instantaneous Causal Operators

TESL has operators to deal with instantaneous causality, i.e., to react to an event occurrence in the very same observation instant.

- `c1 implies c2` means that at any instant where `c1` ticks, `c2` has to tick too.
- `c1 implies not c2` means that at any instant where `c1` ticks, `c2` cannot tick.
- `c1 kills c2` means that at any instant where `c1` ticks, and at any future instant, `c2` cannot tick.

### 1.2.2 Temporal Operators

TESL also has chronometric temporal operators that deal with dates and chronometric delays.

- `c sporadic t` means that clock `c` must have a tick at time `t` on its own time scale.
- `c1 sporadic t on c2` means that clock `c1` must have a tick at an instant where the time on `c2` is `t`.
- `c1 time delayed by d on m implies c2` means that every time clock `c1` ticks, `c2` must have a tick at the first instant where the time on `m` is `d` later than it was when `c1` had ticked. This means that every tick on `c1` is followed by a tick on `c2` after a delay `d` measured on the time scale of clock `m`.
- `c1 time delayed\<bowtie> by d on m implies c2` means that every time clock `c1` ticks, `c2` must have a tick at an instant where the time on `m` is `d` later than it was when `c1` had ticked. This means that every tick on `c1` is followed by at least a tick on `c2` after a delay `d` measured on the time scale of clock `m`. Contrary to the strict version of `time delayed`, `c2` may not tick at the first instant at which the delay expires, and it may tick at several instants, provided that the time on `m` is still `d` later than it was when `c1` had ticked.
- `time relation (c1, c2) in R` means that at every instant, the current time on clocks `c1` and `c2` must be in relation `R`. By default, the time lines of different clocks are independent. This operator allows us to link two time lines, for instance to model the fact that time in a GPS satellite and time in a GPS receiver on Earth are not the same but are related. Time being polymorphic in TESL, this can also be used to model the fact that the angular position on the camshaft of an engine moves twice as fast as the angular position on the crankshaft <sup>1</sup>. We may consider only linear arithmetic relations to restrict the problem to a domain where the resolution is decidable.

---

<sup>1</sup>See <http://wdi.supelec.fr/software/TESL/GalleryEngine> for more details

### 1.2.3 Asynchronous Operators

The last category of TESL operators allows the specification of asynchronous relations between event occurrences. They do not specify the precise instants at which ticks have to occur, they only put bounds on the set of instants at which they should occur.

- **c1 weakly precedes c2** means that for each tick on **c2**, there must be at least one tick on **c1** at a previous or at the same instant. This can also be expressed by stating that at each instant, the number of ticks since the beginning of the run must be lower or equal on **c2** than on **c1**.
- **c1 strictly precedes c2** means that for each tick on **c2**, there must be at least one tick on **c1** at a previous instant. This can also be expressed by saying that at each instant, the number of ticks on **c2** from the beginning of the run to this instant, must be lower or equal to the number of ticks on **c1** from the beginning of the run to the previous instant.



## Chapter 2

# The Core of the TESL Language: Syntax and Basics

```
theory TESL
imports Main

begin
```

### 2.1 Syntactic Representation

We define here the syntax of TESL specifications.

#### 2.1.1 Basic elements of a specification

The following items appear in specifications:

- Clocks, which are identified by a name.
- An instant on a clock is identified by its index, starting from 0
- Tag constants are just constants of a type which denotes the metric time space.

```
datatype clock = Clk <string>
type_synonym instant_index = <nat>

datatype 'τ tag_const = TConst (the_tag_const : 'τ) (τ_cst)
```

Tag variables are used to refer to the time on a clock at a given instant index. Tag expressions are used to build a new tag by adding a constant delay to a tag variable.

```
datatype tag_var =
  TSchematic <clock * instant_index> (τ_var)
datatype 'τ tag_expr =
  AddDelay <tag_var> <'τ tag_const> ((| _ ⊕ _ |))
```

### 2.1.2 Operators for the TESL language

The type of atomic TESL constraints, which can be combined to form specifications.

```
datatype 'τ TESL_atomic =
  SporadicOn      (clock) ('τ tag_const) (clock) (<_ sporadic _ on _> 55)
| TagRelation     (clock) (clock) (('τ tag_const × 'τ tag_const) ⇒ bool)
                  (time-relation [_ , _] ∈ _) 55)
| Implies         (clock) (clock)                (infixr <implies> 55)
| ImpliesNot      (clock) (clock)                (infixr <implies not> 55)
| TimeDelayedBy   (clock) ('τ tag_const) (clock) (clock)
                  (<_ time-delayed by _ on _ implies _> 55)
| RelaxedTimeDelayed (clock) ('τ tag_const) (clock) (clock)
                  (<_ time-delayed by _ on _ implies _> 55)
| WeaklyPrecedes  (clock) (clock)                (infixr <weakly precedes> 55)
| StrictlyPrecedes (clock) (clock)                (infixr <strictly precedes> 55)
| Kills          (clock) (clock)                (infixr <kills> 55)
— The following constraints are not part of the TESL language, they are added only for implementing the
  operational semantics
| SporadicOnTvar   (clock) ('τ tag_expr) (clock) (<_ sporadic# _ on _> 55)
```

Some constraints were introduced for the implementation of the operational semantics. They are not allowed in user-level TESL specification and are not public.

```
fun is_public_atom :: ('τ TESL_atomic ⇒ bool) where
  <is_public_atom (<_ sporadic# _ on _>) = False>
| <is_public_atom _ = True>
```

A TESL formula is just a list of atomic constraints, with implicit conjunction for the semantics.

```
type-synonym 'τ TESL_formula = ('τ TESL_atomic list)
```

```
fun is_public_spec :: ('τ TESL_atomic list ⇒ bool) where
  <is_public_spec [] = True>
| <is_public_spec (φ#S) = ((is_public_atom φ) ∧ (is_public_spec S))>
```

We call *positive atoms* the atomic constraints that create ticks from nothing. Only sporadic constraints are positive in the current version of TESL.

```
fun positive_atom :: ('τ TESL_atomic ⇒ bool) where
  <positive_atom (<_ sporadic _ on _>) = True>
| <positive_atom (<_ sporadic# _ on _>) = True>
| <positive_atom _ = False>
```

The NoSporadic function removes sporadic constraints from a TESL formula.

```
abbreviation NoSporadic :: ('τ TESL_formula ⇒ 'τ TESL_formula)
where
  <NoSporadic f ≡ (List.filter (λfatom. case fatom of
    _ sporadic _ on _ ⇒ False
  | _ ⇒ True) f)>
```

### 2.1.3 Field Structure of the Metric Time Space

In order to handle tag relations and delays, tags must belong to a field. We show here that this is the case when the type parameter of 'τ tag\_const is itself a field.

```
instantiation tag_const :: (field)field
begin
  fun inverse_tag_const
```

```

where ⟨inverse ( $\tau_{cst}$  t) =  $\tau_{cst}$  (inverse t)⟩

fun divide_tag_const
  where ⟨divide ( $\tau_{cst}$  t1) ( $\tau_{cst}$  t2) =  $\tau_{cst}$  (divide t1 t2)⟩

fun uminus_tag_const
  where ⟨uminus ( $\tau_{cst}$  t) =  $\tau_{cst}$  (uminus t)⟩

fun minus_tag_const
  where ⟨minus ( $\tau_{cst}$  t1) ( $\tau_{cst}$  t2) =  $\tau_{cst}$  (minus t1 t2)⟩

definition ⟨one_tag_const  $\equiv \tau_{cst}$  1⟩

fun times_tag_const
  where ⟨times ( $\tau_{cst}$  t1) ( $\tau_{cst}$  t2) =  $\tau_{cst}$  (times t1 t2)⟩

definition ⟨zero_tag_const  $\equiv \tau_{cst}$  0⟩

fun plus_tag_const
  where ⟨plus ( $\tau_{cst}$  t1) ( $\tau_{cst}$  t2) =  $\tau_{cst}$  (plus t1 t2)⟩

```

instance proof

Multiplication is associative.

```

fix a::('τ::field tag_const) and b::('τ::field tag_const)
      and c::('τ::field tag_const)
obtain u where ⟨a =  $\tau_{cst}$  u⟩ using tag_const.exhaust by blast
moreover obtain v where ⟨b =  $\tau_{cst}$  v⟩ using tag_const.exhaust by blast
moreover obtain w where ⟨c =  $\tau_{cst}$  w⟩ using tag_const.exhaust by blast
ultimately show ⟨a * b * c = a * (b * c)⟩
  by (simp add: TESL.times_tag_const.simps)
next

```

Multiplication is commutative.

```

fix a::('τ::field tag_const) and b::('τ::field tag_const)
obtain u where ⟨a =  $\tau_{cst}$  u⟩ using tag_const.exhaust by blast
moreover obtain v where ⟨b =  $\tau_{cst}$  v⟩ using tag_const.exhaust by blast
ultimately show ⟨a * b = b * a⟩
  by (simp add: TESL.times_tag_const.simps)
next

```

One is neutral for multiplication.

```

fix a::('τ::field tag_const)
obtain u where ⟨a =  $\tau_{cst}$  u⟩ using tag_const.exhaust by blast
thus ⟨1 * a = a⟩
  by (simp add: TESL.times_tag_const.simps one_tag_const_def)
next

```

Addition is associative.

```

fix a::('τ::field tag_const) and b::('τ::field tag_const)
      and c::('τ::field tag_const)
obtain u where ⟨a =  $\tau_{cst}$  u⟩ using tag_const.exhaust by blast
moreover obtain v where ⟨b =  $\tau_{cst}$  v⟩ using tag_const.exhaust by blast
moreover obtain w where ⟨c =  $\tau_{cst}$  w⟩ using tag_const.exhaust by blast
ultimately show ⟨a + b + c = a + (b + c)⟩
  by (simp add: TESL.plus_tag_const.simps)
next

```

Addition is commutative.

```
fix a::('τ::field tag_const) and b::('τ::field tag_const)
obtain u where ⟨a = τcst u⟩ using tag_const.exhaust by blast
moreover obtain v where ⟨b = τcst v⟩ using tag_const.exhaust by blast
ultimately show ⟨a + b = b + a⟩
  by (simp add: TESL.plus_tag_const.simps)
next
```

Zero is neutral for addition.

```
fix a::('τ::field tag_const)
obtain u where ⟨a = τcst u⟩ using tag_const.exhaust by blast
thus ⟨0 + a = a⟩
  by (simp add: TESL.plus_tag_const.simps zero_tag_const_def)
next
```

The sum of an element and its opposite is zero.

```
fix a::('τ::field tag_const)
obtain u where ⟨a = τcst u⟩ using tag_const.exhaust by blast
thus ⟨-a + a = 0⟩
  by (simp add: TESL.plus_tag_const.simps
            TESL.uminus_tag_const.simps
            zero_tag_const_def)
next
```

Subtraction is adding the opposite.

```
fix a::('τ::field tag_const) and b::('τ::field tag_const)
obtain u where ⟨a = τcst u⟩ using tag_const.exhaust by blast
moreover obtain v where ⟨b = τcst v⟩ using tag_const.exhaust by blast
ultimately show ⟨a - b = a + -b⟩
  by (simp add: TESL.minus_tag_const.simps
            TESL.plus_tag_const.simps
            TESL.uminus_tag_const.simps)
next
```

Distributive property of multiplication over addition.

```
fix a::('τ::field tag_const) and b::('τ::field tag_const)
      and c::('τ::field tag_const)
obtain u where ⟨a = τcst u⟩ using tag_const.exhaust by blast
moreover obtain v where ⟨b = τcst v⟩ using tag_const.exhaust by blast
moreover obtain w where ⟨c = τcst w⟩ using tag_const.exhaust by blast
ultimately show ⟨(a + b) * c = a * c + b * c⟩
  by (simp add: TESL.plus_tag_const.simps
            TESL.times_tag_const.simps
            ring_class.ring_distrib(2))
next
```

The neutral elements are distinct.

```
show ⟨(0::('τ::field tag_const)) ≠ 1⟩
  by (simp add: one_tag_const_def zero_tag_const_def)
next
```

The product of an element and its inverse is 1.

```
fix a::('τ::field tag_const) assume h:⟨a ≠ 0⟩
obtain u where ⟨a = τcst u⟩ using tag_const.exhaust by blast
moreover with h have ⟨u ≠ 0⟩ by (simp add: zero_tag_const_def)
```

```

ultimately show ⟨inverse a * a = 1⟩
  by (simp add: TESL.inverse_tag_const.simps
        TESL.times_tag_const.simps
        one_tag_const_def)
next

```

Dividing is multiplying by the inverse.

```

fix a::('τ::field tag_const) and b::('τ::field tag_const)
obtain u where ⟨a = τcst u⟩ using tag_const.exhaust by blast
moreover obtain v where ⟨b = τcst v⟩ using tag_const.exhaust by blast
ultimately show ⟨a div b = a * inverse b⟩
  by (simp add: TESL.divide_tag_const.simps
        TESL.inverse_tag_const.simps
        TESL.times_tag_const.simps
        divide_inverse)
next

```

Zero is its own inverse.

```

show ⟨inverse (0::('τ::field tag_const)) = 0⟩
  by (simp add: TESL.inverse_tag_const.simps zero_tag_const_def)
qed

end

```

For comparing dates (which are represented by tags) on clocks, we need an order on tags.

```

instantiation tag_const :: (order)order
begin
  inductive less_eq_tag_const :: ⟨'a tag_const ⇒ 'a tag_const ⇒ bool⟩
  where
    Int_less_eq[simp]:      ⟨n ≤ m ⇒ (TConst n) ≤ (TConst m)⟩

  definition less_tag: ⟨(x::'a tag_const) < y ⟷ (x ≤ y) ∧ (x ≠ y)⟩

  instance proof
    show ⟨∧x y :: 'a tag_const. (x < y) = (x ≤ y ∧ ¬ y ≤ x)⟩
      using less_eq_tag_const.simps less_tag by auto
    next
      fix x::('a tag_const)
      from tag_const.exhaust obtain x0::'a where ⟨x = TConst x0⟩ by blast
      with Int_less_eq show ⟨x ≤ x⟩ by simp
    next
      show ⟨∧x y z :: 'a tag_const. x ≤ y ⇒ y ≤ z ⇒ x ≤ z⟩
        using less_eq_tag_const.simps by auto
    next
      show ⟨∧x y :: 'a tag_const. x ≤ y ⇒ y ≤ x ⇒ x = y⟩
        using less_eq_tag_const.simps by auto
  qed

end

```

For ensuring that time does never flow backwards, we need a total order on tags.

```

instantiation tag_const :: (linorder)linorder
begin
  instance proof
    fix x::('a tag_const) and y::('a tag_const)
    from tag_const.exhaust obtain x0::'a where ⟨x = TConst x0⟩ by blast
    moreover from tag_const.exhaust obtain y0::'a where ⟨y = TConst y0⟩ by blast
  end
end

```

```

      ultimately show  $\langle x \leq y \vee y \leq x \rangle$  using less_eq_tag_const.simps by fastforce
    qed

  end

end

```

## 2.2 Defining Runs

```

theory Run
imports TESL

```

```

begin

```

Runs are sequences of instants, and each instant maps a clock to a pair  $(h, t)$  where  $h$  indicates whether the clock ticks or not, and  $t$  is the current time on this clock. The first element of the pair is called the *ticks* of the clock (to tick or not to tick), the second element is called the *time*.

```

abbreviation ticks where  $\langle ticks \equiv fst \rangle$ 
abbreviation time  where  $\langle time \equiv snd \rangle$ 

```

```

type_synonym 'τ instant =  $\langle clock \Rightarrow (bool \times 'τ tag\_const) \rangle$ 

```

Runs have the additional constraint that time cannot go backwards on any clock in the sequence of instants. Therefore, for any clock, the time projection of a run is monotonous.

```

typedef (overloaded) 'τ::linordered_field run =
   $\{ \varrho :: nat \Rightarrow 'τ instant. \forall c. mono (\lambda n. time (\varrho n c)) \}$ 
proof
  show  $\langle (\lambda \_ \dots (True, \tau_{cst} 0)) \in \{ \varrho. \forall c. mono (\lambda n. time (\varrho n c)) \} \rangle$ 
    unfolding mono_def by blast
qed

```

```

lemma Abs_run_inverse_rewrite:
   $\langle \forall c. mono (\lambda n. time (\varrho n c)) \implies Rep\_run (Abs\_run \varrho) = \varrho \rangle$ 
by (simp add: Abs_run_inverse)

```

A *dense* run is a run in which something happens (at least one clock ticks) at every instant.

```

definition  $\langle dense\_run \varrho \equiv (\forall n. \exists c. ticks ((Rep\_run \varrho) n c)) \rangle$ 

```

`run_tick_count  $\varrho$  K n` counts the number of ticks on clock K in the interval  $[0, n]$  of run  $\varrho$ .

```

fun run_tick_count ::  $\langle ('τ::linordered\_field) run \Rightarrow clock \Rightarrow nat \Rightarrow nat \rangle$ 
   $\langle (\#_{\leq} \_ \_ \_ ) \rangle$ 
where
   $\langle (\#_{\leq} \varrho K 0) = (if ticks ((Rep\_run \varrho) 0 K) then 1 else 0) \rangle$ 
|  $\langle (\#_{\leq} \varrho K (Suc n)) = (if ticks ((Rep\_run \varrho) (Suc n) K) then 1 + (\#_{\leq} \varrho K n) else (\#_{\leq} \varrho K n)) \rangle$ 

```

`run_tick_count_strictly  $\varrho$  K n` counts the number of ticks on clock K in the interval  $[0, n[$  of run  $\varrho$ .

```

fun run_tick_count_strictly ::  $\langle ('τ::linordered\_field) run \Rightarrow clock \Rightarrow nat \Rightarrow nat \rangle$ 
   $\langle (\#_{<} \_ \_ \_ ) \rangle$ 
where

```

```

  ⟨(#< ρ K 0)          = 0⟩
| ⟨(#< ρ K (Suc n)) = #≤ ρ K n⟩

```

`first_time ρ K n τ` tells whether instant `n` in run `ρ` is the first one where the time on clock `K` reaches `τ`.

```

definition first_time :: ⟨'a::linordered_field run ⇒ clock ⇒ nat ⇒ 'a tag_const
                        ⇒ bool⟩

```

where

```

  ⟨first_time ρ K n τ ≡ (time ((Rep_run ρ) n K) = τ)
    ∧ (∀n'. n' < n ∧ time ((Rep_run ρ) n' K) = τ)⟩

```

The time on a clock is necessarily less than `τ` before the first instant at which it reaches `τ`.

lemma before\_first\_time:

```

  assumes ⟨first_time ρ K n τ⟩
    and ⟨m < n⟩
  shows ⟨time ((Rep_run ρ) m K) < τ⟩

```

proof -

```

  have ⟨mono (λn. time (Rep_run ρ n K))⟩ using Rep_run by blast
  moreover from assms(2) have ⟨m ≤ n⟩ using less_imp_le by simp
  moreover have ⟨mono (λn. time (Rep_run ρ n K))⟩ using Rep_run by blast
  ultimately have ⟨time ((Rep_run ρ) m K) ≤ time ((Rep_run ρ) n K)⟩
    by (simp add: mono_def)
  moreover from assms(1) have ⟨time ((Rep_run ρ) n K) = τ⟩
    using first_time_def by blast
  moreover from assms have ⟨time ((Rep_run ρ) m K) ≠ τ⟩
    using first_time_def by blast
  ultimately show ?thesis by simp

```

qed

This leads to an alternate definition of `first_time`:

lemma alt\_first\_time\_def:

```

  assumes ⟨∀m < n. time ((Rep_run ρ) m K) < τ⟩
    and ⟨time ((Rep_run ρ) n K) = τ⟩
  shows ⟨first_time ρ K n τ⟩

```

proof -

```

  from assms(1) have ⟨∀m < n. time ((Rep_run ρ) m K) ≠ τ⟩
    by (simp add: less_le)
  with assms(2) show ?thesis by (simp add: first_time_def)

```

qed

end





## Chapter 3

# Denotational Semantics

```
theory Denotational
imports
  TESL
  Run
```

```
begin
```

The denotational semantics maps TESL formulae to sets of satisfying runs. Firstly, we define the semantics of atomic formulae (basic constructs of the TESL language), then we define the semantics of compound formulae as the intersection of the semantics of their components: a run must satisfy all the individual formulae of a compound formula.

### 3.1 Denotational interpretation for atomic TESL formulae

```
fun TESL_interpretation_atomic
  :: (('τ::linordered_field) TESL_atomic ⇒ 'τ run set) (⟦ _ ⟧TESL)
where
  — K1 sporadic τ on K2 means that K1 should tick at an instant where the time on K2 is τ.
  | ⟨ ⟦ K1 sporadic τ on K2 ⟧TESL =
    { ρ. ∃ n::nat. ticks ((Rep_run ρ) n K1) ∧ time ((Rep_run ρ) n K2) = τ }
  — time-relation [K1, K2] ∈ R means that at each instant, the time on K1 and the time on K2 are in relation R.
  | ⟨ ⟦ time-relation [K1, K2] ∈ R ⟧TESL =
    { ρ. ∀ n::nat. R (time ((Rep_run ρ) n K1), time ((Rep_run ρ) n K2)) }
  — master implies slave means that at each instant at which master ticks, slave also ticks.
  | ⟨ ⟦ master implies slave ⟧TESL =
    { ρ. ∀ n::nat. ticks ((Rep_run ρ) n master) ⟶ ticks ((Rep_run ρ) n slave) }
  — master implies not slave means that at each instant at which master ticks, slave does not tick.
  | ⟨ ⟦ master implies not slave ⟧TESL =
    { ρ. ∀ n::nat. ticks ((Rep_run ρ) n master) ⟶ ¬ ticks ((Rep_run ρ) n slave) }
  — master time-delayed by δτ on measuring implies slave means that at each instant at which master ticks,
    slave will tick after a delay δτ measured on the time scale of measuring.
  | ⟨ ⟦ master time-delayed by δτ on measuring implies slave ⟧TESL =
    — When master ticks, let's call t0 the current date on measuring. Then, at the first instant when the date on
      measuring is t0 + δt, slave has to tick.
    { ρ. ∀ n. ticks ((Rep_run ρ) n master) ⟶
      (let measured_time = time ((Rep_run ρ) n measuring) in
        ∀ m ≥ n. first_time ρ measuring m (measured_time + δτ)) }
```

```

    → ticks ((Rep_run ρ) m slave)
  )
}⟩
| ⟨ master time-delayed by δτ on measuring implies slave ⟩TESL =
  — When master ticks, let's call t0 the current date on measuring. Then, slave will be ticking at some instant(s)
  when the time on measuring is t0 + δt.
  { ρ. ∀ n. ticks ((Rep_run ρ) n master) →
    (let measured_time = time ((Rep_run ρ) n measuring) in
      ∃ m ≥ n. ticks ((Rep_run ρ) m slave)
        ∧ time ((Rep_run ρ) m measuring) = measured_time + δτ
    )
  }⟩
— K1 weakly precedes K2 means that each tick on K2 must be preceded by or coincide with at least one tick
on K1. Therefore, at each instant n, the number of ticks on K2 must be less or equal to the number of ticks
on K1.
| ⟨ K1 weakly precedes K2 ⟩TESL =
  { ρ. ∀ n::nat. (run_tick_count ρ K2 n) ≤ (run_tick_count ρ K1 n) }
— K1 strictly precedes K2 means that each tick on K2 must be preceded by at least one tick on K1 at a
previous instant. Therefore, at each instant n, the number of ticks on K2 must be less or equal to the number
of ticks on K1 at instant n - 1.
| ⟨ K1 strictly precedes K2 ⟩TESL =
  { ρ. ∀ n::nat. (run_tick_count ρ K2 n) ≤ (run_tick_count_strictly ρ K1 n) }
— K1 kills K2 means that when K1 ticks, K2 cannot tick and is not allowed to tick at any further instant.
| ⟨ K1 kills K2 ⟩TESL =
  { ρ. ∀ n::nat. ticks ((Rep_run ρ) n K1)
    → (∀ m ≥ n. ¬ ticks ((Rep_run ρ) m K2)) }
— Additional constraints for the operational semantics
— K1 sporadic# (τvar (Kpast, npast) ⊕ δτ) on K2 means that K1 should tick at an instant where the time
on K2 is (τvar (Kpast, npast) ⊕ δτ).
| ⟨ K1 sporadic# (τvar (Kpast, npast) ⊕ δτ) on K2 ⟩TESL =
  { ρ. ∃ n::nat. ticks ((Rep_run ρ) n K1) ∧ time ((Rep_run ρ) n K2) = time ((Rep_run ρ) npast Kpast)
    + δτ }
— master time-delayed by δτ on measuring implies slave is similar but targets operational execution
and allow time to stagnate before triggering slave

```

## 3.2 Denotational interpretation for TESL formulae

To satisfy a formula, a run has to satisfy the conjunction of its atomic formulae. Therefore, the interpretation of a formula is the intersection of the interpretations of its components.

```

fun TESL_interpretation :: (τ::linordered_field) TESL_formula ⇒ 'τ run set
  (⟨ [ [ _ ] ]TESL ⟩)

```

where

```

  ⟨ [ [ ] ]TESL = {_. True}
  | ⟨ [ [ ϕ # Φ ] ]TESL = [ [ ϕ ] ]TESL ∩ [ [ Φ ] ]TESL

```

lemma TESL\_interpretation\_homo:

```

  ⟨ [ [ ϕ ] ]TESL ∩ [ [ Φ ] ]TESL = [ [ ϕ # Φ ] ]TESL
by simp

```

### 3.2.1 Image interpretation lemma

theorem TESL\_interpretation\_image:

```

  ⟨ [ [ Φ ] ]TESL = ⋂ ( (λϕ. [ [ ϕ ] ]TESL) ' set Φ )
by (induction Φ, simp+)

```

### 3.2.2 Expansion law

Similar to the expansion laws of lattices.

```
theorem TESL_interp_homo_append:
  ⟨[[[ Φ1 @ Φ2 ]]]TESL = [[ Φ1 ]]TESL ∩ [[ Φ2 ]]TESL⟩
by (induction Φ1, simp, auto)
```

## 3.3 Equational laws for the denotation of TESL formulae

```
lemma TESL_interp_assoc:
  ⟨[[[ (Φ1 @ Φ2) @ Φ3 ]]]TESL = [[ Φ1 @ (Φ2 @ Φ3) ]]TESL⟩
by auto
```

```
lemma TESL_interp_commute:
  shows ⟨[[[ Φ1 @ Φ2 ]]]TESL = [[ Φ2 @ Φ1 ]]TESL⟩
by (simp add: TESL_interp_homo_append inf_sup_aci(1))
```

```
lemma TESL_interp_left_commute:
  ⟨[[[ Φ1 @ (Φ2 @ Φ3) ]]]TESL = [[ Φ2 @ (Φ1 @ Φ3) ]]TESL⟩
unfolding TESL_interp_homo_append by auto
```

```
lemma TESL_interp_idem:
  ⟨[[[ Φ @ Φ ]]]TESL = [[ Φ ]]TESL⟩
using TESL_interp_homo_append by auto
```

```
lemma TESL_interp_left_idem:
  ⟨[[[ Φ1 @ (Φ1 @ Φ2) ]]]TESL = [[ Φ1 @ Φ2 ]]TESL⟩
using TESL_interp_homo_append by auto
```

```
lemma TESL_interp_right_idem:
  ⟨[[[ (Φ1 @ Φ2) @ Φ2 ]]]TESL = [[ Φ1 @ Φ2 ]]TESL⟩
unfolding TESL_interp_homo_append by auto
```

```
lemmas TESL_interp_aci = TESL_interp_commute
                        TESL_interp_assoc
                        TESL_interp_left_commute
                        TESL_interp_left_idem
```

The empty formula is the identity element.

```
lemma TESL_interp_neutral1:
  ⟨[[[ [] @ Φ ]]]TESL = [[ Φ ]]TESL⟩
by simp
```

```
lemma TESL_interp_neutral2:
  ⟨[[[ Φ @ [] ]]]TESL = [[ Φ ]]TESL⟩
by simp
```

## 3.4 Decreasing interpretation of TESL formulae

Adding constraints to a TESL formula reduces the number of satisfying runs.

```
lemma TESL_sem_decreases_head:
  ⟨[[[ Φ ]]]TESL ⊇ [[[ φ # Φ ]]]TESL⟩
by simp
```

```
lemma TESL_sem_decreases_tail:
```

$\langle \llbracket \Phi \rrbracket_{TESL} \supseteq \llbracket \Phi \circ [\varphi] \rrbracket_{TESL} \rangle$   
 by (simp add: TESL\_interp\_homo\_append)

Repeating a formula in a specification does not change the specification.

```
lemma TESL_interp_formula_stuttering:
  assumes  $\langle \varphi \in \text{set } \Phi \rangle$ 
  shows  $\langle \llbracket \varphi \# \Phi \rrbracket_{TESL} = \llbracket \Phi \rrbracket_{TESL} \rangle$ 
proof -
  have  $\langle \varphi \# \Phi = [\varphi] \circ \Phi \rangle$  by simp
  hence  $\langle \llbracket \varphi \# \Phi \rrbracket_{TESL} = \llbracket [\varphi] \rrbracket_{TESL} \cap \llbracket \Phi \rrbracket_{TESL} \rangle$ 
  using TESL_interp_homo_append by simp
  thus ?thesis using assms TESL_interpretation_image by fastforce
qed
```

Removing duplicate formulae in a specification does not change the specification.

```
lemma TESL_interp_remdups_absorb:
   $\langle \llbracket \Phi \rrbracket_{TESL} = \llbracket \text{remdups } \Phi \rrbracket_{TESL} \rangle$ 
proof (induction  $\Phi$ )
  case Cons
  thus ?case using TESL_interp_formula_stuttering by auto
qed simp
```

Specifications that contain the same formulae have the same semantics.

```
lemma TESL_interp_set_lifting:
  assumes  $\langle \text{set } \Phi = \text{set } \Phi' \rangle$ 
  shows  $\langle \llbracket \Phi \rrbracket_{TESL} = \llbracket \Phi' \rrbracket_{TESL} \rangle$ 
proof -
  have  $\langle \text{set } (\text{remdups } \Phi) = \text{set } (\text{remdups } \Phi') \rangle$ 
  by (simp add: assms)
  moreover have  $\text{fxpnt}\Phi: \langle \bigcap ((\lambda\varphi. \llbracket \varphi \rrbracket_{TESL}) ' \text{set } \Phi) = \llbracket \Phi \rrbracket_{TESL} \rangle$ 
  by (simp add: TESL_interpretation_image)
  moreover have  $\text{fxpnt}\Phi': \langle \bigcap ((\lambda\varphi. \llbracket \varphi \rrbracket_{TESL}) ' \text{set } \Phi') = \llbracket \Phi' \rrbracket_{TESL} \rangle$ 
  by (simp add: TESL_interpretation_image)
  moreover have  $\langle \bigcap ((\lambda\varphi. \llbracket \varphi \rrbracket_{TESL}) ' \text{set } \Phi) = \bigcap ((\lambda\varphi. \llbracket \varphi \rrbracket_{TESL}) ' \text{set } \Phi') \rangle$ 
  by (simp add: assms)
  ultimately show ?thesis using TESL_interp_remdups_absorb by auto
qed
```

The semantics of specifications is contravariant with respect to their inclusion.

```
theorem TESL_interp_decreases_setinc:
  assumes  $\langle \text{set } \Phi \subseteq \text{set } \Phi' \rangle$ 
  shows  $\langle \llbracket \Phi \rrbracket_{TESL} \supseteq \llbracket \Phi' \rrbracket_{TESL} \rangle$ 
proof -
  obtain  $\Phi_r$  where  $\text{decompose}: \langle \text{set } (\Phi \circ \Phi_r) = \text{set } \Phi' \rangle$  using assms by auto
  hence  $\langle \text{set } (\Phi \circ \Phi_r) = \text{set } \Phi' \rangle$  using assms by blast
  moreover have  $\langle (\text{set } \Phi) \cup (\text{set } \Phi_r) = \text{set } \Phi' \rangle$ 
  using assms decompose by auto
  moreover have  $\langle \llbracket \Phi' \rrbracket_{TESL} = \llbracket \Phi \circ \Phi_r \rrbracket_{TESL} \rangle$ 
  using TESL_interp_set_lifting decompose by blast
  moreover have  $\langle \llbracket \Phi \circ \Phi_r \rrbracket_{TESL} = \llbracket \Phi \rrbracket_{TESL} \cap \llbracket \Phi_r \rrbracket_{TESL} \rangle$ 
  by (simp add: TESL_interp_homo_append)
  moreover have  $\langle \llbracket \Phi \rrbracket_{TESL} \supseteq \llbracket \Phi \rrbracket_{TESL} \cap \llbracket \Phi_r \rrbracket_{TESL} \rangle$  by simp
  ultimately show ?thesis by simp
qed
```

```
lemma TESL_interp_decreases_add_head:
  assumes  $\langle \text{set } \Phi \subseteq \text{set } \Phi' \rangle$ 
```

```

    shows <[[[  $\varphi \# \Phi$  ]]]TESL  $\supseteq$  [[ $\varphi \# \Phi'$  ]]]TESL>
using assms TESL_interp_decreases_setinc by auto

lemma TESL_interp_decreases_add_tail:
  assumes <set  $\Phi \subseteq$  set  $\Phi'$ >
  shows <[[ $\Phi @ [\varphi]$  ]]]TESL  $\supseteq$  [[ $\Phi' @ [\varphi]$  ]]]TESL>
using TESL_interp_decreases_setinc[OF assms]
  by (simp add: TESL_interpretation_image dual_order.trans)

lemma TESL_interp_absorb1:
  assumes <set  $\Phi_1 \subseteq$  set  $\Phi_2$ >
  shows <[[ $\Phi_1 @ \Phi_2$  ]]]TESL = [[ $\Phi_2$  ]]]TESL>
by (simp add: Int_absorb1 TESL_interp_decreases_setinc
    TESL_interp_homo_append assms)

lemma TESL_interp_absorb2:
  assumes <set  $\Phi_2 \subseteq$  set  $\Phi_1$ >
  shows <[[ $\Phi_1 @ \Phi_2$  ]]]TESL = [[ $\Phi_1$  ]]]TESL>
using TESL_interp_absorb1 TESL_interp_commute assms by blast

```

### 3.5 Some special cases

```

lemma NoSporadic_stable [simp]:
  <[[ $\Phi$  ]]]TESL  $\subseteq$  [[NoSporadic  $\Phi$  ]]]TESL>
proof -
  from filter_is_subset have <set (NoSporadic  $\Phi$ )  $\subseteq$  set  $\Phi$ > .
  from TESL_interp_decreases_setinc[OF this] show ?thesis .
qed

lemma NoSporadic_idem [simp]:
  <[[ $\Phi$  ]]]TESL  $\cap$  [[NoSporadic  $\Phi$  ]]]TESL = [[ $\Phi$  ]]]TESL>
using NoSporadic_stable by blast

lemma NoSporadic_setinc:
  <set (NoSporadic  $\Phi$ )  $\subseteq$  set  $\Phi$ >
by (rule filter_is_subset)

end

```



## Chapter 4

# Symbolic Primitives for Building Runs

```
theory SymbolicPrimitive
  imports Run
```

```
begin
```

We define here the primitive constraints on runs, towards which we translate TESL specifications in the operational semantics. These constraints refer to a specific symbolic run and can therefore access properties of the run at particular instants (for instance, the fact that a clock ticks at instant  $n$  of the run, or the time on a given clock at that instant).

In the previous chapters, we had no reference to particular instants of a run because the TESL language should be invariant by stuttering in order to allow the composition of specifications: adding an instant where no clock ticks to a run that satisfies a formula should yield another run that satisfies the same formula. However, when constructing runs that satisfy a formula, we need to be able to refer to the time or ticking predicate of a clock at a given instant.

Counter expressions are used to get the number of ticks of a clock up to (strictly or not) a given instant index.

```
datatype cnt_expr =
  TickCountLess <clock> <instant_index> (<#<>)
| TickCountLeq <clock> <instant_index> (<#≤>)
```

### 4.0.1 Symbolic Primitives for Runs

```
datatype 'τ constr =
```

—  $c \Downarrow n @ \tau$  constrains clock  $c$  to have time  $\tau$  at instant  $n$  of the run.

```
  Timestamp <clock> <instant_index> ('τ tag_const) (<_ ↓ _ @ _>)
```

—  $c \Downarrow n @ \# \tau_{expr}$  constrains clock  $c$  to have time  $\tau_{expr}$  at instant  $n$  of the run.  $\tau_{expr}$  refers to the time at some previous instant on a clock

```
| TimestampTvar <clock> <instant_index> ('τ tag_expr) (<_ ↓ _ @# _>)
```

—  $m @ n \oplus \delta t \Rightarrow s$  constrains clock  $s$  to tick at the first instant at which the time on  $m$  has increased by  $\delta t$  from the value it had at instant  $n$  of the run.

```
| TimeDelay <clock> <instant_index> ('τ tag_const) <clock> (<_ @ _ ⊕ _ ⇒ _>)
```

—  $c \Uparrow n$  constrains clock  $c$  to tick at instant  $n$  of the run.

```
| Ticks <clock> <instant_index> (<_ ↑ _>)
```

—  $c \neg\uparrow n$  constrains clock  $c$  not to tick at instant  $n$  of the run.

| NotTicks (clock) (instant\_index) ( $\langle \_ \neg\uparrow \_ \rangle$ )

—  $c \neg\uparrow < n$  constrains clock  $c$  not to tick before instant  $n$  of the run.

| NotTicksUntil (clock) (instant\_index) ( $\langle \_ \neg\uparrow < \_ \rangle$ )

—  $c \neg\uparrow \geq n$  constrains clock  $c$  not to tick at and after instant  $n$  of the run.

| NotTicksFrom (clock) (instant\_index) ( $\langle \_ \neg\uparrow \geq \_ \rangle$ )

—  $[\tau_1, \tau_2] \in R$  constrains tag variables  $\tau_1$  and  $\tau_2$  to be in relation  $R$ .

| TagArith (tag\_var) (tag\_var) ( $\langle ' \tau \text{ tag\_const} \times ' \tau \text{ tag\_const} \rangle \Rightarrow \text{bool} \rangle$ ) ( $\langle \_ \_ \rangle$ )

—  $[k_1, k_2] \in R$  constrains counter expressions  $k_1$  and  $k_2$  to be in relation  $R$ .

| TickCntArith (cnt\_expr) (cnt\_expr) ( $\langle (\text{nat} \times \text{nat}) \Rightarrow \text{bool} \rangle$ ) ( $\langle \_ \_ \rangle$ )

—  $k_1 \preceq k_2$  constrains counter expression  $k_1$  to be less or equal to counter expression  $k_2$ .

| TickCntLeq (cnt\_expr) (cnt\_expr) ( $\langle \_ \preceq \_ \rangle$ )

**type\_synonym** 'τ system = ( 'τ constr list )

The abstract machine has configurations composed of:

- the past  $\Gamma$ , which captures choices that have already be made as a list of symbolic primitive constraints on the run;
- the current index  $n$ , which is the index of the present instant;
- the present  $\Psi$ , which captures the formulae that must be satisfied in the current instant;
- the future  $\Phi$ , which captures the constraints on the future of the run.

**type\_synonym** 'τ config =  
 ( 'τ system \* instant\_index \* 'τ TESL\_formula \* 'τ TESL\_formula )

## 4.1 Semantics of Primitive Constraints

The semantics of the primitive constraints is defined in a way similar to the semantics of TESL formulae.

```

fun counter_expr_eval :: ( 'τ :: linordered_field ) run  $\Rightarrow$  cnt_expr  $\Rightarrow$  nat
  ( [ [ _  $\vdash$  _ ] cnt_expr ] )
where
  ( [ [  $\varrho \vdash \# < \text{clk} \text{ indx}$  ] cnt_expr ] = run_tick_count_strictly  $\varrho$  clk indx )
  | ( [ [  $\varrho \vdash \# \leq \text{clk} \text{ indx}$  ] cnt_expr ] = run_tick_count  $\varrho$  clk indx )

fun symbolic_run_interpretation_primitive
  :: ( 'τ :: linordered_field ) constr  $\Rightarrow$  'τ run set ( [ [ _ ] prim ] )
where
  ( [ [  $K \uparrow n$  ] prim ] = {  $\varrho$ . ticks ((Rep_run  $\varrho$ ) n K) } )
  | ( [ [  $K @ n_0 \oplus \delta t \Rightarrow K'$  ] prim ] =
      {  $\varrho$ .  $\forall n \geq n_0$ . first_time  $\varrho$  K n (time ((Rep_run  $\varrho$ ) n0 K) +  $\delta t$ )
         $\longrightarrow$  ticks ((Rep_run  $\varrho$ ) n K') } )
  | ( [ [  $K \neg\uparrow n$  ] prim ] = {  $\varrho$ .  $\neg$  ticks ((Rep_run  $\varrho$ ) n K) } )
  | ( [ [  $K \neg\uparrow < n$  ] prim ] = {  $\varrho$ .  $\forall i < n$ .  $\neg$  ticks ((Rep_run  $\varrho$ ) i K) } )
  | ( [ [  $K \neg\uparrow \geq n$  ] prim ] = {  $\varrho$ .  $\forall i \geq n$ .  $\neg$  ticks ((Rep_run  $\varrho$ ) i K) } )
  | ( [ [  $K \Downarrow n @ \tau$  ] prim ] = {  $\varrho$ . time ((Rep_run  $\varrho$ ) n K) =  $\tau$  } )
  | ( [ [  $K \Downarrow n @ \#$  (  $\tau_{var}(K', n') \oplus \delta\tau$  ) ] prim ] = {  $\varrho$ . time ((Rep_run  $\varrho$ ) n K) = time ((Rep_run  $\varrho$ ) n' K') +  $\delta\tau$  } )
  | ( [ [  $\tau_{var}(K_1, n_1), \tau_{var}(K_2, n_2)$  ]  $\in R$  ] prim ] =

```



```

{ ρ. R (time ((Rep_run ρ) n₁ K₁), time ((Rep_run ρ) n₂ K₂)) }
| ⟨ [e₁, e₂] ∈ R ⟩_{prim} = { ρ. R ( [ ρ ⊢ e₁ ]_{cntexpr}, [ ρ ⊢ e₂ ]_{cntexpr} ) }
| ⟨ cnt_e₁ ≤ cnt_e₂ ⟩_{prim} = { ρ. [ ρ ⊢ cnt_e₁ ]_{cntexpr} ≤ [ ρ ⊢ cnt_e₂ ]_{cntexpr} }

```

The composition of primitive constraints is their conjunction, and we get the set of satisfying runs by intersection.

```

fun symbolic_run_interpretation
  :: ('τ::linordered_field) constr list ⇒ ('τ::linordered_field) run set
  (⟨ [ _ ] ⟩_{prim})
where
  ⟨ [ [] ] ⟩_{prim} = { ρ. True }
  | ⟨ [ γ # Γ ] ⟩_{prim} = [ γ ]_{prim} ∩ [ [ Γ ] ]_{prim}

lemma symbolic_run_interp_cons_morph:
  ⟨ [ γ ]_{prim} ∩ [ [ Γ ] ]_{prim} = [ [ γ # Γ ] ]_{prim}
by auto

definition consistent_context :: ('τ::linordered_field) constr list ⇒ bool
where
  ⟨ consistent_context Γ ≡ ( [ [ Γ ] ]_{prim} ≠ {} ) ⟩

```

#### 4.1.1 Defining a method for witness construction

In order to build a run, we can start from an initial run in which no clock ticks and the time is always 0 on any clock.

```

abbreviation initial_run :: ('τ::linordered_field) run ⇒ (⟨ ρ_0 ⟩) where
  ⟨ ρ_0 ≡ Abs_run ((λ _ . (False, τ_cst 0)) :: nat ⇒ clock ⇒ (bool × 'τ tag_const)) ⟩

```

To help avoiding that time flows backward, setting the time on a clock at a given instant sets it for the future instants too.

```

fun time_update
  :: (nat ⇒ clock ⇒ ('τ::linordered_field) tag_const ⇒ (nat ⇒ 'τ instant)
    ⇒ (nat ⇒ 'τ instant))
where
  ⟨ time_update n K τ ρ = (λ n' K'. if K = K' ∧ n ≤ n'
    then (ticks (ρ n K), τ)
    else ρ n' K') ⟩

```

## 4.2 Rules and properties of consistence

```

lemma context_consistency_preservationI:
  ⟨ consistent_context ((γ::('τ::linordered_field) constr)#Γ) ⟩ ⇒ consistent_context Γ
unfolding consistent_context_def by auto

```

— This is very restrictive

```

inductive context_independency
  :: ('τ::linordered_field) constr ⇒ 'τ constr list ⇒ bool (⟨ _ ⋈ _ ⟩)
where
  NotTicks_independency:
    ⟨ (K ⧵ n) ∉ set Γ ⟩ ⇒ ⟨ (K ⧵ n) ⋈ Γ ⟩
  | Ticks_independency:
    ⟨ (K ⧵ n) ∉ set Γ ⟩ ⇒ ⟨ (K ⧵ n) ⋈ Γ ⟩
  | Timestamp_independency:
    ⟨ (⧵ τ'. τ' = τ ∧ (K ⧵ n @ τ) ∈ set Γ) ⟩ ⇒ ⟨ (K ⧵ n @ τ) ⋈ Γ ⟩

```

## 4.3 Major Theorems

### 4.3.1 Interpretation of a context

The interpretation of a context is the intersection of the interpretation of its components.

```
theorem symrun_interp_fixpoint:
  ⟨ $\bigcap ((\lambda \gamma. \llbracket \gamma \rrbracket_{prim}) \text{ ` set } \Gamma) = \llbracket \Gamma \rrbracket_{prim}$ ⟩
by (induction  $\Gamma$ , simp+)
```

### 4.3.2 Expansion law

Similar to the expansion laws of lattices

```
theorem symrun_interp_expansion:
  ⟨ $\llbracket \Gamma_1 @ \Gamma_2 \rrbracket_{prim} = \llbracket \Gamma_1 \rrbracket_{prim} \cap \llbracket \Gamma_2 \rrbracket_{prim}$ ⟩
by (induction  $\Gamma_1$ , simp, auto)
```

## 4.4 Equations for the interpretation of symbolic primitives

### 4.4.1 General laws

```
lemma symrun_interp_assoc:
  ⟨ $\llbracket (\Gamma_1 @ \Gamma_2) @ \Gamma_3 \rrbracket_{prim} = \llbracket \Gamma_1 @ (\Gamma_2 @ \Gamma_3) \rrbracket_{prim}$ ⟩
by auto
```

```
lemma symrun_interp_commute:
  ⟨ $\llbracket \Gamma_1 @ \Gamma_2 \rrbracket_{prim} = \llbracket \Gamma_2 @ \Gamma_1 \rrbracket_{prim}$ ⟩
by (simp add: symrun_interp_expansion inf_sup_aci(1))
```

```
lemma symrun_interp_left_commute:
  ⟨ $\llbracket \Gamma_1 @ (\Gamma_2 @ \Gamma_3) \rrbracket_{prim} = \llbracket \Gamma_2 @ (\Gamma_1 @ \Gamma_3) \rrbracket_{prim}$ ⟩
unfolding symrun_interp_expansion by auto
```

```
lemma symrun_interp_idem:
  ⟨ $\llbracket \Gamma @ \Gamma \rrbracket_{prim} = \llbracket \Gamma \rrbracket_{prim}$ ⟩
using symrun_interp_expansion by auto
```

```
lemma symrun_interp_left_idem:
  ⟨ $\llbracket \Gamma_1 @ (\Gamma_1 @ \Gamma_2) \rrbracket_{prim} = \llbracket \Gamma_1 @ \Gamma_2 \rrbracket_{prim}$ ⟩
using symrun_interp_expansion by auto
```

```
lemma symrun_interp_right_idem:
  ⟨ $\llbracket (\Gamma_1 @ \Gamma_2) @ \Gamma_2 \rrbracket_{prim} = \llbracket \Gamma_1 @ \Gamma_2 \rrbracket_{prim}$ ⟩
unfolding symrun_interp_expansion by auto
```

```
lemmas symrun_interp_aci = symrun_interp_commute
                           symrun_interp_assoc
                           symrun_interp_left_commute
                           symrun_interp_left_idem
```

— Identity element

```
lemma symrun_interp_neutral1:
  ⟨ $\llbracket [] @ \Gamma \rrbracket_{prim} = \llbracket \Gamma \rrbracket_{prim}$ ⟩
by simp
```

```
lemma symrun_interp_neutral2:
  ⟨ $\llbracket \Gamma @ [] \rrbracket_{prim} = \llbracket \Gamma \rrbracket_{prim}$ ⟩
```

by simp

#### 4.4.2 Decreasing interpretation of symbolic primitives

Adding constraints to a context reduces the number of satisfying runs.

```
lemma TESL_sem_decreases_head:
   $\langle \llbracket \Gamma \rrbracket_{prim} \supseteq \llbracket \Gamma \# \gamma \rrbracket_{prim} \rangle$ 
by simp
```

```
lemma TESL_sem_decreases_tail:
   $\langle \llbracket \Gamma \rrbracket_{prim} \supseteq \llbracket \Gamma @ [\gamma] \rrbracket_{prim} \rangle$ 
by (simp add: symrun_interp_expansion)
```

Adding a constraint that is already in the context does not change the interpretation of the context.

```
lemma symrun_interp_formula_stuttering:
  assumes  $\langle \gamma \in \text{set } \Gamma \rangle$ 
  shows  $\langle \llbracket \gamma \# \Gamma \rrbracket_{prim} = \llbracket \Gamma \rrbracket_{prim} \rangle$ 
proof -
  have  $\langle \gamma \# \Gamma = [\gamma] @ \Gamma \rangle$  by simp
  hence  $\langle \llbracket \gamma \# \Gamma \rrbracket_{prim} = \llbracket [\gamma] \rrbracket_{prim} \cap \llbracket \Gamma \rrbracket_{prim} \rangle$ 
    using symrun_interp_expansion by simp
  thus ?thesis using assms symrun_interp_fixpoint by fastforce
qed
```

Removing duplicate constraints from a context does not change the interpretation of the context.

```
lemma symrun_interp_remdups_absorb:
   $\langle \llbracket \Gamma \rrbracket_{prim} = \llbracket \text{remdups } \Gamma \rrbracket_{prim} \rangle$ 
proof (induction  $\Gamma$ )
  case Cons
  thus ?case using symrun_interp_formula_stuttering by auto
qed simp
```

Two identical sets of constraints have the same interpretation, the order in the context does not matter.

```
lemma symrun_interp_set_lifting:
  assumes  $\langle \text{set } \Gamma = \text{set } \Gamma' \rangle$ 
  shows  $\langle \llbracket \Gamma \rrbracket_{prim} = \llbracket \Gamma' \rrbracket_{prim} \rangle$ 
proof -
  have  $\langle \text{set } (\text{remdups } \Gamma) = \text{set } (\text{remdups } \Gamma') \rangle$ 
    by (simp add: assms)
  moreover have  $\text{fxpnt } \Gamma: \langle \bigcap ((\lambda \gamma. \llbracket \gamma \rrbracket_{prim}) \text{ ` } \text{set } \Gamma) = \llbracket \Gamma \rrbracket_{prim} \rangle$ 
    by (simp add: symrun_interp_fixpoint)
  moreover have  $\text{fxpnt } \Gamma': \langle \bigcap ((\lambda \gamma. \llbracket \gamma \rrbracket_{prim}) \text{ ` } \text{set } \Gamma') = \llbracket \Gamma' \rrbracket_{prim} \rangle$ 
    by (simp add: symrun_interp_fixpoint)
  moreover have  $\langle \bigcap ((\lambda \gamma. \llbracket \gamma \rrbracket_{prim}) \text{ ` } \text{set } \Gamma) = \bigcap ((\lambda \gamma. \llbracket \gamma \rrbracket_{prim}) \text{ ` } \text{set } \Gamma') \rangle$ 
    by (simp add: assms)
  ultimately show ?thesis using symrun_interp_remdups_absorb by auto
qed
```

The interpretation of contexts is contravariant with regard to set inclusion.

```
theorem symrun_interp_decreases_setinc:
  assumes  $\langle \text{set } \Gamma \subseteq \text{set } \Gamma' \rangle$ 
  shows  $\langle \llbracket \Gamma \rrbracket_{prim} \supseteq \llbracket \Gamma' \rrbracket_{prim} \rangle$ 
proof -
```

```

obtain  $\Gamma_r$  where decompose:  $\langle \text{set } (\Gamma @ \Gamma_r) = \text{set } \Gamma' \rangle$  using assms by auto
hence  $\langle \text{set } (\Gamma @ \Gamma_r) = \text{set } \Gamma' \rangle$  using assms by blast
moreover have  $\langle (\text{set } \Gamma) \cup (\text{set } \Gamma_r) = \text{set } \Gamma' \rangle$  using assms decompose by auto
moreover have  $\langle \llbracket \Gamma' \rrbracket_{\text{prim}} = \llbracket \Gamma @ \Gamma_r \rrbracket_{\text{prim}} \rangle$ 
  using symrun_interp_set_lifting decompose by blast
moreover have  $\langle \llbracket \Gamma @ \Gamma_r \rrbracket_{\text{prim}} = \llbracket \Gamma \rrbracket_{\text{prim}} \cap \llbracket \Gamma_r \rrbracket_{\text{prim}} \rangle$ 
  by (simp add: symrun_interp_expansion)
moreover have  $\langle \llbracket \Gamma \rrbracket_{\text{prim}} \supseteq \llbracket \Gamma \rrbracket_{\text{prim}} \cap \llbracket \Gamma_r \rrbracket_{\text{prim}} \rangle$  by simp
ultimately show ?thesis by simp
qed

```

```

lemma symrun_interp_decreases_add_head:
  assumes  $\langle \text{set } \Gamma \subseteq \text{set } \Gamma' \rangle$ 
  shows  $\langle \llbracket \gamma \# \Gamma \rrbracket_{\text{prim}} \supseteq \llbracket \gamma \# \Gamma' \rrbracket_{\text{prim}} \rangle$ 
using symrun_interp_decreases_setinc assms by auto

```

```

lemma symrun_interp_decreases_add_tail:
  assumes  $\langle \text{set } \Gamma \subseteq \text{set } \Gamma' \rangle$ 
  shows  $\langle \llbracket \Gamma @ [\gamma] \rrbracket_{\text{prim}} \supseteq \llbracket \Gamma' @ [\gamma] \rrbracket_{\text{prim}} \rangle$ 
proof -
  from symrun_interp_decreases_setinc[OF assms] have  $\langle \llbracket \Gamma' \rrbracket_{\text{prim}} \subseteq \llbracket \Gamma \rrbracket_{\text{prim}} \rangle$  .
  thus ?thesis by (simp add: symrun_interp_expansion dual_order.trans)
qed

```

```

lemma symrun_interp_absorb1:
  assumes  $\langle \text{set } \Gamma_1 \subseteq \text{set } \Gamma_2 \rangle$ 
  shows  $\langle \llbracket \Gamma_1 @ \Gamma_2 \rrbracket_{\text{prim}} = \llbracket \Gamma_2 \rrbracket_{\text{prim}} \rangle$ 
by (simp add: Int_absorb1 symrun_interp_decreases_setinc
  symrun_interp_expansion assms)

```

```

lemma symrun_interp_absorb2:
  assumes  $\langle \text{set } \Gamma_2 \subseteq \text{set } \Gamma_1 \rangle$ 
  shows  $\langle \llbracket \Gamma_1 @ \Gamma_2 \rrbracket_{\text{prim}} = \llbracket \Gamma_1 \rrbracket_{\text{prim}} \rangle$ 
using symrun_interp_absorb1 symrun_interp_commute assms by blast

```

```

end

```

## Chapter 5

# Operational Semantics

```
theory Operational
imports
  SymbolicPrimitive
```

```
begin
```

The operational semantics defines rules to build symbolic runs from a TESL specification (a set of TESL formulae). Symbolic runs are described using the symbolic primitives presented in the previous chapter. Therefore, the operational semantics compiles a set of constraints on runs, as defined by the denotational semantics, into a set of symbolic constraints on the instants of the runs. Concrete runs can then be obtained by solving the constraints at each instant.

### 5.1 Operational steps

We introduce a notation to describe configurations:

- $\Gamma$  is the context, the set of symbolic constraints on past instants of the run;
- $n$  is the index of the current instant, the present;
- $\Psi$  is the TESL formula that must be satisfied at the current instant (present);
- $\Phi$  is the TESL formula that must be satisfied for the following instants (the future).

```
abbreviation uncurry_conf
  :: (('τ::linordered_field) system ⇒ instant_index ⇒ 'τ TESL_formula ⇒ 'τ TESL_formula
     ⇒ 'τ config)
  ((_, _ ⊢ _ ▷ _) 80)
```

```
where
  (Γ, n ⊢ Ψ ▷ Φ ≡ (Γ, n, Ψ, Φ))
```

The only introduction rule allows us to progress to the next instant when there are no more constraints to satisfy for the present instant.

```
inductive operational_semantics_intro
  :: (('τ::linordered_field) config ⇒ 'τ config ⇒ bool)
  ((_ ↦i _) 70)
where
  instant_i:
```

$$\langle \Gamma, n \vdash [] \triangleright \Phi \rangle \hookrightarrow_i \langle \Gamma, \text{Suc } n \vdash \Phi \triangleright [] \rangle$$

The elimination rules describe how TESL formulae for the present are transformed into constraints on the past and on the future.

**inductive operational\_semantics\_elim**

$::(\tau::\text{linordered\_field}) \text{ config} \Rightarrow \tau \text{ config} \Rightarrow \text{bool}$   $(\langle \_ \hookrightarrow_e \_ \rangle \ 70)$

**where**

**sporadic\_on\_e1:**

— A sporadic constraint can be ignored in the present and rejected into the future.

$$\begin{aligned} &\langle \Gamma, n \vdash ((K_1 \text{ sporadic } \tau \text{ on } K_2) \# \Psi) \triangleright \Phi \rangle \\ &\hookrightarrow_e \langle \Gamma, n \vdash \Psi \triangleright ((K_1 \text{ sporadic } \tau \text{ on } K_2) \# \Phi) \rangle \end{aligned}$$

**| sporadic\_on\_e2:**

— It can also be handled in the present by making the clock tick and have the expected time. Once it has been handled, it is no longer a constraint to satisfy, so it disappears from the future.

$$\begin{aligned} &\langle \Gamma, n \vdash ((K_1 \text{ sporadic } \tau \text{ on } K_2) \# \Psi) \triangleright \Phi \rangle \\ &\hookrightarrow_e \langle ((K_1 \uparrow n) \# (K_2 \downarrow n @ \tau) \# \Gamma), n \vdash \Psi \triangleright \Phi \rangle \end{aligned}$$

**| sporadic\_on\_tvar\_e1:**

$$\begin{aligned} &\langle \Gamma, n \vdash ((K_1 \text{ sporadic} \# \tau_{expr} \text{ on } K_2) \# \Psi) \triangleright \Phi \rangle \\ &\hookrightarrow_e \langle \Gamma, n \vdash \Psi \triangleright ((K_1 \text{ sporadic} \# \tau_{expr} \text{ on } K_2) \# \Phi) \rangle \end{aligned}$$

**| sporadic\_on\_tvar\_e2:**

$$\begin{aligned} &\langle \Gamma, n \vdash ((K_1 \text{ sporadic} \# \tau_{expr} \text{ on } K_2) \# \Psi) \triangleright \Phi \rangle \\ &\hookrightarrow_e \langle ((K_1 \uparrow n) \# (K_2 \downarrow n @ \# \tau_{expr}) \# \Gamma), n \vdash \Psi \triangleright \Phi \rangle \end{aligned}$$

**| tagrel\_e:**

— A relation between time scales has to be obeyed at every instant.

$$\begin{aligned} &\langle \Gamma, n \vdash ((\text{time-relation } [K_1, K_2] \in R) \# \Psi) \triangleright \Phi \rangle \\ &\hookrightarrow_e \langle (([\tau_{var}(K_1, n), \tau_{var}(K_2, n)] \in R) \# \Gamma), n \\ &\quad \vdash \Psi \triangleright ((\text{time-relation } [K_1, K_2] \in R) \# \Phi) \rangle \end{aligned}$$

**| implies\_e1:**

— An implication can be handled in the present by forbidding a tick of the master clock. The implication is copied back into the future because it holds for the whole run.

$$\begin{aligned} &\langle \Gamma, n \vdash ((K_1 \text{ implies } K_2) \# \Psi) \triangleright \Phi \rangle \\ &\hookrightarrow_e \langle ((K_1 \neg \uparrow n) \# \Gamma), n \vdash \Psi \triangleright ((K_1 \text{ implies } K_2) \# \Phi) \rangle \end{aligned}$$

**| implies\_e2:**

— It can also be handled in the present by making both the master and the slave clocks tick.

$$\begin{aligned} &\langle \Gamma, n \vdash ((K_1 \text{ implies } K_2) \# \Psi) \triangleright \Phi \rangle \\ &\hookrightarrow_e \langle ((K_1 \uparrow n) \# (K_2 \uparrow n) \# \Gamma), n \vdash \Psi \triangleright ((K_1 \text{ implies } K_2) \# \Phi) \rangle \end{aligned}$$

**| implies\_not\_e1:**

— A negative implication can be handled in the present by forbidding a tick of the master clock. The implication is copied back into the future because it holds for the whole run.

$$\begin{aligned} &\langle \Gamma, n \vdash ((K_1 \text{ implies not } K_2) \# \Psi) \triangleright \Phi \rangle \\ &\hookrightarrow_e \langle ((K_1 \neg \uparrow n) \# \Gamma), n \vdash \Psi \triangleright ((K_1 \text{ implies not } K_2) \# \Phi) \rangle \end{aligned}$$

**| implies\_not\_e2:**

— It can also be handled in the present by making the master clock ticks and forbidding a tick on the slave clock.

$$\begin{aligned} &\langle \Gamma, n \vdash ((K_1 \text{ implies not } K_2) \# \Psi) \triangleright \Phi \rangle \\ &\hookrightarrow_e \langle ((K_1 \uparrow n) \# (K_2 \neg \uparrow n) \# \Gamma), n \vdash \Psi \triangleright ((K_1 \text{ implies not } K_2) \# \Phi) \rangle \end{aligned}$$

**| timedelayed\_e1:**

— A timed delayed implication can be handled by forbidding a tick on the master clock.

$$\begin{aligned} &\langle \Gamma, n \vdash ((K_1 \text{ time-delayed by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Psi) \triangleright \Phi \rangle \\ &\hookrightarrow_e \langle ((K_1 \neg \uparrow n) \# \Gamma), n \vdash \Psi \triangleright ((K_1 \text{ time-delayed by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Phi) \rangle \end{aligned}$$

**| timedelayed\_e2:**

— It can also be handled by making the master clock tick and adding a constraint that makes the slave clock tick when the delay has elapsed on the measuring clock.

$$\begin{aligned} &\langle \Gamma, n \vdash ((K_1 \text{ time-delayed by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Psi) \triangleright \Phi \rangle \\ &\hookrightarrow_e \langle ((K_1 \uparrow n) \# (K_2 @ n \oplus \delta\tau \Rightarrow K_3) \# \Gamma), n \\ &\quad \vdash \Psi \triangleright ((K_1 \text{ time-delayed by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Phi) \rangle \end{aligned}$$

```

| timedelayed_tvar_e1:
  ⟨(Γ, n ⊢ ((K1 time-delayed⊔ by δτ on K2 implies K3) # Ψ) ▷ Φ)
  ↪e (((K1 ↗ n) # Γ), n ⊢ Ψ ▷ ((K1 time-delayed⊔ by δτ on K2 implies K3) # Φ))⟩
| timedelayed_tvar_e2:
  ⟨(Γ, n ⊢ ((K1 time-delayed⊔ by δτ on K2 implies K3) # Ψ) ▷ Φ)
  ↪e (((K1 ↗ n) # Γ), n ⊢ ((K3 sporadic⊔ (⊔τvar(K2, n) ⊕ δτ) on K2) # Ψ)
    ▷ ((K1 time-delayed⊔ by δτ on K2 implies K3) # Φ))⟩
| weakly_precedes_e:
  — A weak precedence relation has to hold at every instant.
  ⟨(Γ, n ⊢ ((K1 weakly precedes K2) # Ψ) ▷ Φ)
  ↪e ((([# ≤ K2 n, # ≤ K1 n] ∈ (λ(x,y). x ≤ y)) # Γ), n
    ⊢ Ψ ▷ ((K1 weakly precedes K2) # Φ))⟩
| strictly_precedes_e:
  — A strict precedence relation has to hold at every instant.
  ⟨(Γ, n ⊢ ((K1 strictly precedes K2) # Ψ) ▷ Φ)
  ↪e ((([# ≤ K2 n, # < K1 n] ∈ (λ(x,y). x ≤ y)) # Γ), n
    ⊢ Ψ ▷ ((K1 strictly precedes K2) # Φ))⟩
| kills_e1:
  — A kill can be handled by forbidding a tick of the triggering clock.
  ⟨(Γ, n ⊢ ((K1 kills K2) # Ψ) ▷ Φ)
  ↪e (((K1 ↗ n) # Γ), n ⊢ Ψ ▷ ((K1 kills K2) # Φ))⟩
| kills_e2:
  — It can also be handled by making the triggering clock tick and by forbidding any further tick of the killed
    clock.
  ⟨(Γ, n ⊢ ((K1 kills K2) # Ψ) ▷ Φ)
  ↪e (((K1 ↗ n) # (K2 ↗ n ≥ n) # Γ), n ⊢ Ψ ▷ ((K1 kills K2) # Φ))⟩

```

A step of the operational semantics is either the application of the introduction rule or the application of an elimination rule.

```

inductive operational_semantics_step
  ::('τ::linordered_field) config ⇒ 'τ config ⇒ bool)          (⟨_ ↪ _⟩ 70)
where
  intro_part:
    ⟨(Γ1, n1 ⊢ Ψ1 ▷ Φ1) ↪i (Γ2, n2 ⊢ Ψ2 ▷ Φ2)
    ⇒ (Γ1, n1 ⊢ Ψ1 ▷ Φ1) ↪ (Γ2, n2 ⊢ Ψ2 ▷ Φ2)⟩
  elims_part:
    ⟨(Γ1, n1 ⊢ Ψ1 ▷ Φ1) ↪e (Γ2, n2 ⊢ Ψ2 ▷ Φ2)
    ⇒ (Γ1, n1 ⊢ Ψ1 ▷ Φ1) ↪ (Γ2, n2 ⊢ Ψ2 ▷ Φ2)⟩

```

We introduce notations for the reflexive transitive closure of the operational semantic step, its transitive closure and its reflexive closure.

```

abbreviation operational_semantics_step_rtrancp
  ::('τ::linordered_field) config ⇒ 'τ config ⇒ bool)          (⟨_ ↪** _⟩ 70)
where
  ⟨C1 ↪** C2 ≡ operational_semantics_step** C1 C2⟩

abbreviation operational_semantics_step_trancp
  ::('τ::linordered_field) config ⇒ 'τ config ⇒ bool)          (⟨_ ↪++ _⟩ 70)
where
  ⟨C1 ↪++ C2 ≡ operational_semantics_step++ C1 C2⟩

abbreviation operational_semantics_step_reflcp
  ::('τ::linordered_field) config ⇒ 'τ config ⇒ bool)          (⟨_ ↪== _⟩ 70)
where
  ⟨C1 ↪== C2 ≡ operational_semantics_step== C1 C2⟩

```

```

abbreviation operational_semantics_step_relpowp
  ::('τ::linordered_field) config ⇒ nat ⇒ 'τ config ⇒ bool)      (⟦_⟧ ⇐ _ 70)
where
  ⟨C1 ⇐n C2 ≡ (operational_semantics_step ^^ n) C1 C2⟩

definition operational_semantics_elim_inv
  ::('τ::linordered_field) config ⇒ 'τ config ⇒ bool)              (⟦_⟧ ⇐e _ 70)
where
  ⟨C1 ⇐e C2 ≡ C2 ⇐e C1⟩

```

## 5.2 Basic Lemmas

If a configuration can be reached in  $m$  steps from a configuration that can be reached in  $n$  steps from an original configuration, then it can be reached in  $n + m$  steps from the original configuration.

```

lemma operational_semantics_trans_generalized:
  assumes ⟨C1 ⇐n C2⟩
  assumes ⟨C2 ⇐m C3⟩
  shows ⟨C1 ⇐n+m C3⟩
using relcomp.relcompI[of (operational_semantics_step ^^ n) _ _
  (operational_semantics_step ^^ m), OF assms]
by (simp add: relpowp_add)

```

We consider the set of configurations that can be reached in one operational step from a given configuration.

```

abbreviation Cnext_solve
  ::('τ::linordered_field) config ⇒ 'τ config set) (⟦Cnext _⟧)
where
  ⟨Cnext S ≡ { S'. S ⇐ S' }⟩

```

Advancing to the next instant is possible when there are no more constraints on the current instant.

```

lemma Cnext_solve_instant:
  (⟦Cnext (Γ, n ⊢ [] ▷ Φ)⟧) ⊇ { Γ, Suc n ⊢ Φ ▷ [] }
by (simp add: operational_semantics_step.simps operational_semantics_intro.instant_i)

```

The following lemmas state that the configurations produced by the elimination rules of the operational semantics belong to the configurations that can be reached in one step.

```

lemma Cnext_solve_sporadicon:
  (⟦Cnext (Γ, n ⊢ ((K1 sporadic τ on K2) # Ψ) ▷ Φ)⟧)
  ⊇ { Γ, n ⊢ Ψ ▷ ((K1 sporadic τ on K2) # Φ),
    ((K1 ↑ n) # (K2 ↓ n @ τ) # Γ), n ⊢ Ψ ▷ Φ }
by (simp add: operational_semantics_step.simps
  operational_semantics_elim.sporadic_on_e1
  operational_semantics_elim.sporadic_on_e2)

```

```

lemma Cnext_solve_sporadicon_tvar:
  (⟦Cnext (Γ, n ⊢ ((K1 sporadic# τexpr on K2) # Ψ) ▷ Φ)⟧)
  ⊇ { Γ, n ⊢ Ψ ▷ ((K1 sporadic# τexpr on K2) # Φ),
    ((K1 ↑ n) # (K2 ↓ n @# τexpr) # Γ), n ⊢ Ψ ▷ Φ }
by (simp add: operational_semantics_step.simps
  operational_semantics_elim.sporadic_on_tvar_e1
  operational_semantics_elim.sporadic_on_tvar_e2)

```



**lemma** Cnext\_solve\_tagrel:

$((C_{next} (\Gamma, n \vdash ((\text{time-relation } [K_1, K_2] \in R) \# \Psi) \triangleright \Phi))$   
 $\supseteq \{ ((\lfloor \tau_{var}(K_1, n), \tau_{var}(K_2, n) \rfloor \in R) \# \Gamma), n$   
 $\vdash \Psi \triangleright ((\text{time-relation } [K_1, K_2] \in R) \# \Phi) \}$

by (simp add: operational\_semantics\_step.simps operational\_semantics\_elim.tagrel\_e)

**lemma** Cnext\_solve\_implies:

$((C_{next} (\Gamma, n \vdash ((K_1 \text{ implies } K_2) \# \Psi) \triangleright \Phi))$   
 $\supseteq \{ ((K_1 \rightarrowtail n) \# \Gamma), n \vdash \Psi \triangleright ((K_1 \text{ implies } K_2) \# \Phi),$   
 $((K_1 \uparrow n) \# (K_2 \uparrow n) \# \Gamma), n \vdash \Psi \triangleright ((K_1 \text{ implies } K_2) \# \Phi) \}$

by (simp add: operational\_semantics\_step.simps operational\_semantics\_elim.implies\_e1  
operational\_semantics\_elim.implies\_e2)

**lemma** Cnext\_solve\_implies\_not:

$((C_{next} (\Gamma, n \vdash ((K_1 \text{ implies not } K_2) \# \Psi) \triangleright \Phi))$   
 $\supseteq \{ ((K_1 \rightarrowtail n) \# \Gamma), n \vdash \Psi \triangleright ((K_1 \text{ implies not } K_2) \# \Phi),$   
 $((K_1 \uparrow n) \# (K_2 \rightarrowtail n) \# \Gamma), n \vdash \Psi \triangleright ((K_1 \text{ implies not } K_2) \# \Phi) \}$

by (simp add: operational\_semantics\_step.simps  
operational\_semantics\_elim.implies\_not\_e1  
operational\_semantics\_elim.implies\_not\_e2)

**lemma** Cnext\_solve\_timedelayed:

$((C_{next} (\Gamma, n \vdash ((K_1 \text{ time-delayed by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Psi) \triangleright \Phi))$   
 $\supseteq \{ ((K_1 \rightarrowtail n) \# \Gamma), n \vdash \Psi \triangleright ((K_1 \text{ time-delayed by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Phi),$   
 $((K_1 \uparrow n) \# (K_2 @ n \oplus \delta\tau \Rightarrow K_3) \# \Gamma), n$   
 $\vdash \Psi \triangleright ((K_1 \text{ time-delayed by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Phi) \}$

by (simp add: operational\_semantics\_step.simps  
operational\_semantics\_elim.timedelayed\_e1  
operational\_semantics\_elim.timedelayed\_e2)

**lemma** Cnext\_solve\_timedelayed\_tvar:

$((C_{next} (\Gamma, n \vdash ((K_1 \text{ time-delayed} \bowtie \text{ by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Psi) \triangleright \Phi))$   
 $\supseteq \{ ((K_1 \rightarrowtail n) \# \Gamma), n \vdash \Psi \triangleright ((K_1 \text{ time-delayed} \bowtie \text{ by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Phi),$   
 $((K_1 \uparrow n) \# \Gamma), n$   
 $\vdash (K_3 \text{ sporadic} \# (\lfloor \tau_{var}(K_2, n) \oplus \delta\tau \rfloor \text{ on } K_2) \# \Psi$   
 $\triangleright ((K_1 \text{ time-delayed} \bowtie \text{ by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Phi) \}$

by (simp add: operational\_semantics\_step.simps  
operational\_semantics\_elim.timedelayed\_tvar\_e1  
operational\_semantics\_elim.timedelayed\_tvar\_e2)

**lemma** Cnext\_solve\_weakly\_precedes:

$((C_{next} (\Gamma, n \vdash ((K_1 \text{ weakly precedes } K_2) \# \Psi) \triangleright \Phi))$   
 $\supseteq \{ ((\lfloor \# \leq K_2 n, \# \leq K_1 n \rfloor \in (\lambda(x,y). x \leq y)) \# \Gamma), n$   
 $\vdash \Psi \triangleright ((K_1 \text{ weakly precedes } K_2) \# \Phi) \}$

by (simp add: operational\_semantics\_step.simps  
operational\_semantics\_elim.weakly\_precedes\_e)

**lemma** Cnext\_solve\_strictly\_precedes:

$((C_{next} (\Gamma, n \vdash ((K_1 \text{ strictly precedes } K_2) \# \Psi) \triangleright \Phi))$   
 $\supseteq \{ ((\lfloor \# \leq K_2 n, \# < K_1 n \rfloor \in (\lambda(x,y). x \leq y)) \# \Gamma), n$   
 $\vdash \Psi \triangleright ((K_1 \text{ strictly precedes } K_2) \# \Phi) \}$

by (simp add: operational\_semantics\_step.simps  
operational\_semantics\_elim.strictly\_precedes\_e)

**lemma** Cnext\_solve\_kills:

$((C_{next} (\Gamma, n \vdash ((K_1 \text{ kills } K_2) \# \Psi) \triangleright \Phi))$   
 $\supseteq \{ ((K_1 \rightarrowtail n) \# \Gamma), n \vdash \Psi \triangleright ((K_1 \text{ kills } K_2) \# \Phi),$   
 $((K_1 \uparrow n) \# (K_2 \rightarrowtail n) \# \Gamma), n \vdash \Psi \triangleright ((K_1 \text{ kills } K_2) \# \Phi) \}$

by (simp add: operational\_semantics\_step.simps operational\_semantics\_elim.kills\_e1)

```
operational_semantics_elim.kills_e2)
```

An empty specification can be reduced to an empty specification for an arbitrary number of steps.

```
lemma empty_spec_reductions:
   $\langle (\square, 0 \vdash \square \triangleright \square) \hookrightarrow^k (\square, k \vdash \square \triangleright \square) \rangle$ 
proof (induct k)
  case 0 thus ?case by simp
next
  case Suc thus ?case
    using instant_i operational_semantics_step.simps by fastforce
qed
end
```

## Chapter 6

# Equivalence of the Operational and Denotational Semantics

```
theory Corecursive_Prop
  imports
    SymbolicPrimitive
    Operational
    Denotational
```

```
begin
```

### 6.1 Stepwise denotational interpretation of TESL atoms

In order to prove the equivalence of the denotational and operational semantics, we need to be able to ignore the past (for which the constraints are encoded in the context) and consider only the satisfaction of the constraints from a given instant index. For this purpose, we define an interpretation of TESL formulae for a suffix of a run. That interpretation is closely related to the denotational semantics as defined in the preceding chapters.

```
fun TESL_interpretation_atomic_stepwise
  :: ('τ::linordered_field) TESL_atomic ⇒ nat ⇒ 'τ run set) (⟦ _ ⟧TESL≥ i ->)
where
  ⟨⟦ K1 sporadic τ on K2 ⟧TESL≥ i =
    {ρ. ∃n≥i. ticks ((Rep_run ρ) n K1) ∧ time ((Rep_run ρ) n K2) = τ}
| ⟨⟦ K1 sporadic# (τvar(Kpast, npast) ⊕ δτ) on K2 ⟧TESL≥ i =
    {ρ. ∃n≥i. ticks ((Rep_run ρ) n K1)
      ∧ time ((Rep_run ρ) n K2) = time ((Rep_run ρ) npast Kpast) + δτ }
| ⟨⟦ time-relation [K1, K2] ∈ R ⟧TESL≥ i =
    {ρ. ∀n≥i. R (time ((Rep_run ρ) n K1), time ((Rep_run ρ) n K2))}
| ⟨⟦ master implies slave ⟧TESL≥ i =
    {ρ. ∀n≥i. ticks ((Rep_run ρ) n master) ⟶ ticks ((Rep_run ρ) n slave)}
| ⟨⟦ master implies not slave ⟧TESL≥ i =
    {ρ. ∀n≥i. ticks ((Rep_run ρ) n master) ⟶ ¬ ticks ((Rep_run ρ) n slave)}
| ⟨⟦ master time-delayed by δτ on measuring implies slave ⟧TESL≥ i =
    {ρ. ∀n≥i. ticks ((Rep_run ρ) n master) ⟶
      (let measured_time = time ((Rep_run ρ) n measuring) in
       ∀m ≥ n. first_time ρ measuring m (measured_time + δτ)
       ⟶ ticks ((Rep_run ρ) m slave))
  )
```

```

    })
  | ⟨[ master time-delayed by  $\delta\tau$  on measuring implies slave ] $_{TESL}^{\geq i}$  =
    { $\varrho. \forall n \geq i. \text{ticks} ((\text{Rep\_run } \varrho) \text{ n master}) \longrightarrow$ 
      (let measured_time = time ((Rep_run  $\varrho$ ) n measuring) in
         $\exists m \geq n. \text{ticks} ((\text{Rep\_run } \varrho) \text{ m slave})$ 
         $\wedge \text{time} ((\text{Rep\_run } \varrho) \text{ m measuring}) = \text{measured\_time} + \delta\tau$ 
      }
    )
  | ⟨[ K1 weakly precedes K2 ] $_{TESL}^{\geq i}$  =
    { $\varrho. \forall n \geq i. (\text{run\_tick\_count } \varrho \text{ K}_2 \text{ n}) \leq (\text{run\_tick\_count } \varrho \text{ K}_1 \text{ n})$ }
  | ⟨[ K1 strictly precedes K2 ] $_{TESL}^{\geq i}$  =
    { $\varrho. \forall n \geq i. (\text{run\_tick\_count } \varrho \text{ K}_2 \text{ n}) \leq (\text{run\_tick\_count\_strictly } \varrho \text{ K}_1 \text{ n})$ }
  | ⟨[ K1 kills K2 ] $_{TESL}^{\geq i}$  =
    { $\varrho. \forall n \geq i. \text{ticks} ((\text{Rep\_run } \varrho) \text{ n K}_1) \longrightarrow (\forall m \geq n. \neg \text{ticks} ((\text{Rep\_run } \varrho) \text{ m K}_2))$ }

```

The denotational interpretation of TESL formulae can be unfolded into the stepwise interpretation.

**lemma** TESL\_interp\_unfold\_stepwise\_sporadicon:

```

  ⟨[ K1 sporadic  $\tau$  on K2 ] $_{TESL}$  =  $\bigcup \{Y. \exists n::\text{nat}. Y = [K_1 \text{ sporadic } \tau \text{ on } K_2]_{TESL}^{\geq n}\}$ 
by auto

```

**lemma** TESL\_interp\_unfold\_stepwise\_sporadicon\_tvar:

```

  ⟨[ K1 sporadic#  $\tau_{expr}$  on K2 ] $_{TESL}$  =  $\bigcup \{Y. \exists n::\text{nat}. Y = [K_1 \text{ sporadic# } \tau_{expr} \text{ on } K_2]_{TESL}^{\geq n}\}$ 
proof (induction  $\tau_{expr}$ )
  case (AddDelay x1a  $\tau$ )
  then show ?case
  proof (induction x1a)
    case (TSchematic xa)
    then show ?case
    proof (induction xa)
      case (Pair K n')
      then show ?case by auto
    qed
  qed
qed

```

**lemma** TESL\_interp\_unfold\_stepwise\_tagrelgen:

```

  ⟨[ time-relation [K1, K2]  $\in R$  ] $_{TESL}$ 
    =  $\bigcap \{Y. \exists n::\text{nat}. Y = [time-relation [K_1, K_2] \in R]_{TESL}^{\geq n}\}$ 
by auto

```

**lemma** TESL\_interp\_unfold\_stepwise\_implies:

```

  ⟨[ master implies slave ] $_{TESL}$ 
    =  $\bigcap \{Y. \exists n::\text{nat}. Y = [master \text{ implies slave } ]_{TESL}^{\geq n}\}$ 
by auto

```

**lemma** TESL\_interp\_unfold\_stepwise\_implies\_not:

```

  ⟨[ master implies not slave ] $_{TESL}$ 
    =  $\bigcap \{Y. \exists n::\text{nat}. Y = [master \text{ implies not slave } ]_{TESL}^{\geq n}\}$ 
by auto

```

**lemma** TESL\_interp\_unfold\_stepwise\_timedelayed:

```

  ⟨[ master time-delayed by  $\delta\tau$  on measuring implies slave ] $_{TESL}$ 
    =  $\bigcap \{Y. \exists n::\text{nat}. Y = [master \text{ time-delayed by } \delta\tau \text{ on measuring implies slave } ]_{TESL}^{\geq n}\}$ 
by auto

```

**lemma** TESL\_interp\_unfold\_stepwise\_timedelayed\_tvar:

```

⟦ master time-delayed by  $\delta\tau$  on measuring implies slave ⟧TESL
=  $\bigcap \{Y. \exists n::\text{nat}. Y = \llbracket \text{master time-delayed by } \delta\tau \text{ on measuring implies slave } \rrbracket_{TESL}^{\geq n}\}$ 
by auto

```

```

lemma TESL_interp_unfold_stepwise_weakly_precedes:
  ⟨ ⟦ K1 weakly precedes K2 ⟧TESL
    =  $\bigcap \{Y. \exists n::\text{nat}. Y = \llbracket K_1 \text{ weakly precedes } K_2 \rrbracket_{TESL}^{\geq n}\}$ 
  ⟩
by auto

```

```

lemma TESL_interp_unfold_stepwise_strictly_precedes:
  ⟨ ⟦ K1 strictly precedes K2 ⟧TESL
    =  $\bigcap \{Y. \exists n::\text{nat}. Y = \llbracket K_1 \text{ strictly precedes } K_2 \rrbracket_{TESL}^{\geq n}\}$ 
  ⟩
by auto

```

```

lemma TESL_interp_unfold_stepwise_kills:
  ⟨ ⟦ master kills slave ⟧TESL =  $\bigcap \{Y. \exists n::\text{nat}. Y = \llbracket \text{master kills slave } \rrbracket_{TESL}^{\geq n}\}$ 
  ⟩
by auto

```

Positive atomic formulae (the ones that create ticks from nothing) are unfolded as the union of the stepwise interpretations.

```

theorem TESL_interp_unfold_stepwise_positive_atoms:
  assumes ⟨positive_atom  $\varphi$ ⟩
  shows ⟨ ⟦  $\varphi::\tau::\text{linordered\_field TESL\_atomic}$  ⟧TESL
        =  $\bigcup \{Y. \exists n::\text{nat}. Y = \llbracket \varphi \rrbracket_{TESL}^{\geq n}\}$ 
  ⟩
proof (cases  $\varphi$ )
  case SporadicOn thus ?thesis using TESL_interp_unfold_stepwise_sporadicon by simp
next
  case SporadicOnTvar thus ?thesis using TESL_interp_unfold_stepwise_sporadicon_tvar by simp
next
  case TagRelation thus ?thesis using assms by simp
next
  case Implies thus ?thesis using assms by simp
next
  case ImpliesNot thus ?thesis using assms by simp
next
  case TimeDelayedBy thus ?thesis using assms by simp
next
  case RelaxedTimeDelayed thus ?thesis using assms by simp
next
  case WeaklyPrecedes thus ?thesis using assms by simp
next
  case StrictlyPrecedes thus ?thesis using assms by simp
next
  case Kills thus ?thesis using assms by simp
qed

```

Negative atomic formulae are unfolded as the intersection of the stepwise interpretations.

```

theorem TESL_interp_unfold_stepwise_negative_atoms:
  assumes ⟨ $\neg$  positive_atom  $\varphi$ ⟩
  shows ⟨ ⟦  $\varphi$  ⟧TESL =  $\bigcap \{Y. \exists n::\text{nat}. Y = \llbracket \varphi \rrbracket_{TESL}^{\geq n}\}$ 
  ⟩
proof (cases  $\varphi$ )
  case SporadicOn thus ?thesis using assms by simp
next
  case SporadicOnTvar thus ?thesis using assms by simp
next
  case TagRelation
  thus ?thesis using TESL_interp_unfold_stepwise_tagrelgen by simp

```

```

next
  case Implies
    thus ?thesis using TESL_interp_unfold_stepwise_implies by simp
next
  case ImpliesNot
    thus ?thesis using TESL_interp_unfold_stepwise_implies_not by simp
next
  case TimeDelayedBy
    thus ?thesis using TESL_interp_unfold_stepwise_timedelayed by simp
next
  case RelaxedTimeDelayed
    thus ?thesis using TESL_interp_unfold_stepwise_timedelayed_tvar by simp
next
  case WeaklyPrecedes
    thus ?thesis
      using TESL_interp_unfold_stepwise_weakly_precedes by simp
next
  case StrictlyPrecedes
    thus ?thesis
      using TESL_interp_unfold_stepwise_strictly_precedes by simp
next
  case Kills
    thus ?thesis
      using TESL_interp_unfold_stepwise_kills by simp
qed

```

Some useful lemmas for reasoning on properties of sequences.

```

lemma forall_nat_expansion:
  
$$\langle (\forall n \geq (n_0 :: \text{nat}). P\ n) = (P\ n_0 \wedge (\forall n \geq \text{Suc}\ n_0. P\ n)) \rangle$$

proof -
  have  $\langle (\forall n \geq (n_0 :: \text{nat}). P\ n) = (\forall n. (n = n_0 \vee n > n_0) \longrightarrow P\ n) \rangle$ 
    using le_less by blast
  also have  $\langle \dots = (P\ n_0 \wedge (\forall n > n_0. P\ n)) \rangle$  by blast
  finally show ?thesis using Suc_le_eq by simp
qed

```

```

lemma exists_nat_expansion:
  
$$\langle (\exists n \geq (n_0 :: \text{nat}). P\ n) = (P\ n_0 \vee (\exists n \geq \text{Suc}\ n_0. P\ n)) \rangle$$

proof -
  have  $\langle (\exists n \geq (n_0 :: \text{nat}). P\ n) = (\exists n. (n = n_0 \vee n > n_0) \wedge P\ n) \rangle$ 
    using le_less by blast
  also have  $\langle \dots = (\exists n. (P\ n_0) \vee (n > n_0 \wedge P\ n)) \rangle$  by blast
  finally show ?thesis using Suc_le_eq by simp
qed

```

```

lemma forall_nat_set_suc:  $\langle \{x. \forall m \geq n. P\ x\ m\} = \{x. P\ x\ n\} \cap \{x. \forall m \geq \text{Suc}\ n. P\ x\ m\} \rangle$ 
proof
  { fix x assume h:  $\langle x \in \{x. \forall m \geq n. P\ x\ m\} \rangle$ 
    hence  $\langle P\ x\ n \rangle$  by simp
    moreover from h have  $\langle x \in \{x. \forall m \geq \text{Suc}\ n. P\ x\ m\} \rangle$  by simp
    ultimately have  $\langle x \in \{x. P\ x\ n\} \cap \{x. \forall m \geq \text{Suc}\ n. P\ x\ m\} \rangle$  by simp
  } thus  $\langle \{x. \forall m \geq n. P\ x\ m\} \subseteq \{x. P\ x\ n\} \cap \{x. \forall m \geq \text{Suc}\ n. P\ x\ m\} \rangle$  ..
next
  { fix x assume h:  $\langle x \in \{x. P\ x\ n\} \cap \{x. \forall m \geq \text{Suc}\ n. P\ x\ m\} \rangle$ 
    hence  $\langle P\ x\ n \rangle$  by simp
    moreover from h have  $\langle \forall m \geq \text{Suc}\ n. P\ x\ m \rangle$  by simp
    ultimately have  $\langle \forall m \geq n. P\ x\ m \rangle$  using forall_nat_expansion by blast
    hence  $\langle x \in \{x. \forall m \geq n. P\ x\ m\} \rangle$  by simp
  }

```

```

} thus ⟨{x. P x n} ∩ {x. ∀m ≥ Suc n. P x m} ⊆ {x. ∀m ≥ n. P x m}⟩ ..
qed

lemma exists_nat_set_suc: ⟨{x. ∃m ≥ n. P x m} = {x. P x n} ∪ {x. ∃m ≥ Suc n. P x m}⟩
proof
  { fix x assume h: ⟨x ∈ {x. ∃m ≥ n. P x m}⟩
    hence ⟨x ∈ {x. ∃m. (m = n ∨ m ≥ Suc n) ∧ P x m}⟩
      using Suc_le_eq antisym_conv2 by fastforce
    hence ⟨x ∈ {x. P x n} ∪ {x. ∃m ≥ Suc n. P x m}⟩ by blast
  } thus ⟨{x. ∃m ≥ n. P x m} ⊆ {x. P x n} ∪ {x. ∃m ≥ Suc n. P x m}⟩ ..
next
  { fix x assume h: ⟨x ∈ {x. P x n} ∪ {x. ∃m ≥ Suc n. P x m}⟩
    hence ⟨x ∈ {x. ∃m ≥ n. P x m}⟩ using Suc_leD by blast
  } thus ⟨{x. P x n} ∪ {x. ∃m ≥ Suc n. P x m} ⊆ {x. ∃m ≥ n. P x m}⟩ ..
qed

```

## 6.2 Coinduction Unfolding Properties

The following lemmas show how to shorten a suffix, i.e. to unfold one instant in the construction of a run. They correspond to the rules of the operational semantics.

```

lemma TESL_interp_stepwise_sporadicon_coind_unfold:
  ⟨[ [ K1 sporadic τ on K2 ] ]_{TESL}^{≥ n} =
    [ [ K1 ↑ n ] ]_{prim} ∩ [ [ K2 ↓ n @ τ ] ]_{prim} — rule sporadic_on_e2
    ∪ [ [ K1 sporadic τ on K2 ] ]_{TESL}^{≥ Suc n} — rule sporadic_on_e1
  unfolding TESL_interpretation_atomic_stepwise.simps(1)
    symbolic_run_interpretation_primitive.simps(1,6)
  using exists_nat_set_suc[of ⟨n⟩ ⟨λϱ n. ticks (Rep_run ϱ n K1)
    ∧ time (Rep_run ϱ n K2) = τ⟩]
  by (simp add: Collect_conj_eq)

lemma TESL_interp_stepwise_sporadicon_tvar_coind_unfold:
  ⟨[ [ K1 sporadic# (τ_{var}(K, n') ⊕ τ) on K2 ] ]_{TESL}^{≥ n} =
    [ [ K1 ↑ n ] ]_{prim} ∩ [ [ K2 ↓ n @# (τ_{var}(K, n') ⊕ τ) ] ]_{prim}
    ∪ [ [ K1 sporadic# (τ_{var}(K, n') ⊕ τ) on K2 ] ]_{TESL}^{≥ Suc n}
  proof -
    have ⟨{ ϱ. ∃m ≥ n. ticks ((Rep_run ϱ) m K1) = True ∧ time ((Rep_run ϱ) m K2) = time ((Rep_run ϱ) n' K) + τ }
      = { ϱ. ticks ((Rep_run ϱ) n K1) = True ∧ time ((Rep_run ϱ) n K2) = time ((Rep_run ϱ) n' K) + τ
        ∨ (∃m ≥ Suc n. ticks ((Rep_run ϱ) m K1) = True ∧ time ((Rep_run ϱ) m K2) = time ((Rep_run ϱ) n' K) + τ) }⟩
      using Suc_leD not_less_eq_eq by fastforce
    then show ?thesis by auto
  qed

lemma TESL_interp_stepwise_sporadicon_tvar_coind_unfold2:
  ⟨[ [ K1 sporadic# τ_{expr} on K2 ] ]_{TESL}^{≥ n} =
    [ [ K1 ↑ n ] ]_{prim} ∩ [ [ K2 ↓ n @# τ_{expr} ] ]_{prim} — rule sporadic_on_tvar_e2
    ∪ [ [ K1 sporadic# τ_{expr} on K2 ] ]_{TESL}^{≥ Suc n} — rule sporadic_on_tvar_e1
  proof -
    from tag_expr.exhaust obtain v τ where ⟨τ_{expr} = (v ⊕ τ)⟩ by blast
    moreover from tag_var.exhaust obtain K n where ⟨v = τ_{var}(K, n)⟩ by auto
    ultimately have ⟨τ_{expr} = (τ_{var}(K, n) ⊕ τ)⟩ by simp
    thus ?thesis using TESL_interp_stepwise_sporadicon_tvar_coind_unfold by blast
  qed

lemma TESL_interp_stepwise_tagrel_coind_unfold:

```

```

⟦ time-relation [K1, K2] ∈ R ⟧TESL≥ n = — rule tagrel_e
  ( ⟦ [τvar(K1, n), τvar(K2, n)] ∈ R ⟧prim
    ∩ ⟦ time-relation [K1, K2] ∈ R ⟧TESL≥ Suc n )
proof -
  have ⟨{ℓ. ∀m ≥ n. R (time ((Rep_run ℓ) m K1), time ((Rep_run ℓ) m K2))}
    = {ℓ. R (time ((Rep_run ℓ) n K1), time ((Rep_run ℓ) n K2))}
    ∩ {ℓ. ∀m ≥ Suc n. R (time ((Rep_run ℓ) m K1), time ((Rep_run ℓ) m K2))}⟩
    using forall_nat_set_suc[of ⟨n⟩ ⟨λx y. R (time ((Rep_run x) y K1),
      time ((Rep_run x) y K2))⟩] by simp
  thus ?thesis by auto
qed

lemma TESL_interp_stepwise_implies_coind_unfold:
  ( ⟦ master implies slave ⟧TESL≥ n =
    ( ⟦ master ↗ n ⟧prim — rule implies_e1
      ∪ ⟦ master ↑ n ⟧prim ∩ ⟦ slave ↑ n ⟧prim — rule implies_e2
    )
    ∩ ⟦ master implies slave ⟧TESL≥ Suc n )
proof -
  have ⟨{ℓ. ∀m ≥ n. ticks ((Rep_run ℓ) m master) ⟶ ticks ((Rep_run ℓ) m slave)}
    = {ℓ. ticks ((Rep_run ℓ) n master) ⟶ ticks ((Rep_run ℓ) n slave)}
    ∩ {ℓ. ∀m ≥ Suc n. ticks ((Rep_run ℓ) m master)
      ⟶ ticks ((Rep_run ℓ) m slave)}⟩
    using forall_nat_set_suc[of ⟨n⟩ ⟨λx y. ticks ((Rep_run x) y master)
      ⟶ ticks ((Rep_run x) y slave)⟩] by simp
  thus ?thesis by auto
qed

lemma TESL_interp_stepwise_implies_not_coind_unfold:
  ( ⟦ master implies not slave ⟧TESL≥ n =
    ( ⟦ master ↗ n ⟧prim — rule implies_not_e1
      ∪ ⟦ master ↑ n ⟧prim ∩ ⟦ slave ↗ n ⟧prim — rule implies_not_e2
    )
    ∩ ⟦ master implies not slave ⟧TESL≥ Suc n )
proof -
  have ⟨{ℓ. ∀m ≥ n. ticks ((Rep_run ℓ) m master) ⟶ ¬ ticks ((Rep_run ℓ) m slave)}
    = {ℓ. ticks ((Rep_run ℓ) n master) ⟶ ¬ ticks ((Rep_run ℓ) n slave)}
    ∩ {ℓ. ∀m ≥ Suc n. ticks ((Rep_run ℓ) m master)
      ⟶ ¬ ticks ((Rep_run ℓ) m slave)}⟩
    using forall_nat_set_suc[of ⟨n⟩ ⟨λx y. ticks ((Rep_run x) y master)
      ⟶ ¬ ticks ((Rep_run x) y slave)⟩] by simp
  thus ?thesis by auto
qed

lemma TESL_interp_stepwise_timedelayed_coind_unfold:
  ( ⟦ master time-delayed by δτ on measuring implies slave ⟧TESL≥ n =
    ( ⟦ master ↗ n ⟧prim — rule timedelayed_e1
      ∪ ( ⟦ master ↑ n ⟧prim ∩ ⟦ measuring @ n ⊕ δτ ⇒ slave ⟧prim )
      — rule timedelayed_e2
    )
    ∩ ⟦ master time-delayed by δτ on measuring implies slave ⟧TESL≥ Suc n )
proof -
  let ?prop = ⟨λℓ m. ticks ((Rep_run ℓ) m master) ⟶
    (let measured_time = time ((Rep_run ℓ) m measuring) in
      ∀p ≥ m. first_time ℓ measuring p (measured_time + δτ)
      ⟶ ticks ((Rep_run ℓ) p slave))⟩
  have ⟨{ℓ. ∀m ≥ n. ?prop ℓ m} = {ℓ. ?prop ℓ n} ∩ {ℓ. ∀m ≥ Suc n. ?prop ℓ m}⟩
    using forall_nat_set_suc[of ⟨n⟩ ?prop] by blast
  also have ⟨... = {ℓ. ?prop ℓ n}
    ∩ ⟦ master time-delayed by δτ on measuring implies slave ⟧TESL≥ Suc n )

```



```

    by simp
    finally show ?thesis by auto
qed

```

```

lemma nat_set_suc:  $\{x. \forall m \geq n. P \ x \ m\} = \{x. P \ x \ n\} \cap \{x. \forall m \geq \text{Suc } n. P \ x \ m\}$ 

```

```

proof

```

```

  { fix x
    assume h:  $\langle x \in \{x. \forall m \geq n. P \ x \ m\} \rangle$ 
    hence  $\langle P \ x \ n \rangle$  by simp
    moreover from h have  $\langle x \in \{x. \forall m \geq \text{Suc } n. P \ x \ m\} \rangle$  by simp
    ultimately have  $\langle x \in \{x. P \ x \ n\} \cap \{x. \forall m \geq \text{Suc } n. P \ x \ m\} \rangle$  by simp
  } thus  $\langle \{x. \forall m \geq n. P \ x \ m\} \subseteq \{x. P \ x \ n\} \cap \{x. \forall m \geq \text{Suc } n. P \ x \ m\} \rangle$  ..

```

```

next

```

```

  { fix x
    assume h:  $\langle x \in \{x. P \ x \ n\} \cap \{x. \forall m \geq \text{Suc } n. P \ x \ m\} \rangle$ 
    hence  $\langle P \ x \ n \rangle$  by simp
    moreover from h have  $\langle \forall m \geq \text{Suc } n. P \ x \ m \rangle$  by simp
    ultimately have  $\langle \forall m \geq n. P \ x \ m \rangle$  using forall_nat_expansion by blast
    hence  $\langle x \in \{x. \forall m \geq n. P \ x \ m\} \rangle$  by simp
  } thus  $\langle \{x. P \ x \ n\} \cap \{x. \forall m \geq \text{Suc } n. P \ x \ m\} \subseteq \{x. \forall m \geq n. P \ x \ m\} \rangle$  ..

```

```

qed

```

```

lemma TESL_interp_stepwise_timedelayed_tvar_coind_unfold:

```

```

   $\langle \llbracket \text{master time-delayed} \bowtie \text{by } \delta\tau \text{ on measuring implies slave } \rrbracket_{TESL}^{\geq n} =$ 
  (
     $\llbracket \text{master } \uparrow n \rrbracket_{prim}$  — rule timedelayed_tvar_e1
     $\cup$  ( $\llbracket \text{master } \uparrow n \rrbracket_{prim} \cap \llbracket \text{slave sporadic} \# (\tau_{var}(\text{measuring}, n) \oplus \delta\tau) \text{ on measuring } \rrbracket_{TESL}^{\geq n}$ )
    — rule timedelayed_tvar_e2
  )

```

```

   $\cap \llbracket \text{master time-delayed} \bowtie \text{by } \delta\tau \text{ on measuring implies slave } \rrbracket_{TESL}^{\geq \text{Suc } n}$ 

```

```

proof -

```

```

  have  $\langle \{ \varrho. \forall m \geq n. \text{ticks } ((\text{Rep\_run } \varrho) \ m \ \text{master}) \longrightarrow$ 
    (let measured_time = time ((Rep_run  $\varrho$ ) m measuring) in
     $\exists p \geq m. \text{ticks } ((\text{Rep\_run } \varrho) \ p \ \text{slave})$ 
     $\wedge \text{time } ((\text{Rep\_run } \varrho) \ p \ \text{measuring}) = \text{measured\_time} + \delta\tau \} \rangle$ 
  =  $\{ \varrho. \text{ticks } ((\text{Rep\_run } \varrho) \ n \ \text{master}) \longrightarrow$ 
    (let measured_time = time ((Rep_run  $\varrho$ ) n measuring) in
     $\exists p \geq n. \text{ticks } ((\text{Rep\_run } \varrho) \ p \ \text{slave})$ 
     $\wedge \text{time } ((\text{Rep\_run } \varrho) \ p \ \text{measuring}) = \text{measured\_time} + \delta\tau \} \rangle$ 
   $\cap \{ \varrho. \forall m \geq \text{Suc } n. \text{ticks } ((\text{Rep\_run } \varrho) \ m \ \text{master}) \longrightarrow$ 
    (let measured_time = time ((Rep_run  $\varrho$ ) m measuring) in
     $\exists p \geq m. \text{ticks } ((\text{Rep\_run } \varrho) \ p \ \text{slave})$ 
     $\wedge \text{time } ((\text{Rep\_run } \varrho) \ p \ \text{measuring}) = \text{measured\_time} + \delta\tau \} \rangle$ 
  using nat_set_suc[of  $\langle n \rangle$   $\langle \lambda x y. \text{ticks } ((\text{Rep\_run } x) \ y \ \text{master}) \longrightarrow$ 
    (let measured_time = time ((Rep_run x) y measuring) in
     $\exists p \geq y. \text{ticks } ((\text{Rep\_run } x) \ p \ \text{slave})$ 
     $\wedge \text{time } ((\text{Rep\_run } x) \ p \ \text{measuring}) = \text{measured\_time} + \delta\tau \rangle]$  by simp

```

```

  then show ?thesis by auto

```

```

qed

```

```

lemma TESL_interp_stepwise_weakly_precedes_coind_unfold:

```

```

   $\langle \llbracket K_1 \text{ weakly precedes } K_2 \rrbracket_{TESL}^{\geq n} =$  — rule weakly_precedes_e
   $\llbracket (\# \leq K_2 \ n, \# \leq K_1 \ n) \in (\lambda(x,y). x \leq y) \rrbracket_{prim}$ 
   $\cap \llbracket K_1 \text{ weakly precedes } K_2 \rrbracket_{TESL}^{\geq \text{Suc } n}$ 

```

```

proof -

```

```

  have  $\langle \{ \varrho. \forall p \geq n. (\text{run\_tick\_count } \varrho \ K_2 \ p) \leq (\text{run\_tick\_count } \varrho \ K_1 \ p) \} \rangle$ 
  =  $\{ \varrho. (\text{run\_tick\_count } \varrho \ K_2 \ n) \leq (\text{run\_tick\_count } \varrho \ K_1 \ n) \} \rangle$ 
   $\cap \{ \varrho. \forall p \geq \text{Suc } n. (\text{run\_tick\_count } \varrho \ K_2 \ p) \leq (\text{run\_tick\_count } \varrho \ K_1 \ p) \} \rangle$ 
  using forall_nat_set_suc[of  $\langle n \rangle$   $\langle \lambda \varrho \ n. (\text{run\_tick\_count } \varrho \ K_2 \ n) \leq (\text{run\_tick\_count } \varrho \ K_1 \ n) \rangle]$ 

```

by simp  
 thus ?thesis by auto  
 qed

lemma TESL\_interp\_stepwise\_strictly\_precedes\_coind\_unfold:

$\langle \llbracket K_1 \text{ strictly precedes } K_2 \rrbracket_{TESL}^{\geq n} = \text{--- rule strictly\_precedes\_e}$   
 $\llbracket (\# \leq K_2 \ n, \# < K_1 \ n) \in (\lambda(x,y). x \leq y) \rrbracket_{prim}$   
 $\cap \llbracket K_1 \text{ strictly precedes } K_2 \rrbracket_{TESL}^{\geq \text{Suc } n}$

proof -

have  $\langle \{ \varrho. \forall p \geq n. (\text{run\_tick\_count } \varrho \ K_2 \ p) \leq (\text{run\_tick\_count\_strictly } \varrho \ K_1 \ p) \}$   
 $= \{ \varrho. (\text{run\_tick\_count } \varrho \ K_2 \ n) \leq (\text{run\_tick\_count\_strictly } \varrho \ K_1 \ n) \}$   
 $\cap \{ \varrho. \forall p \geq \text{Suc } n. (\text{run\_tick\_count } \varrho \ K_2 \ p) \leq (\text{run\_tick\_count\_strictly } \varrho \ K_1 \ p) \}$   
 using forall\_nat\_set\_suc[of  $\langle n \rangle$ ]  $\langle \lambda \varrho \ n. (\text{run\_tick\_count } \varrho \ K_2 \ n)$   
 $\leq (\text{run\_tick\_count\_strictly } \varrho \ K_1 \ n) \rangle$

by simp  
 thus ?thesis by auto  
 qed

lemma TESL\_interp\_stepwise\_kills\_coind\_unfold:

$\langle \llbracket K_1 \text{ kills } K_2 \rrbracket_{TESL}^{\geq n} =$   
 $( \llbracket K_1 \neg \uparrow n \rrbracket_{prim} \text{--- rule kills\_e1}$   
 $\cup \llbracket K_1 \uparrow n \rrbracket_{prim} \cap \llbracket K_2 \neg \uparrow \geq n \rrbracket_{prim} ) \text{--- rule kills\_e2}$   
 $\cap \llbracket K_1 \text{ kills } K_2 \rrbracket_{TESL}^{\geq \text{Suc } n}$

proof -

let ?kills =  $\langle \lambda n \ \varrho. \forall p \geq n. \text{ticks } ((\text{Rep\_run } \varrho) \ p \ K_1)$   
 $\longrightarrow (\forall m \geq p. \neg \text{ticks } ((\text{Rep\_run } \varrho) \ m \ K_2)) \rangle$

let ?ticks =  $\langle \lambda n \ \varrho \ c. \text{ticks } ((\text{Rep\_run } \varrho) \ n \ c) \rangle$

let ?dead =  $\langle \lambda n \ \varrho \ c. \forall m \geq n. \neg \text{ticks } ((\text{Rep\_run } \varrho) \ m \ c) \rangle$

have  $\langle \llbracket K_1 \text{ kills } K_2 \rrbracket_{TESL}^{\geq n} = \{ \varrho. ?kills \ n \ \varrho \} \rangle$  by simp

also have  $\langle \dots = (\{ \varrho. \neg ?ticks \ n \ \varrho \ K_1 \} \cap \{ \varrho. ?kills \ (\text{Suc } n) \ \varrho \})$   
 $\cup (\{ \varrho. ?ticks \ n \ \varrho \ K_1 \} \cap \{ \varrho. ?dead \ n \ \varrho \ K_2 \}) \rangle$

proof

{ fix  $\varrho :: ('a :: \text{linordered\_field}) \text{run}$   
 assume  $\langle \varrho \in \{ \varrho. ?kills \ n \ \varrho \} \rangle$   
 hence  $\langle ?kills \ n \ \varrho \rangle$  by simp  
 hence  $\langle (?ticks \ n \ \varrho \ K_1 \wedge ?dead \ n \ \varrho \ K_2) \vee (\neg ?ticks \ n \ \varrho \ K_1 \wedge ?kills \ (\text{Suc } n) \ \varrho) \rangle$   
 using Suc\_leD by blast  
 hence  $\langle \varrho \in (\{ \varrho. ?ticks \ n \ \varrho \ K_1 \} \cap \{ \varrho. ?dead \ n \ \varrho \ K_2 \})$   
 $\cup (\{ \varrho. \neg ?ticks \ n \ \varrho \ K_1 \} \cap \{ \varrho. ?kills \ (\text{Suc } n) \ \varrho \}) \rangle$   
 by blast  
 } thus  $\langle \{ \varrho. ?kills \ n \ \varrho \}$   
 $\subseteq \{ \varrho. \neg ?ticks \ n \ \varrho \ K_1 \} \cap \{ \varrho. ?kills \ (\text{Suc } n) \ \varrho \}$   
 $\cup \{ \varrho. ?ticks \ n \ \varrho \ K_1 \} \cap \{ \varrho. ?dead \ n \ \varrho \ K_2 \} \rangle$  by blast

next

{ fix  $\varrho :: ('a :: \text{linordered\_field}) \text{run}$   
 assume  $\langle \varrho \in (\{ \varrho. \neg ?ticks \ n \ \varrho \ K_1 \} \cap \{ \varrho. ?kills \ (\text{Suc } n) \ \varrho \})$   
 $\cup (\{ \varrho. ?ticks \ n \ \varrho \ K_1 \} \cap \{ \varrho. ?dead \ n \ \varrho \ K_2 \}) \rangle$   
 hence  $\langle \neg ?ticks \ n \ \varrho \ K_1 \wedge ?kills \ (\text{Suc } n) \ \varrho$   
 $\vee ?ticks \ n \ \varrho \ K_1 \wedge ?dead \ n \ \varrho \ K_2 \rangle$  by blast  
 moreover have  $\langle (\neg ?ticks \ n \ \varrho \ K_1) \wedge (?kills \ (\text{Suc } n) \ \varrho) \longrightarrow ?kills \ n \ \varrho \rangle$   
 using dual\_order.antisym not\_less\_eq\_eq by blast  
 ultimately have  $\langle ?kills \ n \ \varrho \vee ?ticks \ n \ \varrho \ K_1 \wedge ?dead \ n \ \varrho \ K_2 \rangle$  by blast  
 hence  $\langle ?kills \ n \ \varrho \rangle$  using le\_trans by blast  
 } thus  $\langle (\{ \varrho. \neg ?ticks \ n \ \varrho \ K_1 \} \cap \{ \varrho. ?kills \ (\text{Suc } n) \ \varrho \})$   
 $\cup (\{ \varrho. ?ticks \ n \ \varrho \ K_1 \} \cap \{ \varrho. ?dead \ n \ \varrho \ K_2 \})$   
 $\subseteq \{ \varrho. ?kills \ n \ \varrho \} \rangle$  by blast

qed

also have  $\langle \dots = \{ \varrho. \neg ?ticks \ n \ \varrho \ K_1 \} \cap \{ \varrho. ?kills \ (\text{Suc } n) \ \varrho \}$

```

      ∪ { $\varrho$ . ?ticks  $n$   $\varrho$   $K_1$ } ∩ { $\varrho$ . ?dead  $n$   $\varrho$   $K_2$ } ∩ { $\varrho$ . ?kills (Suc  $n$ )  $\varrho$ }
    using Collect_cong Collect_disj_eq by auto
  also have ⟨... =  $\llbracket K_1 \neg\uparrow n \rrbracket_{prim} \cap \llbracket K_1 \text{ kills } K_2 \rrbracket_{TESL}^{\geq \text{Suc } n}$ 
      ∪  $\llbracket K_1 \uparrow n \rrbracket_{prim} \cap \llbracket K_2 \neg\uparrow \geq n \rrbracket_{prim}$ 
      ∩  $\llbracket K_1 \text{ kills } K_2 \rrbracket_{TESL}^{\geq \text{Suc } n}$ ⟩ by simp
  finally show ?thesis by blast
qed

```

The stepwise interpretation of a TESL formula is the intersection of the interpretation of its atomic components.

```

fun TESL_interpretation_stepwise
  :: (' $\tau$ ::linordered_field TESL_formula  $\Rightarrow$  nat  $\Rightarrow$  ' $\tau$  run set)
  (⟨ $\llbracket \_ \rrbracket_{TESL}^{\geq \_}$ ⟩)
where
  ⟨ $\llbracket \Box \rrbracket_{TESL}^{\geq n} = \{\varrho. \text{True}\}$ ⟩
| ⟨ $\llbracket \varphi \# \Phi \rrbracket_{TESL}^{\geq n} = \llbracket \varphi \rrbracket_{TESL}^{\geq n} \cap \llbracket \Phi \rrbracket_{TESL}^{\geq n}$ ⟩

lemma TESL_interpretation_stepwise_fixpoint:
  ⟨ $\llbracket \Phi \rrbracket_{TESL}^{\geq n} = \bigcap ((\lambda\varphi. \llbracket \varphi \rrbracket_{TESL}^{\geq n}) \text{ ` set } \Phi)$ ⟩
by (induction  $\Phi$ , simp, auto)

```

The global interpretation of a TESL formula is its interpretation starting at the first instant.

```

lemma TESL_interpretation_stepwise_zero:
  ⟨ $\llbracket \varphi \rrbracket_{TESL} = \llbracket \varphi \rrbracket_{TESL}^{\geq 0}$ ⟩
proof (induction  $\varphi$ )
case (SporadicOn  $x_1$   $x_2$   $x_3$ )
  then show ?case by simp
next
case (SporadicOnTvar  $K_1$   $\tau_{expr}$   $K_2$ )
  then show ?case
  proof (induction  $\tau_{expr}$ )
    case (AddDelay  $\tau_{var0}$   $\delta\tau$ )
      then show ?case
      proof (induction  $\tau_{var0}$ )
        case (TSchematic tuple)
          then show ?case
          proof (induction tuple)
            case (Pair  $K_{past}$   $n_{past}$ )
              then show ?case by simp
          qed
        qed
      qed
    qed
  qed
next
case (TagRelation  $x_1$   $x_2$   $x_3$ )
  then show ?case by simp
next
case (Implies  $x_1$   $x_2$ )
  then show ?case by simp
next
case (ImpliesNot  $x_1$   $x_2$ )
  then show ?case by simp
next
case (TimeDelayedBy  $x_1$   $x_2$   $x_3$   $x_4$ )
  then show ?case by simp
next
case (RelaxedTimeDelayed  $x_1$   $x_2$   $x_3$   $x_4$ )
  then show ?case by simp
next

```

```

    case (WeaklyPrecedes x1 x2)
    then show ?case by simp
next
    case (StrictlyPrecedes x1 x2)
    then show ?case by simp
next
    case (Kills x1 x2)
    then show ?case by simp
qed

lemma TESL_interpretation_stepwise_zero':
   $\langle \llbracket \Phi \rrbracket_{TESL} = \llbracket \Phi \rrbracket_{TESL}^{\geq 0} \rangle$ 
by (induction  $\Phi$ , simp, simp add: TESL_interpretation_stepwise_zero)

lemma TESL_interpretation_stepwise_cons_morph:
   $\langle \llbracket \varphi \rrbracket_{TESL}^{\geq n} \cap \llbracket \Phi \rrbracket_{TESL}^{\geq n} = \llbracket \varphi \# \Phi \rrbracket_{TESL}^{\geq n} \rangle$ 
by auto

theorem TESL_interp_stepwise_composition:
  shows  $\langle \llbracket \Phi_1 @ \Phi_2 \rrbracket_{TESL}^{\geq n} = \llbracket \Phi_1 \rrbracket_{TESL}^{\geq n} \cap \llbracket \Phi_2 \rrbracket_{TESL}^{\geq n} \rangle$ 
by (induction  $\Phi_1$ , simp, auto)

```

### 6.3 Interpretation of configurations

The interpretation of a configuration of the operational semantics abstract machine is the intersection of:

- the interpretation of its context (the past),
- the interpretation of its present from the current instant,
- the interpretation of its future from the next instant.

```

fun configuration_interpretation
  :: (' $\tau$ ::linordered_field config  $\Rightarrow$  ' $\tau$  run set)
  ( $\langle \llbracket \_ \rrbracket_{config} \rangle$  71)
where
   $\langle \llbracket \Gamma, n \vdash \Psi \triangleright \Phi \rrbracket_{config} = \llbracket \Gamma \rrbracket_{prim} \cap \llbracket \Psi \rrbracket_{TESL}^{\geq n} \cap \llbracket \Phi \rrbracket_{TESL}^{\geq \text{Suc } n} \rangle$ 

lemma configuration_interp_composition:
   $\langle \llbracket \Gamma_1, n \vdash \Psi_1 \triangleright \Phi_1 \rrbracket_{config} \cap \llbracket \Gamma_2, n \vdash \Psi_2 \triangleright \Phi_2 \rrbracket_{config} = \llbracket (\Gamma_1 @ \Gamma_2), n \vdash (\Psi_1 @ \Psi_2) \triangleright (\Phi_1 @ \Phi_2) \rrbracket_{config} \rangle$ 
  using TESL_interp_stepwise_composition symrun_interp_expansion
by (simp add: TESL_interp_stepwise_composition
    symrun_interp_expansion inf_assoc inf_left_commute)

```

When there are no remaining constraints on the present, the interpretation of a configuration is the same as the configuration at the next instant of its future. This corresponds to the introduction rule of the operational semantics.

```

lemma configuration_interp_stepwise_instant_cases:
   $\langle \llbracket \Gamma, n \vdash \Box \triangleright \Phi \rrbracket_{config} = \llbracket \Gamma, \text{Suc } n \vdash \Phi \triangleright \Box \rrbracket_{config} \rangle$ 
proof -
  have  $\langle \llbracket \Gamma, n \vdash \Box \triangleright \Phi \rrbracket_{config} = \llbracket \Gamma \rrbracket_{prim} \cap \llbracket \Box \rrbracket_{TESL}^{\geq n} \cap \llbracket \Phi \rrbracket_{TESL}^{\geq \text{Suc } n} \rangle$ 
  by simp
  moreover have  $\langle \llbracket \Gamma, \text{Suc } n \vdash \Phi \triangleright \Box \rrbracket_{config} = \llbracket \Gamma \rrbracket_{prim} \cap \llbracket \Phi \rrbracket_{TESL}^{\geq \text{Suc } n} \cap \llbracket \Box \rrbracket_{TESL}^{\geq \text{Suc } n} \rangle$ 
  by simp

```

moreover have  $\langle \llbracket \Gamma \rrbracket_{prim} \cap \llbracket \square \rrbracket_{TESL}^{\geq n} \cap \llbracket \Phi \rrbracket_{TESL}^{\geq \text{Suc } n} \rangle$   
 $= \llbracket \Gamma \rrbracket_{prim} \cap \llbracket \Phi \rrbracket_{TESL}^{\geq \text{Suc } n} \cap \llbracket \square \rrbracket_{TESL}^{\geq \text{Suc } n} \rangle$   
 by simp  
 ultimately show ?thesis by blast  
 qed

The following lemmas use the unfolding properties of the stepwise denotational semantics to give rewriting rules for the interpretation of configurations that match the elimination rules of the operational semantics.

lemma configuration\_interp\_stepwise\_sporadicon\_cases:

$\langle \llbracket \Gamma, n \vdash ((K_1 \text{ sporadic } \tau \text{ on } K_2) \# \Psi) \triangleright \Phi \rrbracket_{config} \rangle$   
 $= \llbracket \Gamma, n \vdash \Psi \triangleright ((K_1 \text{ sporadic } \tau \text{ on } K_2) \# \Phi) \rrbracket_{config}$   
 $\cup \llbracket ((K_1 \uparrow n) \# (K_2 \downarrow n \otimes \tau) \# \Gamma), n \vdash \Psi \triangleright \Phi \rrbracket_{config} \rangle$   
 proof -  
 have  $\langle \llbracket \Gamma, n \vdash (K_1 \text{ sporadic } \tau \text{ on } K_2) \# \Psi \triangleright \Phi \rrbracket_{config} \rangle$   
 $= \llbracket \Gamma \rrbracket_{prim} \cap \llbracket (K_1 \text{ sporadic } \tau \text{ on } K_2) \# \Psi \rrbracket_{TESL}^{\geq n} \cap \llbracket \Phi \rrbracket_{TESL}^{\geq \text{Suc } n} \rangle$   
 by simp  
 moreover have  $\langle \llbracket \Gamma, n \vdash \Psi \triangleright ((K_1 \text{ sporadic } \tau \text{ on } K_2) \# \Phi) \rrbracket_{config} \rangle$   
 $= \llbracket \Gamma \rrbracket_{prim} \cap \llbracket \Psi \rrbracket_{TESL}^{\geq n} \cap \llbracket (K_1 \text{ sporadic } \tau \text{ on } K_2) \# \Phi \rrbracket_{TESL}^{\geq \text{Suc } n} \rangle$   
 by simp  
 moreover have  $\langle \llbracket ((K_1 \uparrow n) \# (K_2 \downarrow n \otimes \tau) \# \Gamma), n \vdash \Psi \triangleright \Phi \rrbracket_{config} \rangle$   
 $= \llbracket ((K_1 \uparrow n) \# (K_2 \downarrow n \otimes \tau) \# \Gamma) \rrbracket_{prim} \cap \llbracket \Psi \rrbracket_{TESL}^{\geq n} \cap \llbracket \Phi \rrbracket_{TESL}^{\geq \text{Suc } n} \rangle$   
 by simp  
 ultimately show ?thesis  
 proof -  
 have  $\langle \llbracket (K_1 \uparrow n) \rrbracket_{prim} \cap \llbracket (K_2 \downarrow n \otimes \tau) \rrbracket_{prim} \cup \llbracket K_1 \text{ sporadic } \tau \text{ on } K_2 \rrbracket_{TESL}^{\geq \text{Suc } n} \rangle$   
 $\cap \llbracket \Gamma \rrbracket_{prim} \cap \llbracket \Psi \rrbracket_{TESL}^{\geq n} \rangle$   
 $= \llbracket K_1 \text{ sporadic } \tau \text{ on } K_2 \rrbracket_{TESL}^{\geq n} \cap \llbracket \Psi \rrbracket_{TESL}^{\geq n} \cap \llbracket \Gamma \rrbracket_{prim} \rangle$   
 using TESL\_interp\_stepwise\_sporadicon\_coind\_unfold by blast  
 hence  $\langle \llbracket ((K_1 \uparrow n) \# (K_2 \downarrow n \otimes \tau) \# \Gamma) \rrbracket_{prim} \cap \llbracket \Psi \rrbracket_{TESL}^{\geq n} \rangle$   
 $\cup \llbracket \Gamma \rrbracket_{prim} \cap \llbracket \Psi \rrbracket_{TESL}^{\geq n} \cap \llbracket K_1 \text{ sporadic } \tau \text{ on } K_2 \rrbracket_{TESL}^{\geq \text{Suc } n} \rangle$   
 $= \llbracket (K_1 \text{ sporadic } \tau \text{ on } K_2) \# \Psi \rrbracket_{TESL}^{\geq n} \cap \llbracket \Gamma \rrbracket_{prim} \rangle$  by auto  
 thus ?thesis by auto  
 qed  
 qed

lemma configuration\_interp\_stepwise\_sporadicon\_tvar\_cases:

$\langle \llbracket \Gamma, n \vdash ((K_1 \text{ sporadic} \# \tau_{expr} \text{ on } K_2) \# \Psi) \triangleright \Phi \rrbracket_{config} \rangle$   
 $= \llbracket \Gamma, n \vdash \Psi \triangleright ((K_1 \text{ sporadic} \# \tau_{expr} \text{ on } K_2) \# \Phi) \rrbracket_{config}$   
 $\cup \llbracket ((K_1 \uparrow n) \# (K_2 \downarrow n \otimes \tau_{expr}) \# \Gamma), n \vdash \Psi \triangleright \Phi \rrbracket_{config} \rangle$   
 proof -  
 from tag\_expr.exhaust obtain  $v \ \delta\tau$  where  $\langle \tau_{expr} = (v \oplus \delta\tau) \rangle$  by blast  
 moreover from tag\_var.exhaust obtain  $K_{past} \ n_{past}$  where  $\langle v = \tau_{var}(K_{past}, n_{past}) \rangle$  by auto  
 ultimately have  $\langle \tau_{expr} = (\tau_{var}(K_{past}, n_{past}) \oplus \delta\tau) \rangle$  by simp  
 show ?thesis  
 proof -  
 have  $\langle \llbracket (K_1 \uparrow n) \rrbracket_{prim} \cap \llbracket (K_2 \downarrow n \otimes (\tau_{var}(K_{past}, n_{past}) \oplus \delta\tau)) \rrbracket_{prim} \cup \llbracket K_1 \text{ sporadic} \# (\tau_{var}(K_{past}, n_{past}) \oplus \delta\tau) \text{ on } K_2 \rrbracket_{TESL}^{\geq \text{Suc } n} \rangle$   
 $\cap \llbracket \Gamma \rrbracket_{prim} \cap \llbracket \Psi \rrbracket_{TESL}^{\geq n} \rangle$   
 $= \llbracket K_1 \text{ sporadic} \# (\tau_{var}(K_{past}, n_{past}) \oplus \delta\tau) \text{ on } K_2 \rrbracket_{TESL}^{\geq n} \cap \llbracket \Psi \rrbracket_{TESL}^{\geq n} \cap \llbracket \Gamma \rrbracket_{prim} \rangle$   
 using TESL\_interp\_stepwise\_sporadicon\_tvar\_coind\_unfold[of  $\langle K_1 \rangle \langle K_{past} \rangle \langle n_{past} \rangle \langle \delta\tau \rangle \langle K_2 \rangle \langle n \rangle$ ]  
 Int\_commute by blast  
 then have  $\langle \llbracket ((K_1 \uparrow n) \# (K_2 \downarrow n \otimes (\tau_{var}(K_{past}, n_{past}) \oplus \delta\tau)) \# \Gamma) \rrbracket_{prim} \cap \llbracket \Psi \rrbracket_{TESL}^{\geq n} \cup \llbracket \Gamma \rrbracket_{prim} \cap \llbracket \Psi \rrbracket_{TESL}^{\geq n} \rangle$   
 $\cap \llbracket K_1 \text{ sporadic} \# (\tau_{var}(K_{past}, n_{past}) \oplus \delta\tau) \text{ on } K_2 \rrbracket_{TESL}^{\geq \text{Suc } n} \rangle$   
 $= \llbracket \Gamma \rrbracket_{prim} \cap \llbracket (K_1 \text{ sporadic} \# (\tau_{var}(K_{past}, n_{past}) \oplus \delta\tau) \text{ on } K_2) \# \Psi \rrbracket_{TESL}^{\geq n} \rangle$

```

    by auto
  then have <[ Γ, n ⊢ ((K1 sporadic# (| τvar (Kpast, npast) ⊕ δτ |) on K2) # Ψ) ▷ Φ ]>config
    = [ ((K1 ↑ n) # (K2 ↓ n @# (| τvar (Kpast, npast) ⊕ δτ |) # Γ), n ⊢ Ψ ▷ Φ ]>config
      ∪ [ Γ, n ⊢ Ψ ▷ ((K1 sporadic# (| τvar (Kpast, npast) ⊕ δτ |) on K2) # Φ) ]>config
    by auto
  then show ?thesis using *
    by blast
qed
qed

```

lemma configuration\_interp\_stepwise\_tagrel\_cases:

```

  <[ Γ, n ⊢ ((time-relation [K1, K2] ∈ R) # Ψ) ▷ Φ ]>config
    = [ ((| τvar (K1, n), τvar (K2, n) | ∈ R) # Γ), n
      ⊢ Ψ ▷ ((time-relation [K1, K2] ∈ R) # Φ) ]>config
proof -
  have <[ Γ, n ⊢ (time-relation [K1, K2] ∈ R) # Ψ ▷ Φ ]>config
    = [[ Γ ]>prim ∩ [[ (time-relation [K1, K2] ∈ R) # Ψ ]>TESL≥ n
      ∩ [[ Φ ]>TESL≥ Suc n by simp
  moreover have <[ ((| τvar (K1, n), τvar (K2, n) | ∈ R) # Γ), n
    ⊢ Ψ ▷ ((time-relation [K1, K2] ∈ R) # Φ) ]>config
    = [[ (| τvar (K1, n), τvar (K2, n) | ∈ R) # Γ ]>prim ∩ [[ Ψ ]>TESL≥ n
      ∩ [[ (time-relation [K1, K2] ∈ R) # Φ ]>TESL≥ Suc n
    by simp
  ultimately show ?thesis
proof -
    have <[ | τvar (K1, n), τvar (K2, n) | ∈ R ]>prim
      ∩ [ time-relation [K1, K2] ∈ R ]>TESL≥ Suc n
      ∩ [[ Ψ ]>TESL≥ n = [[ (time-relation [K1, K2] ∈ R) # Ψ ]>TESL≥ n
    using TESL_interp_stepwise_tagrel_coind_unfold
      TESL_interpretation_stepwise_cons_morph by blast
    thus ?thesis by auto
  qed
qed

```

lemma configuration\_interp\_stepwise\_implies\_cases:

```

  <[ Γ, n ⊢ ((K1 implies K2) # Ψ) ▷ Φ ]>config
    = [ ((K1 ↑ n) # Γ), n ⊢ Ψ ▷ ((K1 implies K2) # Φ) ]>config
      ∪ [ ((K1 ↑ n) # (K2 ↑ n) # Γ), n ⊢ Ψ ▷ ((K1 implies K2) # Φ) ]>config
proof -
  have <[ Γ, n ⊢ (K1 implies K2) # Ψ ▷ Φ ]>config
    = [[ Γ ]>prim ∩ [[ (K1 implies K2) # Ψ ]>TESL≥ n ∩ [[ Φ ]>TESL≥ Suc n
    by simp
  moreover have <[ ((K1 ↑ n) # Γ), n ⊢ Ψ ▷ ((K1 implies K2) # Φ) ]>config
    = [[ (K1 ↑ n) # Γ ]>prim ∩ [[ Ψ ]>TESL≥ n
      ∩ [[ (K1 implies K2) # Φ ]>TESL≥ Suc n by simp
  moreover have <[ ((K1 ↑ n) # (K2 ↑ n) # Γ), n ⊢ Ψ ▷ ((K1 implies K2) # Φ) ]>config
    = [[ ((K1 ↑ n) # (K2 ↑ n) # Γ) ]>prim ∩ [[ Ψ ]>TESL≥ n
      ∩ [[ (K1 implies K2) # Φ ]>TESL≥ Suc n by simp
  ultimately show ?thesis
proof -
    have f1: <[ (K1 ↑ n) ]>prim ∪ [ K1 ↑ n ]>prim ∩ [ K2 ↑ n ]>prim
      ∩ [ K1 implies K2 ]>TESL≥ Suc n ∩ ([ Ψ ]>TESL≥ n
      ∩ [[ Φ ]>TESL≥ Suc n)
      = [[ (K1 implies K2) # Ψ ]>TESL≥ n ∩ [[ Φ ]>TESL≥ Suc n
    using TESL_interp_stepwise_implies_coind_unfold
      TESL_interpretation_stepwise_cons_morph by blast
    have <[ K1 ↑ n ]>prim ∩ [[ Γ ]>prim ∪ [ K1 ↑ n ]>prim ∩ [[ (K2 ↑ n) # Γ ]>prim
      = <[ K1 ↑ n ]>prim ∪ [ K1 ↑ n ]>prim ∩ [ K2 ↑ n ]>prim ∩ [[ Γ ]>prim
    by force
  qed

```

hence  $\langle \llbracket \Gamma, n \vdash ((K_1 \text{ implies } K_2) \# \Psi) \triangleright \Phi \rrbracket_{\text{config}}$   
 $= \langle \llbracket K_1 \neg\uparrow n \rrbracket_{\text{prim}} \cap \llbracket \llbracket \Gamma \rrbracket_{\text{prim}} \cup \llbracket K_1 \uparrow n \rrbracket_{\text{prim}} \cap \llbracket (K_2 \uparrow n) \# \Gamma \rrbracket_{\text{prim}} \rangle$   
 $\cap \langle \llbracket \Psi \rrbracket_{\text{TESL} \geq n} \cap \llbracket (K_1 \text{ implies } K_2) \# \Phi \rrbracket_{\text{TESL} \geq \text{Suc } n} \rangle$   
 using f1 by (simp add: inf\_left\_commute inf\_assoc)  
 thus ?thesis by (simp add: Int\_Un\_distrib2 inf\_assoc)

qed

qed

lemma configuration\_interp\_stepwise\_implies\_not\_cases:

$\langle \llbracket \Gamma, n \vdash ((K_1 \text{ implies not } K_2) \# \Psi) \triangleright \Phi \rrbracket_{\text{config}}$   
 $= \langle \langle \llbracket (K_1 \neg\uparrow n) \# \Gamma \rrbracket, n \vdash \Psi \triangleright ((K_1 \text{ implies not } K_2) \# \Phi) \rrbracket_{\text{config}}$   
 $\cup \langle \llbracket (K_1 \uparrow n) \# (K_2 \neg\uparrow n) \# \Gamma \rrbracket, n \vdash \Psi \triangleright ((K_1 \text{ implies not } K_2) \# \Phi) \rrbracket_{\text{config}} \rangle$

proof -

have  $\langle \llbracket \Gamma, n \vdash (K_1 \text{ implies not } K_2) \# \Psi \triangleright \Phi \rrbracket_{\text{config}}$   
 $= \llbracket \llbracket \Gamma \rrbracket_{\text{prim}} \cap \llbracket (K_1 \text{ implies not } K_2) \# \Psi \rrbracket_{\text{TESL} \geq n} \cap \llbracket \Phi \rrbracket_{\text{TESL} \geq \text{Suc } n} \rangle$   
 by simp

moreover have  $\langle \langle \llbracket (K_1 \neg\uparrow n) \# \Gamma \rrbracket, n \vdash \Psi \triangleright ((K_1 \text{ implies not } K_2) \# \Phi) \rrbracket_{\text{config}}$   
 $= \llbracket \llbracket (K_1 \neg\uparrow n) \# \Gamma \rrbracket_{\text{prim}} \cap \llbracket \Psi \rrbracket_{\text{TESL} \geq n} \cap \llbracket \Phi \rrbracket_{\text{TESL} \geq \text{Suc } n} \rangle$   
 $= \llbracket \llbracket (K_1 \text{ implies not } K_2) \# \Phi \rrbracket_{\text{TESL} \geq \text{Suc } n} \rangle$  by simp

moreover have  $\langle \langle \llbracket (K_1 \uparrow n) \# (K_2 \neg\uparrow n) \# \Gamma \rrbracket, n \vdash \Psi \triangleright ((K_1 \text{ implies not } K_2) \# \Phi) \rrbracket_{\text{config}}$   
 $= \llbracket \langle \llbracket (K_1 \uparrow n) \# (K_2 \neg\uparrow n) \# \Gamma \rrbracket_{\text{prim}} \cap \llbracket \Psi \rrbracket_{\text{TESL} \geq n} \rangle$   
 $\cap \llbracket \llbracket (K_1 \text{ implies not } K_2) \# \Phi \rrbracket_{\text{TESL} \geq \text{Suc } n} \rangle$  by simp

ultimately show ?thesis

proof -

have f1:  $\langle \langle \llbracket K_1 \neg\uparrow n \rrbracket_{\text{prim}} \cup \llbracket K_1 \uparrow n \rrbracket_{\text{prim}} \cap \llbracket K_2 \neg\uparrow n \rrbracket_{\text{prim}} \rangle$   
 $\cap \llbracket K_1 \text{ implies not } K_2 \rrbracket_{\text{TESL} \geq \text{Suc } n}$   
 $\cap \langle \llbracket \Psi \rrbracket_{\text{TESL} \geq n} \cap \llbracket \Phi \rrbracket_{\text{TESL} \geq \text{Suc } n} \rangle$   
 $= \llbracket \llbracket (K_1 \text{ implies not } K_2) \# \Psi \rrbracket_{\text{TESL} \geq n} \cap \llbracket \Phi \rrbracket_{\text{TESL} \geq \text{Suc } n} \rangle$

using TESL\_interp\_stepwise\_implies\_not\_coind\_unfold  
 TESL\_interpretation\_stepwise\_cons\_morph by blast

have  $\langle \llbracket K_1 \neg\uparrow n \rrbracket_{\text{prim}} \cap \llbracket \llbracket \Gamma \rrbracket_{\text{prim}} \cup \llbracket K_1 \uparrow n \rrbracket_{\text{prim}} \cap \llbracket (K_2 \neg\uparrow n) \# \Gamma \rrbracket_{\text{prim}} \rangle$   
 $= \langle \llbracket K_1 \neg\uparrow n \rrbracket_{\text{prim}} \cup \llbracket K_1 \uparrow n \rrbracket_{\text{prim}} \cap \llbracket K_2 \neg\uparrow n \rrbracket_{\text{prim}} \rangle \cap \llbracket \llbracket \Gamma \rrbracket_{\text{prim}} \rangle$

by force

then have  $\langle \llbracket \Gamma, n \vdash ((K_1 \text{ implies not } K_2) \# \Psi) \triangleright \Phi \rrbracket_{\text{config}}$   
 $= \langle \llbracket K_1 \neg\uparrow n \rrbracket_{\text{prim}} \cap \llbracket \llbracket \Gamma \rrbracket_{\text{prim}} \cup \llbracket K_1 \uparrow n \rrbracket_{\text{prim}} \cap \llbracket (K_2 \neg\uparrow n) \# \Gamma \rrbracket_{\text{prim}} \rangle$   
 $\cap \langle \llbracket (K_2 \neg\uparrow n) \# \Gamma \rrbracket_{\text{prim}} \cap \langle \llbracket \Psi \rrbracket_{\text{TESL} \geq n} \rangle$   
 $\cap \llbracket \llbracket (K_1 \text{ implies not } K_2) \# \Phi \rrbracket_{\text{TESL} \geq \text{Suc } n} \rangle$

using f1 by (simp add: inf\_left\_commute inf\_assoc)  
 thus ?thesis by (simp add: Int\_Un\_distrib2 inf\_assoc)

qed

qed

lemma configuration\_interp\_stepwise\_timedelayed\_cases:

$\langle \llbracket \Gamma, n \vdash ((K_1 \text{ time-delayed by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Psi) \triangleright \Phi \rrbracket_{\text{config}}$   
 $= \langle \langle \llbracket (K_1 \neg\uparrow n) \# \Gamma \rrbracket, n \vdash \Psi \triangleright ((K_1 \text{ time-delayed by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Phi) \rrbracket_{\text{config}}$   
 $\cup \langle \langle \llbracket (K_1 \uparrow n) \# (K_2 @ n \oplus \delta\tau \Rightarrow K_3) \# \Gamma \rrbracket, n$   
 $\vdash \Psi \triangleright ((K_1 \text{ time-delayed by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Phi) \rrbracket_{\text{config}} \rangle$

proof -

have 1:  $\langle \llbracket \Gamma, n \vdash (K_1 \text{ time-delayed by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Psi \triangleright \Phi \rrbracket_{\text{config}}$   
 $= \llbracket \llbracket \Gamma \rrbracket_{\text{prim}} \cap \llbracket \llbracket (K_1 \text{ time-delayed by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Psi \rrbracket_{\text{TESL} \geq n}$   
 $\cap \llbracket \Phi \rrbracket_{\text{TESL} \geq \text{Suc } n} \rangle$  by simp

moreover have  $\langle \langle \llbracket (K_1 \neg\uparrow n) \# \Gamma \rrbracket, n$   
 $\vdash \Psi \triangleright ((K_1 \text{ time-delayed by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Phi) \rrbracket_{\text{config}}$   
 $= \llbracket \llbracket (K_1 \neg\uparrow n) \# \Gamma \rrbracket_{\text{prim}} \cap \llbracket \Psi \rrbracket_{\text{TESL} \geq n}$   
 $\cap \llbracket \llbracket (K_1 \text{ time-delayed by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Phi \rrbracket_{\text{TESL} \geq \text{Suc } n} \rangle$

by simp

moreover have  $\langle \langle \llbracket (K_1 \uparrow n) \# (K_2 @ n \oplus \delta\tau \Rightarrow K_3) \# \Gamma \rrbracket, n$   
 $\vdash \Psi \triangleright ((K_1 \text{ time-delayed by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Phi) \rrbracket_{\text{config}}$   
 $= \llbracket \llbracket (K_1 \uparrow n) \# (K_2 @ n \oplus \delta\tau \Rightarrow K_3) \# \Gamma \rrbracket_{\text{prim}} \cap \llbracket \Psi \rrbracket_{\text{TESL} \geq n}$

```

     $\cap \llbracket (K_1 \text{ time-delayed by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Phi \rrbracket_{TESL}^{\geq \text{Suc } n}$ 
  by simp
  ultimately show ?thesis
  proof -
    have  $\langle \llbracket \Gamma, n \vdash (K_1 \text{ time-delayed by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Psi \triangleright \Phi \rrbracket_{config}$ 
      =  $\llbracket \llbracket \Gamma \rrbracket_{prim} \cap (\llbracket (K_1 \text{ time-delayed by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Psi \rrbracket_{TESL}^{\geq n}$ 
         $\cap \llbracket \Phi \rrbracket_{TESL}^{\geq \text{Suc } n}) \rangle$ 
    using 1 by blast
    hence  $\langle \llbracket \Gamma, n \vdash (K_1 \text{ time-delayed by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Psi \triangleright \Phi \rrbracket_{config}$ 
      =  $\langle \llbracket K_1 \rightarrow \uparrow n \rrbracket_{prim} \cup \llbracket K_1 \uparrow n \rrbracket_{prim} \cap \llbracket K_2 @ n \oplus \delta\tau \Rightarrow K_3 \rrbracket_{prim}$ 
         $\cap (\llbracket \Gamma \rrbracket_{prim} \cap (\llbracket \Psi \rrbracket_{TESL}^{\geq n}$ 
           $\cap \llbracket (K_1 \text{ time-delayed by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Phi \rrbracket_{TESL}^{\geq \text{Suc } n})) \rangle$ 
    using TESL_interpretation_stepwise_cons_morph
      TESL_interp_stepwise_timedelayed_coind_unfold
  proof -
    have  $\langle \llbracket (K_1 \text{ time-delayed by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Psi \rrbracket_{TESL}^{\geq n}$ 
      =  $\langle \llbracket K_1 \rightarrow \uparrow n \rrbracket_{prim} \cup \llbracket K_1 \uparrow n \rrbracket_{prim} \cap \llbracket K_2 @ n \oplus \delta\tau \Rightarrow K_3 \rrbracket_{prim}$ 
         $\cap \llbracket K_1 \text{ time-delayed by } \delta\tau \text{ on } K_2 \text{ implies } K_3 \rrbracket_{TESL}^{\geq \text{Suc } n} \cap \llbracket \Psi \rrbracket_{TESL}^{\geq n} \rangle$ 
    using TESL_interp_stepwise_timedelayed_coind_unfold
      TESL_interpretation_stepwise_cons_morph by blast
    then show ?thesis
      by (simp add: Int_assoc Int_left_commute)
  qed
  then show ?thesis by (simp add: inf_assoc inf_sup_distrib2)
  qed
  qed
  lemma configuration_interp_stepwise_timedelayed_tvar_cases:
     $\langle \llbracket \Gamma, n \vdash ((K_1 \text{ time-delayed} \bowtie \text{ by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Psi) \triangleright \Phi \rrbracket_{config}$ 
      =  $\llbracket ((K_1 \rightarrow \uparrow n) \# \Gamma), n \vdash \Psi \triangleright ((K_1 \text{ time-delayed} \bowtie \text{ by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Phi) \rrbracket_{config}$ 
         $\cup \llbracket ((K_1 \uparrow n) \# \Gamma), n$ 
           $\vdash (K_3 \text{ sporadic} \# (\tau_{var}(K_2, n) \oplus \delta\tau) \text{ on } K_2) \# \Psi$ 
             $\triangleright ((K_1 \text{ time-delayed} \bowtie \text{ by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Phi) \rrbracket_{config} \rangle$ 
  proof -
    have  $\langle \llbracket \Psi \rrbracket_{TESL}^{\geq n}$ 
       $\cap (\llbracket K_1 \rightarrow \uparrow n \rrbracket_{prim} \cup \llbracket K_1 \uparrow n \rrbracket_{prim} \cap \llbracket K_3 \text{ sporadic} \# (\tau_{var}(K_2, n) \oplus \delta\tau) \text{ on } K_2 \rrbracket_{TESL}^{\geq n}$ 
         $\cap \llbracket K_1 \text{ time-delayed} \bowtie \text{ by } \delta\tau \text{ on } K_2 \text{ implies } K_3 \rrbracket_{TESL}^{\geq \text{Suc } n}$ 
      =  $\llbracket \Psi \rrbracket_{TESL}^{\geq n} \cap \llbracket K_1 \text{ time-delayed} \bowtie \text{ by } \delta\tau \text{ on } K_2 \text{ implies } K_3 \rrbracket_{TESL}^{\geq n} \rangle$ 
    using TESL_interp_stepwise_timedelayed_tvar_coind_unfold[of  $\langle K_1 \rangle \langle \delta\tau \rangle \langle K_2 \rangle \langle K_3 \rangle \langle n \rangle$ ]
      Int_assoc by blast
    then have  $\langle \llbracket \Gamma, n \vdash (K_1 \text{ time-delayed} \bowtie \text{ by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Psi \triangleright \Phi \rrbracket_{config}$ 
      =  $\llbracket \llbracket \Psi \rrbracket_{TESL}^{\geq n}$ 
         $\cap (\llbracket K_1 \rightarrow \uparrow n \rrbracket_{prim} \cup \llbracket K_1 \uparrow n \rrbracket_{prim} \cap \llbracket K_3 \text{ sporadic} \# (\tau_{var}(K_2, n) \oplus \delta\tau) \text{ on } K_2 \rrbracket_{TESL}^{\geq n}$ 
           $\cap \llbracket K_1 \text{ time-delayed} \bowtie \text{ by } \delta\tau \text{ on } K_2 \text{ implies } K_3 \rrbracket_{TESL}^{\geq \text{Suc } n}$ 
           $\cap (\llbracket \Phi \rrbracket_{TESL}^{\geq \text{Suc } n} \cap \llbracket \Gamma \rrbracket_{prim})) \rangle$ 
    by force
    then show ?thesis
      by auto
  qed
  lemma configuration_interp_stepwise_weakly_precedes_cases:
     $\langle \llbracket \Gamma, n \vdash ((K_1 \text{ weakly precedes } K_2) \# \Psi) \triangleright \Phi \rrbracket_{config}$ 
      =  $\llbracket ((\# \leq K_2 \ n, \# \leq K_1 \ n) \in (\lambda(x,y). x \leq y)) \# \Gamma), n$ 
         $\vdash \Psi \triangleright ((K_1 \text{ weakly precedes } K_2) \# \Phi) \rrbracket_{config} \rangle$ 
  proof -
    have  $\langle \llbracket \Gamma, n \vdash (K_1 \text{ weakly precedes } K_2) \# \Psi \triangleright \Phi \rrbracket_{config}$ 
      =  $\llbracket \llbracket \Gamma \rrbracket_{prim} \cap \llbracket (K_1 \text{ weakly precedes } K_2) \# \Psi \rrbracket_{TESL}^{\geq n}$ 
         $\cap \llbracket \Phi \rrbracket_{TESL}^{\geq \text{Suc } n} \rrbracket_{TESL}^{\geq \text{Suc } n} \rangle$  by simp
    moreover have  $\langle ((\# \leq K_2 \ n, \# \leq K_1 \ n) \in (\lambda(x,y). x \leq y)) \# \Gamma), n$ 

```



$$\begin{aligned} & \vdash \Psi \triangleright ((K_1 \text{ weakly precedes } K_2) \# \Phi) \rrbracket_{config} \\ &= \llbracket \llbracket (\# \leq K_2 \ n, \# \leq K_1 \ n] \in (\lambda(x,y). x \leq y)) \# \Gamma \rrbracket_{prim} \\ & \cap \llbracket \llbracket \Psi \rrbracket_{TESL} \geq n \cap \llbracket \llbracket (K_1 \text{ weakly precedes } K_2) \# \Phi \rrbracket_{TESL} \geq \text{Suc } n \rrbracket \end{aligned}$$

by simp

ultimately show ?thesis

proof -

have  $\langle \llbracket \# \leq K_2 \ n, \# \leq K_1 \ n] \in (\lambda(x,y). x \leq y) \rrbracket_{prim}$   
 $\cap \llbracket \llbracket K_1 \text{ weakly precedes } K_2 \rrbracket_{TESL} \geq \text{Suc } n \cap \llbracket \llbracket \Psi \rrbracket_{TESL} \geq n$   
 $= \llbracket \llbracket (K_1 \text{ weakly precedes } K_2) \# \Psi \rrbracket_{TESL} \geq n \rrbracket$

using TESL\_interp\_stepwise\_weakly\_precedes\_coind\_unfold  
 TESL\_interpretation\_stepwise\_cons\_morph by blast

thus ?thesis by auto

qed

qed

lemma configuration\_interp\_stepwise\_strictly\_precedes\_cases:

$\langle \llbracket \Gamma, n \vdash ((K_1 \text{ strictly precedes } K_2) \# \Psi) \triangleright \Phi \rrbracket_{config}$   
 $= \llbracket \llbracket (\# \leq K_2 \ n, \# < K_1 \ n] \in (\lambda(x,y). x \leq y)) \# \Gamma \rrbracket, n$   
 $\vdash \Psi \triangleright ((K_1 \text{ strictly precedes } K_2) \# \Phi) \rrbracket_{config} \rangle$

proof -

have  $\langle \llbracket \Gamma, n \vdash ((K_1 \text{ strictly precedes } K_2) \# \Psi) \triangleright \Phi \rrbracket_{config}$   
 $= \llbracket \llbracket \Gamma \rrbracket_{prim} \cap \llbracket \llbracket (K_1 \text{ strictly precedes } K_2) \# \Psi \rrbracket_{TESL} \geq n$   
 $\cap \llbracket \llbracket \Phi \rrbracket_{TESL} \geq \text{Suc } n \rrbracket$  by simp

moreover have  $\langle \llbracket (\# \leq K_2 \ n, \# < K_1 \ n] \in (\lambda(x,y). x \leq y)) \# \Gamma \rrbracket, n$   
 $\vdash \Psi \triangleright ((K_1 \text{ strictly precedes } K_2) \# \Phi) \rrbracket_{config}$   
 $= \llbracket \llbracket (\# \leq K_2 \ n, \# < K_1 \ n] \in (\lambda(x,y). x \leq y)) \# \Gamma \rrbracket_{prim}$   
 $\cap \llbracket \llbracket \Psi \rrbracket_{TESL} \geq n$   
 $\cap \llbracket \llbracket (K_1 \text{ strictly precedes } K_2) \# \Phi \rrbracket_{TESL} \geq \text{Suc } n \rrbracket$  by simp

ultimately show ?thesis

proof -

have  $\langle \llbracket \# \leq K_2 \ n, \# < K_1 \ n] \in (\lambda(x,y). x \leq y) \rrbracket_{prim}$   
 $\cap \llbracket \llbracket K_1 \text{ strictly precedes } K_2 \rrbracket_{TESL} \geq \text{Suc } n \cap \llbracket \llbracket \Psi \rrbracket_{TESL} \geq n$   
 $= \llbracket \llbracket (K_1 \text{ strictly precedes } K_2) \# \Psi \rrbracket_{TESL} \geq n \rrbracket$

using TESL\_interp\_stepwise\_strictly\_precedes\_coind\_unfold  
 TESL\_interpretation\_stepwise\_cons\_morph by blast

thus ?thesis by auto

qed

qed

lemma configuration\_interp\_stepwise\_kills\_cases:

$\langle \llbracket \Gamma, n \vdash ((K_1 \text{ kills } K_2) \# \Psi) \triangleright \Phi \rrbracket_{config}$   
 $= \llbracket \llbracket (K_1 \dashv \uparrow n) \# \Gamma \rrbracket, n \vdash \Psi \triangleright ((K_1 \text{ kills } K_2) \# \Phi) \rrbracket_{config}$   
 $\cup \llbracket \llbracket (K_1 \uparrow n) \# (K_2 \dashv \uparrow \geq n) \# \Gamma \rrbracket, n \vdash \Psi \triangleright ((K_1 \text{ kills } K_2) \# \Phi) \rrbracket_{config} \rangle$

proof -

have  $\langle \llbracket \Gamma, n \vdash ((K_1 \text{ kills } K_2) \# \Psi) \triangleright \Phi \rrbracket_{config}$   
 $= \llbracket \llbracket \Gamma \rrbracket_{prim} \cap \llbracket \llbracket (K_1 \text{ kills } K_2) \# \Psi \rrbracket_{TESL} \geq n \cap \llbracket \llbracket \Phi \rrbracket_{TESL} \geq \text{Suc } n \rrbracket$

by simp

moreover have  $\langle \llbracket (K_1 \dashv \uparrow n) \# \Gamma \rrbracket, n \vdash \Psi \triangleright ((K_1 \text{ kills } K_2) \# \Phi) \rrbracket_{config}$   
 $= \llbracket \llbracket (K_1 \dashv \uparrow n) \# \Gamma \rrbracket_{prim} \cap \llbracket \llbracket \Psi \rrbracket_{TESL} \geq n$   
 $\cap \llbracket \llbracket (K_1 \text{ kills } K_2) \# \Phi \rrbracket_{TESL} \geq \text{Suc } n \rrbracket$  by simp

moreover have  $\langle \llbracket (K_1 \uparrow n) \# (K_2 \dashv \uparrow \geq n) \# \Gamma \rrbracket, n \vdash \Psi \triangleright ((K_1 \text{ kills } K_2) \# \Phi) \rrbracket_{config}$   
 $= \llbracket \llbracket (K_1 \uparrow n) \# (K_2 \dashv \uparrow \geq n) \# \Gamma \rrbracket_{prim} \cap \llbracket \llbracket \Psi \rrbracket_{TESL} \geq n$   
 $\cap \llbracket \llbracket (K_1 \text{ kills } K_2) \# \Phi \rrbracket_{TESL} \geq \text{Suc } n \rrbracket$  by simp

ultimately show ?thesis

proof -

have  $\llbracket \llbracket (K_1 \text{ kills } K_2) \# \Psi \rrbracket_{TESL} \geq n$   
 $= (\llbracket (K_1 \dashv \uparrow n) \rrbracket_{prim} \cup \llbracket (K_1 \uparrow n) \rrbracket_{prim} \cap \llbracket (K_2 \dashv \uparrow \geq n) \rrbracket_{prim})$   
 $\cap \llbracket \llbracket (K_1 \text{ kills } K_2) \rrbracket_{TESL} \geq \text{Suc } n \cap \llbracket \llbracket \Psi \rrbracket_{TESL} \geq n$

using TESL\_interp\_stepwise\_kills\_coind\_unfold

```
      TESL_interpretation_stepwise_cons_morph by blast
    thus ?thesis by auto
  qed
qed
end
```

# Chapter 7

## Main Theorems

```
theory Hygge_Theory
imports
  Corecursive_Prop
```

```
begin
```

Using the properties we have shown about the interpretation of configurations and the stepwise unfolding of the denotational semantics, we can now prove several important results about the construction of runs from a specification.

### 7.1 Initial configuration

The denotational semantics of a specification  $\Psi$  is the interpretation at the first instant of a configuration which has  $\Psi$  as its present. This means that we can start to build a run that satisfies a specification by starting from this configuration.

```
theorem solve_start:
  shows  $\langle \llbracket \Psi \rrbracket_{TESL} = \llbracket \square, 0 \vdash \Psi \triangleright \square \rrbracket_{config} \rangle$ 
  proof -
    have  $\langle \llbracket \Psi \rrbracket_{TESL} = \llbracket \Psi \rrbracket_{TESL}^{\geq 0} \rangle$ 
    by (simp add: TESL_interpretation_stepwise_zero')
    moreover have  $\langle \llbracket \square, 0 \vdash \Psi \triangleright \square \rrbracket_{config} = \llbracket \square \rrbracket_{prim} \cap \llbracket \Psi \rrbracket_{TESL}^{\geq 0} \cap \llbracket \square \rrbracket_{TESL}^{\geq \text{Suc } 0} \rangle$ 
    by simp
    ultimately show ?thesis by auto
  qed
```

### 7.2 Soundness

The interpretation of a configuration  $\mathcal{S}_2$  that is a refinement of a configuration  $\mathcal{S}_1$  is contained in the interpretation of  $\mathcal{S}_1$ . This means that by making successive choices in building the instants of a run, we preserve the soundness of the constructed run with regard to the original specification.

```
lemma sound_reduction:
  assumes  $\langle \Gamma_1, n_1 \vdash \Psi_1 \triangleright \Phi_1 \rangle \hookrightarrow \langle \Gamma_2, n_2 \vdash \Psi_2 \triangleright \Phi_2 \rangle$ 
  shows  $\langle \llbracket \Gamma_1 \rrbracket_{prim} \cap \llbracket \Psi_1 \rrbracket_{TESL}^{\geq n_1} \cap \llbracket \Phi_1 \rrbracket_{TESL}^{\geq \text{Suc } n_1} \supseteq \llbracket \Gamma_2 \rrbracket_{prim} \cap \llbracket \Psi_2 \rrbracket_{TESL}^{\geq n_2} \cap \llbracket \Phi_2 \rrbracket_{TESL}^{\geq \text{Suc } n_2} \rangle$  (is ?P)
  proof -
```

```

from assms consider
  (a)  $\langle (\Gamma_1, n_1 \vdash \Psi_1 \triangleright \Phi_1) \hookrightarrow_i (\Gamma_2, n_2 \vdash \Psi_2 \triangleright \Phi_2) \rangle$ 
| (b)  $\langle (\Gamma_1, n_1 \vdash \Psi_1 \triangleright \Phi_1) \hookrightarrow_e (\Gamma_2, n_2 \vdash \Psi_2 \triangleright \Phi_2) \rangle$ 
  using operational_semantics_step.simps by blast
thus ?thesis
proof (cases)
  case a
    thus ?thesis by (simp add: operational_semantics_intro.simps)
  next
  case b thus ?thesis
  proof (rule operational_semantics_elim.cases)
    fix  $\Gamma \ n \ K_1 \ \tau \ K_2 \ \Psi \ \Phi$ 
    assume  $\langle (\Gamma_1, n_1 \vdash \Psi_1 \triangleright \Phi_1) = (\Gamma, n \vdash (K_1 \text{ sporadic } \tau \text{ on } K_2) \# \Psi \triangleright \Phi) \rangle$ 
    and  $\langle (\Gamma_2, n_2 \vdash \Psi_2 \triangleright \Phi_2) = (\Gamma, n \vdash \Psi \triangleright ((K_1 \text{ sporadic } \tau \text{ on } K_2) \# \Phi)) \rangle$ 
    thus ?P using configuration_interp_stepwise_sporadicon_cases
      configuration_interpretation.simps by blast
  next
    fix  $\Gamma \ n \ K_1 \ \tau \ K_2 \ \Psi \ \Phi$ 
    assume  $\langle (\Gamma_1, n_1 \vdash \Psi_1 \triangleright \Phi_1) = (\Gamma, n \vdash (K_1 \text{ sporadic } \tau \text{ on } K_2) \# \Psi \triangleright \Phi) \rangle$ 
    and  $\langle (\Gamma_2, n_2 \vdash \Psi_2 \triangleright \Phi_2) = ((K_1 \uparrow n) \# (K_2 \downarrow n @ \tau) \# \Gamma), n \vdash \Psi \triangleright \Phi \rangle$ 
    thus ?P using configuration_interp_stepwise_sporadicon_cases
      configuration_interpretation.simps by blast
  next
    fix  $\Gamma \ n \ K_1 \ \tau_{expr} \ K_2 \ \Psi \ \Phi$ 
    assume  $\langle (\Gamma_1, n_1 \vdash \Psi_1 \triangleright \Phi_1) = (\Gamma, n \vdash (K_1 \text{ sporadic} \# \tau_{expr} \text{ on } K_2) \# \Psi \triangleright \Phi) \rangle$ 
    and  $\langle (\Gamma_2, n_2 \vdash \Psi_2 \triangleright \Phi_2) = (\Gamma, n \vdash \Psi \triangleright ((K_1 \text{ sporadic} \# \tau_{expr} \text{ on } K_2) \# \Phi)) \rangle$ 
    thus ?P using configuration_interp_stepwise_sporadicon_tvar_cases
      configuration_interpretation.simps by blast
  next
    fix  $\Gamma \ n \ K_1 \ \tau_{expr} \ K_2 \ \Psi \ \Phi$ 
    assume  $\langle (\Gamma_1, n_1 \vdash \Psi_1 \triangleright \Phi_1) = (\Gamma, n \vdash (K_1 \text{ sporadic} \# \tau_{expr} \text{ on } K_2) \# \Psi \triangleright \Phi) \rangle$ 
    and  $\langle (\Gamma_2, n_2 \vdash \Psi_2 \triangleright \Phi_2) = ((K_1 \uparrow n) \# (K_2 \downarrow n @ \# \tau_{expr}) \# \Gamma), n \vdash \Psi \triangleright \Phi \rangle$ 
    thus ?P using configuration_interp_stepwise_sporadicon_tvar_cases
      configuration_interpretation.simps by blast
  next
    fix  $\Gamma \ n \ K_1 \ K_2 \ R \ \Psi \ \Phi$ 
    assume  $\langle (\Gamma_1, n_1 \vdash \Psi_1 \triangleright \Phi_1) = (\Gamma, n \vdash (\text{time-relation } [K_1, K_2] \in R) \# \Psi \triangleright \Phi) \rangle$ 
    and  $\langle (\Gamma_2, n_2 \vdash \Psi_2 \triangleright \Phi_2) = (((\tau_{var} (K_1, n), \tau_{var} (K_2, n)) \in R) \# \Gamma), n \vdash \Psi \triangleright ((\text{time-relation } [K_1, K_2] \in R) \# \Phi) \rangle$ 
    thus ?P using configuration_interp_stepwise_tagrel_cases
      configuration_interpretation.simps by blast
  next
    fix  $\Gamma \ n \ K_1 \ K_2 \ \Psi \ \Phi$ 
    assume  $\langle (\Gamma_1, n_1 \vdash \Psi_1 \triangleright \Phi_1) = (\Gamma, n \vdash (K_1 \text{ implies } K_2) \# \Psi \triangleright \Phi) \rangle$ 
    and  $\langle (\Gamma_2, n_2 \vdash \Psi_2 \triangleright \Phi_2) = ((K_1 \neg \uparrow n) \# \Gamma), n \vdash \Psi \triangleright ((K_1 \text{ implies } K_2) \# \Phi) \rangle$ 
    thus ?P using configuration_interp_stepwise_implies_cases
      configuration_interpretation.simps by blast
  next
    fix  $\Gamma \ n \ K_1 \ K_2 \ \Psi \ \Phi$ 
    assume  $\langle (\Gamma_1, n_1 \vdash \Psi_1 \triangleright \Phi_1) = (\Gamma, n \vdash ((K_1 \text{ implies } K_2) \# \Psi) \triangleright \Phi) \rangle$ 
    and  $\langle (\Gamma_2, n_2 \vdash \Psi_2 \triangleright \Phi_2) = ((K_1 \uparrow n) \# (K_2 \uparrow n) \# \Gamma), n \vdash \Psi \triangleright ((K_1 \text{ implies } K_2) \# \Phi) \rangle$ 
    thus ?P using configuration_interp_stepwise_implies_cases
      configuration_interpretation.simps by blast
  next
    fix  $\Gamma \ n \ K_1 \ K_2 \ \Psi \ \Phi$ 
    assume  $\langle (\Gamma_1, n_1 \vdash \Psi_1 \triangleright \Phi_1) = (\Gamma, n \vdash ((K_1 \text{ implies not } K_2) \# \Psi) \triangleright \Phi) \rangle$ 
    and  $\langle (\Gamma_2, n_2 \vdash \Psi_2 \triangleright \Phi_2) = ((K_1 \neg \uparrow n) \# \Gamma), n \vdash \Psi \triangleright ((K_1 \text{ implies not } K_2) \# \Phi) \rangle$ 
    thus ?P using configuration_interp_stepwise_implies_not_cases

```

```

configuration_interpretation.simps by blast

next
  fix  $\Gamma$   $n$   $K_1$   $K_2$   $\Psi$   $\Phi$ 
  assume  $\langle \Gamma_1, n_1 \vdash \Psi_1 \triangleright \Phi_1 \rangle = \langle \Gamma, n \vdash ((K_1 \text{ implies not } K_2) \# \Psi) \triangleright \Phi \rangle$ 
  and  $\langle \Gamma_2, n_2 \vdash \Psi_2 \triangleright \Phi_2 \rangle = \langle ((K_1 \uparrow n) \# (K_2 \neg\uparrow n) \# \Gamma), n \vdash \Psi \triangleright ((K_1 \text{ implies not } K_2) \# \Phi) \rangle$ 
  thus ?P using configuration_interp_stepwise_implies_not_cases
    configuration_interpretation.simps by blast

next
  fix  $\Gamma$   $n$   $K_1$   $\delta\tau$   $K_2$   $K_3$   $\Psi$   $\Phi$ 
  assume  $\langle \Gamma_1, n_1 \vdash \Psi_1 \triangleright \Phi_1 \rangle = \langle \Gamma, n \vdash ((K_1 \text{ time-delayed by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Psi) \triangleright \Phi \rangle$ 
  and  $\langle \Gamma_2, n_2 \vdash \Psi_2 \triangleright \Phi_2 \rangle = \langle ((K_1 \neg\uparrow n) \# \Gamma), n \vdash \Psi \triangleright ((K_1 \text{ time-delayed by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Phi) \rangle$ 
  thus ?P using configuration_interp_stepwise_timedelayed_cases
    configuration_interpretation.simps by blast

next
  fix  $\Gamma$   $n$   $K_1$   $\delta\tau$   $K_2$   $K_3$   $\Psi$   $\Phi$ 
  assume  $\langle \Gamma_1, n_1 \vdash \Psi_1 \triangleright \Phi_1 \rangle = \langle \Gamma, n \vdash ((K_1 \text{ time-delayed by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Psi) \triangleright \Phi \rangle$ 
  and  $\langle \Gamma_2, n_2 \vdash \Psi_2 \triangleright \Phi_2 \rangle = \langle ((K_1 \uparrow n) \# (K_2 @ n \oplus \delta\tau \Rightarrow K_3) \# \Gamma), n \vdash \Psi \triangleright ((K_1 \text{ time-delayed by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Phi) \rangle$ 
  thus ?P using configuration_interp_stepwise_timedelayed_cases
    configuration_interpretation.simps by blast

next
  fix  $\Gamma$   $n$   $K_1$   $\delta\tau$   $K_2$   $K_3$   $\Psi$   $\Phi$ 
  assume  $\langle \Gamma_1, n_1 \vdash \Psi_1 \triangleright \Phi_1 \rangle = \langle \Gamma, n \vdash (K_1 \text{ time-delayed}\bowtie \text{ by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Psi \triangleright \Phi \rangle$ 
  and  $\langle \Gamma_2, n_2 \vdash \Psi_2 \triangleright \Phi_2 \rangle = \langle ((K_1 \neg\uparrow n) \# \Gamma), n \vdash \Psi \triangleright ((K_1 \text{ time-delayed}\bowtie \text{ by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Phi) \rangle$ 
  thus ?P using configuration_interp_stepwise_timedelayed_tvar_cases
    configuration_interpretation.simps by blast

next
  fix  $\Gamma$   $n$   $K_1$   $\delta\tau$   $K_2$   $K_3$   $\Psi$   $\Phi$ 
  assume  $\langle \Gamma_1, n_1 \vdash \Psi_1 \triangleright \Phi_1 \rangle = \langle \Gamma, n \vdash (K_1 \text{ time-delayed}\bowtie \text{ by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Psi \triangleright \Phi \rangle$ 
  and  $\langle \Gamma_2, n_2 \vdash \Psi_2 \triangleright \Phi_2 \rangle = \langle ((K_1 \uparrow n) \# \Gamma), n \vdash (K_3 \text{ sporadic}\sharp (\downarrow \tau_{var} (K_2, n) \oplus \delta\tau \downarrow) \text{ on } K_2) \triangleright \Psi \triangleright ((K_1 \text{ time-delayed}\bowtie \text{ by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Phi) \rangle$ 
  thus ?P using configuration_interp_stepwise_timedelayed_tvar_cases
    configuration_interpretation.simps by blast

next
  fix  $\Gamma$   $n$   $K_1$   $K_2$   $\Psi$   $\Phi$ 
  assume  $\langle \Gamma_1, n_1 \vdash \Psi_1 \triangleright \Phi_1 \rangle = \langle \Gamma, n \vdash ((K_1 \text{ weakly precedes } K_2) \# \Psi) \triangleright \Phi \rangle$ 
  and  $\langle \Gamma_2, n_2 \vdash \Psi_2 \triangleright \Phi_2 \rangle = \langle (((\# \leq K_2 n, \# \leq K_1 n] \in (\lambda(x, y). x \leq y)) \# \Gamma), n \vdash \Psi \triangleright ((K_1 \text{ weakly precedes } K_2) \# \Phi) \rangle$ 
  thus ?P using configuration_interp_stepwise_weakly_precedes_cases
    configuration_interpretation.simps by blast

next
  fix  $\Gamma$   $n$   $K_1$   $K_2$   $\Psi$   $\Phi$ 
  assume  $\langle \Gamma_1, n_1 \vdash \Psi_1 \triangleright \Phi_1 \rangle = \langle \Gamma, n \vdash ((K_1 \text{ strictly precedes } K_2) \# \Psi) \triangleright \Phi \rangle$ 
  and  $\langle \Gamma_2, n_2 \vdash \Psi_2 \triangleright \Phi_2 \rangle = \langle (((\# \leq K_2 n, \# < K_1 n] \in (\lambda(x, y). x \leq y)) \# \Gamma), n \vdash \Psi \triangleright ((K_1 \text{ strictly precedes } K_2) \# \Phi) \rangle$ 
  thus ?P using configuration_interp_stepwise_strictly_precedes_cases
    configuration_interpretation.simps by blast

next
  fix  $\Gamma$   $n$   $K_1$   $K_2$   $\Psi$   $\Phi$ 
  assume  $\langle \Gamma_1, n_1 \vdash \Psi_1 \triangleright \Phi_1 \rangle = \langle \Gamma, n \vdash ((K_1 \text{ kills } K_2) \# \Psi) \triangleright \Phi \rangle$ 
  and  $\langle \Gamma_2, n_2 \vdash \Psi_2 \triangleright \Phi_2 \rangle = \langle ((K_1 \neg\uparrow n) \# \Gamma), n \vdash \Psi \triangleright ((K_1 \text{ kills } K_2) \# \Phi) \rangle$ 
  thus ?P using configuration_interp_stepwise_kills_cases

```

```

configuration_interpretation.simps by blast

next
  fix  $\Gamma$   $n$   $K_1$   $K_2$   $\Psi$   $\Phi$ 
  assume  $\langle \Gamma_1, n_1 \vdash \Psi_1 \triangleright \Phi_1 \rangle = \langle \Gamma, n \vdash ((K_1 \text{ kills } K_2) \# \Psi) \triangleright \Phi \rangle$ 
  and  $\langle \Gamma_2, n_2 \vdash \Psi_2 \triangleright \Phi_2 \rangle =$ 
     $\langle ((K_1 \uparrow n) \# (K_2 \neg \uparrow \geq n) \# \Gamma), n \vdash \Psi \triangleright ((K_1 \text{ kills } K_2) \# \Phi) \rangle$ 
  thus ?P using configuration_interp_stepwise_kills_cases
    configuration_interpretation.simps by blast

qed
qed
qed

inductive_cases step_elim:  $\langle S_1 \hookrightarrow S_2 \rangle$ 

lemma sound_reduction':
  assumes  $\langle S_1 \hookrightarrow S_2 \rangle$ 
  shows  $\langle \llbracket S_1 \rrbracket_{config} \supseteq \llbracket S_2 \rrbracket_{config} \rangle$ 
proof -
  have  $\langle \forall s_1 s_2. (\llbracket s_2 \rrbracket_{config} \subseteq \llbracket s_1 \rrbracket_{config}) \vee \neg(s_1 \hookrightarrow s_2) \rangle$ 
    using sound_reduction by fastforce
  thus ?thesis using assms by blast
qed

lemma sound_reduction_generalized:
  assumes  $\langle S_1 \hookrightarrow^k S_2 \rangle$ 
  shows  $\langle \llbracket S_1 \rrbracket_{config} \supseteq \llbracket S_2 \rrbracket_{config} \rangle$ 
proof -
  from assms show ?thesis
  proof (induction k arbitrary:  $S_2$ )
    case 0
    hence *:  $\langle S_1 \hookrightarrow^0 S_2 \implies S_1 = S_2 \rangle$  by auto
    moreover have  $\langle S_1 = S_2 \rangle$  using * "0.prem" by linarith
    ultimately show ?case by auto
  next
    case (Suc k)
    thus ?case
    proof -
      fix k :: nat
      assume ff:  $\langle S_1 \hookrightarrow^{Suc\ k} S_2 \rangle$ 
      assume hi:  $\langle \bigwedge S_2. S_1 \hookrightarrow^k S_2 \implies \llbracket S_2 \rrbracket_{config} \subseteq \llbracket S_1 \rrbracket_{config} \rangle$ 
      obtain  $S_n$  where red_decomp:  $\langle (S_1 \hookrightarrow^k S_n) \wedge (S_n \hookrightarrow S_2) \rangle$  using ff by auto
      hence  $\langle \llbracket S_1 \rrbracket_{config} \supseteq \llbracket S_n \rrbracket_{config} \rangle$  using hi by simp
      also have  $\langle \llbracket S_n \rrbracket_{config} \supseteq \llbracket S_2 \rrbracket_{config} \rangle$  by (simp add: red_decomp sound_reduction')
      ultimately show  $\langle \llbracket S_1 \rrbracket_{config} \supseteq \llbracket S_2 \rrbracket_{config} \rangle$  by simp
    qed
  qed
qed
qed

```

From the initial configuration, a configuration  $S$  obtained after any number  $k$  of reduction steps denotes runs from the initial specification  $\Psi$ .

```

theorem soundness:
  assumes  $\langle \langle [], 0 \vdash \Psi \triangleright [] \rangle \hookrightarrow^k S \rangle$ 
  shows  $\langle \llbracket \Psi \rrbracket_{TESL} \supseteq \llbracket S \rrbracket_{config} \rangle$ 
  using assms sound_reduction_generalized solve_start by blast

```

## 7.3 Completeness

We will now show that any run that satisfies a specification can be derived from the initial configuration, at any number of steps.

We start by proving that any run that is denoted by a configuration  $\mathcal{S}$  is necessarily denoted by at least one of the configurations that can be reached from  $\mathcal{S}$ .

```

lemma complete_direct_successors:
  shows  $\langle \llbracket \Gamma, n \vdash \Psi \triangleright \Phi \rrbracket_{config} \subseteq (\bigcup_{X \in C_{next}} (\Gamma, n \vdash \Psi \triangleright \Phi). \llbracket X \rrbracket_{config}) \rangle$ 
proof (induct  $\Psi$ )
  case Nil
  show ?case
    using configuration_interp_stepwise_instant_cases operational_semantics_step.simps
      operational_semantics_intro.instant_i
    by fastforce
next
  case (Cons  $\psi$   $\Psi$ ) thus ?case
  proof (cases  $\psi$ )
    case (SporadicOn  $K_1 \tau K_2$ ) thus ?thesis
      using configuration_interp_stepwise_sporadicon_cases
        [of  $\langle \Gamma \rangle \langle n \rangle \langle K_1 \rangle \langle \tau \rangle \langle K_2 \rangle \langle \Psi \rangle \langle \Phi \rangle$ ]
        Cnext_solve_sporadicon[of  $\langle \Gamma \rangle \langle n \rangle \langle \Psi \rangle \langle K_1 \rangle \langle \tau \rangle \langle K_2 \rangle \langle \Phi \rangle$ ] by blast
  next
    case (SporadicOnTvar  $X_1 X_2 X_3$ ) thus ?thesis
      using configuration_interp_stepwise_sporadicon_tvar_cases
        [of  $\langle \Gamma \rangle \langle n \rangle \langle X_1 \rangle \langle X_2 \rangle \langle X_3 \rangle \langle \Psi \rangle \langle \Phi \rangle$ ]
        Cnext_solve_sporadicon_tvar[of  $\langle \Gamma \rangle \langle n \rangle \langle \Psi \rangle \langle X_1 \rangle \langle X_2 \rangle \langle X_3 \rangle \langle \Phi \rangle$ ] by blast
  next
    case (TagRelation  $K_1 K_2 R$ ) thus ?thesis
      using configuration_interp_stepwise_tagrel_cases
        [of  $\langle \Gamma \rangle \langle n \rangle \langle K_1 \rangle \langle K_2 \rangle \langle R \rangle \langle \Psi \rangle \langle \Phi \rangle$ ]
        Cnext_solve_tagrel[of  $\langle K_1 \rangle \langle n \rangle \langle K_2 \rangle \langle R \rangle \langle \Gamma \rangle \langle \Psi \rangle \langle \Phi \rangle$ ] by blast
  next
    case (Implies  $K_1 K_2$ ) thus ?thesis
      using configuration_interp_stepwise_implies_cases
        [of  $\langle \Gamma \rangle \langle n \rangle \langle K_1 \rangle \langle K_2 \rangle \langle \Psi \rangle \langle \Phi \rangle$ ]
        Cnext_solve_implies[of  $\langle K_1 \rangle \langle n \rangle \langle \Gamma \rangle \langle \Psi \rangle \langle K_2 \rangle \langle \Phi \rangle$ ] by blast
  next
    case (ImpliesNot  $K_1 K_2$ ) thus ?thesis
      using configuration_interp_stepwise_implies_not_cases
        [of  $\langle \Gamma \rangle \langle n \rangle \langle K_1 \rangle \langle K_2 \rangle \langle \Psi \rangle \langle \Phi \rangle$ ]
        Cnext_solve_implies_not[of  $\langle K_1 \rangle \langle n \rangle \langle \Gamma \rangle \langle \Psi \rangle \langle K_2 \rangle \langle \Phi \rangle$ ] by blast
  next
    case (TimeDelayedBy  $K_{mast} \tau K_{meas} K_{slave}$ ) thus ?thesis
      using configuration_interp_stepwise_timedelayed_cases
        [of  $\langle \Gamma \rangle \langle n \rangle \langle K_{mast} \rangle \langle \tau \rangle \langle K_{meas} \rangle \langle K_{slave} \rangle \langle \Psi \rangle \langle \Phi \rangle$ ]
        Cnext_solve_timedelayed
        [of  $\langle K_{mast} \rangle \langle n \rangle \langle \Gamma \rangle \langle \Psi \rangle \langle \tau \rangle \langle K_{meas} \rangle \langle K_{slave} \rangle \langle \Phi \rangle$ ] by blast
  next
    case (RelaxedTimeDelayed  $K_{mast} \tau K_{meas} K_{slave}$ ) thus ?thesis
      using configuration_interp_stepwise_timedelayed_tvar_cases
        [of  $\langle \Gamma \rangle \langle n \rangle \langle K_{mast} \rangle \langle \tau \rangle \langle K_{meas} \rangle \langle K_{slave} \rangle \langle \Psi \rangle \langle \Phi \rangle$ ]
        Cnext_solve_timedelayed_tvar
        [of  $\langle K_{mast} \rangle \langle n \rangle \langle \Gamma \rangle \langle \Psi \rangle \langle \tau \rangle \langle K_{meas} \rangle \langle K_{slave} \rangle \langle \Phi \rangle$ ] by blast
  next
    case (WeaklyPrecedes  $K_1 K_2$ ) thus ?thesis
      using configuration_interp_stepwise_weakly_precedes_cases
        [of  $\langle \Gamma \rangle \langle n \rangle \langle K_1 \rangle \langle K_2 \rangle \langle \Psi \rangle \langle \Phi \rangle$ ]

```

```

      Cnext_solve_weakly_precedes[of <K2> <n> <K1> <Γ> <Ψ> <Φ>]
    by blast
  next
    case (StrictlyPrecedes K1 K2) thus ?thesis
      using configuration_interp_stepwise_strictly_precedes_cases
        [of <Γ> <n> <K1> <K2> <Ψ> <Φ>]
        Cnext_solve_strictly_precedes[of <K2> <n> <K1> <Γ> <Ψ> <Φ>]
      by blast
  next
    case (Kills K1 K2) thus ?thesis
      using configuration_interp_stepwise_kills_cases[of <Γ> <n> <K1> <K2> <Ψ> <Φ>]
        Cnext_solve_kills[of <K1> <n> <Γ> <Ψ> <K2> <Φ>] by blast
  qed
qed

lemma complete_direct_successors':
  shows <[ S ]_config ⊆ (⋃ X ∈ C_next S. [ X ]_config)>
proof -
  from configuration_interpretation.cases obtain Γ n Ψ Φ
    where <S = (Γ, n ⊢ Ψ ▷ Φ)> by blast
  with complete_direct_successors[of <Γ> <n> <Ψ> <Φ>] show ?thesis by simp
qed

```

Therefore, if a run belongs to a configuration, it necessarily belongs to a configuration derived from it.

```

lemma branch_existence:
  assumes <ρ ∈ [ S1 ]_config>
  shows <∃ S2. (S1 ↦ S2) ∧ (ρ ∈ [ S2 ]_config)>
proof -
  from assms complete_direct_successors' have <ρ ∈ (⋃ X ∈ C_next S1. [ X ]_config)> by blast
  hence <∃ s ∈ C_next S1. ρ ∈ [ s ]_config> by simp
  thus ?thesis by blast
qed

lemma branch_existence':
  assumes <ρ ∈ [ S1 ]_config>
  shows <∃ S2. (S1 ↦k S2) ∧ (ρ ∈ [ S2 ]_config)>
proof (induct k)
  case 0
    thus ?case by (simp add: assms)
  next
    case (Suc k)
      thus ?case
        using branch_existence relpowp_Suc_I[of <k> <operational_semantics_step>]
        by blast
  qed

```

Any run that belongs to the original specification  $\Psi$  has a corresponding configuration  $\mathcal{S}$  at any number  $k$  of reduction steps from the initial configuration. Therefore, any run that satisfies a specification can be derived from the initial configuration at any level of reduction.

```

theorem completeness:
  assumes <ρ ∈ [[ Ψ ]]_{TESL}>
  shows <∃ S. (([], 0 ⊢ Ψ ▷ []) ↦k S)
    ∧ ρ ∈ [ S ]_config>
  using assms branch_existence' solve_start by blast

```



## 7.4 Progress

Reduction steps do not guarantee that the construction of a run progresses in the sequence of instants. We need to show that it is always possible to reach the next instant, and therefore any future instant, through a number of steps.

```

lemma instant_index_increase:
  assumes  $\langle \varrho \in \llbracket \Gamma, n \vdash \Psi \triangleright \Phi \rrbracket_{config} \rangle$ 
  shows  $\langle \exists \Gamma_k \Psi_k \Phi_k k. ((\Gamma, n \vdash \Psi \triangleright \Phi) \hookrightarrow^k (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k)) \wedge \varrho \in \llbracket \Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k \rrbracket_{config} \rangle$ 
proof (insert assms, induct  $\Psi$  arbitrary:  $\Gamma \Phi$ )
  case (Nil  $\Gamma \Phi$ )
  then show ?case
  proof -
    have  $\langle (\Gamma, n \vdash [] \triangleright \Phi) \hookrightarrow^1 (\Gamma, \text{Suc } n \vdash \Phi \triangleright []) \rangle$ 
    using instant_i intro_part by fastforce
    moreover have  $\langle \llbracket \Gamma, n \vdash [] \triangleright \Phi \rrbracket_{config} = \llbracket \Gamma, \text{Suc } n \vdash \Phi \triangleright [] \rrbracket_{config} \rangle$ 
    by auto
    moreover have  $\langle \varrho \in \llbracket \Gamma, \text{Suc } n \vdash \Phi \triangleright [] \rrbracket_{config} \rangle$ 
    using assms Nil.prem calculation(2) by blast
    ultimately show ?thesis by blast
  qed
next
  case (Cons  $\psi \Psi$ )
  then show ?case
  proof (induct  $\psi$ )
    case (SporadicOn  $K_1 \tau K_2$ )
    have branches:  $\langle \llbracket \Gamma, n \vdash ((K_1 \text{ sporadic } \tau \text{ on } K_2) \# \Psi) \triangleright \Phi \rrbracket_{config} = \llbracket \Gamma, n \vdash \Psi \triangleright ((K_1 \text{ sporadic } \tau \text{ on } K_2) \# \Phi) \rrbracket_{config} \cup \llbracket ((K_1 \uparrow n) \# (K_2 \downarrow n \otimes \tau) \# \Gamma), n \vdash \Psi \triangleright \Phi \rrbracket_{config} \rangle$ 
    using configuration_interp_stepwise_sporadicon_cases by simp
    have br1:  $\langle \varrho \in \llbracket \Gamma, n \vdash \Psi \triangleright ((K_1 \text{ sporadic } \tau \text{ on } K_2) \# \Phi) \rrbracket_{config} \implies \exists \Gamma_k \Psi_k \Phi_k k. ((\Gamma, n \vdash ((K_1 \text{ sporadic } \tau \text{ on } K_2) \# \Psi) \triangleright \Phi) \hookrightarrow^k (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k)) \wedge \varrho \in \llbracket \Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k \rrbracket_{config} \rangle$ 
    proof -
      assume h1:  $\langle \varrho \in \llbracket \Gamma, n \vdash \Psi \triangleright ((K_1 \text{ sporadic } \tau \text{ on } K_2) \# \Phi) \rrbracket_{config} \rangle$ 
      hence  $\langle \exists \Gamma_k \Psi_k \Phi_k k. ((\Gamma, n \vdash \Psi \triangleright ((K_1 \text{ sporadic } \tau \text{ on } K_2) \# \Phi)) \hookrightarrow^k (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k)) \wedge (\varrho \in \llbracket \Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k \rrbracket_{config}) \rangle$ 
      using h1 SporadicOn.prem by simp
      from this obtain  $\Gamma_k \Psi_k \Phi_k k$  where
        fp:  $\langle (\Gamma, n \vdash \Psi \triangleright ((K_1 \text{ sporadic } \tau \text{ on } K_2) \# \Phi)) \hookrightarrow^k (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k) \rangle$ 
         $\wedge \varrho \in \llbracket \Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k \rrbracket_{config}$  by blast
      have
         $\langle (\Gamma, n \vdash ((K_1 \text{ sporadic } \tau \text{ on } K_2) \# \Psi) \triangleright \Phi) \hookrightarrow (\Gamma, n \vdash \Psi \triangleright ((K_1 \text{ sporadic } \tau \text{ on } K_2) \# \Phi)) \rangle$ 
        by (simp add: elims_part sporadic_on_e1)
      with fp relpowp_Suc_I2 have
         $\langle ((\Gamma, n \vdash ((K_1 \text{ sporadic } \tau \text{ on } K_2) \# \Psi) \triangleright \Phi) \hookrightarrow^{\text{Suc } k} (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k)) \rangle$  by auto
      thus ?thesis using fp by blast
    qed
    have br2:  $\langle \varrho \in \llbracket ((K_1 \uparrow n) \# (K_2 \downarrow n \otimes \tau) \# \Gamma), n \vdash \Psi \triangleright \Phi \rrbracket_{config} \implies \exists \Gamma_k \Psi_k \Phi_k k. ((\Gamma, n \vdash ((K_1 \text{ sporadic } \tau \text{ on } K_2) \# \Psi) \triangleright \Phi) \hookrightarrow^k (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k)) \wedge \varrho \in \llbracket \Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k \rrbracket_{config} \rangle$ 

```

proof -

assume h2:  $\langle \varrho \in \llbracket ((K_1 \uparrow n) \# (K_2 \downarrow n @ \tau) \# \Gamma), n \vdash \Psi \triangleright \Phi \rrbracket_{config} \rangle$   
 hence  $\langle \exists \Gamma_k \Psi_k \Phi_k k. (((K_1 \uparrow n) \# (K_2 \downarrow n @ \tau) \# \Gamma), n \vdash \Psi \triangleright \Phi) \hookrightarrow^k (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k) \rangle$   
 $\wedge \varrho \in \llbracket \Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k \rrbracket_{config} \rangle$   
 using h2 SporadicOn.premis by simp

from this obtain  $\Gamma_k \Psi_k \Phi_k k$   
 where fp:  $\langle (((K_1 \uparrow n) \# (K_2 \downarrow n @ \tau) \# \Gamma), n \vdash \Psi \triangleright \Phi) \hookrightarrow^k (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k) \rangle$   
 and rc:  $\langle \varrho \in \llbracket \Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k \rrbracket_{config} \rangle$  by blast  
 have pc:  $\langle (\Gamma, n \vdash ((K_1 \text{ sporadic } \tau \text{ on } K_2) \# \Psi) \triangleright \Phi) \hookrightarrow (((K_1 \uparrow n) \# (K_2 \downarrow n @ \tau) \# \Gamma), n \vdash \Psi \triangleright \Phi) \rangle$   
 by (simp add: elimis\_part sporadic\_on\_e2)  
 hence  $\langle (\Gamma, n \vdash (K_1 \text{ sporadic } \tau \text{ on } K_2) \# \Psi \triangleright \Phi) \hookrightarrow^{\text{Suc } k} (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k) \rangle$   
 using fp relpowp\_Suc\_I2 by auto  
 with rc show ?thesis by blast

qed

from branches SporadicOn.premis(2) have

$\langle \varrho \in \llbracket \Gamma, n \vdash \Psi \triangleright ((K_1 \text{ sporadic } \tau \text{ on } K_2) \# \Phi) \rrbracket_{config} \cup \llbracket ((K_1 \uparrow n) \# (K_2 \downarrow n @ \tau) \# \Gamma), n \vdash \Psi \triangleright \Phi \rrbracket_{config} \rangle$   
 by simp  
 with br1 br2 show ?case by blast

next

case (SporadicOnTvar  $K_1 \tau_{expr} K_2$ )  
 have branches:  $\langle \llbracket \Gamma, n \vdash ((K_1 \text{ sporadic} \# \tau_{expr} \text{ on } K_2) \# \Psi) \triangleright \Phi \rrbracket_{config} = \llbracket \Gamma, n \vdash \Psi \triangleright ((K_1 \text{ sporadic} \# \tau_{expr} \text{ on } K_2) \# \Phi) \rrbracket_{config} \cup \llbracket ((K_1 \uparrow n) \# (K_2 \downarrow n @ \tau_{expr}) \# \Gamma), n \vdash \Psi \triangleright \Phi \rrbracket_{config} \rangle$   
 using configuration\_interp\_stepwise\_sporadicon\_tvar\_cases by simp  
 have br1:  $\langle \varrho \in \llbracket \Gamma, n \vdash \Psi \triangleright ((K_1 \text{ sporadic} \# \tau_{expr} \text{ on } K_2) \# \Phi) \rrbracket_{config} \implies \exists \Gamma_k \Psi_k \Phi_k k. ((\Gamma, n \vdash ((K_1 \text{ sporadic} \# \tau_{expr} \text{ on } K_2) \# \Psi) \triangleright \Phi) \hookrightarrow^k (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k)) \wedge \varrho \in \llbracket \Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k \rrbracket_{config} \rangle$

proof -

assume h:  $\langle \varrho \in \llbracket \Gamma, n \vdash \Psi \triangleright ((K_1 \text{ sporadic} \# \tau_{expr} \text{ on } K_2) \# \Phi) \rrbracket_{config} \rangle$   
 hence  $\langle \exists \Gamma_k \Psi_k \Phi_k k. ((\Gamma, n \vdash \Psi \triangleright ((K_1 \text{ sporadic} \# \tau_{expr} \text{ on } K_2) \# \Phi)) \hookrightarrow^k (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k)) \wedge \varrho \in \llbracket \Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k \rrbracket_{config} \rangle$   
 using Cons.hyps by blast

from this obtain  $\Gamma_k \Psi_k \Phi_k k$  where

$\langle ((\Gamma, n \vdash \Psi \triangleright ((K_1 \text{ sporadic} \# \tau_{expr} \text{ on } K_2) \# \Phi)) \hookrightarrow^k (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k)) \rangle$

and \*:  $\langle \varrho \in \llbracket \Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k \rrbracket_{config} \rangle$  by blast

moreover have  $\langle (\Gamma, n \vdash ((K_1 \text{ sporadic} \# \tau_{expr} \text{ on } K_2) \# \Psi) \triangleright \Phi) \hookrightarrow (\Gamma, n \vdash \Psi \triangleright ((K_1 \text{ sporadic} \# \tau_{expr} \text{ on } K_2) \# \Phi)) \rangle$

by (simp add: sporadic\_on\_tvar\_e1 elimis\_part)

ultimately have  $\langle ((\Gamma, n \vdash ((K_1 \text{ sporadic} \# \tau_{expr} \text{ on } K_2) \# \Psi) \triangleright \Phi) \hookrightarrow^{\text{Suc } k} (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k)) \rangle$

using relpowp\_Suc\_I2[of <operational\_semantics\_step>] by blast

with \* have  $\langle ((\Gamma, n \vdash ((K_1 \text{ sporadic} \# \tau_{expr} \text{ on } K_2) \# \Psi) \triangleright \Phi) \hookrightarrow^{\text{Suc } k} (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k)) \rangle$

$\wedge \varrho \in \llbracket \Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k \rrbracket_{config} \rangle$  by simp

thus ?thesis by blast

qed

moreover have br2:  $\langle \varrho \in \llbracket ((K_1 \uparrow n) \# (K_2 \downarrow n @ \tau_{expr}) \# \Gamma), n \vdash \Psi \triangleright \Phi \rrbracket_{config} \implies \exists \Gamma_k \Psi_k \Phi_k k. ((\Gamma, n \vdash ((K_1 \text{ sporadic} \# \tau_{expr} \text{ on } K_2) \# \Psi) \triangleright \Phi) \hookrightarrow^k (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k)) \rangle$

```

     $\wedge \varrho \in \llbracket \Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k \rrbracket_{\text{config}}$ 
  proof -
    assume h:  $\langle \varrho \in \llbracket ((K_1 \uparrow n) \# (K_2 \downarrow n @ \# \tau_{\text{expr}}) \# \Gamma), n \vdash \Psi \triangleright \Phi \rrbracket_{\text{config}} \rangle$ 
    hence  $\langle \exists \Gamma_k \Psi_k \Phi_k k. \langle ((K_1 \uparrow n) \# (K_2 \downarrow n @ \# \tau_{\text{expr}}) \# \Gamma), n \vdash \Psi \triangleright \Phi \rangle \hookrightarrow^k (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k) \rangle$ 
     $\wedge \varrho \in \llbracket \Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k \rrbracket_{\text{config}}$ 
    using Cons.hyps by blast
    from this obtain  $\Gamma_k \Psi_k \Phi_k k$  where
       $\langle (((K_1 \uparrow n) \# (K_2 \downarrow n @ \# \tau_{\text{expr}}) \# \Gamma), n \vdash \Psi \triangleright \Phi) \hookrightarrow^k (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k) \rangle$ 
    and *:  $\langle \varrho \in \llbracket \Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k \rrbracket_{\text{config}} \rangle$  by blast
    moreover have  $\langle (\Gamma, n \vdash ((K_1 \text{ sporadic} \# \tau_{\text{expr}} \text{ on } K_2) \# \Psi) \triangleright \Phi) \hookrightarrow (((K_1 \uparrow n) \# (K_2 \downarrow n @ \# \tau_{\text{expr}}) \# \Gamma), n \vdash \Psi \triangleright \Phi) \rangle$ 
    by (simp add: sporadic_on_tvar_e2 elims_part)
    ultimately have  $\langle ((\Gamma, n \vdash ((K_1 \text{ sporadic} \# \tau_{\text{expr}} \text{ on } K_2) \# \Psi) \triangleright \Phi) \hookrightarrow^{\text{Suc } k} (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k)) \rangle$ 
    using relpowp_Suc_I2[of 'operational_semantics_step'] by blast
    with * have  $\langle ((\Gamma, n \vdash ((K_1 \text{ sporadic} \# \tau_{\text{expr}} \text{ on } K_2) \# \Psi) \triangleright \Phi) \hookrightarrow^{\text{Suc } k} (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k)) \rangle$ 
     $\wedge \varrho \in \llbracket \Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k \rrbracket_{\text{config}}$  by simp
    thus ?thesis by blast
  qed
  ultimately show ?case
    using branches SporadicOnTvar.premis(2) by blast
next
case (TagRelation K1 K2 R)
  have branches:  $\langle \llbracket \Gamma, n \vdash ((\text{time-relation } [K_1, K_2] \in R) \# \Psi) \triangleright \Phi \rrbracket_{\text{config}} = \llbracket ((\llbracket \tau_{\text{var}}(K_1, n), \tau_{\text{var}}(K_2, n) \rrbracket \in R) \# \Gamma), n \vdash \Psi \triangleright ((\text{time-relation } [K_1, K_2] \in R) \# \Phi) \rrbracket_{\text{config}} \rangle$ 
  using configuration_interp_stepwise_tagrel_cases by simp
  thus ?case
  proof -
    have  $\langle \exists \Gamma_k \Psi_k \Phi_k k. \langle (((\llbracket \tau_{\text{var}}(K_1, n), \tau_{\text{var}}(K_2, n) \rrbracket \in R) \# \Gamma), n \vdash \Psi \triangleright ((\text{time-relation } [K_1, K_2] \in R) \# \Phi)) \hookrightarrow^k (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k) \rangle \wedge \varrho \in \llbracket \Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k \rrbracket_{\text{config}} \rangle$ 
    using TagRelation.premis by simp
    from this obtain  $\Gamma_k \Psi_k \Phi_k k$ 
    where fp:  $\langle (((\llbracket \tau_{\text{var}}(K_1, n), \tau_{\text{var}}(K_2, n) \rrbracket \in R) \# \Gamma), n \vdash \Psi \triangleright ((\text{time-relation } [K_1, K_2] \in R) \# \Phi)) \hookrightarrow^k (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k) \rangle$ 
    and rc:  $\langle \varrho \in \llbracket \Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k \rrbracket_{\text{config}} \rangle$  by blast
    have pc:  $\langle (\Gamma, n \vdash ((\text{time-relation } [K_1, K_2] \in R) \# \Psi) \triangleright \Phi) \hookrightarrow (((\llbracket \tau_{\text{var}}(K_1, n), \tau_{\text{var}}(K_2, n) \rrbracket \in R) \# \Gamma), n \vdash \Psi \triangleright ((\text{time-relation } [K_1, K_2] \in R) \# \Phi)) \rangle$ 
    by (simp add: elims_part tagrel_e)
    hence  $\langle (\Gamma, n \vdash ((\text{time-relation } [K_1, K_2] \in R) \# \Psi) \triangleright \Phi) \hookrightarrow^{\text{Suc } k} (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k) \rangle$ 
    using fp relpowp_Suc_I2 by auto
    with rc show ?thesis by blast
  qed
next
case (Implies K1 K2)
  have branches:  $\langle \llbracket \Gamma, n \vdash ((K_1 \text{ implies } K_2) \# \Psi) \triangleright \Phi \rrbracket_{\text{config}} = \llbracket ((K_1 \rightarrow \uparrow n) \# \Gamma), n \vdash \Psi \triangleright ((K_1 \text{ implies } K_2) \# \Phi) \rrbracket_{\text{config}} \cup \llbracket ((K_1 \uparrow n) \# (K_2 \uparrow n) \# \Gamma), n \vdash \Psi \triangleright ((K_1 \text{ implies } K_2) \# \Phi) \rrbracket_{\text{config}} \rangle$ 
  using configuration_interp_stepwise_implies_cases by simp
  moreover have br1:  $\langle \varrho \in \llbracket ((K_1 \rightarrow \uparrow n) \# \Gamma), n \vdash \Psi \triangleright ((K_1 \text{ implies } K_2) \# \Phi) \rrbracket_{\text{config}} \rangle$ 

```

$\implies \exists \Gamma_k \Psi_k \Phi_k k. ((\Gamma, n \vdash ((K_1 \text{ implies } K_2) \# \Psi) \triangleright \Phi) \hookrightarrow^k (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k))$   
 $\wedge \varrho \in \llbracket \Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k \rrbracket_{\text{config}}$

proof -

assume h1:  $\langle \varrho \in \llbracket ((K_1 \neg\uparrow n) \# \Gamma), n \vdash \Psi \triangleright ((K_1 \text{ implies } K_2) \# \Phi) \rrbracket_{\text{config}} \rangle$   
 then have  $\langle \exists \Gamma_k \Psi_k \Phi_k k. ((\Gamma_k \neg\uparrow n) \# \Gamma), n \vdash \Psi \triangleright ((K_1 \text{ implies } K_2) \# \Phi) \rangle$   
 $\hookrightarrow^k (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k)$   
 $\wedge \varrho \in \llbracket \Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k \rrbracket_{\text{config}}$   
 using h1 `Implies.prem`s by simp  
 from this obtain  $\Gamma_k \Psi_k \Phi_k k$  where  
 fp:  $\langle (((K_1 \neg\uparrow n) \# \Gamma), n \vdash \Psi \triangleright ((K_1 \text{ implies } K_2) \# \Phi)) \hookrightarrow^k (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k) \rangle$   
 and rc:  $\langle \varrho \in \llbracket \Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k \rrbracket_{\text{config}} \rangle$  by blast  
 have pc:  $\langle (\Gamma, n \vdash (K_1 \text{ implies } K_2) \# \Psi \triangleright \Phi) \hookrightarrow ((K_1 \neg\uparrow n) \# \Gamma), n \vdash \Psi \triangleright ((K_1 \text{ implies } K_2) \# \Phi) \rangle$   
 by (simp add: `elims_part implies_e1`)  
 hence  $\langle (\Gamma, n \vdash (K_1 \text{ implies } K_2) \# \Psi \triangleright \Phi) \hookrightarrow^{\text{Suc } k} (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k) \rangle$   
 using fp `relpowp_Suc_I2` by auto  
 with rc show ?thesis by blast

qed

moreover have br2:  $\langle \varrho \in \llbracket ((K_1 \uparrow n) \# (K_2 \uparrow n) \# \Gamma), n \vdash \Psi \triangleright ((K_1 \text{ implies } K_2) \# \Phi) \rrbracket_{\text{config}} \implies \exists \Gamma_k \Psi_k \Phi_k k. ((\Gamma, n \vdash ((K_1 \text{ implies } K_2) \# \Psi) \triangleright \Phi) \hookrightarrow^k (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k)) \wedge \varrho \in \llbracket \Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k \rrbracket_{\text{config}} \rangle$

proof -

assume h2:  $\langle \varrho \in \llbracket ((K_1 \uparrow n) \# (K_2 \uparrow n) \# \Gamma), n \vdash \Psi \triangleright ((K_1 \text{ implies } K_2) \# \Phi) \rrbracket_{\text{config}} \rangle$   
 then have  $\langle \exists \Gamma_k \Psi_k \Phi_k k. ((\Gamma_k \uparrow n) \# (K_2 \uparrow n) \# \Gamma), n \vdash \Psi \triangleright ((K_1 \text{ implies } K_2) \# \Phi) \rangle$   
 $\hookrightarrow^k (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k)$   
 $\rangle \wedge \varrho \in \llbracket \Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k \rrbracket_{\text{config}}$   
 using h2 `Implies.prem`s by simp  
 from this obtain  $\Gamma_k \Psi_k \Phi_k k$  where  
 fp:  $\langle (((K_1 \uparrow n) \# (K_2 \uparrow n) \# \Gamma), n \vdash \Psi \triangleright ((K_1 \text{ implies } K_2) \# \Phi)) \hookrightarrow^k (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k) \rangle$   
 and rc:  $\langle \varrho \in \llbracket \Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k \rrbracket_{\text{config}} \rangle$  by blast  
 have  $\langle (\Gamma, n \vdash ((K_1 \text{ implies } K_2) \# \Psi) \triangleright \Phi) \hookrightarrow ((K_1 \uparrow n) \# (K_2 \uparrow n) \# \Gamma), n \vdash \Psi \triangleright ((K_1 \text{ implies } K_2) \# \Phi) \rangle$   
 by (simp add: `elims_part implies_e2`)  
 hence  $\langle (\Gamma, n \vdash ((K_1 \text{ implies } K_2) \# \Psi) \triangleright \Phi) \hookrightarrow^{\text{Suc } k} (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k) \rangle$   
 using fp `relpowp_Suc_I2` by auto  
 with rc show ?thesis by blast

qed

ultimately show ?case using `Implies.prem`s(2) by blast

next

case (ImpliesNot  $K_1 K_2$ )  
 have branches:  $\langle \llbracket \Gamma, n \vdash ((K_1 \text{ implies not } K_2) \# \Psi) \triangleright \Phi \rrbracket_{\text{config}} = \llbracket ((K_1 \neg\uparrow n) \# \Gamma), n \vdash \Psi \triangleright ((K_1 \text{ implies not } K_2) \# \Phi) \rrbracket_{\text{config}} \cup \llbracket ((K_1 \uparrow n) \# (K_2 \neg\uparrow n) \# \Gamma), n \vdash \Psi \triangleright ((K_1 \text{ implies not } K_2) \# \Phi) \rrbracket_{\text{config}} \rangle$   
 using `configuration_interp_stepwise_implies_not_cases` by simp  
 moreover have br1:  $\langle \varrho \in \llbracket ((K_1 \neg\uparrow n) \# \Gamma), n \vdash \Psi \triangleright ((K_1 \text{ implies not } K_2) \# \Phi) \rrbracket_{\text{config}} \implies \exists \Gamma_k \Psi_k \Phi_k k. ((\Gamma, n \vdash ((K_1 \text{ implies not } K_2) \# \Psi) \triangleright \Phi) \hookrightarrow^k (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k)) \wedge \varrho \in \llbracket \Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k \rrbracket_{\text{config}} \rangle$

proof -

assume h1:  $\langle \varrho \in \llbracket ((K_1 \neg\uparrow n) \# \Gamma), n \vdash \Psi \triangleright ((K_1 \text{ implies not } K_2) \# \Phi) \rrbracket_{\text{config}} \rangle$

then have  $\langle \exists \Gamma_k \Psi_k \Phi_k k.$   
 $(((\Gamma_k \neg \uparrow n) \# \Gamma), n \vdash \Psi \triangleright ((K_1 \text{ implies not } K_2) \# \Phi))$   
 $\hookrightarrow^k (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k))$   
 $\wedge \varrho \in \llbracket \Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k \rrbracket_{\text{config}}$   
 using h1 `ImpliesNot.prem`s by simp  
 from this obtain  $\Gamma_k \Psi_k \Phi_k k$  where  
 $\text{fp} : (((\Gamma_k \neg \uparrow n) \# \Gamma), n \vdash \Psi \triangleright ((K_1 \text{ implies not } K_2) \# \Phi))$   
 $\hookrightarrow^k (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k))$   
 and  $\text{rc} : \langle \varrho \in \llbracket \Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k \rrbracket_{\text{config}} \rangle$  by blast  
 have  $\text{pc} : (\Gamma, n \vdash (K_1 \text{ implies not } K_2) \# \Psi \triangleright \Phi)$   
 $\hookrightarrow ((\Gamma_k \neg \uparrow n) \# \Gamma), n \vdash \Psi \triangleright ((K_1 \text{ implies not } K_2) \# \Phi))$   
 by (simp add: `elims_part implies_not_e1`)  
 hence  $\langle \Gamma, n \vdash (K_1 \text{ implies not } K_2) \# \Psi \triangleright \Phi \rangle \hookrightarrow^{\text{Suc } k} (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k)$   
 using `fp relpowp_Suc_I2` by auto  
 with `rc` show ?thesis by blast  
 qed  
 moreover have  $\text{br2} : \langle \varrho \in \llbracket ((\Gamma_k \uparrow n) \# (K_2 \neg \uparrow n) \# \Gamma), n$   
 $\vdash \Psi \triangleright ((K_1 \text{ implies not } K_2) \# \Phi) \rrbracket_{\text{config}}$   
 $\implies \exists \Gamma_k \Psi_k \Phi_k k. ((\Gamma, n \vdash ((K_1 \text{ implies not } K_2) \# \Psi) \triangleright \Phi)$   
 $\hookrightarrow^k (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k))$   
 $\wedge \varrho \in \llbracket \Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k \rrbracket_{\text{config}} \rangle$   
 proof -  
 assume  $\text{h2} : \langle \varrho \in \llbracket ((\Gamma_k \uparrow n) \# (K_2 \neg \uparrow n) \# \Gamma), n$   
 $\vdash \Psi \triangleright ((K_1 \text{ implies not } K_2) \# \Phi) \rrbracket_{\text{config}}$   
 then have  $\langle \exists \Gamma_k \Psi_k \Phi_k k. ($   
 $(((\Gamma_k \uparrow n) \# (K_2 \neg \uparrow n) \# \Gamma), n$   
 $\vdash \Psi \triangleright ((K_1 \text{ implies not } K_2) \# \Phi)) \hookrightarrow^k (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k)$   
 $\rangle \wedge \varrho \in \llbracket \Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k \rrbracket_{\text{config}}$   
 using `h2 ImpliesNot.prem`s by simp  
 from this obtain  $\Gamma_k \Psi_k \Phi_k k$  where  
 $\text{fp} : (((\Gamma_k \uparrow n) \# (K_2 \neg \uparrow n) \# \Gamma), n \vdash \Psi \triangleright ((K_1 \text{ implies not } K_2) \# \Phi))$   
 $\hookrightarrow^k (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k)$   
 and  $\text{rc} : \langle \varrho \in \llbracket \Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k \rrbracket_{\text{config}} \rangle$  by blast  
 have  $\langle \Gamma, n \vdash ((K_1 \text{ implies not } K_2) \# \Psi) \triangleright \Phi \rangle$   
 $\hookrightarrow (((\Gamma_k \uparrow n) \# (K_2 \neg \uparrow n) \# \Gamma), n \vdash \Psi \triangleright ((K_1 \text{ implies not } K_2) \# \Phi))$   
 by (simp add: `elims_part implies_not_e2`)  
 hence  $\langle \Gamma, n \vdash ((K_1 \text{ implies not } K_2) \# \Psi) \triangleright \Phi \rangle$   
 $\hookrightarrow^{\text{Suc } k} (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k)$   
 using `fp relpowp_Suc_I2` by auto  
 with `rc` show ?thesis by blast  
 qed  
 ultimately show ?case using `ImpliesNot.prem`s(2) by blast  
 next  
 case `(TimeDelayedBy K1  $\delta\tau$  K2 K3)`  
 have branches:  
 $\langle \llbracket \Gamma, n \vdash ((K_1 \text{ time-delayed by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Psi) \triangleright \Phi \rrbracket_{\text{config}}$   
 $= \llbracket ((\Gamma_k \neg \uparrow n) \# \Gamma), n$   
 $\vdash \Psi \triangleright ((K_1 \text{ time-delayed by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Phi) \rrbracket_{\text{config}}$   
 $\cup \llbracket ((\Gamma_k \uparrow n) \# (K_2 \oplus n \oplus \delta\tau \Rightarrow K_3) \# \Gamma), n$   
 $\vdash \Psi \triangleright ((K_1 \text{ time-delayed by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Phi) \rrbracket_{\text{config}} \rangle$   
 using `configuration_interp_stepwise_timedelayed_cases` by simp  
 moreover have  $\text{br1} :$   
 $\langle \varrho \in \llbracket ((\Gamma_k \neg \uparrow n) \# \Gamma), n$   
 $\vdash \Psi \triangleright ((K_1 \text{ time-delayed by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Phi) \rrbracket_{\text{config}}$   
 $\implies \exists \Gamma_k \Psi_k \Phi_k k.$   
 $((\Gamma, n \vdash ((K_1 \text{ time-delayed by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Psi) \triangleright \Phi)$   
 $\hookrightarrow^k (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k))$   
 $\wedge \varrho \in \llbracket \Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k \rrbracket_{\text{config}} \rangle$   
 proof -

```

assume h1: ⟨ $\varrho \in \llbracket ((K_1 \neg\uparrow n) \# \Gamma), n$ 
            $\vdash \Psi \triangleright ((K_1 \text{ time-delayed by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Phi) \rrbracket_{config}$ ⟩
then have ⟨ $\exists \Gamma_k \Psi_k \Phi_k k.$ 
            $((((K_1 \neg\uparrow n) \# \Gamma), n \vdash \Psi \triangleright ((K_1 \text{ time-delayed by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Phi)))$ 
            $\hookrightarrow^k (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k))$ 
            $\wedge \varrho \in \llbracket \Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k \rrbracket_{config}$ ⟩
using h1 TimeDelayedBy.prem by simp
from this obtain  $\Gamma_k \Psi_k \Phi_k k$ 
where fp:⟨ $((((K_1 \neg\uparrow n) \# \Gamma), n$ 
            $\vdash \Psi \triangleright ((K_1 \text{ time-delayed by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Phi)))$ 
            $\hookrightarrow^k (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k))$ 
           and rc:⟨ $\varrho \in \llbracket \Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k \rrbracket_{config}$ ⟩ by blast
have ⟨ $(\Gamma, n \vdash ((K_1 \text{ time-delayed by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Psi) \triangleright \Phi)$ 
            $\hookrightarrow ((K_1 \neg\uparrow n) \# \Gamma), n$ 
            $\vdash \Psi \triangleright ((K_1 \text{ time-delayed by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Phi))$ 
           by (simp add: elim_part timedelayed_e1)
hence ⟨ $(\Gamma, n \vdash ((K_1 \text{ time-delayed by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Psi) \triangleright \Phi)$ 
            $\hookrightarrow^{\text{Suc } k} (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k)$ ⟩
using fp relpowp_Suc_I2 by auto
with rc show ?thesis by blast
qed
moreover have br2:
  ⟨ $\varrho \in \llbracket ((K_1 \uparrow n) \# (K_2 @ n \oplus \delta\tau \Rightarrow K_3) \# \Gamma), n$ 
            $\vdash \Psi \triangleright ((K_1 \text{ time-delayed by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Phi) \rrbracket_{config}$ 
            $\Rightarrow \exists \Gamma_k \Psi_k \Phi_k k.$ 
            $((\Gamma, n \vdash ((K_1 \text{ time-delayed by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Psi) \triangleright \Phi)$ 
            $\hookrightarrow^k (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k))$ 
            $\wedge \varrho \in \llbracket \Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k \rrbracket_{config}$ ⟩
proof -
  assume h2: ⟨ $\varrho \in \llbracket ((K_1 \uparrow n) \# (K_2 @ n \oplus \delta\tau \Rightarrow K_3) \# \Gamma), n$ 
            $\vdash \Psi \triangleright ((K_1 \text{ time-delayed by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Phi) \rrbracket_{config}$ ⟩
  then have ⟨ $\exists \Gamma_k \Psi_k \Phi_k k. ((((K_1 \uparrow n) \# (K_2 @ n \oplus \delta\tau \Rightarrow K_3) \# \Gamma), n$ 
            $\vdash \Psi \triangleright ((K_1 \text{ time-delayed by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Phi)))$ 
            $\hookrightarrow^k (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k))$ 
            $\wedge \varrho \in \llbracket \Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k \rrbracket_{config}$ ⟩
  using h2 TimeDelayedBy.prem by simp
  from this obtain  $\Gamma_k \Psi_k \Phi_k k$ 
  where fp:⟨ $((((K_1 \uparrow n) \# (K_2 @ n \oplus \delta\tau \Rightarrow K_3) \# \Gamma), n$ 
            $\vdash \Psi \triangleright ((K_1 \text{ time-delayed by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Phi)))$ 
            $\hookrightarrow^k (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k)$ 
           and rc:⟨ $\varrho \in \llbracket \Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k \rrbracket_{config}$ ⟩ by blast
  have ⟨ $(\Gamma, n \vdash ((K_1 \text{ time-delayed by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Psi) \triangleright \Phi)$ 
            $\hookrightarrow ((K_1 \uparrow n) \# (K_2 @ n \oplus \delta\tau \Rightarrow K_3) \# \Gamma), n$ 
            $\vdash \Psi \triangleright ((K_1 \text{ time-delayed by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Phi))$ 
           by (simp add: elim_part timedelayed_e2)
  with fp relpowp_Suc_I2 have
    ⟨ $(\Gamma, n \vdash ((K_1 \text{ time-delayed by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Psi) \triangleright \Phi)$ 
            $\hookrightarrow^{\text{Suc } k} (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k)$ ⟩
  by auto
  with rc show ?thesis by blast
qed
ultimately show ?case using TimeDelayedBy.prem(2) by blast
next
case (RelaxedTimeDelayed  $K_1 \delta\tau K_2 K_3$ )
have branches:
  ⟨ $\llbracket \Gamma, n \vdash ((K_1 \text{ time-delayed} \bowtie \text{ by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Psi) \triangleright \Phi \rrbracket_{config}$ 
           =  $\llbracket ((K_1 \neg\uparrow n) \# \Gamma), n$ 
            $\vdash \Psi \triangleright ((K_1 \text{ time-delayed} \bowtie \text{ by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Phi) \rrbracket_{config}$ 
            $\cup \llbracket ((K_1 \uparrow n) \# \Gamma), n$ 

```

```

    ⊢ (K3 sporadic# (⌊τvar(K2, n) ⊕ δτ⌋ on K2) # Ψ
    ▷ ((K1 time-delayed⊔ by δτ on K2 implies K3) # Φ) ]]config⟩
  using configuration_interp_stepwise_timedelayed_tvar_cases by simp
have more_branches:
  ⟨⌊ ((K1 ↑ n) # Γ), n ⊢ ((K3 sporadic# (⌊τvar(K2, n) ⊕ δτ⌋ on K2) # Ψ)
    ▷ ((K1 time-delayed⊔ by δτ on K2 implies K3) # Φ) ]]config⟩
  = ⌊ ((K1 ↑ n) # Γ), n ⊢ Ψ
    ▷ ((K3 sporadic# (⌊τvar(K2, n) ⊕ δτ⌋ on K2)
      # (K1 time-delayed⊔ by δτ on K2 implies K3) # Φ) ]]config
  ∪ ⌊ ((K3 ↑ n) # (K2 ↓ n @# (⌊τvar(K2, n) ⊕ δτ⌋) # (K1 ↑ n) # Γ), n
    ⊢ Ψ ▷ ((K1 time-delayed⊔ by δτ on K2 implies K3) # Φ) ]]config⟩
  using configuration_interp_stepwise_sporadicon_tvar_cases by blast
moreover have br1:
  ⟨ϱ ∈ ⌊ ((K1 ↗ n) # Γ), n
    ⊢ Ψ ▷ ((K1 time-delayed⊔ by δτ on K2 implies K3) # Φ) ]]config
  ⇒ ∃ Γk Ψk Φk k.
    ((Γ, n ⊢ ((K1 time-delayed⊔ by δτ on K2 implies K3) # Ψ) ▷ Φ)
    ↪k (Γk, Suc n ⊢ Ψk ▷ Φk}))
    ∧ ϱ ∈ ⌊ Γk, Suc n ⊢ Ψk ▷ Φk ]]config⟩
proof -
  assume h1: ⟨ϱ ∈ ⌊ ((K1 ↗ n) # Γ), n
    ⊢ Ψ ▷ ((K1 time-delayed⊔ by δτ on K2 implies K3) # Φ) ]]config⟩
  then have ⟨∃ Γk Ψk Φk k.
    (((K1 ↗ n) # Γ), n ⊢ Ψ ▷ ((K1 time-delayed⊔ by δτ on K2 implies K3) # Φ))
    ↪k (Γk, Suc n ⊢ Ψk ▷ Φk}))
    ∧ ϱ ∈ ⌊ Γk, Suc n ⊢ Ψk ▷ Φk ]]config⟩
  using h1 RelaxedTimeDelayed.premis by simp
  from this obtain Γk Ψk Φk k
  where fp: (((K1 ↗ n) # Γ), n
    ⊢ Ψ ▷ ((K1 time-delayed⊔ by δτ on K2 implies K3) # Φ))
    ↪k (Γk, Suc n ⊢ Ψk ▷ Φk}))
    and rc: ϱ ∈ ⌊ Γk, Suc n ⊢ Ψk ▷ Φk ]]config⟩ by blast
  have ⟨(Γ, n ⊢ ((K1 time-delayed⊔ by δτ on K2 implies K3) # Ψ) ▷ Φ)
    ↪ ((K1 ↗ n) # Γ), n
    ⊢ Ψ ▷ ((K1 time-delayed⊔ by δτ on K2 implies K3) # Φ))⟩
  by (simp add: elims_part timedelayed_tvar_e1)
  hence ⟨(Γ, n ⊢ ((K1 time-delayed⊔ by δτ on K2 implies K3) # Ψ) ▷ Φ)
    ↪Suc k (Γk, Suc n ⊢ Ψk ▷ Φk}))⟩
  using fp relpowp_Suc_I2 by auto
  with rc show ?thesis by blast
qed
moreover have br2:
  ⟨ϱ ∈ ⌊ ((K1 ↑ n) # Γ), n ⊢ Ψ ▷ ((K3 sporadic# (⌊τvar(K2, n) ⊕ δτ⌋ on K2)
    # (K1 time-delayed⊔ by δτ on K2 implies K3) # Φ) ]]config
  ⇒ ∃ Γk Ψk Φk k.
    ((Γ, n ⊢ ((K1 time-delayed⊔ by δτ on K2 implies K3) # Ψ) ▷ Φ)
    ↪k (Γk, Suc n ⊢ Ψk ▷ Φk})) ∧ ϱ ∈ ⌊ Γk, Suc n ⊢ Ψk ▷ Φk ]]config⟩
proof -
  assume h2: ⟨ϱ ∈ ⌊ ((K1 ↑ n) # Γ), n ⊢ Ψ
    ▷ ((K3 sporadic# (⌊τvar(K2, n) ⊕ δτ⌋ on K2)
      # (K1 time-delayed⊔ by δτ on K2 implies K3) # Φ) ]]config
  then have ⟨∃ Γk Ψk Φk k. (((K1 ↑ n) # Γ), n ⊢ Ψ
    ▷ ((K3 sporadic# (⌊τvar(K2, n) ⊕ δτ⌋ on K2)
      # (K1 time-delayed⊔ by δτ on K2 implies K3) # Φ))
    ↪k (Γk, Suc n ⊢ Ψk ▷ Φk})) ∧ ϱ ∈ ⌊ Γk, Suc n ⊢ Ψk ▷ Φk ]]config⟩
  using h2 RelaxedTimeDelayed.premis by simp
  from this obtain Γk Ψk Φk k where ⟨(((K1 ↑ n) # Γ), n ⊢ Ψ
    ▷ ((K3 sporadic# (⌊τvar(K2, n) ⊕ δτ⌋ on K2)
      # (K1 time-delayed⊔ by δτ on K2 implies K3) # Φ))

```

$\hookrightarrow^k (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k))$  and  $*(\varrho \in \llbracket \Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k \rrbracket_{\text{config}})$

by blast

moreover have  $\langle (\langle (K_1 \uparrow n) \# \Gamma \rangle, n$   
 $\vdash (K_3 \text{ sporadic} \# (\downarrow \tau_{\text{var}} (K_2, n) \oplus \delta\tau) \downarrow \text{ on } K_2) \# \Psi$   
 $\triangleright ((K_1 \text{ time-delayed} \bowtie \text{ by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Phi))$   
 $\hookrightarrow (\langle (K_1 \uparrow n) \# \Gamma \rangle, n$   
 $\vdash \Psi$   
 $\triangleright ((K_3 \text{ sporadic} \# (\downarrow \tau_{\text{var}} (K_2, n) \oplus \delta\tau) \downarrow \text{ on } K_2)$   
 $\# (K_1 \text{ time-delayed} \bowtie \text{ by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Phi)) \rangle$

by (simp add: elims\_part sporadic\_on\_tvar\_e1)

ultimately have  $\langle (\langle (K_1 \uparrow n) \# \Gamma \rangle, n$   
 $\vdash (K_3 \text{ sporadic} \# (\downarrow \tau_{\text{var}} (K_2, n) \oplus \delta\tau) \downarrow \text{ on } K_2) \# \Psi$   
 $\triangleright ((K_1 \text{ time-delayed} \bowtie \text{ by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Phi))$   
 $\hookrightarrow^{\text{Suc } k} (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k) \rangle$

using relpowp\_Suc\_I2[of 'operational\_semantics\_step'] by blast

moreover have  $\langle (\Gamma, n \vdash ((K_1 \text{ time-delayed} \bowtie \text{ by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Psi) \triangleright \Phi)$   
 $\hookrightarrow (\langle (K_1 \uparrow n) \# \Gamma \rangle, n$   
 $\vdash (K_3 \text{ sporadic} \# (\downarrow \tau_{\text{var}} (K_2, n) \oplus \delta\tau) \downarrow \text{ on } K_2) \# \Psi$   
 $\triangleright ((K_1 \text{ time-delayed} \bowtie \text{ by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Phi)) \rangle$

by (simp add: elims\_part timedelayed\_tvar\_e2)

ultimately have  $\langle (\Gamma, n \vdash ((K_1 \text{ time-delayed} \bowtie \text{ by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Psi) \triangleright \Phi)$   
 $\hookrightarrow^{\text{Suc}(\text{Suc } k)} (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k) \rangle$

using relpowp\_Suc\_I2[of 'operational\_semantics\_step'] by blast

with \* show ?thesis by blast

qed

moreover have br2':

$\langle \varrho \in \llbracket (\langle (K_3 \uparrow n) \# (K_2 \downarrow n \oplus \# (\downarrow \tau_{\text{var}} (K_2, n) \oplus \delta\tau)) \# (K_1 \uparrow n) \# \Gamma \rangle, n$   
 $\vdash \Psi \triangleright ((K_1 \text{ time-delayed} \bowtie \text{ by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Phi) \rrbracket_{\text{config}}$   
 $\implies \exists \Gamma_k \Psi_k \Phi_k k.$   
 $\langle (\Gamma, n \vdash ((K_1 \text{ time-delayed} \bowtie \text{ by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Psi) \triangleright \Phi)$   
 $\hookrightarrow^k (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k) \rangle \wedge \varrho \in \llbracket \Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k \rrbracket_{\text{config}} \rangle$

proof -

assume h2:  $\langle \varrho \in \llbracket (\langle (K_3 \uparrow n) \# (K_2 \downarrow n \oplus \# (\downarrow \tau_{\text{var}} (K_2, n) \oplus \delta\tau)) \# (K_1 \uparrow n) \# \Gamma \rangle, n$   
 $\vdash \Psi \triangleright ((K_1 \text{ time-delayed} \bowtie \text{ by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Phi) \rrbracket_{\text{config}}$

then have  $\langle \exists \Gamma_k \Psi_k \Phi_k k.$   
 $\langle (\langle (K_3 \uparrow n) \# (K_2 \downarrow n \oplus \# (\downarrow \tau_{\text{var}} (K_2, n) \oplus \delta\tau)) \# (K_1 \uparrow n) \# \Gamma \rangle, n$   
 $\vdash \Psi \triangleright ((K_1 \text{ time-delayed} \bowtie \text{ by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Phi) \rangle \hookrightarrow^k (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k) \rangle$   
 $\wedge \varrho \in \llbracket \Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k \rrbracket_{\text{config}} \rangle$

using h2 RelaxedTimeDelayed.premis by simp

from this obtain  $\Gamma_k \Psi_k \Phi_k k$  where  $\langle$   
 $\langle (\langle (K_3 \uparrow n) \# (K_2 \downarrow n \oplus \# (\downarrow \tau_{\text{var}} (K_2, n) \oplus \delta\tau)) \# (K_1 \uparrow n) \# \Gamma \rangle, n$   
 $\vdash \Psi \triangleright ((K_1 \text{ time-delayed} \bowtie \text{ by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Phi))$   
 $\hookrightarrow^k (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k) \rangle \rangle$

and  $*(\varrho \in \llbracket \Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k \rrbracket_{\text{config}})$  by blast

moreover have  $\langle (\langle (K_1 \uparrow n) \# \Gamma \rangle, n \vdash (K_3 \text{ sporadic} \# (\downarrow \tau_{\text{var}} (K_2, n) \oplus \delta\tau) \downarrow \text{ on } K_2) \# \Psi$   
 $\triangleright ((K_1 \text{ time-delayed} \bowtie \text{ by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Phi))$   
 $\hookrightarrow (\langle (K_3 \uparrow n) \# (K_2 \downarrow n \oplus \# (\downarrow \tau_{\text{var}} (K_2, n) \oplus \delta\tau)) \# (K_1 \uparrow n) \# \Gamma \rangle, n$   
 $\vdash \Psi \triangleright ((K_1 \text{ time-delayed} \bowtie \text{ by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Phi)) \rangle$

by (simp add: elims\_part sporadic\_on\_tvar\_e2)

ultimately have  $\langle (\langle (K_1 \uparrow n) \# \Gamma \rangle, n$   
 $\vdash (K_3 \text{ sporadic} \# (\downarrow \tau_{\text{var}} (K_2, n) \oplus \delta\tau) \downarrow \text{ on } K_2) \# \Psi$   
 $\triangleright ((K_1 \text{ time-delayed} \bowtie \text{ by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Phi))$   
 $\hookrightarrow^{\text{Suc } k} (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k) \rangle$

using relpowp\_Suc\_I2[of 'operational\_semantics\_step'] by blast

moreover have  $\langle (\Gamma, n \vdash ((K_1 \text{ time-delayed} \bowtie \text{ by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Psi) \triangleright \Phi)$   
 $\hookrightarrow (\langle (K_1 \uparrow n) \# \Gamma \rangle, n$   
 $\vdash (K_3 \text{ sporadic} \# (\downarrow \tau_{\text{var}} (K_2, n) \oplus \delta\tau) \downarrow \text{ on } K_2) \# \Psi$   
 $\triangleright ((K_1 \text{ time-delayed} \bowtie \text{ by } \delta\tau \text{ on } K_2 \text{ implies } K_3) \# \Phi)) \rangle$

by (simp add: elims\_part timedelayed\_tvar\_e2)



```

ultimately have ⟨⟨Γ, n ⊢ ((K1 time-delayed $\bowtie$  by  $\delta\tau$  on K2 implies K3) # Ψ) ▷ Φ⟩
  ↪Suc(Suc k) (Γk, Suc n ⊢ Ψk ▷ Φk⟩)⟩
  using relpowp_Suc_I2[of ⟨operational_semantics_step⟩] by blast
  with * show ?thesis by blast
qed
ultimately show ?case using RelaxedTimeDelayed.premis(2) branches more_branches by blast
next
case (WeaklyPrecedes K1 K2)
  have ⟨⟨Γ, n ⊢ ((K1 weakly precedes K2) # Ψ) ▷ Φ ⟩config =
    ⟨⟨([#≤ K2 n, #≤ K1 n] ∈ (λ(x, y). x ≤ y)) # Γ), n
      ⊢ Ψ ▷ ((K1 weakly precedes K2) # Φ) ⟩config⟩
    using configuration_interp_stepwise_weakly_precedes_cases by simp
  moreover have ⟨ϱ ∈ ⟨⟨([#≤ K2 n, #≤ K1 n] ∈ (λ(x, y). x ≤ y)) # Γ), n
    ⊢ Ψ ▷ ((K1 weakly precedes K2) # Φ) ⟩config
    ⇒ (∃Γk Ψk Φk k. (⟨Γ, n ⊢ ((K1 weakly precedes K2) # Ψ) ▷ Φ⟩
      ↪k (Γk, Suc n ⊢ Ψk ▷ Φk⟩)⟩
      ∧ (ϱ ∈ ⟨⟨Γk, Suc n ⊢ Ψk ▷ Φk ⟩config⟩)⟩
  proof -
    assume ⟨ϱ ∈ ⟨⟨([#≤ K2 n, #≤ K1 n] ∈ (λ(x, y). x ≤ y)) # Γ), n
      ⊢ Ψ ▷ ((K1 weakly precedes K2) # Φ) ⟩config⟩
    hence ⟨∃Γk Ψk Φk k. (⟨([#≤ K2 n, #≤ K1 n] ∈ (λ(x, y). x ≤ y)) # Γ), n
      ⊢ Ψ ▷ ((K1 weakly precedes K2) # Φ)⟩
      ↪k (Γk, Suc n ⊢ Ψk ▷ Φk⟩)⟩
      ∧ (ϱ ∈ ⟨⟨Γk, Suc n ⊢ Ψk ▷ Φk ⟩config⟩)⟩
    using WeaklyPrecedes.premis by simp
    from this obtain Γk Ψk Φk k
    where fp:⟨⟨([#≤ K2 n, #≤ K1 n] ∈ (λ(x, y). x ≤ y)) # Γ), n
      ⊢ Ψ ▷ ((K1 weakly precedes K2) # Φ)⟩
      ↪k (Γk, Suc n ⊢ Ψk ▷ Φk⟩)⟩
    and rc:⟨ϱ ∈ ⟨⟨Γk, Suc n ⊢ Ψk ▷ Φk ⟩config⟩ by blast
    have ⟨⟨Γ, n ⊢ ((K1 weakly precedes K2) # Ψ) ▷ Φ⟩
      ↪ (([#≤ K2 n, #≤ K1 n] ∈ (λ(x, y). x ≤ y)) # Γ), n
      ⊢ Ψ ▷ ((K1 weakly precedes K2) # Φ)⟩)
    by (simp add: elims_part_weakly_precedes_e)
    with fp relpowp_Suc_I2 have ⟨⟨Γ, n ⊢ ((K1 weakly precedes K2) # Ψ) ▷ Φ⟩
      ↪Suc k (Γk, Suc n ⊢ Ψk ▷ Φk⟩)⟩
    by auto
    with rc show ?thesis by blast
  qed
  ultimately show ?case using WeaklyPrecedes.premis(2) by blast
next
case (StrictlyPrecedes K1 K2)
  have ⟨⟨Γ, n ⊢ ((K1 strictly precedes K2) # Ψ) ▷ Φ ⟩config =
    ⟨⟨([#≤ K2 n, #< K1 n] ∈ (λ(x, y). x ≤ y)) # Γ), n
      ⊢ Ψ ▷ ((K1 strictly precedes K2) # Φ) ⟩config⟩
    using configuration_interp_stepwise_strictly_precedes_cases by simp
  moreover have ⟨ϱ ∈ ⟨⟨([#≤ K2 n, #< K1 n] ∈ (λ(x, y). x ≤ y)) # Γ), n
    ⊢ Ψ ▷ ((K1 strictly precedes K2) # Φ) ⟩config
    ⇒ (∃Γk Ψk Φk k. (⟨Γ, n ⊢ ((K1 strictly precedes K2) # Ψ) ▷ Φ⟩
      ↪k (Γk, Suc n ⊢ Ψk ▷ Φk⟩)⟩
      ∧ (ϱ ∈ ⟨⟨Γk, Suc n ⊢ Ψk ▷ Φk ⟩config⟩)⟩
  proof -
    assume ⟨ϱ ∈ ⟨⟨([#≤ K2 n, #< K1 n] ∈ (λ(x, y). x ≤ y)) # Γ), n
      ⊢ Ψ ▷ ((K1 strictly precedes K2) # Φ) ⟩config⟩
    hence ⟨∃Γk Ψk Φk k. (⟨([#≤ K2 n, #< K1 n] ∈ (λ(x, y). x ≤ y)) # Γ), n
      ⊢ Ψ ▷ ((K1 strictly precedes K2) # Φ)⟩
      ↪k (Γk, Suc n ⊢ Ψk ▷ Φk⟩)⟩
      ∧ (ϱ ∈ ⟨⟨Γk, Suc n ⊢ Ψk ▷ Φk ⟩config⟩)⟩
    using StrictlyPrecedes.premis by simp

```

```

from this obtain  $\Gamma_k \Psi_k \Phi_k k$ 
  where fp:  $\langle \langle \langle \# \leq K_2 n, \# < K_1 n \rangle \in (\lambda(x, y). x \leq y) \rangle \# \Gamma \rangle, n$ 
              $\vdash \Psi \triangleright \langle (K_1 \text{ strictly precedes } K_2) \# \Phi \rangle$ 
              $\hookrightarrow^k (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k)$ 
    and rc:  $\langle \varrho \in \llbracket \Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k \rrbracket_{\text{config}} \rangle$  by blast
have  $\langle (\Gamma, n \vdash \langle (K_1 \text{ strictly precedes } K_2) \# \Psi \rangle \triangleright \Phi) \rangle$ 
   $\hookrightarrow \langle \langle \langle \# \leq K_2 n, \# < K_1 n \rangle \in (\lambda(x, y). x \leq y) \rangle \# \Gamma \rangle, n$ 
   $\vdash \Psi \triangleright \langle (K_1 \text{ strictly precedes } K_2) \# \Phi \rangle$ 
  by (simp add: elims_part strictly_precedes_e)
with fp relpowp_Suc_I2 have  $\langle (\Gamma, n \vdash \langle (K_1 \text{ strictly precedes } K_2) \# \Psi \rangle \triangleright \Phi) \rangle$ 
   $\hookrightarrow^{\text{Suc } k} (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k)$ 

  by auto
  with rc show ?thesis by blast
qed
ultimately show ?case using StrictlyPrecedes.prem2 by blast
next
case (Kills  $K_1 K_2$ )
have branches:  $\langle \llbracket \Gamma, n \vdash \langle (K_1 \text{ kills } K_2) \# \Psi \rangle \triangleright \Phi \rrbracket_{\text{config}}$ 
   $= \llbracket \langle (K_1 \rightarrow n) \# \Gamma \rangle, n \vdash \Psi \triangleright \langle (K_1 \text{ kills } K_2) \# \Phi \rangle \rrbracket_{\text{config}}$ 
   $\cup \llbracket \langle (K_1 \uparrow n) \# (K_2 \rightarrow n) \# \Gamma \rangle, n \vdash \Psi \triangleright \langle (K_1 \text{ kills } K_2) \# \Phi \rangle \rrbracket_{\text{config}}$ 
  using configuration_interp_stepwise_kills_cases by simp
moreover have br1:  $\langle \varrho \in \llbracket \langle (K_1 \rightarrow n) \# \Gamma \rangle, n \vdash \Psi \triangleright \langle (K_1 \text{ kills } K_2) \# \Phi \rangle \rrbracket_{\text{config}}$ 
   $\implies \exists \Gamma_k \Psi_k \Phi_k k. \langle (\Gamma, n \vdash \langle (K_1 \text{ kills } K_2) \# \Psi \rangle \triangleright \Phi) \rangle$ 
   $\hookrightarrow^k (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k)$ 
   $\wedge \varrho \in \llbracket \Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k \rrbracket_{\text{config}}$ 

proof -
  assume h1:  $\langle \varrho \in \llbracket \langle (K_1 \rightarrow n) \# \Gamma \rangle, n \vdash \Psi \triangleright \langle (K_1 \text{ kills } K_2) \# \Phi \rangle \rrbracket_{\text{config}}$ 
  then have  $\langle \exists \Gamma_k \Psi_k \Phi_k k. \langle \langle \langle (K_1 \rightarrow n) \# \Gamma \rangle, n \vdash \Psi \triangleright \langle (K_1 \text{ kills } K_2) \# \Phi \rangle \rangle$ 
     $\hookrightarrow^k (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k)$ 
     $\wedge \varrho \in \llbracket \Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k \rrbracket_{\text{config}} \rangle$ 
    using h1 Kills.prem2 by simp
  from this obtain  $\Gamma_k \Psi_k \Phi_k k$  where
    fp:  $\langle \langle \langle \langle (K_1 \rightarrow n) \# \Gamma \rangle, n \vdash \Psi \triangleright \langle (K_1 \text{ kills } K_2) \# \Phi \rangle \rangle \rangle$ 
         $\hookrightarrow^k (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k) \rangle$ 
    and rc:  $\langle \varrho \in \llbracket \Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k \rrbracket_{\text{config}} \rangle$  by blast
  have pc:  $\langle (\Gamma, n \vdash \langle (K_1 \text{ kills } K_2) \# \Psi \rangle \triangleright \Phi) \rangle$ 
     $\hookrightarrow \langle \langle \langle (K_1 \rightarrow n) \# \Gamma \rangle, n \vdash \Psi \triangleright \langle (K_1 \text{ kills } K_2) \# \Phi \rangle \rangle \rangle$ 
    by (simp add: elims_part kills_e1)
  hence  $\langle (\Gamma, n \vdash \langle (K_1 \text{ kills } K_2) \# \Psi \rangle \triangleright \Phi) \rangle \hookrightarrow^{\text{Suc } k} (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k)$ 
    using fp relpowp_Suc_I2 by auto
  with rc show ?thesis by blast
qed
moreover have br2:
   $\langle \varrho \in \llbracket \langle (K_1 \uparrow n) \# (K_2 \rightarrow n) \# \Gamma \rangle, n \vdash \Psi \triangleright \langle (K_1 \text{ kills } K_2) \# \Phi \rangle \rrbracket_{\text{config}}$ 
   $\implies \exists \Gamma_k \Psi_k \Phi_k k. \langle (\Gamma, n \vdash \langle (K_1 \text{ kills } K_2) \# \Psi \rangle \triangleright \Phi) \rangle$ 
   $\hookrightarrow^k (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k)$ 
   $\wedge \varrho \in \llbracket \Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k \rrbracket_{\text{config}}$ 

proof -
  assume h2:  $\langle \varrho \in \llbracket \langle (K_1 \uparrow n) \# (K_2 \rightarrow n) \# \Gamma \rangle, n \vdash \Psi \triangleright \langle (K_1 \text{ kills } K_2) \# \Phi \rangle \rrbracket_{\text{config}}$ 
  then have  $\langle \exists \Gamma_k \Psi_k \Phi_k k. \langle \langle \langle (K_1 \uparrow n) \# (K_2 \rightarrow n) \# \Gamma \rangle, n \vdash \Psi \triangleright \langle (K_1 \text{ kills } K_2) \# \Phi \rangle \rangle$ 
     $\hookrightarrow^k (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k)$ 
     $\rangle \wedge \varrho \in \llbracket \Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k \rrbracket_{\text{config}} \rangle$ 
    using h2 Kills.prem2 by simp
  from this obtain  $\Gamma_k \Psi_k \Phi_k k$  where
    fp:  $\langle \langle \langle \langle (K_1 \uparrow n) \# (K_2 \rightarrow n) \# \Gamma \rangle, n \vdash \Psi \triangleright \langle (K_1 \text{ kills } K_2) \# \Phi \rangle \rangle \rangle$ 
         $\hookrightarrow^k (\Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k) \rangle$ 
    and rc:  $\langle \varrho \in \llbracket \Gamma_k, \text{Suc } n \vdash \Psi_k \triangleright \Phi_k \rrbracket_{\text{config}} \rangle$  by blast

```

```

have ⟨(Γ, n ⊢ ((K1 kills K2) # Ψ) ▷ Φ)
  ⇔ (((K1 ↑ n) # (K2 ↗ ≥ n) # Γ), n ⊢ Ψ ▷ ((K1 kills K2) # Φ))⟩
  by (simp add: elims_part kills_e2)
hence ⟨(Γ, n ⊢ ((K1 kills K2) # Ψ) ▷ Φ) ⇔Suc k (Γk, Suc n ⊢ Ψk ▷ Φk)⟩
  using fp relpowp_Suc_I2 by auto
with rc show ?thesis by blast
qed
ultimately show ?case using Kills.prem(2) by blast
qed
qed

lemma instant_index_increase_generalized:
  assumes ⟨n < nk⟩
  assumes ⟨ρ ∈ [Γ, n ⊢ Ψ ▷ Φ]config⟩
  shows ⟨∃Γk Ψk Φk k. ((Γ, n ⊢ Ψ ▷ Φ) ⇔k (Γk, nk ⊢ Ψk ▷ Φk))
    ∧ ρ ∈ [Γk, nk ⊢ Ψk ▷ Φk]config⟩
proof -
  obtain δk where diff: ⟨nk = δk + Suc n⟩
  using add commute assms(1) less_iff_Suc_add by auto
  show ?thesis
  proof (subst diff, subst diff, insert assms(2), induct δk)
    case 0 thus ?case
      using instant_index_increase assms(2) by simp
    next
      case (Suc δk)
      have f0: ⟨ρ ∈ [Γ, n ⊢ Ψ ▷ Φ]config ⇒ ∃Γk Ψk Φk k.
        ((Γ, n ⊢ Ψ ▷ Φ) ⇔k (Γk, δk + Suc n ⊢ Ψk ▷ Φk))
        ∧ ρ ∈ [Γk, δk + Suc n ⊢ Ψk ▷ Φk]config⟩
        using Suc.hyps by blast
      obtain Γk Ψk Φk k
      where cont: ⟨((Γ, n ⊢ Ψ ▷ Φ) ⇔k (Γk, δk + Suc n ⊢ Ψk ▷ Φk))
        ∧ ρ ∈ [Γk, δk + Suc n ⊢ Ψk ▷ Φk]config⟩
        using f0 assms(1) Suc.prem by blast
      then have fcontinue: ⟨∃Γk' Ψk' Φk' k'. ((Γk, δk + Suc n ⊢ Ψk ▷ Φk)
        ⇔k' (Γk', Suc (δk + Suc n) ⊢ Ψk' ▷ Φk')
        ∧ ρ ∈ [Γk', Suc (δk + Suc n) ⊢ Ψk' ▷ Φk']config⟩
        using f0 cont instant_index_increase by blast
      obtain Γk' Ψk' Φk' k'
      where cont2: ⟨((Γk, δk + Suc n ⊢ Ψk ▷ Φk)
        ⇔k' (Γk', Suc (δk + Suc n) ⊢ Ψk' ▷ Φk'))
        ∧ ρ ∈ [Γk', Suc (δk + Suc n) ⊢ Ψk' ▷ Φk']config⟩
        using Suc.prem using fcontinue cont by blast
      have trans: ⟨(Γ, n ⊢ Ψ ▷ Φ) ⇔k+k' (Γk', Suc (δk + Suc n) ⊢ Ψk' ▷ Φk')⟩
        using operational_semantics_trans_generalized cont cont2 by blast
      moreover have suc_assoc: ⟨Suc δk + Suc n = Suc (δk + Suc n)⟩ by arith
      ultimately show ?case
      proof (subst suc_assoc)
        show ⟨∃Γk Ψk Φk k.
          ((Γ, n ⊢ Ψ ▷ Φ) ⇔k (Γk, Suc (δk + Suc n) ⊢ Ψk ▷ Φk))
          ∧ ρ ∈ [Γk, Suc δk + Suc n ⊢ Ψk ▷ Φk]config⟩
          using cont2 local.trans by auto
        qed
      qed
    qed
  qed

```

Any run that belongs to a specification  $\Psi$  has a corresponding configuration that develops it up to the  $n^{\text{th}}$  instant.

**theorem progress:**

```

assumes ⟨ $\varrho \in \llbracket \Psi \rrbracket_{TESL}$ ⟩
shows ⟨ $\exists k \Gamma_k \Psi_k \Phi_k. ((\Box, 0 \vdash \Psi \triangleright \Box) \hookrightarrow^k (\Gamma_k, n \vdash \Psi_k \triangleright \Phi_k))$ ⟩
      ∧  $\varrho \in \llbracket \Gamma_k, n \vdash \Psi_k \triangleright \Phi_k \rrbracket_{config}$ ⟩
proof -
  have 1: ⟨ $\exists \Gamma_k \Psi_k \Phi_k k. ((\Box, 0 \vdash \Psi \triangleright \Box) \hookrightarrow^k (\Gamma_k, 0 \vdash \Psi_k \triangleright \Phi_k))$ ⟩
      ∧  $\varrho \in \llbracket \Gamma_k, 0 \vdash \Psi_k \triangleright \Phi_k \rrbracket_{config}$ ⟩
    using assms relpowp_0_I solve_start by fastforce
  show ?thesis
  proof (cases ⟨ $n = 0$ ⟩)
    case True
      thus ?thesis using assms relpowp_0_I solve_start by fastforce
    next
      case False hence pos: ⟨ $n > 0$ ⟩ by simp
      from assms solve_start have ⟨ $\varrho \in \llbracket \Box, 0 \vdash \Psi \triangleright \Box \rrbracket_{config}$ ⟩ by blast
      from instant_index_increase_generalized[OF pos this] show ?thesis by blast
  qed
qed

```

## 7.5 Local termination

Here, we prove that the computation of an instant in a run always terminates. Since this computation terminates when the list of constraints for the present instant becomes empty, we introduce a measure for this formula.

```

primrec measure_interpretation :: ⟨ $\tau::linordered\_field$   $TESL\_formula \Rightarrow nat$ ⟩ ⟨ $\mu$ ⟩
where
  ⟨ $\mu \Box = (0::nat)$ ⟩
| ⟨ $\mu (\varphi \# \Phi) = (case \varphi of$ 
    _ sporadic _ on _  $\Rightarrow 1 + \mu \Phi$ 
  | _ sporadic# _ on _  $\Rightarrow 1 + \mu \Phi$ 
  | _  $\Rightarrow 2 + \mu \Phi)$ ⟩

fun measure_interpretation_config :: ⟨ $\tau::linordered\_field$   $config \Rightarrow nat$ ⟩ ⟨ $\mu_{config}$ ⟩
where
  ⟨ $\mu_{config} (\Gamma, n \vdash \Psi \triangleright \Phi) = \mu \Psi$ ⟩

```

We then show that the elimination rules make this measure decrease.

```

lemma elimination_rules_strictly_decreasing:
  assumes ⟨ $(\Gamma_1, n_1 \vdash \Psi_1 \triangleright \Phi_1) \hookrightarrow_e (\Gamma_2, n_2 \vdash \Psi_2 \triangleright \Phi_2)$ ⟩
  shows ⟨ $\mu \Psi_1 > \mu \Psi_2$ ⟩
using assms by (auto elim: operational_semantics_elim.cases)

lemma elimination_rules_strictly_decreasing_meas:
  assumes ⟨ $(\Gamma_1, n_1 \vdash \Psi_1 \triangleright \Phi_1) \hookrightarrow_e (\Gamma_2, n_2 \vdash \Psi_2 \triangleright \Phi_2)$ ⟩
  shows ⟨ $(\Psi_2, \Psi_1) \in \text{measure } \mu$ ⟩
using assms by (auto elim: operational_semantics_elim.cases)

lemma elimination_rules_strictly_decreasing_meas':
  assumes ⟨ $S_1 \hookrightarrow_e S_2$ ⟩
  shows ⟨ $(S_2, S_1) \in \text{measure } \mu_{config}$ ⟩
proof -
  from assms obtain  $\Gamma_1 n_1 \Psi_1 \Phi_1$  where p1:  $S_1 = (\Gamma_1, n_1 \vdash \Psi_1 \triangleright \Phi_1)$ 
    using measure_interpretation_config.cases by blast
  from assms obtain  $\Gamma_2 n_2 \Psi_2 \Phi_2$  where p2:  $S_2 = (\Gamma_2, n_2 \vdash \Psi_2 \triangleright \Phi_2)$ 
    using measure_interpretation_config.cases by blast
  from elimination_rules_strictly_decreasing_meas assms p1 p2
    have ⟨ $(\Psi_2, \Psi_1) \in \text{measure } \mu$ ⟩ by blast

```

```

hence  $\langle \mu \Psi_2 < \mu \Psi_1 \rangle$  by simp
hence  $\langle \mu_{config} (\Gamma_2, n_2 \vdash \Psi_2 \triangleright \Phi_2) < \mu_{config} (\Gamma_1, n_1 \vdash \Psi_1 \triangleright \Phi_1) \rangle$  by simp
with p1 p2 show ?thesis by simp
qed

```

Therefore, the relation made up of elimination rules is well-founded and the computation of an instant terminates.

```

theorem instant_computation_termination:
   $\langle \text{wfP } (\lambda(S_1::'a::\text{linordered\_field config}) S_2. (S_1 \hookrightarrow_e^{\leftarrow} S_2)) \rangle$ 
proof (simp add: wfP_def)
  show  $\langle \text{wf } \{((S_1::'a::\text{linordered\_field config}), S_2). S_1 \hookrightarrow_e^{\leftarrow} S_2\} \rangle$ 
  proof (rule wf_subset)
    have  $\langle \text{measure } \mu_{config} = \{(S_2, (S_1::'a::\text{linordered\_field config})).$ 
       $\mu_{config} S_2 < \mu_{config} S_1\} \rangle$ 
    by (simp add: inv_image_def less_eq_measure_def)
    thus  $\langle \{((S_1::'a::\text{linordered\_field config}), S_2). S_1 \hookrightarrow_e^{\leftarrow} S_2\} \subseteq (\text{measure } \mu_{config}) \rangle$ 
    using elimination_rules_strictly_decreasing_meas'
      operational_semantics_elim_inv_def by blast
  next
    show  $\langle \text{wf } (\text{measure measure\_interpretation\_config}) \rangle$  by simp
  qed
qed
end

```



## Chapter 8

# Properties of TESL

### 8.1 Stuttering Invariance

**theory** StutteringDefs

**imports** Denotational

**begin**

When composing systems into more complex systems, it may happen that one system has to perform some action while the rest of the complex system does nothing. In order to support the composition of TESL specifications, we want to be able to insert stuttering instants in a run without breaking the conformance of a run to its specification. This is what we call the *stuttering invariance* of TESL.

#### 8.1.1 Definition of stuttering

We consider stuttering as the insertion of empty instants (instants at which no clock ticks) in a run. We characterize this insertion with a dilating function, which maps the instant indices of the original run to the corresponding instant indices of the dilated run. The properties of a dilating function are:

- it is strictly increasing because instants are inserted into the run,
- the image of an instant index is greater than it because stuttering instants can only delay the original instants of the run,
- no instant is inserted before the first one in order to have a well defined initial date on each clock,
- if  $n$  is not in the image of the function, no clock ticks at instant  $n$  and the date on the clocks do not change.

**definition** dilating\_fun

**where**

```
(dilating_fun (f::nat ⇒ nat) (r::'a::linordered_field run)
  ≡ strict_mono f ∧ (f 0 = 0) ∧ (∀n. f n ≥ n
  ∧ ((#n0. f n0 = n) ⇒ (∀c. ¬(ticks ((Rep_run r) n c))))
```




Figure 8.1: Dilating and contracting functions

$$\wedge ((\#n_0. f n_0 = (\text{Suc } n)) \longrightarrow (\forall c. \text{time } ((\text{Rep\_run } r) (\text{Suc } n) c) = \text{time } ((\text{Rep\_run } r) n c)))$$

))

A run  $r$  is a dilation of a run  $\text{sub}$  by function  $f$  if:

- $f$  is a dilating function for  $r$
- the time in  $r$  is the time in  $\text{sub}$  dilated by  $f$
- the ticks in  $r$  is the ticks in  $\text{sub}$  dilated by  $f$

**definition** dilating

**where**

$$\langle \text{dilating } f \text{ sub } r \equiv \text{dilating\_fun } f \text{ } r \wedge (\forall n \text{ c. time } ((\text{Rep\_run } \text{sub}) n \text{ c}) = \text{time } ((\text{Rep\_run } r) (f \text{ } n) \text{ c})) \wedge (\forall n \text{ c. ticks } ((\text{Rep\_run } \text{sub}) n \text{ c}) = \text{ticks } ((\text{Rep\_run } r) (f \text{ } n) \text{ c})) \rangle$$

A run is a *subrun* of another run if there exists a dilation between them.

**definition** is\_subrun :: ('a::linordered\_field run  $\Rightarrow$  'a run  $\Rightarrow$  bool) (infixl  $\ll$  60)

**where**

$$\langle \text{sub } \ll r \equiv (\exists f. \text{dilating } f \text{ sub } r) \rangle$$

A contracting function is the reverse of a dilating fun, it maps an instant index of a dilated run to the index of the last instant of a non stuttering run that precedes it. Since several successive stuttering instants are mapped to the same instant of the non stuttering run, such a function is monotonous, but not strictly. The image of the first instant of the dilated run is necessarily the first instant of the non stuttering run, and the image of an instant index is less than this index because we remove stuttering instants.

**definition** contracting\_fun

**where**  $\langle \text{contracting\_fun } g \equiv \text{mono } g \wedge g \text{ } 0 = 0 \wedge (\forall n. g \text{ } n \leq n) \rangle$

Figure 8.1 illustrates the relations between the instants of a run and the instants of a dilated run, with the mappings by the dilating function  $f$  and the contracting function  $g$ :

A function  $g$  is contracting with respect to the dilation of run  $\text{sub}$  into run  $r$  by the dilating function  $f$  if:



- it is a contracting function ;
- $(f \circ g) \ n$  is the index of the last original instant before instant  $n$  in run  $r$ , therefore:
  - $(f \circ g) \ n \leq n$
  - the time does not change on any clock between instants  $(f \circ g) \ n$  and  $n$  of run  $r$ ;
  - no clock ticks before  $n$  strictly after  $(f \circ g) \ n$  in run  $r$ . See [Figure 8.1](#) for a better understanding. Notice that in this example, 2 is equal to  $(f \circ g) \ 2$ ,  $(f \circ g) \ 3$ , and  $(f \circ g) \ 4$ .

**definition** contracting

where

```

⟨contracting g r sub f ≡ contracting_fun g
  ∧ (∀n. f (g n) ≤ n)
  ∧ (∀n c k. f (g n) ≤ k ∧ k ≤ n
    → time ((Rep_run r) k c) = time ((Rep_run sub) (g n) c))
  ∧ (∀n c k. f (g n) < k ∧ k ≤ n
    → ¬ ticks ((Rep_run r) k c))⟩

```

For any dilating function, we can build its *inverse*, as illustrated on [Figure 8.1](#), which is a contracting function:

**definition**  $\langle \text{dil\_inverse } f :: (\text{nat} \Rightarrow \text{nat}) \equiv (\lambda n. \text{Max } \{i. f \ i \leq n\}) \rangle$

### 8.1.2 Alternate definitions for counting ticks.

For proving the stuttering invariance of TESL specifications, we will need these alternate definitions for counting ticks, which are based on sets.

$\text{tick\_count } r \ c \ n$  is the number of ticks of clock  $c$  in run  $r$  upto instant  $n$ .

**definition**  $\text{tick\_count} :: \langle 'a :: \text{linordered\_field} \text{ run} \Rightarrow \text{clock} \Rightarrow \text{nat} \Rightarrow \text{nat} \rangle$

where

```

⟨tick_count r c n = card {i. i ≤ n ∧ ticks ((Rep_run r) i c)}⟩

```

$\text{tick\_count\_strict } r \ c \ n$  is the number of ticks of clock  $c$  in run  $r$  upto but excluding instant  $n$ .

**definition**  $\text{tick\_count\_strict} :: \langle 'a :: \text{linordered\_field} \text{ run} \Rightarrow \text{clock} \Rightarrow \text{nat} \Rightarrow \text{nat} \rangle$

where

```

⟨tick_count_strict r c n = card {i. i < n ∧ ticks ((Rep_run r) i c)}⟩

```

end

### 8.1.3 Stuttering Lemmas

**theory** StutteringLemmas

**imports** StutteringDefs

**begin**

In this section, we prove several lemmas that will be used to show that TESL specifications are invariant by stuttering.

The following one will be useful in proving properties over a sequence of stuttering instants.

```
lemma bounded_suc_ind:
  assumes ⟨ $\bigwedge k. k < m \implies P \text{ (Suc (z + k))} = P \text{ (z + k)}$ ⟩
  shows ⟨ $k < m \implies P \text{ (Suc (z + k))} = P \text{ z}$ ⟩
proof (induction k)
  case 0
  with assms(1)[of 0] show ?case by simp
next
  case (Suc k')
  with assms[of ⟨Suc k'⟩] show ?case by force
qed
```

#### 8.1.4 Lemmas used to prove the invariance by stuttering

Since a dilating function is strictly monotonous, it is injective.

```
lemma dilating_fun_injects:
  assumes ⟨dilating_fun f r⟩
  shows ⟨inj_on f A⟩
using assms dilating_fun_def strict_mono_imp_inj_on by blast
```

```
lemma dilating_injects:
  assumes ⟨dilating f sub r⟩
  shows ⟨inj_on f A⟩
using assms dilating_def dilating_fun_injects by blast
```

If a clock ticks at an instant in a dilated run, that instant is the image by the dilating function of an instant of the original run.

```
lemma ticks_image:
  assumes ⟨dilating_fun f r⟩
  and ⟨ticks ((Rep_run r) n c)⟩
  shows ⟨ $\exists n_0. f \ n_0 = n$ ⟩
using dilating_fun_def assms by blast
```

```
lemma ticks_image_sub:
  assumes ⟨dilating f sub r⟩
  and ⟨ticks ((Rep_run r) n c)⟩
  shows ⟨ $\exists n_0. f \ n_0 = n$ ⟩
using assms dilating_def ticks_image by blast
```

```
lemma ticks_image_sub':
  assumes ⟨dilating f sub r⟩
  and ⟨ $\exists c. \text{ticks} ((\text{Rep\_run } r) \ n \ c)$ ⟩
  shows ⟨ $\exists n_0. f \ n_0 = n$ ⟩
using ticks_image_sub[OF assms(1)] assms(2) by blast
```

The image of the ticks in an interval by a dilating function is the interval bounded by the image of the bounds of the original interval. This is proven for all 4 kinds of intervals:  $]m, n[$ ,  $[m, n[$ ,  $]m, n]$  and  $[m, n]$ .

```
lemma dilating_fun_image_strict:
  assumes ⟨dilating_fun f r⟩
  shows ⟨ $\{k. f \ m < k \wedge k < f \ n \wedge \text{ticks} ((\text{Rep\_run } r) \ k \ c)\}$ 
    = image f  $\{k. m < k \wedge k < n \wedge \text{ticks} ((\text{Rep\_run } r) \ (f \ k) \ c)\}$ ⟩
  (is ⟨?IMG = image f ?SET⟩)
proof
  { fix k assume h: ⟨ $k \in ?IMG$ ⟩
    from h obtain k0 where k0prop: ⟨ $f \ k_0 = k \wedge \text{ticks} ((\text{Rep\_run } r) \ (f \ k_0) \ c)$ ⟩
```

```

    using ticks_image[OF assms] by blast
    with h have ⟨k ∈ image f ?SET⟩
    using assms dilating_fun_def strict_mono_less by blast
  } thus ⟨?IMG ⊆ image f ?SET⟩ ..
next
  { fix k assume h:⟨k ∈ image f ?SET⟩
    from h obtain k0 where k0prop:⟨k = f k0 ∧ k0 ∈ ?SET⟩ by blast
    hence ⟨k ∈ ?IMG⟩ using assms by (simp add: dilating_fun_def strict_mono_less)
  } thus ⟨image f ?SET ⊆ ?IMG⟩ ..
qed

lemma dilating_fun_image_left:
  assumes ⟨dilating_fun f r⟩
  shows   ⟨{k. f m ≤ k ∧ k < f n ∧ ticks ((Rep_run r) k c)}
    = image f {k. m ≤ k ∧ k < n ∧ ticks ((Rep_run r) (f k) c)}⟩
  (is ⟨?IMG = image f ?SET⟩)
proof
  { fix k assume h:⟨k ∈ ?IMG⟩
    from h obtain k0 where k0prop:⟨f k0 = k ∧ ticks ((Rep_run r) (f k0) c)⟩
    using ticks_image[OF assms] by blast
    with h have ⟨k ∈ image f ?SET⟩
    using assms dilating_fun_def strict_mono_less strict_mono_less_eq by fastforce
  } thus ⟨?IMG ⊆ image f ?SET⟩ ..
next
  { fix k assume h:⟨k ∈ image f ?SET⟩
    from h obtain k0 where k0prop:⟨k = f k0 ∧ k0 ∈ ?SET⟩ by blast
    hence ⟨k ∈ ?IMG⟩
    using assms dilating_fun_def strict_mono_less strict_mono_less_eq by fastforce
  } thus ⟨image f ?SET ⊆ ?IMG⟩ ..
qed

lemma dilating_fun_image_right:
  assumes ⟨dilating_fun f r⟩
  shows   ⟨{k. f m < k ∧ k ≤ f n ∧ ticks ((Rep_run r) k c)}
    = image f {k. m < k ∧ k ≤ n ∧ ticks ((Rep_run r) (f k) c)}⟩
  (is ⟨?IMG = image f ?SET⟩)
proof
  { fix k assume h:⟨k ∈ ?IMG⟩
    from h obtain k0 where k0prop:⟨f k0 = k ∧ ticks ((Rep_run r) (f k0) c)⟩
    using ticks_image[OF assms] by blast
    with h have ⟨k ∈ image f ?SET⟩
    using assms dilating_fun_def strict_mono_less strict_mono_less_eq by fastforce
  } thus ⟨?IMG ⊆ image f ?SET⟩ ..
next
  { fix k assume h:⟨k ∈ image f ?SET⟩
    from h obtain k0 where k0prop:⟨k = f k0 ∧ k0 ∈ ?SET⟩ by blast
    hence ⟨k ∈ ?IMG⟩
    using assms dilating_fun_def strict_mono_less strict_mono_less_eq by fastforce
  } thus ⟨image f ?SET ⊆ ?IMG⟩ ..
qed

lemma dilating_fun_image:
  assumes ⟨dilating_fun f r⟩
  shows   ⟨{k. f m ≤ k ∧ k ≤ f n ∧ ticks ((Rep_run r) k c)}
    = image f {k. m ≤ k ∧ k ≤ n ∧ ticks ((Rep_run r) (f k) c)}⟩
  (is ⟨?IMG = image f ?SET⟩)
proof
  { fix k assume h:⟨k ∈ ?IMG⟩
    from h obtain k0 where k0prop:⟨f k0 = k ∧ ticks ((Rep_run r) (f k0) c)⟩

```

```

    using ticks_image[OF assms] by blast
  with h have ⟨k ∈ image f ?SET⟩
    using assms dilating_fun_def strict_mono_less_eq by blast
} thus ⟨?IMG ⊆ image f ?SET⟩ ..
next
{ fix k assume h:⟨k ∈ image f ?SET⟩
  from h obtain k0 where k0prop:⟨k = f k0 ∧ k0 ∈ ?SET⟩ by blast
  hence ⟨k ∈ ?IMG⟩ using assms by (simp add: dilating_fun_def strict_mono_less_eq)
} thus ⟨image f ?SET ⊆ ?IMG⟩ ..
qed

```

On any clock, the number of ticks in an interval is preserved by a dilating function.

```

lemma ticks_as_often_strict:
  assumes ⟨dilating_fun f r⟩
  shows   ⟨card {p. n < p ∧ p < m ∧ ticks ((Rep_run r) (f p) c)}⟩
        = card {p. f n < p ∧ p < f m ∧ ticks ((Rep_run r) p c)}⟩
    (is ⟨card ?SET = card ?IMG⟩)
proof -
  from dilating_fun_injects[OF assms] have ⟨inj_on f ?SET⟩ .
  moreover have ⟨finite ?SET⟩ by simp
  from inj_on_iff_eq_card[OF this] calculation
    have ⟨card (image f ?SET) = card ?SET⟩ by blast
  moreover from dilating_fun_image_strict[OF assms] have ⟨?IMG = image f ?SET⟩ .
  ultimately show ?thesis by auto
qed

```

```

lemma ticks_as_often_left:
  assumes ⟨dilating_fun f r⟩
  shows   ⟨card {p. n ≤ p ∧ p < m ∧ ticks ((Rep_run r) (f p) c)}⟩
        = card {p. f n ≤ p ∧ p < f m ∧ ticks ((Rep_run r) p c)}⟩
    (is ⟨card ?SET = card ?IMG⟩)
proof -
  from dilating_fun_injects[OF assms] have ⟨inj_on f ?SET⟩ .
  moreover have ⟨finite ?SET⟩ by simp
  from inj_on_iff_eq_card[OF this] calculation
    have ⟨card (image f ?SET) = card ?SET⟩ by blast
  moreover from dilating_fun_image_left[OF assms] have ⟨?IMG = image f ?SET⟩ .
  ultimately show ?thesis by auto
qed

```

```

lemma ticks_as_often_right:
  assumes ⟨dilating_fun f r⟩
  shows   ⟨card {p. n < p ∧ p ≤ m ∧ ticks ((Rep_run r) (f p) c)}⟩
        = card {p. f n < p ∧ p ≤ f m ∧ ticks ((Rep_run r) p c)}⟩
    (is ⟨card ?SET = card ?IMG⟩)
proof -
  from dilating_fun_injects[OF assms] have ⟨inj_on f ?SET⟩ .
  moreover have ⟨finite ?SET⟩ by simp
  from inj_on_iff_eq_card[OF this] calculation
    have ⟨card (image f ?SET) = card ?SET⟩ by blast
  moreover from dilating_fun_image_right[OF assms] have ⟨?IMG = image f ?SET⟩ .
  ultimately show ?thesis by auto
qed

```

```

lemma ticks_as_often:
  assumes ⟨dilating_fun f r⟩
  shows   ⟨card {p. n ≤ p ∧ p ≤ m ∧ ticks ((Rep_run r) (f p) c)}⟩
        = card {p. f n ≤ p ∧ p ≤ f m ∧ ticks ((Rep_run r) p c)}⟩

```

```

  (is ⟨card ?SET = card ?IMG⟩)
proof -
  from dilating_fun_injects[OF assms] have ⟨inj_on f ?SET⟩ .
  moreover have ⟨finite ?SET⟩ by simp
  from inj_on_iff_eq_card[OF this] calculation
    have ⟨card (image f ?SET) = card ?SET⟩ by blast
  moreover from dilating_fun_image[OF assms] have ⟨?IMG = image f ?SET⟩ .
  ultimately show ?thesis by auto
qed

```

The date of an event is preserved by dilation.

```

lemma ticks_tag_image:
  assumes ⟨dilating f sub r⟩
  and     ⟨∃ c. ticks ((Rep_run r) k c)⟩
  and     ⟨time ((Rep_run r) k c) = τ⟩
  shows   ⟨∃ k0. f k0 = k ∧ time ((Rep_run sub) k0 c) = τ⟩
proof -
  from ticks_image_sub'[OF assms(1,2)] have ⟨∃ k0. f k0 = k⟩ .
  from this obtain k0 where ⟨f k0 = k⟩ by blast
  moreover with assms(1,3) have ⟨time ((Rep_run sub) k0 c) = τ⟩
    by (simp add: dilating_def)
  ultimately show ?thesis by blast
qed

```

TESL operators are invariant by dilation.

```

lemma ticks_sub:
  assumes ⟨dilating f sub r⟩
  shows   ⟨ticks ((Rep_run sub) n a) = ticks ((Rep_run r) (f n) a)⟩
using assms by (simp add: dilating_def)

```

```

lemma no_tick_sub:
  assumes ⟨dilating f sub r⟩
  shows   ⟨(∄ n0. f n0 = n) ⟶ ¬ticks ((Rep_run r) n a)⟩
using assms dilating_def dilating_fun_def by blast

```

Lifting a total function to a partial function on an option domain.

```

definition opt_lift::('a ⇒ 'a) ⇒ ('a option ⇒ 'a option)
where
  ⟨opt_lift f ≡ λx. case x of None ⇒ None | Some y ⇒ Some (f y)⟩

```

The set of instants when a clock ticks in a dilated run is the image by the dilation function of the set of instants when it ticks in the subrun.

```

lemma tick_set_sub:
  assumes ⟨dilating f sub r⟩
  shows   ⟨{k. ticks ((Rep_run r) k c)} = image f {k. ticks ((Rep_run sub) k c)}⟩
  (is ⟨?R = image f ?S⟩)
proof
  { fix k assume h:⟨k ∈ ?R⟩
    with no_tick_sub[OF assms] have ⟨∃ k0. f k0 = k⟩ by blast
    from this obtain k0 where k0prop:⟨f k0 = k⟩ by blast
    with ticks_sub[OF assms] h have ⟨ticks ((Rep_run sub) k0 c)⟩ by blast
    with k0prop have ⟨k ∈ image f ?S⟩ by blast
  }
  thus ⟨?R ⊆ image f ?S⟩ by blast
next
  { fix k assume h:⟨k ∈ image f ?S⟩
    from this obtain k0 where ⟨f k0 = k ∧ ticks ((Rep_run sub) k0 c)⟩ by blast

```

```

    with assms have  $\langle k \in ?R \rangle$  using ticks_sub by blast
  }
  thus  $\langle \text{image } f \text{ } ?S \subseteq ?R \rangle$  by blast
qed

```

Strictly monotonous functions preserve the least element.

```

lemma Least_strict_mono:
  assumes  $\langle \text{strict\_mono } f \rangle$ 
  and  $\langle \exists x \in S. \forall y \in S. x \leq y \rangle$ 
  shows  $\langle (\text{LEAST } y. y \in f \text{ } S) = f (\text{LEAST } x. x \in S) \rangle$ 
using Least_mono[OF strict_mono_mono, OF assms] .

```

A non empty set of nats has a least element.

```

lemma Least_nat_ex:
   $\langle (n::\text{nat}) \in S \implies \exists x \in S. (\forall y \in S. x \leq y) \rangle$ 
by (induction n rule: nat_less_induct, insert not_le_imp_less, blast)

```

The first instant when a clock ticks in a dilated run is the image by the dilation function of the first instant when it ticks in the subrun.

```

lemma Least_sub:
  assumes  $\langle \text{dilating } f \text{ sub } r \rangle$ 
  and  $\langle \exists k::\text{nat}. \text{ticks } ((\text{Rep\_run sub}) k \text{ } c) \rangle$ 
  shows  $\langle (\text{LEAST } k. k \in \{t. \text{ticks } ((\text{Rep\_run } r) t \text{ } c)\})$ 
     $= f (\text{LEAST } k. k \in \{t. \text{ticks } ((\text{Rep\_run sub}) t \text{ } c)\}) \rangle$ 
     $\langle \text{is } (\text{LEAST } k. k \in ?R) = f (\text{LEAST } k. k \in ?S) \rangle \rangle$ 
proof -
  from assms(2) have  $\langle \exists x. x \in ?S \rangle$  by simp
  hence least:  $\langle \exists x \in ?S. \forall y \in ?S. x \leq y \rangle$ 
  using Least_nat_ex ..
  from assms(1) have  $\langle \text{strict\_mono } f \rangle$  by (simp add: dilating_def dilating_fun_def)
  from Least_strict_mono[OF this least] have
     $\langle (\text{LEAST } y. y \in f \text{ } ?S) = f (\text{LEAST } x. x \in ?S) \rangle$  .
  with tick_set_sub[OF assms(1), of  $\langle c \rangle$ ] show ?thesis by auto
qed

```

If a clock ticks in a run, it ticks in the subrun.

```

lemma ticks_imp_ticks_sub:
  assumes  $\langle \text{dilating } f \text{ sub } r \rangle$ 
  and  $\langle \exists k. \text{ticks } ((\text{Rep\_run } r) k \text{ } c) \rangle$ 
  shows  $\langle \exists k_0. \text{ticks } ((\text{Rep\_run sub}) k_0 \text{ } c) \rangle$ 
proof -
  from assms(2) obtain k where  $\langle \text{ticks } ((\text{Rep\_run } r) k \text{ } c) \rangle$  by blast
  with ticks_image_sub[OF assms(1)] ticks_sub[OF assms(1)] show ?thesis by blast
qed

```

Stronger version: it ticks in the subrun and we know when.

```

lemma ticks_imp_ticks_subk:
  assumes  $\langle \text{dilating } f \text{ sub } r \rangle$ 
  and  $\langle \text{ticks } ((\text{Rep\_run } r) k \text{ } c) \rangle$ 
  shows  $\langle \exists k_0. f \text{ } k_0 = k \wedge \text{ticks } ((\text{Rep\_run sub}) k_0 \text{ } c) \rangle$ 
proof -
  from no_tick_sub[OF assms(1)] assms(2) have  $\langle \exists k_0. f \text{ } k_0 = k \rangle$  by blast
  from this obtain k_0 where  $\langle f \text{ } k_0 = k \rangle$  by blast
  moreover with ticks_sub[OF assms(1)] assms(2)
  have  $\langle \text{ticks } ((\text{Rep\_run sub}) k_0 \text{ } c) \rangle$  by blast
  ultimately show ?thesis by blast

```

qed

A dilating function preserves the tick count on an interval for any clock.

```

lemma dilated_ticks_strict:
  assumes (dilating f sub r)
  shows   ⟨{i. f m < i ∧ i < f n ∧ ticks ((Rep_run r) i c)}⟩
        = image f {i. m < i ∧ i < n ∧ ticks ((Rep_run sub) i c)}⟩
    (is ⟨?RUN = image f ?SUB⟩)
proof
  { fix i assume h:⟨i ∈ ?SUB⟩
    hence ⟨m < i ∧ i < n⟩ by simp
    hence ⟨f m < f i ∧ f i < (f n)⟩ using assms
      by (simp add: dilating_def dilating_fun_def strict_monoD strict_mono_less_eq)
    moreover from h have ⟨ticks ((Rep_run sub) i c)⟩ by simp
    hence ⟨ticks ((Rep_run r) (f i) c)⟩ using ticks_sub[OF assms] by blast
    ultimately have ⟨f i ∈ ?RUN⟩ by simp
  } thus ⟨image f ?SUB ⊆ ?RUN⟩ by blast
next
  { fix i assume h:⟨i ∈ ?RUN⟩
    hence ⟨ticks ((Rep_run r) i c)⟩ by simp
    from ticks_imp_ticks_subk[OF assms this]
      obtain i₀ where i₀prop:⟨f i₀ = i ∧ ticks ((Rep_run sub) i₀ c)⟩ by blast
    with h have ⟨f m < f i₀ ∧ f i₀ < f n⟩ by simp
    moreover have ⟨strict_mono f⟩ using assms dilating_def dilating_fun_def by blast
    ultimately have ⟨m < i₀ ∧ i₀ < n⟩
      using strict_mono_less strict_mono_less_eq by blast
    with i₀prop have ⟨∃i₀. f i₀ = i ∧ i₀ ∈ ?SUB⟩ by blast
  } thus ⟨?RUN ⊆ image f ?SUB⟩ by blast
qed

```

```

lemma dilated_ticks_left:
  assumes (dilating f sub r)
  shows   ⟨{i. f m ≤ i ∧ i < f n ∧ ticks ((Rep_run r) i c)}⟩
        = image f {i. m ≤ i ∧ i < n ∧ ticks ((Rep_run sub) i c)}⟩
    (is ⟨?RUN = image f ?SUB⟩)
proof
  { fix i assume h:⟨i ∈ ?SUB⟩
    hence ⟨m ≤ i ∧ i < n⟩ by simp
    hence ⟨f m ≤ f i ∧ f i < (f n)⟩ using assms
      by (simp add: dilating_def dilating_fun_def strict_monoD strict_mono_less_eq)
    moreover from h have ⟨ticks ((Rep_run sub) i c)⟩ by simp
    hence ⟨ticks ((Rep_run r) (f i) c)⟩ using ticks_sub[OF assms] by blast
    ultimately have ⟨f i ∈ ?RUN⟩ by simp
  } thus ⟨image f ?SUB ⊆ ?RUN⟩ by blast
next
  { fix i assume h:⟨i ∈ ?RUN⟩
    hence ⟨ticks ((Rep_run r) i c)⟩ by simp
    from ticks_imp_ticks_subk[OF assms this]
      obtain i₀ where i₀prop:⟨f i₀ = i ∧ ticks ((Rep_run sub) i₀ c)⟩ by blast
    with h have ⟨f m ≤ f i₀ ∧ f i₀ < f n⟩ by simp
    moreover have ⟨strict_mono f⟩ using assms dilating_def dilating_fun_def by blast
    ultimately have ⟨m ≤ i₀ ∧ i₀ < n⟩
      using strict_mono_less strict_mono_less_eq by blast
    with i₀prop have ⟨∃i₀. f i₀ = i ∧ i₀ ∈ ?SUB⟩ by blast
  } thus ⟨?RUN ⊆ image f ?SUB⟩ by blast
qed

```

```

lemma dilated_ticks_right:

```

```

assumes ⟨dilating f sub r⟩
shows   ⟨{i. f m < i ∧ i ≤ f n ∧ ticks ((Rep_run r) i c)}⟩
        = image f {i. m < i ∧ i ≤ n ∧ ticks ((Rep_run sub) i c)}⟩
        (is ⟨?RUN = image f ?SUB⟩)
proof
  { fix i assume h:⟨i ∈ ?SUB⟩
    hence ⟨m < i ∧ i ≤ n⟩ by simp
    hence ⟨f m < f i ∧ f i ≤ (f n)⟩ using assms
      by (simp add: dilating_def dilating_fun_def strict_monoD strict_mono_less_eq)
    moreover from h have ⟨ticks ((Rep_run sub) i c)⟩ by simp
    hence ⟨ticks ((Rep_run r) (f i) c)⟩ using ticks_sub[OF assms] by blast
    ultimately have ⟨f i ∈ ?RUN⟩ by simp
  } thus ⟨image f ?SUB ⊆ ?RUN⟩ by blast
next
  { fix i assume h:⟨i ∈ ?RUN⟩
    hence ⟨ticks ((Rep_run r) i c)⟩ by simp
    from ticks_imp_ticks_subk[OF assms this]
      obtain i0 where i0prop:⟨f i0 = i ∧ ticks ((Rep_run sub) i0 c)⟩ by blast
    with h have ⟨f m < f i0 ∧ f i0 ≤ f n⟩ by simp
    moreover have ⟨strict_mono f⟩ using assms dilating_def dilating_fun_def by blast
    ultimately have ⟨m < i0 ∧ i0 ≤ n⟩
      using strict_mono_less strict_mono_less_eq by blast
    with i0prop have ⟨∃i0. f i0 = i ∧ i0 ∈ ?SUB⟩ by blast
  } thus ⟨?RUN ⊆ image f ?SUB⟩ by blast
qed

lemma dilated_ticks:
  assumes ⟨dilating f sub r⟩
  shows   ⟨{i. f m ≤ i ∧ i ≤ f n ∧ ticks ((Rep_run r) i c)}⟩
          = image f {i. m ≤ i ∧ i ≤ n ∧ ticks ((Rep_run sub) i c)}⟩
          (is ⟨?RUN = image f ?SUB⟩)
proof
  { fix i assume h:⟨i ∈ ?SUB⟩
    hence ⟨m ≤ i ∧ i ≤ n⟩ by simp
    hence ⟨f m ≤ f i ∧ f i ≤ (f n)⟩
      using assms by (simp add: dilating_def dilating_fun_def strict_mono_less_eq)
    moreover from h have ⟨ticks ((Rep_run sub) i c)⟩ by simp
    hence ⟨ticks ((Rep_run r) (f i) c)⟩ using ticks_sub[OF assms] by blast
    ultimately have ⟨f i ∈ ?RUN⟩ by simp
  } thus ⟨image f ?SUB ⊆ ?RUN⟩ by blast
next
  { fix i assume h:⟨i ∈ ?RUN⟩
    hence ⟨ticks ((Rep_run r) i c)⟩ by simp
    from ticks_imp_ticks_subk[OF assms this]
      obtain i0 where i0prop:⟨f i0 = i ∧ ticks ((Rep_run sub) i0 c)⟩ by blast
    with h have ⟨f m ≤ f i0 ∧ f i0 ≤ f n⟩ by simp
    moreover have ⟨strict_mono f⟩ using assms dilating_def dilating_fun_def by blast
    ultimately have ⟨m ≤ i0 ∧ i0 ≤ n⟩ using strict_mono_less_eq by blast
    with i0prop have ⟨∃i0. f i0 = i ∧ i0 ∈ ?SUB⟩ by blast
  } thus ⟨?RUN ⊆ image f ?SUB⟩ by blast
qed

```

No tick can occur in a dilated run before the image of 0 by the dilation function.

```

lemma empty_dilated_prefix:
  assumes ⟨dilating f sub r⟩
  and     ⟨n < f 0⟩
  shows   ⟨¬ ticks ((Rep_run r) n c)⟩
proof -

```



```

from assms have False by (simp add: dilating_def dilating_fun_def)
thus ?thesis ..
qed

corollary empty_dilated_prefix':
  assumes (dilating f sub r)
  shows {i. f 0 ≤ i ∧ i ≤ f n ∧ ticks ((Rep_run r) i c)}
    = {i. i ≤ f n ∧ ticks ((Rep_run r) i c)}
proof -
  from assms have (strict_mono f) by (simp add: dilating_def dilating_fun_def)
  hence (f 0 ≤ f n) unfolding strict_mono_def by (simp add: less_mono_imp_le_mono)
  hence (∀i. i ≤ f n = (i < f 0) ∨ (f 0 ≤ i ∧ i ≤ f n)) by auto
  hence {i. i ≤ f n ∧ ticks ((Rep_run r) i c)}
    = {i. i < f 0 ∧ ticks ((Rep_run r) i c)}
      ∪ {i. f 0 ≤ i ∧ i ≤ f n ∧ ticks ((Rep_run r) i c)}
    by auto
  also have (... = {i. f 0 ≤ i ∧ i ≤ f n ∧ ticks ((Rep_run r) i c)})
    using empty_dilated_prefix[OF assms] by blast
  finally show ?thesis by simp
qed

```

```

corollary dilated_prefix:
  assumes (dilating f sub r)
  shows {i. i ≤ f n ∧ ticks ((Rep_run r) i c)}
    = image f {i. i ≤ n ∧ ticks ((Rep_run sub) i c)}
proof -
  have {i. 0 ≤ i ∧ i ≤ f n ∧ ticks ((Rep_run r) i c)}
    = image f {i. 0 ≤ i ∧ i ≤ n ∧ ticks ((Rep_run sub) i c)}
    using dilated_ticks[OF assms] empty_dilated_prefix'[OF assms] by blast
  thus ?thesis by simp
qed

```

```

corollary dilated_strict_prefix:
  assumes (dilating f sub r)
  shows {i. i < f n ∧ ticks ((Rep_run r) i c)}
    = image f {i. i < n ∧ ticks ((Rep_run sub) i c)}
proof -
  from assms have dil:(dilating_fun f r) unfolding dilating_def by simp
  from dil have f0:(f 0 = 0) using dilating_fun_def by blast
  from dilating_fun_image_left[OF dil, of (0) (n) (c)]
  have {i. f 0 ≤ i ∧ i < f n ∧ ticks ((Rep_run r) i c)}
    = image f {i. 0 ≤ i ∧ i < n ∧ ticks ((Rep_run r) (f i) c)} .
  hence {i. i < f n ∧ ticks ((Rep_run r) i c)}
    = image f {i. i < n ∧ ticks ((Rep_run r) (f i) c)}
    using f0 by simp
  also have (... = image f {i. i < n ∧ ticks ((Rep_run sub) i c)})
    using assms dilating_def by blast
  finally show ?thesis by simp
qed

```

A singleton of  $\text{nat}$  can be defined with a weaker property.

```

lemma nat_sing_prop:
  {i::nat. i = k ∧ P(i)} = {i::nat. i = k ∧ P(k)}
by auto

```

The set definition and the function definition of `tick_count` are equivalent.

```

lemma tick_count_is_fun[code]: (tick_count r c n = run_tick_count r c n)
proof (induction n)

```

```

case 0
  have ⟨tick_count r c 0 = card {i. i ≤ 0 ∧ ticks ((Rep_run r) i c)}⟩
    by (simp add: tick_count_def)
  also have ⟨... = card {i::nat. i = 0 ∧ ticks ((Rep_run r) 0 c)}⟩
    using le_zero_eq nat_sing_prop[of ⟨0⟩ ⟨λi. ticks ((Rep_run r) i c)⟩] by simp
  also have ⟨... = (if ticks ((Rep_run r) 0 c) then 1 else 0)⟩ by simp
  also have ⟨... = run_tick_count r c 0⟩ by simp
  finally show ?case .
next
case (Suc k)
  show ?case
  proof (cases ⟨ticks ((Rep_run r) (Suc k) c)⟩)
    case True
      hence ⟨{i. i ≤ Suc k ∧ ticks ((Rep_run r) i c)}⟩
        = insert (Suc k) {i. i ≤ k ∧ ticks ((Rep_run r) i c)} by auto
      hence ⟨tick_count r c (Suc k) = Suc (tick_count r c k)⟩
        by (simp add: tick_count_def)
      with Suc.IH have ⟨tick_count r c (Suc k) = Suc (run_tick_count r c k)⟩ by simp
      thus ?thesis by (simp add: True)
    case False
      hence ⟨{i. i ≤ Suc k ∧ ticks ((Rep_run r) i c)}⟩
        = {i. i ≤ k ∧ ticks ((Rep_run r) i c)}
        using le_Suc_eq by auto
      hence ⟨tick_count r c (Suc k) = tick_count r c k⟩
        by (simp add: tick_count_def)
      thus ?thesis using Suc.IH by (simp add: False)
  qed
qed

```

To show that the set definition and the function definition of `tick_count_strict` are equivalent, we first show that the *strictness* of `tick_count_strict` can be softened using `Suc`.

```

lemma tick_count_strict_suc: ⟨tick_count_strict r c (Suc n) = tick_count r c n⟩
  unfolding tick_count_def tick_count_strict_def using less_Suc_eq_le by auto

```

```

lemma tick_count_strict_is_fun[code]:
  ⟨tick_count_strict r c n = run_tick_count_strictly r c n⟩
proof (cases ⟨n = 0⟩)
  case True
    hence ⟨tick_count_strict r c n = 0⟩ unfolding tick_count_strict_def by simp
    also have ⟨... = run_tick_count_strictly r c 0⟩
      using run_tick_count_strictly.simps(1)[symmetric] .
    finally show ?thesis using True by simp
  next
  case False
    from not0_implies_Suc[OF this] obtain m where *: ⟨n = Suc m⟩ by blast
    hence ⟨tick_count_strict r c n = tick_count r c m⟩
      using tick_count_strict_suc by simp
    also have ⟨... = run_tick_count r c m⟩ using tick_count_is_fun[of ⟨r⟩ ⟨c⟩ ⟨m⟩] .
    also have ⟨... = run_tick_count_strictly r c (Suc m)⟩
      using run_tick_count_strictly.simps(2)[symmetric] .
    finally show ?thesis using * by simp
qed

```

This leads to an alternate definition of the strict precedence relation.

```

lemma strictly_precedes_alt_def1:
  = { ρ. ∀n::nat. (run_tick_count ρ K₂ n) ≤ (run_tick_count_strictly ρ K₁ n) }
  = { ρ. ∀n::nat. (run_tick_count_strictly ρ K₂ (Suc n))

```

$$\leq (\text{run\_tick\_count\_strictly } \varrho \ K_1 \ n) \}$$

by auto

The strict precedence relation can even be defined using only `run_tick_count`:

```
lemma zero_gt_all:
  assumes ⟨P (0::nat)⟩
  and ⟨ $\bigwedge n. n > 0 \implies P \ n$ ⟩
  shows ⟨P n⟩
  using assms neq0_conv by blast

lemma strictly_precedes_alt_def2:
  ⟨{  $\varrho. \forall n::\text{nat}. (\text{run\_tick\_count } \varrho \ K_2 \ n) \leq (\text{run\_tick\_count\_strictly } \varrho \ K_1 \ n) \}$ 
  = {  $\varrho. (\neg \text{ticks } ((\text{Rep\_run } \varrho) \ 0 \ K_2))$ 
     $\wedge (\forall n::\text{nat}. (\text{run\_tick\_count } \varrho \ K_2 \ (\text{Suc } n)) \leq (\text{run\_tick\_count } \varrho \ K_1 \ n)) \}$ 
  (is ⟨?P = ?P'⟩)
proof
  { fix r::('a run)
    assume ⟨r ∈ ?P⟩
    hence ⟨ $\forall n::\text{nat}. (\text{run\_tick\_count } r \ K_2 \ n) \leq (\text{run\_tick\_count\_strictly } r \ K_1 \ n)$ ⟩
    by simp
    hence 1:⟨ $\forall n::\text{nat}. (\text{tick\_count } r \ K_2 \ n) \leq (\text{tick\_count\_strict } r \ K_1 \ n)$ ⟩
    using tick_count_is_fun[symmetric, of r] tick_count_strict_is_fun[symmetric, of r]
    by simp
    hence ⟨ $\forall n::\text{nat}. (\text{tick\_count\_strict } r \ K_2 \ (\text{Suc } n)) \leq (\text{tick\_count\_strict } r \ K_1 \ n)$ ⟩
    using tick_count_strict_suc[symmetric, of ⟨r⟩ ⟨K2⟩] by simp
    hence ⟨ $\forall n::\text{nat}. (\text{tick\_count\_strict } r \ K_2 \ (\text{Suc } (\text{Suc } n))) \leq (\text{tick\_count\_strict } r \ K_1 \ (\text{Suc } n))$ ⟩
    by simp
    hence ⟨ $\forall n::\text{nat}. (\text{tick\_count } r \ K_2 \ (\text{Suc } n)) \leq (\text{tick\_count } r \ K_1 \ n)$ ⟩
    using tick_count_strict_suc[symmetric, of ⟨r⟩] by simp
    hence *:⟨ $\forall n::\text{nat}. (\text{run\_tick\_count } r \ K_2 \ (\text{Suc } n)) \leq (\text{run\_tick\_count } r \ K_1 \ n)$ ⟩
    by (simp add: tick_count_is_fun)
    from 1 have ⟨tick_count r K2 0 ≤ tick_count_strict r K1 0⟩ by simp
    moreover have ⟨tick_count_strict r K1 0 = 0⟩ unfolding tick_count_strict_def by simp
    ultimately have ⟨tick_count r K2 0 = 0⟩ by simp
    hence ⟨ $\neg \text{ticks } ((\text{Rep\_run } r) \ 0 \ K_2)$ ⟩ unfolding tick_count_def by auto
    with * have ⟨r ∈ ?P'⟩ by simp
  } thus ⟨?P ⊆ ?P'⟩ ..
  { fix r::('a run)
    assume h:⟨r ∈ ?P'⟩
    hence ⟨ $\forall n::\text{nat}. (\text{run\_tick\_count } r \ K_2 \ (\text{Suc } n)) \leq (\text{run\_tick\_count } r \ K_1 \ n)$ ⟩ by simp
    hence ⟨ $\forall n::\text{nat}. (\text{tick\_count } r \ K_2 \ (\text{Suc } n)) \leq (\text{tick\_count } r \ K_1 \ n)$ ⟩
    by (simp add: tick_count_is_fun)
    hence ⟨ $\forall n::\text{nat}. (\text{tick\_count } r \ K_2 \ (\text{Suc } n)) \leq (\text{tick\_count\_strict } r \ K_1 \ (\text{Suc } n))$ ⟩
    using tick_count_strict_suc[symmetric, of ⟨r⟩ ⟨K1⟩] by simp
    hence *:⟨ $\forall n. n > 0 \longrightarrow (\text{tick\_count } r \ K_2 \ n) \leq (\text{tick\_count\_strict } r \ K_1 \ n)$ ⟩
    using gr0_implies_Suc by blast
    have ⟨tick_count_strict r K1 0 = 0⟩ unfolding tick_count_strict_def by simp
    moreover from h have ⟨ $\neg \text{ticks } ((\text{Rep\_run } r) \ 0 \ K_2)$ ⟩ by simp
    hence ⟨tick_count r K2 0 = 0⟩ unfolding tick_count_def by auto
    ultimately have ⟨tick_count r K2 0 ≤ tick_count_strict r K1 0⟩ by simp
    from zero_gt_all[of ⟨ $\lambda n. \text{tick\_count } r \ K_2 \ n \leq \text{tick\_count\_strict } r \ K_1 \ n$ ⟩, OF this ] *
    have ⟨ $\forall n. (\text{tick\_count } r \ K_2 \ n) \leq (\text{tick\_count\_strict } r \ K_1 \ n)$ ⟩ by simp
    hence ⟨ $\forall n. (\text{run\_tick\_count } r \ K_2 \ n) \leq (\text{run\_tick\_count\_strictly } r \ K_1 \ n)$ ⟩
    by (simp add: tick_count_is_fun tick_count_strict_is_fun)
    hence ⟨r ∈ ?P⟩ ..
  } thus ⟨?P' ⊆ ?P⟩ ..
qed
```

Some properties of `run_tick_count`, `tick_count` and `Suc`:

```

lemma run_tick_count_suc:
  (run_tick_count r c (Suc n) = (if ticks ((Rep_run r) (Suc n) c)
    then Suc (run_tick_count r c n)
    else run_tick_count r c n))
by simp

```

```

corollary tick_count_suc:
  (tick_count r c (Suc n) = (if ticks ((Rep_run r) (Suc n) c)
    then Suc (tick_count r c n)
    else tick_count r c n))
by (simp add: tick_count_is_fun)

```

Some generic properties on the cardinal of sets of nat that we will need later.

```

lemma card_suc:
  (card {i. i ≤ (Suc n) ∧ P i} = card {i. i ≤ n ∧ P i} + card {i. i = (Suc n) ∧ P i})
proof -
  have {i. i ≤ n ∧ P i} ∩ {i. i = (Suc n) ∧ P i} = {} by auto
  moreover have {i. i ≤ n ∧ P i} ∪ {i. i = (Suc n) ∧ P i}
    = {i. i ≤ (Suc n) ∧ P i} by auto
  moreover have (finite {i. i ≤ n ∧ P i}) by simp
  moreover have (finite {i. i = (Suc n) ∧ P i}) by simp
  ultimately show ?thesis
    using card_Un_disjoint[of {i. i ≤ n ∧ P i} {i. i = Suc n ∧ P i}] by simp
qed

```

```

lemma card_le_leq:
  assumes (m < n)
  shows (card {i::nat. m < i ∧ i ≤ n ∧ P i}
    = card {i. m < i ∧ i < n ∧ P i} + card {i. i = n ∧ P i})
proof -
  have {i::nat. m < i ∧ i < n ∧ P i} ∩ {i. i = n ∧ P i} = {} by auto
  moreover with assms have
    {i::nat. m < i ∧ i < n ∧ P i} ∪ {i. i = n ∧ P i} = {i. m < i ∧ i ≤ n ∧ P i}
  by auto
  moreover have (finite {i. m < i ∧ i < n ∧ P i}) by simp
  moreover have (finite {i. i = n ∧ P i}) by simp
  ultimately show ?thesis
    using card_Un_disjoint[of {i. m < i ∧ i < n ∧ P i} {i. i = n ∧ P i}] by simp
qed

```

```

lemma card_le_leq_0:
  (card {i::nat. i ≤ n ∧ P i} = card {i. i < n ∧ P i} + card {i. i = n ∧ P i})
proof -
  have {i::nat. i < n ∧ P i} ∩ {i. i = n ∧ P i} = {} by auto
  moreover have {i. i < n ∧ P i} ∪ {i. i = n ∧ P i} = {i. i ≤ n ∧ P i} by auto
  moreover have (finite {i. i < n ∧ P i}) by simp
  moreover have (finite {i. i = n ∧ P i}) by simp
  ultimately show ?thesis
    using card_Un_disjoint[of {i. i < n ∧ P i} {i. i = n ∧ P i}] by simp
qed

```

```

lemma card_mnm:
  assumes (m < n)
  shows (card {i::nat. i < n ∧ P i}
    = card {i. i ≤ m ∧ P i} + card {i. m < i ∧ i < n ∧ P i})
proof -
  have 1: {i::nat. i ≤ m ∧ P i} ∩ {i. m < i ∧ i < n ∧ P i} = {} by auto
  from assms have (∀ i::nat. i < n = (i ≤ m) ∨ (m < i ∧ i < n))

```

```

    using less_trans by auto
  hence 2:
    ⟨{i::nat. i < n ∧ P i} = {i. i ≤ m ∧ P i} ∪ {i. m < i ∧ i < n ∧ P i}⟩ by blast
  have 3:⟨finite {i. i ≤ m ∧ P i}⟩ by simp
  have 4:⟨finite {i. m < i ∧ i < n ∧ P i}⟩ by simp
  from card_Un_disjoint[OF 3 4 1] 2 show ?thesis by simp
qed

```

```

lemma card_mnm':
  assumes ⟨m < n⟩
  shows ⟨card {i::nat. i < n ∧ P i}
        = card {i. i < m ∧ P i} + card {i. m ≤ i ∧ i < n ∧ P i}⟩
proof -
  have 1:⟨{i::nat. i < m ∧ P i} ∩ {i. m ≤ i ∧ i < n ∧ P i} = {}⟩ by auto
  from assms have ⟨∀i::nat. i < n = (i < m) ∨ (m ≤ i ∧ i < n)⟩
    using less_trans by auto
  hence 2:
    ⟨{i::nat. i < n ∧ P i} = {i. i < m ∧ P i} ∪ {i. m ≤ i ∧ i < n ∧ P i}⟩ by blast
  have 3:⟨finite {i. i < m ∧ P i}⟩ by simp
  have 4:⟨finite {i. m ≤ i ∧ i < n ∧ P i}⟩ by simp
  from card_Un_disjoint[OF 3 4 1] 2 show ?thesis by simp
qed

```

```

lemma nat_interval_union:
  assumes ⟨m ≤ n⟩
  shows ⟨{i::nat. i ≤ n ∧ P i}
        = {i::nat. i ≤ m ∧ P i} ∪ {i::nat. m < i ∧ i ≤ n ∧ P i}⟩
using assms le_cases nat_less_le by auto

```

```

lemma card_sing_prop:⟨card {i. i = n ∧ P i} = (if P n then 1 else 0)⟩
proof (cases ⟨P n⟩)
  case True
    hence ⟨{i. i = n ∧ P i} = {n}⟩ by (simp add: Collect_conv_if)
    with ⟨P n⟩ show ?thesis by simp
  next
  case False
    hence ⟨{i. i = n ∧ P i} = {}⟩ by (simp add: Collect_conv_if)
    with ⟨¬P n⟩ show ?thesis by simp
qed

```

```

lemma card_prop_mono:
  assumes ⟨m ≤ n⟩
  shows ⟨card {i::nat. i ≤ m ∧ P i} ≤ card {i. i ≤ n ∧ P i}⟩
proof -
  from assms have ⟨{i. i ≤ m ∧ P i} ⊆ {i. i ≤ n ∧ P i}⟩ by auto
  moreover have ⟨finite {i. i ≤ n ∧ P i}⟩ by simp
  ultimately show ?thesis by (simp add: card_mono)
qed

```

In a dilated run, no tick occurs strictly between two successive instants that are the images by  $f$  of instants of the original run.

```

lemma no_tick_before_suc:
  assumes ⟨dilating f sub r⟩
  and ⟨(f n) < k ∧ k < (f (Suc n))⟩
  shows ⟨¬ticks ((Rep_run r) k c)⟩
proof -
  from assms(1) have smf:⟨strict_mono f⟩ by (simp add: dilating_def dilating_fun_def)
  { fix k assume h:⟨f n < k ∧ k < f (Suc n) ∧ ticks ((Rep_run r) k c)⟩

```

```

hence ⟨ $\exists k_0. f\ k_0 = k$ ⟩ using assms(1) dilating_def dilating_fun_def by blast
from this obtain  $k_0$  where ⟨ $f\ k_0 = k$ ⟩ by blast
with h have ⟨ $f\ n < f\ k_0 \wedge f\ k_0 < f\ (\text{Suc } n)$ ⟩ by simp
hence False using smf not_less_eq strict_mono_less by blast
} thus ?thesis using assms(2) by blast
qed

```

From this, we show that the number of ticks on any clock at  $f\ (\text{Suc } n)$  depends only on the number of ticks on this clock at  $f\ n$  and whether this clock ticks at  $f\ (\text{Suc } n)$ . All the instants in between are stuttering instants.

```

lemma tick_count_fsuc:
  assumes ⟨dilating f sub r⟩
  shows ⟨tick_count r c (f (Suc n))
        = tick_count r c (f n) + card {k. k = f (Suc n) ∧ ticks ((Rep_run r) k c)}⟩
proof -
  have smf:⟨strict_mono f⟩ using assms dilating_def dilating_fun_def by blast
  moreover have ⟨finite {k. k ≤ f n ∧ ticks ((Rep_run r) k c)}⟩ by simp
  moreover have *:⟨finite {k. f n < k ∧ k ≤ f (Suc n) ∧ ticks ((Rep_run r) k c)}⟩ by simp
  ultimately have ⟨{k. k ≤ f (Suc n) ∧ ticks ((Rep_run r) k c)} =
    {k. k ≤ f n ∧ ticks ((Rep_run r) k c)}
    ∪ {k. f n < k ∧ k ≤ f (Suc n) ∧ ticks ((Rep_run r) k c)}⟩
  by (simp add: nat_interval_union strict_mono_less_eq)
  moreover have ⟨{k. k ≤ f n ∧ ticks ((Rep_run r) k c)}
    ∩ {k. f n < k ∧ k ≤ f (Suc n) ∧ ticks ((Rep_run r) k c)} = {}⟩
  by auto
  ultimately have ⟨card {k. k ≤ f (Suc n) ∧ ticks (Rep_run r k c)} =
    card {k. k ≤ f n ∧ ticks (Rep_run r k c)}
    + card {k. f n < k ∧ k ≤ f (Suc n) ∧ ticks (Rep_run r k c)}⟩
  by (simp add: * card_Un_disjoint)
  moreover from no_tick_before_suc[OF assms] have
    ⟨{k. f n < k ∧ k ≤ f (Suc n) ∧ ticks ((Rep_run r) k c)} =
    {k. k = f (Suc n) ∧ ticks ((Rep_run r) k c)}⟩
  using smf strict_mono_less by fastforce
  ultimately show ?thesis by (simp add: tick_count_def)
qed

```

```

corollary tick_count_f_suc:
  assumes ⟨dilating f sub r⟩
  shows ⟨tick_count r c (f (Suc n))
        = tick_count r c (f n) + (if ticks ((Rep_run r) (f (Suc n)) c) then 1 else 0)⟩
using tick_count_fsuc[OF assms]
  card_sing_prop[of ⟨f (Suc n)⟩ ⟨λk. ticks ((Rep_run r) k c)⟩] by simp

```

```

corollary tick_count_f_suc_suc:
  assumes ⟨dilating f sub r⟩
  shows ⟨tick_count r c (f (Suc n)) = (if ticks ((Rep_run r) (f (Suc n)) c)
    then Suc (tick_count r c (f n))
    else tick_count r c (f n))⟩
using tick_count_f_suc[OF assms] by simp

```

```

lemma tick_count_f_suc_sub:
  assumes ⟨dilating f sub r⟩
  shows ⟨tick_count r c (f (Suc n)) = (if ticks ((Rep_run sub) (Suc n) c)
    then Suc (tick_count r c (f n))
    else tick_count r c (f n))⟩
using tick_count_f_suc_suc[OF assms] assms by (simp add: dilating_def)

```

The number of ticks does not progress during stuttering instants.

```

lemma tick_count_latest:
  assumes ⟨dilating f sub r⟩
    and ⟨f np < n ∧ (∀k. f np < k ∧ k ≤ n ⟶ (∄k0. f k0 = k))⟩
  shows ⟨tick_count r c n = tick_count r c (f np)⟩
proof -
  have union: {i. i ≤ n ∧ ticks ((Rep_run r) i c)} =
    {i. i ≤ f np ∧ ticks ((Rep_run r) i c)}
    ∪ {i. f np < i ∧ i ≤ n ∧ ticks ((Rep_run r) i c)} using assms(2) by auto
  have partition: {i. i ≤ f np ∧ ticks ((Rep_run r) i c)}
    ∩ {i. f np < i ∧ i ≤ n ∧ ticks ((Rep_run r) i c)} = {}
  by (simp add: disjoint_iff_not_equal)
  from assms have ⟨{i. f np < i ∧ i ≤ n ∧ ticks ((Rep_run r) i c)} = {}⟩
  using no_tick_sub by fastforce
  with union and partition show ?thesis by (simp add: tick_count_def)
qed

```

We finally show that the number of ticks on any clock is preserved by dilation.

```

lemma tick_count_sub:
  assumes ⟨dilating f sub r⟩
  shows ⟨tick_count sub c n = tick_count r c (f n)⟩
proof -
  have ⟨tick_count sub c n = card {i. i ≤ n ∧ ticks ((Rep_run sub) i c)}⟩
  using tick_count_def[of ⟨sub⟩ ⟨c⟩ ⟨n⟩] .
  also have ⟨... = card (image f {i. i ≤ n ∧ ticks ((Rep_run sub) i c)})⟩
  using assms dilating_def dilating_injects[OF assms] by (simp add: card_image)
  also have ⟨... = card {i. i ≤ f n ∧ ticks ((Rep_run r) i c)}⟩
  using dilated_prefix[OF assms, symmetric, of ⟨n⟩ ⟨c⟩] by simp
  also have ⟨... = tick_count r c (f n)⟩
  using tick_count_def[of ⟨r⟩ ⟨c⟩ ⟨f n⟩] by simp
  finally show ?thesis .
qed

```

```

corollary run_tick_count_sub:
  assumes ⟨dilating f sub r⟩
  shows ⟨run_tick_count sub c n = run_tick_count r c (f n)⟩
proof -
  have ⟨run_tick_count sub c n = tick_count sub c n⟩
  using tick_count_is_fun[of ⟨sub⟩ c n, symmetric] .
  also from tick_count_sub[OF assms] have ⟨... = tick_count r c (f n)⟩ .
  also have ⟨... = #≤ r c (f n)⟩ using tick_count_is_fun[of r c ⟨f n⟩] .
  finally show ?thesis .
qed

```

The number of ticks occurring strictly before the first instant is null.

```

lemma tick_count_strict_0:
  assumes ⟨dilating f sub r⟩
  shows ⟨tick_count_strict r c (f 0) = 0⟩
proof -
  from assms have ⟨f 0 = 0⟩ by (simp add: dilating_def dilating_fun_def)
  thus ?thesis unfolding tick_count_strict_def by simp
qed

```

The number of ticks strictly before an instant does not progress during stuttering instants.

```

lemma tick_count_strict_stable:
  assumes ⟨dilating f sub r⟩
  assumes ⟨(f n) < k ∧ k < (f (Suc n))⟩
  shows ⟨tick_count_strict r c k = tick_count_strict r c (f (Suc n))⟩

```

```

proof -
  from assms(1) have smf:(strict_mono f) by (simp add: dilating_def dilating_fun_def)
  from assms(2) have (f n < k) by simp
  hence (∀i. k ≤ i → f n < i) by simp
  with no_tick_before_suc[OF assms(1)] have
    *: (∀i. k ≤ i ∧ i < f (Suc n) → ¬ticks ((Rep_run r) i c)) by blast
  from tick_count_strict_def have
    (tick_count_strict r c (f (Suc n)) = card {i. i < f (Suc n) ∧ ticks ((Rep_run r) i c)}) .
  also have
    (... = card {i. i < k ∧ ticks ((Rep_run r) i c)}
      + card {i. k ≤ i ∧ i < f (Suc n) ∧ ticks ((Rep_run r) i c)})
    using card_mnm' assms(2) by simp
  also have (... = card {i. i < k ∧ ticks ((Rep_run r) i c)}) using * by simp
  finally show ?thesis by (simp add: tick_count_strict_def)
qed

```

Finally, the number of ticks strictly before an instant is preserved by dilation.

```

lemma tick_count_strict_sub:
  assumes (dilating f sub r)
  shows (tick_count_strict sub c n = tick_count_strict r c (f n))
proof -
  have (tick_count_strict sub c n = card {i. i < n ∧ ticks ((Rep_run sub) i c)})
    using tick_count_strict_def[of (sub) (c) (n)] .
  also have (... = card (image f {i. i < n ∧ ticks ((Rep_run sub) i c)}))
    using assms dilating_def dilating_injects[OF assms] by (simp add: card_image)
  also have (... = card {i. i < f n ∧ ticks ((Rep_run r) i c)})
    using dilated_strict_prefix[OF assms, symmetric, of (n) (c)] by simp
  also have (... = tick_count_strict r c (f n))
    using tick_count_strict_def[of (r) (c) (f n)] by simp
  finally show ?thesis .
qed

```

The tick count on any clock can only increase.

```

lemma mono_tick_count:
  (mono (λ k. tick_count r c k))
proof
  { fix x y::nat
    assume (x ≤ y)
    from card_prop_mono[OF this] have (tick_count r c x ≤ tick_count r c y)
      unfolding tick_count_def by simp
    } thus (λ x y. x ≤ y ⇒ tick_count r c x ≤ tick_count r c y) .
  }
qed

```

In a dilated run, for any stuttering instant, there is an instant which is the image of an instant in the original run, and which is the latest one before the stuttering instant.

```

lemma greatest_prev_image:
  assumes (dilating f sub r)
  shows ((#n0. f n0 = n) ⇒ (∃ np. f np < n ∧ (∀ k. f np < k ∧ k ≤ n → (#k0. f k0 = k))))
proof (induction n)
  case 0
    with assms have (f 0 = 0) by (simp add: dilating_def dilating_fun_def)
    thus ?case using "0.premis" by blast
  next
    case (Suc n)
    show ?case
    proof (cases (∃ n0. f n0 = n))
      case True

```



```

    from this obtain n0 where ⟨f n0 = n⟩ by blast
    hence ⟨f n0 < (Suc n) ∧ (∀k. f n0 < k ∧ k ≤ (Suc n) ⟶ (∄k0. f k0 = k))⟩
      using Suc.premis Suc_leI le_antisym by blast
    thus ?thesis by blast
next
case False
from Suc.IH[OF this] obtain np
  where ⟨f np < n ∧ (∀k. f np < k ∧ k ≤ n ⟶ (∄k0. f k0 = k))⟩ by blast
hence ⟨f np < Suc n ∧ (∀k. f np < k ∧ k ≤ n ⟶ (∄k0. f k0 = k))⟩ by simp
with Suc(2) have ⟨f np < (Suc n) ∧ (∀k. f np < k ∧ k ≤ (Suc n) ⟶ (∄k0. f k0 = k))⟩
  using le_Suc_eq by auto
thus ?thesis by blast
qed
qed

```

If a strictly monotonous function on `nat` increases only by one, its argument was increased only by one.

```

lemma strict_mono_suc:
  assumes ⟨strict_mono f⟩
  and ⟨f sn = Suc (f n)⟩
  shows ⟨sn = Suc n⟩
proof -
  from assms(2) have ⟨f sn > f n⟩ by simp
  with strict_mono_less[OF assms(1)] have ⟨sn > n⟩ by simp
  moreover have ⟨sn ≤ Suc n⟩
  proof -
    { assume ⟨sn > Suc n⟩
      from this obtain i where ⟨n < i ∧ i < sn⟩ by blast
      hence ⟨f n < f i ∧ f i < f sn⟩ using assms(1) by (simp add: strict_mono_def)
      with assms(2) have False by simp
    } thus ?thesis using not_less by blast
  qed
  ultimately show ?thesis by (simp add: Suc_leI)
qed

```

Two successive non stuttering instants of a dilated run are the images of two successive instants of the original run.

```

lemma next_non_stuttering:
  assumes ⟨dilating f sub r⟩
  and ⟨f np < n ∧ (∀k. f np < k ∧ k ≤ n ⟶ (∄k0. f k0 = k))⟩
  and ⟨f sn0 = Suc n⟩
  shows ⟨sn0 = Suc np⟩
proof -
  from assms(1) have smf:⟨strict_mono f⟩ by (simp add: dilating_def dilating_fun_def)
  from assms(2) have *:⟨∀k. f np < k ∧ k < Suc n ⟶ (∄k0. f k0 = k)⟩ by simp
  from assms(2) have ⟨f np < n⟩ by simp
  with smf assms(3) have **:⟨sn0 > np⟩ using strict_mono_less by fastforce
  have ⟨Suc n ≤ f (Suc np)⟩
  proof -
    { assume h:⟨Suc n > f (Suc np)⟩
      hence ⟨Suc np < sn0⟩ using ** Suc_lessI assms(3) by fastforce
      hence ⟨∃k. k > np ∧ f k < Suc n⟩ using h by blast
      with * have False using smf strict_mono_less by blast
    } thus ?thesis using not_less by blast
  qed
  hence ⟨sn0 ≤ Suc np⟩ using assms(3) smf using strict_mono_less_eq by fastforce
  with ** show ?thesis by simp
qed

```

The order relation between tick counts on clocks is preserved by dilation.

```

lemma dil_tick_count:
  assumes ⟨sub << r⟩
    and ⟨∀n. run_tick_count sub a n ≤ run_tick_count sub b n⟩
    shows ⟨run_tick_count r a n ≤ run_tick_count r b n⟩
proof -
  from assms(1) is_subrun_def obtain f where *:⟨dilating f sub r⟩ by blast
  show ?thesis
  proof (induction n)
    case 0
    from assms(2) have ⟨run_tick_count sub a 0 ≤ run_tick_count sub b 0⟩ ..
    with run_tick_count_sub[OF *, of _ 0] have
      ⟨run_tick_count r a (f 0) ≤ run_tick_count r b (f 0)⟩ by simp
    moreover from * have ⟨f 0 = 0⟩ by (simp add: dilating_def dilating_fun_def)
    ultimately show ?case by simp
  next
    case (Suc n') thus ?case
    proof (cases ⟨∃n₀. f n₀ = Suc n'⟩)
      case True
      from this obtain n₀ where fn0:⟨f n₀ = Suc n'⟩ by blast
      show ?thesis
      proof (cases ⟨ticks ((Rep_run sub) n₀ a)⟩)
        case True
        have ⟨run_tick_count r a (f n₀) ≤ run_tick_count r b (f n₀)⟩
          using assms(2) run_tick_count_sub[OF *] by simp
        thus ?thesis by (simp add: fn0)
      next
        case False
        hence ⟨¬ ticks ((Rep_run r) (Suc n') a)⟩
          using * fn0 ticks_sub by fastforce
        thus ?thesis by (simp add: Suc.IH le_SucI)
      qed
    next
      case False
      thus ?thesis using * Suc.IH no_tick_sub by fastforce
    qed
  qed
qed

```

Time does not progress during stuttering instants.

```

lemma stutter_no_time:
  assumes ⟨dilating f sub r⟩
    and ⟨∧k. f n < k ∧ k ≤ m ⟹ (∄k₀. f k₀ = k)⟩
    and ⟨m > f n⟩
    shows ⟨time ((Rep_run r) m c) = time ((Rep_run r) (f n) c)⟩
proof -
  from assms have ⟨∀k. k < m - (f n) ⟹ (∄k₀. f k₀ = Suc ((f n) + k))⟩ by simp
  hence ⟨∀k. k < m - (f n)
    ⟹ time ((Rep_run r) (Suc ((f n) + k)) c) = time ((Rep_run r) ((f n) + k) c)⟩
    using assms(1) by (simp add: dilating_def dilating_fun_def)
  hence *:⟨∀k. k < m - (f n) ⟹ time ((Rep_run r) (Suc ((f n) + k)) c) = time ((Rep_run r) (f n) c)⟩
    using bounded_suc_ind[of ⟨m - (f n)⟩ ⟨λk. time (Rep_run r k c)⟩ ⟨f n⟩] by blast
  from assms(3) obtain m₀ where m0:⟨Suc m₀ = m - (f n)⟩ using Suc_diff_Suc by blast
  with * have ⟨time ((Rep_run r) (Suc ((f n) + m₀)) c) = time ((Rep_run r) (f n) c)⟩ by auto
  moreover from m0 have ⟨Suc ((f n) + m₀) = m⟩ by simp
  ultimately show ?thesis by simp
qed

```

```

lemma time_stuttering:
  assumes ⟨dilating f sub r⟩
    and ⟨time ((Rep_run sub) n c) = τ⟩
    and ⟨ $\bigwedge k. f\ n < k \wedge k \leq m \implies (\nexists k_0. f\ k_0 = k)$ ⟩
    and ⟨m > f n⟩
  shows ⟨time ((Rep_run r) m c) = τ⟩
proof -
  from assms(3) have ⟨time ((Rep_run r) m c) = time ((Rep_run r) (f n) c)⟩
    using stutter_no_time[OF assms(1,3,4)] by blast
  also from assms(1,2) have ⟨time ((Rep_run r) (f n) c) = τ⟩ by (simp add: dilating_def)
  finally show ?thesis .
qed

```

The first instant at which a given date is reached on a clock is preserved by dilation.

```

lemma first_time_image:
  assumes ⟨dilating f sub r⟩
  shows ⟨first_time sub c n t = first_time r c (f n) t⟩
proof
  assume ⟨first_time sub c n t⟩
  with before_first_time[OF this]
    have *:⟨time ((Rep_run sub) n c) = t ∧ (∀m < n. time((Rep_run sub) m c) < t)⟩
    by (simp add: first_time_def)
  moreover have ⟨∀n c. time (Rep_run sub n c) = time (Rep_run r (f n) c)⟩
    using assms(1) by (simp add: dilating_def)
  ultimately have **:
    ⟨time ((Rep_run r) (f n) c) = t ∧ (∀m < n. time((Rep_run r) (f m) c) < t)⟩
    by simp
  have ⟨∀m < f n. time ((Rep_run r) m c) < t⟩
  proof -
    { fix m assume hyp:⟨m < f n⟩
      have ⟨time ((Rep_run r) m c) < t⟩
      proof (cases ⟨ $\exists m_0. f\ m_0 = m$ ⟩)
        case True
          from this obtain m0 where mm0:⟨m = f m0⟩ by blast
          with hyp have m0n:⟨m0 < n⟩ using assms(1)
            by (simp add: dilating_def dilating_fun_def strict_mono_less)
          hence ⟨time ((Rep_run sub) m0 c) < t⟩ using * by blast
          thus ?thesis by (simp add: mm0 m0n **)
        case False
          hence ⟨ $\exists m_p. f\ m_p < m \wedge (\forall k. f\ m_p < k \wedge k \leq m \implies (\nexists k_0. f\ k_0 = k))$ ⟩
            using greatest_prev_image[OF assms] by simp
          from this obtain mp where
            mp:⟨f m_p < m ∧ (∀k. f m_p < k ∧ k ≤ m ⟶ (∄k_0. f k_0 = k))⟩ by blast
          hence ⟨time ((Rep_run r) m c) = time ((Rep_run sub) mp c)⟩
            using time_stuttering[OF assms] by blast
          also from hyp mp have ⟨f m_p < f n⟩ by linarith
          hence ⟨m_p < n⟩ using assms
            by (simp add: dilating_def dilating_fun_def strict_mono_less)
          hence ⟨time ((Rep_run sub) mp c) < t⟩ using * by simp
          finally show ?thesis by simp
        qed
      } thus ?thesis by simp
    }
  qed
  with ** show ⟨first_time r c (f n) t⟩ by (simp add: alt_first_time_def)
next
  assume ⟨first_time r c (f n) t⟩
  hence *:⟨time ((Rep_run r) (f n) c) = t ∧ (∀k < f n. time ((Rep_run r) k c) < t)⟩

```

```

    by (simp add: first_time_def before_first_time)
  hence ⟨time ((Rep_run sub) n c) = t⟩ using assms dilating_def by blast
  moreover from * have ⟨(∀k < n. time ((Rep_run sub) k c) < t)⟩
    using assms dilating_def dilating_fun_def strict_monoD by fastforce
  ultimately show ⟨first_time sub c n t⟩ by (simp add: alt_first_time_def)
qed

```

The first instant of a dilated run is necessarily the image of the first instant of the original run.

```

lemma first_dilated_instant:
  assumes ⟨strict_mono f⟩
    and ⟨f (0::nat) = (0::nat)⟩
  shows ⟨Max {i. f i ≤ 0} = 0⟩
proof -
  from assms(2) have ⟨∀n > 0. f n > 0⟩ using strict_monoD[OF assms(1)] by force
  hence ⟨∀n ≠ 0. ¬(f n ≤ 0)⟩ by simp
  with assms(2) have ⟨{i. f i ≤ 0} = {0}⟩ by blast
  thus ?thesis by simp
qed

```

For any instant  $n$  of a dilated run, let  $n_0$  be the last instant before  $n$  that is the image of an original instant. All instants strictly after  $n_0$  and before  $n$  are stuttering instants.

```

lemma not_image_stut:
  assumes ⟨dilating f sub r⟩
    and ⟨n₀ = Max {i. f i ≤ n}⟩
    and ⟨f n₀ < k ∧ k ≤ n⟩
  shows ⟨¬k₀. f k₀ = k⟩
proof -
  from assms(1) have smf:⟨strict_mono f⟩
    and fxge:⟨∀x. f x ≥ x⟩
  by (auto simp add: dilating_def dilating_fun_def)
  have finite_prefix:⟨finite {i. f i ≤ n}⟩ by (simp add: finite_less_ub fxge)
  from assms(1) have ⟨f 0 ≤ n⟩ by (simp add: dilating_def dilating_fun_def)
  hence ⟨{i. f i ≤ n} ≠ {}⟩ by blast
  from assms(3) fxge have ⟨f n₀ < n⟩ by linarith
  from assms(2) have ⟨∀x > n₀. f x > n⟩ using Max.coboundedI[OF finite_prefix]
    using not_le by auto
  with assms(3) strict_mono_less[OF smf] show ?thesis by auto
qed

```

For any dilating function  $f$ ,  $\text{dil\_inverse } f$  is a contracting function.

```

lemma contracting_inverse:
  assumes ⟨dilating f sub r⟩
  shows ⟨contracting (dil_inverse f) r sub f⟩
proof -
  from assms have smf:⟨strict_mono f⟩
    and no_img_tick:⟨∀k. (¬k₀. f k₀ = k) ⟶ (∀c. ¬(ticks ((Rep_run r) k c)))⟩
    and no_img_time:⟨∧n. (¬n₀. f n₀ = (Suc n)) ⟶ (∀c. time ((Rep_run r) (Suc n) c) = time ((Rep_run r) n c))⟩
    and fxge:⟨∀x. f x ≥ x⟩ and f0n:⟨∧n. f 0 ≤ n⟩ and f0:⟨f 0 = 0⟩
  by (auto simp add: dilating_def dilating_fun_def)
  have finite_prefix:⟨∧n. finite {i. f i ≤ n}⟩ by (auto simp add: finite_less_ub fxge)
  have prefix_not_empty:⟨∧n. {i. f i ≤ n} ≠ {}⟩ using f0n by blast

  have 1:⟨mono (dil_inverse f)⟩
  proof -
    { fix x::nat and y::nat assume hyp:⟨x ≤ y⟩
      hence inc:⟨{i. f i ≤ x} ⊆ {i. f i ≤ y}⟩

```

```

    by (simp add: hyp Collect_mono le_trans)
    from Max_mono[OF inc prefix_not_empty finite_prefix]
    have <math>\langle \text{dil\_inverse } f \rangle x \leq \langle \text{dil\_inverse } f \rangle y</math> unfolding dil_inverse_def .
  } thus ?thesis unfolding mono_def by simp
qed

from first_dilated_instant[OF smf f0] have 2:<math>\langle \text{dil\_inverse } f \rangle 0 = 0</math>
  unfolding dil_inverse_def .

from fxge have <math>\langle \forall n. f\ i \leq n \longrightarrow i \leq n \rangle</math> using le_trans by blast
hence 3:<math>\langle \forall n. \langle \text{dil\_inverse } f \rangle n \leq n \rangle</math> using Max_in[OF finite_prefix prefix_not_empty]
  unfolding dil_inverse_def by blast

from 1 2 3 have *:<math>\langle \text{contracting\_fun } (\text{dil\_inverse } f) \rangle</math> by (simp add: contracting_fun_def)

have <math>\langle \forall n. \text{finite } \{i. f\ i \leq n\} \rangle</math> by (simp add: finite_prefix)
moreover have <math>\langle \forall n. \{i. f\ i \leq n\} \neq \{\} \rangle</math> using prefix_not_empty by blast
ultimately have 4:<math>\langle \forall n. f\ (\langle \text{dil\_inverse } f \rangle n) \leq n \rangle</math>
  unfolding dil_inverse_def
  using assms(1) dilating_fun_def dilating_fun_def Max_in by blast

have 5:<math>\langle \forall n\ c\ k. f\ (\langle \text{dil\_inverse } f \rangle n) < k \wedge k \leq n \longrightarrow \neg \text{ticks } (\langle \text{Rep\_run } r \rangle k\ c) \rangle</math>
  using not_image_stut[OF assms] no_img_tick unfolding dil_inverse_def by blast

have 6:<math>\langle \forall n\ c\ k. f\ (\langle \text{dil\_inverse } f \rangle n) \leq k \wedge k \leq n \longrightarrow \text{time } (\langle \text{Rep\_run } r \rangle k\ c) = \text{time } (\langle \text{Rep\_run } \text{sub} \rangle (\langle \text{dil\_inverse } f \rangle n)\ c) \rangle</math>
proof -
  { fix n c k assume h:<math>\langle f\ (\langle \text{dil\_inverse } f \rangle n) \leq k \wedge k \leq n \rangle</math>
    let ? $\tau$  = <math>\langle \text{time } (\langle \text{Rep\_run } \text{sub} \rangle (\langle \text{dil\_inverse } f \rangle n)\ c) \rangle</math>
    have tau:<math>\langle \text{time } (\langle \text{Rep\_run } \text{sub} \rangle (\langle \text{dil\_inverse } f \rangle n)\ c) \rangle = ?\tau</math> ..
    have gn:<math>\langle \text{dil\_inverse } f \rangle n = \text{Max } \{i. f\ i \leq n\}</math> unfolding dil_inverse_def ..
    from time_stuttering[OF assms tau, of k] not_image_stut[OF assms gn]
    have <math>\langle \text{time } (\langle \text{Rep\_run } r \rangle k\ c) = \text{time } (\langle \text{Rep\_run } \text{sub} \rangle (\langle \text{dil\_inverse } f \rangle n)\ c) \rangle</math>
    proof (cases <math>\langle f\ (\langle \text{dil\_inverse } f \rangle n) = k \rangle</math>)
      case True
        moreover have <math>\langle \forall n\ c. \text{time } (\langle \text{Rep\_run } \text{sub} \rangle n\ c) = \text{time } (\langle \text{Rep\_run } r \rangle (f\ n)\ c) \rangle</math>
          using assms by (simp add: dilating_def)
        ultimately show ?thesis by simp
      next
      case False
        with h have <math>\langle f\ (\text{Max } \{i. f\ i \leq n\}) < k \wedge k \leq n \rangle</math> by (simp add: dil_inverse_def)
        with time_stuttering[OF assms tau, of k] not_image_stut[OF assms gn]
        show ?thesis unfolding dil_inverse_def by auto
    qed
  } thus ?thesis by simp
qed

from * 4 5 6 show ?thesis unfolding contracting_def by simp
qed

```

The only possible contracting function toward a dense run (a run with no empty instants) is the inverse of the dilating function as defined by `dil_inverse`.

```

lemma dense_run_dil_inverse_only:
  assumes <math>\langle \text{dilating } f\ \text{sub } r \rangle</math>
    and <math>\langle \text{contracting } g\ r\ \text{sub } f \rangle</math>
    and <math>\langle \text{dense\_run } \text{sub} \rangle</math>
  shows <math>\langle g = (\text{dil\_inverse } f) \rangle</math>

```

```

proof
  from assms(1) have *:⟨ $\bigwedge n. \text{finite } \{i. f\ i \leq n\}$ ⟩
    using finite_less_ub by (simp add: dilating_def dilating_fun_def)
  from assms(1) have ⟨ $f\ 0 = 0$ ⟩ by (simp add: dilating_def dilating_fun_def)
  hence ⟨ $\bigwedge n. 0 \in \{i. f\ i \leq n\}$ ⟩ by simp
  hence *:⟨ $\bigwedge n. \{i. f\ i \leq n\} \neq \{\}$ ⟩ by blast
  { fix n assume h:⟨ $g\ n < (\text{dil\_inverse } f)\ n$ ⟩
    hence ⟨ $\exists k > g\ n. f\ k \leq n$ ⟩ unfolding dil_inverse_def using Max_in[OF *] by blast
    from this obtain k where kprop:⟨ $g\ n < k \wedge f\ k \leq n$ ⟩ by blast
    with assms(3) dense_run_def obtain c where ⟨ticks ((Rep_run sub) k c)⟩ by blast
    hence ⟨ticks ((Rep_run r) (f k) c)⟩ using ticks_sub[OF assms(1)] by blast
    moreover from kprop have ⟨ $f\ (g\ n) < f\ k \wedge f\ k \leq n$ ⟩ using assms(1)
      by (simp add: dilating_def dilating_fun_def strict_monoD)
    ultimately have False using assms(2) unfolding contracting_def by blast
  } hence 1:⟨ $\bigwedge n. \neg(g\ n < (\text{dil\_inverse } f)\ n)$ ⟩ by blast
  { fix n assume h:⟨ $g\ n > (\text{dil\_inverse } f)\ n$ ⟩
    have ⟨ $\exists k \leq g\ n. f\ k > n$ ⟩
      proof -
        { assume ⟨ $\forall k \leq g\ n. f\ k \leq n$ ⟩
          with h have False unfolding dil_inverse_def
            using Max_gr_iff[OF *] by blast
        }
        thus ?thesis using not_less by blast
      qed
    from this obtain k where ⟨ $k \leq g\ n \wedge f\ k > n$ ⟩ by blast
    hence ⟨ $f\ (g\ n) \geq f\ k \wedge f\ k > n$ ⟩ using assms(1)
      by (simp add: dilating_def dilating_fun_def strict_mono_less_eq)
    hence ⟨ $f\ (g\ n) > n$ ⟩ by simp
    with assms(2) have False unfolding contracting_def by (simp add: leD)
  } hence 2:⟨ $\bigwedge n. \neg(g\ n > (\text{dil\_inverse } f)\ n)$ ⟩ by blast
  from 1 2 show ⟨ $\bigwedge n. g\ n = (\text{dil\_inverse } f)\ n$ ⟩ by (simp add: not_less_iff_gr_or_eq)
qed

end

```

### 8.1.5 Main Theorems

```

theory Stuttering
imports StutteringLemmas

```

```

begin

```

Using the lemmas of the previous section about the invariance by stuttering of various properties of TESL specifications, we can now prove that the atomic formulae that compose TESL specifications are invariant by stuttering.

Sporadic specifications are preserved in a dilated run.

```

lemma sporadic_sub:
  assumes ⟨sub  $\ll$  r⟩
    and ⟨sub  $\in \llbracket c \text{ sporadic } \tau \text{ on } c' \rrbracket_{TESL}$ ⟩
    shows ⟨r  $\in \llbracket c \text{ sporadic } \tau \text{ on } c' \rrbracket_{TESL}$ ⟩
proof -
  from assms(1) is_subrun_def obtain f
    where ⟨dilating f sub r⟩ by blast
  hence ⟨ $\forall n\ c. \text{time } ((\text{Rep\_run sub})\ n\ c) = \text{time } ((\text{Rep\_run r})\ (f\ n)\ c)$ ⟩
     $\wedge \text{ticks } ((\text{Rep\_run sub})\ n\ c) = \text{ticks } ((\text{Rep\_run r})\ (f\ n)\ c)$ ⟩ by (simp add: dilating_def)
  moreover from assms(2) have
    ⟨sub  $\in \{r. \exists n. \text{ticks } ((\text{Rep\_run r})\ n\ c) \wedge \text{time } ((\text{Rep\_run r})\ n\ c') = \tau\}$ ⟩ by simp

```

from this obtain  $k$  where  $\langle \text{time } ((\text{Rep\_run sub}) k c') = \tau \wedge \text{ticks } ((\text{Rep\_run sub}) k c) \rangle$  by auto  
 ultimately have  $\langle \text{time } ((\text{Rep\_run r}) (f k) c') = \tau \wedge \text{ticks } ((\text{Rep\_run r}) (f k) c) \rangle$  by simp  
 thus ?thesis by auto  
 qed

Implications are preserved in a dilated run.

theorem implies\_sub:  
 assumes  $\langle \text{sub} \ll r \rangle$   
 and  $\langle \text{sub} \in \llbracket c_1 \text{ implies } c_2 \rrbracket_{TESL} \rangle$   
 shows  $\langle r \in \llbracket c_1 \text{ implies } c_2 \rrbracket_{TESL} \rangle$   
 proof -  
 from assms(1) is\_subrun\_def obtain  $f$  where  $\langle \text{dilating } f \text{ sub } r \rangle$  by blast  
 moreover from assms(2) have  
 $\langle \text{sub} \in \{r. \forall n. \text{ticks } ((\text{Rep\_run r}) n c_1) \longrightarrow \text{ticks } ((\text{Rep\_run r}) n c_2)\} \rangle$  by simp  
 hence  $\langle \forall n. \text{ticks } ((\text{Rep\_run sub}) n c_1) \longrightarrow \text{ticks } ((\text{Rep\_run sub}) n c_2) \rangle$  by simp  
 ultimately have  $\langle \forall n. \text{ticks } ((\text{Rep\_run r}) n c_1) \longrightarrow \text{ticks } ((\text{Rep\_run r}) n c_2) \rangle$   
 using ticks\_imp\_ticks\_subk ticks\_sub by blast  
 thus ?thesis by simp  
 qed

theorem implies\_not\_sub:  
 assumes  $\langle \text{sub} \ll r \rangle$   
 and  $\langle \text{sub} \in \llbracket c_1 \text{ implies not } c_2 \rrbracket_{TESL} \rangle$   
 shows  $\langle r \in \llbracket c_1 \text{ implies not } c_2 \rrbracket_{TESL} \rangle$   
 proof -  
 from assms(1) is\_subrun\_def obtain  $f$  where  $\langle \text{dilating } f \text{ sub } r \rangle$  by blast  
 moreover from assms(2) have  
 $\langle \text{sub} \in \{r. \forall n. \text{ticks } ((\text{Rep\_run r}) n c_1) \longrightarrow \neg \text{ticks } ((\text{Rep\_run r}) n c_2)\} \rangle$  by simp  
 hence  $\langle \forall n. \text{ticks } ((\text{Rep\_run sub}) n c_1) \longrightarrow \neg \text{ticks } ((\text{Rep\_run sub}) n c_2) \rangle$  by simp  
 ultimately have  $\langle \forall n. \text{ticks } ((\text{Rep\_run r}) n c_1) \longrightarrow \neg \text{ticks } ((\text{Rep\_run r}) n c_2) \rangle$   
 using ticks\_imp\_ticks\_subk ticks\_sub by blast  
 thus ?thesis by simp  
 qed

Precedence relations are preserved in a dilated run.

theorem weakly\_precedes\_sub:  
 assumes  $\langle \text{sub} \ll r \rangle$   
 and  $\langle \text{sub} \in \llbracket c_1 \text{ weakly precedes } c_2 \rrbracket_{TESL} \rangle$   
 shows  $\langle r \in \llbracket c_1 \text{ weakly precedes } c_2 \rrbracket_{TESL} \rangle$   
 proof -  
 from assms(1) is\_subrun\_def obtain  $f$  where  $\langle \text{dilating } f \text{ sub } r \rangle$  by blast  
 from assms(2) have  
 $\langle \text{sub} \in \{r. \forall n. (\text{run\_tick\_count } r c_2 n) \leq (\text{run\_tick\_count } r c_1 n)\} \rangle$  by simp  
 hence  $\langle \forall n. (\text{run\_tick\_count } \text{sub } c_2 n) \leq (\text{run\_tick\_count } \text{sub } c_1 n) \rangle$  by simp  
 from dil\_tick\_count[OF assms(1) this]  
 have  $\langle \forall n. (\text{run\_tick\_count } r c_2 n) \leq (\text{run\_tick\_count } r c_1 n) \rangle$  by simp  
 thus ?thesis by simp  
 qed

theorem strictly\_precedes\_sub:  
 assumes  $\langle \text{sub} \ll r \rangle$   
 and  $\langle \text{sub} \in \llbracket c_1 \text{ strictly precedes } c_2 \rrbracket_{TESL} \rangle$   
 shows  $\langle r \in \llbracket c_1 \text{ strictly precedes } c_2 \rrbracket_{TESL} \rangle$   
 proof -  
 from assms(1) is\_subrun\_def obtain  $f$  where  $\langle \text{dilating } f \text{ sub } r \rangle$  by blast  
 from assms(2) have  
 $\langle \text{sub} \in \{ \varrho. \forall n::\text{nat}. (\text{run\_tick\_count } \varrho c_2 n) \leq (\text{run\_tick\_count\_strictly } \varrho c_1 n) \} \rangle$   
 by simp

```

with strictly_precedes_alt_def2[of ⟨c₂⟩ ⟨c₁⟩] have
  ⟨sub ∈ { ρ. (¬ticks ((Rep_run ρ) 0 c₂)) }
  ∧ (∀n::nat. (run_tick_count ρ c₂ (Suc n)) ≤ (run_tick_count ρ c₁ n)) ⟩
by blast
hence ⟨(¬ticks ((Rep_run sub) 0 c₂))
  ∧ (∀n::nat. (run_tick_count sub c₂ (Suc n)) ≤ (run_tick_count sub c₁ n))⟩
  by simp
hence
  1:⟨(¬ticks ((Rep_run sub) 0 c₂))
  ∧ (∀n::nat. (tick_count sub c₂ (Suc n)) ≤ (tick_count sub c₁ n))⟩
by (simp add: tick_count_is_fun)
have ⟨∀n::nat. (tick_count r c₂ (Suc n)) ≤ (tick_count r c₁ n)⟩
proof -
  { fix n::nat
    have ⟨tick_count r c₂ (Suc n) ≤ tick_count r c₁ n⟩
    proof (cases ⟨∃n₀. f n₀ = n⟩)
      case True — n is in the image of f
        from this obtain n₀ where fn:⟨f n₀ = n⟩ by blast
        show ?thesis
        proof (cases ⟨∃sn₀. f sn₀ = Suc n⟩)
          case True — Suc n is in the image of f
            from this obtain sn₀ where fsn:⟨f sn₀ = Suc n⟩ by blast
            with fn strict_mono_suc * have ⟨sn₀ = Suc n₀⟩
              using dilating_def dilating_fun_def by blast
            with 1 have ⟨tick_count sub c₂ sn₀ ≤ tick_count sub c₁ n₀⟩ by simp
            thus ?thesis using fn fsn tick_count_sub[OF *] by simp
          next
            case False — Suc n is not in the image of f
              hence ⟨¬ticks ((Rep_run r) (Suc n) c₂)⟩
                using * by (simp add: dilating_def dilating_fun_def)
              hence ⟨tick_count r c₂ (Suc n) = tick_count r c₂ n⟩
                by (simp add: tick_count_suc)
              also have ⟨... = tick_count sub c₂ n₀⟩
                using fn tick_count_sub[OF *] by simp
              finally have ⟨tick_count r c₂ (Suc n) = tick_count sub c₂ n₀⟩ .
              moreover have ⟨tick_count sub c₂ n₀ ≤ tick_count sub c₂ (Suc n₀)⟩
                by (simp add: tick_count_suc)
              ultimately have
                ⟨tick_count r c₂ (Suc n) ≤ tick_count sub c₂ (Suc n₀)⟩ by simp
              moreover have
                ⟨tick_count sub c₂ (Suc n₀) ≤ tick_count sub c₁ n₀⟩ using 1 by simp
              ultimately have ⟨tick_count r c₂ (Suc n) ≤ tick_count sub c₁ n₀⟩ by simp
              thus ?thesis using tick_count_sub[OF *] fn by simp
            qed
          next
            case False — n is not in the image of f
              from greatest_prev_image[OF * this] obtain nₚ where
                np_prop:⟨f nₚ < n ∧ (∀k. f nₚ < k ∧ k ≤ n ⟶ (∄k₀. f k₀ = k))⟩ by blast
              from tick_count_latest[OF * this] have
                ⟨tick_count r c₁ n = tick_count r c₁ (f nₚ)⟩ .
              hence a:⟨tick_count r c₁ n = tick_count sub c₁ nₚ⟩
                using tick_count_sub[OF *] by simp
              have b:⟨tick_count sub c₂ (Suc nₚ) ≤ tick_count sub c₁ nₚ⟩ using 1 by simp
              show ?thesis
              proof (cases ⟨∃sn₀. f sn₀ = Suc n⟩)
                case True — Suc n is in the image of f
                  from this obtain sn₀ where fsn:⟨f sn₀ = Suc n⟩ by blast

```



```

    from next_non_stuttering[OF * np_prop this] have sn_prop: (sn0 = Suc np) .
    with b have (tick_count sub c2 sn0 ≤ tick_count sub c1 np) by simp
    thus ?thesis using tick_count_sub[OF *] fsn a by auto
  next
  case False — Suc n is not in the image of f
    hence (¬ticks ((Rep_run r) (Suc n) c2))
      using * by (simp add: dilating_def dilating_fun_def)
    hence (tick_count r c2 (Suc n) = tick_count r c2 n)
      by (simp add: tick_count_suc)
    also have (... = tick_count sub c2 np) using np_prop tick_count_sub[OF *]
      by (simp add: tick_count_latest[OF * np_prop])
    finally have (tick_count r c2 (Suc n) = tick_count sub c2 np) .
    moreover have (tick_count sub c2 np ≤ tick_count sub c2 (Suc np))
      by (simp add: tick_count_suc)
    ultimately have
      (tick_count r c2 (Suc n) ≤ tick_count sub c2 (Suc np)) by simp
    moreover have
      (tick_count sub c2 (Suc np) ≤ tick_count sub c1 np) using 1 by simp
    ultimately have (tick_count r c2 (Suc n) ≤ tick_count sub c1 np) by simp
    thus ?thesis using np_prop mono_tick_count using a by linarith
  qed
} thus ?thesis ..
qed
moreover from 1 have (¬ticks ((Rep_run r) 0 c2))
  using * empty_dilated_prefix ticks_sub by fastforce
ultimately show ?thesis by (simp add: tick_count_is_fun strictly_precedes_alt_def2)
qed

```

Time delayed relations are preserved in a dilated run.

**theorem** time\_delayed\_sub:

```

  assumes (sub << r)
    and (sub ∈ [| a time-delayed by δτ on ms implies b |]TESL)
    shows (r ∈ [| a time-delayed by δτ on ms implies b |]TESL)
  proof -
    from assms(1) is_subrun_def obtain f where *: (dilating f sub r) by blast
    from assms(2) have (∀n. ticks ((Rep_run sub) n a)
      → (∀m ≥ n. first_time sub ms m (time ((Rep_run sub) n ms) + δτ)
        → ticks ((Rep_run sub) m b)))
      using TESL_interpretation_atomic.simps(5) [of ⟨a⟩ ⟨δτ⟩ ⟨ms⟩ ⟨b⟩] by simp
    hence **: (∀n0. ticks ((Rep_run r) (f n0) a)
      → (∀m0 ≥ n0. first_time r ms (f m0) (time ((Rep_run r) (f n0) ms) + δτ)
        → ticks ((Rep_run r) (f m0) b)))
      using first_time_image[OF *] dilating_def * by fastforce
    hence (∀n. ticks ((Rep_run r) n a)
      → (∀m ≥ n. first_time r ms m (time ((Rep_run r) n ms) + δτ)
        → ticks ((Rep_run r) m b)))
      proof -
        { fix n assume assm: (ticks ((Rep_run r) n a))
          from ticks_image_sub[OF * assm] obtain n0 where nfn0: (n = f n0) by blast
          with ** assm have ft0:
            (∀m0 ≥ n0. first_time r ms (f m0) (time ((Rep_run r) (f n0) ms) + δτ)
              → ticks ((Rep_run r) (f m0) b))) by blast
          have (∀m ≥ n. first_time r ms m (time ((Rep_run r) n ms) + δτ)
            → ticks ((Rep_run r) m b)))
            proof -
              { fix m assume hyp: (m ≥ n)
                have (first_time r ms m (time ((Rep_run r) n ms) + δτ) → ticks ((Rep_run r) m b))

```

```

proof (cases (∃ m₀. f m₀ = m))
  case True
  from this obtain m₀ where (m = f m₀) by blast
  moreover have (strict_mono f) using * by (simp add: dilating_def dilating_fun_def)
  ultimately show ?thesis using ft0 hyp nfn0 by (simp add: strict_mono_less_eq)
next
  case False thus ?thesis
  proof (cases (m = 0))
    case True
    hence (m = f 0) using * by (simp add: dilating_def dilating_fun_def)
    then show ?thesis using False by blast
  next
    case False
    hence (∃ pm. m = Suc pm) by (simp add: not0_implies_Suc)
    from this obtain pm where mpm: (m = Suc pm) by blast
    hence (∄ pm₀. f pm₀ = Suc pm) using (∄ m₀. f m₀ = m) by simp
    with * have (time (Rep_run r (Suc pm) ms) = time (Rep_run r pm ms))
      using dilating_def dilating_fun_def by blast
    hence (time (Rep_run r pm ms) = time (Rep_run r m ms)) using mpm by simp
    moreover from mpm have (pm < m) by simp
    ultimately have (∃ m' < m. time (Rep_run r m' ms) = time (Rep_run r m ms)) by blast
    hence (¬(first_time r ms m (time (Rep_run r n ms) + δτ)))
      by (auto simp add: first_time_def)
    thus ?thesis by simp
  qed
qed
} thus ?thesis by simp
qed
} thus ?thesis by simp
qed
thus ?thesis by simp
qed

```

Relaxed time delayed relations are preserved in a dilated run.

**theorem** relaxed\_time\_delayed\_sub:

```

  assumes (sub << r)
  and (sub ∈ [ [ a time-delayed< by δτ on ms implies b ] ]TESL)
  shows (r ∈ [ [ a time-delayed< by δτ on ms implies b ] ]TESL)
proof -
  from assms(1) is_subrun_def obtain f where dilf: (dilating f sub r) by blast
  from assms(2) have (∀ n. ticks ((Rep_run sub) n a)
    → (∃ m ≥ n. ticks ((Rep_run sub) m b)
      ∧ time ((Rep_run sub) m ms) = time ((Rep_run sub) n ms) + δτ))
  using TESL_interpretation_atomic.simps(6)[of (a) (δτ) (ms) (b)] by simp
  hence **: (∀ n₀. ticks ((Rep_run r) (f n₀) a)
    → (∃ m₀ ≥ n₀. ticks ((Rep_run r) (f m₀) b)
      ∧ time ((Rep_run r) (f m₀) ms) = time ((Rep_run r) (f n₀) ms) + δτ))
  using first_time_image[OF dilf] dilating_def dilf by fastforce
  hence (∀ n. ticks ((Rep_run r) n a)
    → (∃ m ≥ n. ticks ((Rep_run r) m b)
      ∧ time ((Rep_run r) m ms) = time ((Rep_run r) n ms) + δτ))
proof -
  { fix n assume assm: (ticks ((Rep_run r) n a))
    from ticks_image_sub[OF dilf assm] obtain n₀ where nfn0: (n = f n₀) by blast
    with ** assm have ft0:
      (∃ m₀ ≥ n₀. ticks ((Rep_run r) (f m₀) b)
        ∧ time ((Rep_run r) (f m₀) ms) = time ((Rep_run r) (f n₀) ms) + δτ) by blast
    from this obtain m₀ where

```

```

    ⟨m0 ≥ n0 ∧ ticks ((Rep_run r) (f m0) b)
  ∧ (time ((Rep_run r) (f m0) ms) = time ((Rep_run r) n ms) + δτ)⟩ using nfn0 by blast
  hence ⟨f m0 ≥ n⟩
    and ⟨ticks ((Rep_run r) (f m0) b)
      ∧ (time ((Rep_run r) (f m0) ms) = time ((Rep_run r) n ms) + δτ)⟩
    using dilf nfn0
    by (simp add: dilating_def dilating_fun_def strict_mono_less_eq, simp)
  hence ⟨(∃m ≥ n. ticks ((Rep_run r) m b)
    ∧ time ((Rep_run r) m ms) = time ((Rep_run r) n ms) + δτ)⟩ by blast
} thus ?thesis by simp
qed
thus ?thesis by simp
qed

```

Time relations are preserved through dilation of a run.

```

lemma tagrel_sub':
  assumes ⟨sub << r⟩
    and ⟨sub ∈ ⟦ time-relation [c1,c2] ∈ R ⟧TESL⟩
    shows ⟨R (time ((Rep_run r) n c1), time ((Rep_run r) n c2))⟩
proof -
  from assms(1) is_subrun_def obtain f where *:⟨dilating f sub r⟩ by blast
  moreover from assms(2) TESL_interpretation_atomic.simps(2) have
    ⟨sub ∈ {r. ∀n. R (time ((Rep_run r) n c1), time ((Rep_run r) n c2))}⟩ by blast
  hence 1:⟨∀n. R (time ((Rep_run sub) n c1), time ((Rep_run sub) n c2))⟩ by simp
  show ?thesis
  proof (induction n)
    case 0
      from 1 have ⟨R (time ((Rep_run sub) 0 c1), time ((Rep_run sub) 0 c2))⟩ by simp
      moreover from * have ⟨f 0 = 0⟩ by (simp add: dilating_def dilating_fun_def)
      moreover from * have ⟨∀c. time ((Rep_run sub) 0 c) = time ((Rep_run r) (f 0) c)⟩
        by (simp add: dilating_def)
      ultimately show ?case by simp
    next
      case (Suc n)
      then show ?case
      proof (cases ⟨#n0. f n0 = Suc n⟩)
        case True
          with * have ⟨∀c. time (Rep_run r (Suc n) c) = time (Rep_run r n c)⟩
            by (simp add: dilating_def dilating_fun_def)
          thus ?thesis using Suc.IH by simp
        next
          case False
          from this obtain n0 where n0prop:⟨f n0 = Suc n⟩ by blast
          from 1 have ⟨R (time ((Rep_run sub) n0 c1), time ((Rep_run sub) n0 c2))⟩ by simp
          moreover from n0prop * have ⟨time ((Rep_run sub) n0 c1) = time ((Rep_run r) (Suc n) c1)⟩
            by (simp add: dilating_def)
          moreover from n0prop * have ⟨time ((Rep_run sub) n0 c2) = time ((Rep_run r) (Suc n) c2)⟩
            by (simp add: dilating_def)
          ultimately show ?thesis by simp
        qed
      qed
    qed
  qed

```

corollary tagrel\_sub:

```

  assumes ⟨sub << r⟩
    and ⟨sub ∈ ⟦ time-relation [c1,c2] ∈ R ⟧TESL⟩
    shows ⟨r ∈ ⟦ time-relation [c1,c2] ∈ R ⟧TESL⟩
using tagrel_sub'[OF assms] unfolding TESL_interpretation_atomic.simps(3) by simp

```

Kill relations are preserved in a dilated run.

```

theorem kill_sub:
  assumes ⟨sub << r⟩
    and ⟨sub ∈ ⟦ c1 kills c2 ⟧TESL⟩
    shows ⟨r ∈ ⟦ c1 kills c2 ⟧TESL⟩
proof -
  from assms(1) is_subrun_def obtain f where *:⟨dilating f sub r⟩ by blast
  from assms(2) TESL_interpretation_atomic.simps(8) have
    ⟨∀n. ticks (Rep_run sub n c1) ⟶ (∀m≥n. ¬ ticks (Rep_run sub m c2))⟩ by simp
  hence 1:⟨∀n. ticks (Rep_run r (f n) c1) ⟶ (∀m≥n. ¬ ticks (Rep_run r (f m) c2))⟩
    using ticks_sub[OF *] by simp
  hence ⟨∀n. ticks (Rep_run r (f n) c1) ⟶ (∀m≥ (f n). ¬ ticks (Rep_run r m c2))⟩
  proof -
    { fix n assume ⟨ticks (Rep_run r (f n) c1)⟩
      with 1 have 2:⟨∀ m ≥ n. ¬ ticks (Rep_run r (f m) c2)⟩ by simp
      have ⟨∀ m ≥ (f n). ¬ ticks (Rep_run r m c2)⟩
      proof -
        { fix m assume h:⟨m ≥ f n⟩
          have ⟨¬ ticks (Rep_run r m c2)⟩
          proof (cases ⟨∃m0. f m0 = m⟩)
            case True
              from this obtain m0 where fm0:⟨f m0 = m⟩ by blast
              hence ⟨m0 ≥ n⟩
                using * dilating_def dilating_fun_def h strict_mono_less_eq by fastforce
              with 2 show ?thesis using fm0 by blast
            next
            case False
              thus ?thesis using ticks_image_sub'[OF *] by blast
          qed
        } thus ?thesis by simp
      qed
    } thus ?thesis by simp
  qed
  hence ⟨∀n. ticks (Rep_run r n c1) ⟶ (∀m ≥ n. ¬ ticks (Rep_run r m c2))⟩
    using ticks_imp_ticks_subk[OF *] by blast
  thus ?thesis using TESL_interpretation_atomic.simps(9) by blast
qed

```

strictly\_precedes\_sub kill\_sub relaxed\_time\_delayed\_sub

We can now prove that all atomic specification formulae are preserved by the dilation of runs.

```
lemma atomic_sub:
  assumes ⟨sub ≪ r⟩
    and ⟨is_public_atom ϕ⟩
    and ⟨sub ∈ ⟦ ϕ ⟧TESL⟩
  shows ⟨r ∈ ⟦ ϕ ⟧TESL⟩
using assms(2,3) atomic_sub_lemmas[OF assms(1)] by (cases ϕ, simp_all)
```

Finally, any TESL specification is invariant by stuttering.

```
theorem TESL_stuttering_invariant:
  assumes ⟨sub ≪ r⟩
  shows ⟨[is_public_spec S; sub ∈ ⟦ S ⟧TESL] ⟹ r ∈ ⟦ S ⟧TESL⟩
proof (induction S)
  case Nil
  thus ?case by simp
next
  case (Cons a s) print_facts
  from Cons.prem(1) have puba:⟨is_public_atom a⟩ and pubs:⟨is_public_spec s⟩ by simp+
  from Cons.prem(2) have sa:⟨sub ∈ ⟦ a ⟧TESL⟩ and sb:⟨sub ∈ ⟦ s ⟧TESL⟩
    using TESL_interpretation_image by simp+
  from Cons.IH[OF pubs sb] have ⟨r ∈ ⟦ s ⟧TESL⟩ .
  moreover from atomic_sub[OF assms(1) puba sa] have ⟨r ∈ ⟦ a ⟧TESL⟩ .
  ultimately show ?case using TESL_interpretation_image by simp
qed
end
```



# Bibliography

- [1] F. Boulanger, C. Jacquet, C. Hardebolle, and I. Prodan. TESL: a language for reconciling heterogeneous execution traces. In *Twelfth ACM/IEEE International Conference on Formal Methods and Models for Codesign (MEMOCODE 2014)*, pages 114–123, Lausanne, Switzerland, Oct 2014.
- [2] H. Nguyen Van, T. Balabonski, F. Boulanger, C. Keller, B. Valiron, and B. Wolff. A symbolic operational semantics for TESL with an application to heterogeneous system testing. In *Formal Modeling and Analysis of Timed Systems, 15th International Conference FORMATS 2017*, volume 10419 of *LNCS*. Springer, Sep 2017.