

Bachelor's Thesis

**Design, Simulation, and Evaluation of a
Load Balancing Algorithm for
Peer-to-Peer-Networks based on
Push-Pull Sum and
Deal-Agreement-Based Algorithms**

Emre Bayazıtöğlü

Examiner: Prof. Dr. Christian Schindelhauer

Advisers: Saptadi Nugroho

University of Freiburg

Faculty of Engineering

Department of Computer Science

Chair of Computer Networks and Telematics

January 25th, 2025

Writing Period

18.12.2024 – 01.03.2025

Examiner

Prof. Dr. Christian Schindelhauer

Advisers

Saptadi Nugroho

Declaration

I hereby declare that I am the sole author and composer of my thesis and that no other sources or learning aids, other than those listed, have been used. Furthermore, I declare that I have acknowledged the work of others by providing detailed references of said work.

I hereby also declare that my Thesis has not been prepared for another examination or assignment, either wholly or excerpts thereof.

Place, Date

Signature

Abstract

The Push-Pull Sum protocol, as introduced in [1], combines the Push-Sum [2] and Pull-Sum protocols. The Push-Sum protocol, proposed by Kempe et al., is a load balancing algorithm where each node randomly selects a neighbor and transfers half of its current sum and weight to that neighbor. Like the Push-Sum, the Push-Pull Sum protocol is also a randomized load balancing algorithm. These protocols are used to balance loads in peer-to-peer networks, modeled as undirected graphs. In these networks, nodes exchange loads with their neighbors in order to reach a balanced network state. The Single-Proposal Deal-Agreement-Based load balancing algorithm as proposed in [3], incorporates a Deal-Agreement into the load transfer to achieve only fair load transfers between two nodes.

In this thesis, we introduce and implement a variation of the Push-Pull Sum protocol using principles of the Deal-Agreement-Based protocol and adaptive thresholding, designed to add or modify certain properties of the original Push-Pull Sum protocol. For the newly introduced load balancing approach, we provide the pseudocode, implement the algorithm in a peer-to-peer simulation tool, and analyze the simulation outcomes for different topologies. The aim is to find a compromise solution including overall good performance in different topologies.

The performance of this variations is evaluated using the mean squared error (MSE) reduction over time as a metric for convergence to the ground truth. The results are presented through log-log and log-linear graphs, which allow a comparison of the convergence rates and stability in different scenarios. The slope of the MSE

curves reflects how efficiently the protocols distribute the load across the network. In addition to evaluating the efficiency, this thesis also analyzes potential drawbacks of each variation, such as increased communication overhead or slower convergence in certain scenarios. The data is fitted into different models to get an insight into the rate of convergence.

The findings suggest that while the modification provide improvements in specific aspects—such as faster convergence in some scenarios—others highlight trade-offs between performance and reliability. **(TODO: Some more information about the outcomes.)**

Contents

1	Introduction	1
1.1	Preliminaries	1
1.2	Motivation	2
1.3	Related Work	3
1.4	Hypothesis	4
1.5	Contribution	4
2	Problem Overview	5
2.1	Setting	5
2.2	Approach	6
3	Algorithms	7
3.1	Classic Push-Pull Sum Protocol	7
3.1.1	Example	9
3.2	Contiunous Single-Proposal Deal-Agreement-Based Protocol	9
3.2.1	Example	11
3.3	Adaptive Threshold Push-Pull Sum Protocol	11
3.3.1	Example	11
3.3.2	Aspired Outcome	11
4	Topologies	13
4.1	Complete Graph	13
4.2	Torus Grid Graph	14

4.3	Ring Graph	14
4.4	Star Graph	14
4.5	Lollipop Graph	15
4.6	Ring of Cliques	15
4.7	Expected Outcome	16
5	Implementation	19
5.1	Technology Stack	19
5.1.1	Programming Languages	19
5.1.2	Simulation Framework	19
5.2	Implementation Details	19
5.3	Simulation Approach	19
6	Simulation Outcomes	21
6.1	Complete Graph	21
6.2	Star Graph	21
6.3	Ring Graph	21
6.4	Torus Grid Graph	21
6.5	Ring of Cliques	21
6.6	Lollipop Graph	21
7	Conclusion	23
8	Acknowledgments	25
9	Appendix	27
	Bibliography	31

List of Figures

List of Tables

List of Algorithms

1	Push-Pull Sum protocol	8
2	Continuous Single-Proposal Deal-Agreement-Based protocol	10
3	Adaptive Threshold Push-Pull Sum protocol	11

1 Introduction

Peer-to-peer (P2P) networks are decentralized networks of computers, which are also referred to as nodes or participants. The computers directly interact with each other. Each of the computers is assigned a non-negative load. Loads represent various computational tasks such as, CPU usage, memory utilization, or internet traffic. The main objective when applying load balancing algorithms is to balance the state of the network, meaning that each node has the average load of the network. This objective is achieved by combating over- and underloading through load transfers and effective scheduling. Heavily overloaded nodes may fail to complete the assigned tasks due to overheating. This risk can be avoided by transferring loads to underloaded nodes. In times when clouds are becoming increasingly popular for data storage, synchronization and computing tasks etc., efficient load balancing in networks is crucial. In that sense, load balancing enhances coordination in distributed systems.

1.1 Preliminaries

A graph G is composed of two sets. The set $V := \{v_0, v_1, \dots, v_{n-1}\}$ called vertices and the set $E := \{e_1, e_2, \dots, e_{n-1}\}$ which contains the edges. A graph $G := (V, E)$ may contain only one vertex and zero edges. The number of vertices $|V|$ is often called the order of G . A node and a edge are incident, if the node is an endpoint of the edge. The degree of a node is the number of incident edges. If a edge connects two vertices, these vertices are *adjacent* to each other, or also referred to as *neighboring*

vertices. A loop is an edge with equal endpoints. Multiple edges are edges with same pair of endpoints. A simple graph has no loops, nor multiple edges. A clique is a set of pairwise adjacent vertices. A path is a simple graph whose vertices can be ordered such that two vertices are adjacent, if and only if they are consecutive in the list. A graph is connected if each pair of vertices in the graph G belongs to a path. A graph is classified as bipartite graph, if the set of graph edges is the union of two disjoint independent sets. If G has a path from node u to node v , then the distance from u to v , $d_G(u, v)$ is the shortest length from a u, v -path. The diameter of a graph $\text{diam}G := \max_{u, v \in V} d_G(u, v)$ [4].

(TODO: Make sure that all these information are taken by the slides of Graph theory by schindelbauer.)

1.2 Motivation

The motivation for this thesis stems from the observed performance discrepancies between the Single-Proposal Deal-Agreement-Based protocol proposed by Yefim Dinitz, Shlomi Dolev and Manish Kumar [3] and the Push-Pull Sum Protocol described in the paper by Saptadi Nugroho, Alexander Weinmann and Christian Schindelbauer [1] across different network topologies. The observations were gathered in a the student project with the title "Comparative Analysis of Load Balancing Algorithms in General Graphs" [5]. Judging from the simulations conducted in the student project, the Push-Pull Sum Protocol seems to perform better in reducing the mean squared error for the complete graph and the star graph compared to the Deal-Agreement-Based algorithm performing better in reducing the mean squared error per round for the torus grid graph and the ring graph. The simulations were conducted for different network sizes. The network size also played an role in faster convergence.

To address this, the proposed research introduces a novel algorithm, the Adaptive

Threshold Push-Pull Sum algorithm that leverages the strengths of both protocols, creating a Trade-off to mitigate their individual weaknesses. The newly introduced algorithm uses the mechanic of adaptive thresholding, in order to prevent load transfers with low effect in error reduction, since load transfers are pricy operations. By adapting to the structural characteristics of the investigated networks, this new solution aims to achieve robust performance across a wide range of scenarios, bridging the gap between the Deal-Agreement-Based algorithm and the Push-Pull Sum algorithm.

1.3 Related Work

Nugroho et al.[1] proposed the Push-Pull Sum algorithm, which essentially is a composition of two algorithms: the push algorithm proposed by David Kempe, Alin Dobra and Johannes Gehrke [2] and the Pull-Sum algorithm. The Push and the Pull mechanics are directly adopted from the Push-Pull Sum algorithm. Nugroho et al. used the mean squared error as a metric to evaluate the performance of their algorithm. We will follow an similar approach. Nugroho et al. conducted their experiments in static general graphs, which is also the case for this research. Dinitz et al. [3] suggested two versions of the Single-Proposal Deal-Agreement-Based Protocol two versions of a Multi-Neighbor Load Balancing Algorithm, a round robin approach and a Self-Stabilizing load balancing algorithm. However the only comparable algorithm with ours are the Single-Proposal Deal-Agreement-Based protocols, from which there exist two variations. One for the continuous setting and one for the discrete setting. The main difference between these two is that in the continuous setting any load may be transferred over the edges and in the discrete setting all load transfers must contain integers. For Multi-Neighbor load balancing the nodes may transfer loads to several neighbors in one round. This is only the case for the pull actions where one node responds to every calling node by sending loads back.

The Self-Stabilizing and the round robin approach are asynchronous algorithms and so are not comparable to our synchronous algorithm.

1.4 Hypothesis

The novel hybrid load-balancing algorithm, which integrates key features of the Deal-Agreement-Based Protocol and the Push-Pull Sum Protocol, will demonstrate performance that is intermediate between the two in terms of mean squared error (MSE) reduction across six distinct network topologies. Specifically, it is expected to perform better than the Deal-Agreement-Based Protocol in high-degree networks and perform better than the Push-Pull Sum Protocol in low-degree networks, achieving a balance that improves overall adaptability and efficiency compared to the both.

This hypothesis will be tested through comparative analysis of the MSE for six distinct topologies, demonstrating the algorithm's robustness and scalability across network environments. Model fitting is applied as a analysis technique to see the trend of the data and be able to make statements regarding the convergence rate.

1.5 Contribution

This study introduces a novel load balancing algorithm that combines the strengths of two established approaches randomized load balancing and deal agreement-based balancing while integrating an adaptive threshold mechanism to enhance performance by adapting to the current conditions. The load balancing algorithm uses the push and pull mechanics for convergence to a balanced state.

2 Problem Overview

We consider an undirected general graph $G_r = (V, E_r \subseteq V \times V)$, where V denotes the set of vertices (nodes) and E_t denotes the set of edges at each round r . A load transfer between two nodes u and v may happen, if the two nodes are connected by an edge.

2.1 Setting

The Peer-to-peer network is modeled as a static general graph, meaning that the set of edges may not change during the application of the load balancing algorithms. The main objective is to balance the state of the network. This objective will be achieved with local algorithms, so that each node only collects information of nodes in their direct neighborhood. While the Deal-Agreement-Based approach is solving the load balancing problem by determinism, the Push-Pull Sum protocol and the Adaptive Threshold Push-Pull Sum protocol use elements of randomness, to spread loads more evenly. The nodes for the Push-Pull Sum protocol are provided with the initial sum $s_{i,0}$ and weight $w_{i,0}$ values and list of neighbors as initial information. The Deal-Agreement-Based protocols nodes are provided with initial node values and a list of neighbors. The initial weight values for each node i $w_{i,0} = 1$. The sum of all weights $\sum_i w_i, r$ at any round r is equal to the network size n and the sum $s_{i,0}$ is equal to the data input [1]. The setting is a continuous setting, where data transfer over the edges may contain any amount not just integers. We assume an

synchronous message delivery, where the time of message delivery is constant e.g. $O(1)$ time. Eventhough it is possible to make the asynchronous model synchronous by simply enlarging the time unit, we stick with the synchronous model, where each round takes $O(1)$ time.

2.2 Approach

This research contains of three steps, the design of a load balancing algorithm composed of elements of two established load balancing algorithms, the simulation step to test the ability to balance the state of the network for distinct topologies, and a comparative analysis step, where the simulation outcomes are evaluated, using methods from statistics. In the previous research "Comparative Analysis of Load Balancing Algorithms in General Graphs" [5], the strengths and weaknesses of two distinct load balancing algorithms were determined, by simulating them in different topologies for different network sizes to test the scalability and adaptability of the algorithms to different situations. The design of a novel adaptive threshold load balancing algorithm is based on this knowledge. Simulation outcomes for 30 distinct experiments for further statistical significance, since we operate with randomized algorithms, are gathered and finally evaluated using model fitting to determine the trend of the algorithms regarding mean squared error reduction, and slopes are calculated per round to see the consistency in mean squared error reduction. The results are presented in comprehensive plots, with ellaboration on why the plots look like they do.

3 Algorithms

In the following the three load balancing algorithms under test are presented. Firstly, the classic Push-Pull Sum algorithm and the Continuous Single-Proposal Deal-Agreement-Based Algorithm are introduced. The novel algorithm that is proposed in this paper, the Adaptive Threshold Push-Pull Sum algorithm is then introduced, and it is depicted how the algorithm is composed of the other two algorithms, and why the protocol is composed like that. For all algorithms the pseudo-code and a description of how the algorithms work is presented. Furthermore, examples are provided to enhance the understanding of how the algorithms balance load. For the Adaptive Threshold Push-Pull Sum Protocol additionally the aspired outcome is presented.

3.1 Classic Push-Pull Sum Protocol

The Push-Pull Sum algorithm as proposed in [1] requires each node to have sum $s_{i,r}$ and weight $w_{i,r}$ values as information. The initial weight $w_{i,0}$ for each node is equal to 1. The sum of all weights is equal to the network size N . The sum of $s_{i,0}$ is equal to whatever the required input $x_i \in \mathbb{R}_0^+$ is, in the paper the values for the sums are uniformly distributed values between 0 and 100 [1]. The pseudo code is to be found in figure 3. The Push-Pull Sum algorithm is composed of three different procedures, namely the *RequestData* procedure, the *ResponseData* procedure and the *Aggregate* procedure. In every round r the *Aggregate* procedure is called, except for the first

round, since there is no information to be aggregated. In this procedure, every node gathers all incoming messages $M_{node,r}$ sent by other nodes $\{(s_m, w_m)\}$ in the previous round $r - 1$, requesting data. Also, nodes update their sum values which essentially is $\sum_{m \in M_{node,r}} s_m$ and weight values $\sum_{m \in M_{node,r}} w_m$. And finally these values are form the respective load values by dividing sum by weight. Following that, each node calls the *RequestData* procedure. In this procedure, each node chooses a random neighbor node and sends half of its sum $\frac{s_{node,r}}{2}$ and half of its weight $\frac{w_{node,r}}{2}$ to the chosen node and itself. This is the push mechanism. The pull mechanism is described in the *ResponseData* procedure. Here, each node gathers the incoming requests per round r in a set $R_{node,r}$. Then, each node replies to each requesting node (including itself) with the half of its sum value divided by the number of incoming requests, so $\frac{\frac{s_{node,r}}{2}}{|R_{node,r}|}$.

Algorithm 1 Push-Pull Sum protocol

```

1: procedure REQUESTDATA
2:   Chose a random neighbor node  $v$ 
3:   Send  $(\frac{s_{u,t}}{2}, \frac{w_{u,t}}{2})$  to the chosen node  $v$  and the node  $u$  itself
4: end procedure
5: procedure RESPONSEDATA
6:    $R_{u,t} \leftarrow$  Set of the nodes calling  $u$  at a round  $t$ 
7:   for all  $i \in R_{u,t}$  do
8:     Reply to  $i$  with  $(\frac{\frac{s_{u,t}}{2}}{|R_{u,t}|}, \frac{\frac{w_{u,t}}{2}}{|R_{u,t}|})$ 
9:   end for
10: end procedure
11: procedure AGGREGATE
12:    $M_{u,t} \leftarrow \{(s_m, w_m)\}$  messages sent to  $u$  at a round  $t - 1$ 
13:    $s_{u,t} \leftarrow \sum_{m \in M_{u,t}} s_m, w_{u,t} \leftarrow \sum_{m \in M_{u,t}} w_m$ 
14:    $f_{avg} \leftarrow \frac{s_{u,t}}{w_{u,t}}$ 
15: end procedure

```

The Push-Pull Sum algorithm has the mass-conservation property [1]. This property ensures that the values will converge to the same value but not the correct aggregate of the ground truth. They converge to the true mean. The setting in that paper is similar to ours. While they only inspect a complete graph with 10^4 nodes, we have network sizes of 2^{10} nodes and more topologies under test. 50 experiments each

conducted for 30 rounds were performed. The paper showed that the Push-Pull Sum protocol decreases the expected potential Φ_r exponentially. The potential function is defined as $\Phi_t = \sum_{i,j} (v_{i,j,r} - \frac{w_{i,r}}{n})^2$. The $v_{i,j,r}$ component stores the fractional value of node j 's contribution at round r . The conditional expectation of $\Phi_r + 1$ for the Push-Pull Sum protocol is $\mathbb{E}[\Phi_r + 1 | \Phi_r = \phi] = (\frac{2e-1}{4e} - \frac{1}{4n})\phi$ [1].

3.1.1 Example

3.2 Continuous Single-Proposal Deal-Agreement-Based Protocol

The Continuous Single-Proposal Algorithm Deal-Agreement-Based algorithm proposed by [3], is unlike the Push-Pull Sum protocol not an diffusion-based load balancing algorithm. The goal of load balancing is achieved based on deterministic deal-agreements, where one node proposes node to one neighboring node and the neighboring node either accepts transfer proposal in either full or partialy. Dinitz et al. algorithm is a anytime algorithm, as they never the worsen the state of the network during execution. They can be stopped at *any time* of the execution. They studied the algorithm in a dynamic setting, which means that the graph may experience changes between rounds. Furthermore, the algorithm is a localized one, where the nodes only work with the information regarding the load state of themselves and their neighbors load state. Each node has a set of neighboring nodes and their including the node's initial load itself as initial information. The algorithm is divided into three phases. There is the *proposal*, *deal* and the *summary*-phase. In the *proposal*-phase each node u contacts the minimal loaded neighbor v and sends a proposal to that neighbor, if the neighbor is less loaded. The proposal is of value $(\frac{load_r(u)-load_r(v)}{2})$, which is labeled as a *fair* proposal. Since the load transfer is fair, the resulting load of u is not lower than that of v . Following that, the nodes enter the *deal*-phase. In this phase nodes evaluate the deals proposed to them. A node accepts the deal

of the node that proposes the maximal load transfer. The actual transfer happens and the load values are being updated. Finally, in the *summary*-phase each node informs their neighbors regarding their updated load values. [3] The analysis in

Algorithm 2 Continuous Single-Proposal Deal-Agreement-Based protocol

Input: An undirected graph $G = (V, E, load)$

Output: A load state with discrepancy at most ϵ on G

```

1: for  $r = 1$  and on do
2:   for every node  $u$  do
3:     Find a neighbor,  $v$ , with the minimal load
4:     if  $load_r(u) - load_r(v) > 0$  then
5:        $u$  sends to  $v$  a transfer proposal of value  $(load_r(u) - load_r(v))/2$ 
6:     end if
7:   end for
8:   for every node  $u$  do
9:     if there is at least one transfer proposal to  $u$  then
10:      Find a neighbor,  $w$ , proposing to  $u$  the maximal transfer
11:      Node  $u$  makes a deal: informs node  $w$  on accepting its proposal
12:      The actual transfer from  $w$  to  $u$  is executed
13:    end if
14:  end for
15:  for every node  $u$  do
16:    Node  $u$  sends the updated value of its load to its neighbors
17:  end for
18: end for

```

this paper is based on a potential function. Dinitz et al. defines potential for a node u as $p(u) = (load(u) - L_{avg})^2$ where L_{avg} is the current load average in the network. The potential for the Graph $p(G)$ is defined as $p(G) = \sum_{u \in V} p(u)$, which essentially is the sum of all potential of each node in the graph G . Any fair load transfer of load l decreases the potential of the graph by at least $2 * l^2$. And as a result of any round r of the Continuous Single-Proposal Deal-Agreement-Based Protocol, the graph potential decreases by at least $\frac{K^2}{2D_r}$ where K is the initial discrepancy and D is a bound for the graph diameter. [3]

3.2.1 Example

(TODO: See section 1.1 of Dinitz paper to describe to methods of load balancing fot the DAB.)

3.3 Adaptive Threshold Push-Pull Sum Protocol

Algorithm 3 Adaptive Threshold Push-Pull Sum protocol

```

1: procedure CALCULATETHRESHOLDS
2:    $\theta \leftarrow k * \sqrt{MSE_{t-1}}$ 
3: end procedure
4: procedure CHECKTRESHOLDREQUESTDATA
5:    $RN \leftarrow$  choose  $\lceil \log_2(|neighborhood(u)|) \rceil$  random neighbor
6:   for every node  $v_i \in RN$  do
7:      $\Delta_{u,v_i} \leftarrow |load(u) - load(v_i)|$ 
8:     if  $\Delta_{u,v} > \theta$  then
9:       Send  $(\frac{s_{u,t}}{2}, \frac{w_{u,t}}{2})$  to first node v fulfilling condition and the node  $u$  itself
10:    end if
11:  end for
12: end procedure
13: procedure RESPONSEDATA
14:    $R_{u,t} \leftarrow$  Set of the nodes calling  $u$  at a round  $t$ 
15:   for all  $i \in R_{u,t}$  do
16:     Reply to  $i$  with  $(\frac{\frac{s_{u,t}}{2}}{|R_{u,t}|}, \frac{\frac{w_{u,t}}{2}}{|R_{u,t}|})$ 
17:   end for
18: end procedure
19: procedure AGGREGATE
20:    $M_{u,t} \leftarrow \{(s_m, w_m)\}$  messages sent to  $u$  at a round  $t - 1$ 
21:    $s_{u,t} \leftarrow \sum_{m \in M_{u,t}} s_m, w_{u,t} \leftarrow \sum_{m \in M_{u,t}} w_m$ 
22:    $load(u) \leftarrow \frac{s_{u,t}}{w_{u,t}}$ 
23: end procedure

```

3.3.1 Example

3.3.2 Aspired Outcome

4 Topologies

The simulations were conducted for six distinct network topologies. Each network has 2^{10} (1024) nodes. The behaviour of the algorithms in these different topologies is observed, since each topology has different characteristics, different performances exploiting the specials of the topologies are expected. The topologies contain the *complete graph*, *Torus Grid Graph*, *Ring Graph*, *Star Graph*, *Lollipop Graph* and *Ring of Cliques*. In the following the topologies including there characteristics are presented.

(TODO: introduce and check the abbr. for each graph: complete graph: K_n and so on and verify new edge size and so on)

4.1 Complete Graph

The complete graph K_n as illustrated in figure ?? is a graph where each pair of distinct nodes is connected by an edge. The complete graph or also refered to as fully-connected graph has n nodes and $\frac{n \times (n-1)}{2}$ edges. The complete graph is a regular graph, where each node has a degree of $n - 1$. As it contains the maximum possible number of edges for a given set of nodes (the maximum number of edges per node for undirected graphs is n , when self-loops are allowed), the complete graph is considered a dense graph [4]. The diameter of a complete graph is 1, as each node is directly connected to every other node. Since node has same degree and connectivity, algorithms can treat all nodes uniformly.

(TODO: images auskommentieren und mehr zu den besonderen Charakteristiken der einzelnen graphentypen schreiben)

4.2 Torus Grid Graph

The two-dimensional torus grid graph or also referred to as $m \times n$ -torus graph is a two-dimensional mesh with wrap around edges as depicted in figure ?? [6]. m denotes the height and n denotes the width of the grid. The torus grid graph has $2 \times m \times n$ edges and $m \times n$ nodes and is a regular graph, where each node has a degree of 4. The diameter of a torus grid graph is $\frac{\min(m,n)}{2}$. Tori are scalable, as the number of connections per node is constant, regardless of the graph size. In the previous research "Comparative Analysis of Load Balancing Algorithms in General Graphs" [5], we saw this as the simulation results did not vary over different network sizes.

4.3 Ring Graph

The ring graph is a regular graph, where each node has a degree of two, forming a cycle. The ring graph can be constructed by building a path graph which is closed, meaning that the first and the last nodes of the path graph are connected by an edge as depicted in figure ?. The graph consists of n nodes and n edges. The diameter of a ring is $\lfloor \frac{n}{2} \rfloor$. The uniform structure ensures no single node has an advantage, simplifying algorithm design and guaranteeing fairness in load balancing.

4.4 Star Graph

A star graph as depicted in figure ?? is a bipartite graph [?], structured like a tree graph with one internal node and k -leaves (but no internal nodes and $k + 1$ leaves

when $k \leq 1$). The internal node belongs to one of these disjoint sets, while the leaves are assigned to the other set. A star graph with n nodes has $n - 1$ edges. In this structure, every leave node has a degree of 1, meaning it is connected only to the internal node. The central node has a degree of $n - 1$. The diameter of a star graph is 2 (path from one leave through internal node to another leave). Regarding load balancing the internal node acts as a point of redistribution. This topology is particularly suitable for master-slave or client-server models where the central node delegates tasks and collects results. However, the central node may become overloaded in high-load scenarios, requiring careful design to prevent bottlenecks.

4.5 Lollipop Graph

A (k, m) -lollipop graph $(L_{k,m})$ is a graph that consists of a complete graph and a path graph as depicted in figure ???. The complete graph and the path graph are connected by a bridge node, thus a single edge. The (k, m) -Lollipop graph is composed of a complete graph with k nodes and a path size of m nodes. A lollipop graph has $k + m = n$ nodes and $\binom{k}{m} + k$ or $(\binom{k}{2} + (n - k - 1))$??? edges [?].

4.6 Ring of Cliques

The $(k \times m)$ -ring of cliques, consists of k cliques, each containing k nodes. The cliques are connected to form a ring structure. To create the ring, one edge from each clique is removed, and the endpoints of these removed edges are connected to form a regular graph [6]. A $k \times m$ ring of cliques has $\left(k \times \left(\frac{m \times (m-1)}{2} - 1\right)\right) + k$ edges. The connectivity of the graph increases with larger clique sizes and decreases with smaller clique sizes.

4.7 Expected Outcome

(TODO: Remove these notes/reformulate them) Many load balancing algorithms perform well on 2D torus grids due to the focus on local redistribution, thanks to the wrap around edges eliminating boundary effects, ensuring balanced redistribution across entire grid.

Ring: Unlike complete or torus graphs, the sequential nature of data transfer makes it slower for loads to propagate across the entire ring. Load movement in the ring graph is sequential, making it slower and less flexible than the complete graph.

Star: For the Push-Pull mechanism the star graph is an advantage, since each push action contains a pull action. All leaves request data from the internal node, so the internal node acts here as a point of redistribution. However for the Deal-Agreement-Based protocol some mechanisms like "if condition" act as a contraproductive way of load balancing.

Lollipop: Algorithms must account for the highly connected complete graph (dense communication) and the linear path graph (sequential communication), which introduces a mixed topology challenge. The node linking the complete graph and the path graph often becomes a bottleneck since it bridges two vastly different connectivity regions. In the complete graph, load balancing is efficient due to the high connectivity, enabling rapid redistribution among nodes. Load movement in the path graph is sequential, making it slower and less flexible than the complete graph. Interesting because dense head and sparse tail. For example, diffusion-based approaches work well in the head but may require additional iterations in the tail. We saw that in "Comparative Analysis of Load Balancing algorithms in General Graphs" [5], once we changed the path size in relation to same complete graph, the DAB was faster in reducing error for the first 50 rounds. **(TODO: Do the simulations over again with different path and complete graph size and compare.)**

Ring of cliques: Within each clique, balancing is fast due to the dense connectivity. Load redistributes efficiently among the clique's nodes. Balancing between cliques depends on the single shared node linking each pair of cliques. This structure ensures sequential redistribution across the ring. The shared nodes act as gateways, controlling the flow of load between cliques. Overloading these nodes can cause bottlenecks.

5 Implementation

5.1 Technology Stack

5.1.1 Programming Languages

5.1.2 Simulation Framework

5.2 Implementation Details

5.3 Simulation Approach

6 Simulation Outcomes

6.1 Complete Graph

6.2 Star Graph

6.3 Ring Graph

6.4 Torus Grid Graph

6.5 Ring of Cliques

6.6 Lollipop Graph

7 Conclusion

8 Acknowledgments

First and foremost, I would like to thank...

- advisers
- examiner
- person1 for the dataset
- person2 for the great suggestion
- proofreaders

9 Appendix

ToDo Counters

To Dos: 7; 1, 2, 3, 4, 5, 6, 7

Parts to extend: 0;

Draft parts: 0;

Bibliography

- [1] S. Nugroho, A. Weinmann, and C. Schindelhauer, *Adding Pull to Push Sum for Approximate Data Aggregation*. Springer, 2023.
- [2] D. Kempe, A. Dobra, and J. Gehrke, “Gossip-based computation of aggregate information,” in *44th Annual IEEE Symposium on Foundations of Computer Science, 2003. Proceedings.*, pp. 482–491, 2003.
- [3] Y. Dinitz, S. Dolev, and M. Kumar, “Local deal-agreement algorithms for load balancing in dynamic general graphs,” *Theory of Computing Systems*, vol. 67, pp. 348–382, Apr 2023.
- [4] C. Schindelhauer, “Lecture notes in graph theory,” 2021.
- [5] E. Bayazitoglu, “Comparative analysis of load balancing algorithms in general graphs.” University of Freiburg, 2024.
- [6] P. Mahlmann, *Peer-to-peer networks based on random graphs*. PhD thesis, University of Paderborn, 2010. Paderborn, Univ., Diss., 2010.

