```
--BbC04v
Content-Disposition: file; filename="essayfile.txt"
Content-Type: text/plain
...contents of essayfile.txt...
--BbC04y
Content-Disposition: file; filename="imagefile.gif"
Content-Type: image/gif
Content-Transfer-Encoding: binary
...contents of imagefile.gif...
--BbC04y--
--AaB03x--
```

15.4.4 多部分范围响应

HTTP 对范围请求的响应也可以是多部分的。这样的响应中有 Content-Type: multipart/byteranges 首部和带有不同范围的多部分主体。下面是一个例子,展 示了对文档不同范围的请求产生的响应:

```
HTTP/1.0 206 Partial content
Server: Microsoft-IIS/5.0
Date: Sun, 10 Dec 2000 19:11:20 GMT
Content-Location: http://www.joes-hardware.com/gettysburg.txt
Content-Type: multipart/x-byteranges; boundary = -- [abcdefghijklmnopqrstu
vwxyz] --
Last-Modified: Sat. 09 Dec 2000 00:38:47 GMT
-- [abcdefghijklmnopqrstuvwxyz] --
Content-Type: text/plain
Content-Range: bytes 0-174/1441
Fourscore and seven years ago our fathers brought forth on this
continent a new nation, conceived in liberty and dedicated to the
proposition that all men are created equal.
-- [abcdefghijklmnopgrstuvwxyz] --
Content-Type: text/plain
Content-Range: bytes 552-761/1441
But in a larger sense, we can not dedicate, we can not consecrate,
we can not hallow this ground. The brave men, living and dead who
struggled here have consecrated it far above our poor power to add
or detract.
-- [abcdefghijklmnopqrstuvwxyz] --
Content-Type: text/plain
Content-Range: bytes 1344-1441/1441
and that government of the people, by the people, for the people shall
not perish from the earth.
-- [abcdefghijklmnopqrstuvwxyz] --
```

本章后面将详细讨论范围请求。

350