</ Location headers (Location 首部), 520 single clients (单个客户端), 456 loading (加載), serial (串行), 87 LOCK method (LOCK 方法), 433 lock refreshes (锁的刷新), 435 status codes (状态码), 436

docktoken> element (<locktoken> 元素), 434 Lock-Token headers (Lock-Token 首部), 431 logging (日志), 483 ~ 492

clockinfo> element (<lockinfo> 元素), 434

locking (锁定), 433

commonly logged fields (通常会记录的字段), 483 interpretation (解释), 484

Combined Log Format (组合日志格式), 485 log formats (日志格式), 484 ~ 492

Netscape Extended 2 Log Format (网景扩展 2 日志格式), 487 ~ 489 Netscape Extended Log Format (网景扩展日志格式), 486 Common Log Format (常见日志格式), 484

Squid Proxy Log Format (Squid 代理日志格式), 489 ~ 492 loops (web robots) [循环 (Web 机器人)], 217 privacy concerns (隐私考虑), 495

MAC (Media Access Control) addresses (媒体访问控制地址), 459 nan-in-the-middle attacks (中间人攻击), 304 nailto scheme (mailto 方案), 38 magic typing (魔法分类), 126

nanual client proxy configuration (手工客户端代理配置), 142 nax-age response headers (max-age 响应首部), 183 master origin server (主原始服务器), 420

Max-Forwards headers (Max-Forwards 首部), 155, 521

Media Access Control (MAC) addresses(媒体访问控制地址),459 media types (媒体类型), 348 MD5, 288, 291, 293, 347 MD5-sess, 291, 293

message digest algorithms (根文摘要算法), 291 ~ 294

message body (根文主体), 44

multipart (多部分), 349

message transport layer (HTTP-NG) (报文传输层), 249, 250 message/* MIME types (message/* MIME 类型), 563 message integrity protection (根文完整性保护), 299 symmetric authentication (对称认证), 298 message truncation (报文载尾), 344

CMETA HTTP-EQUIV>tag (<META HTTP-EQUIV> 标签), 187 messages (see HTTP messages) (报文, 参见 HTTP 报文) META tag directives (META 标签指令), 239

Meter headers (Meter 首部), 196, 493 meta-information (元信息), 43

extension methods (扩展方法), 58 methods (方法), 46, 48, 53 ~ 59 CONNECT, 206, 208, 336 **DELETE**, 58, 441

GET, 53

POST, 55

OPTIONS, 57, 159, 445

HEAD, 54

redirection status codes (重定向状态码), 64 PUT, 54, 444

Microsoft FrontPage (see FrontPage) (微软的 FrontPage, 参见 FrontPage) unsupported (不支持的), handling (处理), 158 TRACE, 55