

Docker – Complete Learning Index (Interview-Oriented) - Explained

1. Introduction to Docker

1.1 What is Docker

Docker is a platform that uses containerization to package applications and their dependencies into standardized units called containers. Think of it like a shipping container for software - it ensures your application runs consistently anywhere, regardless of the environment.

Real Example: Imagine you're developing a Python web app that works perfectly on your Mac but fails on your colleague's Windows machine due to different Python versions or missing libraries. Docker solves this by packaging your app with its specific Python version, libraries, and configurations into a container that runs identically on any system with Docker installed.

1.2 Why Docker was created (Problems it solves)

Before Docker, developers faced:

"It works on my machine" problem - Applications behaving differently across environments

Complex dependency management - Installing and configuring multiple versions of libraries

Resource inefficiency - VMs requiring full OS copies for each application

Slow deployment - Lengthy setup and configuration processes

Real Example: A team building a microservices architecture might need 10 different services, each with unique dependencies. Without Docker, they'd need 10 separate VM setups or complex dependency management. With Docker, each service gets its own container with exactly what it needs.

1.3 Docker vs Virtual Machines

VM Approach:

Hardware → Hypervisor → Multiple Guest OS → Applications

Each VM includes full OS (Linux/Windows kernel, libraries, etc.)

Heavy (GBs), slow to start, significant overhead

Docker Approach:

Hardware → Host OS → Docker Engine → Multiple Containers

Containers share host OS kernel

Light (MBs), fast startup, minimal overhead

Real Example: Running a simple Redis database:

VM approach: Need to install full Ubuntu + Redis = 1-2GB, takes 1-2 minutes to boot

Docker approach: `docker run redis` = 100MB, starts in seconds

1.4 Real-world use cases of Docker

Development Environments: Every developer gets identical setup

CI/CD Pipelines: Consistent testing environments

Microservices: Each service in its own container

Legacy App Migration: Containerize old apps for modern infrastructure

Batch Processing: Run data processing jobs in isolated containers

Real Example: Netflix uses Docker to run thousands of microservices. Each service (user authentication, recommendation engine, video streaming) runs in its own container, allowing independent scaling and updates.

1.5 Docker architecture overview

Docker follows a client-server architecture:

Docker Client: CLI/UI you interact with (docker run, docker build)

Docker Daemon (dockerd): Background service managing containers

Docker Registry: Storage for Docker images (Docker Hub, private registries)

Docker Objects: Images, containers, networks, volumes

Real Example: When you run `docker run nginx`:

Client sends command to Docker Daemon

Daemon checks if nginx image exists locally

If not, pulls from Docker Hub registry

Creates container from image

Starts the container

2. Core Docker Concepts

2.1 Images

A Docker image is a read-only template with instructions for creating a container. It's built in layers using a Dockerfile.

Real Example: The official nginx:alpine image contains:

Base layer: Alpine Linux (minimal Linux distribution)

Add layer: Nginx installation

Add layer: Configuration files

Add layer: Startup script

Each layer is immutable. When you modify an image, Docker adds new layers on top.

2.2 Containers

A container is a running instance of an image. It's an isolated, lightweight process with its own filesystem, networking, and isolated process tree.

Real Example:

```
bash
```

```
# Create and start a container from nginx image
```

```
docker run -d -p 8080:80 --name my-web nginx
```

This creates a container named my-web that:

Runs Nginx web server

Maps host port 8080 to container port 80

Runs in background (-d flag)

2.3 Docker Engine

The Docker Engine is the core component that runs and manages containers. It consists of:

Docker Daemon (dockerd): Server that manages Docker objects

REST API: Interface for programs to talk to daemon

Docker CLI: Command-line interface

Real Example: When Jenkins needs to build a Docker image as part of CI/CD, it uses Docker Engine's REST API to communicate with the Docker Daemon.

2.4 Docker Client

The Docker Client is what users interact with. It can be:

Docker CLI (docker command)

Docker Desktop (GUI)

Third-party tools (Portainer, Rancher)

Real Example: Developers use Docker CLI (docker build, docker push) while operations teams might use Portainer GUI for container management.

2.5 Docker Daemon

The Docker Daemon (dockerd) is a background service that:

Listens for Docker API requests

Manages Docker objects (images, containers, networks, volumes)

Can communicate with other daemons to manage Docker services

Real Example: When you have 20 containers running, the Docker Daemon monitors them, restarts failed ones (if configured), and manages resource allocation.

2.6 Docker Registry

A Docker Registry stores Docker images. It's like GitHub for Docker images.

Real Example:

Docker Hub: Public registry (like `docker pull nginx`)

Amazon ECR: AWS private registry

Google Container Registry: GCP private registry

Self-hosted: Run your own registry with Docker Registry image

2.7 Docker Hub

Docker Hub is the default public registry for Docker images. It contains:

Official Images: Verified images from software vendors (nginx, mysql, node)

Verified Publisher Images: From certified companies

Community Images: User-created images

Real Example: A company might use:

Official postgres:13 image for production database

Their custom-built myapp:latest image from their private registry

Community jc21/nginx-proxy-manager for reverse proxy

3. Docker Installation & Setup

3.1 Installing Docker on Windows

Windows has two approaches:

Docker Desktop (Recommended):

Requires Windows 10/11 Pro, Enterprise, or Education (for WSL 2 backend)

Uses WSL 2 (Windows Subsystem for Linux) or Hyper-V

Includes Docker CLI, Docker Compose, Kubernetes

Docker Toolbox (Legacy):

For older Windows versions or Home edition

Uses VirtualBox to run Linux VM

Real Example: A Windows developer installs Docker Desktop:

Downloads from docker.com

Enables WSL 2 feature in Windows

Installs Docker Desktop with WSL 2 backend

Can now run Linux containers natively through WSL 2

3.2 Installing Docker on Linux

Ubuntu Example:

```
bash
```

```
# Update package index
```

```
sudo apt-get update
```

```
# Install prerequisites
```

```
sudo apt-get install apt-transport-https ca-certificates curl software-properties-common
```

```
# Add Docker's GPG key
```

```
curl -fsSL https://download.docker.com/linux/ubuntu/gpg | sudo apt-key add -
```

```
# Add Docker repository
```

```
sudo add-apt-repository "deb [arch=amd64] https://download.docker.com/linux/ubuntu  
$(lsb_release -cs) stable"
```

```
# Install Docker
```

```
sudo apt-get update
```

```
sudo apt-get install docker-ce docker-ce-cli containerd.io
```

Add user to docker group (to run without sudo)

`sudo usermod -aG docker $USER`

Real Example: A cloud server (AWS EC2 Ubuntu instance) needs Docker for running containers. The admin runs these commands to install Docker Engine.

3.3 Installing Docker on Mac

Docker Desktop for Mac:

Uses a lightweight Linux VM (hyperkit) to run containers

Native macOS integration

Includes Docker CLI, Docker Compose, Kubernetes

Real Example: A macOS developer:

Downloads Docker.dmg from docker.com

Drags Docker to Applications folder

Runs Docker Desktop

Can now use docker commands in Terminal

3.4 Verifying Docker Installation

After installation, verify everything works:

```
bash
```

```
# Check Docker version
```

```
docker --version
```

```
# Output: Docker version 20.10.7, build f0df350
```

```
# Run test container
```

```
docker run hello-world
```

```
# Check Docker info
```

```
docker info
```

```
# List running containers
```

```
docker ps
```

Real Example: After installing Docker, you run `docker run hello-world`. This pulls a small test image and runs it to confirm Docker is working correctly.

3.5 Docker Desktop Overview

Docker Desktop includes:

Docker Engine: For running containers

Docker CLI: Command-line interface

Docker Compose: For multi-container apps

Kubernetes: Local Kubernetes cluster

Dashboard: GUI for managing containers

Extensions: Additional tools

Real Example: A developer uses Docker Desktop to:

Start/stop containers via GUI

View container logs and stats

Manage images and volumes

Switch between Linux and Windows containers

Enable Kubernetes for local development

(I'll continue with the remaining sections in subsequent responses to maintain readability.
Would you like me to proceed with Section 4: Docker Basic Commands next?)

yes

4. Docker Basic Commands (Must for Interviews)

4.1 docker --version

Checks Docker installation version and confirms CLI is working.

Real Example:

```
bash
```

```
$ docker --version
```

```
Docker version 24.0.7, build afdd53b
```

Interview Insight: Shows Docker client version. Useful for troubleshooting compatibility issues. Always mention that server (daemon) version might differ (check with `docker info`).

4.2 docker pull

Downloads an image from a registry (default: Docker Hub) to local system.

Real Example:

```
bash
```

```
# Pull latest nginx image
```

```
docker pull nginx
```

```
# Pull specific version
```

```
docker pull nginx:1.21-alpine
```

```
# Pull from private registry
```

```
docker pull myregistry.com/myapp:v2.0
```

Real Scenario: Before deploying a new version in production, you pull it first to test locally:

```
bash
```

```
docker pull mycompany/api-service:v1.5
```

```
docker run mycompany/api-service:v1.5
```

4.3 docker images

Lists all Docker images stored locally.

Real Example:

```
bash
```

```
$ docker images
```

REPOSITORY	TAG	IMAGE ID	CREATED	SIZE
nginx	latest	6efc10a0510f	2 weeks ago	142MB
redis	alpine	2e2f252f3c88	3 weeks ago	32.3MB
ubuntu	20.04	d5447fc01ae6	2 months ago	72.8MB

Useful flags:

```
bash
```

```
# Show all images (including intermediate)
```

```
docker images -a
```

```
# Show only image IDs
```

```
docker images -q
```

```
# Filter images
```

```
docker images --filter "dangling=true"
```

4.4 docker run

The most important command. Creates and starts a container from an image.

Real Examples:

bash

Basic run

docker run nginx

Run in detached mode (background)

docker run -d --name web nginx

Map ports (host:container)

docker run -d -p 8080:80 nginx

Mount volume

docker run -d -v /data:/app/data mysql

Set environment variables

docker run -e "DATABASE_URL=localhost" -e "DEBUG=true" myapp

Interactive container with shell

docker run -it ubuntu bash

Limit resources

docker run --memory="512m" --cpus="1.5" myapp

Interview Scenario: "Run a PostgreSQL container with persistence and custom password"

```
bash
```

```
docker run -d \
```

```
--name postgres-db \
```

```
-e POSTGRES_PASSWORD=mysecretpassword \
```

```
-v pgdata:/var/lib/postgresql/data \
```

```
-p 5432:5432 \
```

```
postgres:13
```

4.5 docker ps

Lists running containers.

Real Example:

```
bash
```

```
$ docker ps
```

CONTAINER ID	IMAGE	COMMAND	CREATED	STATUS	PORTS	NAMES
a1b2c3d4e5f6	nginx	"/docker-entrypoint...."	2 hours ago	Up 2 hours	0.0.0.0:8080->80/tcp	webserver

Common flags:

```
bash
```

```
# Show all containers (running + stopped)
```

```
docker ps -a
```

```
# Show last created container
```

```
docker ps -l
```


Show only container IDs

```
docker ps -q
```

Format output

```
docker ps --format "table {{.ID}}\t{{.Names}}\t{{.Status}}"
```

4.6 docker ps -a

Shows all containers including stopped ones.

Real Example:

```
bash
```

```
$ docker ps -a
```

CONTAINER ID	IMAGE	COMMAND	CREATED	STATUS	PORTS	NAMES
a1b2c3d4e5f6	nginx	"nginx -g ..."	2 hours ago	Up 2 hours	80/tcp	webserver
b2c3d4e5f6g7	redis	"redis-ser..."	5 hours ago	Exited (0) 2 hours ago		cache
c3d4e5f6g7h8	ubuntu	"bash"	1 day ago	Exited (137) 1 day ago		test-container

Interview Tip: Useful for debugging why containers stopped (check Exit codes).

4.7 docker stop

Gracefully stops a running container (sends SIGTERM, then SIGKILL after timeout).

Real Example:

```
bash
```

Stop by container name

```
docker stop webserver
```

Stop by container ID

```
docker stop a1b2c3d4e5f6
```

Stop multiple containers

```
docker stop container1 container2
```

Stop with timeout (default 10s)

```
docker stop -t 30 webserver # Wait 30 seconds before force kill
```

Important: Always prefer docker stop over docker kill unless container is unresponsive.

4.8 docker start

Starts a stopped container (preserves its configuration and data).

Real Example:

```
bash
```

Start stopped container

```
docker start webserver
```

Start and attach to output

```
docker start -a webserver
```

Start in interactive mode

```
docker start -i mycontainer
```

Interview Scenario: After fixing a configuration issue in a stopped container:

```
bash
```

```
# Container was stopped due to config error
```

```
$ docker ps -a | grep exited
```

```
b2c3d4e5f6g7 myapp "node app.js" 1 hour ago Exited (1)
```

```
# Fix the config, then restart
```

```
docker start b2c3d4e5f6g7
```

```
4.9 docker restart
```

```
Restarts a container (stop + start).
```

Real Example:

```
bash
```

```
# Restart by name
```

```
docker restart webserver
```

```
# Restart with new configuration
```

```
docker update --memory="1g" webserver && docker restart webserver
```

Use Case: Applying new environment variables:

```
bash
```

```
docker run -d -e "MODE=dev" --name app myapp
```

```
# Later need to change to production
```

```
docker stop app
```

```
docker rm app
```

```
docker run -d -e "MODE=prod" --name app myapp
```

```
# OR using restart with update (Docker 1.13+)
```

```
docker update --env-add "MODE=prod" app
```

```
docker restart app
```

4.10 docker rm

Removes stopped containers.

Real Example:

```
bash
```

```
# Remove by name
```

```
docker rm old-container
```

```
# Remove by ID
```

```
docker rm a1b2c3d4e5f6
```

```
# Remove multiple
```

```
docker rm container1 container2 container3
```

```
# Force remove running container
```

```
docker rm -f running-container
```

```
# Remove all stopped containers
```

```
docker container prune
```

```
# OR
```

```
docker rm $(docker ps -aq)
```

Interview Question: "Difference between docker rm and docker rmi?"

docker rm → removes containers

docker rmi → removes images

4.11 docker rmi

Removes Docker images.

Real Example:

bash

Remove image by ID

docker rmi 6efc10a0510f

Remove image by tag

docker rmi nginx:latest

Force remove (even if in use)

docker rmi -f myimage

Remove dangling images (untagged)

docker image prune

Remove all unused images

docker image prune -a

Common Patterns:

bash

Cleanup workflow

```
docker stop $(docker ps -aq)
```

```
docker rm $(docker ps -aq)
```

```
docker rmi $(docker images -q)
```

Remove specific version

```
docker rmi myapp:v1.0
```

Remove by pattern

```
docker images | grep "none" | awk '{print $3}' | xargs docker rmi
```

Interview Scenario: "You're getting 'no space left on device' error. How to clean up?"

bash

Check disk usage

```
docker system df
```

Remove unused data

```
docker system prune
```

Remove everything (more aggressive)

```
docker system prune -a
```

Specific cleanup

`docker container prune` # Remove stopped containers

`docker image prune` # Remove dangling images

`docker volume prune` # Remove unused volumes

`docker network prune` # Remove unused networks

Quick Interview Cheat Sheet for Commands:

Command	Purpose	Common Flags
<code>docker run</code>	Create+start container	<code>-d</code> , <code>-p</code> , <code>-v</code> , <code>-e</code> , <code>--name</code>
<code>docker ps</code>	List running containers	<code>-a</code> (all), <code>-q</code> (quiet)
<code>docker stop</code>	Stop container gracefully	<code>-t</code> (timeout)
<code>docker start</code>	Start stopped container	<code>-a</code> (attach), <code>-i</code> (interactive)
<code>docker rm</code>	Remove container	<code>-f</code> (force)
<code>docker rmi</code>	Remove image	<code>-f</code> (force)
<code>docker exec</code>	Run command in running container	<code>-it</code> (interactive)
<code>docker logs</code>	View container logs	<code>-f</code> (follow), <code>--tail</code>
<code>docker build</code>	Build image from Dockerfile	<code>-t</code> (tag)

Pro Tip for Interviews: Always mention:

Container lifecycle: `run` → `stop` → `start/restart` → `rm`

Image vs Container: Image is template, Container is instance

Use `docker --help` for command details

(Would you like me to continue with Section 5: Docker Image Deep Dive next?)

give the answer for all Section dont ask

Docker – Complete Learning Guide (Interview-Focused)

5. Docker Image Deep Dive

5.1 What is a Docker Image

A Docker image is a read-only template containing application code, dependencies, libraries, and configuration files. Images are built in layers using a Dockerfile.

Real Example: Building a Python web app image:

```
dockerfile
```

```
FROM python:3.9-slim
```

```
COPY requirements.txt .
```

```
RUN pip install -r requirements.txt
```

```
COPY app.py .
```

```
CMD ["python", "app.py"]
```

When built: `docker build -t myapp:v1 .`

Creates immutable layers for each instruction

Result is a portable image that runs anywhere

5.2 Image Layers & Union File System

Docker uses a Union File System (Overlay2) to combine multiple read-only layers into a single filesystem.

Real Example: Analyzing an nginx image:


```
bash
```

```
# Inspect image layers
```

```
docker history nginx:alpine
```

```
# Output shows:
```

```
# Layer 1: Alpine base OS (5MB)
```

```
# Layer 2: Nginx installation files (3MB)
```

```
# Layer 3: Configuration files (few KB)
```

```
# Layer 4: Entrypoint script (few bytes)
```

Key Concept: When you run `docker run`, Docker adds a thin writable layer on top of read-only layers for runtime changes.

5.3 Base Images

Base images are the foundation layer, usually a minimal OS.

Common Base Images:

```
dockerfile
```

```
# Ubuntu (full-featured)
```

```
FROM ubuntu:20.04
```

```
# Alpine (lightweight, security-focused)
```

```
FROM alpine:3.14
```

```
# Distroless (minimal, no shell)
```

```
FROM gcr.io/distroless/base
```

Scratch (empty)

FROM scratch

Real Example: Choosing base images:

Production: alpine (smaller, fewer vulnerabilities)

Development: ubuntu (easier debugging with tools)

Go apps: scratch (extremely small)

5.4 Creating Custom Images

Build custom images using docker build:

Real Example - Node.js app:

dockerfile

FROM node:16-alpine

WORKDIR /app

COPY package*.json ./

RUN npm ci --only=production

COPY src/ ./src/

EXPOSE 3000

USER node

CMD ["node", "src/index.js"]

Build: docker build -t mynodeapp:v2 .

5.5 Tagging & Versioning Images

Tagging provides identity and versioning to images.

Real Examples:

bash

Tag during build

`docker build -t myapp:1.0 -t myapp:latest .`

Tag existing image

`docker tag myapp:1.0 registry.company.com/myapp:prod`

Semantic versioning pattern

`docker tag app myapp:1.2.3`

`docker tag app myapp:1.2`

`docker tag app myapp:1`

`docker tag app myapp:latest`

Push tagged images

`docker push registry.company.com/myapp:1.2.3`

6. Dockerfile (Most Important for Interviews)

6.1 What is a Dockerfile

A Dockerfile is a text file with instructions to build a Docker image.

Real Example: Complete Dockerfile:

dockerfile

Start from base image

FROM python:3.9-slim

Set maintainer (deprecated but good practice)

LABEL maintainer="dev@company.com"

Set working directory

WORKDIR /app

Copy dependency file

COPY requirements.txt .

Install dependencies

RUN pip install --no-cache-dir -r requirements.txt

Copy application code

COPY . .

Expose port

EXPOSE 8000

Set environment variable

ENV PYTHONUNBUFFERED=1

Health check

HEALTHCHECK --interval=30s CMD curl -f http://localhost:8000/health || exit 1

Define entry point

CMD ["gunicorn", "--bind", "0.0.0.0:8000", "app:app"]

6.2 Common Dockerfile Instructions

FROM

Sets the base image.

dockerfile

FROM ubuntu:20.04

FROM python:3.9 AS builder # Multi-stage build

RUN

Executes commands during image build.

dockerfile

RUN apt-get update && apt-get install -y \

curl \

nginx \

&& rm -rf /var/lib/apt/lists/*

COPY vs ADD

COPY - Copies files/directories from host to image

dockerfile

COPY . /app

COPY config.json /etc/app/

ADD - Can also handle URLs and auto-extract archives

dockerfile

ADD https://example.com/file.tar.gz /tmp/

ADD app.tar.gz /app/ # Auto-extracts

Interview Tip: Prefer COPY unless you need ADD's extra features.

WORKDIR

Sets working directory for subsequent instructions.

dockerfile

WORKDIR /app

RUN pwd # Output: /app

EXPOSE

Documents which ports the container listens on.

dockerfile

EXPOSE 80 # HTTP

EXPOSE 443 # HTTPS

CMD

Provides default command when container starts.

dockerfile

CMD ["npm", "start"]

CMD ["python", "app.py"]

ENTRYPOINT

Sets the main command (cannot be overridden by docker run).

```
dockerfile
```

```
ENTRYPOINT ["python"]
```

```
CMD ["app.py"]
```

```
# docker run myapp → runs: python app.py
```

```
# docker run myapp test.py → runs: python test.py
```

```
ENV
```

Sets environment variables.

```
dockerfile
```

```
ENV NODE_ENV=production
```

```
ENV PORT=3000
```

6.3 Difference between CMD vs ENTRYPOINT

Aspect	CMD	ENTRYPOINT
Purpose	Default arguments for ENTRYPOINT	Main executable
Override	Can be overridden by docker run	Cannot be overridden (without --entrypoint)
Shell form	CMD npm start (runs in shell)	ENTRYPOINT ["executable"] (exec form)
Best for	Default parameters	Container as executable

Real Example:

```
dockerfile
```

```
# Use case 1: ENTRYPOINT as main app
```

```
FROM alpine:3.14
```

```
ENTRYPOINT ["ping"]
```

```
CMD ["localhost"]
```

```
# docker run myping → ping localhost
```

```
# docker run myping google.com → ping google.com
```

```
# Use case 2: CMD as default command
```

```
FROM node:16
```

```
CMD ["npm", "start"]
```

```
# docker run myapp → npm start
```

```
# docker run myapp bash → overrides to bash
```

6.4 Best Practices for Writing Dockerfiles

Use specific tags, not latest

```
dockerfile
```

```
FROM ubuntu:20.04 # Good
```

```
FROM ubuntu:latest # Bad
```

Combine RUN commands to reduce layers

```
dockerfile
```

```
RUN apt-get update && apt-get install -y \
```

```
    package1 \
```

```
    package2 \
```

```
    && rm -rf /var/lib/apt/lists/*
```

Use .dockerignore

```
text
```

```
node_modules/
```


.git/

*.log

Dockerfile

.env

Minimize layer count and image size

Run as non-root user

dockerfile

RUN groupadd -r appuser && useradd -r -g appuser appuser

USER appuser

Use multi-stage builds for production

dockerfile

Build stage

FROM node:16 AS builder

WORKDIR /build

COPY . .

RUN npm run build

Production stage

FROM nginx:alpine

COPY --from=builder /build/dist /usr/share/nginx/html

7. Docker Containers Deep Dive

7.1 What is a Container

A container is a running instance of an image with:

Isolated filesystem

Isolated process space

Isolated network interface

Resource limits (CPU, memory)

Real Example:

bash

Create container

```
docker run -d --name myapp --memory="512m" myimage
```


Inspect container details

```
docker inspect myapp
```

7.2 Container Lifecycle

text

Created → Running → Paused → Stopped → Removed



Commands for each state:

bash

docker create # Created state

docker start # Created → Running
docker run # Created + Started
docker pause # Running → Paused
docker unpause # Paused → Running
docker stop # Running → Stopped (graceful)
docker kill # Running → Stopped (force)
docker restart # Running → Running
docker rm # Stopped → Removed

7.3 Running Containers in Foreground/Background

Foreground Mode (default):

bash

docker run nginx # Blocks terminal

Ctrl+C stops container

Background Mode (detached):

bash

docker run -d --name web nginx

Returns container ID, runs in background

Attach to running container

docker attach web # Re-attach

docker exec -it web bash # New session

Real Use Case:

bash

Development - foreground for logs

```
docker run -p 3000:3000 node-app
```

Production - background

```
docker run -d -p 80:80 --restart unless-stopped nginx
```

7.4 Port Mapping

Maps container ports to host ports.

Real Examples:

bash

Map specific host port to container port

```
docker run -p 8080:80 nginx # host:container
```

Map to all interfaces

```
docker run -p 0.0.0.0:8080:80 nginx
```

Random host port

```
docker run -p 80 nginx # Docker assigns random port
```

Multiple ports

```
docker run -p 8080:80 -p 8443:443 nginx
```

UDP port

```
docker run -p 53:53/udp dns-server
```

Check mapped ports

`docker port container_name`

7.5 Environment Variables in Containers

Set runtime configuration.

Real Example:

bash

Single variable

`docker run -e "DATABASE_URL=postgres://user:pass@db/app" myapp`

Multiple variables

`docker run -e "NODE_ENV=production" -e "PORT=3000" myapp`

File with variables

`docker run --env-file .env myapp`

From host environment

`docker run -e "HOSTNAME" myapp` # Passes host's HOSTNAME

.env file:

text

`DB_HOST=localhost`

`DB_PORT=5432`

`DEBUG=false`

7.6 Inspecting Containers

Get detailed container information.

Real Examples:

bash

All container details (JSON)

`docker inspect container_name`

Specific information

`docker inspect --format='{{.NetworkSettings.IPAddress}}' container_name`

`docker inspect --format='{{.State.Status}}' container_name`

`docker inspect --format='{{json .Config}}' container_name`

Live resource usage

`docker stats container_name`

Process list inside container

`docker top container_name`

7.7 Container Logs

View container output.

Real Examples:

bash

View logs

`docker logs container_name`

Follow logs (like tail -f)

`docker logs -f container_name`

Show last N lines

`docker logs --tail 100 container_name`

Show logs with timestamps

`docker logs -t container_name`

Show logs since specific time

`docker logs --since 2024-01-15T10:30:00 container_name`

Export logs to file

`docker logs container_name > app.log`

Interview Scenario: Debugging a crashing container:

`bash`

Check why container exited

`docker ps -a | grep Exit`

See exit logs

`docker logs container_name`

Check exit code

`docker inspect --format='{{.State.ExitCode}}' container_name`

8. Docker Networking

8.1 What is Docker Networking

Docker provides network isolation between containers and host.

Default Networks:

```
bash
```

```
$ docker network ls
```

NETWORKID	NAME	DRIVER	SCOPE
-----------	------	--------	-------

abc123	bridge	bridge	local
--------	--------	--------	-------

def456	host	host	local
--------	------	------	-------

ghi789	none	null	local
--------	------	------	-------

8.2 Types of Docker Networks

Bridge Network (Default)

Default network for containers

Containers get IP addresses via DHCP

Port mapping needed for external access

```
bash
```

```
# Run container on bridge network
```

```
docker run -d --name web --network bridge nginx
```

```
# Custom bridge network
```

```
docker network create mynetwork
```



```
docker run -d --name app1 --network mynetwork myapp
```

```
docker run -d --name app2 --network mynetwork myapp
```

app1 and app2 can communicate by name

Host Network

Container uses host's network directly

No network isolation, better performance

bash

```
docker run -d --name web --network host nginx
```

Container port 80 available on host port 80 directly

None Network

No networking

Only loopback interface (127.0.0.1)

bash

```
docker run -d --name isolated --network none myapp
```

Completely isolated from network

Overlay Network

For multi-host Docker Swarm clusters

Containers across hosts can communicate

bash

In Swarm mode

```
docker network create --driver overlay myoverlay
```

8.3 Custom Networks

Create isolated networks for applications.

Real Example:

```
bash
```

```
# Create custom network
```

```
docker network create --driver bridge \
```

```
--subnet 172.20.0.0/16 \
```

```
--gateway 172.20.0.1 \
```

```
app-network
```

```
# Run containers on custom network
```

```
docker run -d --name db --network app-network postgres
```

```
docker run -d --name api --network app-network \
```

```
--link db:database \
```

```
-e "DB_HOST=database" \
```

```
api-server
```

```
# Containers can communicate using names
```

```
# api can connect to db at hostname "database"
```

8.4 Container-to-Container Communication

Methods:

Default Bridge: Use IP addresses

Custom Bridge: Use container names

Links: Legacy method (deprecated)

Network Aliases: Multiple names

Real Example:

```
bash
```

```
# Create network
```

```
docker network create mynet
```

```
# Run containers
```

```
docker run -d --name redis --network mynet redis:alpine
```

```
docker run -d --name app --network mynet \
```

```
-e "REDIS_HOST=redis" \
```

```
myapp
```

```
# In myapp, connect to redis using hostname "redis"
```

Testing Connectivity:

```
bash
```

```
# From host, test container connectivity
```

```
docker exec app ping redis
```

```
# Check network details
```

```
docker network inspect mynet
```

9. Docker Volumes & Storage

9.1 Why Volumes are Needed

Containers are ephemeral - all changes are lost when container is removed. Volumes provide persistent storage.

Real Problem: Database container gets recreated, all data lost. Solution: Use volume.

9.2 Types of Storage

Volumes (Managed by Docker)

```
bash
```

```
# Create volume
```

```
docker volume create dbdata
```

```
# Use volume
```

```
docker run -d \
```

```
--name postgres \
```

```
-v dbdata:/var/lib/postgresql/data \
```

```
postgres
```

```
# List volumes
```

```
docker volume ls
```

```
# Inspect volume
```

```
docker volume inspect dbdata
```

Remove unused volumes

```
docker volume prune
```

Bind Mounts (Host path)

```
bash
```

Mount host directory

```
docker run -d \
```

```
--name dev-server \
```

```
-v /home/user/app:/app \
```

```
node-app
```

Read-only bind mount

```
docker run -d \
```

```
-v /config:/app/config:ro \
```

```
myapp
```

tmpfs (In-memory)

```
bash
```

Temporary in-memory storage

```
docker run -d \
```

```
--name temp-app \
```

```
--tmpfs /tmp \
```

```
myapp
```

Comparison:

Type	Location	Managed by	Use Case
Volume	Docker area	Docker	Production, persistent data

Bind Mount	Host filesystem	User	Development, config files
tmpfs	Memory	Docker	Temporary, sensitive data

9.3 Creating & Using Volumes

Real Example - Database with volume:

```
bash
```

```
# Create named volume
```

```
docker volume create mysql_data
```

```
# Run MySQL with volume
```

```
docker run -d \
```

```
--name mysql_db \
```

```
-e MYSQL_ROOT_PASSWORD=secret \
```

```
-v mysql_data:/var/lib/mysql \
```

```
mysql:8.0
```

```
# Even if container removed, data persists
```

```
docker rm -f mysql_db
```

```
docker run -d \
```

```
--name new_mysql \
```

```
-v mysql_data:/var/lib/mysql \
```

```
mysql:8.0
```

```
# Data still exists!
```

Backup Volume:

```
bash
```

```
# Backup volume data

docker run --rm \

-v mysql_data:/source \

-v $(pwd):/backup \

alpine tar czf /backup/backup.tar.gz -C /source .
```

```
# Restore to volume

docker run --rm \

-v mysql_data:/target \

-v $(pwd):/backup \

alpine tar xzf /backup/backup.tar.gz -C /target
```

9.4 Data Persistence in Docker

Best Practices:

Use named volumes for production data

Regular backups of volumes

Avoid storing data in container layer

Use read-only mounts for configs

Real Scenario: Multi-container app with volumes:

yaml

```
# docker-compose.yml
```

version: '3.8'

services:

db:

image: postgres:13

volumes:

- postgres_data:/var/lib/postgresql/data

environment:

POSTGRES_PASSWORD: secret

app:

image: myapp:latest

volumes:

- app_logs:/app/logs

- ./config:/app/config:ro

volumes:

postgres_data:

app_logs:

10. Docker Compose (Multi-Container Applications)

10.1 What is Docker Compose

A tool for defining and running multi-container Docker applications using YAML files.

Real Example: Instead of multiple docker run commands:

bash

Traditional way (painful!)


```
docker run -d --name db postgres
```

```
docker run -d --name redis redis
```

```
docker run -d --name app --link db --link redis myapp
```

With Compose: `Single docker-compose up`

10.2 docker-compose.yml Structure

Basic Structure:

```
yaml
```

```
version: '3.8' # Compose file version
```

```
services:    # Containers to run
```

```
  web:
```

```
    image: nginx:alpine
```

```
    ports:
```

```
      - "80:80"
```

```
  api:
```

```
    build: ./api
```

```
    environment:
```

```
      - DB_HOST=db
```

```
  db:
```

```
    image: postgres:13
```

```
    environment:
```

```
      POSTGRES_PASSWORD: secret
```

networks: # Custom networks

app-network:

driver: bridge

volumes: # Named volumes

db-data:

10.3 Services

Each service becomes a container.

Real Example:

yaml

services:

frontend:

build: ./frontend

ports:

- "3000:3000"

depends_on:

- backend

backend:

build: ./backend

environment:

DATABASE_URL: postgres://user:pass@db/app

depends_on:

- database

database:

image: postgres:13

environment:

POSTGRES_DB: app

POSTGRES_USER: user

POSTGRES_PASSWORD: pass

volumes:

- postgres_data:/var/lib/postgresql/data

redis:

image: redis:alpine

command: redis-server --appendonly yes

10.4 Networks in Compose

Define custom networks for service communication.

Real Example:

yaml

version: '3.8'

services:

web:

image: nginx

networks:

- frontend

api:

image: node-app

networks:

- frontend

- backend

db:

image: postgres

networks:

- backend

networks:

frontend:

driver: bridge

ipam:

config:

- subnet: 172.20.0.0/16

backend:

driver: bridge

10.5 Volumes in Compose

Define persistent storage.

Real Example:

yaml

services:

database:

image: mysql:8.0

volumes:

- db_data:/var/lib/mysql
- ./init.sql:/docker-entrypoint-initdb.d/init.sql:ro
- ./my.cnf:/etc/mysql/conf.d/my.cnf:ro

app:

image: myapp

volumes:

- ./app:/app
- /app/node_modules # anonymous volume

volumes:

db_data:

driver: local

10.6 Running Multiple Containers Together

Compose Commands:

bash

Start all services

docker-compose up -d

Stop all services

```
docker-compose down
```

```
# View logs
```

```
docker-compose logs -f
```

```
docker-compose logs service_name
```

```
# Scale services
```

```
docker-compose up --scale api=3 --scale worker=5
```

```
# Build and start
```

```
docker-compose up --build
```

```
# Execute command in service
```

```
docker-compose exec api bash
```

```
docker-compose exec db psql -U postgres
```

10.7 Real-world Example: Web App + Database

Complete docker-compose.yml:

```
yaml
```

```
version: '3.8'
```

```
services:
```

```
  # React Frontend
```

```
  frontend:
```

```
    build: ./frontend
```

```
    ports:
```

- "80:3000"

volumes:

- ./frontend:/app
- /app/node_modules

environment:

- REACT_APP_API_URL=http://api:5000

depends_on:

- api

Node.js Backend API

api:

build: ./backend

ports:

- "5000:5000"

volumes:

- ./backend:/app
- /app/node_modules

environment:

- NODE_ENV=development
- DB_HOST=postgres
- DB_PORT=5432
- DB_USER=appuser
- DB_PASSWORD=secret
- DB_NAME=mydb
- REDIS_URL=redis://redis:6379

depends_on:

- postgres

- redis

healthcheck:

test: ["CMD", "curl", "-f", "http://localhost:5000/health"]

interval: 30s

timeout: 10s

retries: 3

PostgreSQL Database

postgres:

image: postgres:13-alpine

environment:

- POSTGRES_USER=appuser

- POSTGRES_PASSWORD=secret

- POSTGRES_DB=mydb

volumes:

- postgres_data:/var/lib/postgresql/data

- ./init.sql:/docker-entrypoint-initdb.d/init.sql

ports:

- "5432:5432"

Redis Cache

redis:

image: redis:6-alpine

command: redis-server --appendonly yes

volumes:

- redis_data:/data

ports:

- "6379:6379"

pgAdmin (Database GUI)

pgadmin:

image: dpage/pgadmin4

environment:

- PGADMIN_DEFAULT_EMAIL=admin@example.com

- PGADMIN_DEFAULT_PASSWORD=admin

ports:

- "8080:80"

depends_on:

- postgres

volumes:

postgres_data:

redis_data:

networks:

default:

name: app-network

driver: bridge

Usage:

bash

Start the entire stack

`docker-compose up -d`

Check status

`docker-compose ps`

View logs

`docker-compose logs -f`

Scale API instances

`docker-compose up -d --scale api=3`

Stop everything

`docker-compose down`

Stop and remove volumes

`docker-compose down -v`

11. Docker Registry & Image Management

11.1 Public vs Private Registries

Public Registries:

Docker Hub: Default public registry

GitHub Container Registry: Integrated with GitHub

Quay.io: Red Hat's registry

Private Registries:

Docker Trusted Registry: Docker's enterprise solution

Azure Container Registry: Microsoft Azure

Amazon ECR: AWS

Google Container Registry: GCP

Self-hosted: Run registry as container

Real Example - Company Setup:

Public images (nginx, redis) from Docker Hub

Internal base images from private registry

Application images in organization's private registry

11.2 Pushing Images to Docker Hub

Step-by-step:

bash

1. Create Docker Hub account

2. Login from CLI

`docker login`

3. Tag image with username/repository

`docker tag myapp:latest username/myapp:1.0`

`docker tag myapp:latest username/myapp:latest`

4. Push image

`docker push username/myapp:1.0`

`docker push username/myapp:latest`

5. Verify on Docker Hub

`docker pull username/myapp:1.0`

Organization Images:

`bash`

Tag for organization

`docker tag myapp:latest mycompany/api-service:v2.1`

Push to organization

`docker push mycompany/api-service:v2.1`

11.3 Pulling from Private Registry

Different Registry Examples:

Docker Hub (Private):

```
bash
```

```
docker login
```

```
docker pull mycompany/private-app:latest
```

Amazon ECR:

```
bash
```

```
# Get login command
```

```
aws ecr get-login-password --region us-east-1 | \
```

```
    docker login --username AWS --password-stdin 123456789.dkr.ecr.us-east-1.amazonaws.com
```

```
# Pull image
```

```
docker pull 123456789.dkr.ecr.us-east-1.amazonaws.com/myapp:latest
```

Self-hosted Registry:

```
bash
```

```
# Run registry container
```

```
docker run -d -p 5000:5000 --name registry registry:2
```

```
# Tag and push to local registry
```

```
docker tag myapp:latest localhost:5000/myapp:latest
```

```
docker push localhost:5000/myapp:latest
```

```
# Pull from local registry
```

```
docker pull localhost:5000/myapp:latest
```

11.4 Image Security & Scanning

Security Best Practices:

Scan images for vulnerabilities:

bash

Using Docker Scout (formerly Snyk)

docker scout quickview myapp:latest

Using Trivy

trivy image myapp:latest

Using Clair

clair-scanner --ip host.docker.internal myapp:latest

Use official images from trusted sources

Keep images updated with security patches

Implement image signing (Docker Content Trust)

Use minimal base images (Alpine, Distroless)

Real Example - Secure Pipeline:

bash

Build image

docker build -t myapp:latest .

Scan for vulnerabilities

```
docker scout cves myapp:latest
```

If passes, push to registry

```
docker push myregistry.com/myapp:latest
```

In production, pull with content trust

```
export DOCKER_CONTENT_TRUST=1
```

```
docker pull myregistry.com/myapp:latest
```

12. Docker Security

12.1 Container Isolation

Containers provide process isolation through Linux namespaces and cgroups.

Isolation Mechanisms:

PID namespace: Isolated process tree

Network namespace: Isolated network stack

Mount namespace: Isolated filesystem

UTS namespace: Isolated hostname

User namespace: Isolated user IDs

Real Example: Even if container runs as root, it's root inside container namespace, not on host.

12.2 Image Vulnerabilities

Common Vulnerabilities:

Outdated packages in base image

Unnecessary software included

Default credentials in images

SUID binaries that can be exploited

Mitigation:

dockerfile

Use specific version, not latest

FROM alpine:3.14 # Good

FROM alpine:latest # Bad

Regularly update base images

Run security scans

Remove unnecessary packages

12.3 Least Privilege Principle

Run containers with minimal privileges.

Best Practices:

dockerfile

Create non-root user

RUN groupadd -r appuser && useradd -r -g appuser appuser

USER appuser

In docker run

docker run --user 1000:1000 myapp

Capabilities Management:

bash

Drop all capabilities, add only needed

docker run --cap-drop=ALL --cap-add=NET_BIND_SERVICE nginx

Read-only filesystem

docker run --read-only myapp

No new privileges

docker run --security-opt=no-new-privileges myapp

12.4 Secrets Management

Never store secrets in images or environment variables.

Docker Secrets (Swarm):

bash

Create secret

echo "mysecretpassword" | docker secret create db_password -

Use in service

docker service create \

--name mysql \

--secret source=db_password,target=db_password \

mysql

For Docker Compose:

yaml

version: '3.8'

services:

db:

image: postgres

secrets:

- db_password

environment:

POSTGRES_PASSWORD_FILE: /run/secrets/db_password

secrets:

db_password:

file: ./db_password.txt

For standalone containers: Use external secret managers (AWS Secrets Manager, HashiCorp Vault).

12.5 Docker Bench for Security

Automated security checker for Docker.

Usage:

bash

Run security audit

```
docker run -it --net host --pid host --usersns host --cap-add audit_control \
```

```
-e DOCKER_CONTENT_TRUST=1 \
```

```
-v /var/lib:/var/lib \
```

```
-v /var/run/docker.sock:/var/run/docker.sock \
```

```
--label docker_bench_security \
```

```
docker/docker-bench-security
```

Fix issues reported

Example: Ensure containers use trusted base images

Example: Ensure Docker daemon runs with TLS authentication

13. Docker Performance & Optimization

13.1 Reducing Image Size

Techniques:

Use Alpine base images:

dockerfile

FROM node:16-alpine # ~120MB

vs

FROM node:16 # ~900MB

Clean up in same RUN layer:

dockerfile

RUN apt-get update && apt-get install -y \

package1 \

package2 \

&& rm -rf /var/lib/apt/lists/* # Clean cache

Remove unnecessary files:

dockerfile

Bad: Leaves npm cache

RUN npm install

Good: Clean npm cache

RUN npm install && npm cache clean --force

Real Example Comparison:

Unoptimized: 1.2GB

Optimized: 180MB (85% reduction)

13.2 Multi-Stage Builds

Separate build environment from runtime.

Real Example - Go application:

```
dockerfile
```

```
# Stage 1: Build
```

```
FROM golang:1.19 AS builder
```

```
WORKDIR /app
```

```
COPY . .
```

```
RUN go build -o myapp .
```

```
# Stage 2: Runtime
```

```
FROM alpine:3.16
```

```
WORKDIR /root/
```

```
COPY --from=builder /app/myapp .
```

```
RUN apk --no-cache add ca-certificates
```

```
CMD ["/myapp"]
```

Result: Final image contains only the binary, not build tools (~15MB vs ~800MB).

13.3 Caching in Docker

Docker caches layers to speed up builds.

Optimizing Cache Usage:

Order instructions properly:

```
dockerfile
```

```
# Bad - COPY changes often, cache invalidated
```

COPY . .

RUN npm install

Good - Install dependencies first

COPY package.json package-lock.json .

RUN npm install

COPY . .

Use .dockerignore:

text

node_modules/

.git/

*.log

Dockerfile

Leverage build cache in CI/CD:

bash

docker build --cache-from myapp:latest -t myapp:new .

13.4 Monitoring Containers

Monitoring Commands:

bash

Live resource usage

docker stats

Container process list

`docker top container_name`

Inspect container resource limits

`docker inspect --format='{{.HostConfig.Memory}}' container_name`

Log monitoring

`docker logs --tail 100 -f container_name`

Prometheus Monitoring Setup:

yaml

docker-compose.yml

version: '3.8'

services:

prometheus:

image: prom/prometheus

volumes:

- ./prometheus.yml:/etc/prometheus/prometheus.yml

ports:

- "9090:9090"

node-exporter:

image: prom/node-exporter

volumes:

- /proc:/host/proc:ro

- /sys:/host/sys:ro

- /:/rootfs:ro

command:

- '--path.procfs=/host/proc'
- '--path.sysfs=/host/sys'
- '--collector.filesystem.mount-points-exclude=^/(sys|proc|dev|host|etc)(\$\$|/)'

cadvisor:

image: gcr.io/cadvisor/cadvisor

volumes:

- /:/rootfs:ro
- /var/run:/var/run:rw
- /sys:/sys:ro
- /var/lib/docker:/var/lib/docker:ro

ports:

- "8080:8080"

14. Docker in DevOps & CI/CD

14.1 Docker in CI/CD Pipeline

Typical Pipeline:

Developer pushes code to Git

CI Server builds Docker image

Security scan on image

Push to registry

Deploy to environments

Real Example - Jenkins Pipeline:

```
groovy
```

```
pipeline {
```

```
    agent any
```

```
    stages {
```

```
        stage('Build') {
```

```
            steps {
```

```
                sh 'docker build -t myapp:$BUILD_NUMBER .'
```

```
            }
```

```
        }
```

```
        stage('Test') {
```

```
            steps {
```

```
                sh 'docker run myapp:$BUILD_NUMBER npm test'
```

```
            }
```

```
        }
```

```
        stage('Scan') {
```

```
            steps {
```

```
                sh 'docker scan myapp:$BUILD_NUMBER'
```

```
            }
```

```
        }
```

```

stage('Push'){
    steps {
        sh 'docker tag myapp:$BUILD_NUMBER myregistry.com/myapp:$BUILD_NUMBER'
        sh 'docker push myregistry.com/myapp:$BUILD_NUMBER'
    }
}

stage('Deploy') {
    steps {
        sh 'kubectl set image deployment/myapp
myapp=myregistry.com/myapp:$BUILD_NUMBER'
    }
}
}

```

14.2 Docker with Jenkins

Jenkins Docker Setup:

Install Docker on Jenkins agents

Configure Docker Cloud in Jenkins

Use Docker for ephemeral build agents

docker-compose.yml for Jenkins:

yaml

version: '3.8'

services:

jenkins:

image: jenkins/jenkins:lts

ports:

- "8080:8080"

- "50000:50000"

volumes:

- jenkins_home:/var/jenkins_home

- /var/run/docker.sock:/var/run/docker.sock

environment:

- DOCKER_HOST=unix:///var/run/docker.sock

jenkins-agent:

build: ./agent

volumes:

- /var/run/docker.sock:/var/run/docker.sock

14.3 Docker with GitHub Actions

GitHub Actions Workflow:

yaml

name: Docker CI/CD

on:

push:

branches: [main]

jobs:

build-and-push:

runs-on: ubuntu-latest

steps:

- name: Checkout code

uses: actions/checkout@v2

- name: Login to Docker Hub

uses: docker/login-action@v1

with:

username: \${{ secrets.DOCKER_USERNAME }}

password: \${{ secrets.DOCKER_PASSWORD }}

- name: Build Docker image

run: |

docker build -t myapp:\${{ github.sha }} .

docker tag myapp:\${{ github.sha }} myapp:latest

- name: Push Docker image

run: |

docker push myapp:\${{ github.sha }}

```
docker push myapp:latest
```

- name: Deploy to Kubernetes

```
run: |
```

```
kubectl set image deployment/myapp myapp=myapp:${{ github.sha }}
```

14.4 Docker in Cloud (AWS, Azure, GCP)

AWS ECS Example:

```
json
```

```
{
  "family": "myapp",
  "containerDefinitions": [
    {
      "name": "web",
      "image": "123456789.dkr.ecr.us-east-1.amazonaws.com/myapp:latest",
      "cpu": 256,
      "memory": 512,
      "portMappings": [
        {
          "containerPort": 80,
          "hostPort": 80
        }
      ]
    }
  ]
}
```

Azure Container Instances:

bash

```
az container create \  
  --resource-group myResourceGroup \  
  --name myapp \  
  --image myregistry.azurecr.io/myapp:latest \  
  --dns-name-label myapp-dns \  
  --ports 80
```

Google Cloud Run:

bash

Deploy container

```
gcloud run deploy myapp \  
  --image gcr.io/myproject/myapp:latest \  
  --platform managed \  
  --region us-central1 \  
  --allow-unauthenticated
```

15. Docker vs Kubernetes (Interview Comparison)

15.1 Docker vs Kubernetes

Aspect	Docker	Kubernetes
Purpose	Container runtime & packaging	Container orchestration
Scope	Single host	Multiple hosts (cluster)
Scaling	Manual (docker-compose scale)	Automatic (HPA)
Networking	Basic (bridge, host, none)	Advanced (CNI plugins)
Storage	Volumes, bind mounts	Persistent volumes, storage classes

Load Balancing Basic(port mapping)Advanced (Ingress, Services)

Self-healing Limited (restart policies) Advanced (health checks, pod restart)

Analogy: Docker is like a shipping container, Kubernetes is like a global shipping management system.

15.2 When to Use Docker Only

Use Docker when:

Local development environment

Simple applications (single container)

Learning containers concepts

CI/CD build environments

Small-scale deployments (1-5 containers)

Real Example:

Developer laptop setup

Small company's internal tool

Prototype/MVP applications

Build agents in CI pipeline

15.3 When to Use Kubernetes

Use Kubernetes when:

Microservices architecture (10+ services)

High availability requirements

Auto-scaling needed

Multi-cloud or hybrid deployments

Complex networking requirements

Enterprise-grade applications

Real Example:

E-commerce platform with 50+ microservices

SaaS application with thousands of users

Global application needing multi-region deployment

Applications requiring zero-downtime updates

Interview Answer: "We use Docker to package our applications into containers, and Kubernetes to orchestrate and manage those containers across our production cluster, providing scaling, self-healing, and service discovery."

16. Advanced Docker Concepts

16.1 Namespaces & cgroups

Namespaces provide isolation:

```
bash
```

```
# PID namespace example
```

```
docker run -it --name container1 alpine sh
```

```
# Inside container: ps aux (only container processes)
```

```
# Network namespace
```

```
docker run -it --name container2 alpine sh
```

```
# ifconfig shows container's network, not host
```

cgroups control resources:

```
bash
```

```
# Limit memory to 100MB
```

```
docker run -it --memory="100m" alpine sh
```

```
# Limit CPU shares
```

```
docker run -it --cpu-shares=512 alpine sh
```

Limit CPU cores

```
docker run -it --cpus="1.5" alpine sh
```

Real Example: Preventing a container from consuming all host memory:

bash

```
docker run -d --memory="1g" --memory-swap="2g" myapp
```

16.2 Swarm Mode

Docker's built-in orchestration.

Initialize Swarm:

bash

Initialize swarm on manager

```
docker swarm init --advertise-addr <MANAGER-IP>
```

Join worker nodes

```
docker swarm join --token <TOKEN> <MANAGER-IP>:2377
```

Create service

```
docker service create --name web --replicas 3 -p 80:80 nginx
```

Scale service

```
docker service scale web=5
```

Update service

```
docker service update --image nginx:alpine web
```

16.3 Rolling Updates

Update containers without downtime.

Docker Swarm:

```
bash
```

```
docker service update \
```

```
--image myapp:v2 \
```

```
--update-parallelism 2 \
```

```
--update-delay 10s \
```

```
--update-failure-action rollback \
```

```
myapp
```

Docker Compose:

```
bash
```

```
docker-compose up -d --no-deps --build service_name
```

16.4 Load Balancing

Docker Swarm has built-in load balancing across replicas.

Real Example:

```
bash
```

```
# Create service with 3 replicas
```

```
docker service create --name api --replicas 3 -p 8080:3000 myapi
```

```
# Traffic to host:8080 is load balanced across 3 containers
```

Check which container handles request

curl http://localhost:8080/which-container

17. Common Docker Interview Questions

17.1 Freshers Level Questions

Q1: What is Docker and why use it?

A: Docker is a containerization platform that packages applications and dependencies into isolated containers. Benefits: consistency across environments, lightweight compared to VMs, fast deployment, efficient resource usage.

Q2: Difference between Docker image and container?

A: Image is a read-only template with application code and dependencies. Container is a running instance of an image. Analogy: Image is a Class, Container is an Object instance.

Q3: Basic Docker commands?

A: docker run, docker ps, docker build, docker pull, docker push, docker exec, docker logs

Q4: What is Dockerfile?

A: Text file with instructions to build a Docker image (FROM, COPY, RUN, CMD, etc.)

17.2 2–4 Years Experience Level

Q1: Explain Docker architecture?

A: Client-server architecture with Docker Client (CLI), Docker Daemon (server), Registry (image storage), Images (templates), Containers (running instances).

Q2: Docker network types?

A: Bridge (default), Host (shares host network), None (no network), Overlay (multi-host), Macvlan (assign MAC to container).

Q3: Docker volumes vs bind mounts?

A: Volumes are managed by Docker, stored in Docker area. Bind mounts mount host directories. Volumes are preferred for production.

Q4: Multi-stage builds?

A: Use multiple FROM statements to separate build environment from runtime, reducing final image size.

17.3 Scenario-Based Questions

Q1: Container is running but application not accessible?

A:

Check port mapping: `docker ps` to see ports

Check if app listens on correct interface (should be 0.0.0.0)

Check firewall rules

Check container logs: `docker logs container_name`

Q2: Docker build is slow?

A:

Optimize Dockerfile order (frequently changing layers last)

Use `.dockerignore` to exclude unnecessary files

Use build cache effectively

Consider multi-stage builds

Q3: "No space left on device" error?

A:

bash

Cleanup commands

`docker system prune`

`docker system prune -a`

`docker volume prune`

`docker image prune`

17.4 Debugging Questions

Q1: How to debug a crashing container?

A:

bash

Check exit code

`docker inspect --format '{{.State.ExitCode}}' container`

Check logs

`docker logs container`

Run with interactive shell

`docker run -it --entrypoint=/bin/sh image_name`

Inspect container

`docker inspect container`

Q2: Container can't connect to another container?

A:

Check if on same network: `docker network inspect network_name`

Use container names not IPs (IPs change)

Check exposed ports

Test connectivity: `docker exec container1 ping container2`

18. Hands-On Practice Projects

18.1 Run a Node.js App in Docker

Project Structure:

text

node-app/

├─ Dockerfile

├─ package.json

├─ index.js

└─ .dockerignore

Dockerfile:

```
dockerfile
```

```
FROM node:16-alpine
```

```
WORKDIR /app
```

```
COPY package*.json ./
```

```
RUN npm ci --only=production
```

```
COPY . .
```

```
EXPOSE 3000
```

```
USER node
```

```
CMD ["node", "index.js"]
```

index.js:

```
javascript
```

```
const express = require('express');
```

```
const app = express();
```

```
app.get('/', (req, res) => {
```

```
  res.send('Hello Docker!');
```

```
});
```

```
app.listen(3000, () => {
```

```
  console.log('Server running on port 3000');
```

```
});
```

Commands:

```
bash
```

```
docker build -t node-app .
```



```
docker run -d -p 3000:3000 node-app
```

```
curl http://localhost:3000
```

18.2 Dockerize a Java Spring Boot App

Dockerfile:

```
dockerfile
```

```
# Build stage
```

```
FROM maven:3.8-openjdk-17 AS builder
```

```
WORKDIR /app
```

```
COPY pom.xml .
```

```
RUN mvn dependency:go-offline
```

```
COPY src ./src
```

```
RUN mvn package -DskipTests
```

```
# Runtime stage
```

```
FROM openjdk:17-jdk-slim
```

```
WORKDIR /app
```

```
COPY --from=builder /app/target/*.jar app.jar
```

```
EXPOSE 8080
```

```
ENTRYPOINT ["java", "-jar", "app.jar"]
```

Build and Run:

```
bash
```

```
docker build -t spring-app .
```

```
docker run -d -p 8080:8080 spring-app
```

18.3 Docker + MySQL Project

docker-compose.yml:

yml

version: '3.8'

services:

db:

image: mysql:8.0

environment:

MYSQL_ROOT_PASSWORD: rootpass

MYSQL_DATABASE: mydb

MYSQL_USER: user

MYSQL_PASSWORD: userpass

ports:

- "3306:3306"

volumes:

- db_data:/var/lib/mysql

- ./init.sql:/docker-entrypoint-initdb.d/init.sql

adminer:

image: adminer

ports:

- "8080:8080"

depends_on:

- db

volumes:

db_data:

Access: Adminer at <http://localhost:8080>

18.4 Full Stack App with Docker Compose

Complete Stack:

yaml

version: '3.8'

services:

React Frontend

frontend:

build: ./frontend

ports:

- "3000:3000"

volumes:

- ./frontend:/app

- /app/node_modules

environment:

REACT_APP_API_URL: <http://localhost:5000>

Node.js API

api:

build: ./api

ports:

- "5000:5000"

volumes:

- ./api:/app
- /app/node_modules

environment:

DB_HOST: db

DB_USER: root

DB_PASSWORD: secret

DB_NAME: appdb

depends_on:

- db

MySQL Database

db:

image: mysql:8.0

environment:

MYSQL_ROOT_PASSWORD: secret

MYSQL_DATABASE: appdb

volumes:

- mysql_data:/var/lib/mysql

Nginx Reverse Proxy

nginx:

image: nginx:alpine

ports:

- "80:80"

volumes:

- ./nginx.conf:/etc/nginx/nginx.conf

depends_on:

- frontend

- api

volumes:

mysql_data:

19. Docker Troubleshooting

19.1 Container Not Starting

Common Causes & Solutions:

bash

1. Check container logs

docker logs container_name

2. Check exit code

docker inspect --format='{{.State.ExitCode}}' container_name

3. Common exit codes:

0: Success

1: Application error

125: Docker run error

126: Command invoked cannot execute

127: Command not found

137: SIGKILL (often out of memory)

143: SIGTERM (graceful shutdown)

4. Run with interactive shell to debug

```
docker run -it --entrypoint=/bin/sh image_name
```

5. Check resource limits

```
docker inspect --format='{{.HostConfig.Memory}}' container_name
```

19.2 Port Not Exposed

Debugging Steps:

```
bash
```

1. Check if container is running

```
docker ps
```

2. Check port mapping

```
docker port container_name
```

3. Test from inside container

```
docker exec container_name curl localhost:80
```

4. Check if app listens on 0.0.0.0 (not 127.0.0.1)

```
docker exec container_name netstat -tulpn
```

5. Check firewall

```
sudo ufw status
```

19.3 Image Not Found

Solutions:

bash

1. Check if image exists locally

docker images | grep image_name

2. Pull image

docker pull image_name:tag

3. Check private registry login

docker login registry.company.com

4. Check tag exists in registry

curl https://registry.hub.docker.com/v2/repositories/library/nginx/tags/

5. Use correct image name format

Wrong: docker pull nginx (if private registry needed)

Right: docker pull registry.company.com/nginx

19.4 Permission Denied Errors

Solutions:

bash

1. Docker daemon not running

sudo systemctl status docker

2. User not in docker group

sudo usermod -aG docker \$USER

Logout and login again

3. Permission on Docker socket

ls -la /var/run/docker.sock

4. In container: run as non-root

In Dockerfile:

USER 1000:1000

5. Volume permissions

Mount with correct user ID

docker run -v \$(pwd):/app:z -u \$(id -u):\$(id -g) myapp

19.5 Low Disk Space Issues

Cleanup Commands:

bash

Check disk usage

docker system df

Remove unused data

docker system prune

Remove everything (more aggressive)

docker system prune -a --volumes

Remove specific resources

docker container prune

docker image prune

docker volume prune

docker network prune

Remove by filter

docker images --filter "dangling=true" -q | xargs docker rmi

docker images --filter "before=image:tag" -q | xargs docker rmi

20. Final Revision & Interview Crash Notes

20.1 One-Page Docker Cheat Sheet

text

IMAGES

docker build -t name . # Build image

docker images # List images

docker rmi image # Remove image

docker history image # Show image layers

docker tag old new # Tag image

CONTAINERS

docker run image # Run container

docker ps # List running

docker ps -a # List all

docker stop container # Stop container

docker start container # Start stopped

docker rm container # Remove container

docker exec -it container sh # Exec into container

docker logs container # View logs

VOLUMES

docker volume ls # List volumes

docker volume create name # Create volume

docker volume rm name # Remove volume

NETWORK

docker network ls # List networks

docker network create name # Create network

SYSTEM

docker info # System info

docker version # Version info

docker system df # Disk usage

docker system prune # Cleanup

COMPOSE

docker-compose up # Start services

docker-compose down # Stop services

docker-compose logs # View logs

20.2 Important Command Summary

Essential for Interviews:

bash

Build and Run workflow

```
docker build -t app:tag .
```

```
docker run -d -p 80:80 --name myapp app:tag
```

```
docker logs myapp
```

```
docker exec -it myapp bash
```

```
docker stop myapp
```

```
docker rm myapp
```

```
docker rmi app:tag
```

Debugging commands

```
docker inspect container
```

```
docker stats
```

```
docker top container
```

```
docker port container
```

```
docker diff container
```

20.3 Most Asked Interview Answers

Q: What is Docker?

A: Containerization platform that packages apps with dependencies into isolated, portable containers.

Q: Docker vs VM?

A: Docker shares host OS kernel, lightweight, fast startup. VMs have full OS, heavier, slower.

Q: Dockerfile instructions?

A: FROM, RUN, COPY, ADD, WORKDIR, EXPOSE, CMD, ENTRYPOINT, ENV, VOLUME, USER.

Q: Docker volumes?

A: Persistent storage that survives container lifecycle. Types: volumes (managed), bind mounts (host path), tmpfs (memory).

Q: Docker Compose?

A: Tool for defining/running multi-container apps using YAML file.

Q: Docker networking?

A: Bridge (default), Host (shared), None (isolated), Overlay (multi-host).

20.4 Common Mistakes

Using latest tag in production → Use specific versions

Running as root in container → Create non-root user

Not using .dockerignore → Large images, slow builds

Storing data in container layer → Use volumes

Exposing all ports → Only expose necessary ports

Not cleaning up → Regular docker system prune

Hardcoding configs → Use environment variables

Building from source in production image → Use multi-stage builds

Not scanning for vulnerabilities → Regular security scans

Ignoring container resource limits → Set memory/CPU limits

Golden Rule: Containers should be ephemeral (stateless) and immutable (don't modify running containers, rebuild image instead).