

# **Applications of Formal Verification**

# **Functional Verification of Java Programs: Java Modeling Language**

Shmuel Tyszberowicz based on materials by Bernhard Beckert · Vladimir Klebanov | 2014





#### Hoare triple

Has the form

{ Precondition} Prog-Segment { Postcondition}

#### Expresses partial correctness

If the Prog-Segment starts with a state satisfying the precondition and it terminates then the final state of the Prog-Segment satisfies the postscondition

- Example
  - $\{X \ge 0\} X := X+1; \{X \ge 1\}$



#### Hoare triple

Has the form

{ Precondition} Prog-Segment { Postcondition}

#### Expresses partial correctness

If the Prog-Segment starts with a state satisfying the precondition and it terminates then the final state of the Prog-Segment satisfies the postscondition

- Example
  - $\{X \ge 0\} X := X+1; \{X \ge 1\}$



#### Hoare triple

Has the form

{ Precondition} Prog-Segment { Postcondition}

#### Expresses partial correctness

If the Prog-Segment starts with a state satisfying the precondition

and it terminates

then the final state of the Prog-Segment satisfies the postscondition

- Example
  - $\{X \ge 0\} X := X+1; \{X \ge 1\}$



#### Hoare triple

Has the form

{ Precondition} Prog-Segment { Postcondition}

#### Expresses partial correctness

If the Prog-Segment starts with a state satisfying the precondition and it terminates

then the final state of the Prog-Segment satisfies the postscondition

- Example
  - $\{X \ge 0\} X := X+1; \{X \ge 1\}$



#### Hoare triple

Has the form

{ Precondition} Prog-Segment { Postcondition}

#### Expresses partial correctness

If the Prog-Segment starts with a state satisfying the precondition and it terminates then the final state of the Prog-Segment satisfies the postscondition

- Example
  - $\{X \ge 0\} X := X+1; \{X \ge 1\}$



#### Hoare triple

Has the form

{ Precondition} Prog-Segment { Postcondition}

#### Expresses partial correctness

If the Prog-Segment starts with a state satisfying the precondition and it terminates then the final state of the Prog-Segment satisfies the postscondition

- Example
  - $\{X \ge 0\}$  X:=X+1;  $\{X \ge 1\}$



#### Idea

Specifications fix a contract between caller and callee of a method (between client and implementor of a module)

- Interface documentation
- Contracts described in a mathematically precise language
  - Higher degree of precision
  - Automation of program analysis of various kinds
    - Runtime assertion checking
    - Static verification
- Note: Errors in specifications are at least as common as errors in code



#### Idea

Specifications fix a contract between caller and callee of a method (between client and implementor of a module)

If the caller guarantees precondition

then the callee guarantees postcondition

- Interface documentation
- Contracts described in a mathematically precise language
  - Higher degree of precision
  - Automation of program analysis of various kinds
    - Runtime assertion checking
    - Static verification
- Note: Errors in specifications are at least as common as errors in code



#### Idea

Specifications fix a contract between caller and callee of a method (between client and implementor of a module)

- Interface documentation
- Contracts described in a mathematically precise language
  - Higher degree of precision
  - Automation of program analysis of various kinds
    - Runtime assertion checking
    - Static verification
- Note: Errors in specifications are at least as common as errors in code



#### Idea

Specifications fix a contract between caller and callee of a method (between client and implementor of a module)

- Interface documentation
- Contracts described in a mathematically precise language
  - Higher degree of precision
  - Automation of program analysis of various kinds
    - Runtime assertion checking
    - Static verification
- Note: Errors in specifications are at least as common as errors in code



#### Idea

Specifications fix a contract between caller and callee of a method (between client and implementor of a module)

- Interface documentation
- Contracts described in a mathematically precise language
  - Higher degree of precision
  - Automation of program analysis of various kinds
    - Runtime assertion checking
    - Static verification
- Note: Errors in specifications are at least as common as errors in code



#### Idea

Specifications fix a contract between caller and callee of a method (between client and implementor of a module)

- Interface documentation
- Contracts described in a mathematically precise language
  - Higher degree of precision
  - Automation of program analysis of various kinds
    - Runtime assertion checking
    - Static verification
- Note: Errors in specifications are at least as common as errors in code



#### Idea

Specifications fix a contract between caller and callee of a method (between client and implementor of a module)

- Interface documentation
- Contracts described in a mathematically precise language
  - Higher degree of precision
  - Automation of program analysis of various kinds
    - Runtime assertion checking
    - Static verification
- Note: Errors in specifications are at least as common as errors in code



#### Idea

Specifications fix a contract between caller and callee of a method (between client and implementor of a module)

- Interface documentation
- Contracts described in a mathematically precise language
  - Higher degree of precision
  - Automation of program analysis of various kinds
    - Runtime assertion checking
    - Static verification
- Note: Errors in specifications are at least as common as errors in code



```
/*@ public normal_behavior
  @ requires pin == correctPin;
  @ ensures customerAuthenticated;
  @*/
public void enterPIN (int pin) {
    ...
```

- specifications
- Within a JML annotation, an '@' is ignored:
  - If it is the first (non-white) character in the line
  - If it is the last character before '\*/'
  - ⇒ The blue '@'s are not required, but it is a *convention* to use them
- JML specifications may themselves contain comments



```
/*@ public normal_behavior
  @ requires pin == correctPin;
  @ ensures customerAuthenticated;
  @*/
public void enterPIN (int pin) {
    ...
```

- Java comments with '@' as first character are JML specifications
- Within a JML annotation, an '@' is ignored:
  - If it is the first (non-white) character in the line
  - If it is the last character before '\*/'
  - $\Rightarrow$  The blue '@'s are not required, but it is a *convention* to use them
- JML specifications may themselves contain comments



```
/*@ public normal_behavior
@ requires pin == correctPin;
@ ensures customerAuthenticated;
@*/
public void enterPIN (int pin) {
    ...
```

- Java comments with '@' as first character are JML specifications
- Within a JML annotation, an '@' is ignored:
  - If it is the first (non-white) character in the line
  - If it is the last character before '\*/'
  - ⇒ The blue '@'s are not required, but it is a *convention* to use them
- JML specifications may themselves contain comments



```
/*@ public normal_behavior
@ requires pin == correctPin;
@ ensures customerAuthenticated;
@*/
public void enterPIN (int pin) {
...
```

- Java comments with '@' as first character are JML specifications
- Within a JML annotation, an '@' is ignored:
  - If it is the first (non-white) character in the line
  - If it is the last character before '\*/'
  - ⇒ The blue '@'s are not required, but it is a *convention* to use them
- JML specifications may themselves contain comments



```
/*@ public normal_behavior
  @ requires pin == correctPin;
  @ ensures customerAuthenticated;
  @*/
public void enterPIN (int pin) {
    ...
```

- Java comments with '@' as first character are JML specifications
- Within a JML annotation, an '@' is ignored:
  - If it is the first (non-white) character in the line
  - If it is the last character before '\*/'
  - ⇒ The blue '@'s are not required, but it is a *convention* to use them
- JML specifications may themselves contain comments



- Java comments with '@' as first character are JML specifications
- Within a JML annotation, an '@' is ignored:
  - If it is the first (non-white) character in the line
  - If it is the last character before '\*/'
  - ⇒ The blue '@'s are not required, but it is a *convention* to use them
- JML specifications may themselves contain comments



- Modifiers to specification cases have no influence on their semantics
- public specification items cannot refer to private fields
- Private fields can be declared public for specification purposes only



- Modifiers to specification cases have no influence on their semantics
- public specification items cannot refer to private fields
- Private fields can be declared public for specification purposes only



- Modifiers to specification cases have no influence on their semantics
- public specification items cannot refer to private fields
- Private fields can be declared public for specification purposes only



- Modifiers to specification cases have no influence on their semantics
- public specification items cannot refer to private fields
- Private fields can be declared public for specification purposes only



```
/*@ requires pre;
  @ ensures post;
  @ assignable a;
  @ diverges d;
  @ signals only E1, ..., En;
  @ signals(E e) s;
  a*/
T m(...);
```

```
exceptional_behavior = ensures false;
```



```
/*@ requires pre; //what is the caller's obligation?
  @ ensures post;
  @ assignable a;
  @ diverges d;
  @ signals_only E1, ..., En;
  @ signals(E e) s;
  a*/
T m(...);
```

```
exceptional_behavior = ensures false;
```



```
/*@ requires pre; //what is the caller's obligation?
  @ ensures post; //what must hold on normal termination?
  @ assignable a;
  @ diverges d;
  @ signals_only E1, ..., En;
  @ signals(E e) s;
  a*/
T m(...);
```

```
exceptional_behavior = ensures false;
```



```
/*@ requires pre; //what is the caller's obligation?
  @ ensures post; //what must hold on normal termination?
  @ assignable a; //which locations may be assigned by m?
  @ diverges d;
  @ signals_only E1, ..., En;
  @ signals(E e) s;
 a*/
T m(...);
```

```
exceptional_behavior = ensures false;
```



```
/*@ requires pre; //what is the caller's obligation?
  @ ensures post; //what must hold on normal termination?
  @ assignable a; //which locations may be assigned by m?
  @ diverges d; //when may m non-terminate?
  @ signals only E1, ..., En;
  @ signals(E e) s;
 a*/
T m(...);
```

```
signals (Exception e) false;
exceptional_behavior = ensures false;
```



```
/*@ requires r; //what is the caller's obligation?
  @ ensures post; //what must hold on normal termination?
  @ assignable a; //which locations may be assigned by m?
  @ diverges d; //when may m non-terminate?
  @ signals only E1, ..., En; //what exc-types may be thrown?
  @ signals(E e) s;
 a*/
T m(...);
```

```
signals (Exception e) false;
exceptional_behavior = ensures false;
```



```
/*@ requires pre; //what is the caller's obligation?
  @ ensures post; //what must hold on normal termination?
  @ assignable a; //which locations may be assigned by m?
  @ diverges d; //when may m non-terminate?
  @ signals only E1, ..., En; //what exc-types may be thrown?
  @ signals(E e) s; //what must hold when an E is thrown?
 a*/
T m(...);
```

```
signals (Exception e) false;
exceptional_behavior = ensures false;
```



```
/*@ requires pre; //what is the caller's obligation?
  @ ensures post; //what must hold on normal termination?
  @ assignable a; //which locations may be assigned by m?
  @ diverges d; //when may m non-terminate?
  @ signals only E1, ..., En; //what exc-types may be thrown?
  @ signals(E e) s; //what must hold when an E is thrown?
 a*/
T m(...);
```

#### **Implicitly**

```
normal_behavior
                        signals (Exception e) false;
exceptional behavior = ensures false;
```



```
/*@ requires pre; //what is the caller's obligation?
@ ensures post; //what must hold on normal termination?
@ assignable a; //which locations may be assigned by m?
@ diverges d; //when may m non-terminate?
@ signals_only E1,...,En; //what exc-types may be thrown?
@ signals(E e) s; //what must hold when an E is thrown?
@*/
T m(...);
```

#### **Implicitly**

```
normal_behavior = signals(Exception e) false;
exceptional_behavior = ensures false;
```

The keyword also separates the contracts of a method Shmuel Tyszberowicz based on materials by Bernhard Beckert · Vladimir Klebanov –



```
/*@ requires pre; //what is the caller's obligation?
  @ ensures post; //what must hold on normal termination?
  @ assignable a; //which locations may be assigned by m?
  @ diverges d; //when may m non-terminate?
  @ signals only E1, ..., En; //what exc-types may be thrown?
  @ signals(E e) s; //what must hold when an E is thrown?
 (a*/
T m(...);
```

#### **Implicitly**

```
normal_behavior
                        signals (Exception e) false;
exceptional_behavior = ensures false;
```

The keyword also separates the contracts of a method Shmuel Tyszberowicz based on materials by Bernhard Beckert - Vladimir Klebanov —

#### **Class Invariants**



```
//@ invariant i;
```

- Express global consistency properties
  - Not specific to a particular method
- Must always hold

#### **Class Invariants**



```
//@ invariant i;
```

- Express global consistency properties
  - Not specific to a particular method
- Must always hold

#### **Class Invariants**



```
//@ invariant i;
```

- Express global consistency properties
  - Not specific to a particular method
- Must always hold

#### **Pure Methods**



Pure methods terminate and have no side effects

```
\texttt{`pure'} \approx \texttt{`diverges false;'} + \texttt{`assignable} \setminus \texttt{nothing;'}
```

After declaring

```
public /*@ pure @*/ boolean cardIsInserted() {
   return insertedCard!=null;
}
```

cardIsInserted()

could replace

insertedCard != null

in JML annotations

#### **Pure Methods**



Pure methods terminate and have no side effects

```
'pure' pprox 'diverges false;' + 'assignable \nothing;'
```

After declaring

```
public /*@ pure @*/ boolean cardIsInserted() {
   return insertedCard!=null;
}
```

cardIsInserted()

could replace

insertedCard != null

#### **Pure Methods**



Pure methods terminate and have no side effects

```
'pure' \approx 'diverges false;' + 'assignable \nothing;'
```

After declaring

```
public /*@ pure @*/ boolean cardIsInserted() {
  return insertedCard!=null:
```

cardIsInserted()

could replace

insertedCard != null



- All Java expressions without side-effects
- ==>, <==>: implication, equivalence
- \forall, \exists
- \num\_of, \sum, \product, \min, \max
- ▶ \old(...): referring to pre-state in postconditions
- \result: referring to return value in postconditions



- All Java expressions without side-effects
- ==>, <==>: implication, equivalence
- \forall, \exists
- \num\_of, \sum, \product, \min, \max
- \old(...): referring to pre-state in postconditions
- \result: referring to return value in postconditions



- All Java expressions without side-effects
- ==>, <==>: implication, equivalence
- \forall, \exists
- \num\_of, \sum, \product, \min, \max
- ▶ \old(...): referring to pre-state in postconditions
- \result: referring to return value in postconditions



- All Java expressions without side-effects
- ==>, <==>: implication, equivalence
- \forall, \exists
- \num\_of, \sum, \product, \min, \max
- \old(...): referring to pre-state in postconditions
- \result: referring to return value in postconditions



- All Java expressions without side-effects
- ==>, <==>: implication, equivalence
- \forall, \exists
- $ightharpoonup \setminus \text{num\_of}, \setminus \text{sum}, \setminus \text{product}, \setminus \text{min}, \setminus \text{max}$
- \old(...): referring to pre-state in postconditions
- \result: referring to return value in postconditions



- All Java expressions without side-effects
- ==>, <==>: implication, equivalence
- \forall, \exists
- $ightharpoonup \setminus \text{num\_of}, \setminus \text{sum}, \setminus \text{product}, \setminus \text{min}, \setminus \text{max}$
- \old(...): referring to pre-state in postconditions
- \result: referring to return value in postconditions



```
(\forall int i; 0<=i && i<\result.length; \result[i]>0)
equivalent to
(\forall int i; 0<=i && i<\result.length ==> \result[i]>0
(\exists int i; 0<=i && i<\result.length; \result[i]>0)
equivalent to
(\exists int i; 0<=i && i<\result.length && \result[i]>0)
```

- Quantifiers bind two expressions: the range predicate and the body expression
- A missing range predicate is by default true



```
(\forall int i; 0<=i && i<\result.length; \result[i]>0)
equivalent to
(\forall int i; 0<=i && i<\result.length ==> \result[i]>0)
(\exists int i; 0<=i && i<\result.length; \result[i]>0)
equivalent to
(\exists int i; 0<=i && i<\result.length && \result[i]>0)
```

- Quantifiers bind two expressions: the range predicate and the body expression
- A missing range predicate is by default true



```
(\forall int i; 0<=i && i<\result.length; \result[i]>0)
equivalent to
(\forall int i; 0<=i && i<\result.length ==> \result[i]>0)
(\exists int i; 0<=i && i<\result.length; \result[i]>0)
equivalent to
(\exists int i; 0<=i && i<\result.length && \result[i]>0)
```

- Quantifiers bind two expressions: the range predicate and the body expression
- A missing range predicate is by default true



```
(\forall int i; 0<=i && i<\result.length; \result[i]>0)
equivalent to
(\forall int i; 0<=i && i<\result.length ==> \result[i]>0)
(\exists int i; 0<=i && i<\result.length; \result[i]>0)
equivalent to
(\exists int i; 0<=i && i<\result.length && \result[i]>0)
```

- Quantifiers bind two expressions: the range predicate and the body expression
- A missing range predicate is by default true



```
(\forall int i; 0<=i && i<\result.length; \result[i]>0)
equivalent to
(\forall int i; 0<=i && i<\result.length ==> \result[i]>0)
(\exists int i; 0<=i && i<\result.length; \result[i]>0)
equivalent to
(\exists int i; 0<=i && i<\result.length && \result[i]>0)
```

- Quantifiers bind two expressions: the range predicate and the body expression
- A missing range predicate is by default true



```
(\forall int i; 0<=i && i<\result.length; \result[i]>0)
equivalent to
(\forall int i; 0<=i && i<\result.length ==> \result[i]>0)
(\exists int i; 0<=i && i<\result.length; \result[i]>0)
equivalent to
(\exists int i; 0<=i && i<\result.length && \result[i]>0)
```

- Quantifiers bind two expressions: the range predicate and the body expression
- A missing range predicate is by default true



```
(\forall int i; 0<=i && i<\result.length; \result[i]>0)
equivalent to
(\forall int i; 0<=i && i<\result.length ==> \result[i]>0)
(\exists int i; 0<=i && i<\result.length; \result[i]>0)
equivalent to
(\exists int i; 0<=i && i<\result.length && \result[i]>0)
```

- Quantifiers bind two expressions: the range predicate and the body expression
- A missing range predicate is by default true



```
(\forall int i; 0<=i && i<\result.length; \result[i]>0)
equivalent to
(\forall int i; 0<=i && i<\result.length ==> \result[i]>0)
(\exists int i; 0<=i && i<\result.length; \result[i]>0)
equivalent to
(\exists int i; 0<=i && i<\result.length && \result[i]>0)
```

- Quantifiers bind two expressions: the range predicate and the body expression
- A missing range predicate is by default true

# Generalized and Numerical Quantifiers



# The assignable Clause



- Specifies frame conditions
- Locations in this (comma-separated) may be assigned to
- List of:
  - e.f (where f a field)

# The assignable Clause



- Specifies frame conditions
- Locations in this (comma-separated) may be assigned to
- List of:
  - e.f (where f a field)
  - a[\*], a[x..y] (where a an array expression)

# The assignable Clause



- Specifies frame conditions
- Locations in this (comma-separated) may be assigned to
- List of:
  - e.f (where f a field)
  - a[\*], a[x..y] (where a an array expression)
  - \nothing, \everything (default)



```
diverges e;
```

with a boolean JML expression e specifies that the method may not terminate only when e is true in the pre-state

#### Examples

diverges false;

The method must always terminate

diverges true;

The method may terminate or not

diverges n == 0;

The method must terminate, when called in a state with n! = 0



```
diverges e;
```

with a boolean JML expression e specifies that the method may not terminate only when e is true in the pre-state

#### Examples

diverges false;

The method must always terminate

diverges true;

The method may terminate or not

diverges n == 0;

The method must terminate, when called in a state with n!=0



```
diverges e;
```

with a boolean JML expression e specifies that the method may not terminate only when e is true in the pre-state

#### Examples

diverges false;

The method must always terminate

diverges true;

The method may terminate or not

diverges n == 0;

The method must terminate, when called in a state with n!=0



```
diverges e;
```

with a boolean JML expression e specifies that the method may not terminate only when e is true in the pre-state

#### Examples

diverges false;

The method must always terminate

diverges true;

The method may terminate or not

diverges n == 0;

The method must terminate, when called in a state with n!=0



```
ensures p;
signals_only ET1, ..., ETm;
signals (E1 e1) s1;
...
signals (En en) sn;
```

- Normal termination ⇒ p must hold (in post-state)
- Exception thrown  $\Rightarrow$  must be of type ET1, ..., or ETm
- Exception of type E1 thrown ⇒ s1 must hold (in post-state)

. . .

■ Exception of type En thrown ⇒ sn must hold (ir post-state)



```
ensures p;
signals_only ET1, ..., ETm;
signals (E1 e1) s1;
...
signals (En en) sn;
```

- Normal termination ⇒ p must hold (in post-state)
- Exception thrown  $\Rightarrow$  must be of type ET1, ..., or ETm
- Exception of type E1 thrown ⇒ s1 must hold (in post-state)

. . .

■ Exception of type En thrown ⇒ sn must hold (in post-state)



```
ensures p;
signals_only ET1, ..., ETm;
signals (E1 e1) s1;
...
signals (En en) sn;
```

- Normal termination ⇒ p must hold (in post-state)
- Exception thrown ⇒ must be of type ET1, ..., or ETm
- Exception of type E1 thrown ⇒ s1 must hold (in post-state)
  - . . .
- Exception of type En thrown ⇒ sn must hold (in post-state)



```
ensures p;
signals_only ET1, ..., ETm;
signals (E1 e1) s1;
...
signals (En en) sn;
```

- Normal termination ⇒ p must hold (in post-state)
- Exception thrown ⇒ must be of type ET1, ..., or ETm
- Exception of type E1 thrown ⇒ s1 must hold (in post-state)

■ Exception of type En thrown ⇒ sn must hold (in



```
ensures p;
signals_only ET1, ..., ETm;
signals (E1 e1) s1;
...
signals (En en) sn;
```

- Normal termination ⇒ p must hold (in post-state)
- Exception thrown ⇒ must be of type ET1, ..., or ETm
- Exception of type E1 thrown ⇒ s1 must hold (in post-state)

. . .

■ Exception of type En thrown ⇒ sn must hold (in post-state)



```
public interface IBonusCard {
 public void addBonus(int newBonusPoints);
```

How to add contracts to abstract methods in interfaces? Remember: There are no attributes in interfaces More precisely: Only static final fields



```
public interface IBonusCard {
 public void addBonus(int newBonusPoints);
```

How to add contracts to abstract methods in interfaces? Remember: There are no attributes in interfaces

More precisely: Only static final fields



```
public interface IBonusCard {
 public void addBonus(int newBonusPoints);
```

How to add contracts to abstract methods in interfaces? Remember: There are no attributes in interfaces



```
public interface IBonusCard {
 public void addBonus(int newBonusPoints);
```

How to add contracts to abstract methods in interfaces? Remember: There are no attributes in interfaces More precisely: Only static final fields

## **Model Fields**



```
public interface IBonusCard {
/*@ public instance model int bonusPoints; @*/
 public void addBonus(int newBonusPoints);
```

How to add contracts to abstract methods in interfaces? Remember: There are no attributes in interfaces More precisely: Only static final fields

## **Model Fields**



```
public interface IBonusCard {
/*@ public instance model int bonusPoints; @*/
/*@ ensures bonusPoints == \old(bonusPoints) +newBonusPoints;
 public void addBonus (int newBonusPoints);
```

How to add contracts to abstract methods in interfaces? Remember: There are no attributes in interfaces More precisely: Only static final fields

### **Model Fields**



```
public interface IBonusCard {
/*@ public instance model int bonusPoints; @*/
/*@ ensures bonusPoints == \old(bonusPoints) +newBonusPoints;
  @ assignable bonusPoints;
  a*/
 public void addBonus (int newBonusPoints);
```

How to add contracts to abstract methods in interfaces? Remember: There are no attributes in interfaces More precisely: Only static final fields

## Implementing Interfaces



```
public interface IBonusCard {
    /*@ public instance model int bonusPoints; @*/
    /*@ ... @*/
    public void addBonus(int newBonusPoints);
```

#### **Implementation**

```
public class BankCard implements IBonusCard{
    public int bankCardPoints;
/*@ private represents bonusPoints = bankCardPoints; @*/
    public void addBonus(int newBonusPoints) {
        bankCardPoints += newBonusPoints; }
}
```

# Implementing Interfaces



```
public interface IBonusCard {
    /*@ public instance model int bonusPoints; @*/
    /*@ ... @*/
    public void addBonus(int newBonusPoints);
```

#### Implementation

```
public class BankCard implements IBonusCard{
    public int bankCardPoints;

public void addBonus(int newBonusPoints) {
    bankCardPoints += newBonusPoints; }
}
```

## Implementing Interfaces



```
public interface IBonusCard {
    /*@ public instance model int bonusPoints; @*/
    /*@ ... @*/
    public void addBonus(int newBonusPoints);
```

#### Implementation

```
public class BankCard implements IBonusCard{
    public int bankCardPoints;
/*@ private represents bonusPoints = bankCardPoints; @*/
    public void addBonus(int newBonusPoints) {
        bankCardPoints += newBonusPoints; }
}
```

## **Other Representations**



```
/*@ private represents bonusPoints
= bankCardPoints; @*/
```

```
/*@ private represents bonusPoints
= bankCardPoints * 100; @*/
```

```
/*@ represents x \such_that A(x); @*/
```

## **Other Representations**



```
/*@ private represents bonusPoints
= bankCardPoints; @*/
```

```
/*@ private represents bonusPoints
= bankCardPoints * 100; @*/
```

```
/*@ represents x \such_that A(x); @*/
```

## **Other Representations**



```
/*@ private represents bonusPoints
= bankCardPoints; @*/
```

```
/*@ private represents bonusPoints
= bankCardPoints * 100; @*/
```

```
/*@ represents x \such_that A(x); @*/
```

# Inheritance of Specifications in JML



- An invariant to a class is inherited by all its subclasses
- An operation contract is inherited by all overridden methods
  - It can be extended there

# Inheritance of Specifications in JML



- An invariant to a class is inherited by all its subclasses
- An operation contract is inherited by all overridden methods
  - It can be extended there

# Inheritance of Specifications in JML



- An invariant to a class is inherited by all its subclasses
- An operation contract is inherited by all overridden methods
  - It can be extended there



- loop invariants //@ loop\_invariant p;
- data groups
- assertions //@ assert e;
- many more...



- loop invariants //@ loop\_invariant p;
- data groups
- assertions //@ assert e;
- many more...



- loop invariants //@ loop\_invariant p;
- data groups
- assertions //@ assert e;
- many more...



- loop invariants //@ loop\_invariant p;
- data groups
- assertions //@ assert e;
- many more...

# **Problems with Specifications Using** Integers



```
/*@ requires y >= 0;
  @ ensures \result >= 0;
  @ ensures \result * \result <= y;</pre>
  @ ensures (\result+1) * (\result+1) > y;
  a */
 public static int isqrt(int y)
```

Shmuel Tyszberowicz based on materials by Bernhard Beckert - Vladimir Klebanov – Applications of Formal Verification

# **Problems with Specifications Using Integers**



```
/*@ requires y >= 0;
@ ensures \result >= 0;
@ ensures \result * \result <= y;
@ ensures (\result+1) * (\result+1) > y;
@ */
public static int isqrt(int y)
```

For y=1 and  $\result=1073741821=\frac{1}{2}(MAX\_INT-5)$  the above postcondition is true, though 1073741821 is not a square root of 1

JML uses the Java semantics of integers:

```
1073741821 * 1073741821 = -2147483639

1073741822 * 1073741822 = 4
```

Shmuel Tyszberowicz based on materials by Bernhard Beckert · Vladimir Klebanov –

# **Problems with Specifications Using** Integers



```
/*@ requires y >= 0;
  @ ensures \result >= 0;
  @ ensures \result * \result <= y;</pre>
  @ ensures (\result+1) * (\result+1) > y;
  a */
 public static int isqrt(int y)
```

For y = 1 and  $\result = 1073741821 = \frac{1}{2}(MAX\_INT - 5)$  the above postcondition is true, though 1073741821 is not a square root of 1

JML uses the Java semantics of integers:

```
1073741821 * 1073741821 = -2147483639
1073741822 * 1073741822 = 4
```

Shmuel Tyszberowicz based on materials by Bernhard Beckert · Vladimir Klebanov – Applications of Formal Verification

# **Problems with Specifications Using Integers**



```
/*@ requires y >= 0;
@ ensures \result >= 0;
@ ensures \result * \result <= y;
@ ensures (\result+1) * (\result+1) > y;
@ */
public static int isqrt(int y)
```

For y=1 and  $\result=1073741821=\frac{1}{2}(MAX\_INT-5)$  the above postcondition is true, though 1073741821 is not a square root of 1

JML uses the Java semantics of integers:

```
1073741821 * 1073741821 = -2147483639

1073741822 * 1073741822 = 4
```

The JML type \bigint provides arbitrary precision integers



#### Many tools support JML (see JML homepage); among them:

- jml: JML syntax checker
- jmldoc: code documentation (like Javadoc)
- jmlc: compiles Java+JML into bytecode with assertion checks
- jmlunit: unit testing (like JUnit)
- rac: runtime assertion checker
- ESC/Java2: leightweight static verification
- KeY: full static verification
- ...



#### Many tools support JML (see JML homepage); among them:

- jml: JML syntax checker
- jmldoc: code documentation (like Javadoc)
- jmlc: compiles Java+JML into bytecode with assertion checks
- jmlunit: unit testing (like JUnit)
- rac: runtime assertion checker
- ESC/Java2: leightweight static verification
- KeY: full static verification
- ...



Many tools support JML (see JML homepage); among them:

- jml: JML syntax checker
- jmldoc: code documentation (like Javadoc)
- jmlc: compiles Java+JML into bytecode with assertion checks
- jmlunit: unit testing (like JUnit)
- rac: runtime assertion checker
- ESC/Java2: leightweight static verification
- KeY: full static verification
- **...**



Many tools support JML (see JML homepage); among them:

- jml: JML syntax checker
- jmldoc: code documentation (like Javadoc)
- jmlc: compiles Java+JML into bytecode with assertion checks
- jmlunit: unit testing (like JUnit)
- rac: runtime assertion checker
- ESC/Java2: leightweight static verification
- KeY: full static verification
- . . . .



Many tools support JML (see JML homepage); among them:

- jml: JML syntax checker
- jmldoc: code documentation (like Javadoc)
- jmlc: compiles Java+JML into bytecode with assertion checks
- jmlunit: unit testing (like JUnit)
- rac: runtime assertion checker
- ESC/Java2: leightweight static verification
- KeY: full static verification
- ...



Many tools support JML (see JML homepage); among them:

- jml: JML syntax checker
- jmldoc: code documentation (like Javadoc)
- jmlc: compiles Java+JML into bytecode with assertion checks
- jmlunit: unit testing (like JUnit)
- rac: runtime assertion checker
- ESC/Java2: leightweight static verification
- KeY: full static verification
- **.** . . .



Many tools support JML (see JML homepage); among them:

- jml: JML syntax checker
- jmldoc: code documentation (like Javadoc)
- jmlc: compiles Java+JML into bytecode with assertion checks
- jmlunit: unit testing (like JUnit)
- rac: runtime assertion checker
- ESC/Java2: leightweight static verification
- KeY: full static verification
- . . . .



Many tools support JML (see JML homepage); among them:

- jml: JML syntax checker
- jmldoc: code documentation (like Javadoc)
- jmlc: compiles Java+JML into bytecode with assertion checks
- jmlunit: unit testing (like JUnit)
- rac: runtime assertion checker
- ESC/Java2: leightweight static verification
- KeY: full static verification
- **.**..



Many tools support JML (see JML homepage); among them:

- jml: JML syntax checker
- jmldoc: code documentation (like Javadoc)
- jmlc: compiles Java+JML into bytecode with assertion checks
- jmlunit: unit testing (like JUnit)
- rac: runtime assertion checker
- ESC/Java2: leightweight static verification
- KeY: full static verification
- **.** . . .