


# Chapter 8: Deadlocks

---





# Chapter 8: Deadlocks

---

- System Model
- Deadlock in Multithreaded Applications
- Deadlock Characterization
- Methods for Handling Deadlocks
- Deadlock Prevention
- Deadlock Avoidance
- Deadlock Detection
- Recovery from Deadlock





# Chapter Objectives

---

- Illustrate how deadlock can occur when mutex locks are used
- Define the four necessary conditions that characterize deadlock
- Identify a deadlock situation in a resource allocation graph
- Evaluate the four different approaches for preventing deadlocks
- Apply the banker's algorithm for deadlock avoidance
- Apply the deadlock detection algorithm
- Evaluate approaches for recovering from deadlock





# System Model

---

- System consists of resources
- Resource types  $R_1, R_2, \dots, R_m$   
*CPU cycles, memory space, I/O devices*
- Each resource type  $R_i$  has  $W_i$  instances.
- Each process utilizes a resource as follows:
  - **request**
  - **use**
  - **release**





# Deadlock Characterization

Deadlock can arise if four conditions hold simultaneously.

- **Mutual exclusion:** only one process at a time can use a resource
- **Hold and wait:** a process holding at least one resource is waiting to acquire additional resources held by other processes
- **No preemption:** a resource can be released only voluntarily by the process holding it, after that process has completed its task
- **Circular wait:** there exists a set  $\{P_0, P_1, \dots, P_n\}$  of waiting processes such that  $P_0$  is waiting for a resource that is held by  $P_1$ ,  $P_1$  is waiting for a resource that is held by  $P_2$ , ...,  $P_{n-1}$  is waiting for a resource that is held by  $P_n$ , and  $P_n$  is waiting for a resource that is held by  $P_0$ .





# Resource-Allocation Graph

A set of vertices  $V$  and a set of edges  $E$ .


- $V$  is partitioned into two types:
  - $P = \{P_1, P_2, \dots, P_n\}$ , the set consisting of all the processes in the system
  - $R = \{R_1, R_2, \dots, R_m\}$ , the set consisting of all resource types in the system
- **request edge** – directed edge  $P_i \rightarrow R_j$
- **assignment edge** – directed edge  $R_j \rightarrow P_i$





# Resource-Allocation Graph (Cont.)


- Process




- Resource Type with 4 instances



- $P_i$  requests instance of  $R_j$




- $P_i$  is holding an instance of  $R_j$





# Resource Allocation Graph Example


- One instance of R1
- Two instances of R2
- One instance of R3
- Three instance of R4
- T1 holds one instance of R2 and is waiting for an instance of R1
- T2 holds one instance of R1, one instance of R2, and is waiting for an instance of R3
- T3 is holds one instance of R3








# Resource Allocation Graph With A Deadlock





# Graph With A Cycle But No Deadlock





# Basic Facts

---

- If graph contains no cycles  $\Rightarrow$  no deadlock
- If graph contains a cycle  $\Rightarrow$ 
  - if only one instance per resource type, then deadlock
  - if several instances per resource type, possibility of deadlock





# Methods for Handling Deadlocks

---

- Ensure that the system will *never* enter a deadlock state:
  - Deadlock prevention
  - Deadlock avoidance
- Allow the system to enter a deadlock state and then recover
- Ignore the problem and pretend that deadlocks never occur in the system.





# Deadlock Prevention

---

Invalidate one of the four necessary conditions for deadlock:

- **Mutual Exclusion** – not required for sharable resources (e.g., read-only files); must hold for non-sharable resources
- **Hold and Wait** – must guarantee that whenever a process requests a resource, it does not hold any other resources
  - Require process to request and be allocated all its resources before it begins execution, or allow process to request resources only when the process has none allocated to it.
  - Low resource utilization; starvation possible





# Deadlock Prevention (Cont.)

## ■ No Preemption –

- If a process that is holding some resources requests another resource that cannot be immediately allocated to it, then all resources currently being held are released
- Preempted resources are added to the list of resources for which the process is waiting
- Process will be restarted only when it can regain its old resources, as well as the new ones that it is requesting

## ■ Circular Wait – impose a total ordering of all resource types, and require that each process requests resources in an increasing order of enumeration

▶ Normally define a function:

–  $F:R \rightarrow N$ , **F: function**, **R: resources**, **N : natural numbers**

▶ **Example:** if resources={tape drive, disk drive, printer}

–  $F(\text{tape drive})=1$ ,  $F(\text{printer})=11$ ,  $F(\text{disk drive})=5$

– If a process wants to use the tape drive and the printer, it should first request the tape drive, then the printer

– Whenever a process requests a resource  $R_i$ , it must release all **resources  $R_j$  with,  $F(R_j) \geq F(R_i)$ .**

– With this rule, **a circular wait is impossible**






# Circular Wait

- Invalidating the circular wait condition is most common.
- Simply assign each resource (i.e. mutex locks) a unique number.
- Resources must be acquired in order.
- If:

`first_mutex = 1`  
`second_mutex = 5`

code for `thread_two` could not be written as follows:



```
/* thread.one runs in this function */
void *do_work_one(void *param)
{
    pthread_mutex_lock(&first_mutex);
    pthread_mutex_lock(&second_mutex);
    /**
     * Do some work
     */
    pthread_mutex_unlock(&second_mutex);
    pthread_mutex_unlock(&first_mutex);

    pthread_exit(0);
}

/* thread.two runs in this function */
void *do_work_two(void *param)
{
    pthread_mutex_lock(&second_mutex);
    pthread_mutex_lock(&first_mutex);
    /**
     * Do some work
     */
    pthread_mutex_unlock(&first_mutex);
    pthread_mutex_unlock(&second_mutex);

    pthread_exit(0);
}
```





# Deadlock Avoidance

---

Requires that the system has some additional *a priori* information available

- Simplest and most useful model requires that each process declare the *maximum number* of resources of each type that it may need
- The deadlock-avoidance algorithm **dynamically** examines the **resource-allocation state** to ensure that there **can never be a circular-wait condition**
- **Resource-allocation state** is defined by the number of available and allocated resources, and the maximum demands of the processes







# Safe State

- When a process requests an available resource, system must decide if immediate allocation leaves the system in a safe state
- System is in **safe state** if there exists a sequence  $\langle P_1, P_2, \dots, P_n \rangle$  of ALL the processes in the systems such that for each  $P_i$ , the resources that  $P_i$  can still request can be satisfied by currently available resources + resources held by all the  $P_j$  with  $j < i$
- That is:
  - If  $P_i$  resource needs are not immediately available, then  $P_i$  can wait until all  $P_j$  have finished
  - When  $P_j$  is finished,  $P_i$  can obtain needed resources, execute, return allocated resources, and terminate
  - When  $P_i$  terminates,  $P_{i+1}$  can obtain its needed resources, and so on
- **A state is safe** if the system can allocate resources to each process in some order (safe sequence) avoiding a deadlock.
- **A deadlock** is unsafe state





# Example

- Consider a system that has 12 tape drives and 3 processes p0, p1, p2. Assume, we know the maximum number of the tape drives each process may request as:
  - P0 requires 10 tape drives
  - P1 requires 4 tape drives
  - Pp2 requires 9 tape drives
  - Initially 9 tape drives are allocated as follows”
    - ▶  $P0 \leftarrow 5, p1 \leftarrow 2, p2 \leftarrow 2$

Processes	Allocated	Max.Need	Current Need	Available
P0	5	10	5	3
P1	2	4	2	
P2	2	9	7	

- ▶
  - Current *Need* = *Max*[ Need– *Allocated*
  - ▶ **P1 will continue, when it finishes, P0 might continue and when it finishes P2 might continue.**
  - ▶ **Safe sequence is p1, p0, p2**





# Basic Facts


---

- If a system is in **safe state**  $\Rightarrow$  **no deadlocks**
- If a system is in unsafe state  $\Rightarrow$  **possibility of deadlock**
- **Avoidance**  $\Rightarrow$  ensure that a system will never enter an unsafe state.





# Safe, Unsafe, Deadlock State





# Avoidance Algorithms

---

- Single instance of a resource type
  - Use a resource-allocation graph
- Multiple instances of a resource type
  - Use the Banker's Algorithm





# Resource-Allocation Graph Scheme


---

- **Claim edge**  $P_i \rightarrow R_j$  indicated that process  $P_i$  may request resource  $R_j$ ; represented by a dashed line
- Claim edge converts to request edge when a process requests a resource
- Request edge converted to an assignment edge when the resource is allocated to the process
- When a resource is released by a process, assignment edge reconverts to a claim edge
- Resources must be claimed *a priori* in the system






# Resource-Allocation Graph





# Unsafe State In Resource-Allocation Graph







# Resource-Allocation Graph Algorithm

---

- Suppose that process  $P_i$  requests a resource  $R_j$
- The request can be granted **only if converting the request edge to an assignment edge does not result in the formation of a cycle** in the resource allocation graph





# Banker's Algorithm

---

- Multiple instances of resources
- Each process must a priori claim maximum use
- When a process requests a resource it may have to wait
- When a process gets all its resources it must return them in a finite amount of time





# Data Structures for the Banker's Algorithm

Let  $n$  = number of processes, and  $m$  = number of resources types.

Ex.  $M=3$ ,  $R=\{R1,R2,R3\}=\{3,2,5\}$ ; // instances for each resource type

- **Available:** Vector of length  $m$ . If available  $[j] = k$ , there are  $k$  instances of resource type  $R_j$  available
- **Max:**  $n \times m$  matrix. If  $Max[i,j] = k$ , then process  $P_i$  may request at most  $k$  instances of resource type  $R_j$
- **Allocation:**  $n \times m$  matrix. If  $Allocation[i,j] = k$  then  $P_i$  is currently allocated  $k$  instances of  $R_j$
- **Need:**  $n \times m$  matrix. If  $Need[i,j] = k$ , then  $P_i$  may need  $k$  more instances of  $R_j$  to complete its task

$$Need[i,j] = Max[i,j] - Allocation[i,j]$$





# Safety Algorithm

1. Let **Work** and **Finish** be vectors of length  $m$  and  $n$ , respectively.  
Initialize:

**$Work = Available$**

**$Finish[i] = false$  for  $i = 0, 1, \dots, n-1$**

2. Find an  $i$  such that both:

(a)  **$Finish[i] = false$**

(b)  **$Need_i \leq Work$**

If no such  $i$  exists, go to step 4

3.  **$Work = Work + Allocation_i$**   
 **$Finish[i] = true$**   
go to step 2

4. If  **$Finish[i] == true$**  for all  $i$ , then the system is in a safe state





# Resource-Request Algorithm for Process $P_i$

**$Request_i$**  = request vector for process  $P_i$ . If  **$Request_i[j] = k$**  then process  $P_i$  wants  $k$  instances of resource type  $R_j$

1. If  **$Request_i \leq Need_i$** , go to step 2. Otherwise, raise error condition, since process has exceeded its maximum claim
2. If  **$Request_i \leq Available$** , go to step 3. Otherwise  $P_i$  must wait, since resources are not available
3. Pretend to allocate requested resources to  $P_i$  by modifying the state as follows:

$$Available = Available - Request_i;$$

$$Allocation_i = Allocation_i + Request_i;$$

$$Need_i = Need_i - Request_i;$$

- If safe  $\Rightarrow$  the resources are allocated to  $P_i$
- If unsafe  $\Rightarrow P_i$  must wait, and the old resource-allocation state is restored





# Example of Banker's Algorithm

- 5 processes  $P_0$  through  $P_4$ ;

3 resource types:

$A$  (10 instances),  $B$  (5 instances), and  $C$  (7 instances)

- Snapshot at time  $T_0$ :

	<u>Allocation</u>	<u>Max</u>	<u>Available</u>
	$A \ B \ C$	$A \ B \ C$	$A \ B \ C$
$P_0$	0 1 0	7 5 3	3 3 2
$P_1$	2 0 0	3 2 2	
$P_2$	3 0 2	9 0 2	
$P_3$	2 1 1	2 2 2	
$P_4$	0 0 2	4 3 3	





## Example (Cont.)

- The content of the matrix ***Need*** is defined to be ***Max – Allocation***

	<u><i>Need</i></u>		
	<i>A</i>	<i>B</i>	<i>C</i>
$P_0$	7	4	3
$P_1$	1	2	2
$P_2$	6	0	0
$P_3$	0	1	1
$P_4$	4	3	1

- The system is in a safe state since the sequence  $\langle P_1, P_3, P_4, P_2, P_0 \rangle$  satisfies safety criteria





## Example: $P_1$ Request (1,0,2)

- Check that Request  $\leq$  Available (that is,  $(1,0,2) \leq (3,3,2) \Rightarrow$  true

	<u>Allocation</u>	<u>Need</u>	<u>Available</u>
	<i>A B C</i>	<i>A B C</i>	<i>A B C</i>
$P_0$	0 1 0	7 4 3	2 3 0
$P_1$	3 0 2	0 2 0	
$P_2$	3 0 2	6 0 0	
$P_3$	2 1 1	0 1 1	
$P_4$	0 0 2	4 3 1	

- Executing safety algorithm shows that sequence  $\langle P_1, P_3, P_4, P_0, P_2 \rangle$  satisfies safety requirement
- Can request for (3,3,0) by  $P_4$  be granted?
- Can request for (0,2,0) by  $P_0$  be granted?







# Deadlock Detection

---

- Allow system to enter deadlock state
- Detection algorithm
- Recovery scheme





# Single Instance of Each Resource Type


---

- Maintain **wait-for** graph
  - Nodes are processes
  - $P_i \rightarrow P_j$  if  $P_i$  is waiting for  $P_j$
- Periodically invoke an algorithm that searches for a cycle in the graph. If there is a cycle, there exists a deadlock
- An algorithm to detect a cycle in a graph requires an order of  $n^2$  operations, where  $n$  is the number of vertices in the graph






# Resource-Allocation Graph and Wait-for Graph



Resource-Allocation Graph



Corresponding wait-for graph





# Several Instances of a Resource Type

- **Available:** A vector of length  $m$  indicates the number of available resources of each type
- **Allocation:** An  $n \times m$  matrix defines the number of resources of each type currently allocated to each process
- **Request:** An  $n \times m$  matrix indicates the current request of each process. If  $Request[i][j] = k$ , then process  $P_i$  is requesting  $k$  more instances of resource type  $R_j$





# Detection Algorithm

1. Let ***Work*** and ***Finish*** be vectors of length ***m*** and ***n***, respectively  
Initialize:
  - (a) ***Work* = Available**
  - (b) For ***i* = 1, 2, ..., n**, if ***Allocation<sub>i</sub> ≠ 0***, then  
***Finish[i] = false***; otherwise, ***Finish[i] = true***
2. Find an index ***i*** such that both:
  - (a) ***Finish[i] == false***
  - (b) ***Request<sub>i</sub> ≤ Work***If no such ***i*** exists, go to step 4
3. ***Work = Work + Allocation<sub>i</sub>***  
***Finish[i] = true***  
go to step 2
4. If ***Finish[i] == false***, for some ***i***,  $1 \leq i \leq n$ , then the system is in  
deadlock state. Moreover, if ***Finish[i] == false***, then ***P<sub>i</sub>*** is deadlocked

**Algorithm requires an order of  $O(m \times n^2)$  operations to detect whether the system is in deadlocked state**






# Example of Detection Algorithm

- Five processes  $P_0$  through  $P_4$ ; three resource types A (7 instances), B (2 instances), and C (6 instances)
- Snapshot at time  $T_0$ :

	<u>Allocation</u>	<u>Request</u>	<u>Available</u>
	<i>A B C</i>	<i>A B C</i>	<i>A B C</i>
$P_0$	0 1 0	0 0 0	0 0 0
$P_1$	2 0 0	2 0 2	
$P_2$	3 0 3	0 0 0	
$P_3$	2 1 1	1 0 0	
$P_4$	0 0 2	0 0 2	

What is the execution sequence of these processes that will lead the system in safe state?

- Sequence  $\langle P_0, P_2, P_3, P_4, P_1 \rangle$  will result in  $Finish[i] = true$  for all  $i$





# Solution

- Finish=[f, f, f, f, f] and work= available=[0 0 0]
- P0: finish[0]= false and request(0)≤work
  - Work=work+allocation[0]=[0 0 0]+[0 1 0]=[0 1 0]
  - Finish[0]=true
- P1: finish[1]=false but request(1)>work
- P2: finish[2]=false and request(2)≤work
  - Work=[0 1 0]+[3 0 3]=[3 1 3]
  - finish[2]=true
- P3: finish[3]=false and request(3)≤work
  - Work=[3 1 3]+[2 1 1]=[5 2 4]
  - finish[3]=true
- P4: finish[4]=false and request(4)≤work
  - Work=[5 2 4]+[0 0 2]=[5 2 6]
  - finish[4]=true
- P1: finish[1]=false and request(1)≤work
  - Work=[5 2 6]+[2 0 2]=[7 2 8]
  - finish[1]=true

Finish[i]=true for i=0 to 4  
Safe sequence:  $P_0, P_2, P_3, P_4, P_1$





## Example (Cont.)

- $P_2$  requests an additional instance of type  $C$

	<u>Request</u>		
	$A$	$B$	$C$
$P_0$	0	0	0
$P_1$	2	0	2
$P_2$	0	0	1
$P_3$	1	0	0
$P_4$	0	0	2

- State of system?
  - Can reclaim resources held by process  $P_0$ , but insufficient resources to fulfill other processes; requests
  - Deadlock exists, consisting of processes  $P_1$ ,  $P_2$ ,  $P_3$ , and  $P_4$







# Detection-Algorithm Usage

---

- When, and how often, to invoke depends on:
  - How often a deadlock is likely to occur?
  - How many processes will need to be rolled back?
    - ▶ one for each disjoint cycle
- If detection algorithm is invoked arbitrarily, there may be many cycles in the resource graph and so we would not be able to tell which of the many deadlocked processes “caused” the deadlock.





# Recovery from Deadlock: Process Termination

---

- Abort all deadlocked processes
- Abort one process at a time until the deadlock cycle is eliminated
- In which order should we choose to abort?
  1. Priority of the process
  2. How long process has computed, and how much longer to completion
  3. Resources the process has used
  4. Resources process needs to complete
  5. How many processes will need to be terminated
  6. Is process interactive or batch?





# Recovery from Deadlock: Resource Preemption

---

- **Selecting a victim** – minimize cost
- **Rollback** – return to some safe state, restart process for that state
- **Starvation** – same process may always be picked as victim, include number of rollback in cost factor



# End of Chapter 8

---

