Hydraulic Fracturing Fluid Product Component Information Disclosure: Maximum Ingredient Weight in Pounds Format

	09/07/2012
Last Fracture Date	
State:	California
County:	Kern
API Number:	04-030-47533
Operator Name:	Aera Energy Llc
Well Name and Number:	Lost Hills One 6397
Longitude:	-119.7220982
Latitude:	35.6068079
Long/Lat Projection:	NAD83
Production Type:	Oil
True Vertical Depth (TVD):	2,360
Total Chemical Mass (lbs)*:	1,132,159
Total Max. Ingredient Mass (Ibs)*:	1,132,697
Total Product Volume (gal)*:	112,690
Total Water Volume (gal)*:	98,112



Hydraulic Fracturing Fluid Composition:

Trade Name	Supplier	Purpose	Ingredients	Chemical Abstract Service Number (CAS #)	Maximum Ingredient Concentration in Additive (% by mass)**	Maximum Ingredient Weight in HF Fluid (Ibs mass)	Comments
Water	Operator	Carrier	Water	7732-18-5	100.00%	818,038	
X-Cide 207	Baker Hughes	Biocide	2-Methyl-4-Isothiazolin-3-One	2682-20-4	5.00%	1.200000	
			5-Chloro-2-Methyl-4-Isothiazolin-3-One	26172-55-4	10.00%	2.400000	
			Crystalline Silica: Cristobalite	14464-46-1	1.00%	0.240000	
			Crystalline Silica: Quartz (SiO2)	14808-60-7	1.00%	0.240000	
			Diatomaceous Earth, Calcined	91053-39-3	60.00%	14.400000	
			Magnesium Chloride	7786-30-3	5.00%	1.200000	

			Magnesium Nitrate	10377-60-3	10.00%	2.400000
Enzyme G-I	Baker Hughes	Breaker	Hemicellulase Enzyme Concentrate	9025-56-3	3.00%	15.258174 SmartCare Product
			Water	7732-18-5	97.00%	493.347626
BF-8L	Baker Hughes	Buffer	Monoethanolamine	141-43-5	85.00%	956.243736
Clay Master-5C (Tote)	Baker Hughes	Clay Control	Oxyakylated Amine Quat	138879-94-4	60.00%	200.682960
XLW-4	Baker Hughes	Crosslinker	Sodium Borate Decahydrate	1303-96-4	30.00%	118.660752 SmartCare Product
GW-3LDF	Baker Hughes	Gelling Agent	1-Butoxy-2-Propanol	5131-66-8	5.00%	155.034000 SmartCare Product
			Cyrstalline Silica, Quartz (SiO2)	14808-60-7	5.00%	155.034000
			Guar Gum	9000-30-0	60.00%	1,860.408000
			Isotridecanol, ethoxylated	9043-30-5	5.00%	155.034000
			Paraffinic Petroleum Distillate	64742-55-8	30.00%	930.204000
			Petroleum Distillates	64742-47-8	30.00%	930.204000
Ferrotrol 300L (Totes)	Baker Hughes	Iron Control	Citric Acid	77-92-9	60.00%	151.304112 SmartCare Product
Sand, Brown, 8/40	Baker Hughes	Proppant	Crystalline Silica (Quartz)	14808-60-7	100.00%	308,280.000000
ScaleSorb 3, (25# pail)	Baker Hughes	Scale Inhibitor	Amino Alkyl Phosphonic Acid	Trade Secret	30.00%	30.000000 SmartCare Product
			Crystalline Silica: Quartz (SiO2)	14808-60-7	1.00%	1.000000
			Diatomaceous Earth, Calcined	91053-39-3	100.00%	100.000000
			Phosphonic Acid	13598-36-2	1.00%	1.000000
Ingredients shown abo	ove are subject	to 29 CFR 1910.1200(i	and appear on Material Safety Data She	eets (MSDS). Ingredients s	hown below are Non-I	MSDS.
			2-Butoxy-1-Propanol	15821-83-7		2.480544
			Glycerin	56-81-5		
			Water	7732-18-5		100.869408

^{*} Total Chemical Mass is the total amount of Trade Name volume, supplied to the customer, converted to pounds.

Ingredient information for chemicals subject to 29 CFR 1910.1200(i) and Appendix D are obtained from suppliers Material Safety Data Sheets (MSDS)

^{*} Total Max. Ingredient Mass is the summation of all masses listed in the Maximum Ingredient Weight (pounds) column.

^{*} Total Product Volume is the total amount of Water plus Trade Name volume in gallons supplied to the customer or Baker Hughes.

^{*} Total Water Volume is the total amount of water volume in gallons used on the hydraulic fracture treatment.

^{**} Information is based on the maximum potential for concentration and thus the total may be over 100%