## Hydraulic Fracturing Fluid Product Component Information Disclosure: Maximum Ingredient Weight in Pounds Format

	07/06/2012
Last Fracture Date	
State:	California
County:	Kern
API Number:	04-030-47148
Operator Name:	Aera Energy Llc
Well Name and Number:	Ellis 65DXR2-19
Longitude:	-119.7473779
Latitude:	35.4760315
Long/Lat Projection:	NAD83
Production Type:	Oil
True Vertical Depth (TVD):	1,950
Total Chemical Mass (lbs)*:	1,416,341
Total Max. Ingredient Mass (Ibs)*:	1,417,095
Total Product Volume (gal)*:	143,186
Total Water Volume (gal)*:	126,336



## Hydraulic Fracturing Fluid Composition:

Trade Name	Supplier	Purpose	Ingredients	Chemical Abstract Service Number (CAS #)	Maximum Ingredient Concentration in Additive (% by mass)**	Maximum Ingredient Weight in HF Fluid (Ibs mass)	Comments
Water	Operator	Carrier	Water	7732-18-5	100.00%	1,053,364	
X-Cide 207	Baker Hughes	Biocide	2-Methyl-4-Isothiazolin-3-One	2682-20-4	5.00%	1.800000	
			5-Chloro-2-Methyl-4-Isothiazolin-3-One	26172-55-4	10.00%	3.600000	
			Crystalline Silica: Cristobalite	14464-46-1	1.00%	0.360000	
			Crystalline Silica: Quartz (SiO2)	14808-60-7	1.00%	0.360000	
			Diatomaceous Earth, Calcined	91053-39-3	60.00%	21.600000	
			Magnesium Chloride	7786-30-3	5.00%	1.800000	

			Magnesium Nitrate	10377-60-3	10.00%	3.600000	
GBW-5	Baker Hughes	Breaker	Ammonium Persulfate	7727-54-0	100.00%		SmartCare Product
Enzyme G-I	Baker Hughes		Hemicellulase Enzyme Concentrate	9025-56-3	3.00%		SmartCare Product
,			Water	7732-18-5	97.00%	679.363944	
Clay Master-5C (Tote)	Baker Hughes	Clay Control	Oxyakylated Amine Quat	138879-94-4	60.00%	690.585480	
XLW-10A	Baker Hughes		Ethylene Glycol	107-21-1	30.00%		SmartCare Product
	Ü		Sodium Hydroxide	1310-73-2	10.00%	147.000000	
			Sodium Tetraborate	1330-43-4	30.00%	441.000000	
GW-3LDF	Baker Hughes	Gelling Agent	1-Butoxy-2-Propanol	5131-66-8	5.00%		SmartCare Product
	J	3 3	Cyrstalline Silica, Quartz (SiO2)	14808-60-7	5.00%	189.964500	
			Guar Gum	9000-30-0	60.00%	2,279.574000	
			Isotridecanol, ethoxylated	9043-30-5	5.00%	189.964500	
			Paraffinic Petroleum Distillate	64742-55-8	30.00%	1,139.787000	
			Petroleum Distillates	64742-47-8	30.00%	1,139.787000	
Sand, Brown, 8/40	Baker Hughes	Proppant	Crystalline Silica (Quartz)	14808-60-7	100.00%	355,640.000000	
ScaleSorb 3, (25# pail)		Scale Inhibitor	Amino Alkyl Phosphonic Acid	Trade Secret	30.00%		SmartCare Product
-, ( -	1 3 10		Crystalline Silica: Quartz (SiO2)	14808-60-7	1.00%	1.000000	
			Diatomaceous Earth, Calcined	91053-39-3	100.00%	100.000000	
			Phosphonic Acid	13598-36-2	1.00%	1.000000	
			The special state of the speci				
	I	1	I and the second	1	I		1

1	i .	i	i .	

1	i .	i	i .	

1	i .	i	i .	

Ingredients shown	above are subject		nd appear on Material Safety Data She		hown below are Non		
			2-Butoxy-1-Propanol	15821-83-7		3.039432	
			Water	7732-18-5		294.000000	
	j.	ii .	T. Control of the Con	T. Control of the Con	i .	i	

<sup>\*</sup> Total Chemical Mass is the total amount of Trade Name volume, supplied to the customer, converted to pounds.

Ingredient information for chemicals subject to 29 CFR 1910.1200(i) and Appendix D are obtained from suppliers Material Safety Data Sheets (MSDS)

<sup>\*</sup> Total Max. Ingredient Mass is the summation of all masses listed in the Maximum Ingredient Weight (pounds) column.

<sup>\*</sup> Total Product Volume is the total amount of Water plus Trade Name volume in gallons supplied to the customer or Baker Hughes.

<sup>\*</sup> Total Water Volume is the total amount of water volume in gallons used on the hydraulic fracture treatment.

<sup>\*\*</sup> Information is based on the maximum potential for concentration and thus the total may be over 100%