Hydraulic Fracturing Fluid Product Component Information Disclosure

11/20/2012
California
Kern
04-030-48261
Aera Energy Llc
733LL-29
-119.7383335
35.4654016
NAD83
Oil
1,638
11,046

Hydraulic Fracturing Fluid Composition:

Trade Name	Supplier	Purpose	Ingredients	Chemical Abstract Service Number (CAS #)	Maximum Ingredient Concentration in Additive (% by mass)**	Maximum Ingredient Concentration in HF Fluid (% by mass)**	Comments
Water	Operator	Carrier	Water	7732-18-5	100.00%	98.81804%	
GBW-5	Baker Hughes	Breaker	Ammonium Phosphate	7727-54-0	100.00%	0.00536%	SmartCare Product
Enzyme G-I	Baker Hughes	Breaker	Hemicellulase Enzyme Concentrate	9025-56-3	3.00%	0.00349%	SmartCare Product
			Water	7732-18-5	97.00%	0.11281%	
Clay Master-5C (Tote)	Baker Hughes	Clay Control	Oxyakylated Amine Quat	138879-94-4	60.00%	0.07600%	
XLW-10A	Baker Hughes	Crosslinker	Ethylene Glycol	107-21-1	30.00%	0.05070%	SmartCare Product
			Sodium Hydroxide	1310-73-2	10.00%	0.01690%	
			Sodium Tetraborate	1330-43-4	30.00%	0.05070%	
GW-3LDF	Baker Hughes	Gelling Agent	1-Butoxy-2-Propanol	5131-66-8	5.00%	0.03080%	SmartCare Product
			Cyrstalline Silica, Quartz (SiO2)	14808-60-7	5.00%	0.03080%	
			Guar Gum	9000-30-0	60.00%	0.36965%	
			Isotridecanol, ethoxylated	9043-30-5	5.00%	0.03080%	
			Paraffinic Petroleum Distillate	64742-55-8	30.00%	0.18483%	
			Petroleum Distillates	64742-47-8	30.00%	0.18483%	
Ingredients shown	above are sub	ject to 29 CFR 1910.12	00(i) and appear on Material Safety Dat	a Sheets (MSDS). Ingredier	nts shown below are	Non-MSDS.	
			2-Butoxy-1-Propanol	15821-83-7		0.0004928706%	
			Water	7732-18-5		0.0337979428%	

** Information is based on the maximum potential for concentration and thus the total may be over 100%

Ingredient information for chemicals subject to 29 CFR 1910.1200(i) and Appendix D are obtained from suppliers Material Safety Data Sheets (MSDS)