

Hydraulic Fracturing Fluid Product Component Information Disclosure

Last Fracture Date	05/02/2012
State:	California
County:	Kern
API Number:	04-030-46049
Operator Name:	Aera Energy Llc
Well Name and Number:	764CL-29
Longitude:	-119.7311451
Latitude:	35.4641356
Long/Lat Projection:	NAD83
Production Type:	Oil
True Vertical Depth (TVD):	1,965
Total Water Volume (gal)*:	20,748

Hydraulic Fracturing Fluid Composition:

Trade Name	Supplier	Purpose	Ingredients	Chemical Abstract Service Number (CAS #)	Maximum Ingredient Concentration in Additive (% by mass)**	Maximum Ingredient Concentration in HF Fluid (% by mass)**	Comments
Water	Operator	Carrier	Water	7732-18-5	100.00%	76.76088%	
GBW-5	Baker Hughes	Breaker	Ammonium Persulfate	7727-54-0	100.00%	0.00444%	SmartCare Product
Enzyme G-I	Baker Hughes	Breaker	Hemicellulase Enzyme Concentrate	9025-56-3	3.00%	0.00266%	SmartCare Product
			Water	7732-18-5	97.00%	0.08613%	
Clay Master-5C (Tote)	Baker Hughes	Clay Control	Oxyakylated Amine Quat	138879-94-4	60.00%	0.07071%	
XLW-10A	Baker Hughes	Crosslinker	Ethylene Glycol	107-21-1	30.00%	0.04193%	SmartCare Product
			Sodium Hydroxide	1310-73-2	10.00%	0.01398%	
			Sodium Tetraborate	1330-43-4	30.00%	0.04193%	
GW-3LDF	Baker Hughes	Gelling Agent	1-Butoxy-2-Propanol	5131-66-8	5.00%	0.01741%	SmartCare Product
			Cyrstalline Silica, Quartz (SiO2)	14808-60-7	5.00%	0.01741%	
			Guar Gum	9000-30-0	60.00%	0.20892%	
			Isotridecanol, ethoxylated	9043-30-5	5.00%	0.01741%	
			Paraffinic Petroleum Distillate	64742-55-8	30.00%	0.10446%	
			Petroleum Distillates	64742-47-8	30.00%	0.10446%	
Sand, White, 20/40	Baker Hughes	Proppant	Crystalline Silica (Quartz)	14808-60-7	100.00%	22.47902%	

Ingredients shown above are subject to 29 CFR 1910.1200(i) and appear on Material Safety Data Sheets (MSDS). Ingredients shown below are Non-MSDS.

			2-Butoxy-1-Propanol	15821-83-7		0.0002785659%	
--	--	--	---------------------	------------	--	---------------	--

