A Lattice Boltzmann Method for immiscible multiphase flow simulations using the Level Set Method

Lorenz Hufnagel, Daniel Zint

BGCE Student Project

August 20th, 2015

Multiphase flow

Examples

- Liquid-liquid mixtures (e.g. oil in water)
- Gas-liquid mixtures (e.g. bubble dynamics)



Multiphase flow

Examples

- Liquid-liquid mixtures (e.g. oil in water)
- Gas-liquid mixtures (e.g. bubble dynamics)





Macroscopic fluid mechanics

- N immiscible fluids.
- Each has own ρ_i, ν_i
- Hydrodynamics described by (incompressible) NSE

Macroscopic fluid mechanics

- N immiscible fluids.
- Each has own ρ_i, ν_i
- Hydrodynamics described by (incompressible) NSE

Macroscopic fluid mechanics

- N immiscible fluids.
- Each has own ρ_i, ν_i
- Hydrodynamics described by (incompressible) NSE

$$\nabla \cdot \vec{v} = 0$$

$$\frac{\partial \vec{v}}{\partial t} + (\vec{v} \cdot \nabla) \vec{v} = -\frac{1}{\varrho_i} \nabla \rho + \nu_i \nabla^2 \vec{v}$$

Interface conditions





Figure: Two fluid domains Ω_i and interface Γ inbetween

■ Velocity across interface is C_0 -continous

$$[v] = \lim_{\epsilon \to 0} (\vec{v} (x + \epsilon \vec{n}) - \vec{v} (x - \epsilon \vec{n})) = 0$$


Interface conditions cont'd



lacktriangle Normal stress is balanced by surface tension ightarrow pressure jump

$$[T] \cdot \vec{n} = \lim_{\epsilon \to 0} (\mathbf{T}_2(x + \epsilon \vec{n}) - \mathbf{T}_1(x - \epsilon \vec{n})) \cdot \vec{n} = 2\sigma \kappa \vec{n}$$

Interface conditions cont'd



 \blacksquare Normal stress is balanced by surface tension \to pressure jump

$$[T] \cdot \vec{n} = \lim_{\epsilon \to 0} (\mathbf{T}_2(x + \epsilon \vec{n}) - \mathbf{T}_1(x - \epsilon \vec{n})) \cdot \vec{n} = 2\sigma \kappa \vec{n}$$

where \mathbf{T}_i is the stress tensor $\mathbf{T}_i = 2\nu_i \rho_i \mathbf{S}_i - p\mathbb{I}$ and κ is the curvature of the interface $\nabla \cdot \vec{n}$. $\mathbf{S}_{ij} = \frac{1}{2}(\partial_i v_j + \partial_j v_i)$.

To solve the two-phase problem we need to:

- lacksquare solve the flow equations ightarrow LBM
- compute the motion of the interface → Level Set Method
- $lue{}$ couple the two algorithms ightarrow according BC's

To solve the two-phase problem we need to:

- lacksquare solve the flow equations ightarrow LBM
- compute the motion of the interface → Level Set Method
- $lue{}$ couple the two algorithms o according BC's

To solve the two-phase problem we need to:

- lacksquare solve the flow equations ightarrow LBM
- compute the motion of the interface → Level Set Method
- lacktriangle couple the two algorithms o according BC's

Interface capturing

The interface between fluid phases is captured by a Level-Set Method. I.e. a *level set function* $\varphi := \varphi(x,t) \to \mathbb{R}$ is tracked through the fluid domain. The interface is given (implicitly) by the zero-isosurface of this function. It holds:

$$\frac{\partial \varphi}{\partial t} + \vec{\mathbf{v}} \cdot \nabla \varphi = \mathbf{0}$$

where \vec{v} is the velocity at the interface; given by NSE. Benefit of Level-Set Method:

- Implicit surface description eases bubble coalescence/breakup in code
- High density and viscosity ratios (> 10³) possible for simulation

Interface capturing

The interface between fluid phases is captured by a Level-Set Method. I.e. a *level set function* $\varphi := \varphi(x,t) \to \mathbb{R}$ is tracked through the fluid domain. The interface is given (implicitly) by the zero-isosurface of this function. It holds:

$$\frac{\partial \varphi}{\partial t} + \vec{\mathbf{v}} \cdot \nabla \varphi = \mathbf{0}$$

where \vec{v} is the velocity at the interface; given by NSE. Benefit of Level-Set Method:

- Implicit surface description eases bubble coalescence/breakup in code
- High density and viscosity ratios (> 10³) possible for simulation

Interface capturing

The interface between fluid phases is captured by a Level-Set Method. I.e. a *level set function* $\varphi := \varphi(x,t) \to \mathbb{R}$ is tracked through the fluid domain. The interface is given (implicitly) by the zero-isosurface of this function. It holds:

$$\frac{\partial \varphi}{\partial t} + \vec{\mathbf{v}} \cdot \nabla \varphi = 0$$

where \vec{v} is the velocity at the interface; given by NSE. Benefit of Level-Set Method:

- Implicit surface description eases bubble coalescence/breakup in code
- High density and viscosity ratios (> 10³) possible for simulation


Interface implementation (Methods Coupling)

Hydrodynamics are solved by LBM (Stream-Collide, D2Q9, SRT for our first test)

■ Interface becomes a new boundary condition for LBM

$$f_i(x, t+1) = f_{i*}^+(x, t) + 6\Delta x f_i^* c_i \cdot \tilde{v} + R_i$$

- \tilde{v} is the velocity on the interface along the direction c_i
- R_i ensures the jump conditions of the normal stress and corrects the error terms resulting from the bounce back treatment




Interface implementation (Methods Coupling)

Hydrodynamics are solved by LBM (Stream-Collide, D2Q9, SRT for our first test)

■ Interface becomes a new boundary condition for LBM

$$f_i(x, t+1) = f_{i^*}^+(x, t) + 6\Delta x f_i^* c_i \cdot \tilde{v} + R_i$$

- \tilde{v} is the velocity on the interface along the direction c_i
- R_i ensures the jump conditions of the normal stress and corrects the error terms resulting from the bounce back treatment




Interface implementation (Methods Coupling)

Hydrodynamics are solved by LBM (Stream-Collide, D2Q9, SRT for our first test)

■ Interface becomes a new boundary condition for LBM

$$f_i(x, t+1) = f_{i*}^+(x, t) + 6\Delta x f_i^* c_i \cdot \tilde{v} + R_i$$

- \tilde{v} is the velocity on the interface along the direction c_i
- R_i ensures the jump conditions of the normal stress and corrects the error terms resulting from the bounce back treatment



$$\tilde{v}=qv(x_2,t)+(1-q)v(x_1,t)$$

$$\tilde{v}=qv(x_2,t)+(1-q)v(x_1,t)$$

 R_i consists of several parts:

$$R_i = 6\Delta x^2 f_i^* \Lambda_i : A$$

$$\tilde{v} = qv(x_2, t) + (1 - q)v(x_1, t)$$

 R_i consists of several parts:

$$R_i = 6\Delta x^2 f_i^* \Lambda_i : A$$

with:

$$\Lambda_i = c_i \otimes c_i - \frac{1}{3} |c_i|^2 \mathbb{I}$$

$$A = -q(1-q)[S] - (q-1/2)S^2 + O(\Delta x)$$

- $S^{(k)}$ velocity gradient at x_k
- $[S] = \lim_{\epsilon \to 0} (S(x + \epsilon \vec{n}) S(x \epsilon \vec{n}))$ jump of velocity gradient at the interface. Depends on normal, tangent and curvature.

$$\tilde{v} = qv(x_2,t) + (1-q)v(x_1,t)$$

 R_i consists of several parts:

$$R_i = 6\Delta x^2 f_i^* \Lambda_i : A$$

with:

$$egin{aligned} \Lambda_i &= c_i \otimes c_i - rac{1}{3} |c_i|^2 \mathbb{I} \ A &= -q(1-q)[S] - (q-1/2)S^2 + O(\Delta x) \end{aligned}$$

- $S^{(k)}$ velocity gradient at x_k
- $[S] = \lim_{\epsilon \to 0} (S(x + \epsilon \vec{n}) S(x \epsilon \vec{n}))$ jump of velocity gradient at the interface. Depends on normal, tangent and curvature.

$$\tilde{v} = qv(x_2, t) + (1 - q)v(x_1, t)$$

 R_i consists of several parts:

$$R_i = 6\Delta x^2 f_i^* \Lambda_i : A$$

with:

$$\Lambda_i = c_i \otimes c_i - \frac{1}{3} |c_i|^2 \mathbb{I}$$

$$A = -q(1-q)[S] - (q-1/2)S^2 + O(\Delta x)$$

- $S^{(k)}$ velocity gradient at x_k
- $[S] = \lim_{\epsilon \to 0} (S(x + \epsilon \vec{n}) S(x \epsilon \vec{n}))$ jump of velocity gradient at the interface. Depends on normal, tangent and curvature.

Algorithm for LBM with level set

■ Create initial interface

- Run level set method to calculate surface description
- Run LBM for a prescribed number of steps
- Run level set method for the same time interval
- Repeat until end of simulation

- Create initial interface
- Run level set method to calculate surface description
- Run LBM for a prescribed number of steps
- Run level set method for the same time interval
- Repeat until end of simulation

- Create initial interface
- Run level set method to calculate surface description
- Run LBM for a prescribed number of steps
- Run level set method for the same time interval
- Repeat until end of simulation


- Create initial interface
- Run level set method to calculate surface description
- Run LBM for a prescribed number of steps
- Run level set method for the same time interval
- Repeat until end of simulation


- Create initial interface
- Run level set method to calculate surface description
- Run LBM for a prescribed number of steps
- Run level set method for the same time interval
- Repeat until end of simulation


Results


Setup

Transient couette flow with immersed drop.









... more to come

Outlook

...so far intermediate results

Outlook:

- Add correction term to prevent mass loss
- Reduce computational effort: Store Level-Set function only in narrow band around interface, Adalsteinsson and Sethian
- \longrightarrow ...?

Outlook

...so far intermediate results

Outlook:

- Add correction term to prevent mass loss
- Reduce computational effort: Store Level-Set function only in narrow band around interface, Adalsteinsson and Sethian
- \longrightarrow ...?

Outlook

...so far intermediate results

Outlook:

- Add correction term to prevent mass loss
- Reduce computational effort: Store Level-Set function only in narrow band around interface, Adalsteinsson and Sethian
- \blacksquare \rightarrow ...?

- Thömmes, Guido, et al. "A lattice Boltzmann method for immiscible multiphase flow simulations using the level set method." Journal of Computational Physics 228.4 (2009): 1139-1156
- D. Adalsteinsson, and J. A. Sethian. A fast level set method for propagating interfaces. J. Comput. Phys., 118(2):269-277, 1995
- Mitchell, Ian, A Toolbox of Level Set Methods