# Factory and Test Certificate

| | | | |
|---|---|---|---|
| Date of report: | 01-12-17 | Filled by: | M. Pleskach |
| Reference: | 2017-01612 | Tested by: | E. Kebkal |

## Product Description

| | | | |
|---|---|---|---|
| Product name: | S2C R 18/34 Hydroacoustic Modem w/USBL | Firmware: | v1.9.13 |
| Serial Number: | 1834/19#139/10 | Interfaces: | 1 Ethernet 192.168.0.139<br>2.<br>3. |
| Housing Material: | Delrin | Maximum depth (m) | 200 |
| Transducer type: | 18/34 | Maximum depth (m) | - |

## Installed Options

- [ ] Acoustic wake-up module
- [x] AHRS
- [ ] Data logger
- [ ] Additional virtual data channels
- [X] Distance and speed measurement
- [x] USBL Antenna
- [ ] Opto-coupler
- [ ] Sensor integration

Local address: 1

Remote Address: 0

Sensor name:

Other/ Comments

## Tests Conducted

| | Test | Value | Status |
|---|---|---|---|
| X | Source Level (SrcLev=0), dB re 1 uPa @ 1 m | 183.94 | OK |
| X | Frequency Range, kHz | 18-34 | OK |
| X | Power consumption Rx Mode, W | 2.50 | OK |
| X | Power consumption Tx Mode, W | 67.50 | OK |
| | Power consumption WakeUp Idle Mode, mW | | |
| | Power consumption WakeUp Active Mode, mW | | |
| X | Data Transmission, kbps | 13.9 | OK |
| X | Vacuum test, bar | -0.8 | OK |
| X | Pressure test, bar | 20 | OK |
| | Boot time (wake-up module), ms | | |
| X | Noise level, dB | -103 | OK |

## Connector Configuration

Data/Power Eth

| Description | PIN | Description | PIN |
|---|---|---|---|
| TxD+OUT | 1 | | |
| TxD-OUT | 2 | | |
| RxD+IN | 3 | | |
| RxD-IN | 4 | | |
| V+ (24V) | 5 | | |
| V- (Power_GND) | 6 | | |
| POWER ON | 7 | | |
| NC | 8 | | |
| | | | |
| | | | |

Subconn FCR1508M

not installed

Signed by Sergey Yakovlev

Company Stamp