

Kubernetes Helper Commands

| Command | Description |
|---|--|
| k8appl <i>file</i> | kubectl apply -f |
| k8del <i>file</i> | kubectl delete -f |
| k8cp | kubectl cp file unique_part_of_podname |
| k8exec <i>unique_part_of_podname</i> | kubectl exec -it |
| k8logs [-f] <i>unique_part_of_podname</i> | k8logs logs |
| k8deploy-get <i>deployment-name</i> | k get deploy -o wide --show-labels "\$@" |
| k8pod-get | k get pods -o wide --show-labels "\$@" |
| k8describe | k describe "\$@" |
| k8svc-get | k get services -o wide --show-labels "\$@" |
| k8svc-aget | k get services -A -o wide --show-labels "\$@" |
| k8cfg-get | k config get-contexts "\$@" |
| k8cfg-set | k config set-context "\$@" |
| k8cfg-use | k config use-context "\$@" |
| k8cfg-view | k config view "\$@" |
| k8namespace-get | k get ns "\$@" |
| k8nodes-get | k get nodes -o wide --show-labels "\$@" |
| k8-ev | k get events --sort-by=.metadata.creationTimestamp "\$@" |
| k8-eva | k get events --sort-by=.metadata.creationTimestamp -A "\$@" |
| k8all-aget | kubectl get all |