

Markdown Utilities provided by ConfigShell

Christian Engel

1st February 2024

Contents

| | | |
|----------|---|----------|
| 1 | About | 1 |
| 2 | Version | 1 |
| 3 | A Classical Situation | 1 |
| 4 | Further Advantages of md2pdf | 3 |
| 4.1 | Use of default L ^A T _E X tool | 3 |
| 4.2 | Unicode Support | 3 |
| 4.3 | Short markdown file names | 3 |
| 4.4 | Language-specific Support | 3 |
| 4.5 | Link-colours | 4 |
| 4.6 | Definition of default paper-sizes | 4 |
| 4.7 | Automatic add of documentation at the end | 4 |
| 5 | md2pdf options | 4 |

1 About

L^AT_EX is still considered to be the best typesetting solution existing in the IT market. Nevertheless, it can be considered to be too complex for a lot of normal usages.

Markdown can be considered as a simplified version of a batch formatting system such as L^AT_EX. Its rules are much easier to learn than the ones of L^AT_EX and TeX. ConfigShell provides scripts to convert and format Markdown documents to the interim format L^AT_EX and then to PDF. This combines the easiness of Markdown with with excellent formatting of L^AT_EX. This wonderful process is supported by the OSS tool pandoc.

The scripts and templates provided by ConfigShell shall help to use this tool-chain more effectively.

2 Version

This document is version: 1.1.0. It describes the md2pdf software in its version 1.1.0 and above.

3 A Classical Situation

Imagine you format a Markdown document like this:

```
# Markdown Utilities provided by ConfigShell
```

```
## Contents
```

```
You might use an automatic table of contents (TOC) as  
created by tools such as typora or vscode (extension: Markdown  
all in One)
```

```
## About
```

```
...
```

With this automatic TOC this might look like:

```
# Markdown Utilities provided by ConfigShell
```

```
## Contents
```

```
- [Markdown Utilities provided by ConfigShell](#markdown-utilities-provided-by-configshell)
- [Contents](#contents)
- [About](#about)
- [A Classical Situation](#a-classical-situation)
```

```
## About
```

```
...
```

If such a document is stored as a `README.md` file, then many git repository front-ends would automatically format this document and it all looks ok. Often, we are interested to format this Markdown file also the PDF. Then, even local clones of this directory can be used to display this Markdown file in a well looking form.

But, if we want to format this document to PDF using `pandoc`, we run into some challenges:

- No \LaTeX title, author is defined
- The table of contents is based on Markdown, not \LaTeX : by far not so beautiful as it could, as it should be.
- Only one section exists. This is supposed to be the title. All *normal* elements are subsections and below.

Here is an example how it looks like:

Markdown Utilities provided by ConfigShell

Contents

- Markdown Utilities provided by ConfigShell
 - Contents
 - About
 - A Classical Situation

About

\LaTeX is still considered to be the best typesetting solution existing in the IT market. Nevertheless, it can be considered to be too complex for a lot of normal usages.

This is where `md2pdf` (same as `markdown2pdf`) comes into the game. Let's use the `ConfigShell` tool to format it:

```
md2pdf README.pdf
```

And here the output:

Markdown Utilities provided by ConfigShell

Christian Engel

31st January 2024

Contents

| | | |
|----------|------------------------------|----------|
| 1 | About | 1 |
| 2 | A Classical Situation | 1 |

1 About

LaTeX is still considered to be the best typesetting solution existing in the IT market. Nevertheless, it can
We can see:

- The markdown title is the \LaTeX title
- The \LaTeX table of contents macro is used
- All sections and below are on the right level

4 Further Advantages of md2pdf

4.1 Use of default \LaTeX tool

It uses \LaTeX instead of xelatex for a higher level of compatibility. Some problems with larger levels of table of contents structures were detected with xelatex. You can change this behaviour by options to pandoc or a wrapper script around pandoc. md2pdf offers the variable PANDOC_OPTIONS for this. By default, the variable is not set.

4.2 Unicode Support

- It extends \LaTeX to allow for the use of Unicode characters. For example, the use of \geq and \leq are made possible in the \LaTeX header file by entries like:

```
\DeclareUnicodeCharacter{2264}{\leq$}  
\DeclareUnicodeCharacter{2265}{\geq$}
```

4.3 Short markdown file names

Instead of specifying the full name like markdownFile.md, you can just specify markdownFile.; the md2pdf command will automatically add the md suffix. This helps in case of completion topics.

4.4 Language-specific Support

\LaTeX is currently set to support UK English, this is controlled by the settings:

```
\usepackage[UKenglish]{babel}  
\usepackage[UKenglish]{isodate}
```

You can easily change this to different languages by copying this header file, change these entries, and finally calling md2pdf with the option:

```
md2pdf -H ./doc/useThisHeaderfile.tex file.md
```

4.5 Link-colours

Link colours and other formatting options can also be set in the header file. The default settings are shown here:

```
\usepackage{hyperref}
\hypersetup{
  colorlinks,
  citecolor=green,
  filecolor=blue,
  linkcolor=blue,
  urlcolor=red
}
```

4.6 Definition of default paper-sizes

The used sizes for papers (e.g. letter or DIN A4,...) do not change to often for a team. Here, a definition is created in the header file and automatically applied to all documents:

```
\usepackage[a4paper, total={6.5in, 10in}]{geometry}
```

4.7 Automatic add of documentation at the end

The option `-F` allows to add text at the end of a document. You can use this to add disclaimers, copyright information, ... to all documents easily.

5 md2pdf options

`md2pdf` is a bash script residing in `/opt/ConfigShell/bin`. Its main options can be retrieved by the built-in help functionality:

NAME

`md2pdf`

SYNOPSIS

```
md2pdf [-D] [dir...]
md2pdf [-V]
md2pdf -h
```

VERSION

1.1.0

DESCRIPTION

Convert a markdown file to PDF using pandoc. This version works more stable when using classical `\LaTeX{}` instead of `xelatex`. The starting position is: The markdown file can be formatted by itself and is 'good looking'. No `\LaTeX{}` commands are included. But: Elements of the source markdown file before the comment

```
[//]: # (demo)
```

will be deleted when processing using pandoc. Additionally, if a file `header_tex.yaml` exists, this file is prepended to the stripped markdown file. Furthermore, a file named `footer_tex.tex` is appended for pandoc processing if it exists. Usually, the header file contains a `\LaTeX{}` title and a table of contents declaration which will end up in better looking `\LaTeX{}`/PDF version. The names of the header and footer files can be changed for CLI options. A local headerfile overwrites a default headerfile.

Further options can be passed to the pandoc command using the environment variable `PANDOC_OPTIONS`. This environment variable is not double-quoted, so it can contain multiple options.

OPTIONS

-H <<file>> ::= optional headerfile with YAML, \LaTeX{} commands,
 default: header_tex.yaml
-F <<file>> ::= append the markdown file with the following \LaTeX{} file if the file exists.
 default: footer_tex.tex
-D ::= enable debug output
-V ::= output the version number to stderr and exit with 0
-x ::= disable \LaTeX{} processing. This is useful if the markdown file shall be
 formatted to look nice in \LaTeX{}. Only one section (#) is allowed which
 is translated into a \LaTeX{} title. All other sections below (e.g. subsection (##
 will be moved one level up.
-h ::= show usage message to stderr and exit with 0