

Experiment No.7
Implement Circular Linked List ADT.
Name: Rutuja Pednekar
Roll No:47
Date of Performance:
Date of Submission:
Marks:
Sign:

Experiment No. 7: Circular Linked List Operations

Aim: Implementation of Circular Linked List ADT Objective:

In circular linked list last node is connected to first node. On other hand circular linked list can be used to implement traversal along web pages.

Theory:

In a circular linked list, the last node contains a pointer to the first node of the list. We can have a circular singly linked list as well as a circular doubly linked list. While traversing a circular linked list, we can begin at any node and traverse the list in any one direction, forward or backward, until we reach the same node where we started. Thus, a circular linked list has no beginning and no ending.

Inserting a New Node in a Circular Linked List Case

1: The new node is inserted at the beginning.

Case 2: The new node is inserted at the end.

Deleting a Node from a Circular Linked List Case

1: The first node is deleted.

Case 2: The last node is deleted.

Insertion and Deletion after or before a given node is same as singly linked list.

Algorithm

Algorithm to insert a new node at the beginning

Step 1: IF AVAIL = NULL

Write OVERFLOW

Go to Step 9 [END OF IF]

Step 2: SET NEW NODE = AVAIL

Step 3: SET AVAIL = AVAIL □ NEXT

Step 4: SET NEW NODE-->DATA = VAL

Step 5: SET PTR=START

Repeat Step 6 while PTR NEXT != START

Step 6: SET PTR = PTR NEXT [END OF LOOP]

Step 7: SET NEW NODE--> NEXT= START

Step 8: SET PTR-->NEXT = START

Step 9: SET START = NEW NODE

Step 10: EXIT

Algorithm to insert a new node at the end

Step 1: IF AVAIL = NULL

Write OVERFLOW

Go to Step 11 [END OF IF]

Step 2: SET NEW NODE = AVAIL

Step 3: SET AVAIL = AVAIL--> NEXT

Step 4: SET NEW NODE -->DATA = VAL

Step 5: SET NEW NODE-->NEXT = START

Step 6: SET PTR = START

Step 7: Repeat Step 8 while PTR--> NEXT != START

Step 8: SET PTR = PTR -->NEXT [END OF LOOP]

Step 9: SET PTR -->NEXT = NEW NODE

Step 10: EXIT

Algorithm to delete the first node

Step 1: IF START = NULL

Write UNDERFLOW



Go to Step 6 [END OF IF]

Step 2: SET PTR = START

Step 3: Repeat Step 4 while PTR--> NEXT != START

Step 4: SET PTR = PTR -->NEXT [END OF LOOP]

Step 4: SET PTR \square NEXT = START --> NEXT

Step 5: FREE START

Step 6: EXIT

Algorithm to delete the last node

Step 1: IF START = NULL

Write UNDERFLOW

Go to Step 7 [END OF IF]

Step 2: SET PTR = START [END OF LOOP]

Step 3: Repeat Step 4 and Step 5 while PTR -->NEXT != START

Step 4: SET PREPTR = PTR

Step 5: SET PTR = PTR -->NEXT

Step 6: SET PREPTR-->NEXT = START

Step 7: FREE PTR

Step 8: EXIT

Code:

#include

#include #include

struct node { int

data; struct node

*next;

}; struct node *start = NULL;

struct node *create_cll(struct node *);

struct node *display(struct node *); struct

node *insert beg(struct node *); struct




```
node *insert end(struct node *); struct
node *delete beg(struct node *); struct
node *delete end(struct node *); struct
node *delete after(struct node *); struct
node *delete list(struct node *); int
main() { int option; clrscr(); do {
printf("\n\n *****MAIN MENU *****");
printf("\n 1: Create a list"); printf("\n 2: Display
the list"); printf("\n 3: Add a node at the
beginning"); printf("\n 4: Add a node at the
end"); printf("\n 5: Delete a node from the
beginning"); printf("\n 6: Delete a node from
the end"); printf("\n 7: Delete a node after a
given node"); printf("\n 8: Delete the entire
list"); printf("\n 9: EXIT"); printf("\n\n Enter
your option: "); scanf("%d", &option);
switch(option) { case 1:
start = create cll(start);
printf("\n CIRCULAR LINKED LIST CREATED");
break; case 2: start =
display(start); break;
case 3: start =
insert beg(start); break;
case 4: start =
insert end(start); break;
case 5: start =
```



```
delete beg(start); break;
case 6: start =
delete_end(start); break;
case 7: start =
delete_after(start); break;
case 8:
start = delete_list(start);
printf("\n CIRCULAR LINKED LIST DELETED");
break; }
}while(o
ption
!=9);
getch();
return 0;
} struct
node
*create_
cll(struct
node
*start) {
struct
node
*new_no
de, *ptr;
int num;
printf("\n
```







```
new nod
e; start
new nod
e;
} else { ptr = start; while(ptr
-> next != start) ptr = ptr ->
next; ptr -> next = new_node;
new node -> next = start; }
printf("\n Enter the data : ");
scanf("%d", &num);
} return start;
} struct node *display(struct node *start) { struct
node *ptr; ptr=start; while(ptr -> next != start) {
printf("\t \%d", ptr -> data); ptr = ptr -> next; 
printf("\t %d", ptr -> data); return start; } struct node
*insert beg(struct node *start) { struct node
*new node, *ptr; int num; printf("\n Enter the data:
"); scanf("%d", &num); new node = (struct node
*)malloc(sizeof(struct node)); new node -> data =
num;
ptr = start; while(ptr ->
next != start) ptr = ptr ->
next; ptr -> next =
new node; new node ->
```



```
next = start; start =
new node; return start;
} struct node *insert end(struct node *start) {
struct node *ptr, *new node;
                                     int num;
printf("\n Enter the data: "); scanf("%d",
&num);
new node = (struct node *)malloc(sizeof(struct node));
new node \rightarrow data = num;
ptr = start; while(ptr -> next != start) ptr =
ptr \rightarrow next; ptr \rightarrow next = new node;
new node -> next = start; return start; }
struct node *delete beg(struct node *start) {
struct node *ptr; ptr = start; while(ptr ->
next != start) ptr = ptr -> next; ptr -> next =
start -> next; free(start); start = ptr -> next;
return start;
} struct node *delete end(struct node *start) {
struct node *ptr,*preptr; ptr = start; while(ptr
-> next != start) { preptr = ptr; ptr = ptr ->
next;
} preptr -> next = ptr ->
next; free(ptr); return start;
} struct node *delete after(struct node *start) { struct node *ptr,
*preptr; int val; printf("\n Enter the value after which the node
has to deleted: "); scanf("%d", &val);
```



```
ptr = start; preptr = ptr;
while(preptr -> data != val) { preptr
= ptr; ptr = ptr -> next; } preptr ->
next = ptr -> next; if(ptr == start)
start = preptr -> next; free(ptr);
return start;
} struct node *delete_list(struct node *start) {
struct node *ptr; ptr = start; while(ptr -> next
!= start) start = delete_end(start); free(start);
return start;
}
```

Output:

```
Enter the data: 4
Enter the data: -1
CIRCULAR LINKED LIST CREATED
Enter your option : 3
Enter your option : 5
Enter your option : 2
5 1 2
Enter your option : 9
*****MAIN MENU *****
1: Create a list
2: Display the list
3: Add a node at the beginning
8: Delete the entire list
9: EXIT
Enter your option : 1
Enter -1 to end
Enter the data: 1
Enter the data: 2
```

Conclusion:

Write an example of insertion and deletion in the circular linked list while traversing the web pages?

```
#include <stdio.h>
```



```
#include <stdlib.h>
#include <string.h>
// Structure for a web page node in the circular linked list struct
WebPage {
  char title[50];
                  struct
WebPage* next;
};
struct WebPage* current = NULL;
// Function to insert a new web page void insertPage(char title[]) {
WebPage* newPage = (struct WebPage*)malloc(sizeof(struct WebPage));
strcpy(newPage->title, title);
  if (current == NULL) {
                               current = newPage;
                                                       newPage->next =
newPage; // Make it point to itself in a circular list.
  } else {
                   newPage->next =
current->next;
                     current->next =
newPage;
               current = newPage;
  }
}
```



```
// Function to delete the current web page
void deletePage() {    if (current ==
NULL) {
              printf("No web page to
delete.\n");
                return;
  }
  struct WebPage* nextPage = current->next;
  if (current == current->next) {
free(current);
                   current = NULL;
} else {
           current->next = nextPage-
           free(nextPage);
>next;
  }
}
// Function to display the current web page
void displayCurrentPage() {
                              if (current
                 printf("No current web
== NULL)  {
page.\n");
               printf("Current Page: %s\n",
  } else {
current->title);
  }
}
```



```
int
           main()
insertPage("Home
                    Page");
insertPage("About
                      Us");
insertPage("Contact
                      Us");
displayCurrentPage();
                          //
Displays "Contact Us"
  deletePage();
                    // Deletes "Contact Us"
displayCurrentPage(); // Displays "About Us"
  deletePage();
                    // Deletes "About Us"
displayCurrentPage(); // Displays "Home Page"
  return 0;
}
```

