
Temperature Compensated Crystal Oscillators (TCXO, VCTCXO) Surface Mount Type TCXO (LSI Type) KT3225 Series



3.2×2.5mm



Features

- Miniature SMD type (3.2×2.5×1.0mm)
- AFC function available
- Freq. temp. characteristics. : $\pm 2.0 \times 10^{-6} / -30 \text{ to } +85^{\circ}\text{C}$
- 1.68 to 3.6V drive available
- Reflow compatible
- Ultra low supply current 600μA typ. Conditions of 26MHz and 0.4Vp-p (Option)

Applications

- 3G (CDMA, W-CDMA, TD-SCDMA), GPRS, GSM, W-LAN, WiMAX
- Low power radio communications

How to Order

 $\frac{\text{KT3225K}}{\text{1}} \ \frac{26000}{\text{2}} \ \frac{\text{D}}{\text{3}} \ \frac{\text{C}}{\text{4}} \ \frac{\text{W}}{\text{5}} \ \frac{28}{\text{6}} \ \frac{\text{T}}{\text{7}} \ \frac{\text{xx}}{\text{8}}$

- 1 Series
- 2 Output Frequency
- ③ Freq. Temp. Chrst.

В	±1.0×10 ⁻⁶	
С	±1.5×10 ⁻⁶	
D	±2.0×10 ⁻⁶	

4 Lower Operating Temp.

С	−30°C
Е	−20°C
G	−10°C

(5) Upper Operating Temp.

	1 0	
W	+85°C	
٧	+80°C	
U	+75°C	

6 Supply Voltage

18	1.8V	28	2.8V
30	3.0V	33	3.3V

(7) Voltage Control Function

o .oago			
Т	TCXO		
Other*	VCTCXO		

* Customer Spec.

® Option Code

Packaging (Tape & Reel 12000 pcs./ reel)


Specifications

Item	Symbol	Conditions	Min.	Max.	Units
Output Frequency Range	fo	Standard Frequency: 13, 19.2, 26, 38.4, 40, 52	10	52	MHz
		vs Temperature	-2	+2	
Frequency Tolerance	f_tol	vs Load	-0.1	+0.1	×10 ⁻⁶
		vs Voltage	-0.2	+0.2	
Frequency Aging	f_age	Per Year	-1	+1	×10 ⁻⁶
Storage Temperature Range	T_stg		-40	+85	°C
Operating Temperature Range	T_use		-30	+85	°C
Voltage Control Range	f _cont	Positive	±8	±15	×10 ⁻⁶
Supply Voltage	Vcc		1.68	3.6	V
Output Level	Vpp	Clipped Sine*, Load: 10k ohm / / 10pF	0.8	_	Vp-p
Current Consumption	Icc		_	2	mA
Harmonics	_		_	-5	dBc


^{*:} A DC-cut capacitor is not embedded in this crystal oscillator. Connect a DC-cut capacitor (21nF) to the line-out terminal of the oscillator.

(Unit: mm)

Dimensions




Test Circuit



Recommended Land Pattern





^{*} Please contact us for other specifications.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

AVX:

<u>KT3225F16369ACW28TA0</u> <u>KT3225F27456ZAW28TA0</u> <u>KT3225P27456ZAW28TN0</u> <u>KT3225T32768EAW30TAA</u> KT3225K26000ZAW28TCS KT3225K40000ECV28TAS