


●● UL 865 Series

UMTS | HSPA 7.2/5.76 Embedded



Product Description

The UL865 is a 3G module in the xL865 family. It is based on the latest Intel chipset to protect the developer's design investments as a long term availability solution. The UL865 features VQFN packaging that is fully pad-level compatible with its 2G companion, the GL865-DUAL V3.

Key Benefits

- Simple drop-in migration and technology upgrade path to 3G high-speed performance for designs currently using the GL865-DUAL V3
- Ideal for fleet management and track-and-tracing application with easy to follow reference designs for pairing with Telit GPS and GPS | GLONASS receivers
- Internet application friendly with integrated TCP/IP and UDP/IP stacks
- Voice-capable for applications requiring digital (DVI) interface
- Complete SMT platform for m2m solutions running the customer application inside the module with embedded Python Script Interpreter
- Over-the-Air firmware update by means Premium FOTA Management
- Battery-friendly 1.8V GPIO

Family Concept

The Telit xL865 family was conceived to address system integrators and developers needing to start with low volumes (LCC mount) as well as those already running high volumes (VQFN mount). Its ultra-compact package allows integration into very small devices. The family includes products that are pin-to-pin and API compatible in GSM | GPRS, CDMA | 1xRTT and UMTS | HSPA.

Variants

Band combination variants available for European and North American applications

m2mAIR Mobile and Cloud Ready

This product is capable of supporting the extensive suite of Value Added Services from m2mAIR Mobile including Module Management and others which make the management of m2m deployments under mobile networks effective, enhancing profitability and reliability. It is also Cloud-ready which means that the AT command library in this module includes a set of high-level commands designed exclusively for quick and hassle-free on-boarding of the device to the cloud and to back-end systems and servers. Telit Cloud-ready modules powered by deviceWISE make application-level data flows and controls simple to program, maintain and improve.

AVAILABLE FOR

- EMEA
- North America
- Latin America
- APAC
- Africa
- Russia

Click-to-Cloud – with Powerfull AT Commands



Combine your Cellular module with

- Short Range modules 
- GNSS modules 

www.telit.com

Complete, Ready to Use Access to the Internet of Things



Telit Modules + m2mAIR Mobile Value-Added Services including Connectivity

m2mAIR MOBILE

ONE STOP.
ONE SHOP. NOW, INNOVATE!

	UL865-EUR	UL865-EUD	UL865-NAR	UL865-NAD
Market	EMEA / APAC	EMEA / APAC	North America	North America
HSPA Upload (Mbps)	5.76	5.76	5.76	5.76
HSPA Download (Mbps)	7.2	7.2	7.2	7.2
Frequencies				
UMTS HSPA bands (MHz)	900/2100	900/2100	850/1900	850/1900
GSM GPRS EDGE bands (MHz)	900/1800	900/1800	850/1900	850/1900
Features				
Data	●	●	●	●
Voice	●		●	

●● UL865 Series

Product features

- Supported bands
- EUR/EUD variants:
 - 2 Bands GSM | GPRS | EDGE 900 / 1800 MHz
 - 2 Bands UMTS | HSPA 900 / 2100 MHz
- NAR/NAD variants:
 - 2 Bands GSM | GPRS | EDGE 850 / 1900 MHz
 - 2 Bands UMTS | HSPA 850 / 1900 MHz
- SIM Access Profile
- 3GPP release 7 compliant
- Control via AT commands according to 3GPP TS27.005, 27.007 and customized Telit AT commands
- Serial port multiplexer 3GPP TS27.010
- SIM application Tool Kits 3GPP TS 51.014
- Built in UDP / TCP / FTP / SMTP stack
- Digital voice and SMS
- IP stack with TCP and UDP protocol
- Standard and extended AT command set

- UART
- SPI
- 1.8 V / 3 V SIM interface
- 2 A/D plus 1 D/A converters

Approvals

- RoHS Compliant
- CE, GCF (Europe)
- FCC, PTCRB, IC (North America)

Electrical

- Output power
 - Class 4 (2 W, 33 dBm) @ GSM 850 / 900
 - Class 1 (1 W, 30 dBm) @ GSM 1800 / 1900
 - Class 3 (0.25 W, 24 dBm) @ UMTS
 - Class E2 (0.5 W, 27 dBm) @ EDGE 850 / 900
 - Class E2 (0.4 W, 26 dBm) @ EDGE 1800 / 1900
- Supply voltage
 - Nominal: 3.8 VDC
 - Range: 3.4 - 4.2 VDC

Additional features

- PFM (Premium FOTA Management) Over-The-Air Update service
- Remote AT commands
- Event monitor

Environmental

- Small dimensions 24.4 x 24.4 x 2.6 mm
- Temperature range -40°C to +85°C
- Interfaces
- 8 I/O ports maximum including multifunctional I/Os (1.8 V logic level)
- I2S for digital audio interface
- USB 2.0 HS

Software

- Python* application resources
- Python* version = 2.7.2
- Python* script interpreter (module takes the application code directly in the Python* language)
- Memory: 2 MB of NV memory for the user scripts and 2 MB RAM for the Python engine usage

Telit reserves all rights to this document and the information contained herein. Products, names, logos and designs described herein may in whole or in part be subject to intellectual property rights. The information contained herein is provided "as is". No warranty of any kind, either express or implied, is made in relation to the accuracy, reliability, fitness for a particular purpose or content of this document. This document may be revised by Telit at any time. For most recent documents, please visit www.telit.com

Copyright © 2014, Telit
 * Copyright © 1990-2014, Python Software Foundation



Join the Telit Technical Forum

For a quicker and more rewarding integration experience join the Telit Technical Forum. There you can browse the first open forum covering all m2m topics, get direct support by region (EMEA, North America, Latin America, APAC), take part in this quickly growing m2m community and exchange experiences.

Telit Communications S.p.A.
 Via Stazione di Prosecco, 5/B
 I-34010 Sgonico (Trieste), Italy
Phone +39 040 4192 200
Fax +39 040 4192 383
E-Mail EMEA@telit.com

Telit Wireless Solutions Inc.
 3131 RDU Center Drive, Suite 135
 Morrisville, NC 27560, USA
Phone +1 888 846 9773 or +1 919 439 7977
Fax +1 888 846 9774 or +1 919 840 0337
E-Mail NORTHAMERICA@telit.com

Telit Wireless Solutions Inc.
 Rua Paes Leme, 524, Conj. 126
 05424-101, Pinheiros
 São Paulo-SP-Brazil
Phone +55 11 3031 5051
Fax +55 11 3031 5051
E-Mail LATINAMERICA@telit.com

Telit Wireless Solutions Co., Ltd.
 8th Fl., Shinyoung Securities Bld.
 6, Gukjegeumyung-ro8-gil, Yeongdeungpo-gu
 Seoul, 150-884, Korea
Phone +82 2 368 4600
Fax +82 2 368 4606
E-Mail APAC@telit.com

www.telit.com
 www.telit.com/techforum
 www.telit.com/facebook
 www.telit.com/twitter